FIDELITY CUTS VS. FUNCTION CUTS: WHAT COMPRESSING SPECULATIVE-DECODING DRAFT HEADS DESTROYS, AND HOW TO DETECT IT BEFORE DEPLOYMENT

Anonymous Authors[1]

ABSTRACT

Co-trained multi-token-prediction heads give Qwen- and DeepSeek-lineage models built-in speculative decoding at a fixed price: the head's full-vocabulary projection reads 1.33GB of weights per drafted token on a 9B model, and separate-artifact deployments hold 1 to 2GB of GPU memory. We compress the head and measure exactly what each kind of compression destroys, using the verifier itself as a per-token oracle. Every drafted token is a labeled test of whether compression changed the function. The measurements sort all compression into two families. Fidelity cuts (uniform precision reduction) cost at most 1.9 acceptance-retention points under severe domain shift, with 8-bit exactly free. Function cuts (channel pruning, low-rank factorization, distillation) keep 97% of their acceptance on calibration-register text and pay 10 to 19 retention points on genuinely shifted text. The tax grows with shift distance and survives six selection schemes, including selection calibrated on the pruned head's own observed failures. The mechanism is statistical: parameters serving rare content accumulate no mass on any finite calibration sample. Three practical results follow. A zero-training recipe (trim the vocabulary to the model's own 32k hottest tokens, quantize to NVFP4, verify full-vocabulary) cuts per-token reads to 0.21GB. It delivers 1.8 to 2.7× end-to-end speedup over plain decoding on Qwen3.5-9B and Qwen3.6-27B in a production CUDA engine, with outputs distribution-exact by construction. A forward-pass audit classifies any compressed draft before deployment: harm-per-disagreement separates the families (0.14 versus 0.28 to 0.54), and in-distribution disagreement ranks the off-distribution tax exactly on our hardest suite (Spearman 1.0, exact $p = 0.0002$). A measurement protocol makes sampled-decoding comparisons reproducible after we found single-prompt sampled cells swing 12 acceptance points across seeds. All negative results appear in full.

1 INTRODUCTION

Models in the Qwen and DeepSeek lineages ship with a co-trained multi-token-prediction head (Gloeckle et al., 2024; DeepSeek-AI, 2024): one spare transformer block that drafts tokens for speculative decoding (Leviathan et al., 2023; Chen et al., 2023), trained alongside the trunk. The head reaches acceptance rates external drafters struggle to match, and it costs accordingly. Its output projection spans the full 248,320-token vocabulary, so each drafted token reads 1.33GB of weights on a 9B model. Decode is bandwidth-bound, so those reads price directly into generation speed. Deployments that load the head as a separate file also surrender 1 to 2GB of GPU memory that could hold context.

Compressing the head looks routine: the toolbox (vocabulary trimming, quantization, pruning, low-rank factorization, distillation) is mature. Choosing from it safely is the hard part. Standard practice evaluates compressed models on data resembling the calibration set, and on such data the dangerous cuts look free. We measure a pruned head that keeps 97% of its acceptance on calibration-register text and keeps only 80% on genuinely shifted text, a collapse the calibration-side numbers cannot reveal. Which compressions carry this hidden liability, and how a practitioner detects it before deployment, are the questions this paper answers.

The answer is a two-family taxonomy. **Fidelity cuts** reduce the numeric precision of every weight uniformly; quantization is the family. **Function cuts** remove selected structure (channels, ranks) or refit the function on selected data (distillation). Measured across seven compression arms, two models, and three evaluation corpora at increasing distance from calibration, the family alone determines shift behavior. Fidelity cuts pay at most 1.9 acceptance-retention points under severe domain shift, with 8-bit exactly free. Function cuts pay 10 to 19 points on the same suite, a gap of an order of magnitude, and the gap grows with shift distance. The mechanism is statistical, independent of architecture. The parameters serving rare content fire too rarely to accumulate mass on any finite calibration sample, so every selection statistic misses exactly the function that shift will demand.

We test six selection schemes, including one calibrated on the pruned head's own observed failures. All six fail identically.

Draft heads are the right place to establish this, twice over. Verification makes draft errors free: a wrong draft costs latency and leaves the output untouched, so the head tolerates aggressive fidelity loss. Verification also labels every drafted token against ground truth, which makes compression damage countable per token at a scale no task benchmark matches.

This paper contributes:

1. **A zero-training compression recipe.** Trim the head's vocabulary to the model's own 32k hottest tokens, quantize the remainder to NVFP4, keep full-vocabulary verification. The head's per-token reads drop from 1.33GB to 0.21GB and verification keeps the output distribution exact by construction.

2. **The fidelity/function taxonomy with the evidence that makes it actionable.** A 2×2 design separates dimensionality from calibration-dependence: data-free SVD pays more than calibrated SVD, so dimensionality itself is the liability. The six-scheme study shows the function-cut tax survives every zero-training selection statistic.

3. **A pre-deployment audit that needs no shifted data.** Running the compressed head beside its reference on in-distribution documents yields two numbers: disagreement rate and harm per disagreement. Harm classifies the family (0.14 for fidelity cuts versus 0.28 to 0.54 for function cuts). Disagreement ranks the off-distribution tax exactly (Spearman 1.0, exact $p = 0.0002$, on the domain-shift suite).

On Qwen3.5-9B and Qwen3.6-27B in a production CUDA engine, the recipe delivers 1.8× and 2.2× on a short-prompt suite, and 2.0× and 2.7× on a long-context suite, from 212MB and 259MB draft artifacts. Every cell aggregates 80 or 20 prompts and three sampling seeds. The 27B long-context configuration reaches 127.5 tokens per second against 47.7 for plain decoding. An independently built third configuration reproduces the recipe's pattern. The negative results that shaped the taxonomy, six failed selection schemes, two falsified mechanisms, and one retracted headline, appear in full, together with the measurement protocol that makes sampled-decoding comparisons reproducible.




Figure 1. Weights read per drafted token on Qwen3.5-9B. The full-vocabulary output projection dominates the reference head's cost; the recipe (§3.5) cuts total reads 6.3×.

2 Setting: Draft Heads, and Verification as an Oracle

2.1 Co-trained draft heads

Speculative decoding accelerates autoregressive generation by drafting K candidate tokens cheaply and verifying them with one batched pass of the target model (Leviathan et al., 2023; Chen et al., 2023). Classical pipelines draft with a separate small model, which must exist, fit in memory, and match the target's distribution. Co-trained multi-token-prediction heads (Gloeckle et al., 2024; DeepSeek-AI, 2024) remove those requirements: the model ships with one extra transformer block, trained jointly with the trunk, that predicts ahead from the trunk's hidden state. The head inherits the trunk's distribution by construction and reaches acceptance rates external drafters struggle to match.

The built-in convenience carries a fixed cost with two parts (Figure 1). The output projection spans the full vocabulary: 248,320 rows at Qwen3.5 scale, 1.06GB of 8-bit weights read per drafted token. The block itself adds 0.26GB. Decode-time inference is bandwidth-bound, so at $K{=}4$ the head's 5.3GB of reads per round competes directly with the target's own weights for the same memory bus. Deployments that load the head as a separate artifact pay in capacity as well: 1 to 2GB of a consumer GPU's memory that could hold context.

2.2 The verifier as a measurement instrument

Two properties make draft heads the right laboratory for studying compression. First, drafting is error-tolerant by construction. The target verifies every drafted token; a wrong draft costs one round of wasted speculation and never changes the output. Compression errors that would corrupt a base model only slow a draft head down. Second, verification labels every drafted token against ground truth. Each position yields an exact, binary, task-grounded measurement of whether compression changed the function's behavior there, at a scale of millions of labeled positions per GPU-hour. Classifier benchmarks measure compression




Figure 2. The two-family taxonomy with its measured signatures. Family membership alone predicts behavior under distribution shift (§4.3) and the audit's harm rate (§5).

damage through task metrics with their own noise; the verifier measures it directly. We use the first property to justify aggressive compression and the second to measure precisely what each kind of compression destroys.

3 The Cut Taxonomy and the Recipe

3.1 Where the bytes go

The co-trained head is one transformer block plus an output projection over the full vocabulary. On Qwen3.5-9B the projection is $248{,}320 \times 4096$ (1.06GB at 8-bit) and the block is roughly 243M parameters (0.26GB), so a single drafted token reads 1.33GB. Speculative decoding drafts K tokens per round, so at $K{=}4$ the head reads 5.3GB per verify pass. Every compression method attacks this budget somewhere: the projection's rows, the block's precision, the block's channels or rank, or the whole function. We group the methods by what they remove (Figure 2). **Fidelity cuts** lower the numeric precision of every weight and leave the function's structure intact. **Function cuts** remove structure: channels, ranks, or the function itself in favor of a retrained substitute.

3.2 Trim: remove outputs, keep computation

Trim ranks vocabulary rows by frequency over text the model itself generated and keeps the top 32,768 plus every special token, following the load-time trimming direction of FR-Spec (Zhao et al., 2025). A draft-to-target index map converts the trimmed head's argmax back to full-vocabulary token ids, and verification runs against the full vocabulary. The draft can only propose hot tokens, so trim's ceiling is hot coverage: 95 to 99% of generated tokens on our suites. Trim deletes no computation. Every channel, head, and rank still executes; only output rows the draft would rarely propose disappear. This is the structural reason trim carries no distribution-shift tax in §4.3. It is also the reason trim creates no further pruning headroom. We measured the hot-logit energy of every FFN channel: each channel spreads its output over hot and cold rows in proportion to their count. Deleting cold rows orphans no channel.

3.3 Fidelity cuts: uniform precision loss

Quantizing the head's matrices to 8-bit or 4-bit blocks perturbs every weight by a small rounding error. The perturbation is uniform by construction: the rounding selects no weight, so it singles out no sub-function for damage. The draft setting makes this nearly free twice over. A draft error costs one round of latency and never correctness, because the target verifies every token; and the head's job, ranking likely continuations, survives logit noise that would matter in a lossless setting. Our 4-bit format is NVFP4 (16-element blocks, e2m1 values, fp8 sub-scales), the project's deployment standard; Q4_0 behaves the same within noise. Section 4.3 quantifies the family's worst case at 1.9 retention points under severe domain shift, with 8-bit exactly free.

3.4 Function cuts: selection is the liability

Channel pruning and low-rank factorization remove specific structure, chosen either by a statistic over calibration data or, for data-free SVD, by the weight matrix's own spectrum. Distillation replaces the head with a smaller one trained on chosen data. All three tie the surviving function to a finite sample: the calibration set, the spectrum's large directions, or the training distribution. Content that the sample under-represents loses its machinery, and §4.3 shows the loss arrives exactly there, at 10 to 19 retention points under domain shift. The six-scheme study in §4.5 shows the liability follows from selection itself: statistics computed on finite samples cannot see rare-firing function, whatever the statistic.

Distillation deserves one scoping sentence. A distilled replacement reaches 91 to 98% of the teacher's chain acceptance on its training register at 13% of the compute. It is the only option when a model ships no co-trained head, or when a quantized base breaks the head it has. When a strong co-trained head exists, the trained substitute never beat the trimmed original in our aggregate cells, and it inherits the function-cut robustness profile.

3.5 The recipe

The safe moves compose: trim the projection (structural, coverage-capped, shift-proof in §4.3) and quantize what remains (uniform, 1.9 points worst case). One command exports the artifact from a HuggingFace checkpoint: rank the vocabulary on the model's own output, gather the hot rows, quantize head and block to NVFP4, and emit a standalone draft file with the index map. The 9B artifact is 212MB

against the natural head's 1.33GB of per-token reads; the 27B artifact is 259MB. No training step exists anywhere in the pipeline, so the recipe runs on the deployment machine in minutes.

4 Evaluation

4.1 Setup

We evaluate on Qwen3.5-9B and Qwen3.6-27B, two dense hybrid models that ship co-trained MTP heads, running in bw24, a production CUDA engine, on a single RTX PRO 6000 (96GB). Two prompt suites cover the serving range. The short suite is MT-Bench: 80 prompts across eight categories, 256 generated tokens each. The long suite is 20 prompts of 1.9k to 5.9k tokens (documents with analysis instructions, long code files with review instructions), 512 generated tokens each. Each cell reports acceptance (accepted drafts over drafted tokens at $K{=}4$) and end-to-end tokens per second against the same-suite plain-decode baseline, for greedy decoding and for temperature 0.7 with three sampling seeds.

The aggregate protocol is itself a finding. A single-prompt sampled cell swings by 12 acceptance points across seeds: the sampler wanders into a different trajectory, and acceptance reflects whatever content appears. Toggling an attention-kernel variant moves the trajectory the same way. Suite-level aggregation with three seeds brings the spread under 1.5 points. Every number below is an aggregate; we report single-prompt cells nowhere. One earlier headline of ours (a 2.68× sampled cell) failed this protocol; we retracted it in the lab record.

Arms. The reference is the unmodified head. Trim replaces the 248,320-row output projection with the 32,768 rows ranked hottest on the model's own generated text, plus an index map into the full vocabulary. Verification stays full-vocabulary, so greedy output stays identical and sampled output stays distribution-exact. Trim-Q8 and trim-NVFP4 quantize all head matrices to 8-bit and 4-bit blocks on top of the trim. The robustness study (§4.3) adds channel pruning at two budgets, low-rank factorization at a byte-matched rank in data-free and calibrated variants, and the distilled replacement head.

4.2 The recipe matches or beats every arm end to end

Table 1 reports the full grid, and Figure 3 plots the greedy cells. On the 9B short suite, trim-NVFP4 reaches 262.8 tok/s (1.82× over plain decode) against 256.5 (1.78×) for trim-Q8 and 219.1 (1.52×) for the unmodified head. On the 9B long suite the ordering tightens: trim-Q8 292.3 (2.04×), trim-NVFP4 282.5 (1.98×), unmodified 245.8 (1.72×). At 27B the 4-bit arm leads outright. It reaches 103.3 tok/s (2.15×) on the short suite, tying Q8 to the decimal at half the head bytes. On the long suite it reaches 127.5 tok/s (2.67×), ahead of Q8's 123.6 and the unmodified head's 115.3. Sampled cells track greedy with a 0.1 to 0.2× penalty across all arms.

Table 1. End-to-end results, greedy aggregate cells: acceptance at $K{=}4$ and speedup over the same-suite plain-decode baseline. Sampled cells (temperature 0.7, three seeds) track greedy with a 0.1 to 0.2× penalty.

Suite	Arm	Acceptance	Speedup
9B short	reference	50.1%	1.52×
	trim-Q8	47.0%	1.78×
	trim-NVFP4	45.6%	**1.82**×
9B long	reference	61.6%	1.72×
	trim-Q8	60.0%	**2.04**×
	trim-NVFP4	54.7%	1.98×
27B short	reference	53.2%	2.02×
	trim-Q8	50.4%	**2.15**×
	trim-NVFP4	48.6%	**2.15**×
27B long	reference	69.7%	2.42×
	trim-Q8	69.5%	2.59×
	trim-NVFP4	67.5%	**2.67**×




Figure 3. Speedup over plain decode across both models and suites (greedy aggregate cells). Trim-NVFP4 is fastest or tied-fastest everywhere, and every arm's gain grows with target scale (§4.4).

Acceptance explains the shape. Trimming costs 0 to 3 acceptance points (at 27B long, 0.2 points) because hot-vocabulary coverage on generated text is 95 to 99%. Four-bit quantization costs another 1.4 to 5.3 points. The bandwidth saving buys those points back everywhere except one cell (9B long greedy, where Q8's higher acceptance wins by 3%). A third configuration built independently in the engine's own lane, with a different vocabulary ranking and a q4_K block, reproduced the pattern and beat its own prior champion on both speed and acceptance.

Takeaway. Trim-NVFP4 turns the 1.33GB-per-token head into a 212MB artifact that is the fastest or tied-fastest arm in every aggregate cell, with zero training and unchanged




Figure 4. Acceptance retention versus shift distance for all seven arms. Solid blue: fidelity cuts. Dashed red: function cuts. Family membership alone determines the trajectory, and the separation grows with shift distance.

outputs.

4.3 Robustness separates the families by an order of magnitude

We measure each compressed arm's acceptance retention (arm accuracy over reference accuracy on identical states) on three corpora at increasing distance from the calibration distribution. The first is held-out generated documents (in-distribution). The second is fresh generations on unseen topics (same register). The third is a genuine domain-shift suite of German, Chinese, Hebrew, and Russian Wikipedia, PubMed abstracts, and C4 web text, on which the reference head's own accuracy drops from 0.88 to 0.36.

The tax divides the arms into two families. Figure 4 traces all seven arms across the three corpora, and Table 2 gives the values. Fidelity cuts stay within noise of free: Q8 retains 99.8 to 99.9% everywhere, and the 4-bit arms retain 97.5 to 99.4%, a worst-case tax of 1.9 points with a confidence interval that includes zero. Function cuts pay 10 to 19 points on the domain-shift suite: 16.8 for pruning at 25% keep, 10.2 at 50% keep, 16.8 to 18.7 for the low-rank arms. The family gap of 14.5 retention points is significant at the permutation-test floor for seven arms ($p = 0.029$), and every function-cut tax individually excludes zero at 95% confidence. The same ordering appears on the same-register corpus at one tenth the magnitude: same-register evaluation understates the effect that deployment will see.

The taxonomy also survives quantization of the base model itself. A cross on the 9B model pairs each head arm with a bf16 base and an NVFP4-quantized base, since deployed bases are rarely full-precision. Head-compression costs stay base-independent: the 4-bit head costs 4.5 acceptance points against the bf16 base and 6.0 against the quantized base, and each compressed head's absolute acceptance moves under one point across bases. Fidelity cuts to head and base compound in speed rather than in damage. The quantized base decodes 32% faster on its own, and adding the trim-NVFP4 head reaches 292.7 tokens per second, 2.03× over bf16 plain decode.

Table 2. Acceptance retention (%) by corpus, and the shift tax (in-distribution retention minus domain-shift retention, in points). Positions per corpus: 2,500 in-distribution, 2,500 same-register, 2,500 domain-shift.

Arm	In-dist	Same-reg	Dom-shift	Tax
Q8	99.8	100.0	99.9	−0.1
Q4_0	99.4	99.5	97.7	1.7
NVFP4	99.3	100.1	97.5	1.9
prune 25%	97.2	95.0	80.4	16.8
prune 50%	98.4	97.9	88.2	10.2
SVD (data-free)	89.9	85.1	71.1	18.7
SVD (calibrated)	90.5	87.0	73.7	16.8




Figure 5. Per-bin retention under domain shift by token log-frequency quintile. Pruning's damage concentrates in rare bins (66% at the rarest, 93% at the hottest); the low-rank arm damages every bin; NVFP4 stays near 97% throughout.

The full grid replicates on Qwen3.6-27B. On the same domain-shift suite, re-extracted through the 27B trunk, fidelity taxes stay at or under 1.5 points and function taxes run 7.6 to 12.7 points. The family gap survives the model change.

Two internal comparisons localize the cause. Data-free SVD pays a larger tax than calibration-weighted SVD at equal rank, so dimensionality itself drives the damage, independent of calibration data. And pruning's tax concentrates in rare-token bins while the low-rank tax spreads across all bins (Figure 5), yet both pay: selective cuts choose different function to delete, and shift surfaces the deletion either way.

Takeaway. Under genuine distribution shift, function cuts cost an order of magnitude more acceptance than fidelity cuts, the gap widens with shift distance, and the effect is invisible to in-distribution evaluation.

4.4 Speedups grow with target scale

Every arm gains more at 27B than at 9B: the unmodified head goes from 1.52×/1.72× (short/long) to 2.02×/2.42×, and trim-NVFP4 from 1.82×/1.98× to 2.15×/2.67×. The draft's cost shrinks relative to the target's verify pass as the target grows, so each accepted token buys more. Draft compression compounds with this trend: the cheaper the round, the higher the optimal speculation depth the deployment can afford. $K{=}8$ remains counterproductive for all arms at both scales; $K{=}4$ is the operating point throughout.

Takeaway. The recipe's value increases with model size; 27B gains roughly double the 9B gains in absolute tokens per second saved.

4.5 No selection statistic escapes the function-cut tax

Six selection schemes for channel pruning fail identically. The first four rank by activation statistics: global mass, activation-times-weight-norm (Sun et al., 2023), wide calibration over 100 documents, and an online exponential-moving-average mask updated on the live stream. The last two condition the statistic: vocabulary-conditioned selection by hot-logit energy, and divergence-conditioned selection calibrated on the exact positions where the pruned head fails. The last is the sharpest: restoring pruned channels ranked by their activation at observed failure positions recovers less accuracy than restoring channels by plain global mass. The mechanism is statistical. The channels that serve rare content fire rarely, so they accumulate negligible mass on any finite calibration sample. The hot-logit energy of every channel sits in a narrow band around the hot vocabulary's share, so no channel specializes in the trimmed vocabulary and none identifies as safe to cut. We scope this result to zero-training, statistics-based selection: gradient-based selection and prune-then-finetune recovery lie outside this paper's zero-training envelope.

Takeaway. Within zero-training compression, the function-cut tax is a property of selection from finite samples, and switching the statistic does not remove it.

5 The Audit: Classify a Compressed Draft Before Deploying It

5.1 Why an audit

Section 4.3's taxes are measurable only with a domain-shift test set, which a deployment rarely has: the traffic that breaks a compressed draft is the traffic nobody collected. The practical question is whether in-distribution measurements, which any deployment can produce in minutes, predict the off-distribution behavior. They do.

5.2 Protocol

Run the compressed head and its uncompressed reference on the same in-distribution documents, teacher-forced over identical states, and record two numbers per arm. The **disagreement rate** is the fraction of positions where the two heads' top-1 predictions differ. The **harm rate** is the accuracy the compressed head loses per disagreement: how often a disagreement replaces a correct prediction with a wrong one instead of trading predictions of equal value. Both numbers come from forward passes only; the whole audit on 2,500 positions takes minutes on one GPU.

5.3 What the two numbers say

Harm rate identifies the family. Fidelity cuts disagree by tie-flipping: their rounding noise swaps tokens of near-equal probability, so a disagreement costs almost nothing (harm 0.14 across our 4-bit arms; Q8 disagrees 8 times in 2,500 positions, too few to score and too few to matter). Function cuts disagree by losing function: their disagreements land where machinery vanished, so each one costs accuracy (harm 0.28 to 0.54). Disagreement rate then ranks severity within and across families: on the same-register corpus it predicts the off-distribution tax at Spearman 0.89 (exact $p = 0.006$) over seven arms.

The decision rule for a deployment has two branches. Harm rate near 0.15 means the compression is noise-type, and its in-distribution cost is the full cost. Harm rate above 0.25 means the compression is function-type, and live traffic will multiply the in-distribution damage. In our measurements the multiplier under genuine shift is 6 to 10×.

5.4 Validation under genuine shift

On the domain-shift suite (§4.3), where the taxes are largest, the audit's in-distribution disagreement ranking orders the seven arms' taxes exactly: Spearman 1.0, exact $p = 0.0002$ (Figure 6). The 27B replication reproduces the exact ranking over its own seven arms, so the instrument transfers across model scale unchanged. The audit gets stronger where it matters more, because larger true taxes are easier to rank. The instrument's limits are its inputs: it compares against the uncompressed reference (which must exist), and it certifies the compression alone; model quality is out of its scope.

5.5 The statistic that failed

Our first audit scored the concentration of disagreements in rare-token bins, on the mechanism's logic that function cuts damage rare continuations. It failed on both families.




Figure 6. The audit. In-distribution disagreement (x-axis, forward passes only) ranks the domain-shift tax (y-axis) exactly over the seven arms. Circles: fidelity cuts. Squares: function cuts.




Figure 7. Hot-logit energy ratio for all 12,288 FFN channels. The distribution peaks at the hot vocabulary's uniform share (dashed line): no channel specializes in the trimmed vocabulary, so trim orphans nothing that pruning could harvest.

Quantized arms also disagree disproportionately on rare tokens, harmlessly, by tie-flip, since rare-token logit margins are thin. The low-rank arms damage all bins. Rarity-concentration measures where disagreements sit; harm rate measures what they cost, and only cost separates the families. We report this because instrument design is the contribution: the obvious statistic reads plausibly and misclassifies every quantized arm.

6 Why Selection Fails: The Tail Is Statistically Invisible

6.1 Rare function, rare evidence

An activation statistic assigns each channel the evidence its firing history provides. A channel that serves common syntax fires at every position and dominates any ranking. A channel that serves rare content, an uncommon language, a technical register, an unusual construction, fires on the rare positions that need it. Over a finite calibration sample its accumulated mass is indistinguishable from a useless channel's. The selection problem is therefore ill-posed for exactly the parameters that carry shifted-content function: the calibration data that would reveal them is by definition the data the deployment has never seen. Widening the sample does not help at any width we tested (12 to 100 documents, and an online mask over the live stream itself), because the tail scales with the sample.

The divergence-conditioned scheme sharpens the point. We restored pruned channels ranked by their activation at the exact positions where the pruned head fails, the most failure-targeted statistic available without gradients. It recovered less accuracy than restoring channels by plain global mass. Even conditioning on observed failures does not expose the tail, because at those positions the missing channels are missing: they cannot fire in the pruned network that produced the failures.

6.2 Superposition blocks the shortcut

Vocabulary trim suggests a shortcut: after deleting 87% of the output rows, some block machinery should serve only the deleted rows and die harmlessly. We measured it. For every FFN channel we computed the fraction of its output-projection energy landing on hot rows. The distribution is a narrow band (0.116 to 0.159 across all 12,288 channels) around the hot vocabulary's share of total energy (Figure 7). Every channel spreads its influence across the whole vocabulary in near-uniform proportion, the signature of features stored in superposition. Trim therefore orphans no computation, which explains both of its properties at once: it is shift-proof because it removes no function, and it creates no pruning headroom because no function became dead.

6.3 Falsified explanations

Two mechanisms we believed earlier failed their tests, and both failures tightened the result. First, carrier compounding: we hypothesized that pruning corrupts the hidden state each draft step passes to the next, compounding down the chain. Teacher-forced chain measurements refuted it: the pruned head holds 97% of the full head's chain acceptance on calibration-register text, in torch and in the engine. The damage is content-conditional and needs no error accumulation. Second, rarity-concentration as the audit signal (§5.5): where disagreements sit does not separate the families; what they cost does. The surviving mechanism is the statistical one above, and it makes one falsifiable prediction the data

confirms: the tax must grow with shift distance, because shift raises the frequency of positions whose machinery was invisible at selection time. Retention falls monotonically from held-out (97 to 99%) through same-register (95 to 97%) to domain shift (71 to 88%) for every function cut, while every fidelity cut stays within two points across the whole range.

7 Related Work

Speculative decoding with cheap drafts. FR-Spec (Zhao et al., 2025) trims the draft vocabulary at load time and reports 1 to 3% end-to-end gain in llama.cpp. On a bandwidth-optimized engine we measure trim alone at 1.8 to 2.7×, and it composes with quantization. QSpec (Zhao et al., 2024) and ML-SpecQD (Georganas et al., 2025) draft with quantized variants of the target model itself: QSpec switches quantization schemes within one model, ML-SpecQD direct-casts the target to MXFP4 as a plug-and-play draft. Both established that 4-bit drafting preserves acceptance; neither compresses a co-trained head (their drafts are whole-model copies measured in gigabytes), and neither analyzes which compressions are safe. A hierarchical-framework study (Zhang et al., 2025) evaluates speculative decoding on quantized targets and finds the combination fragile in the memory dimension. EAGLE-family drafters (Li et al., 2024) and SlimSpec's low-rank drafter head (Plaksin et al., 2026) address models without co-trained heads; the co-trained head's acceptance is the reason we compress it instead of replacing it.

Compression damages the tail. Hooker et al. established with Pruning Identified Exemplars (Hooker et al., 2019) that pruned vision classifiers sacrifice underrepresented examples first, with quantization milder. LLM-era evaluations (LLM-KICK (Jaiswal et al., 2024) and successors) report broad capability loss from pruning that perplexity hides. This line measures example-level task accuracy on whole models with one cut type at a time. We add four things: the token-level oracle (millions of exact labels per GPU-hour), the 2×2 design separating dimensionality from calibration-dependence, the six-scheme selection study that turns an observation into a selection-theoretic account, and the dose-response measurement across three shift distances. The taxonomy's practical half, the harm-rate audit, has no counterpart in this line: prior work diagnoses damage post hoc on curated test sets, where the audit predicts it pre-deployment from in-distribution forward passes.

Quantization robustness. The QAT and post-training-quantization literature long ago established that uniform quantization degrades gracefully; we claim no priority there. Our contribution is comparative and mechanistic: at matched in-distribution retention, quantization's damage stays flat under distribution shift while every selective cut's damage grows, and the difference traces to what each cut removes.

8 Playbook and Limitations

8.1 Constraint to cut

Table 3 maps deployment constraints to the safe cut.

8.2 Limitations

The evidence covers one model family (Qwen3.5-9B, Qwen3.6-27B) and one engine, with an independent third configuration reproducing the recipe's pattern. Other architectures' heads may sit differently on the cost curve. The taxonomy's mechanism (§6) has no model-specific ingredient. The impossibility result covers zero-training, statistics-based selection; gradient-informed selection and prune-then-finetune recovery sit outside the zero-training envelope this paper commits to, and could in principle re-earn their cuts. The audit requires the uncompressed reference head for its comparison passes. The domain-shift suite, though genuinely shifted (the reference's own accuracy drops 2.4×), is 24 documents; the taxes it measures carry the confidence intervals of §4.3, and wider suites would tighten them. Hot-vocabulary coverage caps trim at 95 to 99% on the registers we serve. A deployment dominated by content outside its hot set needs its vocabulary re-ranked. Coverage is measurable in-distribution, and re-export takes minutes.

References

Chen, C., Borgeaud, S., Irving, G., Lespiau, J.-B., Sifre, L., and Jumper, J. Accelerating large language model decoding with speculative sampling. *arXiv preprint arXiv:2302.01318*, 2023.

DeepSeek-AI. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*, 2024.

Georganas, E., Kalamkar, D., Kozlov, A., and Heinecke, A. ML-SpecQD: Multi-level speculative decoding with quantized drafts. *arXiv preprint arXiv:2503.13565*, 2025.

Gloeckle, F., Youbi Idrissi, B., Rozière, B., Lopez-Paz, D., and Synnaeve, G. Better & faster large language models via multi-token prediction. *arXiv preprint arXiv:2404.19737*, 2024.

Hooker, S., Courville, A., Clark, G., Dauphin, Y., and Frome, A. What do compressed deep neural networks forget? *arXiv preprint arXiv:1911.05248*, 2019.

Jaiswal, A., Gan, Z., Du, X., Zhang, B., Wang, Z., and Yang, Y. Compressing LLMs: The truth is rarely pure and never simple. In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2310.01382.

Table 3. The playbook: deployment constraint to safe action.

Your situation	Do this	Expect
Model ships a co-trained head; decode is bandwidth-bound	Trim + NVFP4 (the recipe, §3.5)	1.8 to 2.7× over plain decode; 212 to 259MB artifact; no training
Memory pressure demands more than 4-bit trim delivers	Stop. Pruning and low-rank buy at most 90MB more and pay 10 to 19 acceptance points on shifted traffic	Run the audit (§5) before believing any further cut
Compressed draft from any source, provenance unknown	Audit it: harm rate under 0.15 is noise-type, above 0.25 is function-type	Minutes of forward passes; Spearman 1.0 tax ranking on our hardest suite
No co-trained head exists, or a quantized base broke it	Distill a replacement on the model's own serving-regime output (chain KD, then brief CE)	91 to 98% of a co-trained teacher's chain acceptance; function-cut robustness profile
Benchmarking any sampled-decoding change	Aggregate suites with 3+ seeds; never single prompts	Single-prompt sampled cells swing 12 points across seeds

Leviathan, Y., Kalman, M., and Matias, Y. Fast inference from transformers via speculative decoding. In *International Conference on Machine Learning (ICML)*, 2023. arXiv:2211.17192.

Li, Y., Wei, F., Zhang, C., and Zhang, H. EAGLE: Speculative sampling requires rethinking feature uncertainty. In *International Conference on Machine Learning (ICML)*, 2024. arXiv:2401.15077.

Plaksin, A., Krutikov, S., Skvortsov, S., and Samarin, A. SlimSpec: Low-rank draft LM-head for accelerated speculative decoding. *arXiv preprint arXiv:2605.10453*, 2026.

Sun, M., Liu, Z., Bair, A., and Kolter, J. Z. A simple and effective pruning approach for large language models. *arXiv preprint arXiv:2306.11695*, 2023.

Zhang, Y., Zhao, W., Han, X., Zhao, T., Xu, W., Cao, H., and Zhu, C. Speculative decoding meets quantization: Compatibility evaluation and hierarchical framework design. *arXiv preprint arXiv:2505.22179*, 2025.

Zhao, J., Lu, W., Wang, S., Kong, L., and Wu, C. QSpec: Speculative decoding with complementary quantization schemes. *arXiv preprint arXiv:2410.11305*, 2024.

Zhao, W., Pan, T., Han, X., Zhang, Y., Sun, A., Huang, Y., Zhang, K., Zhao, W., Li, Y., Wang, J., Liu, Z., and Sun, M. FR-Spec: Accelerating large-vocabulary language models via frequency-ranked speculative sampling. *arXiv preprint arXiv:2502.14856*, 2025.