Simple Tables

Source-backed grouped table sample

Tables

These tables are grouped from source-backed LaTeX table data and compiled as a single benchmark data point.

max-min iter.	μ_l	μ_h	$\mu_{x_{in}}$	μ_{z_x}	μ_{r_s}	μ_c	μ_a	$\mu_{r_{cat}}$	μ_m	μ_d
1	5	10	3	5	1.0	8	tanh	0.9	0.4	uniform
2	3	5	2	5	0.1	2	identity	1.0	0.4	uniform
3	12	128	13	200	0.0	2	identity	0.4	0.0	uniform
4	3	5	2	6	0.6	2	tanh	1.0	0.0	exponential
5	10	64	8	32	0.4	2	tanh	1.0	0.0	uniform
6	8	32	5	13	0.8	10	identity	0.0	0.2	normal
7	10	64	8	162	0.9	6	elu	0.6	0.0	normal
8	5	10	3	13	0.0	10	tanh	0.8	0.0	uniform
9	5	10	3	5	0.3	6	identity	0.6	0.0	exponential
10	5	10	3	5	0.1	10	tanh	0.5	0.0	normal
11	3	5	2	5	0.0	8	relu	1.0	0.0	normal
12	3	5	2	5	0.6	4	relu	0.6	0.0	exponential
13	3	5	2	5	0.4	6	tanh	0.6	0.0	normal
14	5	10	3	5	0.8	8	identity	0.8	0.0	exponential
15	3	5	2	5	1.0	8	elu	0.6	0.0	uniform
16	3	5	2	6	0.7	6	identity	0.3	0.0	uniform
17	8	32	5	91	0.0	2	tanh	1.0	0.0	exponential
18	3	5	2	5	0.0	8	tanh	1.0	0.0	exponential
19	3	5	2	6	0.2	6	tanh	0.2	0.0	exponential
20	12	128	13	200	0.2	2	identity	0.1	0.0	exponential
21	3	5	2	6	0.9	8	relu	0.6	0.0	exponential
22	3	5	2	5	0.3	8	identity	0.2	0.0	uniform
23	5	10	3	5	0.2	4	tanh	0.3	0.0	normal
24	3	5	2	5	0.8	8	identity	0.1	0.0	uniform
25	3	5	2	5	0.2	4	relu	1.0	0.0	exponential
26	3	5	2	5	0.5	8	tanh	0.8	0.0	normal
27	8	32	5	13	0.1	4	identity	0.0	0.0	exponential
28	3	5	2	6	0.4	4	tanh	0.1	0.0	exponential
29	3	5	2	5	0.1	8	identity	0.2	0.0	exponential

Table 1: Source table 1: 2512.03307_table_5

#	Word type	*f*
1.	*te* (‘at’, ‘to’, COMP)	1018
2.	*dat* (‘that’)	658
3.	*niet* (‘not’)	650
4.	*om* (‘to’)	446
5.	*de* (‘the’, MASC/FEM/PL)	291
6.	*er* (‘there’)	271
7.	*geen* (‘no’)	270
8.	*elk* (‘every’, NEUT)	251
9.	*iedere* (‘every’, MASC/FEM)	247
10.	*of* (‘or’, ‘whether’)	244
11.	*elke* (‘every’, MASC/FEM)	229
12.	*ieder* (‘every’, NEUT)	223
13.	*alle* (‘all’)	215
14.	*een* (‘a’, ‘one’)	212
15.	*ik* (‘I’)	194
16.	*massa’s* (‘masses’)	186
17.	*het* (‘the’, NEUT;SG)	180
30.	*[illegible]*	96