STRUCTURE & SKY
STUDIOS

LOGO USAGE GUIDE
Version 1.0 · October 2026

THE LOGO

A building seen before it exists: floors, a lifted roof, and a drone dot on an open orbit. Use the master mark wherever it can be 32 px / 9 mm tall or larger. Below that, use the small cut.



Master on light · master on dark · one-colour black / on brass / white



Small cut: 4 floors, no orbit. For favicons and sizes under 32 px.

CLEAR SPACE AND SIZE



Keep clear space on every side equal to one sixth of the mark height (about the height of the lifted roof). Nothing enters it.

- Master mark: minimum 32 px / 9 mm tall
- Small cut: 16 px / 5 mm tall
- Horizontal lockup: minimum 120 px / 30 mm wide
- Stacked lockup: minimum 90 px / 24 mm wide

OVER RENDERS AND VIDEO

- Use the one-colour white mark at 60% opacity
- Bottom-right corner, margin 4% of frame width
- Under 64 px tall, use the small cut
- Never over faces or the building being shown

COLOUR

Ink #0E1824
RGB 14 24 36 · CMYK ~61 33 0 86

Ivory #F2EBDD
RGB 242 235 221 · CMYK ~0 3 9 5

Brass #C8A064
RGB 200 160 100 · CMYK ~0 20 50 22

Deep brass #A87C3E
Brass on light backgrounds · CMYK ~0 26 63 34

Slate #6B6F75
Secondary text · CMYK ~0 0 0 65

CMYK values are straight conversions. Proof before printing; pick Pantone matches by eye.

PLEASE DON'T



Stretch · recolour · rotate · add shadows or effects. Also: don't move the dot off its orbit, don't outline the mark, don't change the weights in the wordmark, don't put the master on busy images (use one-colour).

MOTION

- Intro plays once, about 5 seconds; don't speed it up
- End on the still logo
- Reduced-motion viewers get the still logo