

6. Create new VPC network with automatic subnets. Configure the firewall rule to allow ssh access from only Quantiphi's IP. Use Console

VPC with automatic subnets:

← Create a VPC network

Name ?

av-a1-q6

Description (Optional)

VPC with automatic subnets. (gcp-asgn1 q6)

Subnets

Subnets let you create your own private cloud topology within Google Cloud. Click Automatic to create a subnet in each region, or click Custom to manually define the subnets. [Learn more](#)

Subnet creation mode

Custom

Automatic

⚠ These IP address ranges will be assigned to each region in your VPC network. When an instance is created for your VPC network, it will be assigned an IP from the appropriate region's address range.

<< Previous

1

2

Next >>

Region	IP address range
us-central1	10.128.0.0/20
eu-west-1	10.132.0.0/20
us-west1	10.138.0.0/20
asia-east1	10.140.0.0/20
us-east1	10.142.0.0/20
asia-northeast1	10.146.0.0/20

Firewall rule to allow ssh access from Q's IP addresses only:

←

Create a firewall rule

Firewall rules control incoming or outgoing traffic to an instance. By default, incoming traffic from outside your network is blocked. [Learn more](#)

Name ?

av-a1-q6

Description (Optional)

allow ssh access only to Q's IP addrs. gcp assgn-1 q6

Logs
Turning on firewall logs can generate a large number of logs which can increase costs in Stackdriver. [Learn more](#)

☐ On
☒ Off

Network ?

av-a1-q6

Priority ?

Source filter ?

IP ranges

Source IP ranges ?

59.152.53.168/30

59.152.53.104/29

59.152.53.200/29

59.152.53.120/29

59.152.52.104/29

59.152.52.152/29

59.152.52.172/30

202.122.21.69/32

Second source filter ?

None

Protocols and ports ?

☐ Allow all

☒ Specified protocols and ports

☒ tcp :

22

☐ udp :

all

☐ Other protocols

protocols, comma separated, e.g. ah, sctp

[↕ Disable rule](#)

Create

Cancel