

51% completed



Search Course

Java Concurrency
Reference

- Setting-up Threads
- Basic Thread Handling
- Executor Framework
- Executor Implementations
- Thread Pools
- Types of Thread Pools
- An Example: Timer vs ScheduledThreadPool
- ThreadPoolExecutor
- Callable Interface
- Future Interface
- CompletionService Interface
- ThreadLocal
- ThreadLocalRandom
- CountDownLatch
- CyclicBarrier
- Concurrent Collections
- ConcurrentHashMap
- ConcurrentModificationException

Practice Mock Interview →

Java Multithreading for Senior Engineering Interviews / ... / CyclicBarrier

CyclicBarrier

Explanation

`CyclicBarrier` is a synchronization mechanism introduced in JDK 5 in the `java.util.concurrent` package. It allows multiple threads to wait for each other at a common point (barrier) before continuing execution. The threads wait for each other by calling the `await()` method on the `CyclicBarrier`. All threads that wait for each other to reach barrier are called parties. *You can read-up on designing and implementing a barrier for an interview question [here](#).

`CyclicBarrier` is initialized with an integer that denotes the number of threads that need to call the `await()` method on the barrier. Second argument in `CyclicBarrier`'s constructor is a `Runnable` instance that includes the action to be executed once the last thread arrives. The most useful property of `CyclicBarrier` is that it can be reset to its initial state by calling the `reset()` method. It can be reused after all the threads have been released. Lets take an example where `CyclicBarrier` is initialized with 3 worker threads that will have to cross the barrier. All the threads need to call the `await()` method. Once all the threads have reached the barrier, it gets broken and each thread starts its execution from that point onwards.

```
/**
 * Runnable task for each thread.
 */
class Task implements Runnable {

    private CyclicBarrier barrier;

    public Task(CyclicBarrier barrier) {
        this.barrier = barrier;
    }

    //Await is invoked to wait for other threads
    @Override
    public void run() {
        try {
            System.out.println(Thread.currentThread().getName() + " is waiting on barrier");
            barrier.await();
            //printing after crossing the barrier
            System.out.println(Thread.currentThread().getName() + " has crossed the barrier");
        } catch (InterruptedException ex) {
            Logger.getLogger(Task.class.getName()).log(Level.SEVERE, null, ex);
        } catch (BrokenBarrierException ex) {
            Logger.getLogger(Task.class.getName()).log(Level.SEVERE, null, ex);
        }
    }
}

/**
 * Main thread that demonstrates how to use CyclicBarrier.
 */
public class Main {
    public static void main (String args[]) {

        //Creating CyclicBarrier with 3 parties i.e. 3 Threads needs to call await()
        final CyclicBarrier cb = new CyclicBarrier(3, new Runnable(){

            //Action that executes after the last thread arrives

        });

        /**
         * Main thread that demonstrates how to use CyclicBarrier.
         */
        public class Main {
            public static void main (String args[]) {

                //Creating CyclicBarrier with 3 parties i.e. 3 Threads needs to call await()
                final CyclicBarrier cb = new CyclicBarrier(3, new Runnable(){

                    //Action that executes after the last thread arrives
                    @Override
                    public void run(){
                        System.out.println("All parties have arrived at the barrier, lets continue execution.");
                    }
                });

                //starting each thread
                Thread t1 = new Thread(new Task(cb), "Thread 1");
                Thread t2 = new Thread(new Task(cb), "Thread 2");
                Thread t3 = new Thread(new Task(cb), "Thread 3");

                t1.start();
                t2.start();
                t3.start();
            }
        }
    }
}
```

Java




> main.java

Saved

```
1- import java.util.concurrent.BrokenBarrierException;
2- import java.util.concurrent.CyclicBarrier;
3-
4- /**
5-  * Main thread that demonstrates how to use CyclicBarrier.
6-  */
7- public class main {
8-     public static void main (String args[]) {
9-
10         //Creating CyclicBarrier with 3 parties i.e. 3 Threads needs to call await()
11         final CyclicBarrier cb = new CyclicBarrier(3, new Runnable()){
12
```

A pictorial representation appears below:



[← Back lesson](#)

[✓ Mark As Completed](#) [Next →](#)

CountDownLatch

Concurrent Collections