


JAVA TRAINING CENTER

Java Training Center
(No.1 in Training & placement)



java.lang WorkBook

Master the content...

W.B-3

Author

Som Prakash Rai

JAVA TRAINING CENTER

Topic

Jtc 1: Example using Object class Method.

Jtc 2: Example using equals Method.

Jtc 3: Example using cloning.

Jtc 4: Example for GC

Jtc 5: Example For Immutable Class

Jtc 6 – Jtc 19: Example using String Class

Jtc 20: Example using StringBuffer class .

Jtc 21: Example using StringBuffer class .

Jtc 22: Example using System class .

Jtc 23: Example using Runtime class .

Jtc 24: Example using Singleton class. (C)

Jtc 25: Example using Wrapper Class

java.lang APIs

JAVA TRAINING CENTER

Jtc 1: Example using Object class Method


```
package com.JTC.obj.test;
/*
 * @Author   : Som Prakash Rai
 * @Join      : Java Training Center
 * @visit     : www.jtcindia.org
 * @Call      : +91-9990399111
 */
public class Jtc1 {
    public static void main(String[] args) {
        System.out.println("**** hashCode ****");
        System.out.println("=== Student ===");
        Student st1 = new Student(99, "Som", 399111);
        Student st2 = new Student(99, "Som", 399111);
        Student st3 = new Student(88, "Prakash", 399111);
        Student st4 = st1;
        System.out.println(st1.hashCode());
        System.out.println(st2.hashCode());
        System.out.println(st3.hashCode());
        System.out.println(st4.hashCode());
        System.out.println(st1 == st2);
        System.out.println(st1 == st3);
        System.out.println(st1 == st4);
        System.out.println("=== Employee ===");
        Employee emp1 = new Employee(99, "Som", 399111);
        Employee emp2 = new Employee(99, "Som", 399111);
        Employee emp3 = new Employee(88, "Prakash", 7458965);
        Employee emp4 = emp1;
        System.out.println(emp1.hashCode());
        System.out.println(emp2.hashCode());
        System.out.println(emp3.hashCode());
        System.out.println(emp4.hashCode());
        System.out.println(emp1 == emp2);
        System.out.println(emp1 == emp3);
        System.out.println(emp1 == emp4);
        System.out.println("\n**** getClass ****");
        ClassService.showClassInfo("JTC");
        ClassService.showClassInfo(st1);
        ClassService.showClassInfo(emp1);
        System.out.println("\n**** toString ****");
        System.out.println(st1);
    }
}
```

JAVA TRAINING CENTER

```
System.out.println(st2);
System.out.println(st1.toString());
System.out.println(st2.toString());
String str1 = "OK";
str1 = str1 + st1;
System.out.println(str1);
System.out.println(emp1);
System.out.println(emp3);
Employee emp5 = null;
System.out.println(emp5);
String str11 = "OK";
str11 = str11 + emp5;
System.out.println(str11);
//System.out.println(emp5.toString());
System.out.println("-----");
System.out.println(st1);
System.out.println(st1.toString());
String cName=st1.getClass().getName();
int hs=st1.hashCode();
String hx=Integer.toHexString(hs);
String msg=cName+"@"+hx;
System.out.println(msg);
}
}
class ClassService {
static void showClassInfo(Object obj) {
Class cl = obj.getClass();
System.out.println("\nName\t:" + cl.getName());
System.out.println("Name\t:" + cl.getSimpleName());
System.out.println("Super Class\t:" + cl.getSuperclass());
System.out.println("Package \t:" + cl.getPackage());
Class intrs[] = cl.getInterfaces();
for (int i = 0; i < intrs.length; i++) {
Class in = intrs[i];
System.out.println(in);
}
}
}
interface Inter1 {}
interface Inter2 {}
class Person {}
class Student extends Person implements Inter1, Inter2 {
```

JAVA TRAINING CENTER

```
int sid;
String name;
long phone;
public Student(int sid, String name, long phone) {
    this.sid = sid;
    this.name = name;
    this.phone = phone;
}
}
class User {}
class Employee extends User {
    int eid;
    String name;
    long phone;
    public Employee(int eid, String name, long phone) {
        this.eid = eid;
        this.name = name;
        this.phone = phone;
    }
    public String toString() {
        return "Info Eid :" + eid + ", Name :" + name + ", Phone :" + phone;
    }
    public int hashCode() {
        return (int) (phone << name.length());
    }
}
```



Jtc 2: Example using equals Method

```
package edu.SP.obj.test;
/*
 * @Author   : Som Prakash Rai
 * @Join     : Java Training Center
 * @visit    : www.jtcindia.org
 * @Call     : +91-9990399111
 */
public class Jtc2 {
    public static void main(String[] args) {
        String st1 = "JTC";
        String st2 = "JTC";
        String st3 = new String("JTC");
        System.out.println(st1 + "\t" + st2 + "\t" + st3);
    }
}
```


JAVA TRAINING CENTER

```
System.out.println(st1 == st2);
System.out.println(st1 == st3);
System.out.println("-----");
System.out.println(st1.equals(st2));
System.out.println(st1.equals(st3));
System.out.println("-- Student ---");
Student stu1 = new Student(99, "SomPrakash");
Student stu2 = new Student(99, "SomPrakash");
System.out.println("==\t:" + (stu1 == stu2));
System.out.println("eq()\t:" + stu1.equals(stu2));
System.out.println("-- Employee ---");
Employee emp1 = new Employee(99, "SomPrakash");
Employee emp2 = new Employee(99, "SomPrakash");
Employee emp3 = new Employee(98, "SomPrakash");
System.out.println("==\t:" + (emp1 == emp2));
System.out.println("eq()\t:" + emp1.equals(emp2));
System.out.println("eq()\t:" + emp1.equals(emp3));
}
}
class Student {
int sid;
String name;
public Student(int sid, String name) {
this.sid = sid;
this.name = name;
}
}
class Employee {
int eid;
String name;
public Employee(int eid, String name) {
this.eid = eid;
this.name = name;
}
public boolean equals(Object obj) {
Employee emp = (Employee) obj;
return this.eid == emp.eid && this.name.equals(emp.name);
}
}
```

JAVA TRAINING CENTER

Jtc 3: Example using cloning

```
/*
 * @Author : Som Prakash Rai
 * @Join : Java Training Center
 * @Visit : www.jtcindia.org
 * @Call : +91-9990399111
 */
public class Jtc3 {
    public static void main(String[] args) throws CloneNotSupportedException {
        Employee emp1 = new Employee(88, "Manish");
        emp1.showClone();
        System.out.println("\n-----");
        LoginInfo log = new LoginInfo(101, "somsree", "JTCindia");
        Address ad = new Address("c-29", "Noida", 201301);
        Student st = new Student(999, "SomPrakash", 6526668, ad, log);
        System.out.println(st);
        Student stud = (Student) st.clone();
        System.out.println("\n*** After Cloning the Object ***");
        System.out.println(st == stud);
        System.out.println(st.studAdd == stud.studAdd);
        System.out.println(st.login == stud.login);
        System.out.println(st);
        System.out.println(stud);
        System.out.println("\n=== MODIFYING THE DATA ===");
        stud.sid = 90909;
        stud.name = "Manish";
        stud.phone = 745896;
        stud.studAdd.street = "DELHI";
        stud.login.uname = "JTCuser";
        System.out.println(st);
        System.out.println(stud);
    }
}
class Student implements Cloneable
{
    int sid;
    String name;
    long phone;
    Address studAdd;
    LoginInfo login;
    public Student(int sid, String name, long phone, Address studAdd, LoginInfo login) {
```


JAVA TRAINING CENTER

```
this.sid = sid;
this.name = name;
this.phone = phone;
this.studAdd = studAdd;
this.login = login;
}
public String toString() {
return "\nStud Info\t:" + sid + "\t" + name + "\t" + phone+ "\nAdd Info\t:" + studAdd +
"\nLogin Info\t:" + login;
}
public Object clone() throws CloneNotSupportedException {
Object obj=null;
if(this instanceof Cloneable){
Address ad=new Address(this.studAdd.aid,this.studAdd.street,this.studAdd.pin);
LoginInfo info=new LoginInfo(this.login.loginId, this.login.uname, this.login.pwd);
obj=new Student(this.sid,this.name,this.phone,ad,info);
}else{
throw new CloneNotSupportedException(this.getClass().getName());
}
return obj;
}
}
class Employee implements Cloneable {
int eid;
String name;
public Employee(int eid, String name) {
this.eid = eid;
this.name = name;
System.out.println("-- Employee(int,String) --");
}
public String toString() {
return eid + "\t" + name;
}
void showClone() throws CloneNotSupportedException {
Employee ep = (Employee) clone();
System.out.println("this\t\t:" + this);
System.out.println("Cloned Obj\t:" + ep);
System.out.println(this == ep);
}
}

class Address {
```


JAVA TRAINING CENTER

```
String aid;
String street;
int pin;
public Address(String aid, String street, int pin) {
    super();
    this.aid = aid;
    this.street = street;
    this.pin = pin;
}
public String toString() {
    return aid + "\t" + street + "\t" + pin;
}
}
class LoginInfo {
    int loginId;
    String uname;
    String pwd;
    public LoginInfo(int loginId, String uname, String pwd) {
        this.loginId = loginId;
        this.uname = uname;
        this.pwd = pwd;
    }
    public String toString() {
        return loginId + "\t" + uname + "\t" + pwd;
    }
}
```



Jtc 4: Example for GC

```
package com.JTC.gc.test;
import java.sql.Connection;
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc4 {
    public static void main(String[] args) {
        System.out.println("-- IN Main --");
        new Student(99);
        Student st = new Student(88);
        st.finalize();
        System.out.println("Value of sid\t:" + st.sid);
    }
}
```

JAVA TRAINING CENTER

```
st = null;
Student st1 = new Student(77);
st1 = new Student(66);
Student st2 = new Student(55);
Student st3 = new Student(44);
st2 = st3;
System.gc();
show();
for (int i = 0; i < 5; i++) {
    System.out.println("I value\t:" + i);
}
Student st99 = new Student(33);
System.gc();
System.out.println("-- Main Completed --");
}
static void show() {
    Student stud1 = new Student(101);
    Student stud2 = new Student(202);
    // Statements
}
}
final class Student {
    int sid;
    private Connection con = null;
    Student(int sid) {
        this.sid = sid;
        // Code to Connect With DB
        System.out.println("-- Connected with Resource --\t:" + sid);
    }
    void addInfo() {
        // Using the con to intract with DB
    }
    void deleteInfo() {
        // Using the con to intract with DB
    }
    public void finalize() {
        // Code to close the DB Connection
        System.out.println("*** Resource is RELEASED **\t:" + sid);
    }
}
```

JAVA TRAINING CENTER

Jtc 5: Example For Immutable Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc5 {
    public static void main(String[] args) {
        Address add = new Address(101, " c-29 Sector-2 noida ", "Noida", 201301);
        Student stud = new Student(99, "SomPrakash", 6526668, add);
        System.out.println(stud);
        System.out.println("-- Modifying the add ref in Main --");
        // stud.studAdd.aid = 1234;
        add.aid = 14523;
        add.street = "Sector 2 noida";
        System.out.println(stud);
        System.out.println(stud.getSid());
        Address ref = stud.getStudAddress();
        ref.aid = 11111;
        System.out.println(stud);
    }
    final class Student {
        private final int sid;
        private final String name;
        private final long phone;
        private final Address studAdd;
        public Student(int sid, String name, long phone, Address studAdd) {
            this.sid = sid;
            this.name = name;
            this.phone = phone;
            this.studAdd = new Address(studAdd.aid, studAdd.street, studAdd.city, studAdd.pin);
        }
        public String toString() {
            return "Stud Info\t:" + sid + "\t" + name + "\t" + phone + "\nAdd Info\t:" + studAdd;
        }
        public int getSid() {
            return this.sid;
        }

        public Address getStudAddress(){
```

JAVA TRAINING CENTER

```
return (Address)studAdd.clone();
}
}
class Address{
int aid;
String street;
String city;
int pin;
public Address(int aid, String street, String city, int pin) {
this.aid = aid;
this.street = street;
this.city = city;
this.pin = pin;
}
public Object clone() {
return new Address(this.aid, this.street, this.city, this.pin);
}
public String toString() {
return aid + "\t" + street + "\t" + city + "\t" + pin;
}
}
```

Jtc 6: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc6 {
public static void main(String[] args) {
String str1 = "JTC";
String str2 = "JTC";
String str3 = "JTC";
System.out.println(str1 + "\t" + str2 + "\t" + str3);
System.out.println(str1 == str2);
System.out.println(str1 == str3);
System.out.println("-----");
String ref1 = new String("JTC");
String ref2 = new String("JTC");
System.out.println(ref1 + "\t" + ref2);
System.out.println(ref1 == ref2);
}
```

JAVA TRAINING CENTER

```
System.out.println(str1 == ref1);
System.out.println(str1 == ref2);
String ref3 = new String("SP");
String ref4 = new String("SP");
System.out.println(ref3 + "\\t" + ref4);
System.out.println(ref3 == ref4);
}
}
```

Jtc 7: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc7 {
    public static void main(String[] args) {
        String st1 = new String("JTC");
        String st2 = st1.intern();
        System.out.println(st1 == st2);
        String st3 = "JTC";
        System.out.println(st3 == st2);
        String st4 = "OK".intern();
        String st5 = "OK";
        System.out.println(st4 + "\\t" + st5);
        System.out.println(st4 == st5);
    }
}
```

Jtc 8: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc8 {
    public static void main(String[] args) {
        String st1 = "JTC";
        String st2 = "INDIA";
        String st3 = st1 + st2;
        String st4 = st1 + "INDIA";
        String st5 = "JTC" + st2;
```


JAVA TRAINING CENTER

```
System.out.println(st3+"\t"+st4+"\t"+st5);
System.out.println(st3==st4);
System.out.println(st3==st5);
System.out.println(st4==st5);
String st6 = "JTC" + "INDIA";
final String st7 = "JTC";
final String st8 = "INDIA";
String st9 = st7 + st8;
System.out.println(st6+"\t"+st9);
System.out.println(st6==st9);
String st10="JTCINDIA";
System.out.println(st6==st10);
}
}
```

Jtc 9: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc9 {
    public static void main(String[] args) {
        String st1 = "JTC";
        String st2 = "JTC";
        String st3 = new String("JTC");
        String st4 = "JTC";
        System.out.println(st1 + "\t" + st2 + "\t" + st3 + "\t" + st4);
        System.out.println(st1 == st2);
        System.out.println(st1 == st3);
        System.out.println(st1.equals(st3));
        System.out.println(st1.equals(st4));
        System.out.println(st1.equalsIgnoreCase(st4));
        System.out.println("-----");
        int ab = 94;
        int bc = 76;
        int res = ab - bc;
        System.out.println(res);
        System.out.println("ABC".compareTo("ABC"));
        System.out.println("AEC".compareTo("ABC"));
        System.out.println("ABH".compareTo("ADC"));
```

JAVA TRAINING CENTER

```
System.out.println("ABC".compareTo("ABCDEFGH"));
System.out.println("ABC".compareTo("ABMDEFGH"));
System.out.println("ABC".compareTo("Abc"));
System.out.println("ABC".compareToIgnoreCase("Abc"));
System.out.println("ABC".compareToIgnoreCase("Abg"));
}
}
```

Jtc 10: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc10 {
    public static void main(String[] args) {
        int ab = 10;
        // String st1=ab;
        // String st2=(String)ab;
        String st3 = String.valueOf(ab);
        System.out.println(st3);
        boolean b1 = true;
        String st4 = String.valueOf(b1);
        System.out.println(st4);
        long val = 1234L;
        String st5 = String.valueOf(val);
        System.out.println(st5);
        Employee emp1 = null;
        Employee emp2 = new Employee();
        String st6 = String.valueOf(emp1);
        String st7 = String.valueOf(emp2);
        Person p = new Person();
        String st8 = String.valueOf(p);
        System.out.println(st6);
        System.out.println(st7);
        System.out.println(st8);
    }
}

class Employee {}
class Person {
    public String toString() {
        return "Person Obj";
    }
}
```

JAVA TRAINING CENTER

```
}  
}
```

Jtc 11: Example using String Class

```
/*  
 * @Author : Som Prakash Rai  
 * @Join: Java Training Center  
 * @Visit : www.jtcindia.org  
 */  
public class Jtc11 {  
    public static void main(String[] args) {  
        String str = "Hi This is JTC. Full name Java Training Center. We are providing Best  
        training for Java with Best SylJtcus. Jtc is no.1 in Training & placement,Thanks";  
        System.out.println(str);  
        System.out.println(str.startsWith("Hi"));  
        System.out.println(str.startsWith("Welcome"));  
        System.out.println(str.startsWith("Full"));  
        System.out.println(str.startsWith("Full", 16));  
        System.out.println(str.endsWith("placement"));  
        System.out.println(str.endsWith("Thanks"));  
        System.out.println("-----");  
        String st1 = str.replace('J', 'Y');  
        System.out.println(st1);  
        String st2 = str.replaceAll("Java", "XYZ");  
        System.out.println(st2);  
        String st3 = str.replaceFirst("Java", "XYZ");  
        System.out.println(st3);  
        System.out.println(str);  
        System.out.println("-----");  
        String st4 = str.toLowerCase();  
        String st5 = str.toUpperCase();  
        System.out.println(st4);  
        System.out.println(st5);  
    }  
}
```

Jtc 12: Example using String Class

```
/*  
 * @Author : Som Prakash Rai  
 * @Join: Java Training Center  
 * @Visit : www.jtcindia.org  
 */  
public class Jtc12 {
```

JAVA TRAINING CENTER

```
public static void main(String[] args) {
String str = " Hi This is JTC. Full name Java Training Center. We are providing Best
training for Java with Best Syllabus. Jtc is no.1 in Training & placement,Thanks ";
System.out.println(str.indexOf('X'));
System.out.println(str.indexOf('J'));
System.out.println(str.indexOf('J', 11));
System.out.println(str.indexOf('J', 12));
System.out.println(str.indexOf('J', 27));
System.out.println();
System.out.println(str.indexOf("XYZ"));
System.out.println(str.indexOf("Java"));
System.out.println(str.indexOf("Java", 26));
System.out.println(str.indexOf("Java", 27));
System.out.println("-----");
System.out.println(str.lastIndexOf('J'));
System.out.println(str.lastIndexOf('J', 120));
System.out.println(str.lastIndexOf("Java"));
System.out.println(str.lastIndexOf("Java", 120));
System.out.println(str.lastIndexOf("Java", 15));
}
}
```

Jtc 13: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc13 {
public static void main(String[] args) {
String st = " Hello JTC Students ";
System.out.println(st + ":\t:" + st.length());
String st1 = st.trim();
System.out.println(st1 + ":\t:" + st1.length());
System.out.println();
String str1 = "Hello JTC Students,";
String str2 = "Welcome to All";
String str = str1.concat(str2);
System.out.println(str);
System.out.println();
String st11 = str.substring(7);
System.out.println(st11);
}
```


JAVA TRAINING CENTER

```
String st12 = str.substring(7, 17); // 17 is lastIndex+1 (16+1)
System.out.println(st12);
// str.substring(7, 2);//Exception
System.out.println(st1.charAt(0));
System.out.println(st1.charAt(14));
System.out.println(st1.charAt(189));// Exception
}
}
```

Jtc 14: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc14 {
    public static void main(String[] args) {
        String st = "JTCINDIA";
        char arr[] = st.toCharArray();
        for (int i = 0; i < arr.length; i++) {
            char c = arr[i];
            System.out.println(i + "\t" + c);
        }
        System.out.println("-----");
        byte bArr[] = st.getBytes();
        for (int i = 0; i < bArr.length; i++) {
            byte b = bArr[i];
            System.out.println(i + "\t" + b + "\t" + (char) b);
        }
        System.out.println("-----");
        char chArr[] = new char[10];
        st.getChars(2, 6, chArr, 0);
        for (int i = 0; i < chArr.length; i++) {
            char c = chArr[i];
            System.out.println(i + "\t" + c);
        }
        System.out.println("\n-----");
        char chArr1[] = new char[10];
        st.getChars(2, 6, chArr1, 4);
        for (int i = 0; i < chArr1.length; i++) {
            char c = chArr1[i];
            System.out.println(i + "\t" + c);
        }
    }
}
```


JAVA TRAINING CENTER

```
}  
}  
}
```

Jtc 15: Example using String Class

```
/*  
 * @Author : Som Prakash Rai  
 * @Join: Java Training Center  
 * @Visit : www.jtcindia.org  
 */  
public class Jtc15 {  
    public static void main(String[] args) {  
        char chArr[] = { 'J', 'T', 'C', 'N', 'O', 'T', 'D', 'A' };  
        String st1 = new String(chArr);  
        System.out.println(st1);  
        String st2 = new String(chArr, 2, 3); // 3 is number of character  
        System.out.println(st2);  
        System.out.println();  
        byte bArr[] = { 65, 89, 97, 78, 120 };  
        String st3 = new String(bArr);  
        System.out.println(st3);  
        String st4 = new String(bArr, 1, 3); // 3 is number of character  
        System.out.println(st4);  
    }  
}
```

Jtc 16: Example using String Class

```
/*  
 * @Author : Som Prakash Rai  
 * @Join: Java Training Center  
 * @Visit : www.jtcindia.org  
 */  
public class Jtc16 {  
    public static void main(String[] args) {  
        String str = "Hi this is Java Training Center.No 1 in training and placement.Providing  
training on java and java related concepts";  
        System.out.println(str);  
        String res[] = str.split("java");  
        for (int i = 0; i < res.length; i++) {  
            String st = res[i];  
            System.out.println(i + "\\t" + st);  
        }  
    }  
}
```

JAVA TRAINING CENTER

```
System.out.println("-----");
res = str.split("java", 2);
for (int i = 0; i < res.length; i++) {
String st = res[i];
System.out.println(i + "\t" + st);
}
}
}
```

Jtc 17: Example using String Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc17 {
public static void main(String[] args) {
String st = "BBCmni45";
String pattern = "^[A-H][A-Za-z]*"; // RegularExpression pattern
System.out.println(st.matches(pattern));
String st1 = "ABCmni987";
String pattern1 = "^[A-H][A-Za-z0-9]*"; // RegularExpression pattern
System.out.println(st1.matches(pattern1));
System.out.println("-----");
String st11 = "JTC is No 1 in Noida";
String st12 = "welcome to JTCNoida";
String st13 = "welcome to JTCNoida";
System.out.println(st11.regionMatches(12, st12, 14, 5));
System.out.println(st11.regionMatches(12, st12, 14, 2));
System.out.println(st11.regionMatches(12, st13, 14, 2));
System.out.println(st11.regionMatches(false, 12, st13, 14, 2));
System.out.println(st11.regionMatches(true, 12, st13, 14, 2));
}
}
```

Jtc 18: Example using String Class (From Java 5)

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc18 {
```

JAVA TRAINING CENTER

```
public static void main(String[] args) {  
    int ab = 10;  
    int bc = 23;  
    String str = String.format("Sum of %d and %d is %d", ab, bc, (ab + bc));  
    System.out.println(str);  
    int val = 97;  
    String st = String.format("%d %h %o %c", val, val, val, val);  
    System.out.println(st);  
    System.out.printf("%d %h %o %c", val, val, val, val);  
}  
}
```

Jtc 19: Example using String Class

```
/*  
 * @Author : Som Prakash Rai  
 * @Join: Java Training Center  
 * @Visit : www.jtcindia.org  
 */  
  
public class Jtc19 {  
    public static void main(String[] args) {  
        String st1 = "JTC";  
        String st2 = "JTC";  
        System.out.println(st1 == st2);  
        System.out.println("Result is :" + st1 == st2);  
        System.out.println("Result is :" + (st1 == st2));  
    }  
}
```

Jtc 20: Example using StringBuffer Class

```
/*  
 * @Author : Som Prakash Rai  
 * @Join: Java Training Center  
 * @Visit : www.jtcindia.org  
 */  
  
public class Jtc20 {  
    public static void main(String[] args) {  
        StringBuffer sb = new StringBuffer();  
        System.out.println(sb.length());  
        System.out.println(sb.capacity());  
        sb.append(true);  
        sb.append(1234);  
        sb.append(985.251);  
    }  
}
```

JAVA TRAINING CENTER

```
System.out.println();
System.out.println(sb.length());
System.out.println(sb.capacity());
sb.append('A');
sb.append(new Student());
System.out.println();
System.out.println(sb.length());
System.out.println(sb.capacity());
System.out.println("-----");
StringBuffer sb1 = new StringBuffer(30);
System.out.println(sb1.length());
System.out.println(sb1.capacity());
System.out.println("-----");
StringBuffer sb2 = new StringBuffer("HELLO");
System.out.println(sb2.length());
System.out.println(sb2.capacity());
System.out.println("----");
StringBuffer sb3 = new StringBuffer();
System.out.println(sb3.length());
System.out.println(sb3.capacity());
sb3.append("qwertyuioplkjhgfdsazxcvbnm1234567mnbghjkiuytredfr");
System.out.println(sb3.length());
System.out.println(sb3.capacity());
}
}
class Student {}
```

Jtc 21: Example using StringBuffer Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc21 {
    public static void main(String[] args) {
        StringBuffer sb = new StringBuffer("JTC");
        char arr[] = { 'A', 'B', 'C', 'D' };
        sb.append(true);
        sb.append(123);
        sb.append(arr);
        System.out.println(sb);
    }
}
```

JAVA TRAINING CENTER

```
sb.reverse();
System.out.println(sb);
sb.deleteCharAt(4);
System.out.println(sb);
System.out.println(sb.length());
sb.setLength(20);
System.out.println(sb.length());
System.out.println(sb);
sb.append("SomPrakash");
System.out.println(sb);
System.out.println(sb.length());
System.out.println(sb.capacity());
sb.setLength(7);
System.out.println(sb);
System.out.println(sb.length());
System.out.println(sb.capacity());
sb.insert(4, "JAVATRAININGCENTER");
System.out.println(sb);
System.out.println("-----");
String str = "ABC";
StringBuffer sbo = new StringBuffer("ABC");
System.out.println(str.equals(sbo));
System.out.println(str.contentEquals(sbo));
System.out.println();
StringBuffer obj=new StringBuffer("OKJTC");
System.out.println(obj.length());
System.out.println(obj.capacity());
obj.trimToSize();
System.out.println(obj.length());
System.out.println(obj.capacity());
}
}
```

Jtc 22: Example using System Class

```
import java.io.*;
import java.util.*;
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
```


JAVA TRAINING CENTER

```
*/  
public class Jtc22 {  
    public static void main(String[] args) throws Exception {  
        System sys = null;  
        // sys = new System();  
        System.out.println("OUT MSG 1");  
        System.out.println("OUT MSG 2");  
        System.err.println("ERR MSG 1");  
        System.err.println("ERR MSG 2");  
        // System.out=null;  
        long ms = System.currentTimeMillis();  
        System.out.println(new Date(ms));  
        System.out.println(System.getenv("path")); // From Java 5  
        System.out.println("*****");  
        Map values = System.getenv();  
        Iterator it = values.entrySet().iterator();  
        while (it.hasNext()) {  
            Map.Entry ent = (Map.Entry) it.next();  
            System.out.println(ent.getKey() + "\t\t" + ent.getValue());  
        }  
        System.out.println("\n***** Properties Name *****\n");  
        System.setProperty("java.ins.name", "Java Training Center");  
        System.out.println(System.getProperty("os.name"));  
        System.setProperty("os.name", "UNIX");  
        System.out.println(System.getProperty("os.name"));  
        Properties p = System.getProperties();  
        Enumeration enu = p.propertyNames();  
        while (enu.hasMoreElements()) {  
            String nm = (String) enu.nextElement();  
            System.out.println(nm + "\t\t" + p.getProperty(nm));  
        }  
        System.out.println("*****");  
        System.setProperty("runtime.test", "true");  
        System.out.println(Boolean.getBoolean("true"));  
        System.out.println(Boolean.getBoolean("runtime.test"));  
        System.out.println("*****");  
        System.out.println("-----");  
        System.out.println("Message Before Changing");  
        System.err.println(System.out);  
        System.err.println(System.err);  
        System.err.println(System.out == System.err);  
        System.setOut(new PrintStream(new FileOutputStream("res.txt")));
```

JAVA TRAINING CENTER

```
System.out.println("Message After Changing 1");
System.out.println("Message After Changing 2");
System.err.println("ERR MSG After changing Out");
System.exit(0);
System.err.println("Error");
for (int i = 0; i < 10; i++) {
System.err.println("Value is \t:" + i);
}
}
}
```

Jtc 23: Example using Runtime Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 */
public class Jtc23 {
public static void main(String[] args) throws Exception {
Runtime rt = null;
// rt=new Runtime();
// rt.avaiJtcleProcessors();
rt = Runtime.getRuntime();
System.out.println(rt);
System.out.println(Runtime.getRuntime());
System.out.println(Runtime.getRuntime());
System.out.println(Runtime.getRuntime());
System.out.println(rt.totalMemory());
System.out.println(rt.freeMemory());
System.out.println(rt.maxMemory());
System.out.println(rt.avaiJtcleProcessors());
// No_Of_Processors env value
Process p1 = rt.exec("notepad");
Process p2 = rt.exec("calc");
Process p3 = rt.exec("mspaint");
System.out.println(System.getenv("path"));
Process p4 = rt.exec("C:\\Program Files\\Windows Media Player\\wmplayer");
// rt.exec("res.txt");
System.out.println("Press Enter To Close Calculator");
System.in.read();
p1.destroy();
p2.destroy();
```

JAVA TRAINING CENTER

```
p3.destroy();
p4.destroy();
}
}
/*
java -Xms256m -Xmx1024m RuntimeTest
*/
```

Jtc 25: Example using Wrapper Class

```
/*
 * @Author : Som Prakash Rai
 * @Join: Java Training Center
 * @Visit : www.jtcindia.org
 * */
public final class Jtc25 {
    public static void main(String[] args) {
        /* Primitive to Wrapper */
        Integer in1 = new Integer(987);
        Boolean b1 = new Boolean(true);
        Character ch1 = new Character('A');
        Byte by11 = new Byte((byte) 12);
        Integer in2 = Integer.valueOf(123);
        Character ch2 = Character.valueOf('A');
        Boolean b2 = Boolean.valueOf(false);

        /* Wrapper to Primitive */
        byte byVal = in1.byteValue();
        short shVal = in1.shortValue();
        int iVal = in1.intValue();
        long lnVal = in1.longValue();
        float fVal = in1.floatValue();
        double dVal = in1.doubleValue();

        char chVal = ch1.charValue();
        boolean bVal = b1.booleanValue();

        /* Primitive To String */
        int val = 12345;
        String st1 = val + "";
        String st2 = "" + val;
        String st3 = String.valueOf(val);
```

JAVA TRAINING CENTER

```
String st4 = Integer.toString(val);
```

```
/* String to Primitive */
```

```
int ab = Integer.parseInt("765");
```

```
byte by1 = Byte.parseByte("123");
```

```
// int bc=Integer.parseInt("123.90");
```

```
// int cd=Integer.parseInt("A");
```

```
// byte by2=Byte.parseByte("128");
```

```
boolean b3 = Boolean.parseBoolean("OK");// From Java 5
```

```
/* String to Wrapper */
```

```
Integer in3 = new Integer("1234");
```

```
// Integer in4 = new Integer("JTC");
```

```
Boolean b4 = new Boolean("Som");
```

```
Boolean b5 = new Boolean("TrUE");
```

```
/* Wrapper to String */
```

```
String str1 = in1.toString();
```

```
String str2 = ch1.toString();
```

```
String str3 = b1.toString();
```

```
/* OTHER METHODS */
```

```
String binStr = Integer.toBinaryString(6567533);
```

```
System.out.println(binStr);
```

```
String hexStr = Integer.toHexString(6567533);
```

```
System.out.println(hexStr);
```

```
String octStr = Integer.toOctalString(6567533);
```

```
System.out.println(octStr);
```

```
Integer in11 = new Integer(123);
```

```
Integer in12 = new Integer(123);
```

```
System.out.println(in11.compareTo(in12));
```

```
System.out.println(in11.equals(in12));
```

```
System.out.println(Character.isAlphabetic('A'));
```

```
System.out.println(Character.isAlphabetic('9'));
```

```
System.out.println(Character.isPigit('4'));
```

```
System.out.println(Character.isPigit('j'));
```

```
System.out.println(Character.isMirrored('M'));
```

```
System.out.println(Character.isMirrored('('));
```

```
System.out.println(Character.isMirrored('{'));
```

```
}
```

```
}
```


JAVA TRAINING CENTER

java.lang.Object

```
public class java.lang.Object{
public java.lang.Object();
public final native java.lang.Class getClass();
public native int hashCode();
public boolean equals(java.lang.Object);
protected native java.lang.Object clone() throws java.lang.CloneNotSupportedException;
public java.lang.String toString();
public final native void notify();
public final native void notifyAll();
public final native void wait(long) throws java.lang.InterruptedException;
public final void wait(long, int) throws java.lang.InterruptedException;
public final void wait() throws java.lang.InterruptedException;
protected void finalize() throws java.lang.Throwable;
}
```

java.lang.String

```
public final class java.lang.String extends java.lang.Object implements java.io.
Serializable, java.lang.Comparable, java.lang.CharSequence{
public java.lang.String();
public java.lang.String(java.lang.String);
public java.lang.String(char[]);
public java.lang.String(byte[], int, int, int);
public java.lang.String(java.lang.StringBuffer);
public java.lang.String(java.lang.StringBuilder);
public int length();
public boolean isEmpty();
public char charAt(int);
void getChars(char[], int);
public void getChars(int, int, char[], int);
public void getBytes(int, int, byte[], int);
public boolean equals(java.lang.Object);
public boolean contentEquals(java.lang.StringBuffer);
public boolean contentEquals(java.lang.CharSequence);
public boolean equalsIgnoreCase(java.lang.String);
}
```


JAVA TRAINING CENTER

```
public int compareTo(java.lang.String);
public int compareToIgnoreCase(java.lang.String);
public boolean regionMatches(int, java.lang.String, int, int);
public boolean regionMatches(boolean, int, java.lang.String, int, int);
public boolean startsWith(java.lang.String, int);
public boolean startsWith(java.lang.String);
public boolean endsWith(java.lang.String);
public int hashCode();
public int indexOf(int);
public int indexOf(int, int);
public int lastIndexOf(int);
public int lastIndexOf(int, int);
public int indexOf(java.lang.String);
public int indexOf(java.lang.String, int);
public int lastIndexOf(java.lang.String);
public int lastIndexOf(java.lang.String, int);
public java.lang.String substring(int);
public java.lang.String substring(int, int);
public java.lang.CharSequence subSequence(int, int);
public java.lang.String concat(java.lang.String);
public java.lang.String replace(char, char);
public boolean matches(java.lang.String);
public java.lang.String replaceFirst(java.lang.String, java.lang.String);
public java.lang.String replaceAll(java.lang.String, java.lang.String);
public java.lang.String[] split(java.lang.String, int);
public java.lang.String[] split(java.lang.String);
public java.lang.String toLowerCase(java.util.Locale);
public java.lang.String toLowerCase();
public java.lang.String toUpperCase(java.util.Locale);
public java.lang.String toUpperCase();
public java.lang.String trim();
public java.lang.String toString();
public char[] toCharArray();
public static java.lang.String format(java.lang.String, java.lang.Object[]);
public static java.lang.String valueOf(java.lang.Object);
public static java.lang.String valueOf(double); //Overloaded Method
public native java.lang.String intern();
public int compareTo(java.lang.Object);
}
```

JAVA TRAINING CENTER

java.lang.StringBuffer

```
public final class java.lang.StringBuffer extends java.lang.AbstractStringBuilder
implements java.io.Serializable, java.lang.CharSequence{
public java.lang.StringBuffer();
public java.lang.StringBuffer(int);
public java.lang.StringBuffer(java.lang.String);
public java.lang.StringBuffer(java.lang.CharSequence);
public synchronized int length();
public synchronized int capacity();
public synchronized void ensureCapacity(int);
public synchronized void trimToSize();
public synchronized void setLength(int);
public synchronized char charAt(int);
public synchronized void getChars(int, int, char[], int);
public synchronized void setCharAt(int, char);
public synchronized java.lang.StringBuffer append(java.lang.Object);
// Overloaded Method

public synchronized java.lang.StringBuffer delete(int, int);
public synchronized java.lang.StringBuffer deleteCharAt(int);
public synchronized java.lang.StringBuffer replace(int, int, java.lang.String);
public synchronized java.lang.String substring(int);
public synchronized java.lang.CharSequence subSequence(int, int);
public synchronized java.lang.String substring(int, int);
public java.lang.StringBuffer insert(int, boolean);
// Overloaded Method

public int indexOf(java.lang.String);
public synchronized int indexOf(java.lang.String, int);
public int lastIndexOf(java.lang.String);
public synchronized int lastIndexOf(java.lang.String, int);
public synchronized java.lang.StringBuffer reverse();
public synchronized java.lang.String toString();
}
```

java.lang.Number

```
public abstract class java.lang.Number extends java.lang.Object implements
java.io.Serializable{
public java.lang.Number();
```

JAVA TRAINING CENTER

```
public abstract int intValue();
public abstract long longValue();
public abstract float floatValue();
public abstract double doubleValue();
public byte byteValue();
public short shortValue();
}
```

java.lang.Boolean

```
public final class java.lang.Boolean extends java.lang.Object implements
java.io.Serializable, java.lang.Comparable{
    public static final java.lang.Boolean TRUE;
    public static final java.lang.Boolean FALSE;
    public static final java.lang.Class TYPE; //From Java 5
    public java.lang.Boolean(boolean);
    public java.lang.Boolean(java.lang.String);
    public static boolean parseBoolean(java.lang.String); //From Java 5
    public boolean booleanValue();
    public static java.lang.Boolean valueOf(boolean);
    public static java.lang.Boolean valueOf(java.lang.String);
    public static java.lang.String toString(boolean);
    public java.lang.String toString();
    public int hashCode();
    public boolean equals(java.lang.Object);
    public static boolean getBoolean(java.lang.String);
    public int compareTo(java.lang.Boolean);
    public int compareTo(java.lang.Object);
}
```

java.lang.Character

```
public final class java.lang.Character extends java.lang.Object implements java.
io.Serializable, java.lang.Comparable{
    public static final int SIZE;
    public java.lang.Character(char);
    public static java.lang.Character valueOf(char);
    public char charValue();
    public int hashCode();
    public boolean equals(java.lang.Object);
    public java.lang.String toString();
    public static java.lang.String toString(char);
}
```

JAVA TRAINING CENTER

```
public static boolean isLowerCase(char);
public static boolean isUpperCase(char);
public static boolean isTitleCase(char);
public static boolean isPigit(char);
public static boolean isLetter(char);
public static boolean isLetterOrDigit(char);
public static boolean isJavaLetter(char);
public static boolean isJavaLetterOrDigit(char);
public static boolean isJavaIdentifierStart(char);
public static boolean isJavaIdentifierPart(char);
public static char toLowerCase(char);
public static char toUpperCase(char);
public static int getNumericValue(char);
public static boolean isSpaceChar(char);
public static boolean isWhitespace(char);
public static boolean isISOControl(char);
public static boolean isMirrored(char);
public int compareTo(java.lang.Character);
public int compareTo(java.lang.Object);
}
```

java.lang.Integer

```
public final class java.lang.Integer extends java.lang.Number implements java.la
ng.Comparable{
public static final int MIN_VALUE;
public static final int MAX_VALUE;
public static final java.lang.Class TYPE;
public static final int SIZE;
public static java.lang.String toHexString(int);
public static java.lang.String toOctalString(int);
public static java.lang.String toBinaryString(int);
public static java.lang.String toString(int);
public static int parseInt(java.lang.String, int)
public static int parseInt(java.lang.String)
public static java.lang.Integer valueOf(java.lang.String)
public static java.lang.Integer valueOf(int);
public java.lang.Integer(int);
public java.lang.Integer(java.lang.String)
public byte byteValue();
public short shortValue();
}
```


JAVA TRAINING CENTER

```
public int intValue();
public long longValue();
public float floatValue();
public double doubleValue();
public java.lang.String toString();
public int hashCode();
public boolean equals(java.lang.Object);
public static java.lang.Integer getInteger(java.lang.String);
public int compareTo(java.lang.Integer);
public int compareTo(java.lang.Object);
}
```

java.lang.Long


```
public final class java.lang.Long extends java.lang.Number implements java.lang.
Comparable{
public static final long MIN_VALUE;
public static final long MAX_VALUE;
public static final java.lang.Class TYPE;
public static final int SIZE;
public static java.lang.String toString(long, int);
public static java.lang.String toHexString(long);
public static java.lang.String toOctalString(long);
public static java.lang.String toBinaryString(long);
public static java.lang.String toString(long);
public static long parseLong(java.lang.String, int)
public static long parseLong(java.lang.String)
public static java.lang.Long valueOf(java.lang.String, int)
public static java.lang.Long valueOf(java.lang.String)
public static java.lang.Long valueOf(long);
public static java.lang.Long decode(java.lang.String)
public java.lang.Long(long);
public java.lang.Long(java.lang.String)
public byte byteValue();
public short shortValue();
public int intValue();
public long longValue();
public float floatValue();
public double doubleValue();
public java.lang.String toString();
public int hashCode();
}
```


JAVA TRAINING CENTER

```
public boolean equals(java.lang.Object);  
public static java.lang.Long getLong(java.lang.String);  
public int compareTo(java.lang.Long);  
}
```

java.lang.Byte

```
public final class java.lang.Byte extends java.lang.Number implements java.lang.  
Comparable{  
    public static final byte MIN_VALUE;  
    public static final byte MAX_VALUE;  
    public static final java.lang.Class TYPE;  
    public static final int SIZE;  
    public static java.lang.String toString(byte);  
    public static java.lang.Byte valueOf(byte);  
    public static byte parseByte(java.lang.String)  
    public static byte parseByte(java.lang.String, int)  
    public static java.lang.Byte valueOf(java.lang.String, int)  
    public static java.lang.Byte valueOf(java.lang.String  
    public java.lang.Byte(byte);  
    public java.lang.Byte(java.lang.String)  
    public byte byteValue();  
    public short shortValue();  
    public int intValue();  
    public long longValue();  
    public float floatValue();  
    public double doubleValue();  
    public java.lang.String toString();  
    public int hashCode();  
    public boolean equals(java.lang.Object);  
    public int compareTo(java.lang.Byte);  
    public int compareTo(java.lang.Object);  
}
```



java.lang.Short

```
public final class java.lang.Short extends java.lang.Number implements  
java.lang.Comparable{  
    public static final short MIN_VALUE;  
    public static final short MAX_VALUE;
```

JAVA TRAINING CENTER

```
public static final java.lang.Class TYPE;
public static final int SIZE;
public static java.lang.String toString(short);
public static short parseShort(java.lang.String)
public static short parseShort(java.lang.String, int)
public static java.lang.Short valueOf(java.lang.String, int)
public static java.lang.Short valueOf(java.lang.String)
public static java.lang.Short valueOf(short);
public static java.lang.Short decode(java.lang.String)
public java.lang.Short(short);
public java.lang.Short(java.lang.String)
public byte byteValue();
public short shortValue();
public int intValue();
public long longValue();
public float floatValue();
public double doubleValue();
public java.lang.String toString();
public int hashCode();
public boolean equals(java.lang.Object);
public int compareTo(java.lang.Short);
public int compareTo(java.lang.Object);
}
```

java.lang.Float

```
public final class java.lang.Float extends java.lang.Number implements
java.lang.Comparable{
public static final float POSITIVE_INFINITY;
public static final float NEGATIVE_INFINITY;
public static final float NaN;
public static final float MAX_VALUE;
public static final float MIN_VALUE;
public static final int SIZE;
public static final java.lang.Class TYPE;
public static java.lang.String toString(float);
public static java.lang.String toHexString(float);
public static java.lang.Float valueOf(java.lang.String)
public static java.lang.Float valueOf(float);
public static float parseFloat(java.lang.String)
public static boolean isNaN(float);
public static boolean isInfinite(float);
}
```

JAVA TRAINING CENTER

```
public java.lang.Float(float);
public java.lang.Float(double);
public java.lang.Float(java.lang.String)
public boolean isNaN();
public boolean isInfinite();
public java.lang.String toString();
public byte byteValue();
public short shortValue();
public int intValue();
public long longValue();
public float floatValue();
public double doubleValue();
public int hashCode();
public boolean equals(java.lang.Object);
public int compareTo(java.lang.Float);
public int compareTo(java.lang.Object);
}
```

java.lang.Double

```
public final class java.lang.Double extends java.lang.Number implements
java.lang.Comparable{
public static final double POSITIVE_INFINITY;
public static final double NEGATIVE_INFINITY;
public static final double NaN;
public static final double MAX_VALUE;
public static final double MIN_VALUE;
public static final int SIZE;
public static final java.lang.Class TYPE;
public static java.lang.String toString(double);
public static java.lang.String toHexString(double);
public static java.lang.Double valueOf(java.lang.String)
public static java.lang.Double valueOf(double);
public static double parseDouble(java.lang.String)
public static boolean isNaN(double);
public static boolean isInfinite(double);
public java.lang.Double(double);
public java.lang.Double(java.lang.String)
public boolean isNaN();
public boolean isInfinite();
public java.lang.String toString();
public byte byteValue();
}
```

JAVA TRAINING CENTER

```
public short shortValue();
public int intValue();
public long longValue();
public float floatValue();
public double doubleValue();
public int hashCode();
public boolean equals(java.lang.Object);
public int compareTo(java.lang.Double);
public int compareTo(java.lang.Object);
}
```

java.lang.System

```
public final class java.lang.System extends java.lang.Object{
public static final java.io.InputStream in;
public static final java.io.PrintStream out;
public static final java.io.PrintStream err;
public static void setIn(java.io.InputStream);
public static void setOut(java.io.PrintStream);
public static void setErr(java.io.PrintStream);
public static java.io.Console console();
public static void setSecurityManager(java.lang.SecurityManager);
public static java.lang.SecurityManager getSecurityManager();
public static native long currentTimeMillis();
public static native long nanoTime();
public static native void arraycopy(java.lang.Object, int, java.lang.Object,
int, int);
public static java.util.Properties getProperties();
public static void setProperties(java.util.Properties);
public static java.lang.String getProperty(java.lang.String);
public static java.lang.String getProperty(java.lang.String, java.lang.String);
public static java.lang.String setProperty(java.lang.String, java.lang.String);
public static java.lang.String clearProperty(java.lang.String);
public static java.lang.String getenv(java.lang.String);
public static java.util.Map getenv();
public static void exit(int);
public static void gc();
public static void runFinalization();
public static void load(java.lang.String);
public static void loadLibrary(java.lang.String);
}
```


JAVA TRAINING CENTER

java.lang.Runtime

```
public class java.lang.Runtime extends java.lang.Object{
public static java.lang.Runtime getRuntime();
public void exit(int);
public void addShutdownHook(java.lang.Thread);
public boolean removeShutdownHook(java.lang.Thread);
public void halt(int);
public java.lang.Process exec(java.lang.String)
public java.lang.Process exec(java.lang.String, java.lang.String
public native int availJtcleProcessors();
public native long freeMemory();
public native long totalMemory();
public native long maxMemory();
public native void gc();
public void runFinalization();
public void load(java.lang.String);
public void loadLibrary(java.lang.String);
}
```

java.lang.Math

```
public final class java.lang.Math extends java.lang.Object{
public static final double E;
public static final double PI;
public static double sin(double);
public static double cos(double);
public static double tan(double);
public static double asin(double);
public static double acos(double);
public static double atan(double);
public static double toRadians(double);
public static double toDegrees(double);
public static double exp(double);
public static double log(double);
public static double sqrt(double);
public static double cbrt(double);
public static double ceil(double);
public static double floor(double);
public static double pow(double, double);
public static long round(double);
public static double random();
public static int abs(int);
```


JAVA TRAINING CENTER

```
public static long abs(long);  
public static double abs(double);  
public static int max(int, int);  
public static long max(long, long);  
public static double max(double, double);  
public static int min(int, int);  
public static long min(long, long);  
public static double min(double, double);  
public static double sinh(double);  
public static double cosh(double);  
public static double tanh(double);  
}
```

