

Learning Objectives

By the end of this worksheet, you will:

- Analyse the average-case running time of an algorithm.

1. **Average-case analysis.** Consider the following algorithm that we studied a few weeks ago. The input is an array A of length n , containing a list of n integers.

```
1 def has_even(lst: List[int]) -> int:
2     n = len(lst)
3     for i in range(n):
4         if lst[i] % 2 == 0:
5             return i
6
7     return -1
```

We proved that the worst-case running time of this algorithm is $\Theta(n)$. In this problem we will analyse its *average-case* running time.

For this analysis, we will consider the sets of *binary* lists lst of length n , for each $n \in \mathbb{Z}^+$. That is, lst is a list of n integers, where each integer is either 0 or 1.

- (a) For each $n \in \mathbb{Z}^+$, let \mathcal{I}_n be the set of all binary lists of length n . Find an expression (in terms of n) for $|\mathcal{I}_n|$, the size of \mathcal{I}_n .

size of $\mathcal{I}_n = 2^n$

- (b) For each $n \in \mathbb{Z}^+$ and each $i \in \{0, 1, \dots, n-1\}$, let $S_{n,i}$ denote the *set* of all binary lists lst of length n where the first 0 occurs in position i . More precisely, every list lst in $S_{n,i}$ satisfies the following two properties:

- (i) $lst[i] = 0$.
- (ii) for all $j \in \mathbb{N}$, if $j < i$ then $lst[j] = 1$.

For each i , $0 \leq i \leq n$, find an expression for $|S_{n,i}|$.

spaces after i = n - i - 1

$$S = 2^{(n-i-1)}$$

- (c) Also, for each $n \in \mathbb{Z}^+$, let $S_{n,n}$ denote the set of binary lists of length n that do not contain a 0 at all. Find an expression for $|S_{n,n}|$.

1

- (d) Give a brief argument (informal proof) that for every $n \in \mathbb{Z}^+$, each binary list of length n is in exactly one set $S_{n,i}$ (for some $i \in \{0, 1, \dots, n\}$). That is, you're arguing that $S_{n,0}, S_{n,1}, \dots, S_{n,n}$ form a *partition* of \mathcal{I}_n .

In = lists with 0, all lists without 0

Lists with a 0 in it, the index of first 0 = i, $i \in \{0, 1, \dots, n-1\}$

List without a 0, $[0,0,0,\dots,0]$ length $n = S_{n,n}$

The sets don't overlap. Unique position of list in S .

- (e) Assume that we calculate the running time of `has_even` by counting just the costs of Lines 4 and 7. Find an exact expression for the average runtime of this algorithm for this input set \mathcal{I}_n , in terms of n .

You should get a summation; do not simplify the summation in this part.

$$\frac{\sum_{i=0}^n (i+1)(S_n, i)}{(n+1)1 + \sum_{i=0}^{n-1} (i+1)(2^{n-i-1})} \cdot \frac{1}{2^n}$$

$$\begin{aligned} T(n) &= \max\{t(i): |i| = n\} \\ \text{let } i' &= i + 1 \\ n+1 + \sum_{i'=1}^n i' \cdot 2^{n-i'} \\ &= 2^{n+1} \end{aligned}$$

- (f) Show that the average running time expression that you calculated is in $\mathcal{O}(1)$. You may use the fact that for all $x \in \mathbb{R}$, if $|x| < 1$, then $\sum_{i=1}^{\infty} ix^i = \frac{x}{(1-x)^2}$.