EXERCISE 8 (Part 2) - Descending with Flap

AIM To investigate the effect of flaps on the Rate of Descent in the glide and with power to adjust a touch down point.

AIRMANSHIP LOOKOUT - VFE (WHITE ARC) - ENGINE CONSIDERATIONS **M.S.A**

EXERCISE **LOOK OUT**

(CARB HEAT ON)

GLIDE DESCENT

IDLE POWER **WINGS LEVEL**

ATTITUDE

TRIM - 65kt

Note Touchdown Point

Rate of Descent - 500 fpm

1. **10° FLAP**

IDLE POWER **WINGS LEVEL**

ATTITUDE

TRIM - 65kt

Note Touchdown Point

Rate of Descent - 700 fpm

2. **20° FLAP**

IDLE POWER **WINGS LEVEL**

ATTITUDE

TRIM - 65kt

Note Touchdown Point

Rate of Descent - 800 fpm

3. **30° FLAP**

IDLE POWER **WINGS LEVEL**

ATTITUDE

TRIM - 65kt

Note Touchdown Point

Rate of Descent - 900 fpm

ADJUST ATTITUDE TO MAINTAIN AIRSPEED, THEN TRIM - NOTE RATE OF DESCENT AND PICTURE

FLAPS UP IN STAGES - BACK TO STRAIGHT AND LEVEL

ENGINE WARM EVERY 500'

With a combination of power and flap a landing point can be chosen

4. **Increase RPM to 1500**
   Trim for 65kts
   Note Touch Down Change