


Configure AEM Cloud Service



[Find your journey at learning.adobe.com >](https://learning.adobe.com)

Contents

Configure AEM Cloud Service

Introduction

OSGi Configuration: An Overview

JSON Configuration Files

Common OSGi Configurations for AEM

Exercise 1: Use the OSGi Installer Configuration Printer

Exercise 2: Configure AEM with OSGi

Securing Background Services

Service Users

Service ID

ServiceUserMapper

ResourceResolverFactory

SlingRepositoryInitializer

Exercise 3: Define service user using repoint

©2020 Adobe. All rights reserved.

DevOps for AEM as a Cloud Service

If this guide is distributed with software that includes an end user agreement, this guide, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by any such license, no part of this guide may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Adobe. Please note that the content in this guide is protected under copyright law even if it is not distributed with software that includes an end user license agreement.

The content of this guide is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Adobe. Adobe assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide.

Please remember that existing artwork or images that you may want to include in your project may be protected under copyright law. The unauthorized incorporation of such material into your new work could be a violation of the rights of the copyright owner. Please be sure to obtain any permission required from the copyright owner.

Any references to company names in sample templates are for demonstration purposes only and are not intended to refer to any actual organization.

Adobe, the Adobe logo, Acrobat, the Creative Cloud logo, and the Adobe Marketing Cloud logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

All other trademarks are the property of their respective owners.

Adobe, 345 Park Avenue, San Jose, California 95110, USA.

Notice to U.S. Government End Users. The Software and Documentation are "Commercial Items," as that term is defined at 48 C.F.R. §2.101, consisting of "Commercial Computer Software" and "Commercial Computer Software Documentation," as such terms are used in 48 C.F.R. §12.212 or 48 C.F.R. §227.7202, as applicable. Consistent with 48 C.F.R. §12.212 or 48 C.F.R. §§227.7202-1 through 227.7202-4, as applicable, the Commercial Computer Software and Commercial Computer Software Documentation are being licensed to U.S. Government end users (a) only as Commercial Items and (b) with only those rights as are granted to all other end users pursuant to the terms and conditions herein. Unpublished-rights reserved under the copyright laws of the United States. Adobe agrees to comply with all applicable equal opportunity laws including, if appropriate, the provisions of Executive Order 11246, as amended, Section 402 of the Vietnam Era Veterans Readjustment Assistance Act of 1974 (38 USC 4212), and Section 503 of the Rehabilitation Act of 1973, as amended, and the regulations at 41 CFR Parts 60-1 through 60-60, 60-250, and 60-741. The affirmative action clause and regulations contained in the preceding sentence shall be incorporated by reference.

10-14-2020

Introduction

Adobe Experience Manager (AEM) developers and administrators use OSGi(Open Service Gateway Initiative) configurations to manage AEM Service settings in conjunction with supported runmodes. They can create and customize OSGi configurations based on business requirements.

Objectives

After completing this module, you will be able to:

- Explain OSGi configurations
- Describe the most used OSGi configurations
- Create an OSGi configuration
- Explain the role of System Users
- Describe the Repository Initializer Service and its language

OSGi Configuration: An Overview

OSGi is a fundamental element in the technology stack of AEM. OSGi provides the standardized primitives that enable applications to be constructed from small, reusable and collaborative modules. These modules, commonly known as 'bundles', can be composed into an application and deployed. An OSGi application is typically made up of a set of bundles, configuration information and artifacts.

OSGi supports the modular deployment of the bundles that make up the application. You can stop, install, and start these bundles individually. Each bundle contains one or more OSGi components. The OSGi container handles the interdependencies between the bundles and their components automatically.

OSGi configurations are the definitions of the system parameters and settings contained in bundles. You can manage the configuration settings for OSGi components through the configuration files that are part of an AEM code project.

JSON Configuration Files ¹

The recommended best practice is to define OSGi configurations by using JSON configuration files. You should define the configurations in the AEM Project's code packages (ui.apps) as configuration files (.cfg,.json).

OSGi configurations target OSGi components through their Persistent Identity (PID), which by default takes the OSGi component's Java class name. The OSGi configurations are deployed as JSON files with the following file naming convention:

```
<PID><~unique qualifier for factory services>.cfg.json
```

For example, to provide the configuration for the Day CQ Root Mapping Servlet, as implemented by *com.day.cq.commons.servlets.RootMappingServlet* (a singleton service), you can define an OSGi configuration file at: **/apps/<my-app>/config/com.day.cq.commons.servlets.RootMappingServlet.cfg.json**. The contents of the configuration file will follow the **cfg.json** OSGi configuration format:

```
{  
  
  "rootmapping.target" : "/sites.html"  
  
}
```

OSGi configuration changes are applied immediately to the relevant OSGi component.

Note: The prior versions of AEM supported OSGi configuration files using different file formats such as .cfg, .config and as XML sling:OsgiConfig resource definitions. These formats are superseded by the cfg.json OSGi configuration format.

Common OSGi Configurations for AEM

Following are the common OSGi configurations:

- Day CQ WCM Undo
- Day CQ Root Mapping
- Maintenance Tasks
- Workflow Purge
- Ad-hoc Task Purge
- Project Purge

Day CQ WCM Undo

Persistent Identity: `com.day.cq.wcm.undo.UndoConfig`

AEM stores a history of actions that you perform and the sequence in which you performed them, so that you can undo multiple actions in the order you performed them and redo one or more actions if necessary. You can use these commands to restore the recent state of your web page as you make decisions about the content.

Day CQ Root Mapping

Persistent Identity: `com.day.cq.commons.servlets.RootMappingServlet`

The Day CQ Root Mapping defines where to direct a request to '/'.

Maintenance Tasks ²

Maintenance Tasks are the processes that run on a schedule to optimize the repository. In AEM as a Cloud Service, customers need to do only minimal configuration of the Maintenance Task operational properties. Customers can focus their resources on application-level concerns, leaving the infrastructure operations to Adobe.

Caution: Adobe reserves the right to override a customer's maintenance task configuration settings to mitigate issues such as performance degradation.

Customers can schedule the Workflow Purge, Ad-hoc Task Purge and Project Purge Maintenance tasks to be executed during the daily, weekly, or monthly maintenance windows. These task scheduling configurations should be defined in the AEM Project's code packages (`ui.apps`) as configuration files (`.cfg.json`).

Workflow Purge

Persistent Identity: `com.adobe.granite.workflow.purge.Scheduler`

Minimizing the number of workflow instances increases the performance of the workflow engine. Adobe recommends that you regularly purge completed or running workflow instances from the repository. You can purge workflow instances according to their age, status, and model.

Because the service is a factory service, the name of the `slings:OsgiConfig` node requires an identifier suffix, for example: **`com.adobe.granite.workflow.purge.Scheduler~myidentifier`**

Ad-hoc Task Purge

Persistent Identity: `com.adobe.granite.taskmanagement.impl.purge.TaskPurgeMaintenanceTask`

Tasks represent the items of work to be done on content. You can use Tasks as a part of a workflow or assign them independent of the workflow, as a stand-alone tasks. Just like you need to purge workflow instances to free up repository space, you also need to purge unnecessary ad-hoc tasks on a regular basis.

Project Purge

Persistent Identity: `com.adobe.cq.projects.purge.Scheduler`

Projects help you group resources into one entity. Resources may include project and team information, assets, workflows, and other types of information. Unused project instances should be purged when no longer needed.

Because the service is a factory service, the name of the `slings:OsgiConfig` node requires an identifier suffix, for example: **`com.adobe.cq.projects.purge.Scheduler~myidentifier`**

Exercise 1: Use the OSGi Installer Configuration Printer


Scenario: Determine the JSON format for an existing node-based OSGi configuration.

Prerequisites:


- Local AEM author service
- AEM project created from AEM Maven Archetype

In this exercise, you will determine the correct JSON file format for an existing node-based OSGi configuration.


1. From the **Navigation**, navigate to **Tools > Operations > Web Console**, as shown:



2. Using the Web Console menus, select **OSGi > OSGi Installer Configuration Printer**, as shown:



3. On another tab, open **CRXDE Lite** and navigate to **/apps/training/config.author**.
4. Select the **com.day.cq.wcm.mobile.core.impl.MobileEmulatorProvider-training** node, as shown:



The property values are displayed.

- Copy the `com.day.cq.wcm.mobile.core.impl.MobileEmulatorProvider-training` node name and paste it on the **PID** field on OSGi Configuration Printer tab.
- Click **Print**, as shown:

Adobe Experience Manager Web Console
OSGi Installer Configuration Printer

Main OSGi Sling Status Web Console

OSGi Installer Configuration Printer

To emit the configuration properties just enter the configuration PID, select a [serialization format](#) and click 'Print'

PID `com.day.cq.wcm.mobile.core.impl.MobileEmulatorProvider-training`

Serialization Format OSGi Configurator JSON Print

An error is displayed, as shown:

OSGi Installer Configuration Printer

To emit the configuration properties just enter the configuration PID, select a [serialization format](#) and click 'Print'

PID `com.day.cq.wcm.mobile.core.impl.MobileEmulatorProvider-training`

Serialization Format OSGi Configurator JSON Print

Serialized Configuration Properties No configuration properties for pid 'com.day.cq.wcm.mobile.core.impl.MobileEmulatorProvider-training' found!

The error is due to a mismatch between the naming convention of node-based OSGi factory configurations and the new naming convention of JSON-based OSGi factory configuration files. You need to change the PID to the unique configuration identifier that will be used for the JSON file.

- Change the '-' (just before the training unique modifier) to '~' and click **Print**. The **Serialized Configuration Properties** is displayed, as shown:

OSGi Installer Configuration Printer

To emit the configuration properties just enter the configuration PID, select a [serialization format](#) and click 'Print'

PID `com.day.cq.wcm.mobile.core.impl.MobileEmulatorProvider~training`


Serialization Format OSGi Configurator JSON Print

Serialized Configuration Properties

```
{
  "mobile.resourceTypes": [
    "training/components/page"
  ],
  "README": "Indicate which page resource types should display the mobile emulators."
}
```

- Compare the OSGi configuration JSON format and the property values to those of the node-based configuration.

Tip: To validate the format of JSON configuration files, you can also use the Configuration Printer by navigating to **OSGi > Configuration** and selecting the **Show configuration as JSON** button, as shown:



You now know how to use the OSGi Installer Configuration Printer to provide the correct JSON format for existing node-based OSGi configuration.

Exercise 2: Configure AEM with OSGi

Scenario: Modify the redirect target location, for requests made to '/', to /sites.html. For example, requests to the URL <http://localhost:4502> should redirect to <http://localhost:4502/sites.html>.

Prerequisites:

- Local AEM author service
- AEM project created from AEM Maven Archetype
- AEM project imported into Eclipse
- Maven 'Run As' Profiles defined


OSGi configuration files should be under change control. As a result, you should create the configuration files in your AEM project. Deploy the AEM project to AEM to test the newly defined configurations. In this exercise, you define the OSGi configuration files in JSON format, deploy the configurations to AEM and verify the configuration changes.

This exercise includes the following tasks:


1. Create an OSGi configuration file in JSON format
2. Install and verify the configuration

Task 1: Create an OSGi Configuration File in JSON format


1. Using **Eclipse**, in Project Explorer, navigate to **ui.apps/src/main/content/jcr:root/apps/training**, as shown:



2. Right-click on the **config** folder and select **New > File**.
3. Enter **com.day.cq.commons.servlets.RootMappingServlet.cfg.json** as the file name and click **Finish**.



4. The file will open in the editor. Copy the contents of the file **com.day.cq.commons.servlets.RootMappingServlet.cfg.json** from **devops-training/training-files/OSGiConfig** and paste it in the newly created file.
5. Verify the file contents and click **Save** to save the changes in the Eclipse editor.



```
1 {
2     "rootmapping.target" : "/sites.html"
3 }
4
```


Task 2: Install and Verify the configuration

1. If you do not already have a command line window open in your < AEM Project > directory, open one now.

2. Enter the following command to deploy your changes to the local AEM author instance:

```
$ mvn clean install -P adobe-public -P autoInstallSinglePackage
```

3. Verify that the build completed successfully, as shown:




```
[INFO] -----
[INFO] Reactor Summary for devops 1.0-SNAPSHOT:
[INFO]
[INFO] devops ..... SUCCESS [ 0.313 s]
[INFO] DevOps Project - Core ..... SUCCESS [ 7.499 s]
[INFO] DevOps Project - Repository Structure Package ..... SUCCESS [ 0.736 s]
[INFO] DevOps Project - UI apps ..... SUCCESS [ 9.348 s]
[INFO] DevOps Project - UI content ..... SUCCESS [ 3.703 s]
[INFO] DevOps Project - All ..... SUCCESS [ 7.862 s]
[INFO] DevOps Project - Integration Tests Bundles ..... SUCCESS [ 1.137 s]
[INFO] DevOps Project - Integration Tests Launcher ..... SUCCESS [ 2.129 s]
[INFO] DevOps Project - Dispatcher ..... SUCCESS [ 0.456 s]
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 34.655 s
[INFO] Finished at: 2020-06-03T13:59:44-07:00
[INFO] -----
```

Note: Any changes you sync back to your maven project should be committed into source control:

```
git commit -a -m "added new files".
```


4. Open **CRXDE Lite** and navigate to **apps/training/config**.

5. Verify that the `com.day.cq.commons.servlets.RootMappingServlet.cfg.json` OSGi configuration file was deployed. Open the file and verify its contents, as shown:




6. On another browser tab, from the **Navigation** page, navigate to **Tools > Operations > Web Console**.

7. Search for **Day CQ Root Mapping** and verify that the **Target Path** value is `/sites.html`.



8. On another browser tab, enter the AEM root path: <http://localhost:4502> and verify that the root path redirects to `/sites.html`, as shown:



You have defined an OSGi configuration file in the JSON format, deployed the configuration to AEM, and verified the results.

Securing Background Services³

A service is a piece or collection of functionality. Examples of services include the Sling queuing system, Tenant Administration, Event Handlers, custom Workflow processes, and a Message Transfer System. Each service is identified by a unique service name. Because a service is implemented as a component in an OSGi bundle, services are named by the bundles providing them.

Adobe recommends running a service within the calling user's permission context when possible. However, background tasks are often not associated with a specific user. As a result, Apache Sling provides the following three parts mechanism for service authentication and authorization.

- Service user
- Service ID
- ServiceUserMapper

Service Users

A service user is a JCR user with no password set and a minimal set of privileges that are necessary to perform a specific task. Having no password set means that it will not be possible to log in with a service user, except as a known service.

Service ID

A service may be comprised of multiple parts, so each part of the service may be further identified by a subservice name. A subservice name is optional. The examples of subservice name are the names for the subsystems in a Message Transfer System, such as accepting messages, queueing messages, and delivering messages.

The combination of the Service Name and Subservice Name defines the Service ID. The Service ID is finally mapped to a Resource Resolver and/or JCR user ID for authentication.

Therefore, the actual service identification (service ID) is defined as:

```
service-id = service-name [ ":" subservice-name ]
```


ServiceUserMapper

The ServiceUserMapper service enables you to map the Service IDs comprised of the Service Names defined by the providing bundles and optional Subservice Name to ResourceResolver and/or JCR Repository user IDs. This mapping is configurable such that system administrators are in full control of assigning users to services.

ResourceResolverFactory

The Sling ResourceResolverFactory provides a factory method to allow the service to authenticate to the repository, as shown:

```
ResourceResolver getServiceResourceResolver(Map<String, Object>  
authenticationInfo) throws LoginException;
```



SlingRepositoryInitializer 4

The Apache Sling SlingRepositoryInitializer enables you to create resources at startup before the Sling Repository Service is registered as an OSGi service. As a result, the application logic can consider the existence of those resources for granted. Repoint statements should be under change control and therefore are defined in OSGi configurations.

The *repoint* Repository Initialization language:

- Creates paths, service users and Access Control Lists in a content repository
- Registers JCR namespaces and node types

An example of *repoint* statements:

```
create service user training-user-3
set ACL on /content
  allow jcr:read for training-user-3
end
create path /content/example3.com(sling:Folder)"
create path /content/example3.com(sling:Folder mixin mix:referenceable,
mix:sharable)
```

Note: The repoint statements are defined in an OSGi configuration (immutable). However, repoint statements often refer to or modify mutable content.

Exercise 3: Define service user using repointit

Scenario: A developer is implementing a background service that requires authentication and authorization to write to the repository. A service user is necessary to authenticate the service to the repository and to create a permission context within which the service will run. In addition, the service user needs to be granted the appropriate permissions.

Prerequisites:


- Local AEM author service
- AEM project created from AEM Maven Archetype
- AEM project imported into Eclipse
- Maven 'Run As' Profiles defined

This exercise includes the following tasks:

1. Create an OSGi configuration file in JSON format
2. Install and verify the configuration


Task 1: Define the repointit OSGi configuration file in JSON format

1. Using Eclipse, in Project Explorer, navigate to **ui.apps/src/main/content/jcr:root/apps/training**, as shown:



2. Right-click the **config** folder and select **New > File**.
3. Enter **org.apache.sling.jcr.repointit.RepositoryInitializer~training.cfg.json** in the File Name field and click **Finish**. The RepositoryInitializer service is a factory service, so a unique identifier is added to the Persistent Identity of the service.
4. The file will open in the editor. Copy the contents of the file **org.apache.sling.jcr.repointit.RepositoryInitializer~training.cfg.json** from **devops-training/training-files/OSGiConfig** and paste it in the newly created file.

5. Verify the file contents and click **Save** to save your changes in the Eclipse editor, as shown:



```
1 {
2   "scripts:String[]":[
3     "create service user training-user",
4     "set ACL on /content \r\nallow jcr:all for training-user \r\nend"
5   ],
6   "references":[
7     ""
8   ]
9 }
```


Task 2: Install and verify the configuration

1. If you do not already have a command line window open in your < AEM Project > directory, open one now.

2. Enter the following command to deploy your changes to the local AEM author instance:

```
$ mvn clean install -P adobe-public -P autoInstallSinglePackage
```

3. Verify that the build is completed successfully, as shown:



```
[INFO] -----
[INFO] Reactor Summary for devops 1.0-SNAPSHOT:
[INFO]
[INFO] devops ..... SUCCESS [ 0.313 s]
[INFO] DevOps Project - Core ..... SUCCESS [ 7.499 s]
[INFO] DevOps Project - Repository Structure Package ..... SUCCESS [ 0.736 s]
[INFO] DevOps Project - UI apps ..... SUCCESS [ 9.348 s]
[INFO] DevOps Project - UI content ..... SUCCESS [ 3.703 s]
[INFO] DevOps Project - All ..... SUCCESS [ 7.862 s]
[INFO] DevOps Project - Integration Tests Bundles ..... SUCCESS [ 1.137 s]
[INFO] DevOps Project - Integration Tests Launcher ..... SUCCESS [ 2.129 s]
[INFO] DevOps Project - Dispatcher ..... SUCCESS [ 0.456 s]
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 34.655 s
[INFO] Finished at: 2020-06-03T13:59:44-07:00
[INFO] -----
```

Note: Any changes you sync back to your maven project should be committed into source control:

```
git commit -a -m "added new files".
```

4. Open **CRXDE Lite** and navigate to **apps/training/config**.


5. Verify that the **org.apache.sling.jcr.repoinit.RepositoryInitializer~training.cfg.json** OSGi configuration file is deployed. Open the file and verify the contents, as shown:



```
1 {
2   "scripts:String[]":[
3     "create service user training-user",
4     "set ACL on /content \r\nallow jcr:all for training-user \r\nend"
5   ],
6   "references":[
7     ""
8   ]
9 }
10
```

6. On a browser tab, from the **Navigation** page, navigate to **Tools > Security > Permissions**.

7. Select Users from the drop-down menu and search for the **training-user** to verify that the user is created and an ACE was created, as shown:



You now know how to initialize configuration information for an AEM instance. You have defined a set of repository statements in an OSGi configuration, deployed the configuration to AEM and verified the results.

References

1. Configuring OSGi for AEM as a Cloud Service: <https://docs.adobe.com/content/help/en/experience-manager-cloud-service/implementing/deploying/configuring-osgi.html> ↗
2. Maintenance Tasks: <https://docs.adobe.com/content/help/en/experience-manager-cloud-service/operations/maintenance.html> ↗
3. Service Authentication: <https://sling.apache.org/documentation/the-sling-engine/service-authentication.html> ↗
4. Apache Sling Repository Initializer: <https://sling.apache.org/documentation/bundles/repository-initialization.html> ↗