

LOW PROFILE SHIELDED SMD CHIP POWER INDUCTOR

ASPI-0615FS



RoHS/RoHS II Compliant



6.0 x 6.0 x 2.0mm

FEATURES:

- Small size and low profile: 2.0mm
- Small DCR and high rated current
- High reliability to mechanical strength
- Magnetically shielded by magnetic powder molding
- Suitable for RoHS reflow profile

APPLICATIONS:

- DC/DC converter for LCD display of notebook PC
- Portable communication equipment
- Digital cameras

ELECTRICAL SPECIFICATIONS:


| | |
|------------------------------------|---|
| Abrakon P/N: | ASPI-0615FS Series |
| Operating Temperature & Humidity : | -40°C to +125°C (Including self generated heat) |
| Storage Temperature & Humidity: | -40°C to +125°C |

| Part Number ASPI-0615FS- Inductance Code | Inductance | Inductance Tolerance | DCR | DCR Tolerance | Saturation Current | Temperature Rise Current |
|--|------------|-------------------------|-----|------------------|-----------------------|-----------------------------|
| Units | H | % | mΩ | % | A | A |
| Symbol | L | M, N | DCR | | Isat | Irms |
| ASPI-0615FS-R50 | 0.5 | N | 9 | ±30% | 7.00 | 5.20 |
| ASPI-0615FS-R80 | 0.8 | N | 12 | | 6.00 | 4.10 |
| ASPI-0615FS-1R5 | 1.5 | N | 17 | | 4.00 | 3.60 |
| ASPI-0615FS-2R2 | 2.2 | N | 24 | | 3.50 | 2.90 |
| ASPI-0615FS-3R3 | 3.3 | M | 30 | ±20% | 2.80 | 2.80 |
| ASPI-0615FS-4R7 | 4.7 | M | 43 | | 2.40 | 2.20 |
| ASPI-0615FS-5R6 | 5.6 | M | 55 | | 2.20 | 2.00 |
| ASPI-0615FS-6R8 | 6.8 | M | 60 | | 2.00 | 1.80 |
| ASPI-0615FS-100 | 10 | M | 90 | | 1.90 | 1.50 |
| ASPI-0615FS-150 | 15 | M | 120 | | 1.30 | 1.20 |
| ASPI-0615FS-220 | 22 | M | 170 | | 1.10 | 1.00 |
| ASPI-0615FS-330 | 33 | M | 310 | | 0.90 | 0.90 |
| ASPI-0615FS-470 | 47 | M | 370 | | 0.80 | 0.80 |

Test Conditions

1. Inductance is measured in HP-4285A Precision LCR Meter.
2. RDC is measured in DU-5011 milli ohm meter.(or equivalent).
3. Isat : Based on inductance change ($\Delta L/L_0 : \leq -30\%$)
4. Irms : Based on temperature rise ($\Delta T : 40^\circ\text{C TYP.}$)
5. Test Freq: 100KHz, 1Vrms

OPTIONS AND PART IDENTIFICATION



LOW PROFILE SHIELDED SMD CHIP POWER INDUCTOR

ASPI-0615FS




RoHS/RoHS II Compliant




6.0 x 6.0 x 2.0mm

OUTLINE DRAWING:



| A | B | C | D Typ. |
|---------|---------|---------|--------|
| 6.0±0.2 | 6.0±0.2 | 2.0±0.2 | 1.50 |



Recommended Land Pattern

Dimension: mm

LOW PROFILE SHIELDED SMD CHIP POWER INDUCTOR



6.0 x 6.0 x 2.0mm


ASPI-0615FS





RoHS/RoHS II Compliant

TAPE & REEL:

T2: 2,000pcs / reel



| Dim | W | A0 | B0 | K0 | P | E | F | D0 | P0 | P2 | T |
|-------------|----------|---------|---------|---------|---------|---------|----------|---------|---------|---------|-----------|
| ASPI-0615FS | 12.0±0.3 | 6.3±0.1 | 6.3±0.1 | 2.2±0.1 | 8.0±0.1 | 7.5±0.1 | 1.75±0.1 | 1.5±0.1 | 4.0±0.1 | 2.0±0.1 | 0.35±0.05 |



| | |
|---|----------|
| A | 330±0.5 |
| B | 100±0.5 |
| C | 13.5±0.5 |
| W | 12.5±0.5 |

Dimension: mm

LOW PROFILE SHIELDED SMD CHIP POWER INDUCTOR




6.0 x 6.0 x 2.0mm

ASPI-0615FS



RoHS/RoHS II Compliant

REFLOW PROFILE:



| Zone | Description | Temperature | Time |
|------|----------------|---------------------|---------------|
| 1 | Preheat / Soak | T_{SMAX} 150°C | 60 ~ 100 sec. |
| 2 | Reflow | T_L 200°C | 20 sec. MAX |
| 3 | Peak heat | T_P 260°C | 10 sec. MAX |

Dimension: mm

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

[ASPI-0615FS-100M-T2](#) [ASPI-0615FS-150M-T2](#) [ASPI-0615FS-220M-T2](#) [ASPI-0615FS-2R2M-T2](#) [ASPI-0615FS-330M-T2](#) [ASPI-0615FS-3R3M-T2](#) [ASPI-0615FS-470M-T2](#) [ASPI-0615FS-4R7M-T2](#) [ASPI-0615FS-6R8M-T2](#) [ASPI-0615FS-KIT](#) [ASPI-0615FS-3R3N-T2](#) [ASPI-0615FS-1R5N-T2](#) [ASPI-0615FS-2R2N-T2](#) [ASPI-0615FS-5R6M-T2](#) [ASPI-0615FS-R50N-T2](#) [ASPI-0615FS-R80N-T2](#)