8-3A-4: Zoning District Dimensional Standards

| <u>5-074-4.</u> <u>2</u>                  | 1 1 | <u>District Dimensional Standards</u> Minimum Yard Setbacks  Note Conditions |                            |   |                |  |  |
|---|-----|--|----------------------------|---|----------------|--|--|
| Zoning<br>District                        |     | Front (1)  | Rear                       | Interior Side                                       | Street<br>Side |  |  |
| Α   | 50' | 30'  | 30'                        | 30'   | 20'            |  |  |
| R-R                                       | 35' | 30'  | 30'                        | 20'   | 20'            |  |  |
| R-1                                       | 35' | 30'  | 30'                        | 10'   | 20'            |  |  |
| R-2                                       | 35' | 20'  | 20'                        | 10'   | 20'            |  |  |
| R-3                                       | 35' | 15' to living area/side load garage 20' to garage face                       | 15'                        | 5' per story (2)                                    | 20'            |  |  |
| R-4                                       | 35' | 15' to living area<br>20' to garage face                                     | 15'                        | 5' per story (2)                                    | 20'            |  |  |
| R-5                                       | 35' | 15' to living area/side load garage 20' to garage face                       | 15'                        | 5'  | 20'            |  |  |
| R-6 to<br>R-11<br>detache<br>d<br>housing | 35' | 15' to living area<br>20' to garage<br>10' if alley loaded                   | 15'<br>4' if alley<br>load | 3'  | 20'            |  |  |
| R-6 to<br>R-11<br>attache<br>d<br>housing | 35' | 15' to living area<br>20' to garage<br>10' if alley load                     | 15'<br>4' if alley<br>load | 0' for common walls<br>5' at end of building        | 20'            |  |  |
| R-12<br>and<br>higher                     | 35' | 15' to living area<br>20' to garage  | 15'<br>4' if alley<br>load | 5' for single story<br>10' feet for multi-<br>story | 20'            |  |  |
| CBD                                       | 35' | 0'   | 0'                         | 0'  | 0'             |  |  |
| C-1                                       | 35' | 20'  | 5'                         | 0'  | 20'            |  |  |
| C-2                                       | 35' | 20'  | 5'                         | 0'  | 20'            |  |  |
| LO  | 35' | 20'  | 10'                        | 0'  | 20'            |  |  |

| PS | 35'  | 20' | 10' | 0' | 20' |  |
|----|--|-----|-----|----|-----|--|
| MU | MU  For MU and CBD - Unless otherwise approved by the Council as a part of a F development agreement, all residential buildings shall follow the residential shown in this table based upon the project density and all other buildings shall setbacks for the C-2 zone (3). |     |     |    |     |  |

#### Notes:

- (1) Front yard setback shall be measured from the face of the garage to the face of the sidewalk, allowing for 20 feet of parking on the driveway without overhang onto the sidewalk.
- (2) Interior side yard setbacks for lots with 50 feet or less of lot width shall be allowed 5 feet interior side yard setbacks for one and two-story structures.
- (3) All setbacks in the M-U zone shall be a minimum 15 feet when adjacent to a residential use or zone.

### Note Conditions:

## A. Minimum Property Size:

- 1. Each property shall be of sufficient size to meet the minimum setbacks as established in this section.
- 2. Minimum property size shall be determined exclusive of land that is used for the conveyance of irrigation water, drainage, creek or river flows unless: a) the water is conveyed through pipe or tile; and b) included as part of a utility easement that generally runs along the property lines.
- 3. When two (2) or more parcels of land, each of which is of inadequate area and dimension to qualify for a permitted use under the requirements of the district in which the parcels are located, are held in one ownership, they shall be used as one property for such use.

# B. Minimum Street Frontage:

- 1. Properties with street frontages on cul-de-sacs or at approximately a ninety-degree (90°) angle shall be a minimum of twenty feet (20') measured as a chord measurement.
- 2. Street knuckles shall be separated from through traffic by a landscape island. Properties with frontages on such knuckles shall be a minimum of twenty feet (20') measured as a chord measurement.
- 3. All other properties with street frontage shall have a minimum of thirty feet (35 feet).

### C. Additional Setback Criteria:

1. Chimneys, pop out windows, direct vent gas fireplaces, entertainment centers, window

seats and other projections which do not increase the usable floor area and do not exceed eight feet (8') in width may project up to two feet (2') into any required setback, provided that projections that are at finished grade, including, but not limited to, chimneys and fireplaces, do not encroach within a side yard utility easement.

- 2. One detached accessory building that is less than two hundred (200) square feet in area and nine feet (9') or less in height shall be allowed in the required rear yard. In no case shall an accessory building be allowed in the street yard or the required side yard.
- 3. Accessory structures, such as decks and patios, which are one foot (1') or less in height, as measured from the property's finished grade, may occupy any yard area.
- 4. In all residential zones garages and carports opening onto a side street must have a minimum distance between the opening of such garage or carport and the side street lot line of not less than twenty feet (20').
- 5. Front yard setback from arterial and collector streets (as identified on the highway district functional classification map) is thirty feet (30') in all residential zoning districts.
- 6. Street side setback on arterial and collector streets (as identified on the highway district functional classification map) is twenty feet (20') in all residential zoning districts.
- 7. Setback areas are subject to drainage compliance or otherwise specified within this title.
- 8. If a conditional use, PUD or development agreement in lieu of a PUD is utilized, waivers to setbacks shall be permitted if determined by the council to be appropriate for the said development and that such waivers will be compatible with the area and that the overall density allowed by the said zoning district is not exceeded.

## D. Maximum Height Limit:

- 1. Height exceptions shall not be permitted except by discretion of the council with the submittal of a conditional use permit or development agreement application.
- 2. The maximum height limitations shall not apply to the following architectural features, not intended for human occupation: spire or steeple, belfry, cupola, chimney. Such architectural features shall have a maximum height limit of twenty feet (20'), as measured from the roofline.
- 3. The maximum height limitations shall not apply to the following: amateur radio antenna; bridge tower; fire and hose tower; observation tower; power line tower; smokestack; water tank or tower; ventilator; windmill; wireless communication facility, or other commercial or personal tower and/or antenna structure; or other appurtenances usually required to be placed above the level of the ground and not intended for human occupancy.
- 4. No exception shall be allowed to the height limit where the height of any structures will constitute a hazard to the safe landing and takeoff of aircraft in an established airport.

E. All new residential and accessory structures within any zoning district shall comply with residential setbacks.

F. Spite strips, common lots, phasing, or any other means of any type purposely or otherwise used to block services or development, including but not limited to sewer, water, streets, or utilities are not allowed in any zoning district within the City of Star.

(Ord. 303, 2-11-2020; amd. Ord. 310, 7-21-2020)