

ILP formulation

- q is an upper bound of the total quantity of MDS ($length/2$)
- $=$ is string equivalence
- $MIC[i, j]$ ($MAC[i, j]$) is the substring starting at i and finishing at j (i, j being positions) of the $MIC(MAC)$. Can be trivially defined using string concatenation and $MIC(i, c)$ ($MAC(i, c)$).
- $reverse_complement(String)$ is the Watson-Crick reverse complement of $String$
- Size of the Oxytricha Input genome: MIC is fragmented into $\sim 750\ 000$ MDSs, MAC into $300\ 000$.
- Variables marked with $*$ are populated during the preprocessing phase.

objective function:
$$\min \sum_{i,j} MDS_{MACstart}(i, j)$$

Variables definitions

$$*Eq(i, j, h, l) = \begin{cases} 0 \\ 1, & \text{if } MIC[i:j] = MAC[h:l] \end{cases}$$

$$*cwc(i, j, h, l) = \begin{cases} 0 \\ 1, & \text{if } MIC[i:j] \text{ is the reverse complement of } MAC[h:l] \end{cases}$$

$$*Possible_{MDSMAC}(i, a, b) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ can start at } a \text{ and finish at } b \text{ in the MAC} \end{cases}$$

$$*Possible_{MDSMIC}(i, a, b) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ can start at } a \text{ and finish at } b \text{ in the MIC} \end{cases}$$

$$Possible_{assignment}(a, b, c, d) = Eq(a, b, c, d)$$

$$MDS_{MICstart}(i, j) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ starts at position } j \text{ in the MIC} \end{cases}$$

$$MDS_{MICend}(i, j) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ ends at position } j \text{ in the MIC} \end{cases}$$

$$MDS_{MACstart}(i, j) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ starts at position } j \text{ in the MAC} \end{cases}$$

$$MDS_{MACend}(i, j) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ ends at position } j \text{ in the MAC} \end{cases}$$

$$Inv(i) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ is inverted in the MAC} \end{cases}$$

$$P_{start}(i, j) = \begin{cases} 0 \\ 1, & \text{if } MDS_{MACstart}(i, j) = 1, \text{ Pointer } i \text{ starts at position } j \text{ in the MAC} \end{cases}$$

$$P_{end}(i, j) = \begin{cases} 0 \\ 1, & \text{if } MDS_{MACend}(i-1, j) = 1, \text{ Pointer } i \text{ ends at position } j \text{ in the MAC} \end{cases}$$

$$*MAC(i, c) = \begin{cases} 0 \\ 1, & \text{if } c \text{ is the character at position } i \text{ in the MAC} \end{cases}$$

$$*MIC(i, c) = \begin{cases} 0 \\ 1, & \text{if } c \text{ is the character at position } i \text{ in the MIC} \end{cases}$$

$$Cov_{MIC}(i, j) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ covers the position } j \text{ in the MIC} \end{cases}$$

$$Cov_{MAC}(i, j) = \begin{cases} 0 \\ 1, & \text{if MDS } i \text{ covers the position } j \text{ in the MAC} \end{cases}$$

Constraints

Internally Eliminated Sequences

$$IES(j) = \begin{cases} 0 \\ 1, & \text{if } i \text{ is part of an IES: } \sum_{0 \leq i \leq q} Cov_{MIC}(i, j) = 0 \end{cases}$$

MDSs must correspond to identical or reverse and complemented substrings of MIC and MAC.

The following constraints enforce this fact:

$$MDS_{MICstart}(i, a) + MDS_{MICend}(i, b) + MDS_{MACstart}(i, c) + MDS_{MACend}(i, d) + Inv(i) - 5cwc(a, b, c, d) = 0$$

$$MDS_{MICstart}(i, a) + MDS_{MICend}(i, b) + MDS_{MACstart}(i, c) + MDS_{MACend}(i, d) - 4Eq(a, b, c, d) = Inv(i)$$

$$\sum_j MDS_{MICstart}(i, j) \leq 1$$

$$\sum_j MDS_{MICend}(i, j) = \sum_j MDS_{MICstart}(i, j)$$

Coverage

$$\sum_{l \leq j} MDS_{MICstart}(i, l) + \sum_{l \geq j} MDS_{MICend}(i, l) - 2Cov_{MIC}(i, j) = 0$$

$$\sum_{l \leq j} MDS_{MACstart}(i, l) + \sum_{l \geq j} MDS_{MACend}(i, l) - 2Cov_{MAC}(i, j) = 0$$