

Command Center — KPI & Tile Specification

Every metric on the dashboard: definition, source, formula, and display rules.

Altametrics Back Office & Growth / Plum · Engineering handoff · Derived from the working prototype

How to read this document. Each tile is specified as *Source* → *Formula* → *Display* → *Interaction*. Formulas are written against the data model in §2, not against prototype code. Where the prototype currently uses synthetic demo data instead of a real query, the spec says **SYNTHETIC** and states what production must compute instead — those are the items that need a data contract before build.

1. Scope and screens

The Command Center has two screens and one settings area. All three read the same alert engine.

SCREEN	PURPOSE	METRICS DEFINED IN
Daily Brief	Landing view. What changed overnight, what to act on first.	§4
Dashboard	Live exception board — health cards, module rollups, alert tiles.	§5–§8
Settings	Alert / Module / KPI / Theme configuration. Writes overrides consumed by §5–§8.	§10

2. Data model

Three entities underpin every number on the screen.

Store

ENTITY

KEY

storeNumber — e.g. #0142

FIELDS

name , brand (client), organization , region , district , manager

DISPLAY

Store labels render as {storeNumber} - {locationName} . The brand is stripped from the label — it belongs in the Client column, which is visible only to Altametrics logins (§3).

Alert definition (check)

CONFIGURATION · ONE ROW PER CATALOGUE ENTRY

KEY

code — stable short id, e.g. inp

FIELDS

name , module (area), product , defaultSeverity , triggerMode (method | formula), method or formula , evaluationWindow , recommendedAction , columns[] , autoEscalate config

NOTE

product is **derived from the module**, never stored independently. Re-homing a check to a Growth module moves it to the Growth board automatically.

Exception (alert instance)

RUNTIME · ONE ROW PER (CHECK × STORE) THAT IS CURRENTLY FAILING

KEY	alertId
FIELDS	code , storeNumber , severity , status (Open Escalated Resolved Ignored), firstSeenAt , openHours , valueAtStake , columns{}
OPENHOURS	now - firstSeenAt , in hours. Drives ageing, the <i>Aging > 24h</i> counter, and store-level <i>Oldest open</i> .
LIFECYCLE	An exception closes automatically when its trigger condition stops evaluating true. Resolve and Ignore are manual overrides that remove it from the open list and must be written to an audit trail with actor and timestamp.

Severity

Four levels, ordered Critical (4) > High (3) > Medium (2) > Low (1). The rank drives sorting and roll-up status everywhere. Each check carries a default severity; an instance may escalate above it based on the check's own thresholds (days delayed, dollar value, hours offline).

SYNTHETIC. The prototype assigns instance severity by hashing storeNumber + code across the check's severity band. Production must derive it from the threshold rules defined per check in Alert Setup.

3. Scoping — applies to every number in this document

No tile queries the raw exception table. Every metric is computed over a scoped set, filtered in this order. Getting this chain wrong is the most likely source of numbers that disagree between tiles.

```
scoped = exceptions
  .filter(e => check(e.code).product === activeProduct) // 1 product board
  .filter(e => inRoleScope(e))                          // 2 role entitlement
  .filter(e => matchesFilters(e))                       // 3 Client / Org / Region
  .filter(e => !severityFilter || e.severity === severityFilter) // 4 donut selection

sc-camel-open-alerts = scoped.filter(e => e.status !== 'Resolved' && e.status !== 'Ignored')
```

3.1 Role entitlement

ROLE	SEES
Super User	All clients, all stores. Altametrics staff only.
Corporate Admin	All stores within the signed-in client.
Regional Admin	Assigned regions only.
District Manager	Assigned districts only.
Store Manager	Own store only.

A client login is additionally pinned to its own brand , so the role scope is always intersected with the tenant. The **Client column is hidden entirely for client logins** — it is only meaningful to Altametrics staff viewing across tenants.

3.2 Fleet denominator

Every percentage on the board divides by `totalStores` = the count of stores visible under the current role and filters — **not** the global fleet. Changing role or filter changes the denominator, and every percentage must recompute.

4. Daily Brief

The landing screen. Answers "what changed overnight" before the user reaches the live board.

New exceptions · 12h

BRIEF · LEFT RAIL

SOURCE `openAlerts where firstSeenAt > now - 12h`

FORMULA `count(newExceptions)`

DISPLAY Integer.

WHY Separates today's work from the standing backlog. A user who cleared yesterday's list only needs this number.

Critical among new

BRIEF · LEFT RAIL

FORMULA `count(newExceptions where severity = 'Critical')`

DISPLAY Integer. Red when > 0.

New check types

BRIEF · LEFT RAIL

FORMULA `distinct(newExceptions.code).length` displayed as N of {totalActiveChecks}

WHY Distinguishes "one check failing at 40 stores" from "12 different things broke" — different responses.

Operations check

BRIEF · LEFT RAIL · ALSO §6 AS A RING

DEFINITION Share of all check×store evaluations currently passing.

FORMULA `totalChecks = activeChecks.length × totalStores`

`failing =  $\sum$  storesFlagged(check)`

`opsCheck% = round((totalChecks - failing) / totalChecks × 100)`

DISPLAY Percentage. Label *stable* at ≥ 65%, *degraded* below.

NOTE Denominator moves with role scope and with the number of enabled checks. Adding a check in Settings changes this figure — expected, but worth surfacing in release notes.

Lead story / Keep an eye on it

BRIEF · CENTRE COLUMN · 4 ITEMS

SOURCE	Top 6 checks ranked by <code>severityRank DESC, storesFlagged DESC</code> , then new-today items floated to the top; first 4 shown.
HEADLINE	<code>{checkName} – {storesFlagged} stores ({pctOfFleet} of fleet)</code>
WHAT'S DRIVING IT	<code>{module} check failing across {n} locations · {evaluationWindow}</code> . plus age — "Appeared this morning" if < 24h, else "Open for {age}".
WHAT TO DO	The check's <code>recommendedAction</code> from Alert Setup.
INTERACTION	Opens that check's drill-down table.

Stores to watch

BRIEF · LEFT RAIL · TOP 4

FORMULA	Stores ranked by <code>count(distinct failing checks)</code> descending.
DISPLAY	Rank, store name, failing-check count.

Module report card

BRIEF · RIGHT RAIL

PER MODULE	<code>impacted% = round(storesFlaggedInModule / totalStores × 100)</code>
GRADE	Letter grade banded off <code>impacted%</code> — A at the low end through to F. Bands are configurable.

SYNTHETIC — needs a data contract. In the prototype the "new in last 12h" test is a hash of the check code, not a real timestamp. Production requires `firstSeenAt` persisted per exception instance. Until that exists, every Brief metric in §4 is illustrative.

5. Dashboard — severity KPIs

Severity Mix donut

DASHBOARD · HEALTH CARD 1

SOURCE	<code>openAlerts</code> grouped by severity
SEGMENTS	Arc length $\propto \text{count(severity)} / \text{count(openAlerts)}$. Zero-count severities are omitted, not drawn at zero.
CENTRE	Total open exceptions.
LEGEND	Level, absolute count, and share as a whole percent.
INTERACTION	Clicking a segment sets <code>severityFilter</code> — a global filter (step 4 of §3). Every tile, module rollup and store list recomputes. Clicking the active segment clears it. Unselected segments drop to 25% opacity.

The same `openAlerts` set yields the counters below. They are not separate queries and must always reconcile against the donut.

COUNTER	FORMULA
Open	<code>count(openAlerts)</code>
Critical / High / Medium / Low	<code>count(openAlerts where severity = L)</code>
Stores affected	<code>distinct(openAlerts.storeNumber).length</code>
Aging > 24h	<code>count(openAlerts where openHours > 24)</code>
Escalated	<code>count(openAlerts where status = 'Escalated')</code>
Resolved	<code>count(scoped where status = 'Resolved')</code> — note this reads the full scoped set, not openAlerts

6. Dashboard — health cards

Operations Check ring

DASHBOARD · HEALTH CARD 2

FORMULA	As §4 <i>Operations check</i> . Same figure, rendered as a ring.
DISPLAY	Percent in the centre; arc = the same percent.

Operational Signals

DASHBOARD · 6 TILES

SIGNALS	Sales / PMIX polling · Clock online · Order submission rate · Order fulfilment rate · Inventory post rate · Payroll post rate
DEFINITION	Per signal, the share of in-scope stores passing the checks mapped to that category.
FORMULA	<code>passRate = (totalStores - distinct stores failing any mapped check) / totalStores × 100</code>
DISPLAY	Percent to one decimal, an 8-point sparkline of the trailing period, and <code>{passing}</code> of <code>{totalStores}</code> stores .
INTERACTION	Opens the drill-down for the worst-performing mapped check.
MAPPING	Polling → <code>dat, pds</code> · Clock → <code>clk</code> · Order submission → <code>ordc</code> · Fulfilment → <code>rcv, late</code> · Inventory → <code>inp, idi, iwi, ipi</code> · Payroll → <code>pay</code>

SYNTHETIC. Signal percentages and their sparklines are generated in the 95–99% band and are *not* derived from the mapped checks — the tiles can read 98% while the underlying check shows widespread failure. Production must compute the pass rate from the mapping above and persist a daily history for the sparkline.

User Activity / Mobile Usage

DASHBOARD · HEALTH CARDS 3–4

USER ACTIVITY	Back-office logins split by role over the trailing period.
MOBILE USAGE	Active users by app — Zip Schedules, Zip Inventory, Zip Clock / DAR. Donut segments ∝ users per app; centre shows the total.
STATUS	SYNTHETIC — fixed demo constants. Requires a telemetry feed of login and app-session events before these can ship.

7. Module rollups

One row per module. The left panel is the module summary; the tiles to its right are its checks (§8).

Stores flagged (module chip)	
MODULE ROW · LEFT PANEL	
FORMULA	<code>distinct(stores where ANY check in module is failing).length</code>
CRITICAL	This is a distinct store count, not the sum of its tiles . A store failing three Inventory checks counts once. Summing the tiles overstates the number and will exceed the fleet size.
SUFFIX	<code>flagged</code> , or <code>services</code> for modules containing only platform-level checks (§9).

Module status	
MODULE ROW · DOT COLOUR AND LABEL	
RULE	<code>0 flagged → Healthy (green)</code>
	<code>worstSeverity = Critical → Critical (red)</code>
	<code>worstSeverity = High → Attention (orange)</code>
	<code>otherwise → Watch (amber)</code>
IMPACT BAR	<code>round(storesFlagged / totalStores × 100)</code> , floor 3% so a non-zero value is always visible.

8. Alert tile — the core unit

One tile per check, 130 × 100 px, laid out in a single row per module. This is the most-repeated component on the board; every field below is required.

Alert tile	
MODULE ROW · REPEATED PER CHECK	
STORES IMPACTED	<code>distinct(openAlerts where code = C).storeNumber.length</code>
DENOMINATOR	<code>totalStores</code> in scope. Rendered <code>{impacted}/{total}</code> .
PERCENTAGE	<code>round(impacted / total × 100, 1)</code> . Renders <code><0.1%</code> when the value rounds to zero but <code>impacted > 0</code> — never a bare <code>0%</code> against a non-zero count.
ALERT COUNT	<code>count(openAlerts where code = C)</code> . Equals the store count for most checks; differs for the two cases in §9.
BAR	Width = percentage, clamped to <code>[4, 100]</code> so a small non-zero value stays visible.
COLOUR	The check's effective severity colour — <code>severityOverride[check] ?? defaultSeverity</code> . Applied to the top border, icon tint, count chip and bar.
ESCALATION CHIP	Present only when auto-escalation is configured. See §11.
INTERACTION	Opens the drill-down table: one row per affected store, with the check's own KPI columns, plus select / Resolve / Ignore / Send Email.

8.1 Drill-down table

Columns are `Store` + `Client` (Altametrics logins only) + the check's own `columns[]` from §12. A select column supports per-row and select-all. Selecting rows reveals **Resolve** and **Ignore** with a live count; both write to the audit trail and remove the rows from the open list.

9. Two exceptions to the one-row-per-store rule

Windowed checks — Missing labor / sales / PMIX data

CHECK CODE `DAT`

GRAIN	One row per (store × missing feed) . Labor, Sales and PMIX are separate feeds; a store missing two feeds yields two rows.
WINDOW	User picks Last 4h / 8h / 24h. Rows filter to <code>gap ≤ window</code> .
CONSEQUENCE	Alert count > store count. The tile shows both, and the table footer must read <code>{alerts} alerts across {stores} stores</code> — never conflate the two.
CONSISTENCY	Tile count and table rows must come from the same generator. They diverged in an earlier build because the tile read the seeded list while the table read the window.

Platform-level checks

ENVIRONMENT NOT LIVE · SSO LOGIN FAILED · HUBWORKS INSTANCE · POLLING INSTANCE

GRAIN	One row per service , not per store. These describe infrastructure, so store scoping does not apply.
COLUMNS	First column is <code>Service</code> ; row identity is <code>Environment / Region</code> ; then Down For, Last Response, Status.
ROLLUP	A module containing only platform checks reports <code>N services</code> , not stores.

10. By-store view

Same data, pivoted store-first. Answers "which of my stores is worst today" — the alert-first board cannot.

COLUMN	FORMULA
Open	<code>count(distinct failing checks at that store)</code> , after severity filter
Severity mix	Chips per level present, e.g. <code>2 crit · 1 high</code>
Module chips	Affected modules with a per-module count
Exposure	<code>Σ max(currency value in each exception's columns)</code> . Formatted <code>\$34k</code> ; red at ≥ \$50k.
Oldest	<code>max(openHours)</code> . Amber ≥ 24h, red ≥ 48h.

Default sort — priority: `worstSeverity DESC → criticalCount DESC → highCount DESC → totalOpen DESC → oldest DESC`. Alternatives: Open, \$ exposure, Oldest.

Clicking a store opens its drawer: open count, exposure and oldest across the top, then every exception grouped by module and sorted by severity then age.

11. Auto-escalation

Escalation timer

PER CHECK · CONFIGURED IN ALERT SETUP

CONFIG	<code>escalateAfterMinutes</code> (15-minute steps, 15 min – 4 h), <code>userRole</code> (required, defaults to the first role), <code>additionalEmail</code> (optional)
COUNTDOWN	<code>remaining = escalateAfterMinutes × 60 - elapsed(escalationStartedAt)</code> , displayed <code>mm:ss</code> on the tile and refreshed once per second.
ON EXPIRY	Send to every user in <code>userRole</code> , restricted to their assigned stores , plus <code>additionalEmail</code> . Mark the check escalated; the chip becomes Re-Send Email .
RE-SEND	Resets <code>escalationStartedAt</code> and clears the fired flag; the countdown restarts.
SCOPE RULE	Recipients never receive exceptions for stores outside their assignment. This is the rule that keeps escalation credible — without it people stop reading the mail.

12. Configuration overrides

Settings writes overrides that the tiles read at render time. All are keyed by check `code` and must survive save/reload.

OVERRIDE	EFFECT
<code>nameOverride</code>	Renames the check everywhere it renders
<code>moduleOverride</code>	Re-homes the check; product follows the module and the check moves boards
<code>severityOverride</code>	Changes tile colour, sort rank and module status
<code>triggerOverride</code>	<code>{ mode: 'method' 'formula', method, formula }</code>
<code>escalationConfig</code>	<code>{ minutes, role, email }</code> — drives §11
<code>customChecks[]</code>	User-created checks; behave identically to catalogue entries

Trigger definition is either a *Method* — a built-in detection routine such as *Not posted check*, *Threshold breach*, *Variance vs theoretical*, *Polling gap check* — or a *Formula*, a boolean expression supporting AND / OR, e.g. `posted = false AND days_delayed > 2`. Exactly one applies per check.

13. Alert catalogue

Every check, its module, default severity and evaluation window. Drill-down columns are listed per check in the appendix table below.

13.1 Altametrics Back Office

MODULE	CHECK	SEVERITY	EVALUATION WINDOW
Integrations	Inbound API errors	High	Last hour
	Missing labor / sales / PMIX data	Critical	Last 4h / 8h / 24h (user-selectable)
	Missing previous-day sales	High	Business date · Yesterday
	No poll in last 6 hours	Critical	Last poll · > 6h ago

MODULE	CHECK	SEVERITY	EVALUATION WINDOW
	Outbound API errors	High	Last hour
	SFTP connection failure	High	Food vendor feeds
	Sync failure	High	Since · 1h ago
Forecast	Forecast posted late	High	Vs posting deadline
	Forecasted hours vs scheduled hours	High	Current week
	High variance vs actual sales	High	System vs actual sales
	Missing forecast	Critical	Forecast date · Jun 25
Scheduling	Above target labor %	High	Vs labor target
	Late schedule post	High	Vs 14-day deadline
	Minor / labor-law violation	Critical	This week
	Overtime scheduled	High	This week
	Schedule not published	Critical	Week of Jun 22–28
Timekeeping	Meal & break violation	Critical	This week
	No-show vs schedule	High	Today's shifts
	Offline clock	Medium	Last ping · > 15m
	Overtime threshold reached	High	Current week
	Payroll not posted	Critical	Pay period · Jun 16–22
Ordering	Late delivery	Medium	Today's deliveries
	Manual receiving	High	Rolling 30 days
	Missing invoice on delivery date	High	Delivery date · Today
	Order not posted	Critical	Delivery date
	Order not submitted by cutoff	Critical	Cutoff · Today 14:00
	Receiving not confirmed	High	Today's deliveries
Inventory	Food cost is high	Critical	Vs theoretical
	High variance locations	High	Theoretical vs actual
	Inventory not posted	Critical	Inventory date · Yesterday
	Missing daily inventory	High	Business date · Yesterday
	Missing period inventory	Critical	Period · P6
	Missing weekly inventory	High	Week of Jun 22–28
	Transfer not posted	High	Rolling 30 days
	Waste not posted	High	Business date
Application Usage	Store users not logged in	Medium	Last 7 days
	Stores not placed orders	High	Last 7 days

MODULE	CHECK	SEVERITY	EVALUATION WINDOW
	Stores not posted payroll	High	Last 15 days
	Stores not posted weekly inventory	High	Current week
	Users not using DAR application	High	Last 7 days
	Users not using Inventory application	Medium	Last 7 days
	Users not using Schedule application	Medium	Last 7 days

13.2 Altametrics Growth / Plum

MODULE	CHECK	SEVERITY	EVALUATION WINDOW
Billing	Billing not paid	High	Due date + 7 days
Terminals & Devices	Clock offline	Medium	Last sync > 15 min
	PAX offline	High	No comms with primary device
	Plum terminal offline	High	Last sync > 15 min
	Un-batch	High	No settlement > 2 days
Data & Polling	Data not polled in 30 minutes	High	EOCshMain stale > 90 min
	Payroll not posted	High	Past processing window
	Polling instance not live (DC) · PLATFORM	High	Instance not responding
	Sales data not polled — whole day	Critical	No sales polled today
Platform Health	Environment is not live (SSO / application down) · PLATFORM	Critical	App or SSO unavailable
	Hubworks instance not live (DC) · PLATFORM	Critical	Instance not responding
	SSO user login failed · PLATFORM	Medium	Auth service unresponsive
Partner Connector	ACK packet not processed (PC → HW)	Medium	Created 10 min – 2 h, unprocessed
	Catalog packet not processed (PC → HW)	Medium	Created 10 min – 2 h, unprocessed
	Invoice packet not processed (PC → HW)	Medium	Created 10 min – 2 h, unprocessed
	Partner disabled	Medium	Partner inactive
	Unable to scan files from FTP / SFTP	Medium	Scan error, last 20–120 min
Orders	Electronic vendor orders not processing	High	EOOutTracker FAILED, 30–360 min
	Failed online orders at PA	Medium	Item / modifier mapping error
	Online order failed for OLO	High	Validation or processing failure

MODULE	CHECK	SEVERITY	EVALUATION WINDOW
POS Sync	Order not received on receiver from TX Server	High	TX Server unreachable
	PlumPOS config not synced from Hubworks	Medium	Fetch from HW failed
	PlumPOS config not synced to TX Server	Medium	Push to TX failed
	Q-to-Q normalization failed (PlumPOS)	Medium	AnyConnector component down
Data Pipeline	Site not synced to TX Server	High	Consumers down
	Data not out from Plum	High	Unprocessed 1–3 h
	Data stuck in queue	High	Consumers down or slow
	EOOutTracker outbound failed	High	FAILED or NULL, 30 min – 12 h
	Xformity data not outbound	High	Unprocessed 30 min – 12 h

14. Open items for the build

Items that need a decision or a data source before development starts.

#	ITEM
1	Exception persistence. <code>firstSeenAt</code> , status transitions and the audit trail are not modelled yet. Everything age-related in §4 and §10 depends on them.
2	Signal pass rates. §6 needs the real per-category computation plus daily history for sparklines.
3	Usage telemetry. User Activity and Mobile Usage need login and app-session feeds.
4	Severity thresholds. Each check needs its escalation bands defined — currently only a default level exists.
5	Owner and acknowledgement. No exception carries an assignee or an "emailed / acknowledged" state, so two managers can work the same item.
6	Above Store role. Named as an escalation recipient but not selectable as a viewing role.
7	Undefined drill-down columns. <i>Outbound API errors</i> has no KPI columns specified; its detail table would render Store and Client only. Columns need defining before build.
8	Saved views. Users land on the full firehose each session; a persisted default filter set is the most-requested shortcut.

Appendix A — Drill-down columns per check

The columns rendered in each check's detail table, in order. `Client` is suppressed for client logins (§3.1). Platform-level checks replace `Store` with `Service` (§9).

Altametrics Back Office

CHECK	COLUMNS
Inbound API errors	Store · Client · Endpoint · Errors · Top code
Missing labor / sales / PMIX data	Store · Client · Missing data · Last received · Gap
Missing previous-day sales	Store · Client · Business date · POS status · Expected sales
No poll in last 6 hours	Store · Client · Business date · Last poll · Gap · Device
Outbound API errors	Store · Client · columns not yet defined — see §14 item 7
SFTP connection failure	Store · Client · Vendor · Feed · Failed attempts
Sync failure	Store · Client · Connector · Adaptor · Last sync · Error
Forecast posted late	Store · Client · Forecast week · Posted · Days late · Deadline
Forecasted hours vs scheduled hours	Store · Client · Week # · Forecasted hours · Scheduled hours · Variance hours · Variance %
High variance vs actual sales	Store · Client · Week date · System forecast · Manager forecast · Actual sales · Variance
Missing forecast	Store · Client · Forecast date · Forecast Creation Date · Days missing
Above target labor %	Store · Client · Actual labor % · Target % · Over by
Late schedule post	Store · Client · Week · Posted · Days late · Deadline
Minor / labor-law violation	Store · Client · Type · Employees · Detail
Overtime scheduled	Store · Client · Employees · OT hours · Est. cost
Schedule not published	Store · Client · Week · Status · Deadline · Days late
Meal & break violation	Store · Client · Type · Employees · Detail
No-show vs schedule	Store · Client · Shift · Employees · Coverage
Offline clock	Store · Client · Device · Last ping · Punches buffered
Overtime threshold reached	Store · Client · Employees · Hours worked · Threshold
Payroll not posted	Store · Client · Pay period · Stage · Employees
Late delivery	Store · Client · Vendor · Delivery Schedule · Actual Delivery Date · Delay
Manual receiving	Store · Client · Delivery date · PO number · Invoice number · Invoice amount · Received by
Missing invoice on delivery date	Store · Client · Delivery date/time · Vendor · Invoice amount · Missing invoices
Order not posted	Store · Client · Delivery date · PO number · Invoice number · Invoice amount
Order not submitted by cutoff	Store · Client · Vendor · Order date/time · Cutoff · Overdue · Line items
Receiving not confirmed	Store · Client · Vendor · Delivered · Unconfirmed lines

CHECK	COLUMNS
Food cost is high	Store · Client · Inventory date · Count freq · Net sales · Actual \$ · Theo \$ · Variance \$ · Variance %
High variance locations	Store · Client · Inventory date · Count Frequency · Theoretical · Actual · Variance · Var %
Inventory not posted	Store · Client · Inventory date · Expected posting · Count Frequency · Days delayed · Inventory amount
Missing daily inventory	Store · Client · Inventory date · Count Frequency · Status · Days missing
Missing period inventory	Store · Client · Inventory date · Count Frequency · Status · Days overdue
Missing weekly inventory	Store · Client · Inventory date · Count Frequency · Status · Weeks missing
Transfer not posted	Store · Client · Transfer from · Transfer to · Transfer date · Amount
Waste not posted	Store · Client · Business date · Waste amount
Store users not logged in	Store · Client · User name · Last login
Stores not placed orders	Store · Client · Delivery date · PO number · Invoice number · Invoice amount
Stores not posted payroll	Store · Client · Payroll date
Stores not posted weekly inventory	Store · Client · Inventory date · Count freq · Amount
Users not using DAR application	Store · Client · User name · Last login
Users not using Inventory application	Store · Client · User name · Last login
Users not using Schedule application	Store · Client · User name · Last login

Altametrics Growth / Plum

CHECK	COLUMNS
Billing not paid	Store · Client · Billing due date · Activation date · Deactivation date · Delayed
Clock offline	Store · Client · Clock name · Last sync time · Last punch polled
PAX offline	Store · Client · Device · Terminal type · Last sync time
Plum terminal offline	Store · Client · Terminal name · Terminal type · Last sync time
Un-batch	Store · Client · Device · Terminal type · Pending amount · Days unsettled
Data not polled in 30 minutes	Store · Client · Last polled · Store hours · Error
Payroll not posted	Store · Client · Pay period · Scheduled window · Days pending
Polling instance not live (DC)	Service · Environment · Region · Down for · Last response · Status
Sales data not polled — whole day	Store · Client · Business date · Last polled
Environment is not live (SSO / application down)	Service · Environment · Region · Down for · Last response · Status
Hubworks instance not live (DC)	Service · Environment · Region · Down for · Last response · Status
SSO user login failed	Service · Environment · Region · Down for · Last response · Status
ACK packet not processed (PC → HW)	Store · Client · Partner · Packet ID · Created · Error
Catalog packet not processed (PC → HW)	Store · Client · Partner · Packet ID · Created · Error
Invoice packet not processed (PC → HW)	Store · Client · Partner · Packet ID · Created · Error
Partner disabled	Store · Client · Partner · Integration · Disabled since
Unable to scan files from FTP / SFTP	Store · Client · Partner · Endpoint · Last scan · Error
Electronic vendor orders not processing	Store · Client · Partner · Tracker ID · Failed records · Age
Failed online orders at PA	Store · Client · Channel · Failed orders · Reason
Online order failed for OLO	Store · Client · Channel · Failed orders · Reason
Order not received on receiver from TX Server	Store · Client · Order ID · Sent at · Receiver status
PlumPOS config not synced from Hubworks	Store · Client · Component · Last attempt · Error
PlumPOS config not synced to TX Server	Store · Client · Component · Last attempt · Error
Q-to-Q normalization failed (PlumPOS)	Store · Client · Component · Last attempt · Error
Site not synced to TX Server	Store · Client · Sync stage · Started · Status
Data not out from Plum	Store · Client · Tracker · Pending records · Age
Data stuck in queue	Store · Client · Queue · Backlog · Stuck for
EOOutTracker outbound failed	Store · Client · Partner · Tracker ID · Failed records · Age
Xformity data not outbound	Store · Client · Tracker · Pending records · Age