

Coaxial

Low Noise Amplifier

ZX60-33LN+

50Ω

50 to 3000 MHz

Features

- wide bandwidth, 50 to 3000 MHz
- low noise figure 1.0 dB typ.
- output power, up to 17.5 dBm typ.
- protected by US patent 6,790,049

Applications

- front-end amplifier
- cellular
- GPS
- bluetooth
- lab
- instrumentation
- test equipment



CASE STYLE: GC957

Connectors	Model	Price	Qty.
SMA	ZX60-33LN-S+	\$79.95 ea.	(1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.


Electrical Specifications $T_{AMB}=25^{\circ}\text{C}$

MODEL NO.	FREQUENCY (MHz)	DC VOLTS (V)	NOISE FIGURE (dB)		GAIN (dB)					MAXIMUM POWER (dBm)			INTERCEPT POINT (dBm)	VSWR (:1) Typ.			DC OPERATING CURRENT @Pin V+ (mA)	
					over frequency, GHz					Output (1 dB Compr.)								
					Typ.	Max.	0.1	1.0	2.0	3.0	Min. at 2 GHz	Typ.		Min.	Input (no damage)	Typ.		
ZX60-33LN+	50-3000	5.0	1.1	1.9	21.9	18.8	14.5	11.9	13.0	16.5	14.5	+13	32	2.0	1.6	70	80	

Maximum Ratings

Operating Temperature	-40°C to 85°C case
Storage Temperature	-55°C to 100°C
DC Voltage	5.5V
Input Power (no damage)	13 dBm
Power	0.44W

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	wt
.74	.75	.46	1.18	.04	.17	.45	.59	.33	.21	.22	.18	1.00	.37	.18	.106	grams
18.80	19.05	11.68	29.97	1.02	4.32	11.43	14.99	8.38	5.33	5.59	4.57	25.40	9.40	4.57	2.69	23.0

Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS

minicircuits.com

REV. A
M116867
ZX60-33LN+
ED-12875/2
MM/CP
080328
Page 1 of 2

Typical Performance Data/Curves

ZX60-33LN+

FREQUENCY (MHz)	GAIN (dB)		DIRECTIVITY (dB)		VSWR IN (:1)		VSWR OUT (:1)		NOISE FIGURE (dB)		POUT at 1dB COMPR. (dBm)		IP3 (dBm)	
	3V	5V	3V	5V	3V	5V	3V	5V	3V	5V	3V	5V	3V	5V
50.00	21.75	21.99	5.60	5.48	1.89	1.93	1.26	1.27	1.26	1.60	16.47	17.63	28.47	31.95
100.00	21.65	21.94	5.12	4.98	1.78	1.85	1.15	1.12	0.96	1.11	16.67	17.55	28.75	32.29
200.00	21.54	21.84	5.05	4.95	1.77	1.85	1.08	1.07	1.09	0.97	16.68	17.71	29.11	32.08
300.00	21.34	21.63	5.24	5.24	1.79	1.88	1.05	1.11	0.90	0.98	16.66	17.66	29.31	32.09
400.00	21.06	21.32	5.64	5.74	1.83	1.93	1.03	1.16	0.92	0.99	16.93	17.86	29.63	32.27
500.00	20.71	20.94	6.09	6.37	1.88	1.99	1.04	1.22	0.92	1.01	16.83	17.87	29.86	32.51
600.00	20.28	20.47	6.67	7.17	1.94	2.05	1.07	1.28	0.94	1.04	16.94	17.88	29.59	32.48
700.00	19.61	19.76	7.73	8.45	1.87	1.98	1.14	1.35	1.20	1.30	16.80	17.87	29.35	32.33
800.00	19.37	19.46	7.82	8.83	2.03	2.16	1.15	1.40	0.95	1.04	16.79	17.80	29.32	32.03
900.00	19.11	19.19	8.08	9.32	1.78	1.90	1.20	1.42	0.95	1.03	16.61	17.66	29.23	31.29
1000.00	18.80	18.82	8.35	9.88	1.97	2.09	1.22	1.48	0.87	0.96	16.72	17.56	29.10	30.95
1500.00	16.71	16.54	10.35	13.28	2.16	2.27	1.42	1.76	0.85	0.95	15.92	16.91	28.04	30.66
2000.00	14.79	14.51	11.49	14.99	2.14	2.18	1.62	2.01	1.05	1.20	15.62	16.63	27.99	28.58
2500.00	13.42	13.11	11.42	14.60	2.00	1.94	1.75	2.15	1.03	1.18	16.37	16.83	27.92	28.55
3000.00	12.22	11.90	11.12	13.78	1.75	1.63	1.76	2.17	1.20	1.33	16.50	16.95	28.16	28.14

