Scene-aware and Social-aware Motion Prediction for Autonomous Driving

Alfred Nguyen, Baris Sözüdogru

Technical University of Munich

January 06, 2024

Agenda

1. Motivation
2. Method
   - Data collection
   - Filtering process
   - Integration Model
3. Result
   - Scenario Filtering
   - Integration Method
4. Future Work

Agenda

Agenda

Agenda

Previous Integration Model

Distance and Velocity Equations (Ballistic Integration):

Previous Integration Model

Distance and Velocity Equations (Ballistic Integration):

$$s(k+1) = s(k) + dt \cdot v(k) + \frac{dt^2}{2} a(k)$$

$$v(k+1) = v(k) + dt \cdot a(k)$$

Previous Integration Model

Distance and Velocity Equations (Ballistic Integration):

$$s(k+1) = s(k) + dt \cdot v(k) + \frac{dt^2}{2} a(k)$$
$$v(k+1) = v(k) + dt \cdot a(k)$$

Acceleration Equations:

$$a(k) = \frac{2}{dt^2}\Big(s(k+1) - s(k) - dt \cdot v(k)\Big)$$
$$a(k) = \frac{1}{dt}\Big(v(k+1) - v(k)\Big)$$

Previous Integration Model

Distance and Velocity Equations (Ballistic Integration):

$$s(k+1) = s(k) + dt \cdot v(k) + \frac{dt^2}{2} a(k)$$
$$v(k+1) = v(k) + dt \cdot a(k)$$

Acceleration Equations:

$$a(k) = \frac{2}{dt^2}\Big(s(k+1) - s(k) - dt \cdot v(k)\Big)$$
$$a(k) = \frac{1}{dt}\Big(v(k+1) - v(k)\Big)$$

Problem: Accelerations don't add up!

Our Integration Model

Our Distance and Velocity Equations:

Our Integration Model

Our Distance and Velocity Equations:

$$s(t+1) = s(t) + dt \cdot v(t) + c_1 a(t) + c_2 a(t-1)$$
$$v(t+1) = v(t) + c_3 a(t) + c_4 a(t-1)$$

Our Integration Model

Our Distance and Velocity Equations:

$$s(t+1) = s(t) + dt \cdot v(t) + c_1 a(t) + c_2 a(t-1)$$
$$v(t+1) = v(t) + c_3 a(t) + c_4 a(t-1)$$

Our Acceleration Equations:

$$a(k) = -\overline{c_1} a(k-1) + \overline{c_2}\big(s(k+1) - s(k) - dt \cdot v(k)\big)$$
$$a(k) = -\overline{c_3} a(k-1) + \overline{c_4}\big(v(k+1) - v(k)\big)$$

Our Integration Model

Model in matrix form:

$$\begin{bmatrix} a(k-1) \end{bmatrix} = \begin{bmatrix} -a(k) & v(k+1) - v(k) \end{bmatrix} \begin{bmatrix} \overline{c_1} \\ \overline{c_2} \end{bmatrix}$$

$$\begin{bmatrix} a(k-1) \end{bmatrix} = \begin{bmatrix} -a(k) & s(k+1) - s(k) - dt\ v(k) \end{bmatrix} \begin{bmatrix} \overline{c_3} \\ \overline{c_4} \end{bmatrix}$$

Our Integration Model

Model in matrix form:

$$[a(k-1)] = \begin{bmatrix} -a(k) & v(k+1) - v(k) \end{bmatrix} \begin{bmatrix} \overline{c_1} \\ \overline{c_2} \end{bmatrix}$$

$$[a(k-1)] = \begin{bmatrix} -a(k) & s(k+1) - s(k) - dt\ v(k) \end{bmatrix} \begin{bmatrix} \overline{c_3} \\ \overline{c_4} \end{bmatrix}$$

$\Rightarrow$ This can be solved using linear regression.

Agenda

Video demo of the scenarios

Agenda

Results: Integration Method

Accuracy of the prediction for the acceleration (MSE): 3.0955e-03



Results: Integration Method

Rearranging the formula to the distance and velocity gives us these results:

Video demo of predicted car

Agenda

Agenda

1. Motivation
2. Method
   - Data collection
   - Filtering process
   - Integration Model
3. Result
   - Scenario Filtering
   - Integration Method
4. Future Work

Future Work

Scenario Filtering:

Future Work

Scenario Filtering:

- Specify even more scenario for a broader range of use cases.
- Explore other datasets

Future Work

Scenario Filtering:

- Specify even more scenario for a broader range of use cases.
- Explore other datasets

Integration Model:

- Finetune the integration model (adding other parameteres)
- Test the integration model with the neural network for performance (task for the next team)

Thank you for your attention:)

Acceleration Modification in the Y-axis



Acceleration Modification in the Y-axis



Acceleration Modification in the Y-axis



Acceleration Modification in the Y-axis



Motivation for Set-Based Prediction [1]



[1] M. Althoff and S. Magdici, "Set-based prediction of traffic participants on arbitrary road networks," IEEE Transactions on Intelligent Vehicles, vol. 1, no. 2, pp. 187–202, 2016.

SPOT

SPOT: A tool for set-based prediction of traffic participants [2]



Initial configuration and $\mathcal{O}(t)$ for $t \in [1.5\,\mathrm{s}, 2.0\,\mathrm{s}]$

[2] M. Koschi and M. Althoff, "SPOT: A tool for set-based prediction of traffic participants," in Proc. of the IEEE Intelligent Vehicles Symposium, pp. 1679–1686, 2017.

Conclusions

- Item
- Item
- Item

beginframe

Distance and Velocity Equations:

$$s(k+1) = s(k) + dt \cdot v(k) + \frac{dt^2}{2} a(k) \qquad v(k+1) = v(k) + dt \cdot a(k)$$

onslide¡2¿

Acceleration Equations:

$$a(k) = \frac{2}{dt^2}\Big(s(k+1) - s(k) - dt \cdot v(k)\Big) \qquad a(k) = \frac{1}{dt}\Big(v(k+1) - v(k)\Big)$$

endframe

Results: Integration Method





Results: Integration Method

Video demo of predicted car

Our Integration Model

Our Distance and Velocity Equations:

Our Integration Model

Our Distance and Velocity Equations:

$$s(t+1) = s(t) + dt \cdot v(t) + c_1 a(t) + c_2 a(t-1)$$
$$v(t+1) = v(t) + c_3 a(t) + c_4 a(t-1)$$

Our Integration Model

Our Distance and Velocity Equations:

$$s(t+1) = s(t) + dt \cdot v(t) + c_1 a(t) + c_2 a(t-1)$$
$$v(t+1) = v(t) + c_3 a(t) + c_4 a(t-1)$$

Our Acceleration Equations:

$$a(k) = -\overline{c}_1 a(k-1) + \overline{c}_2 \big(s(k+1) - s(k) - dt \cdot v(k)\big)$$
$$a(k) = -\overline{c}_3 a(k-1) + \overline{c}_4 \big(v(k+1) - v(k)\big)$$

Our Integration Model

Model in matrix form:

$$\begin{bmatrix} a(k) \\ a(k) \end{bmatrix} = \begin{bmatrix} -a(k-1) & s(k+1) - s(k) - dt \cdot v(k) & 0 & 0 \\ 0 & 0 & -a(k-1) & v(k+1) - v(k) \end{bmatrix} \begin{bmatrix} \overline{c_1} \\ \overline{c_2} \\ \overline{c_3} \\ \overline{c_4} \end{bmatrix}$$

Our Integration Model

Model in matrix form:

$$\begin{bmatrix} a(k) \\ a(k) \end{bmatrix} = \begin{bmatrix} -a(k-1) & s(k+1) - s(k) - dt \cdot v(k) & 0 & 0 \\ 0 & 0 & -a(k-1) & v(k+1) - v(k) \end{bmatrix} \begin{bmatrix} \overline{c_1} \\ \overline{c_2} \\ \overline{c_3} \\ \overline{c_4} \end{bmatrix}$$

$\Rightarrow$ This can be solved using linear regression.