

Учёт физических параметров сети

Лабораторная работа № 7

Шулуужук А. В.

12 февраль 2025

Российский университет дружбы народов, Москва, Россия

Получить навыки работы с физической рабочей областью Packet Tracer, а также учесть физические параметры сети.

Выполнение лабораторной работы



Рис. 1: физическая рабочая область Packet Tracer

Выполнение лабораторной работы




Рис. 2: территории Donskaya, Pavlovskaya




Рис. 3: серверное помещение здания Donskaya

Выполнение лабораторной работы





Рис. 4: перемещение коммутатора и конечных устройств на территорию Pavlovskaya



The screenshot shows a network simulator window titled "msk-donskaya-avshuluuzhuk-sw-1". It has tabs for "Physical", "Config", "CLI", and "Attributes". The "CLI" tab is active, displaying the "IOS Command Line Interface". The interface shows a series of ping commands being executed from the "msk-donskaya-avshuluuzhuk-sw-1" device to the IP address "10.128.1.6". Each command is followed by a status message indicating the success rate and the number of successful pings out of five.

```
msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echoes to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#enable
Password:
msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echoes to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echoes to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echoes to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echoes to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echoes to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#
```

Рис. 5: проверка соединения




Рис. 6: настройка физических характеристик




Рис. 7: физическая рабочая область Packet Tracer - размещение расстояния между территориями




Рис. 8: проверка соединения сети




Рис. 9: добавление в логическую область два повторителя




Рис. 10: перемещение повторителя на территорию Pavlovskaya





Рис. 11: подключение устройств



The screenshot shows a terminal window titled "msk-donskaya-avshuluuzhuk-sw-1" with tabs for "Physical", "Config", "CLI", and "Attributes". The "CLI" tab is active, displaying the "IOS Command Line Interface". The user has entered the command "enable", followed by "msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6". The output shows three failed ping attempts to 10.128.1.6, each with a success rate of 0 percent. The user then enters "msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.5", and the output shows one failed ping attempt to 10.128.1.5, also with a success rate of 0 percent. The terminal text is as follows:

```
msk-donskaya-avshuluuzhuk-sw-1>enable
Translating "enable"...domain server (255.255.255.255)
% Unknown command or computer name, or unable to find computer address

msk-donskaya-avshuluuzhuk-sw-1#enable
Password:
msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.6

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.128.1.6, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#ping 10.128.1.5

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.128.1.5, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

msk-donskaya-avshuluuzhuk-sw-1#
```

Рис. 12: проверка соединения сети

Выводы

В результате выполнения лабораторной работы были получены навыки работы с физической рабочей областью Packet Tracer, а также учесть физические параметры сети.