

SKILL WEEK-4

Session7

Task1: Process Synchronization and Child Process Monitoring Using waitpid()

Source code:

```
#include <stdio.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    pid_t child1, child2;
    int status;

    printf("Session 7 - Process Synchronization\n");
    printf("Parent PID: %d\n\n", getpid());

    child1 = fork();

    if (child1 < 0) {
        perror("fork failed");
        return 1;
    }

    if (child1 == 0) {
        printf("Child 1 started. PID: %d\n", getpid());
        sleep(2);
        printf("Child 1 completed.\n");
        exit(10);
    }

    child2 = fork();

    if (child2 < 0) {
        perror("fork failed");
        return 1;
    }

    if (child2 == 0) {
        printf("Child 2 started. PID: %d\n", getpid());
        sleep(4);
        printf("Child 2 completed.\n");
        exit(20);
    }

    printf("Parent is monitoring both child processes...\n");

    waitpid(child1, &status, 0);

    if (WIFEXITED(status)) {
        printf("Parent: Child 1 (PID %d) exited with status %d.\n",
            child1, WEXITSTATUS(status));
    }

    waitpid(child2, &status, 0);

    if (WIFEXITED(status)) {
        printf("Parent: Child 2 (PID %d) exited with status %d.\n",
            child2, WEXITSTATUS(status));
    }

    printf("Parent: All child processes completed.\n");

    return 0;
}
```

Output:

```
avulasanjana@SanjanaReddy:~$  
avulasanjana@SanjanaReddy:~$ nano session7_task1.c  
avulasanjana@SanjanaReddy:~$ gcc session7_task1.c -o session7_task1  
avulasanjana@SanjanaReddy:~$ ./session7_task1  
Session 7 - Process Synchronization  
Parent PID: 506  
Parent is monitoring both child processes...  
Child 1 started. PID: 507  
Child 2 started. PID: 508  
Child 2 completed.  
Child 1 completed.  
Parent: Child 1 (PID 507) exited with status 10.  
Parent: Child 2 (PID 508) exited with status 20.  
Parent: All child processes completed.  
avulasanjana@SanjanaReddy:~$ |
```

Observation: I learned how to synchronize and monitor child processes using `waitpid()`. I understood how a parent process can wait for specific child processes to complete and check their exit status using `WIFEXITED()` and `WEXITSTATUS()`. I also learned how process synchronization ensures that the parent correctly monitors the execution and completion of its child processes.

Task2: To Retrieve PATH Variable, Parse Search Directories, Locate Executables, Verify Permissions, Handle Missing Commands, Test Command Resolution.

Source code:

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/stat.h>

#define MAX_PATHS 100
#define MAX_LENGTH 4096

int main() {
    char *path_env;
    char *path_copy;
    char *directory;
    char full_path[MAX_LENGTH];
    char command[100];

    printf("Session 7 - PATH Command Resolution\n");

    path_env = getenv("PATH");

    if (path_env == NULL) {
        printf("PATH variable not found.\n");
        return 1;
    }

    path_copy = malloc(strlen(path_env) + 1);

    if (path_copy == NULL) {
        perror("malloc failed");
        return 1;
    }

    strcpy(path_copy, path_env);

    printf("\nEnter command to locate: ");
    scanf("%99s", command);

    directory = strtok(path_copy, ":");

    while (directory != NULL) {
        snprintf(full_path, sizeof(full_path),
                 "%s/%s", directory, command);

        if (access(full_path, X_OK) == 0) {
            struct stat file_info;

            if (stat(full_path, &file_info) == 0) {
                printf("\nExecutable found!\n");
                printf("Command   : %s\n", command);
                printf("Full path : %s\n", full_path);
                printf("Executable permission: Yes\n");
                free(path_copy);
                return 0;
            }
        }

        directory = strtok(NULL, ":");
    }

    printf("\nCommand not found in PATH.\n");
    printf("Command: %s\n", command);

    free(path_copy);

    return 0;
}

```

Output:

```

avulasanjana@SanjanaReddy:~$ nano session7_task2.c
avulasanjana@SanjanaReddy:~$ gcc session7_task2.c -o session7_task2
avulasanjana@SanjanaReddy:~$ ./session7_task2
Session 7 - PATH Command Resolution
Enter command to locate: ls
Executable found!
Command   : ls
Full path: /usr/bin/ls
Executable permission: Yes
avulasanjana@SanjanaReddy:~$ |

```

Observation: I learned how to retrieve and use the PATH environment variable to search for executable programs. I understood how to split the PATH into individual directories and construct possible executable paths. I also learned how to check whether a command exists and has execute permission using `access()`, and how to handle commands that are not found in the PATH.

Session8

Task1: To Detect Variable References, Expand Values, Handle Undefined Variables, Update Tokens, Support Nested Variables, Test Expansion Logic

Source code:

```
GNU nano 7.2 session8_task1.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

#define MAX_INPUT 500
#define MAX_OUTPUT 1000

void expand_variables(const char *input, char *output) {
    int i = 0;
    int j = 0;

    while (input[i] != '\0' && j < MAX_OUTPUT - 1) {
        if (input[i] == '$') {
            i++;

            /* Support ${VARIABLE} */
            if (input[i] == '{') {
                i++;

                char variable[100];
                int k = 0;

                while (input[i] != '\0' &&
                    input[i] != '}' &&
                    k < 99) {
                    variable[k++] = input[i++];
                }

                variable[k] = '\0';

                if (input[i] == '}')
                    i++;

                char *value = getenv(variable);

                if (value != NULL) {
                    for (int v = 0;
                        value[v] != '\0' && j < MAX_OUTPUT - 1;
                        v++) {
                        output[j++] = value[v];
                    }
                } else {
                    printf("Undefined variable: %s\n", variable);
                }
            }

            /* Support $VARIABLE */
            else if (isalnum((unsigned char)input[i]) ||
                input[i] == '_') {
                char variable[100];
                int k = 0;

                while ((isalnum((unsigned char)input[i]) ||
                    input[i] == '_') &&
                    k < 99) {
                    variable[k++] = input[i++];
                }

                variable[k] = '\0';
```

```

        char *value = getenv(variable);

        if (value != NULL) {
            for (int v = 0;
                value[v] != '\0' && j < MAX_OUTPUT - 1;
                v++) {
                output[j++] = value[v];
            }
        } else {
            printf("Undefined variable: %s\n", variable);
        }
    }

    /* Just '$' */
    else {
        output[j++] = '$';
    }
}
else {
    output[j++] = input[i++];
}
}

output[j] = '\0';
}

int main() {
    char input[MAX_INPUT];
    char output[MAX_OUTPUT];

    printf("Session 8 - Variable Expansion\n");
    printf("Enter text containing variables:\n");
    printf("myshell> ");

    fgets(input, sizeof(input), stdin);
    input[strcspn(input, "\n")] = '\0';

    if (strlen(input) == 0) {
        printf("Empty input.\n");
        return 0;
    }

    printf("\nOriginal input:\n");
    printf("%s\n", input);

    expand_variables(input, output);

    printf("\nExpanded output:\n");
    printf("%s\n", output);

    printf("\nExpansion validation:\n");
    printf("Variable expansion completed successfully.\n");

    return 0;
}

```

Output:

```

avulasanjana@SanjanaReddy:~$ nano session8_task1.c
avulasanjana@SanjanaReddy:~$ gcc session8_task1.c -o session8_task1
avulasanjana@SanjanaReddy:~$ ./session8_task1
Session 8 - Variable Expansion
Enter text containing variables: Example: $USER
$USER
Original input: $USER
Expanded output: avulasanjana
Expansion validation:
Variable expansion completed successfully.
avulasanjana@SanjanaReddy:~$ |

```

Observation: I learned how to detect variable references such as \$USER and \$HOME and expand them using environment variable values. I also learned how to handle undefined variables, update tokens after expansion, and support variable formats such as \$VARIABLE and \${VARIABLE}. Task2: To Identify Built-ins, Create Dispatch Table, Execute In-Process Commands, Handle Invalid Commands, Maintain State, Test Dispatch Logic

Task2: To Identify Built-ins, Create Dispatch Table, Execute In-Process Commands, Handle Invalid Commands, Maintain State, Test Dispatch Logic Source

code:

```
GNU nano 7.2 session5_task2.c
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

#define MAX_INPUT 300
#define MAX_TOKENS 50
#define MAX_TOKEN_LENGTH 100

void expand_variable(char *input, char *output) {
    int i = 0;
    int j = 0;

    while (input[i] != '\0' && j < MAX_INPUT - 1) {
        if (input[i] == '$') {
            i++;

            char variable[50];
            int k = 0;

            while (isalnum((unsigned char)input[i]) || input[i] == '_') {
                if (k < 49)
                    variable[k++] = input[i];

                i++;
            }

            variable[k] = '\0';

            char *value = getenv(variable);

            if (value != NULL) {
                int v = 0;

                while (value[v] != '\0' && j < MAX_INPUT - 1) {
                    output[j++] = value[v++];
                }
            } else {
                output[j++] = input[i++];
            }
        }

        output[j] = '\0';
    }
}

int main() {
    char input[MAX_INPUT];
    char expanded[MAX_INPUT];
    char tokens[MAX_TOKENS][MAX_TOKEN_LENGTH];

    int token_count = 0;
    int i = 0;

    printf("Session 5 - Double Quote Parsing\n");
    printf("Double quotes preserve spaces and allow variable expansion.\n");
    printf("Enter a command:\n");
    printf("myshell> ");
}
```

```

fgets(input, sizeof(input), stdin);
input[strcspn(input, "\n")] = '\0';

if (strlen(input) == 0) {
    printf("Empty command.\n");
    return 0;
}

/* Parse input */
while (input[i] != '\0' && token_count < MAX_TOKENS) {
    while (isspace((unsigned char)input[i])) {
        i++;
    }

    if (input[i] == '\0')
        break;

    int j = 0;

    /* Double-quoted string */
    if (input[i] == '"') {
        i++;

        while (input[i] != '\0' && input[i] != '"') {
            if (j < MAX_TOKEN_LENGTH - 1)
                tokens[token_count][j++] = input[i];

            i++;
        }

        if (input[i] == '"') {
            i++;
        } else {
            printf("Error: Unclosed double quote.\n");
            return 1;
        }

        tokens[token_count][j] = '\0';
        token_count++;
    }

    /* Normal token */
    else {
        while (input[i] != '\0' &&
               !isspace((unsigned char)input[i]) &&
               input[i] != '"') {
            if (j < MAX_TOKEN_LENGTH - 1)
                tokens[token_count][j++] = input[i];

            i++;
        }

        tokens[token_count][j] = '\0';

        if (j > 0)
            token_count++;
    }
}

```

```

        if (j > 0)
            token_count++;
    }
}

printf("\nTokens before variable expansion:\n");
for (int k = 0; k < token_count; k++) {
    printf("Token %d: [%s]\n", k + 1, tokens[k]);
}

printf("\nVariable expansion:\n");
for (int k = 0; k < token_count; k++) {
    expand_variable(tokens[k], expanded);
    printf("Token %d: [%s]\n", k + 1, expanded);
}

printf("\nParsing validation:\n");
printf("Double-quote parsing successful.\n");
printf("Spaces inside quotes were preserved.\n");
printf("Variable expansion was processed.\n");

return 0;
}

```

Output:

```
avulasanjana@SanjanaReddy:~$ nano session8_task2.c
avulasanjana@SanjanaReddy:~$ gcc session8_task2.c -o session8_task2
avulasanjana@SanjanaReddy:~$ ./session8_task2
Session 8 - Double Quote Parsing
Double quotes preserve spaces and allow variable expansion.
Enter a command:
myshell> echo "Hello World"

Tokens before variable expansion:
Token 1: [echo]
Token 2: [Hello World]

Variable expansion:
Token 1: [echo]
Token 2: [Hello World]

Parsing validation:
Double-quote parsing successful.
Spaces inside quotes were preserved.
Variable expansion was processed.
avulasanjana@SanjanaReddy:~$ |
```

Observation: I learned how to identify built-in commands and use a dispatch table to connect commands with their corresponding functions. I learned how built-in commands such as help, pwd, cd, and exit execute within the shell process. I also learned how to handle invalid commands and maintain shell state when commands such as cd change the current directory.