Attenuation-based Light Field Displays

Bachelorarbeit

der Philosophisch-naturwissenschaftlichen Fakultät der Universität Bern

vorgelegt von

Adrian Wälchli

2015

Leiter der Arbeit: Prof. Dr. Matthias Zwicker Institut für Informatik und angewandte Mathematik

Abstract

Abstract goes here

Contents

1	Introduction					
	1.1	Related Work	1			
2	Cap	turing a Light Field	2			
	2.1	The Plenoptic Function and the Light Field	2			
	2.2	Light Field Acquisition				
	2.3	Spectral Analysis	3			
	2.4	Light Field Tomography	3			
A	ap1		4			
	A.1	apsec1	4			
	List	of Tables	5			
	List	of Figures	5			
	Bib	liography	6			

Chapter 1

Introduction

1.1 Related Work

Chapter 2

Capturing a Light Field

2.1 The Plenoptic Function and the Light Field

The plenoptic function, as introduced by [AB91], is a 7D function that describes the intensity of light for every frequency, along every light ray in space, at any time. It is defined as

$$P \colon \mathbb{R}^3 \times [0, 2\pi) \times [0, \pi] \times \mathbb{R}^2 \to \mathbb{R}^+$$
$$(x, y, z, \theta, \phi, t, \lambda) \mapsto P(x, y, z, \theta, \phi, t, \lambda),$$

where the parameters (x,y,z) are the coordinates of a point in 3D space and the angles (θ,ϕ) describe the direction of an incoming light ray at time t. The light's intensity is given for every wavelength λ and thus, the plenoptic function not only captures the visible frequency spectrum but all electromagnetic waves. A commonly used measure for light is the radiance, which is obtained from P by integrating over all wavelengths: $R(x,y,z,\theta,\phi,t) = \int_{\mathbb{R}} P(x,y,z,\theta,\phi,t,\lambda) \, d\lambda$.

In practice, it is impossible to acquire all the data needed to model the 7D plenoptic function and hence it is reasonable to consider only a subset of the parameters. Dropping the time parameter t in $R(x, y, z, \theta, \phi, t)$ yields a 5D function for the radiance in a static scene. As described by [LH96], this five dimensional representation can further be reduced to four dimensions in the following way. The radiance along a line is constant in free space and so, the 5D plenoptic function holds redundant information for the points on this line. Ignoring this redundancy leads to the equivalent 4D parameterization of the ray space. [LH96] propose a parameterization by two parallel planes, as seen in figure 2.1, where the coordinates of the lines (rays) are given by the intersections with the two planes. The 4D light field L(u, v, s, t) is therefore defined as the radiance along the line intersecting the two planes at coordinates (u, v) and (s,t). This two plane parameterization of the light field is the most common one seen in literature, but there are many ways to choose a parameterization. For instance, one can use a plane and two angles to define each ray passing this plane, which would result in a light field $L(u, v, \theta, \phi)$ where $\theta, \phi \in (0, \pi)$.



Figure 2.1: Parametrization of the light field with two planes.

2.2 Light Field Acquisition

For practical applications, the light field must be discretized and so an appropriate sampling method needs to be chosen. One way is to capture the light field with a grid of optical systems, e.g. cameras. Typically, the (u, v)-plane is uniformly sampled on a grid $G_{uv} = \{(u_i, v_j) \mid i = 1, \ldots, n, j = 1, \ldots, m\}$ on the (u, v)-plane with a resolution $n \times m$. The extent in horizontal (vertical) direction is called the horizontal (vertical) baseline. This means that only a slice of the actual light field can be captured and the two planes are clipped to form a rectangle.

The samples on the (u, v)-plane correspond to the virtual positions of the camera. Properties of the light field do not change under re-parameterization.

Orthographic Projections

Perspective Projections

- 2.3 Light Field Tomography
- 2.4 Spectral Analysis

Appendix A ap1

A.1 apsec1

List of Tables

List of Figures

2.1	Parametrization	of the ligh	t field with	two planes	•
Z.I	- гагашентханоп	от тие пет	it neia with	i two bianes.	

Bibliography

- [AB91] ADELSON, E. H.; BERGEN, J.: The Plenoptic Function and the Elements of Early Vision. In: Computational Models of Visual Processing (1991), S. 3–20
- [LH96] Levoy, M. ; Hanrahan, P.: Light Field Rendering. (1996), S. 1-12
- [WLHR11] Wetzstein, G.; Lanman, D.; Heidrich, W.; Raskar, R.: Layered 3D: Tomographic Image Synthesis for Attenuation-based Light Field and High Dynamic Range Displays. In: *ACM Trans. Graph.* 30 (2011), Nr. 4
- [WLHR12] WETZSTEIN, G.; LANMAN, D.; HIRSCH, M.; RASKAR, R.: Tensor Displays: Compressive Light Field Synthesis using Multilayer Displays with Directional Backlighting. In: ACM Trans. Graph. (Proc. SIGGRAPH) 31 (2012), Nr. 4, S. 1–11
 - [Yan10] Yan, Ming: Convergence Analysis of SART by Bregman Iteration and Dual Gradient Descent. (2010), S. 1–15

<u>Erklärung</u>

gemäss Art. 28 Abs. 2 RSL 05

Name/Vorname:	
Matrikelnummer:	
Studiengang:	
	Bachelor
Titel der Arbeit:	
LeiterIn der Arbeit:	
Ich erkläre hiermit, o	dass ich diese Arbeit selbständig verfasst und keine anderen als die
	n benutzt habe. Alle Stellen, die wörtlich oder sinngemäss aus Quellen
	habe ich als solche gekennzeichnet. Mir ist bekannt, dass andernfalls
_	rtikel 36 Absatz 1 Buchstabe o des Gesetztes vom 5. September 1996 um Entzug des auf Grund dieser Arbeit verliehenen Titels berechtigt ist.
Ort/Datum	
	Unterschrift