Physics-Informed Neural Networks for Urban Air Pollution Modelling: Analysis, Simulation and Prediction of $PM_{2.5}$ over Delhi

Mohammad Zaid Agha 2024ADPS0840G
Adwait Eklavya 2024ADPS0825G
Shivank Mishra 2024ADPS0823G
Asvin Subderiyal 2024ADPS0867G
Rayasam Venkata Pradyumn 2024B5AD0973G

Abstract

We model the hourly, mixing-layer-averaged concentration of fine particulate matter ($PM_{2.5}$) over Delhi with a two-dimensional, time-dependent advection–diffusion–reaction (ADR) equation and embed it in a physics-informed neural network (PINN). Wind and boundary-layer height are taken from the ERA5 reanalysis; the eddy diffusivity, a spatial emission field and a diurnal emission profile are learned. We analyse the equation (non-dimensionalisation, Fourier stability and equilibrium, mass balance, positivity, identifiability and forward sensitivity), verify our implementation against an exact Gaussian-puff solution, and evaluate the PINN in two settings, always on monitoring stations withheld from training: (i) a synthetic twin in which the truth is generated by a reference finite-difference solver driven by real ERA5 forcing and sampled at the 45 real monitor locations, and (ii) observed $PM_{2.5}$ from 45 and 42 regulatory monitors in a severe winter window (10–20 November 2025) and a moderate spring window (1–11 March 2025). On the synthetic twin the PINN reduces the held-out RMSE from 29.9 ± 9.9 to 22.1 ± 3.1 µg/m^3 relative to an identical network trained without physics, and the whole-field RMSE from 54.5 to 31.3 µg/m^3. On observed data the physics term again improves on the data-only network in all six runs (e.g. winter 83.3 versus 111.4 µg/m^3) and yields fields whose PDE residual is 3.7–8 times smaller, but it does *not* outperform simple spatial baselines: inverse-distance weighting and the training-station mean are statistically indistinguishable in winter and better in spring. We trace this negative result to the dominance of a spatially coherent regional signal and to specific simplifications of the model, and we show that the eddy diffusivity is not identifiable from these data, as the Péclet-number analysis predicts.

Contents

1 Introduction and motivation **3**

2 Problem definition and objectives **3**

3 Background and related work **3**

4 Data **4**

5 Assumptions **6**

6 Mathematical formulation **6**
6.1 Governing equation 6
6.2 Non-dimensionalisation and dimensionless groups 7
6.3 PDE residual 7

7 Mathematical analysis **7**
7.1 Stability of the continuous problem 7
7.2 Equilibrium 8
7.3 Mass balance and positivity 8
7.4 Identifiability 8
7.5 Forward sensitivity 8

8 Numerical methodology **9**
8.1 Reference finite-difference solver 9
8.2 PINN architecture 9
8.3 Loss function 10
8.4 Evaluation protocol 10

9 Numerical simulations: the synthetic twin **11**

10 Results and interpretation **13**
10.1 Synthetic twin 13
10.2 Observed data 16

11 Limitations **19**

12 Conclusion **19**

1 Introduction and motivation

Delhi regularly records some of the highest urban $PM_{2.5}$ concentrations in the world; in our winter window the mean over 45 regulatory monitors was 258 µg/m^3, about seventeen times the World Health Organization 24-hour guideline value of 15 µg/m^3. Health-relevant exposure varies across the city, yet concentrations are measured only at a few dozen points. Estimating the concentration *between* monitors is therefore a central practical problem.

Two classes of method exist. Chemical transport models solve conservation laws for many species on a grid but need detailed emission inventories and meteorology [16, 18]. Purely statistical methods (interpolation, regression, machine learning) need neither, but carry no physical structure: nothing prevents a neural network fitted to monitors from producing a field that could not have been produced by the wind actually blowing. Physics-informed neural networks [8, 15] sit between the two: a network represents the concentration field and is trained to fit the observations *and* to satisfy a governing partial differential equation (PDE) at arbitrary points of space and time. The question this project asks is whether, and when, that physical constraint improves estimates at locations the model has never seen.

2 Problem definition and objectives

Problem. Given hourly $PM_{2.5}$ at a set of monitoring stations in Delhi and hourly reanalysis meteorology, estimate the concentration field $C(x, y, t)$ over the city, in particular at monitor locations withheld from training.

Objectives.

1. Formulate a transport model whose every input is either measured, estimated from public data, or learned, and state its assumptions explicitly.
2. Analyse the model mathematically: scaling, stability, equilibria, conservation and identifiability.
3. Implement and verify a PINN for this model, with tests against exact solutions.
4. Compare the PINN with an identical network trained without physics and with conventional baselines, on held-out monitors, using MAE, RMSE, R^2 and the PDE residual.
5. Determine whether the physics improves generalisation in a controlled synthetic experiment and on observed data, and explain the outcome in either case.

3 Background and related work

Atmospheric dispersion. Mass conservation for a passive or slowly reacting tracer leads to the advection–diffusion–reaction equation; with turbulent fluxes closed by an eddy-diffusivity (K-theory) assumption it is the basis of most dispersion models [16, 18]. The Gaussian plume is its steady-state solution for a point source in uniform wind and is used for stack emissions; it requires known point sources, which are not available for city-wide $PM_{2.5}$. Diurnal variation of the atmospheric boundary layer is a dominant control on near-surface concentrations [19].

Physics-informed neural networks. Raissi et al. [15] introduced PINNs for forward and inverse problems; Karniadakis et al. [8] review the field. Training is a multi-objective optimisation and is known to fail when loss terms have very different gradient magnitudes [20] and for advection-dominated or stiff problems [10]. Both pathologies appear in our study and inform our design (non-dimensionalisation, weight selection, time-domain decomposition).

Baselines. Inverse-distance weighting [17] is the classical interpolation method for scattered stations; random forests [2] are a strong general-purpose regressor.

4 Data

Table 1: Data sources and the status of every quantity in the model.

Quantity	Status	Source	Resolution
$PM_{2.5}$ at monitors	Observed	CPCB/DPCC/IMD/IITM via OpenAQ [3, 13]	15 min → hourly
Wind u, v (10 m)	Estimated	ERA5 [6] via Open-Meteo [12]	hourly, ≈25 km
Boundary-layer height H	Estimated	ERA5 via Open-Meteo	hourly
Removal rate λ	Fixed (literature scale)	§5	constant
Diffusivity D, emissions q, g	Calibrated (learned)	PINN	—
Twin truth fields	Synthetic	reference solver, §9	1 km, hourly

Monitors. The OpenAQ v3 API lists 97 locations measuring $PM_{2.5}$ in the study box (28.40–28.88°N, 76.84–77.35°E). We keep regulatory monitors only (excluding seven low-cost sensors) whose reporting period covers the window, and download their daily files from the public OpenAQ archive. The cleaning pipeline (`src/data/preprocessing.py`, unit-tested) removes sentinel and invalid values (negative, > 2000 µg/m^3), rejects non-µg/m^3 units, converts IST to UTC, averages 15-minute values to hourly means, collapses duplicate timestamps, removes stuck sensors (six or more identical consecutive hours) and drops stations with less than 75 % hourly coverage. Table 2 summarises the result and Figure 1 shows the stations.

Table 2: Observed data after cleaning (raw counts are 15-minute records).

Window	Raw records	Hourly values	Stations	Mean $PM_{2.5}$ (µg/m^3)
Winter, 10–20 Nov 2025	43 339	9 828	45	258
Spring, 1–11 Mar 2025	45 039	9 693	42	67

Choice of windows. We planned a winter window in November 2024; the OpenAQ archive, however, holds files for only 1 of 55 regulatory monitors in that month, so the winter window was moved to the same dates in 2025 (47 monitors complete). This is a data constraint, not a choice based on results.

Spatial support. Inter-station correlation of hourly $PM_{2.5}$ has median 0.70 (winter) and 0.73 (spring): a strong common signal with genuine local deviations (station means range from 117 to 369 µg/m^3 in winter). Thirty-odd stations over $\approx 50\,\text{km} \times 50\,\text{km}$ cannot resolve the field continuously; we never present interpolated values as measurements, and every map in this report is either a model evaluation or a synthetic truth.




Figure 1: Regulatory monitors used in each window, coloured by window-mean $PM_{2.5}$ and marked by role in the seed-42 split (OBSERVED). Axes: local tangent plane centred at 28.63°N, 77.15°E.




Figure 2: Observed hourly $PM_{2.5}$: median and 10–90 % range across monitors (left) and the diurnal cycle (right). The night-time maximum and afternoon minimum mirror the diurnal cycle of the boundary layer.

5 Assumptions

A1 **Well-mixed layer.** $PM_{2.5}$ is vertically uniform within a mixing layer of depth $H(t)$, so the concentration measured at the surface represents the layer average. This reduces the problem from 3D to 2D.

A2 **Uniform, time-varying wind.** The transporting wind $(u(t), v(t))$ is spatially uniform over the domain and equal to the ERA5 10 m wind at the domain centre. ERA5's ≈ 25 km grid cannot resolve intra-urban variations, so we do not pretend to model them.

A3 **K-theory closure.** Turbulent horizontal fluxes are $-D\nabla C$ with a constant, isotropic eddy diffusivity $D \in [10, 2000]$ m^2/s.

A4 **Linear removal.** Dry deposition and other first-order losses act at a constant rate $\lambda = 5 \times 10^{-6}$/s (an e-folding time of 2.3 days, the order of magnitude of a deposition velocity of ~ 0.1 cm/s over a 200 m layer); secondary aerosol chemistry is not modelled.

A5 **Separable emissions.** Emissions are a non-negative spatial flux $q(x, y)$ modulated by a 24-hour profile $g(\tau)$ with mean one, injected into the mixing layer: $S = q\, g / \max(H, H_{\min})$, with $H_{\min} = 50$ m to avoid the singularity at the very small ERA5 night-time values ($\approx$10 m).

A6 **Boundaries.** Inflow concentrations (regional background) are unknown; we impose only a weak zero-normal-gradient condition on outflow faces.

A7 **No entrainment term.** The dilution of the layer when it deepens, and the exchange with the residual layer aloft, are not represented (the term derived in Section 6.1 is omitted). This is not a small correction: during the morning growth of the boundary layer, from $\sim$50 m to $\sim$1500 m in about five hours, $(1/H)\,\mathrm{d}H/\mathrm{d}t \approx 2 \times 10^{-4}$ s^{-1}, about forty times the removal rate λ. For a few hours each day it is therefore the largest loss term in the equation. We omit it to keep the forcing to quantities available from ERA5 and to avoid introducing the unknown residual-layer concentration C_r; Sections 7.5 and 10.2 discuss its consequences.

A7 **No entrainment term.** The dilution of the layer when it deepens, and the exchange with the residual layer aloft, are not represented (the term derived in Section 6.1 is omitted). This is not a small correction: during the morning growth of the boundary layer, from $\sim$50 m to $\sim$1500 m in about five hours, $(1/H)\,\mathrm{d}H/\mathrm{d}t \approx 2 \times 10^{-4}$ s^{-1}, about forty times the removal rate λ. For a few hours each day it is therefore the largest loss term in the equation. We omit it to keep the forcing to quantities available from ERA5 and to avoid introducing the unknown residual-layer concentration C_r; Sections 7.5 and 10.2 discuss its consequences.

6 Mathematical formulation

6.1 Governing equation

Conservation of tracer mass in a control volume of the mixing layer, with the fluxes of A2–A3, the sink of A4 and the source of A5, gives

$$\frac{\partial C}{\partial t} + u(t)\frac{\partial C}{\partial x} + v(t)\frac{\partial C}{\partial y} = D\left(\frac{\partial^2 C}{\partial x^2} + \frac{\partial^2 C}{\partial y^2}\right) - \lambda C + \frac{q(x,y)\, g(\tau(t))}{\max\{H(t), H_{\min}\}}, \tag{1}$$

on $\Omega \times (0, T]$, $\Omega = [x_{\min}, x_{\max}] \times [y_{\min}, y_{\max}]$ (49.8 km by 53.4 km), where $\tau(t)$ is the local hour. Units: C in μg m^{-3}, q in μg m^{-2} s^{-1}, so every term is in μg m^{-3} s^{-1}. For the PINN the initial condition is not prescribed: $C(\cdot, 0)$ is known only at stations and enters through the data loss. On outflow faces ($\boldsymbol{u} \cdot \boldsymbol{n} > 0$) we impose $\nabla C \cdot \boldsymbol{n} = 0$; for the synthetic truth inflow faces additionally carry the Dirichlet value $C = C_{\text{in}}$.

Omitted dilution term. The source term in (1) follows from a mass balance on an air column of unit horizontal area and depth $H(t)$, which contains the mass $M = HC$:

$$\frac{\partial(HC)}{\partial t} + \nabla\cdot(H\mathbf{u}C) = \nabla\cdot(HD\nabla C) + q\,g - \lambda HC.$$

Because H depends on time only, dividing by H recovers (1) together with one additional term, $-(C/H)\,\mathrm{d}H/\mathrm{d}t$, which arises from the time derivative of the product HC. This term represents dilution of the pollutant already in the layer as the layer deepens. In its physically consistent form it acts only during growth and dilutes towards the concentration C_r of the residual layer aloft,

$$-\,\frac{\max\{0,\ \mathrm{d}H/\mathrm{d}t\}}{H}\,\big(C - C_r\big),$$

since a collapsing layer leaves air behind rather than compressing it. Equation (1) omits this term (A7). The model is therefore only partly consistent: the column balance is used for the source $q\,g/H$ but not for the storage term, so the dilution of new emissions is represented but the dilution of the existing pollutant is not.

6.2 Non-dimensionalisation and dimensionless groups

With $x' = (x - x_c)/L$, $y' = (y - y_c)/L$, $t' = 2t/T - 1$ and $C' = C/C_{\mathrm{ref}}$, where $L = 26.7\,\mathrm{km}$ is the half-width, T the window length and C_{ref} the mean training concentration, equation (1) becomes

$$\frac{\partial C'}{\partial t'} + U\frac{\partial C'}{\partial x'} + V\frac{\partial C'}{\partial y'} = K\nabla'^2 C' - \Lambda C' + S', \qquad U = \frac{uT}{2L},\ V = \frac{vT}{2L},\ K = \frac{DT}{2L^2},\ \Lambda = \frac{\lambda T}{2},\ S' = \frac{S\,T}{2C_{\mathrm{ref}}}. \tag{2}$$

The physically meaningful groups are the Péclet and Damköhler numbers over the domain size $\ell \approx 50\,\mathrm{km}$ and a typical wind $\bar{u} \approx 1.5\,\mathrm{m/s}$:

$$\mathrm{Pe} = \frac{\bar{u}\,\ell}{D} \approx 75\text{–}750, \qquad \mathrm{Da} = \frac{\lambda\,\ell}{\bar{u}} \approx 0.17, \qquad t_{\mathrm{adv}} = \frac{\ell}{\bar{u}} \approx 9\,\mathrm{h}. \tag{3}$$

Transport is advection-dominated ($\mathrm{Pe} \gg 1$), removal is weak over one transit ($\mathrm{Da} \ll 1$), and air crosses the city in hours, so *hourly* data can in principle see transport between stations. For the PINN on 80-hour windows, $U \approx 5.4\,u/(\mathrm{m/s})$, $K \approx 0.06$ and $\Lambda \approx 0.72$: all coefficients are $O(10^{-2})$–$O(10)$, which keeps the residual well scaled.

6.3 PDE residual

For a candidate field $\hat{C}'$ the residual

$$r = \frac{\partial \hat{C}'}{\partial t'} + U\frac{\partial \hat{C}'}{\partial x'} + V\frac{\partial \hat{C}'}{\partial y'} - K\nabla'^2\hat{C}' + \Lambda\hat{C}' - S' \tag{4}$$

vanishes identically for an exact solution. All derivatives are computed exactly by automatic differentiation [1].

7 Mathematical analysis

7.1 Stability of the continuous problem

Proposition 1 (Fourier stability)**.** *For constant coefficients, the homogeneous part of* (1) *on* $\mathbb{R}^2$ *damps every Fourier mode.*

Proof. Substituting $C = \hat{c}\,e^{i\boldsymbol{k}\cdot\boldsymbol{x}+\sigma t}$ gives $\sigma = -i\,\boldsymbol{u}\cdot\boldsymbol{k} - D|\boldsymbol{k}|^2 - \lambda$, so $\mathrm{Re}\,\sigma = -(D|\boldsymbol{k}|^2 + \lambda) < 0$ for all $\boldsymbol{k}$ when $D \geq 0$ and $\lambda > 0$. Advection only rotates the phase; diffusion damps short waves fastest and removal damps all modes at rate λ. □

Consequently perturbations of the initial state are forgotten on the time scale $1/\lambda \approx 56\,\mathrm{h}$ (or faster, by outflow through the boundary on the scale t_{adv}), which justifies spinning the synthetic truth up for 24 h and not prescribing an initial field for the PINN.

7.2 Equilibrium

For spatially uniform, constant source S_0 the spatially uniform solution obeys $\dot{C} = S_0 - \lambda C$, so

$$C(t) = \frac{S_0}{\lambda} + \Big(C_0 - \frac{S_0}{\lambda}\Big)e^{-\lambda t} \;\longrightarrow\; C^* = \frac{S_0}{\lambda}, \tag{5}$$

a globally asymptotically stable equilibrium. With the diurnal factor $g(\tau)/H(t)$ the forcing is periodic and the solution converges instead to a periodic orbit; the large day–night ratio of H (up to ~ 40 in our windows, Figure 5) produces the night-time maxima seen in Figure 2. Both the decay and the approach to C^* are unit tests of our solver.

7.3 Mass balance and positivity

Integrating (1) over Ω gives

$$\frac{d}{dt}\int_\Omega C\,dA = \int_\Omega S\,dA - \lambda\int_\Omega C\,dA - \oint_{\partial\Omega}\big(\boldsymbol{u}C - D\nabla C\big)\cdot\boldsymbol{n}\,ds, \tag{6}$$

so in the absence of removal, sources and boundary flux the total mass is conserved (tested to 10^{-3} for the solver). By the parabolic maximum principle, $C_0 \geq 0$, $S \geq 0$ and non-negative inflow values imply $C \geq 0$; the PINN enforces $C \geq 0$ and $q \geq 0$ by construction through a softplus output. [1]

7.4 Identifiability

Two structural issues determine which parameters the data can constrain.

1. **The source can absorb the residual.** If S were an unrestricted function of (x, y, t), any field $\hat{C}$ would satisfy (4) with $S := \partial_t\hat{C} + \boldsymbol{u}\cdot\nabla\hat{C} - D\nabla^2\hat{C} + \lambda\hat{C}$, and the physics loss would carry no information. We therefore restrict S to the separable form A5 (q: a two-layer network of 32 units with a smoothness penalty; g: 24 values), so the time dependence of the source is fixed up to 24 numbers and the remaining space–time structure must be explained by transport.

2. **The diffusivity is weakly identifiable.** With Pe $= O(10^2$–$10^3)$ diffusion contributes a small fraction of the transport; changes in D barely alter concentrations at the stations (Section 7.5). We therefore expect D to be poorly determined, and test this directly.

7.5 Forward sensitivity

We re-ran the reference solver of Section 8 with one parameter varied at a time and sampled the result at the 45 monitor locations (Figure 3). Over the ranges shown the elasticity $\partial\ln\bar{C}/\partial\ln p$ of the station-mean concentration is -0.15 for λ, -0.03 for D and -0.35 for $H_{\min}$. The near-zero sensitivity to D is the quantitative form of the identifiability argument; the mixing-height floor, a modelling choice, matters more than either physical rate.

We attribute this partly to the omitted dilution term (A7): the night-time floor and the morning transition out of it are the parts of the boundary-layer cycle that the model represents least well, and without the dilution term the night-time accumulation is removed only by advection and the slow sink λ, so the result depends strongly on how deep the night-time layer is assumed to be.We attribute this partly to the omitted dilution term (A7): the night-time floor and the morning transition out of it are the parts of the boundary-layer cycle that the model represents least well, and without the dilution term the night-time accumulation is removed only by advection and the slow sink λ, so the result depends strongly on how deep the night-time layer is assumed to be.

[1] Equation (6) is the balance for the model as written. The physically conserved quantity is the column mass $\int_\Omega HC\,\mathrm{d}A$, which equation (1) conserves only when H is constant; see Section 6.1.




Figure 3: Forward-model sensitivity of station concentrations to λ, D and $H_{\min}$ (one at a time, reference solver, 3-day winter forcing). Values relative to the baseline run.

8 Numerical methodology

8.1 Reference finite-difference solver

For the synthetic twin and for verification we solve (1) by the method of lines on a cell-centred grid ($\Delta x = \Delta y = 1\,\mathrm{km}$, 51×54 cells) [7]: third-order upwind-biased differences for advection (for $u > 0$, $\partial_x C_i \approx (2C_{i+1} + 3C_i - 6C_{i-1} + C_{i-2})/6\Delta x$), second-order central differences for diffusion, and the strong-stability-preserving third-order Runge–Kutta method in time [5]. Two ghost cells carry Dirichlet values on inflow faces and zero-gradient extrapolation on outflow faces.

Stability (von Neumann). For the central diffusion operator the semi-discrete symbol is $-\frac{4D}{\Delta x^2}\sin^2\frac{\theta_x}{2} - \frac{4D}{\Delta y^2}\sin^2\frac{\theta_y}{2}$, whose most negative value is $-4D(\Delta x^{-2} + \Delta y^{-2})$. SSP-RK3 is stable on the negative real axis up to $|z| \approx 2.51$, so explicit stability requires $D\Delta t(\Delta x^{-2} + \Delta y^{-2}) \lesssim 0.63$; we use 0.25. For advection we limit the Courant number $\Delta t(|u|/\Delta x + |v|/\Delta y) \le 0.5$, inside the stability region of the upwind-biased/RK3 combination. The time step is the smaller of the two limits.

Verification. The solver reproduces pure exponential decay and the approach to $C^* = S_0/\lambda$ to a relative error of 10^{-5}, conserves mass to 10^{-3}, and converges to the exact advected–diffusing Gaussian puff

$$C(\boldsymbol{x}, t) = \frac{M}{4\pi D t}\exp\Big(-\frac{|\boldsymbol{x} - \boldsymbol{x}_0 - \boldsymbol{u}t|^2}{4Dt} - \lambda t\Big) \tag{7}$$

with relative L^2 errors 1.4×10^{-2}, 1.1×10^{-3} and 1.9×10^{-4} on 750 m, 375 m and 188 m grids (observed orders 3.7 and 2.6, consistent with third-order advection combined with second-order diffusion).

8.2 PINN architecture

The concentration network (Figure 4) maps dimensionless $(x', y', t') \in [-1, 1]^3$ to

$$\hat{C}' = \mathrm{softplus}\big(\mathrm{MLP}(x', y', t')\big),$$

with five hidden layers of 64 units, tanh activations and Glorot initialisation [4]. The activation must be smooth: with ReLU the second derivatives in the diffusion term would vanish almost everywhere. Meteorology is *not* an input, so that $\partial\hat{C}/\partial t$ is the true partial derivative of the field; it enters only through the coefficients of (2). The diffusivity is $D = D_{\min} + (D_{\max} - D_{\min})\,\sigma(\theta_D)$ with σ the logistic function, initialised at $300\,\mathrm{m}^2/\mathrm{s}$.




Figure 4: PINN architecture. The concentration network and the source model are trained jointly with the bounded diffusivity D; wind and mixing height are fixed inputs to the residual.

8.3 Loss function

With N_d training observations, N_c collocation points and N_b boundary points,

$$\mathcal{L} = w_d \mathcal{L}_{\text{data}} + w_p \mathcal{L}_{\text{phys}} + w_b \mathcal{L}_{\text{bc}} + w_i \mathcal{L}_{\text{ic}} + w_s \mathcal{L}_{\text{src}}, \tag{8}$$

$$\mathcal{L}_{\text{data}} = \frac{1}{N_d} \sum_j \big(\hat{C}'(\boldsymbol{z}_j) - C'_j\big)^2, \qquad \mathcal{L}_{\text{phys}} = \frac{1}{N_c} \sum_k r(\boldsymbol{z}_k)^2, \tag{9}$$

$$\mathcal{L}_{\text{bc}} = \frac{1}{N_b} \sum_m \mathbb{1}[\boldsymbol{u} \cdot \boldsymbol{n}_m > 0] \left(\nabla \hat{C}' \cdot \boldsymbol{n}_m\right)^2, \qquad \mathcal{L}_{\text{src}} = \overline{|\nabla q|^2} + \tfrac{1}{24} \textstyle\sum_h (g_{h+1} - 2g_h + g_{h-1})^2. \tag{10}$$

$\mathcal{L}_{\text{ic}}$ (misfit to a known initial field) is used only for testing: on real data the initial field is known only at stations and is already part of $\mathcal{L}_{\text{data}}$. We use $w_d = 1$, $w_b = 0.1$, $w_s = 10^{-3}$, $w_i = 0$, and select w_p as described in Section 9. The *data-only network* is the identical model and optimiser with $w_p = w_b = w_s = 0$; only its concentration network is trained.

Training. Adam [9] for 6000 iterations with the learning rate decaying exponentially from 10^{-3} to 10^{-4}; 4096 collocation points (Latin hypercube [11]) and 512 boundary points, resampled every 250 iterations. Validation stations are evaluated every 100 iterations and the weights with the lowest validation error are kept; validation stations never contribute gradients. Implementation in PyTorch [14]. We also implemented gradient-norm balancing of w_p [20]; started from $w_p = 1$ it adapted too slowly and was not competitive, so we report fixed weights.

Time-domain decomposition. The twin windows are 73 h long. Real windows are 240 h; the advective coefficient U grows with T and a single network must represent ten diurnal cycles, both known causes of PINN failure [10]. We therefore split each real window into three consecutive 80-hour chunks and train one data-only network and one PINN per chunk.

8.4 Evaluation protocol

Stations, not observations, are split into training (70 %), validation (15 %) and test (15 %) sets. Stations closer than 1 km (co-located instruments, e.g. two at Pusa) are grouped so that a test station never has a near-duplicate in training; leakage is asserted in code. All models use the same split. We repeat with three or four splits (seeds) and report mean ± standard deviation of MAE, RMSE, R^2 and bias at the test stations. Baselines: the hourly mean of the training stations (a spatially uniform field), inverse-distance weighting with power 2 [17], and a random forest [2] on (x, y, t), hour of day and ERA5 u, v, H.

9 Numerical simulations: the synthetic twin

Design. The truth is the solution of (1) by the reference solver with $D = 300\,\mathrm{m}^2/\mathrm{s}$, $\lambda = 5 \times 10^{-6}\,\mathrm{s}^{-1}$, inflow $C_{\mathrm{in}} = 60\,\mu\mathrm{g}/\mathrm{m}^3$, a background flux of $0.4\,\mu\mathrm{g}/(\mathrm{m}^2\,\mathrm{s})$ plus three Gaussian hotspots (illustrative, not an inventory), and a traffic-like diurnal profile, driven by the *real* ERA5 forcing of 12–15 November 2024 (Figure 5) after a 24-hour spin-up. It is sampled hourly at the 45 real monitor locations with 5 % multiplicative noise (Figure 6). The twin is *model-correct*: the PINN's structural form matches the truth, so it measures what the method can achieve when its assumptions hold, and lets us score the whole field, not just stations.




Figure 5: ERA5 forcing used for the synthetic twin (estimated quantities). Grey band: the 3-day twin window.

Choice of the physics weight. Figure 7 shows the effect of w_p. At $w_p = 1$ the physics term dominates the gradient (its initial value is ≈ 12 against ≈ 0.55 for the data term) and the optimiser under-fits the data, a manifestation of the imbalance described by Wang et al. [20]; accuracy improves steadily as w_p decreases to 0.003–0.01. We fixed $w_p = 0.01$ for all subsequent experiments, including the real data, *before* running them.




Figure 6: Synthetic emission field and the station split (seed 42) at the real monitor locations.




Figure 7: Synthetic twin: held-out-station and whole-field RMSE against w_p (seed 42).

10 Results and interpretation

10.1 Synthetic twin

Table 3: Synthetic twin, held-out stations (mean ± s.d. over 4 splits; µg/m^3). Field RMSE is against the known truth on the 1 km grid every 3 h.

Model	RMSE	MAE	Field RMSE
IDW	43.8 ± 9.5	28.8 ± 6.4	—
Random forest	43.8 ± 5.6	27.0 ± 3.0	—
Data-only NN	29.9 ± 9.9	18.9 ± 3.9	54.5 ± 9.6
PINN ($w_p = 0.01$)	$\mathbf{22.1 \pm 3.1}$	$\mathbf{15.1 \pm 1.6}$	$\mathbf{31.3 \pm 2.3}$

Table 3 and Figure 8 summarise the twin. The PINN has the lowest error and, notably, the smallest spread across splits. It beats the data-only network at the held-out stations in three of four splits and on the whole field in all four, by 43 % on average: the improvement is largest away from stations, where the data alone say nothing and the PDE propagates information along the wind (Figure 9; the PINN has the lower field error in 72 of 73 hours for seed 42). The same experiment on an earlier, randomly placed 36-station layout gave the same ordering (RMSE 24.9 ± 6.8 versus 31.2 ± 8.7; field 31.5 versus 49.3), so the result does not depend on the station geometry. Figure 10 shows why early stopping matters for the data-only network: its validation error rises after ≈ 2000 iterations while the PINN's keeps falling.




Figure 8: Synthetic twin: model comparison over four station splits (dots: individual splits).

Physical consistency. The PINN's fields satisfy the PDE far better than the data-only network's: its median residual is 0.35 against 1.35 even after we freeze the data-only field and fit an emission model and D to it (Figure 11). Fitting the stations is therefore not sufficient to produce a transport-consistent field.

Parameter recovery. Figure 12 confirms the identifiability analysis. Although D was initialised at its true value of 300 m^2/s, every split drives it to 58–60 m^2/s: the data are consistent with a broad range of diffusivities and the optimiser trades diffusion for other degrees of freedom. The diurnal profile, by contrast, is recovered well (both peaks and the night-time minimum), with the evening peak about an hour late.




Figure 9: Synthetic twin: truth and reconstructions at the hour of largest spatial variance (chosen by rule, seed 42), absolute errors, and field RMSE at every hour. Every panel is a model evaluated on the grid.




Figure 10: Synthetic twin training history (seed 42). Left: data and validation losses. Right: unweighted PINN loss terms.




Figure 11: Synthetic twin: absolute PDE residual at 20 000 random points (seed 42).




Figure 12: Synthetic twin: learned D against the truth, and learned versus true diurnal profile.

Table 4: Observed $PM_{2.5}$, held-out monitors: RMSE ($\mu g/m^3$), mean $\pm$ s.d. over 3 splits; 6–8 test monitors and 1 372–1 726 test hours per run. $w_p = 0.01$ fixed in advance.

Model	Winter (mean 258)	Spring (mean 67)
Training-station mean	84.8 ± 21.2	$\mathbf{29.7 \pm 4.6}$
IDW	84.4 ± 19.2	33.2 ± 3.8
Random forest	94.2 ± 20.4	36.8 ± 4.1
Data-only NN	111.4 ± 62.5	41.4 ± 2.8
PINN	$\mathbf{83.3 \pm 24.7}$	33.1 ± 3.7

10.2 Observed data

Table 4 and Figures 13–15 give the real-data results. Three findings stand out.

1. **Physics regularises the network.** The PINN is better than the identical data-only network in all six runs, and much more stable: the data-only network's winter RMSE ranges from 65 to 182 µg/m^3 across splits, the PINN's from 61 to 110.

2. **The PINN's fields are more physically consistent.** Its median PDE residual is 0.61 (winter) and 0.50 (spring), against 2.24 and 4.13 for the data-only field with a post-hoc fitted source (Figure 16).

3. **The PINN does not beat simple spatial baselines.** In winter, PINN, IDW and the station mean differ by less than 2 µg/m^3, far less than the spread between splits; in spring the training-station mean, which has no spatial structure at all, is best. The PINN is best in only one of the six runs.




Figure 13: Observed data: RMSE at held-out monitors over three splits (dots: individual splits).

Why the physics does not help more on real data. The contrast with the twin isolates the cause: the method works when the model is right, so the shortfall on real data reflects the model's mismatch with Delhi's atmosphere.

- *A strong common signal.* The median inter-station correlation is about 0.7. A spatially uniform estimate already captures most of the variance at an unseen station, leaving little that transport between stations can add.

- *Uniform wind.* The monitors' own anemometers (winter only; the March 2025 archive files contain no wind data) correlate with the ERA5 wind at $r = 0.50$ and read much lower (0.55 versus 1.38 m/s; Figure 17). Rooftop instruments in the urban canopy are expected to read low, but the moderate correlation means that the transporting wind, and certainly its spatial variation, are uncertain.

- **Missing processes.** The model has no entrainment term (A7), no regional inflow (A6) and no secondary aerosol formation (A4). Regional transport during the post-monsoon season enters the domain through the boundaries, which the PINN cannot represent except through the learned source. The missing dilution term has a specific consequence: the




Figure 14: Observed data: predicted against measured $PM_{2.5}$ at held-out monitors (seed 42).




Figure 15: Observed data: one held-out monitor per window and its reconstructions (seed 42).




Figure 16: Observed data: PDE residual in the first 80-hour chunk (seed 42).

observed morning decline (Figure 2) is largely a dilution effect, and the only component of the model that can reproduce it is the learned profile g. On observed data the late-morning and afternoon values of g therefore partly represent boundary-layer dilution rather than emissions, and should not be read as an emission inventory. This does not affect the synthetic twin, whose truth was generated by the same equation and also lacks the term.

- *Unidentified diffusivity.* Across the 18 real-data chunks the learned D ranges from 37 to 266 m^2/s with no consistent value, as on the twin.

The sweep in Figure 18 shows that the conclusion does not hinge on the a-priori choice $w_p = 0.01$: over $w_p \in \{0.003, 0.01, 0.03\}$ the PINN's winter RMSE stays between 78.5 and 81.0 and its spring RMSE between 30.4 and 32.8, always better than the data-only network and never clearly better than IDW.




Figure 17: Monitor anemometers (median and IQR, 39 stations) against the ERA5 wind used in the PDE, winter window.




Figure 18: Observed data: PINN test RMSE against w_p (seed 42); labels give the validation MSE.

11 Limitations

- **Model structure.** Two-dimensional, well-mixed, uniform-wind transport with constant D and λ and no chemistry or entrainment (A1–A7). The omission of entrainment is also an internal inconsistency: the column mass balance that gives the source $q\,g/H$ also gives a dilution term that we omit (Section 6.1). The real-data results indicate that these simplifications, not the PINN method, limit accuracy.
- **Boundary conditions.** Inflow concentrations are unknown; only a weak outflow condition is imposed. A regional background (for example from a chemical transport model, labelled as model output) would be the natural next step.
- **Sparse data and short windows.** 30 training stations, 6–8 test stations and two ten-day windows give wide uncertainty bands; with three splits per window, differences of a few µg/m^3 are not significant.
- **Synthetic twin is optimistic.** It shares the PINN's structural form, so it is an upper bound on performance.
- **Optimisation.** Results depend on w_p, iteration count and time-domain decomposition; adaptive weighting did not help in our implementation. Repeated runs on different CPU thread counts differ in the last digit.
- **Data provenance.** OpenAQ redistributes CPCB/DPCC data; gaps in the archive (November 2024) forced a change of window, and timestamps of 15-minute values were aggregated by hour, which may shift averages by up to one hour.

12 Conclusion

We built and analysed a two-dimensional advection–diffusion–reaction model of Delhi's $PM_{2.5}$ whose inputs are measured, estimated from reanalysis or learned, verified its numerical and automatic-differentiation implementations against exact solutions, and trained a PINN on it. When the model's assumptions hold (synthetic twin with real forcing and real station locations), the physics constraint reduces the error at unseen stations by 26 % and the error over the whole field by 43 % relative to an identical network without physics, and produces fields that are consistent with transport. On observed data the physics still stabilises the network and enforces physical consistency, but the simplified model does not capture enough of the real variability to beat simple interpolation. The analysis explains the outcome: Delhi's $PM_{2.5}$ is dominated by a spatially

coherent signal, the eddy diffusivity is not identifiable at Péclet numbers of 10^2–10^3, and processes we omitted (regional inflow, entrainment, local wind structure) carry much of the residual variability. A physics-informed model is only as useful as the physics it encodes; the clearest routes to improvement are a regional boundary condition and a mixing-height entrainment term.

Reproducibility. All code, tests (50, `pytest`), configuration and seeds are in the project repository; `data/README.md` documents data download and provenance, and every figure is regenerated by `experiments/make_figures_twin.py` and `experiments/make_figures_real.py`.

References

[1] A. G. Baydin, B. A. Pearlmutter, A. A. Radul, and J. M. Siskind. Automatic differentiation in machine learning: a survey. *Journal of Machine Learning Research*, 18(153):1–43, 2018.

[2] L. Breiman. Random forests. *Machine Learning*, 45:5–32, 2001. doi: 10.1023/A:1010933404324.

[3] Central Pollution Control Board, Government of India. Continuous ambient air quality monitoring stations. `https://cpcb.nic.in`, 2026. Original source of the monitor data redistributed by OpenAQ.

[4] X. Glorot and Y. Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the 13th International Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 9 of *PMLR*, pages 249–256, 2010.

[5] S. Gottlieb and C.-W. Shu. Total variation diminishing Runge–Kutta schemes. *Mathematics of Computation*, 67(221):73–85, 1998. doi: 10.1090/S0025-5718-98-00913-2.

[6] H. Hersbach, B. Bell, P. Berrisford, et al. The ERA5 global reanalysis. *Quarterly Journal of the Royal Meteorological Society*, 146(730):1999–2049, 2020. doi: 10.1002/qj.3803.

[7] W. Hundsdorfer and J. G. Verwer. *Numerical Solution of Time-Dependent Advection-Diffusion-Reaction Equations*, volume 33 of *Springer Series in Computational Mathematics*. Springer, Berlin, 2003.

[8] G. E. Karniadakis, I. G. Kevrekidis, L. Lu, P. Perdikaris, S. Wang, and L. Yang. Physics-informed machine learning. *Nature Reviews Physics*, 3:422–440, 2021. doi: 10.1038/s42254-021-00314-5.

[9] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015. arXiv:1412.6980.

[10] A. S. Krishnapriyan, A. Gholami, S. Zhe, R. M. Kirby, and M. W. Mahoney. Characterizing possible failure modes in physics-informed neural networks. In *Advances in Neural Information Processing Systems*, volume 34, 2021. arXiv:2109.01050.

[11] M. D. McKay, R. J. Beckman, and W. J. Conover. A comparison of three methods for selecting values of input variables in the analysis of output from a computer code. *Technometrics*, 21 (2):239–245, 1979.

[12] Open-Meteo. Historical weather API (ERA5 reanalysis). `https://open-meteo.com/en/docs/historical-weather-api`, 2026. Accessed 1 November 2026.

[13] OpenAQ. OpenAQ open air quality data platform and AWS open-data archive (`openaq-data-archive`). `https://openaq.org`, 2026. Hourly $PM_{2.5}$ from CPCB/DPCC/IMD/IITM monitors; accessed 6 November 2026.

[14] A. Paszke, S. Gross, F. Massa, et al. PyTorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

[15] M. Raissi, P. Perdikaris, and G. E. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019. doi: 10.1016/j.jcp.2018.10.045.

[16] J. H. Seinfeld and S. N. Pandis. *Atmospheric Chemistry and Physics: From Air Pollution to Climate Change*. Wiley, 3rd edition, 2016.

[17] D. Shepard. A two-dimensional interpolation function for irregularly-spaced data. In *Proceedings of the 23rd ACM National Conference*, pages 517–524, 1968. doi: 10.1145/800186.810616.

[18] J. M. Stockie. The mathematics of atmospheric dispersion modeling. *SIAM Review*, 53(2): 349–372, 2011. doi: 10.1137/10080991X.

[19] R. B. Stull. *An Introduction to Boundary Layer Meteorology*. Kluwer Academic Publishers, Dordrecht, 1988.

[20] S. Wang, Y. Teng, and P. Perdikaris. Understanding and mitigating gradient flow pathologies in physics-informed neural networks. *SIAM Journal on Scientific Computing*, 43(5):A3055–A3081, 2021. doi: 10.1137/20M1318043.