

Assignment 6 + Smoothing 3

(SNLP Tutorial 7)

Vilém Zouhar, Awantee Deshpande, Julius Steuer

8th, 10th June 2021

github.com/zouharvi/uds-snlp-tutorial

- Contributions welcome
- “Cheating” allowed

Assignment 6

- Exercise 1: MAP and MLE
- Exercise 2: Good Turing Smoothing
- Exercise 3: Cross-Validation

Kneser-Ney Smoothing

Idea: Can we use the lower order distributions in a better way?

I WENT TO THE GROCERY _____ .

Options:

W_1 : STORE

W_2 : YORK

Kneser-Ney Smoothing

Idea: Can we use the lower order distributions in a better way?

I WENT TO THE GROCERY _____ .

Options:

W_1 : STORE

W_2 : YORK

Use the fact that YORK generally appears as context or *continuation* of the word NEW.

Kneser-Ney Smoothing

$$P_{\text{continuation}}(w) = \frac{|\{w' : C(w', w) > 0\}|}{|\{(w_i, w_j) : C(w_i, w_j) > 0\}|}$$

For bigrams,

$$P_{KN}(w_i | w_{i-1}) = \frac{\max\{C(w_{i-1}, w_i) - d, 0\}}{\sum_{w'} C(w_{i-1} w')} + \lambda(w_{i-1}) P_{\text{CONTINUATION}}(w_i)$$

$$\lambda(w_{i-1}) = \frac{d}{c(w_{i-1})} \cdot |\{w : C(w_{i-1}, w) > 0\}|$$

Kneser-Ney Smoothing

General Formula

$$P_{KN}(w_i | w_{i-n+1:i-1}) = \frac{\max\{C_{KN}(w_{i-n+1:i-1}, w_i) - d, 0\}}{\sum_{w'} C_{KN}(w_{i-n+1:i-1} w')} + \lambda(w_{i-n+1:i-1}) \cdot P_{KN}(w_i | w_{i-n+2:i-1})$$

$$\text{where } C_{KN}(\bullet) = \begin{cases} \text{count}(\bullet) & \text{for highest order} \\ \text{continuation_count}(\bullet) & \text{for lower orders} \end{cases} \quad (1)$$

Kneser-Ney Smoothing Questions

- How are unseen words handled by KN Smoothing?
- For a KN-Smoothed language model,

$$\text{Information content("Vader")} = 15$$

$$\text{Information content("Star")} = 10$$

Which unigram is assigned a higher probability by KN smoothing? Would the information content be the same for absolute discounting?

- Will the probabilities be affected for frequent higher order n-grams?
- Can Kneser-Ney smoothing be implemented for unigrams?

Pruning

- Back-off models and interpolation save n-grams of all orders.

We are storing all $V^n + V^{n-1} + \dots + V + 1$ distributions!

- Idea: Store the counts which exceed a threshold $c(\bullet) \geq K$. Also called a “cut-off”.

Pruning: Error in Assignment 7

```
assert tree.get("5634") == 4
```

Pruning: How to build a count tree

```
tree.add("ABCE")
```

Pruning: How to build a count tree

```
for _ in range(3):  
    tree.add("ABCD")
```

Pruning: How to build a count tree

```
for _ in range(5):  
    tree.add("1234")
```

Pruning: How to build a count tree

```
tree.add("5634")
```

Pruning: $K \leq 4$?

```
tree.prune("5634")
```

Prune a node iff $C(\textit{history}) \leq 4$, not the value of the node itself!

Assignment 7

- Exercise 1: Count Trees and Pruning
- Exercise 2: Kneser-Ney Smoothing
- Bonus: Comparison of smoothing techniques

Resources

- ① UdS SNLP Class: <https://teaching.lsv.uni-saarland.de/snlp/>
- ② n-gram models: <https://web.stanford.edu/~jurafsky/slp3/3.pdf>
- ③ Kneser-Ney Smoothing: <https://medium.com/@dennyc/a-simple-numerical-example-for-kneser-ney-smoothing-nlp-4600addf38b8>
- ④ Comparison of Smoothing Techniques:
https://people.eecs.berkeley.edu/~klein/cs294-5/chen_goodman.pdf