

Assignment 8,9 + Classifiers

(SNLP Tutorial 9)

Vilém Zouhar, Awantee Deshpande, Julius Steuer

22nd, 24th June

Assignment 8

- Exercise 1: Feature Selection (DF, PMI)
- Exercise 2: χ^2
- Exercise 3: Author identification
- Bonus: Features for clustering

Decision Trees

- Can be used for classification as well as regression
- Algorithm


```
function DECISION-TREE-LEARNING(examples, attributes, parent_examples) returns a tree
  if examples is empty then return PLURALITY-VALUE(parent_examples)
  else if all examples have the same classification then return the classification
  else if attributes is empty then return PLURALITY-VALUE(examples)
  else
     $A \leftarrow \underset{a \in \text{attributes}}{\text{argmax}} \text{ IMPORTANCE}(\text{examples})$ 
    tree  $\leftarrow$  a new decision tree with root test A
    for each value  $v_k$  of A do
      exs  $\leftarrow \{e : e \in \text{examples} \text{ and } e.A = v_k\}$ 
      subtree  $\leftarrow$  DECISION-TREE-LEARNING(exs, attributes - A, examples)
      add a branch to tree with label (A =  $v_k$ ) and subtree subtree
  return tree
```

What is plurality value?

What is importance?


Decision Trees - Questions

- Which of the 2 splits has a better information gain?



Decision Trees - Questions


- Which of the 2 splits has a better information gain?



- What are the pros and cons of decision trees?

Decision Trees - Questions

- Which of the 2 splits has a better information gain?



- What are the pros and cons of decision trees?
- How to avoid overfitting?

Naïve Bayes

TODO

kNN

- Algorithm

```
k-Nearest Neighbor  
Classify (X, Y,  $x$ ) // X: training data, Y: class labels of X,  $x$ : unknown sample  
for  $i = 1$  to  $m$  do  
    Compute distance  $d(\mathbf{X}_i, x)$   
end for  
Compute set  $I$  containing indices for the  $k$  smallest distances  $d(\mathbf{X}_i, x)$ .  
return majority label for  $\{Y_i \text{ where } i \in I\}$ 
```

Source: https://www.researchgate.net/figure/Pseudocode-for-KNN-classification_fig7_260397165

Questions

- What are the training and test computation times for kNN?
- What are the pros and cons of kNN classifiers?
- Can kNN be used for regression?
- How will the value of k affect the bias?

SVM

- Find a boundary that maximizes the distance to closest vectors
- If not possible, find one that minimizes the error
- Add the kernel trick

Perceptron

- Binary classification
- Linear boundary in feature space
- $\hat{y} = \text{sign}(wx + b)$

Perceptron

- Binary classification
- Linear boundary in feature space
- $\hat{y} = \text{sign}(wx + b)$

Algorithm:

- $w_0 = \vec{0}$
- For every data point x_i
 - ▶ $\hat{y}_i = \text{sign}(w_k x_i + b)$
 - ▶ if $\hat{y}_i \neq y_i$:
 - ▶ ★ $w_{k+1} = w_k - \hat{y}_i \cdot x$
 - ▶ else:
 - ▶ ★ $w_{k+1} = w_k$

Perceptron

- Binary classification
- Linear boundary in feature space
- $\hat{y} = \text{sign}(wx + b)$

Algorithm:

- $w_0 = \vec{0}$
- For every data point x_i
 - ▶ $\hat{y}_i = \text{sign}(w_k x_i + b)$
 - ▶ if $\hat{y}_i \neq y_i$:
 - ▶ ★ $w_{k+1} = w_k - \hat{y}_i \cdot x$
 - ▶ else:
 - ▶ ★ $w_{k+1} = w_k$
- TODO: illustration

• TODO: advantages/disadvantages

Useful Python Implementations

Resources

- ① UdS SNLP Class, WSD: <https://teaching.lsv.uni-saarland.de/snlp/>
- ② Decision Trees:
<https://www.kdnuggets.com/2020/01/decision-tree-algorithm-explained.html>
- ③ kNN Example: <https://iq.opengenus.org/text-classification-using-k-nearest-neighbors/>