

COLLABORATORS					
	TITLE: crystal_facet_uml user				
ACTION	NAME	DATE	SIGNATURE		
WRITTEN BY	Andreas Warnke	2020-09-06			

REVISION HISTORY					
NUMBER	DATE	DESCRIPTION	NAME		

Contents


1	Intr	oduction	n	1
	1.1	Goal .		1
	1.2	Feature	es	1
	1.3	Usage	Overview	3
2	Exa	mple Di	agrams	3
	2.1	Feature	e List	3
	2.2	Examp	ole UML Behavioral Views	5
	2.3	Examp	ole UML Static Views	8
	2.4	Examp	ole SysML Views	10
	2.5	More E	Examples	12
3	GUI	/ Usage	e Manual	12
	3.1	Windo	w Area Overview	12
	3.2	Tool B	ar	13
		3.2.1	Create/Use DB	13
		3.2.2	Export	13
		3.2.3	New Window	14
		3.2.4	Search	14
		3.2.5	Navigate	14
		3.2.6	Edit	14
		3.2.7	Create	14
		3.2.8	Cut	14
		3.2.9	Copy	15
		3.2.10	Paste	15
		3.2.11	Delete	15
		3.2.12	Instantiate	15
		3.2.13	Highlight	15
		3.2.14	Reset Selection	15
		3.2.15	Undo	16
		3.2.16	Redo	16
		3.2.17	About	16
	3.3	Drawin	ng Area	16
		3.3.1	Search	16
		3.3.2	Navigate	16
		3.3.3	Edit	17
		3.3.4	Create	17

	3.4	Element C	onfiguration Area	17
		3.4.1 Co	ommit	18
	3.5	Notificatio	n Bar	18
		3.5.1 Inf	formation	18
		3.5.2 Wa	arning	18
		3.5.3 Er	ror	18
4	Diag	grams and l	Elements Spec	19
	4.1	Classifiers		19
	4.2	Features .		22
	4.3	Relationsh	ips	23
	4.4	Diagrams		24
	4.5	Maximum	stringlengths	26
5	Mod	leling Guid	elines	27
	5.1	crystal_fac	eet_uml Hints	27
		5.1.1 Tro	ee Structure	27
		5.1.2 Fo	cus	27
		5.1.3 Na	umespaces	27
		5.1.4 At	tic/Storage room	28
	5.2	General H	ints on Architecture Documentation	28
		5.2.1 Pro	oblem vs. Solution	28
		5.2.2 Na	mes	28
		5.2.3 De	escription	28
		5.2.4 Pro	ecise sentences	28
		5.2.5 Di	stinguish similar things	28
A	Con	figuration		28
	A.1	Download	, Installation and License	28
		A.1.1 Do	ownload Links	28
		A.1.2 Ins	stallation on Linux	29
		A.1.3 Ins	stallation on Windows/Wine	31
		A.1.4 Lie	cense	31

1 Introduction



crystal_facet_uml creates diagrams to document system and software architecture.



Similar to a crystal which shows different facets of the same thing, this application shows different views of the same system.

1.1 Goal



As software architect, you create a set of diagrams describing use-cases, requirements, structural views, behavioral and deployment views.

crystal_facet_uml keeps element names and element hierarchies consistent. It exports diagrams in svg, pdf, ps and png formats to be used in text processing systems like docbook, html, latex. This tool runs on your local PC and is based on glib, gdk, gtk, cairo, pango, sqlite.

1.2 Features



crystal_facet_uml provides a graphical user interface to

create diagrams
 (use-case, deployment, component, composite-structure, package, class, activity, state, timing, communication, sequence)

· create uml elements

(actor, system-boundary, use-case, node, component, part, interface, package, class, activity, state, object, artifact, comment, requirement)

- · move, modify and delete uml elements
- create, modify and delete relationships

(dependency, association, aggregation, composition, generalization, realization, contains, sync-call, return-call, async-message, communication-path, control-flow, object-flow, deployment, manifest, include, extend)

 create, modify and delete features (port, field, operation)

- cut, copy, paste uml elements between diagrams
- · undo and redo are supported
- multiple windows can show different or same parts of the uml model

Diagrams are layouted part-automatically:

- The user chooses the relative location of uml elements towards others
- crystal_facet_uml selects the exact locations of uml elements
- The user controls the positions of messages/transitions in sequence and timing diagrams
- crystal_facet_uml auto-layouts relationships in other diagrams

crystal_facet_uml manages a meta model:

- Diagrams are organized as a tree, similar to a book's table-of-contents
- Uml elements exist only once even if shown in many diagrams
- Relationships and features are consistent between all diagrams
- Diagram-local messages/transitions are supported in scenario-based diagrams (sequence, communication, timing)

crystal_facet_uml exports diagrams as

• vector graphics (pdf, ps, svg)

pixel graphics (png)

• textual representation (utf-8-txt, docbook, xhtml)

 machine-readable model (xmi)

crystal_facet_uml can also be started from command line to export all diagrams automatically or to check and repair database files.

1.3 Usage Overview




crystal_facet_uml can be started in graphical mode (see Section 3) or from command line (for help run crystal_facet_uml -h).


2 Example Diagrams


This sections presents the features of crystal_facet_uml.


2.1 Feature List

This section lists what kind of elements crystal_facet_uml can draw in diagrams.













2.2 Example UML Behavioral Views


This section lists what kind of elements crystal_facet_uml can draw in diagrams.





















2.3 Example UML Static Views

This section lists what kind of elements crystal_facet_uml can draw in diagrams.












2.4 Example SysML Views

This section lists what kind of elements $crystal_facet_uml$ can draw in diagrams.







2.5 More Examples

There are further examples available as html:

- http://www.awarnke.keepfree.de/crystal_facet_uml/mouse_droid/mouse_droid.xhtml
- http://www.awarnke.keepfree.de/crystal_facet_uml/quality/quality.xhtml

And in crystal_facet_uml binary format:


- https://github.com/awarnke/crystal_facet_uml/tree/master/example_diagrams
- https://github.com/awarnke/crystal_facet_uml/tree/master/architecture/doc

3 GUI / Usage Manual


3.1 Window Area Overview

If started in graphical mode, crystal_facet_uml shows a window with

- toolbar on top,
- drawing area in the center,
- element configuration widgets to the right and
- an optional notification bar at the bottom.



3.2 Tool Bar



3.2.1 Create/Use DB



• Opens an existing database file or creates a new database file

3.2.2 Export



• Exports all diagrams to the selected folder (supported formats are png, pdf, ps, svg, txt. xhtml, docbook, xmi)

3.2.3 New Window



• Opens another window on the same database.

This new window allows you to work reliably with multiple windows on the same database.

3.2.4 Search



• Find diagrams that contain the searched elements (see Section 3.3.1)

3.2.5 Navigate



- · Navigate to parent or child diagrams
- Create a new diagram (see Section 3.3.2)

3.2.6 Edit



• Modify elements in the diagram (see Section 3.3.3)

3.2.7 Create



• Create elements in the diagram (see Section 3.3.4)

3.2.8 Cut



• Cut all selected (pink-cornered) elements to the clipboard (features of classifiers are copied if the classifier is selected)

3.2.9 Copy



• Copy all selected (pink-cornered) elements to the clipboard (features of classifiers are copied if the classifier is selected)

3.2.10 Paste



- If the clipboard contains a diagram, this diagram is pasted below the current diagram. All other elements are pasted into the new diagram.
- If the clipboard does not contain diagrams, classifiers and relationships from the clipboard are copied into the current diagram.
- If the name of a classifier is identical to an existing one, an instance of the existing classifier is pasted to the diagram. Otherwise a new classifier is created.

3.2.11 Delete



• Deletes all selected (pink-cornered) elements. This operation may fail if a selected diagram contains non-selected elements.

3.2.12 Instantiate



- Toggles the selected (pink-cornered) classifiers between classes, named instances and anonymous instances.
- No effect on relationships and features.

3.2.13 Highlight



• Toggles the selected (pink-cornered) classifiers between yellow-marked, greyed-out and normal. (Does not work for relationships and features)

3.2.14 Reset Selection







• Resets the (pink-cornered) selection

3.2.15 Undo



• Un-does the last operation (Opening a database and exporting files cannot be undone)

3.2.16 Redo




• Re-does the last un-done operation

3.2.17 About



• Shows version, license and copyrights

3.3 Drawing Area



Diagrams are layouted automatically. You can influence the locations of classifiers only. When adding too many classifiers or relations, auto layouting may not achieve the expected results. In many cases, splitting the diagram into two or more diagrams solves the layouting issues and at the same time improves understandability by focusing on one aspect/topic per diagram.

3.3.1 Search



• Enter the ID of an element (e.g. C0001) or a part of its name or description to find diagrams containing this element.

3.3.2 Navigate



- To navigate to parent, sibling or children diagrams, click on the diagram.
- To create a new diagram, click on the + icon, or the smaller icon for a new child-diagram.
- To restructure the diagram tree, drag a diagram name to the new location.

3.3.3 Edit




- To focus the diagram or a classifier or a feature or a relationship (yellow corners), click on this object.
- To select an element (pink corners), click on these objects twice.
- To move classifiers within the diagram, 1.) press, 2.) drag and 3.) release the mouse button.

 Note: When moving a classifier, this is moved in all diagrams where it appears. Order and locations of things stay consistent between different views.


3.3.4 Create



- 1. To create a classifier, click at an empty space in the diagram.
- 2. To create a child classifier, click into the white space of a classifier. (Alternatively, create a classifier (see 1) and a containment relationship (see 4).)
- 3. To create a feature, click onto a classifier (name or border).
- 4. To create a relationship, press on the source classifier and drag it to the destination classifier.



3.4 Element Configuration Area



Edit the properties of the focused (yellow-cornered) object.

- name of the focused object
- stereotype/valuetype of the focused object (deactivated depending on object-type)
- type of the focused object
- description of the focused object.


For xhtml and docbook export, use a double linebreak to create a new paragraph, start lines with *, + or - to format a list, use D0001#id and D0001#name to create a link to the diagram D0001 (showing either the id or the name).

3.4.1 Commit



• Stores the latest changes to the database immediately. This feature is optional, it is not necessary to explicitly save the file.

3.5 Notification Bar



3.5.1 Information



• Informs on success of an operation, e.g. an export

3.5.2 Warning



• Informs on a possible problem

3.5.3 Error



· Informs on an error

4 Diagrams and Elements Spec



This program creates diagrams that strive for compatibility to

- UML 2.5
- SysML 1.5
- MOF 1.4.1

In some cases, it deviates from these standards for several reasons:

- Reduce complexity to be able to handle such models in a small open source project
- · Reduce feature-set to improve understandability of diagrams even to non-software-architects
- Reduce feature-set to enhance usability of the program

This section gives an overview on standards and implementation-status of crystal_facet_uml. It may be incomplete.

4.1 Classifiers

Classifiers are the nodes in the model-graph.

The table shows the classifier types introduced by different specifications, if they filter/hide their features and a comment stating how this is implemented in crystal_facet_uml.

	Spec	Diagram Context and Filter	Comment
Block	SysML	*/-	Limitations: Compartment Order is "properties, operations" instead of "constraints, operations, receptions, parts, (bound) references, values, properties, stereotype-tagged-values, behavior, namespace, structure" Limitations: No labeled compartments Limitations: no Multiplicities of Block-Instances.
Constraint Property/Equation	SysML	Parametric / -	Limitations: Only the rounded-rect symbol is supported, ports are not completely inside the rounded-rect.
Node	UML	Deployment / -	
Component	UML	*/-	
Part	UML	*/-	

	Spec	Diagram Context and Filter	Comment
Interface	UML	*/-	
Package	UML, SysML	*/-	
Class	UML	* / -	Limitations: No active classes
Object	UML	*/-	
Artifact	UML	*/-	
Comment	UML, SysML	* / unconditional features	
Feature/Composite Requirement	SysML	* / -	Represents a group of requirements
Requirement	SysML	*/-	
Actor	UML, SysML	Use Case, Sequence / unconditional features	
Use Case	UML, SysML	Use Case / -	Limitations: No SysML extension points
System Boundary	UML, SysML	Use Case / unconditional features	
Diagram Reference	UML	Interaction Overview / unconditional features	Hint: To easily find the referenced diagram, name the reference identical to the diagram.
Activity	UML 2.5 (ch15.2)	Activity / -	Limitations: Object Node Pin notation not supported, draw the object between activities
Interruptable Region	UML	Activity / unconditional features	
$\rightarrow \begin{array}{c} \rightarrow \\ \rightarrow \\ \rightarrow \end{array}$ Fork	UML, SysML	Activity / unconditional features	

	Spec	Diagram Context and Filter	Comment
$\begin{array}{c} \rightarrow \\ \rightarrow \\ \rightarrow \end{array} \rightarrow$ Join	UML, SysML	Activity / unconditional features	
Accept Event	UML, SysML	Activity / unconditional features	
Accept Time Event	UML, SysML	Activity / unconditional features	
Send Signal	UML, SysML	Activity / unconditional features	
Decision/Choice	UML 2.5 (ch14.2.4,15.3), SysML	Activity, State / unconditional features	In activity diagrams, this is called decision, in statesmachines it is called choice
Initial Node	UML 2.5 (ch14.2.4), SysML	Activity, State / unconditional features	Limitations: There is no distinction in ActivityInitial and FlowInitial Limitations: There is no separate entryPoint state-type
Final Node	UML 2.5 (ch14.2.4), SysML	Activity, State / unconditional features	Limitations: There is no distinction in ActivityFinal and FlowFinal Limitations: There is no separate exitPoint and terminate state-type
State	UML 2.5 (ch14.2), SysML	State, Timing / -	Limitations: No symbol for hidden decompositions, no regions (swimlanes) in composite states Limitations: entry/exit/do list Limitations: entryPoint and exitPoint states cannot be drawn on parent state border line
Shallow History	UML 2.5 (ch14.2.4), SysML	State / unconditional features	
Deep History	UML 2.5 (ch14.2.4), SysML	State / unconditional features	
× Value Type	SysML	-/-	not supported. Limitations: Compartment Order of Classifiers is "properties, operations" instead of "operations, properties, stereotype-tagged-values"
× Enumeration	UML, SysML	-/-	not supported. Note: Use a class instead.
× ActivityParameterNode	SysML	-/-	not supported.

	Spec	Diagram Context and Filter	Comment
× MergeNode/Junction	UML 2.5 (ch15.3), SysML	Activity, State / unconditional features	In activity diagrams, it is called merge, in state diagrams junction node. This is not supported. Note: You may directly connect the arrows to the target activity/state.
× ActivityPartition	UML, SysML	Activity / unconditional features	not supported. Note: Use a parent activity instead.

LEGEND

Filter Defines which elements related to a classifier are not visible

An InstanceSpecification (UML) denotes an instantiation of a classifier. crystal_facet_uml allows any classifier to appear in different diagrams as classifier, as anonymous InstanceSpecification or as named InstanceSpecification. (Rationale: If a classifier is an instance may depend on the context: An M1-class may be an instance if shown in an M2-meta-class diagram, an XML-parser-class may be an instance if shown in the context of stream processors.)

4.2 Features

Features are elements attached to one classifier.

The table shows the feature types introduced by different specifications, if they are visible in any diagram or just once, and a comment stating how this is implemented in crystal_facet_uml.

	Spec	Scope	Comment
Property	UML, SysML	unconditional	Limitations: no SysML Flow-Properties refinement
Operation	UML, SysML	unconditional	
Port	UML, SysML	unconditional	Limitations: no SysML-compartment Notation supported Limitations: no SysML-nested-ports, SysML-proxy-port, SysML full-ports supported Limitations: no flow property, no compartment notation, no port-compartments Limitations: no UML behavior ports
O	UML, SysML	unconditional	
Nequired Interface	UML, SysML	unconditional	
Lifeline	UML 2.5 (ch17.2), SysML	scenario, 1 per diagram	Limitations: One lifeline is visible only in one diagram Limitations: Lifelines start and end only at diagram border Limitations: ExecutionSpecification (ActivityBar) are not supported

LEGEND

Scope scope is unconditional if a feature belongs to a classifier unconditionally, scenario if only applicable in 1 diagram

4.3 Relationships

Relationships are the edges of the model-graph.

The table shows the relationship types introduced by different specifications, a classification in which diagram type to use them preferably, and a comment stating how this is implemented in crystal_facet_uml.

	Spec	Diagram Context	Comment
> Dependency	UML, SysML	any	
Containment	UML, SysML	Deployment, Package, Internal Block, Composite Structure, Activity, State	
«dep ioy»→ Deploy	UML	Deployment	
«mani ————————————————————————————————————	UML	Deployment	
Communication Path	UML, SysML	Component, Composite Structure, Block, Internal Block	
Association	UML, SysML	Class, Use Case	Note: SysML calls this ReferenceAssociation Limitations: no AssociationClass(SysML: ParticipantProperty) exists. Limitations: no AssociationEnd Classes exist, no multiplicities, no roles, no ownership (dot notation). Limitations: no ternary associations (only two ends supported). Limitations: no non-navigateable ends (crosses) suported yet - see todo.txt.
Aggregation	UML, SysML	Class	Note: SysML calls this SharedAssociation
Composition	UML, SysML	Class	Note: SysML calls this PartAssociation
——————————————————————————————————————	UML, SysML	Class, Use Case(?)	Limitations: no Generalization-Sets supported
> Realization	UML	Class	

	Spec	Diagram Context	Comment
«tra −> Trace	SysML	Requirement	
«re fine»→	SysML	Requirement	
end»	UML, SysML	Use Case	Limitations: no SysML-condition-notes can be attched to this relationship
«incl ————————————————————————————————————	UML, SysML	Use Case	
Control Flow	UML, SysML	Activity	
Object Flow	UML, SysML	Activity	
Async. Call	UML, SysML (?)	Sequence, Timing, Communication	
Sync. Call	UML, SysML (?)	Sequence, Timing, Communication	
<-−- Return Call	UML, SysML (?)	Sequence, Timing, Communication	
× Connector	UML, SysML	Internal Block	not supported. Limitations: No Bi-directional Connectors Note: SysML calls this BindingConnector Note: Use a Communication Path instead.
× Item Flow	SysML	Block Definition	not supported. Note: Use an Object Flow instead.
× Exception Flow	UML 2.5 (ch15.5)	Block Definition	not yet supported, see todo.txt.

4.4 Diagrams

Diagrams are views on the model-graph. They select classifiers and may filter their features and relationships.

The table shows the diagram types introduced by different specifications, if they filter/hide their features and/or relationships and a comment stating how this is implemented in crystal_facet_uml.

	Spec	Filter	Comment
List Diagram	-	any feature, any relationship	This is an overview diagram showing only classifiers without features and without relationships

	Spec	Filter	Comment
Box Diagram	-	any feature, any relationship	This is an overview diagram showing only classifiers without features and without relationships
Block Definition Diagram	SysML	lifelines	
Internal Block Diagram	SysML	lifelines	
Parametric Diagram	SysML	lifelines	
Deployment Diagram	UML	lifelines	
Component Diagram	UML	lifelines	
Composite Structure Diagram	UML	lifelines	
Package Diagram	UML, SysML	lifelines	
Class Diagram	UML	lifelines	
«me ta» Profile Diagram	UML	lifelines	not supported
Requirements Diagram	SysML	lifelines	
Use Case Diagram	UML, SysML	lifelines	
Interaction Overview Diagram	UML	lifelines	Limitations: There is no link from Diagram-References to referenced Diagrams
Activity Diagram	UML 2.5 (ch15.2), SysML	lifelines	Limitations: Swimlanes not supported
State Machine Diagram	UML, SysML	lifelines	

	Spec	Filter	Comment
		unconditional	
		relationships	
1-2:	UML	(Scenario),	
Communication Diagram		unconditional	
		features	
Sequence Diagram	UML, SysML	unconditional	
		relationships	
		(Scenario),	
		unconditional	
		features	
Timing Diagram	UML	unconditional	
		relationships	
		(Scenario),	
		unconditional	
Immig Diagram		features	

LEGEND

Filter Defines which elements are not visible in the diagram

Scenario Diagrams show only relationships associated with a lifeline of a visible classifier.

4.5 Maximum stringlengths

All strings (names, descriptions, stereotypes) have a maximum length.

Ascii characters require one, most other characters two bytes. Current sizes in bytes are:

Classifiers:

- DATA_CLASSIFIER_MAX_NAME_LENGTH = 47,
- DATA_CLASSIFIER_MAX_STEREOTYPE_LENGTH = 47,
- DATA_CLASSIFIER_MAX_DESCRIPTION_LENGTH = 4095,

Features:

- DATA_FEATURE_MAX_KEY_LENGTH = 47, (name)
- DATA_FEATURE_MAX_VALUE_LENGTH = 255, (type)
- DATA_FEATURE_MAX_DESCRIPTION_LENGTH = 1023,

Relationships:

- DATA_RELATIONSHIP_MAX_NAME_LENGTH = 47,
- DATA_RELATIONSHIP_MAX_DESCRIPTION_LENGTH = 1023,

Diagrams:

- DATA_DIAGRAM_MAX_NAME_LENGTH = 47,
- DATA_DIAGRAM_MAX_DESCRIPTION_LENGTH = 8191,


5 Modeling Guidelines

This page lists remarks on creating a software architecture and design document in general and it lists hints on efficiently using the tool crystal_facet_uml.


5.1 crystal_facet_uml Hints

5.1.1 Tree Structure

Diagrams are organized as a tree. Start the root of the tree explaining the document structure. At the second level of the tree, list the main areas to be shown, for example based on the arc42 template https://arc42.org/overview/:



In case you show several layers of abstraction, each building block may contain its sub-blocks, sub-blocks may again show sub-sub-blocks. In this case, structure the specification of the sub-blocks in the same way: apply the proposed folder structure recursively, omitting possibly empty or superfluous folders.



5.1.2 Focus

Put only few elements into each diagram. This increases understandability of the main purpuse of the diagram. Put further aspects of a topic into a separate diagram. Do not hesitate to copy an element from one diagram to the next. This is what crystal_facet_uml is good at: it keeps the model in sync.

5.1.3 Namespaces

Put a prefix to all your elements denoting its namespace. You can then distinguish a GLOBAL_START_STATE from an AUDIO_START_STATE. Or global::start from audio::start.

To achieve a more compact layout of an element, one may insert space characters into names. (In case names get long, the space allows for a linebreak).

5.1.4 Attic/Storage room

If you are not sure if you really want to delete elements, 1) copy them to an attic-diagram and then 2) delete them from the original diagram.

5.2 General Hints on Architecture Documentation

5.2.1 Problem vs. Solution

Distinguish things that are

- given constraints (problem space),
- · decisions, chosen and rejected alternatives and
- the designed solution

5.2.2 Names

Names of things are crucial: If the reader gets a wrong understanding by the name of an element, a hundred correct sentences of describing text cannot set this straight again.

5.2.3 Description

Every design element needs a description, maybe a list of responsibilities: What shall this element do, what is it for? Names alone cannot explain a system part.

5.2.4 Precise sentences

Be precise: Write in active form, e.g. The persistence component shall store and retrieve binary data records indentified by string-based keys.

5.2.5 Distinguish similar things

Things that are similar but not the same shall be different entities when modelling. E.g. The process in which an example application runs may be different from the storage location and may be different from the software-component. These are three things: Example_App_Process (Type: Node), Example_App_ObjectFile (Type:Artifact) and Example_App_SWComponent (Type:Component).

A Configuration

A.1 Download, Installation and License

A.1.1 Download Links

Find the latest version of crystal_facet_uml at:

- https://www.heise.de/download/product/crystal-facet-uml/
- https://sourceforge.net/projects/crystal-facet-uml/
- https://github.com/awarnke/crystal_facet_uml

- https://build.opensuse.org/package/show/home:awarnke/crystal_facet_uml
- https://download.opensuse.org/repositories/devel:/tools/openSUSE_Leap_15.1/x86_64
- https://salsa.debian.org/debian-edu-pkg-team/crystal-facet-uml

User documentation is available here:

- http://www.andreaswarnke.de/crystal_facet_uml/crystal_facet_uml_user_documentation.pdf
- https://github.com/awarnke/crystal_facet_uml/blob/master/user_doc/crystal_facet_uml_user_documentation.pdf


A.1.2 Installation on Linux

The .deb and .rpm packages can be installed by the package installers of your system.

For installation on ubuntu, debian or raspbian, you may e.g. invoke **sudo dpkg --install <filename>** on the command line:

```
andi@debian1zotac:~/Downloads$ sudo dpkg --install crystal-facet-uml_1.12.0-1_amd64.deb
    We trust you have received the usual lecture from the local System
    Administrator. It usually boils down to these three things:
#1) Respect the privacy of others.
#2) Think before you type.
#3) With great power comes great responsibility.
[sudo] password for andi:
Selecting previously unselected package crystal-facet-uml.
(Reading database ... 198990 files and directories currently installed.)
Preparing to unpack crystal-facet-uml_1.12.0-1_amd64.deb ...
Unpacking crystal-facet-uml (1.12.0-1) ...
Setting up crystal-facet-uml (1.12.0-1) ...
Processing triggers for gnome-menus (3.13.3-9) ...
Processing triggers for desktop-file-utils (0.23-1) ...
Processing triggers for mime-support (3.60) ...
Processing triggers for man-db (2.7.6.1-2) ...
andi@debian1zotac:~/Downloads$
```

For installation you may use a gui-installation tool like yast. Because the packages are not signed, you may want to ignore the warning.




For installation on opeSuSE, you may e.g. invoke sudo zypper install <filename> on the command line:

```
andi@linux-uv90:~/Downloads> sudo zypper install crystal-facet-uml-1.13.1-1.x86_64.rpm
[sudo] Passwort für root:
Repository-Daten werden geladen...
Installierte Pakete werden gelesen...
Paketabhängigkeiten werden aufgelöst...
Das folgende Paket wird aktualisiert:
crystal-facet-uml
1 Paket wird aktualisiert.
Gesamtgröße des Downloads: 698,6 KiB. Bereits im Cache gespeichert: 0 B. Nach der \leftrightarrow
   Operation werden zusätzlich 8,8 KiB belegt.
Fortfahren? [j/n/...? zeigt alle Optionen] (j): j
Paket crystal-facet-uml-1.13.1-1.x86_64 abrufen ←
                                                                 (1/1), 698,6 KiB \leftrightarrow
   ( 1,2 MiB entpackt)
crystal-facet-uml-1.13.1-1.x86_64.rpm:
Package is not signed!
crystal-facet-uml-1.13.1-1.x86_64 (Einfacher Cache für RPM-Dateien): Fehler beim \leftrightarrow
   Überprüfen der Signatur [6-File is unsigned]
Abbrechen, wiederholen, ignorieren? [a/w/i] (a): i
Überprüfung auf Dateikonflikte läuft: \leftarrow
   fertial
(1/1) Installieren: crystal-facet-uml-1.13.1-1.x86_64 \leftrightarrow
   fertig]
andi@linux-uv90:~/Downloads>
```

Alternatively, you may want to build the software from the .orig source-package and then install it by **sudo make install**; see the readme file for more information.

A.1.3 Installation on Windows/Wine



- On windows, doubleclick on crystal_facet_uml.exe,
- or using the wine emulation, call wine crystal_facet_uml.exe to start.

A.1.4 License

License of crystal_facet_uml is Apache-2.0. Copyright 2016-2020 Andreas Warnke; Email-contact: cfu-at-andreaswarnke-dot-de