






Drywall Partition System

Components&Approx Requirements Per 100m2 of Drywall Partition

Material	Picture	Function	Siz(mm)	Quantity
PLASTERBOARD		Facing of partition system	1200×2400,1200×3000mm Thickness 9.5,12.5,15,16,18 mm Other Sizes & thicknesses available upon request.	varies based on system.
GALVANIZED RUNNER		Main supporting section to which plasterboard is screwed	Width:42mm → 200mm Length:3m. → 12m Thickness:0.35 → 1.5mm	66LM
GALVANIZED STUD		Vertical frame of partition	Width:42. → 200mm Length:3m → 12m Thickness:0.35 → 1.5mm	200LM
DRYWALL SCREWS		Fastening drywall boards to steel framing structure	Various Sizes	Varies based on system
FRYAMING SCREWS		Fastening metal frame members together	Length:11mm	Varies based on system
DRYWALL JOINT TAPE		Enforcing tapered edge joints (Paper or fiberglass tape)	50mm×90m	150LM
CORNER TAPE		Efnorcing internal & external angles	50mm×30m	Varies based on system
DRYWALL L-BEAD		Enforcement of external angles that need maximum rotection	25×25×3000mm 25×16×3000mm Thickness:0.4 & 0.45mm	Varies based on system
READ MIXED JOINT CPD		Embedding joint tape,finishing joints & skim coating wall board	28Kg/pail 15Kg/pail 5Kg/pail	Varies based on system
FURRING CHANNEL		Main supporting section to which plasterboard is screwed	Siz:12×22×35×22×12mm Length:3m → 12m Thickness:0.35 → 1mm	66LM

Material	Picture	Function	Siz(mm)	Quantity
PRIMARY CHANNEL (C-channel)		Intermediate support for furring channel.	Siz:11×38×11mm Length:3m → 12m Thickness:0.35 → 1mm	66LM
PERIMETER ANGLE		Fixed on the perimeter to receive furring channel ends & outer edges of plaster boards	Size:25×25mm Length:3m → 12m Thickness:0.4 → 0.6mm	40LM Might vary based on desing
SHADOW LINE WALL ANGLES		Fixed on the perimeter to receive furring channel ends & outer edges of plaster boards	- Size: 19×9×9×19 mm, 19×19×19×19 mm, 25×25×25×25 mm - Length: 3 m ~12 m - Thickness: 0.4~0.6 mm	40LM Might vary based on desing
ADJUSTABLE ROD HANGER		Hanging system from structural soffit to dropped false ceiling	Rod hanger - Diameter: 3.7 mm	70sets Might vary based on design load.
THREADED ROD SYSTEM		Hanging system from structural soffit to dropped false ceiling	Threaded rod - Diameter: 6.0 mm	70ets Might vary based on design load.
WIR CONNECTING CLIPS		Connecting furring channels to primary C-channels	Size: 38×2.5 mm	420 EA

**Available in both galvanized and powder coated upon request.
special sizes available upon request.**