

# Eclipse Scout

## *Migration Guide*

Scout Team

Version 8.0

# Table of Contents

About This Document .....	1
Service Release Migration .....	1
API Changes (Java) .....	1
Java 8 Required .....	2
CalendarComponent .....	2
AbstractCacheValueResolver .....	2
Deprecation of SequenceBox EqualColumnWidths .....	2
Removed Constants/Methods From ClientUIPreferences .....	3
Removed Property "focusable" From IFormField, AbstractFormField .....	3
Removal of Old "SmartField", Renaming of "SmartField2" Back to "SmartField" .....	3
IContentAssistField Classes and Interfaces Removed .....	4
GroupBox: Moved "minWidthInPixel" .....	5
Adjusted Behavior of Widget Initialization .....	5
GzipServletFilter .....	6
HttpCacheControl .....	6
HttpProxy .....	6
Replacement for IActionVisitor, ITreeVisitor, IFormFieldVisitor .....	6
New Convenience Methods on IFormField .....	7
Config Properties .....	7
Customizing CSP Rules Via Config Property .....	11
IUIServletRequestHandler .....	11
Table: Remove Obsolete "POPULATED" Event and Methods .....	12
PageField: Status of Page Table Visible by Default .....	12
SmartField: changed behavior for applying styles from a lookup-row on the field (since 8.0.0.021) .....	12
AbstractIcons: Changed constants .....	13
Removed ActivityMapMenuType .....	13
Texts and Multi Language Support (NLS) Moved to Platform .....	13
Moved Mail-Related Classes to New Module to org.eclipse.scout.rt.mail (since 8.0.0.021) .....	13
Deprecated Methods on DefaultAuthToken and Introduced DefaultAuthTokenSigner and DefaultAuthTokenVerifier (since 8.0.0.021) .....	15
StyleHelper Moved to Platform (since 8.0.0.034) .....	15
API Changes (JavaScript) .....	15
Rename of LESS Variables .....	15
Widget.js: New Argument for clone() .....	16
Widget.js: "addChild" & "removeChild" Changed to Private .....	16
FormField.js: "visit()" Renamed to "visitFields" .....	16
Tree._visitNodes & Tree.visitNodes .....	16
Automatic Preloading of Web Fonts .....	16

Radio Button Group .....	17
Layout of Fields in Radio Button Group and Sequence Box .....	17
Form.open() .....	18
Status .....	18
MenuBar .....	18
LookupRow: Removed Constructor .....	18
Call: Skip Retries by Default (since 8.0.0.021) .....	18
ErrorHandler: Extended Support for Arbitrary Errors (since 8.0.0.021) .....	19
SmartField / DateField: Renamed touch to touchMode (since 8.0.0.021) .....	20
Other Changes .....	21
jQuery Update .....	21

# About This Document

This document describes all relevant changes **from Eclipse Scout 7.0 to Eclipse Scout 8.0**. If existing code has to be migrated, instructions are provided here.

## Service Release Migration

After the final Eclipse Photon release, there are no more Eclipse *service releases* (see [the Simultaneous Release Cycle FAQ](#) for details). Scout 8.0 will continue to be maintained for a while and a new build may be released from time to time. Beside bugfixes, these releases may even contain some minor features.

The following changes were made after the initial 8.0 release.

### Simrel 2018-09 — Released on September 19, 2018

The initial release of this version was **8.0.0.021** (Maven: 8.0.0.021\_Simrel\_2018\_09)

- [SmartField](#): changed behavior for applying styles from a lookup-row on the field (since 8.0.0.021)
- [\[Moved mail related classes to new module to org.eclipse.scout.rt.mail \(since 8.0.0.021\)\]](#)
- [Call](#): Skip Retries by Default (since 8.0.0.021)
- [ErrorHandler](#): Extended Support for Arbitrary Errors (since 8.0.0.021)
- [SmartField / DateField](#): Renamed touch to touchMode (since 8.0.0.021)
- [Deprecated Methods on DefaultAuthToken and Introduced DefaultAuthTokenSigner and DefaultAuthTokenVerifier](#) (since 8.0.0.021)

### Simrel 2018-12 — Released on December 19, 2018

The initial release of this version was **8.0.0.031** (Maven: 8.0.0.031\_Simrel\_2018\_12)

### Upcoming — No Planned Release Date

The following changes were made after the latest official release build. No release date has been fixed yet.



The here described functionality has not yet been released and is part of an upcoming release.

- [StyleHelper Moved to Platform](#) (since 8.0.0.034)

## API Changes (Java)

# Java 8 Required

The required Java Runtime Environment (JRE) to run an Eclipse Scout application has changed: Starting with Eclipse Scout 8.0, a **Java 8 runtime is required**.



The Scout 8.0 Runtime does not support Java 9 yet. The Java 9 support is planned for Eclipse *Photon* release (Scout 8.0) in summer 2018.

To reflect this change, some existing Scout classes have been migrated to the newly available Java 8 classes:

Old Scout class:	Replaced with Java 8 equivalent:
<code>org.eclipse.scout.rt.platform.filter.IFilter</code>	<code>java.util.function.Predicate</code>
<code>org.eclipse.scout.rt.platform.filter.AlwaysFilter</code>	<code>java.util.function.Predicate</code> e.g. <code>a → true</code>
<code>org.eclipse.scout.rt.platform.filter.NotFilter</code>	<code>java.util.function.Predicate#negate</code>
<code>org.eclipse.scout.rt.platform.filter.OrFilter</code>	<code>java.util.function.Predicate#or</code>
<code>org.eclipse.scout.rt.platform.util.concurrent.IConsumer</code>	<code>java.util.function.Consumer</code>
<code>org.eclipse.scout.rt.platform.util.concurrent.IFunction</code>	<code>java.util.function.Function</code>
<code>org.eclipse.scout.rt.platform.util.concurrent.IBiConsumer</code>	<code>java.util.function.BiConsumer</code>
<code>org.eclipse.scout.rt.platform.util.concurrent.IBiFunction</code>	<code>java.util.function.BiFunction</code>
<code>org.eclipse.scout.rt.client.ui.action.IActionFilter</code>	<code>java.util.function.Predicate&lt;IAction&gt;</code>

## CalendarComponent

Removed deprecated method `Date[]` `getCoveredDays()` on `org.eclipse.scout.rt.client.ui.basic.calendar.CalendarComponent`.

*Migration:* Use `Range<Date>` `getCoveredDaysRange()` instead with start and end date.

## AbstractCacheValueResolver

Abstract implementation was replaced by default method in interface `ICacheValueResolver`.

*Migration:* Implement interface `ICacheValueResolver` directly instead of extending `AbstractCacheValueResolver`.

## Deprecation of SequenceBox EqualColumnWidths

The methods `SequenceBox#getConfiguredEqualColumnWidths()`, `SequenceBox#isEqualColumnWidths()` and `SequenceBox#setEqualColumnWidths()` have been deprecated. As this property was not used by Scout since several releases it can be deleted.

You can search for these method names in your code to find any usages. Alternatively your IDE may mark the usage of deprecated methods (depends on settings).

## Removed Constants/Methods From ClientUIPreferences

Since the new Html UI was introduced with Scout 5.2 some constants and methods in `ClientUIPreferences` had no effect on the UI anymore. Since Scout is now a browser application we don't have any control over the application window anymore. The form bounds are stored in the local browser storage thus they're not required in the Java model anymore.

The following constants/methods were dropped:

- ~~APPLICATION\_WINDOW\_MAXIMIZED~~
- ~~APPLICATION\_WINDOW\_BOUNDS~~
- ~~FORM\_BOUNDS~~
- ~~getFormBounds()~~
- ~~setFormBounds(IForm form, Rectangle bounds)~~
- ~~getApplicationWindowMaximized()~~
- ~~setApplicationWindowPreferences(BoundsSpec r, boolean maximized)~~

## Removed Property "focusable" From IFormField, AbstractFormField

Since the new Html UI was introduced with Scout 5.2 the property `focusable` had no effect on the UI anymore. Instead the UI uses sensible defaults for each field type. For instance: a *LabelField* is never focusable, a normal *StringField* is always focusable, as long as it is enabled. Since the property was rarely used, we removed the related code:

- Method ~~boolean IFormField#isFocusable()~~
- Method ~~void IFormField#setFocusable(boolean f)~~
- Field ~~boolean IFormField#PROP\_FOCUSABLE~~
- Method ~~boolean AbstractFormField#getConfiguredFocusable()~~
- Class ~~AbstractNonFocusableButton~~
- Class ~~AbstractNonFocusableRadioButton~~

*Migration:* Since there is no replacement for the `focusable` property, remove all code that uses one of the methods/properties listed above.

## Removal of Old "SmartField", Renaming of "SmartField2" Back to "SmartField"

In Scout 7.0 a new smart field implementation named *SmartField2* was created. The old implementation was still available, but its use was discouraged. With Scout 8.0 the old *SmartField*

implementation was finally dropped. The new implementation *SmartField2* was renamed back to *SmartField*.

The following table lists the different names used in the past Scout releases. (The naming applies to all associated files, such as interfaces, abstract field classes, Java packages and JavaScript and LESS files.)

Scout <= 6.1	Scout 7.0	Scout >= 8.0
SmartField ( <i>old implementation</i> )	SmartField ( <i>old implementation</i> )	&mdash;
&mdash;	SmartField2 (new implementation)	SmartField (new implementation)

*Migration:*

- If you have already used the new *SmartField2* in Scout 7.0 you must move / rename all references back to the (new) *SmartField*.
- If you are migrating from an older Scout version (<= 6.1), you *might* have to adjust your code to the new implementation. See the corresponding 7.0 migration guide.

## IContentAssistField Classes and Interfaces Removed

The base class and interfaces of the old SmartField implementation was IContentAssistField. With the new SmartField implementation this interfaces and all classes containing the word "ContentAssist" in their name, have been either removed or renamed to "SmartField". If your code references one of these classes you should simply try to rename all references. Since the API of the new SmartField is almost the same as the old, this should work and should cause no or few changes in your code. The following classes have been removed without replacement:

- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.AbstractMixedSmartField~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.ContentAssistFieldEvent~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.ContentAssistFieldListener~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.ContentAssistFieldTable~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.IMixedSmartField~~

Since the new SmartField implementation does not have a proposal chooser model anymore these classes have also been removed. If you must have a special implementation of a proposal chooser, you must implement a proposal chooser in JavaScript (see: *ProposalChooser.js*), which renders the data and lookup rows it receives from the server-side SmartField. The following classes have been removed without replacement:

- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.AbstractProposalChooser~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.IProposalChooser~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.IProposalChooserProvider~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.TableProposalChooser~~
- ~~org.eelipse.scout.rt.client.ui.form.fields.smartfield.TreeProposalChooser~~

## GroupBox: Moved "minWidthInPixel"

The property `minWidthInPixel` has been moved to `LogicalGridLayoutConfig`.

*Migration:* Instead of using `getConfiguredMinWidthInPixel` you should now set the property as follows:

```
@Override
protected LogicalGridLayoutConfig getConfiguredBodyLayoutConfig() {
    return super.getConfiguredBodyLayoutConfig()
        .withMinWidth(400);
}
```

## Adjusted Behavior of Widget Initialization

The goal was to harmonize all the init methods (`initField`, `initTile`, `initForm` etc.) and to make sure, `init()` is only executed once. This is important for dynamic widgets like accordion or tiles. These widgets initialize the newly added children by themselves so that the caller does not need to take care of it. For these cases it is important that `init()` is not called multiple times.

But: there may be cases which require `init()` to be called multiple times, like resetting a search form. For such cases, `reinit()` has to be used from now on. Also, after the widget is disposed, `init()` may be called again. So remember: `execInit` may be called more than once in some circumstances. This is existing behavior!

We also renamed the initConfig guard of `IFormField` from `isInitialized` to `isInitDone` to make clear what initialization has been done. It has furthermore been moved to `AbstractWidget` so that individual widgets don't have to care about it and to use the same pattern as for `init` and `dispose`.

These new methods (`init()`, `dispose()` and `reinit()`) handle the whole widget tree including all child widgets recursively. Child items that need initialization and are NO widgets must be initialized explicitly as it is already now. All children that are widgets must NOT be initialized because this is done automatically by the `AbstractWidget` implementation. To modify that behavior use the methods `initChildren()` or `disposeChildren()` (e.g. if you want to exclude a child widget from automatically getting initialized). This also means that the methods `ActionUtility.initActions()`, `ActionUtility.disposeActions()`, `FormUtility.postInitConfig()`, `FormUtility.initFormFields()` and `FormUtility.disposeFormFields()` have been removed because the corresponding method can be called directly on the instance instead. Use `widget.init()` or `widget.dispose()` instead of these utility functions.

Please note that the phase `postInit` has been removed for the items that supported it. The corresponding code can be moved to the end of the `initConfigInternal()` method instead.

We also renamed the initConfig guard of `IFormField` from `isInitialized` to `isInitDone` to make clear what initialization has been done. It has furthermore been moved to `AbstractWidget` so that individual widgets don't have to care about it and to use the same pattern as for `init` and `dispose`.

*Migration:*



If you used one of the deprecated methods (`initField`, `initAction` etc.), replace them with one of the following methods: `init`, `reinit` or `initInternal`.

- Use `init` if you created a field and need to initialize it.
- Use `reinit` if you explicitly want to reinitialize an already initialized field.
- Use `initInternal` if your custom widget overrides `initField`.

## GzipServletFilter

Replaced init parameters `get_pattern` and `post_pattern` with `content_types`. If you set these init parameters in your web.xml, replace or remove them accordingly.

## HttpCacheControl

The argument `pathInfo` has been removed from the method `HttpCacheControl.checkAndSetCacheHeaders` since it has no effect anymore.

## HttpProxy

HTTP Proxy doesn't set cache control `no-cache` header anymore.

## Replacement for IActionVisitor, ITreeVisitor, IFormFieldVisitor

A new tree visitor engine has been added to the `org.eclipse.scout.rt.platform.util.visitor` package. It contains classes to depth-first or breadth-first traverse any tree data structures. Use the class `org.eclipse.scout.rt.platform.util.visitor.TreeTraversals` as entry point.

This new visitors can be used on any widget and tree node. It replaces the former `IActionVisitor`, `ITreeVisitor` and `IFormFieldVisitor`. The `org.eclipse.scout.rt.client.ui.IWidget` interface also declares various overloads accepting `java.util.function.Consumer`, `java.util.function.Function` and the new `org.eclipse.scout.rt.platform.util.visitor.IDepthFirstTreeVisitor` and `org.eclipse.scout.rt.platform.util.visitor.IBreadthFirstTreeVisitor`. Depending on how much control and data you need for your visitor the matching type can be used.

Until now only pre-order visitors have been available on these items. Therefore the migration to the new visitor takes the following steps:

- `visitFields` or `acceptVisitor` method on `IFormField` or `IAction` have been replaced with the `visit` method on `IWidget`.
- The new visitor allows to control how visiting should be continued in a more detailed level. Instead returning `true` or `false` to indicate if visiting should continue all options as defined in `org.eclipse.scout.rt.platform.util.visitor.TreeVisitResult` are available. A return value of `TreeVisitResult.CONTINUE` corresponds to `true` and a return value of `false` can be migrated to `TreeVisitResult.TERMINATE`.

- If using the `IDepthFirstTreeVisitor` the method `preVisit` must be overridden to have the same functionality as before. Consider also using the `DepthFirstTreeVisitorAdapter` instead of directly using the interface.
- If the visitor should only be called for a certain type of input element and just continue visiting for all others the overloads defining a type filter can be used for widgets. Using this instance of checks and type casts are often not necessary anymore.
- There is a `org.eclipse.scout.rt.platform.util.visitor.CollectingVisitor` class to convert the items of a tree to a list.
- `IFormField.visitParents` takes a `java.util.function.Predicate<IFormField>` instead of an `IFormFieldVisitor`.

## New Convenience Methods on IFormField

There are new methods for setting mandatory state (`setMandatory`), status visibility (`setStatusVisible`), field style (`setFieldStyle`) and disabled style (`setDisabledStyle`) that allow to specify if child form fields should be changed as well.

So if you have overridden one of these methods in your code, please override the new one instead. The method now takes an additional boolean flag to indicate if children should be processed as well.

## Config Properties

### Descriptions

Config properties based on `org.eclipse.scout.rt.platform.config.IConfigProperty` include a description text. This description is stored in the new `description()` method.

All properties must now implement this new method and return a description text of that property. The class `org.eclipse.scout.rt.platform.config.ConfigDescriptionExporter` can be used to export these descriptions. By default an `AsciiDoctor` exporter is included.

### Default value

Config properties based on `org.eclipse.scout.rt.platform.config.IConfigProperty` include a default value. The default value is stored in the `getDefaultValue()` method.

The `method` was moved from `org.eclipse.scout.rt.platform.config.AbstractConfigProperty<DATA_TYPE, RAW_TYPE>` to the interface. Therefore the visibility has changed from protected to public.

### Validation

The concrete implementation `org.eclipse.scout.rt.platform.config.ConfigPropertyValidator` which validates the configuration of `config.properties` files will also check if a configured value matches the default value. In case it does a info message (warn in development mode) will be logged but the platform will still start.

To minimize configuration files such entries should be removed from `config.properties` files.

## Renamed Config Property Keys

The following config property keys have been renamed (the old keys are no longer valid and must be renamed accordingly):

*Table 1. Config Property Renames*

Old Key	New Key
<code>scout.auth.anonymous.enabled</code>	<code>scout.auth.anonymousEnabled</code>
<code>scout.auth.cookie.enabled</code>	<code>scout.auth.cookieEnabled</code>
<code>scout.auth.cookie.maxAge</code>	<code>scout.auth.cookieMaxAge</code>
<code>scout.auth.cookie.name</code>	<code>scout.auth.cookieName</code>
<code>scout.auth.cookie.session.validate.secure</code>	<code>scout.auth.cookieSessionValidateSecure</code>
<code>scout.auth.credentials.plaintext</code>	<code>scout.auth.credentialsPlaintext</code>
<code>scout.auth.publickey</code>	<code>scout.auth.publicKey</code>
<code>scout.auth.privatekey</code>	<code>scout.auth.privateKey</code>
<code>scout.auth.token.ttl</code>	<code>scout.auth.tokenTtl</code>
<code>scout.server.url</code>	<code>scout.backendUrl</code>
<code>session.jobCompletionDelayOnSessionShutdown</code>	<code>scout.client.jobCompletionDelayOnSessionShutdown</code>
<code>org.eclipse.scout.memory</code>	<code>scout.client.memoryPolicy</code>
<code>notification.user.authenticator</code>	<code>scout.client.notificationSubject</code>
<code>org.eclipse.scout.testing.client.ClientSessionProviderWithCache#expiration</code>	<code>scout.client.testingSessionTtl</code>
<code>user.area</code>	<code>scout.client.userArea</code>
<code>org.eclipse.scout.rt.server.clientnotification.ClientNotificationService#maxMessages</code>	<code>scout.clientnotification.chunkSize</code>
<code>org.eclipse.scout.rt.server.clientnotification.ClientNotificationService#blockingTimeout</code>	<code>scout.clientnotification.maxNotificationBlockingTimeout</code>
<code>org.eclipse.scout.rt.server.clientnotification.ClientNotificationNodeQueue#capacity</code>	<code>scout.clientnotification.nodeQueueCapacity</code>
<code>org.eclipse.scout.rt.server.clientnotification.ClientNotificationRegistry#m_queueExpireTime</code>	<code>scout.clientnotification.notificationQueueExpireTime</code>
<code>org.eclipse.scout.rt.server.services.common.clustersync.ClusterSynchronizationService#user</code>	<code>scout.clustersync.user</code>
<code>scout.beans.createTunnelToServerBeans</code>	<code>scout.createTunnelToServerBeans</code>
<code>scout.csp.enabled</code>	<code>scout.cspEnabled</code>
<code>scout.csp.directive</code>	<code>scout.cspDirective</code>
<code>scout.dev.mode</code>	<code>scout.devMode</code>
<code>scout.external.base.url</code>	<code>scout.externalBaseUrl</code>
<code>scout.healthcheck.remoteUrls</code>	<code>scout.healthCheckRemoteUrls</code>
<code>scout.http.apache_connection_time_to_live</code>	<code>scout.http.connectionTtl</code>
<code>scout.http.ignore_proxy</code>	<code>scout.http.ignoreProxyPatterns</code>
<code>scout.http.apache_keep_alive</code>	<code>scout.http.keepAlive</code>
<code>scout.http.apache_max_connections_per_route</code>	<code>scout.http.maxConnectionsPerRoute</code>

Old Key	New Key
scout.http.apache_max_connections_total	scout.http.maxConnectionsTotal
scout.http.proxy	scout.http.proxyPatterns
scout.http.apache_retry_post	scout.http.retryPost
scout.http.transport_factory	scout.http.transportFactory
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#host	scout.imap.host
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#mailbox	scout.imap.mailbox
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#password	scout.imap.password
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#port	scout.imap.port
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#sslProtocols	scout.imap.sslProtocols
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#userName	scout.imap.username
jandex.rebuild	scout.jandex.rebuild
jaxws.consumer.connectTimeout	scout.jaxws.consumer.connectTimeout
jaxws.consumer.portCache.corePoolSize	scout.jaxws.consumer.portCache.corePoolSize
jaxws.consumer.portCache.enabled	scout.jaxws.consumer.portCache.enabled
jaxws.consumer.portCache.ttl	scout.jaxws.consumer.portCache.ttl
jaxws.consumer.portPool.enabled	scout.jaxws.consumer.portPoolEnabled
jaxws.consumer.readTimeout	scout.jaxws.consumer.readTimeout
jaxws.implementor	scout.jaxws.implementor
jaxws.loghandler.debug	scout.jaxws.loghandlerDebug
jaxws.provider.authentication.basic.realm	scout.jaxws.provider.authentication.basicRealm
jaxws.provider.user.authenticator	scout.jaxws.provider.user.authenticator
jaxws.provider.user.handler	scout.jaxws.provider.user.handler
scout.mom.requestreply.cancellation.topic	scout.mom.requestreply.cancellationTopic
scout.node.id	scout.nodeId
scout.permission.level.check.cache.ttl	scout.permissionLevelCacheTtl
org.eclipse.scout.rt.server.services.common.file.RemoteFileService#rootPath	scout.remotefileRootPath
org.eclipse.scout.rt.server.session.ServerSessionProviderWithCache#expiration	scout.serverSessionTtl
org.eclipse.scout.serviceTunnel.compress	scout.servicetunnel.compress
org.eclipse.scout.rt.servicetunnel.apache_max_connections_per_route	scout.servicetunnel.maxConnectionsPerRoute
org.eclipse.scout.rt.servicetunnel.apache_max_connections_total	scout.servicetunnel.maxConnectionsTotal
org.eclipse.scout.rt.servicetunnel.targetUrl	scout.servicetunnel.targetUrl
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#debugReceiverEmail	scout.smtp.debugReceiverEmail
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#defaultFromEmail	scout.smtp.defaultFromEmail

Old Key	New Key
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#host	scout.smtp.host
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#password	scout.smtp.password
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#port	scout.smtp.port
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#sslProtocols	scout.smtp.sslProtocols
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#subjectPrefix	scout.smtp.subjectPrefix
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#useAuthentication	scout.smtp.useAuth
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#username	scout.smtp.username
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#useSmtps	scout.smtp.useSsl
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#directJdbcConnection	scout.sql.jdbc.driverName
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcDriverName	scout.sql.jdbc.driverUnload
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcDriverUnload	scout.sql.jdbc.mappingName
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcMappingName	scout.sql.jdbc.pool.connectionBusyTimeout
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcPoolConnectionBusyTimeout	scout.sql.jdbc.pool.connectionIdleTimeout
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcPoolConnectionLifetime	scout.sql.jdbc.pool.size
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcPoolSize	scout.sql.jdbc.properties
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcProperties	scout.sql.jdbc.statementCacheSize
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcStatementCacheSize	scout.sql.jndi.initialContextFactory
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiInitialContextFactory	scout.sql.jndi.name
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiName	scout.sql.jndi.providerUrl
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiProviderUrl	scout.sql.jndi.urlPkgPrefixes
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiUrlPkgPrefixes	scout.sql.password
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#password	scout.sql.transactionMemberId
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#transactionMemberId	scout.sql.username
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#username	

Old Key	New Key
<code>scout.text.providers.show.keys</code>	<code>scout.texts.showKeys</code>
<code>scout.background.polling.interval</code>	<code>scout.ui.backgroundPollingMaxWaitTime</code>
<code>scout.max.user.idle.time</code>	<code>scout.ui.maxUserIdleTime</code>
<code>scout.ui.model.jobs.await.timeout</code>	<code>scout.ui.modelJobTimeout</code>
<code>scout.sessionstore.housekeepingDelay</code>	<code>scout.ui.sessionstore.housekeepingDelay</code>
<code>scout.sessionstore.housekeepingMaxWaitForShutdown</code>	<code>scout.ui.sessionstore.housekeepingMaxWaitForShutdown</code>
<code>scout.sessionStore.maxWaitForAllShutdown</code>	<code>scout.ui.sessionStore.maxWaitForAllShutdown</code>
<code>scout.sessionStore.valueUnboundMaxWaitForWriteLock</code>	<code>scout.ui.sessionStore.valueUnboundMaxWaitForWriteLock</code>

## Customizing CSP Rules Via Config Property

The new config property `scout.cspDirective` makes subclassing and replacing the `ContentSecurityPolicy` class obsolete as you can configure all CSP settings with this property now. An example from the Scout Widgets application:

```
@Replace
public class WidgetsContentSecurityPolicy extends ContentSecurityPolicy {

    @Override
    protected void initDirectives() {
        super.initDirectives();
        // Demo app uses external images in html field and custom widgets -> allow it
        withImgSrc("*");
    }
}
```

This class was deleted and replaced by a config property in `config.properties`:

```
# CSP - Demo app uses external images in html field and custom widgets -> allow it
scout.cspDirective[img-src]=*
```

## UIServletRequestHandler

The methods `handleGet` and `handlePost` on `UIServletRequestHandler` were replaced by the single method `handle`. This new method is called for all HTTP methods.

To retrieve the HTTP method, call `getMethod` on `HttpServletRequest`. When using `AbstractUIServletRequestHandler` no migration should be required because `AbstractUIServletRequestHandler` delegates to the Java methods for the common HTTP methods `handleGet`, `handlePost`, `handlePut` and `handleDelete`.

Methods `proxyGet` and `proxyPost` on `HttpProxy` are replaced by the common method `proxy`.

## Table: Remove Obsolete "POPULATED" Event and Methods

We removed remnants of the long-obsolete "population" event in tables:

- ~~`ITable.tablePopulated()`~~
- ~~`TableEvent.TYPE_TABLE_POPULATED`~~

*Migration:* Remove any references to the removed method or event from your code. (This should not cause any change in behavior, as the event was not fired by Scout anyways.)

## PageField: Status of Page Table Visible by Default

The table field contained in a *PageField* used to have `statusVisible` set to *false*. This default was changed back to *true* to make it consistent with all other fields. Whether the status should be invisible can only be determined correctly by the programmer, because the *PageField* can not know about the status visibility in the inner forms (search form and search form).

*Migration:* To hide the status of a specific *PageField*'s table field, override `execInitField()` and set the desired status visibility:

```
public class MyPageField extends AbstractPageField<MyTablePage> {  
  
    @Override  
    protected void execInitField() {  
        getTableField().setStatusVisible(false); // <--  
    }  
}
```

## SmartField: changed behavior for applying styles from a lookup-row on the field (since 8.0.0.021)

The *SmartField* in Scout ≤ 6.0 applied the lookup-row properties `foregroundColor`, `backgroundColor`, `font` and `toolTipText` automatically on the field when a lookup-row has been selected. Because that automatic behavior didn't fit every business requirement, we removed it completely. This means you must implement the property-synchronization where required.

Since we prefer to do styling with CSS and LESS, we now copy the `cssClass` property from the lookup-row to the field. In some cases this new feature can be used to migrate from older Scout version.

Check the *HowTo* section *SmartField: how to apply colors and styles from a lookup-row* in Scout's technical guide to find examples for migration and how to work with the `cssClass` property.

## AbstractIcons: Changed constants

- `AbstractIcons.Menu` ⇒ `AbstractIcons.MenuBold`
- `AbstractIcons.File` ⇒ `AbstractIcons.FileSolid`
- `AbstractIcons.Category` ⇒ `AbstractIcons.CategoryBold`

## Removed ActivityMapMenuType

For migration, simply remove any references to this class.

## Texts and Multi Language Support (NLS) Moved to Platform

The classes `AbstractDynamicNlsTextProviderService`, `ITextProviderService`, `ScoutTexts` and `TEXTS` have been moved from the shared module to the platform. Accordingly the package of these classes has been changed to `org.eclipse.scout.rt.platform.text`.

*Migration:* Change the `imports` in your `*.java` files accordingly.

## Moved Mail-Related Classes to New Module to `org.eclipse.scout.rt.mail` (since 8.0.0.021)

The following classes were moved from `org.eclipse.scout.rt.shared.mail` to a new module named `org.eclipse.scout.rt.mail` to the package `org.eclipse.scout.rt.mail`:

- `BinaryResourceDataSource`
- `CharsetSafeMimeMessage`
- `MailAttachment`
- `MailHelper`
- `MailMessage`
- `MailParticipant`
- `RFCWrapperPart`

For migration, replace all imports for `org.eclipse.scout.rt.shared.mail` by imports for `org.eclipse.scout.rt.mail` and add a dependency to the new module `org.eclipse.scout.rt.mail`.

A new helper `org.eclipse.scout.rt.mail.smtp.SmtHelper` replaces the service `org.eclipse.scout.rt.server.services.common.smtp.ISMTPService` and its abstract implementation `org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService`.

The only remaining property is `SmtDebugReceiverEmailProperty` (`scout.smtp.debugReceiverEmail`). The following properties are obsolete and configuration must be set in `org.eclipse.scout.rt.mail.smtp.SmtServerConfig`:



- `SmtphostProperty (scout.smtp.host)`
- `SmtpportProperty (scout.smtp.port)`
- `SmtptextProperty ('scout.smtp.username)`
- `SmtppasswordProperty (scout.smtp.password)`
- `SmtpsslprotocolsProperty (scout.smtp.sslProtocols)`
- `SmtptextAuthenticationProperty (scout.smtp.useAuth)`
- `SmtptextSmtptextProperty (scout.smtp.useSsl)`

`Smtphelper` has no support for subject prefix and default from email anymore.

If a subject prefix is required, i.e. the property `SmtptextSubjectPrefixProperty (scout.smtp.subjectPrefix)` was in use, the subject prefix must be prepended to the subject before calling `Smtphelper` by using `MailHelper.addPrefixToSubject`.

If a default from email is required, i.e. the property `SmtptextDefaultFromEmailProperty (scout.smtp.defaultFromEmail)` was in use, the default from email must be ensured before calling `Smtphelper` by using `MailHelper.ensureFromAddress`.

The following classes are marked deprecated:

- `org.eclipse.scout.rt.server.services.common.imap.IIMAPService`
- `org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService`
- `org.eclipse.scout.rt.server.services.common.imap.IImapAdapter`
- `org.eclipse.scout.rt.server.services.common.imap.ImapAdapter`

A new helper `org.eclipse.scout.rt.mail.imap.ImapHelper` provides some basic (stateless) functionality to connect to an IMAP server, find and create folders or move message to a new folder. Any other functionality must be implemented manually by operating on `javax.mail.Message` or `javax.mail.Folder` objects directly.

The following properties are obsolete and configuration must be set in `org.eclipse.scout.rt.mail.imap.ImapServerConfig`:

- `ImaphostProperty (scout.imap.host)`
- `ImapportProperty (scout.imap.port)`
- `ImapmailboxProperty (scout.imap.mailbox)`
- `ImaptextUsernameProperty (scout.imap.username)`
- `ImappasswordProperty (scout.imap.password)`
- `ImapsslprotocolsProperty (scout.imap.sslProtocols)`

`MailHelper#createMimeMessage` was improved regarding the structure of the generated mime message. So far a multipart message was always created, even if a simpler structure would have been enough. The new implementation only creates the required parts depending on the provided input: plain text, html, attachments and inline attachments (newly supported).

# Deprecated Methods on DefaultAuthToken and Introduced DefaultAuthTokenSigner and DefaultAuthTokenVerifier (since 8.0.0.021)

In order to be able to reuse authentication token code `DefaultAuthToken` was refactored. Signing and verifying of tokens is now separated from token and its (de-)serialization. The new classes `DefaultAuthTokenSigner` and `DefaultAuthTokenVerifier` do now provide this functionality.

## StyleHelper Moved to Platform (since 8.0.0.034)

The `StyleHelper` bean was moved from `org.eclipse.scout.rt.client` to `org.eclipse.scout.rt.platform`, so it is available to server-side code as well. The old `StyleHelper` bean in the `client` module was marked as deprecated and should no longer be used. It will eventually be removed in Scout 10.

*Migration:* Update your imports to point to the new `org.eclipse.scout.rt.platform.html.StyleHelper` bean. Methods that passed an `IStylable` as first argument are no longer available. Instead, directly call the corresponding method on the `IStylable` element itself.

# API Changes (JavaScript)

## Rename of LESS Variables

If you created a custom theme, you might have to adjust some LESS variables.

- Split `@group-title-padding-y` into `@group-box-title-padding-top` and `@group-box-title-padding-bottom`
- Split `@tree-node-padding` into `@tree-node-padding-y`, `@tree-node-padding-left` and `@tree-node-padding-right`
- Renamed `@group-title-border-width` to `@group-box-title-border-width`
- Renamed `@group-margin-bottom` to `@group-box-body-padding-bottom`
- Renamed `@group-margin-top` to `@group-box-body-padding-top`
- Added `@group-box-title-margin-top`
- Renamed `@tabbox-padding-x` to `@tab-item-padding-x`
- Renamed `@tabbox-focus-arrow-width` to `@tab-item-focus-arrow-width`
- Renamed `@tabbox-border-width` to `@tab-area-border-width`
- Renamed `@compact-outline-node-padding-v` to `@compact-outline-node-padding-y`
- Renamed `@box-margin-v` to `@box-margin-y`
- Renamed `@outline-breadcrumb-node-padding-v` to `@outline-breadcrumb-node-padding-y`
- Renamed `@tile-padding-h` to `@tile-field-padding-x`
- Renamed `@tile-padding-v` to `@tile-field-padding-y`

- Renamed `@planner-header-buttons` to `@planner-header-button-height`
- Renamed `@calendar-header-buttons` to `@calendar-header-button-height`
- Renamed `@logical-grid-height` to `@logical-grid-row-height`
- Renamed `@applink-color` to `@link-color`

## Widget.js: New Argument for clone()

The `clone()` function of any widget got an `options` parameter. The options define what properties and events are synchronized between the widget and its clone.

## Widget.js: "addChild" & "removeChild" Changed to Private

The methods `addChild()` and `removeChild()` have been renamed to `_addChild()` and `_removeChild()`. This means the methods are considered to have `private` visibility now. Use the methods `setParent()`, `setOwner()` and `destroy()` to connect or disconnect widgets. These methods will add or remove the child widget automatically.

## FormField.js: "visit()" Renamed to "visitFields"

The `visit()` method on all FormFields has been renamed to `visitFields()`. This change is necessary to clarify what is visited and to distinguish between the visit methods available on widget level (e.g. `visitChildren()`).

## Tree.\_visitNodes & Tree.visitNodes

The argument order of the method `scout.Tree.visitNodes` have changed from (nodes, func, parentNode) to (func, nodes, parentNode). So the func (the visitor) and the nodes to visit have changed positions.

The arguments of `scout.Tree.prototype._visitNodes` have changed from (nodes, func, parentNode) to (func, parentNode). So the nodes to visit must no longer be specified. Instead always the root nodes of the tree are used. Furthermore the method is public now and has therefore be renamed to `visitNodes()`.

## Automatic Preloading of Web Fonts

Scout can now detect the web fonts (\*.woff) to preload automatically. It's therefore no longer necessary to list the font names manually in the bootstrap argument of `scout.App`.

*Migration:*

Remove the `fonts` property from the bootstrap parameter object passed to the `init()` function of your Scout app.

For example, the default *index.js* file generated by the Scout "helloworld" archetype looks like this:

```
$(document).ready(function() {  
  var app = new scout.RemoteApp();  
  app.init({  
    bootstrap: {  
      fonts: ['scoutIcons'] // <-- this property is no longer required  
    }  
  });  
});
```

If no other init options remain, the file can be simplified to:

```
$(document).ready(function() {  
  var app = new scout.RemoteApp();  
  app.init();  
});
```



To find all files that need migration, search for the text `bootstrap: {` in all `*.js` files in your workspace. The files are called *index.js* by default and are usually located at *your.project.ui.html/src/main/resources/WebContent/res*.

This migration is recommended but optional. Listing all fonts to preload manually still works. To disable font preloading entirely, set the *fonts* bootstrap property to an empty array `[]`.

## Radio Button Group

- The property `formFields` has been renamed to `fields` to be consistent with the Java implementation and with other composites like `GroupBox`.
- The function `selectButton` now selects the button even if it is disabled. Only the user must not select disabled buttons but the developer should still be able to do it. If you use this function, you may have to insert a check for the enabled state.

## Layout of Fields in Radio Button Group and Sequence Box

Until now it was required to explicitly set grid positions for child fields of Radio Button Groups and Sequence Boxes. This was because the automatic grid layout was not yet implemented in the Scout JavaScript layer. This was no issue however if the fields have been used in connection with a Java model because then the Java layer takes care about the layout.

Now also pure JavaScript Scout applications have automatic layout for child fields of Radio Button Groups and Sequence Boxes. So if explicit grid positions (`gridData.x`, `gridData.y`) have been specified, it can be removed now as Scout takes care about it now (as it was in the Java layer already).

## Form.open()

`open()` now calls `load()` first before calling `show()`. The reason is to prevent showing an empty form before any data is loaded. If you relied on the previous behavior, (e.g. if you accessed ui properties like `$container` right after opening the form) you would need to put that code in a function executed delayed using `form.open().then()`.

## Status

The static function `scout.Status.warn()` was renamed to `scout.Status.warning()` to bring it in line with the name of the corresponding severity constant `scout.Status.Severity.WARNING`.

## MenuBar

In previous versions, right aligned menus were not stacked when there was not enough horizontal space. If this behavior is still required, the property `stackable` has to be set to `false`.

## LookupRow: Removed Constructor

The custom *LookupRow* constructor with key and text parameter was removed. LookupRows must be created using the `scout.create()` object factory call.

Old style code like:

```
var lookupRow = new scout.LookupRow(data[0], data[1]);
```

must be replaced by:

```
var lookupRow = scout.create('LookupRow', {  
  key: data[0],  
  text: data[1],  
  parentKey: data[2] ①  
});
```

① Optional parent key and other properties

## Call: Skip Retries by Default (since 8.0.0.021)

`Call` objects no longer perform retries by default. Retries should only be active if the target service can handle repeated calls correctly.

The use retries, specify the desired number of maximal retries or a *retryIntervals* array in the model when creating the `Call` object:

```
var call1 = scout.create('AjaxCall', {
  ajaxOptions: { ... }
  maxRetries: 5
});
var call2 = scout.create('AjaxCall', {
  ajaxOptions: { ... }
  retryIntervals: [100, 200, 500, 500, 500];
});
```

## ErrorHandler: Extended Support for Arbitrary Errors (since 8.0.0.021)

Because errors that happen in asynchronous calls (promise chains) are not delegated to the `window.onerror` handler, Scout's `ErrorHandler` class was extended. It can now be used to handle arbitrary errors in "catch" clauses or "promise fail" functions. As a consequence, the signature of the `handle()` has been changed. It used to be hard-wired to the `window.onerror` event. Now it supports a flexible number of arguments.

A global instance of `ErrorHandler` is still being installed as the `window.onerror` handler. Additionally, this instance is now available as `scout.errorHandler`.

Example usages:

```
// Handling errors in "try" blocks
try {
  // ...
} catch (err) {
  scout.errorHandler.handle(err);
}

// Handle errors in jQuery AJAX calls
$.ajax ajaxOptions)
  .done(function(data, textStatus, jqXHR) {
    /* handle success */
  })
  .fail(function(jqXHR, textStatus, errorThrown) {
    // Style 1:
    scout.errorHandler.handle(jqXHR, textStatus, errorThrown);
    // Style 2 (recommended!):
    scout.errorHandler.handle(arguments);
  })

// Handling errors in promises
doSomethingAsynchronous()
  .then(function() { /* handle result */ })
  .then(function() { /* more handling */ })
  .fail(function() {
    scout.errorHandler.handle(arguments);
  });
```

#### Migration:

Projects that implemented their own `ErrorHandler` must update their code.

- Instead of overriding `handle()`, override `_onWindowError()`.
- Please note that the method `createLogMessage()` no longer exists. If you still need it, copy it from the old implementation or use `analyzeError()` to calculate a similar result.

## SmartField / DateField: Renamed touch to touchMode (since 8.0.0.021)

Smart fields and date fields use the property `touch` to indicate that the field is running in touch mode. Unfortunately this property overrides the function `touch()` of the `FormField`. This means `touch()` cannot be used for these fields, which was not intended.

*Migration:* The property `touch` is actually set automatically, so most people don't have to migrate anything. If you set the property manually (e.g. to always run such a field in touch mode), you need to rename it to `touchMode`.

# Other Changes

## jQuery Update

The jQuery version bundled with Scout has been updated to version 3.3.1. If a *SpecRunnerMaven.html* is used to run Jasmine tests, the corresponding script tag must be updated to include `jquery-3.3.1.js` instead of `jquery-3.2.1.js`.



Do you want to improve this document? Have a look at the [sources](#) on GitHub.