

Eclipse Scout

Migration Guide

Scout Team

Version 7.1

Table of Contents

About This Document	1
Service Release Migration	1
API Changes (Java)	1
Removed property focusable from IFormField, AbstractFormField	1
ISmartField2 replaced old ISmartField	2
IContentAssistField classes and interfaces removed	2
GroupBox: moved minWidthInPixel	2
Config Properties	3
Descriptions	3
Default value	3
Validation	3
Renamed Config Property Keys	3
Default Values Validation	7
API Changes (JavaScript)	7
Other Changes	7

About This Document

This document describes all relevant changes **from Eclipse Scout 7.0 to Eclipse Scout 7.1**. If existing code has to be migrated, instructions are provided here.



If you are upgrading from version 6.1, please also read the migration guide for the 7.0 (*Oxygen preview*) release:

<https://eclipsescout.github.io/7.0/migration-guide.html>

- [AbstractFormField](#)

Service Release Migration

The following changes were made after the initial 7.1 release (Eclipse Photon release). Additionally follow these instructions when updating to a *service release*.

Photon.1 (7.1.100) Release expected on September, 2018

Attention: The here described functionality has not yet been released and is part of an upcoming release.

API Changes (Java)

Removed property **focusable** from IFormField, AbstractFormField

Since the new Html UI was introduced with Scout 5.2 this property had no effect on the UI anymore. Instead the UI uses sensible defaults for each field type. For instance: a LabelField is never focusable, a normal StringField is always focusable, as long as it is enabled. Since the property was rarely used, we removed all methods from the interface/class FormField. Removed methods/properties:

- boolean IFormField#isFocusable()
- void IFormField#setFocusable(boolean f)
- boolean IFormField#PROP_FOCUSABLE
- boolean AbstractFormField#getConfiguredFocusable()
- class AbstractNonFocusableButton
- class AbstractNonFocusableRadioButton

Since there is no replacement for the focusable property, remove all code that uses one of the methods/properties listed above.

ISmartField2 replaced old ISmartField

In Scout 7.0 the new SmartField implementation used the package and name `smartfield2.SmartField2`. With Scout 7.1 the new SmartField replaced the old SmartField completely, and thus was moved to and renamed to `smartfield.SmartField`. If you have already used the new SmartField in Scout 7.0 you must move / rename all references to these classes.

IContentAssistField classes and interfaces removed

The base class and interfaces of the old SmartField implementation was IContentAssistField. With the new SmartField implementation this interfaces and all classes containing the word "ContentAssist" in their name, have been either removed or renamed to "SmartField". If your code references one of these classes you should simply try to rename all references. Since the API of the new SmartField is almost the same as the old, this should work and should cause no or few changes in your code. The following classes have been removed without replacement:

- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.AbstractMixedSmartField`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.ContentAssistFieldEvent`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.ContentAssistFieldListener`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.ContentAssistFieldTable`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.IMixedSmartField`

Since the new SmartImplementation does not have a proposal chooser model anymore these classes have also been removed. If you must have a special implementation of a proposal chooser, you must implement a proposal chooser in JavaScript (see: `ProposalChooser.js`), which renders the data / lookup-rows it receives from the server-side SmartField:

- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.AbstractProposalChooser`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.IProposalChooser`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.IProposalChooserProvider`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.TableProposalChooser`
- `org.eclipse.scout.rt.client.ui.form.fields.smartfield.TreeProposalChooser`

GroupBox: moved minWidthInPixel

The property `minWidthInPixel` has been moved to the object `LogicalGridLayoutConfig`. Instead of using `getConfiguredMinWidthInPixel` you should now set the property as follows:

```
@Override
protected LogicalGridLayoutConfig getConfiguredBodyLayoutConfig() {
    return super.getConfiguredBodyLayoutConfig()
        .withMinWidth(400);
}
```

Config Properties

Descriptions

Config properties based on `org.eclipse.scout.rt.platform.config.IConfigProperty` include a description text. This description is stored in the new `description()` method.

All properties must now implement this new method and return a description text of that property. The class `org.eclipse.scout.rt.platform.config.ConfigDescriptionExporter` can be used to export these descriptions. By default an AsciiDoctor exporter is included.

Default value

Config properties based on `org.eclipse.scout.rt.platform.config.IConfigProperty` include a default value. The default value is stored in the `getDefaultValue()` method.

The `method` was moved from `org.eclipse.scout.rt.platform.config.AbstractConfigProperty<DATA_TYPE, RAW_TYPE>` to the interface. Therefore the visibility has changed from protected to public.

Validation

The concrete implementation `org.eclipse.scout.rt.platform.config.ConfigPropertyValidator` which validates the configuration of `config.properties` files will also check if a configured value matches the default value. In case it does a info message (warn in development mode) will be logged but the platform will still start.

To minimize configuration files such entries should be removed from `config.properties` files.

Renamed Config Property Keys

The following config property keys have been renamed (the old keys are no longer valid and must be renamed accordingly):

Table 1. Config Property Renames

Old Key	New Key
<code>scout.auth.anonymous.enabled</code>	<code>scout.auth.anonymousEnabled</code>
<code>scout.auth.cookie.enabled</code>	<code>scout.auth.cookieEnabled</code>

Old Key	New Key
scout.auth.cookie.maxAge	scout.auth.cookieMaxAge
scout.auth.cookie.name	scout.auth.cookieName
scout.auth.cookie.session.validate.secure	scout.auth.cookieSessionValidateSecure
scout.auth.credentials.plaintext	scout.auth.credentialsPlaintext
scout.auth.token.ttl	scout.auth.tokenTtl
scout.server.url	scout.backendUrl
session.jobCompletionDelayOnSessionShutdown	scout.client.jobCompletionDelayOnSessionShutdown
org.eclipse.scout.memory	scout.client.memoryPolicy
notification.user.authenticator	scout.client.notificationSubject
org.eclipse.scout.testing.client.ClientSessionProviderWithCache#expiration	scout.client.testingSessionTtl
user.area	scout.client.userArea
org.eclipse.scout.rt.server.clientnotification.ClientNotificationService#maxMessages	scout.clientnotification.chunkSize
org.eclipse.scout.rt.server.clientnotification.ClientNotificationService#blockingTimeout	scout.clientnotification.maxNotificationBlockingTimeout
org.eclipse.scout.rt.server.clientnotification.ClientNotificationNodeQueue#capacity	scout.clientnotification.nodeQueueCapacity
org.eclipse.scout.rt.server.clientnotification.ClientNotificationRegistry#m_queueExpireTime	scout.clientnotification.notificationQueueExpireTime
org.eclipse.scout.rt.server.services.common.clustersync.ClusterSynchronizationService#user	scout.clustersync.user
scout.beans.createTunnelToServerBeans	scout.createTunnelToServerBeans
scout.csp.enabled	scout.cspEnabled
scout.csp.directive	scout.cspDirective
scout.dev.mode	scout.devMode
scout.external.base.url	scout.externalBaseUrl
scout.healthcheck.remoteUrls	scout.healthCheckRemoteUrls
scout.http.apache_connection_time_to_live	scout.http.connectionTtl
scout.http.ignore_proxy	scout.http.ignoreProxyPatterns
scout.http.apache_keep_alive	scout.http.keepAlive
scout.http.apache_max_connections_per_route	scout.http.maxConnectionsPerRoute
scout.http.apache_max_connections_total	scout.http.maxConnectionsTotal
scout.http.proxy	scout.http.proxyPatterns
scout.http.apache_retry_post	scout.http.retryHost
scout.http.transport_factory	scout.http.transportFactory
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#host	scout.imap.host
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#mailbox	scout.imap.mailbox
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#password	scout.imap.password
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#port	scout.imap.port

Old Key	New Key
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#sslProtocols	scout.imap.sslProtocols
org.eclipse.scout.rt.server.services.common.imap.AbstractIMAPService#userName	scout.imap.username
jandex.rebuild	scout.jandex.rebuild
jaxws.consumer.connectTimeout	scout.jaxws.consumer.connectTimeout
jaxws.consumer.portCache.corePoolSize	scout.jaxws.consumer.portCache.corePoolSize
jaxws.consumer.portCache.enabled	scout.jaxws.consumer.portCache.enabled
jaxws.consumer.portCache.ttl	scout.jaxws.consumer.portCache.ttl
jaxws.consumer.portPool.enabled	scout.jaxws.consumer.portPoolEnabled
jaxws.consumer.readTimeout	scout.jaxws.consumer.readTimeout
jaxws.implementor	scout.jaxws.implementor
jaxws.loghandler.debug	scout.jaxws.loghandlerDebug
jaxws.provider.authentication.basic.realm	scout.jaxws.provider.authentication.basicRealm
jaxws.provider.user.authenticator	scout.jaxws.provider.user.authenticator
jaxws.provider.user.handler	scout.jaxws.provider.user.handler
scout.mom.requestreply.cancellation.topic	scout.mom.requestreply.cancellationTopic
scout.node.id	scout.nodeId
scout.permission.level.check.cache.ttl	scout.permissionLevelCacheTtl
org.eclipse.scout.rt.server.services.common.file.RemoteFileService#rootPath	scout.remotefileRootPath
org.eclipse.scout.rt.server.session.ServerSessionProviderWithCache#expiration	scout.serverSessionTtl
org.eclipse.scout.serviceTunnel.compress	scout.servicetunnel.compress
org.eclipse.scout.rt.servicetunnel.apache_max_connections_per_route	scout.servicetunnel.maxConnectionsPerRoute
org.eclipse.scout.rt.servicetunnel.apache_max_connections_total	scout.servicetunnel.maxConnectionsTotal
org.eclipse.scout.rt.servicetunnel.targetUrl	scout.servicetunnel.targetUrl
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#debugReceiverEmail	scout.smtp.debugReceiverEmail
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#defaultFromEmail	scout.smtp.defaultFromEmail
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#host	scout.smtp.host
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#password	scout.smtp.password
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#port	scout.smtp.port
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#sslProtocols	scout.smtp.sslProtocols
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#subjectPrefix	scout.smtp.subjectPrefix
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#useAuthentication	scout.smtp.useAuth
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#username	scout.smtp.username

Old Key	New Key
org.eclipse.scout.rt.server.services.common.smtp.AbstractSMTPService#useSmtps	scout.smtp.useSsl
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#directJdbcConnection	scout.sql.directJdbcConnection
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcDriverName	scout.sql.jdbc.driverName
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcDriverUnload	scout.sql.jdbc.driverUnload
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcMappingName	scout.sql.jdbc.mappingName
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcPoolConnectionBusyTimeout	scout.sql.jdbc.pool.connectionBusyTimeout
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcPoolConnectionLifetime	scout.sql.jdbc.pool.connectionIdleTimeout
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcPoolSize	scout.sql.jdbc.pool.size
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcProperties	scout.sql.jdbc.properties
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jdbcStatementCacheSize	scout.sql.jdbc.statementCacheSize
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiInitialContextFactory	scout.sql.jndi.initialContextFactory
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiName	scout.sql.jndi.name
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiProviderUrl	scout.sql.jndi.providerUrl
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#jndiUrlPkgPrefixes	scout.sql.jndi.urlPkgPrefixes
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#password	scout.sql.password
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#transactionMemberId	scout.sql.transactionMemberId
org.eclipse.scout.rt.server.services.common.jdbc.AbstractSqlService#username	scout.sql.username
scout.text.providers.show.keys	scout.texts.showKeys
scout.background.polling.interval	scout.ui.backgroundPollingMaxWaitTime
scout.max.user.idle.time	scout.ui.maxUserIdleTime
scout.ui.model.jobs.await.timeout	scout.ui.modelJobTimeout
scout.sessionstore.housekeepingDelay	scout.ui.sessionstore.housekeepingDelay
scout.sessionstore.housekeepingMaxWaitForShutdown	scout.ui.sessionstore.housekeepingMaxWaitForShutdown
scout.sessionStore.maxWaitForAllShutdown	scout.ui.sessionStore.maxWaitForAllShutdown
scout.sessionStore.valueUnboundMaxWaitForWriteLock	scout.ui.sessionStore.valueUnboundMaxWaitForWriteLock

Default Values Validation

API Changes (JavaScript)

N/A

Other Changes

N/A



Do you want to improve this document? Have a look at the [sources](#) on GitHub.