

Intro To Asymmetric Cryptography

RP1SEC

Avi Weinstock (aweinstock)

October 29, 2019

```
static inline void bn_rand_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &&
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        if (mod < (BN_ULONG)16) mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
}
```

Symmetric vs Asymmetric Cryptosystems

Examples of symmetric crypto:

- ▶ classical ciphers (caesar, vigenere)
- ▶ block ciphers (DES, AES)
- ▶ stream ciphers (OTP, RC4, Salsa20)
- ▶ hash functions (MD5, SHA256)
- ▶ MACs (HMAC, Poly1305)

Examples of asymmetric crypto:

- ▶ key exchange (Diffie-Hellman)
- ▶ encryption (RSA, ElGamal)
- ▶ signatures (RSA, DSA, Schnorr)
- ▶ homomorphic encryption (Paillier, RSA, Gentry)

```

static int prime_probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint32_t mod = NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test, */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mod[i] = (uint32_t)mod;
    }

    /* it has to be such that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (bits > BN_BITS2) {
        if (BN_rand_word(1, BN_BITS2 - 1)) {
            /* Avoid undefined behavior. */
            BN_ULONG limit = ((BN_ULONG)0) - get_word(rnd);
            size_t limit = ((BN_ULONG)1) << bits - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            delta = 0;
        } else {
            delta = BN_MASK2 - 1;
        }
    } else {
        delta = 0;
    }

    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mod[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) == 1 (except for 2) */
            if (((mod[i] + delta) % primes[i]) < 1) && (i > 1)) {
                delta += 2;
            }
        }
    }
}

```

What is the significance of RSA?

- ▶ Historically the first asymmetric cryptosystem (published in 1977)
- ▶ Named for its inventors: Rivest, Shamir, Adleman
- ▶ Very flexible: can be used for both encryption and signing, is multiplicatively homomorphic
- ▶ Easy to implement
- ▶ Easy to mess up implementing, on account of its flexibility

```
static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }

    /* If bits is greater than BN_BITS2 then we
     * must not exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        (void)BN_set_maxdelta(rnd, size_limit);
        maxdelta = size_limit;
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) rnd is greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) <= 1) {
                delta += 2;
            }
        }
    }
}
```

What is RSA?

- ▶ p and q are distinct large primes
- ▶ $n = p * q$
- ▶ $\varphi(n) = (p - 1) * (q - 1)$
- ▶ $e * d \equiv 1 \pmod{\varphi(n)}$
- ▶ (n, e) is the "public key"
- ▶ (p, q, d) is the "private key"
- ▶ $\text{enc}(x) = \text{rem}(x^e, n)$
- ▶ $\text{dec}(x) = \text{rem}(x^d, n)$

```
static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &&
        return 0;
    )

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) ||
                ((i > 1) && (rnd_word % primes[i]) == 0)) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
    return 1;
}
```

Example RSA encryption/decryption

- ▶ $n = p * q$
- ▶ $\varphi(n) = (p - 1) * (q - 1)$
- ▶ $e * d \equiv 1 \pmod{\varphi(n)}$
- ▶ $\text{enc}(x) = \text{rem}(x^e, n)$
- ▶ $\text{dec}(x) = \text{rem}(x^d, n)$
- ▶ $\text{pow}(x, k, n) = \text{rem}(x^k, n)$

- ▶ Public: $(n, e) = (667, 3)$
- ▶ Message "hi", encoded as $7 * 26 + 8 = 190$
- ▶ $\text{pow}(190, 3, 667) == 239$

```
static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;

        /* If bits is so small that it fits into a single word then we
         * additionally don't want to exceed that many bits. */
        if (is_single_word) {
            BN_ULONG size_limit =
                /* random number between 0 and 2^bits - 1 */
                size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
    return 1;
}
```

Example RSA encryption/decryption

- ▶ $n = p * q$
- ▶ $\varphi(n) = (p - 1) * (q - 1)$
- ▶ $e * d \equiv 1 \pmod{\varphi(n)}$
- ▶ $\text{enc}(x) = \text{rem}(x^e, n)$
- ▶ $\text{dec}(x) = \text{rem}(x^d, n)$
- ▶ $\text{pow}(x, k, n) = \text{rem}(x^k, n)$

▶ Public: $(n, e) = (667, 3)$

▶ Message "hi", encoded as $7 * 26 + 8 = 190$

▶ $\text{pow}(190, 3, 667) == 239$

▶ Private: $(p, q, d) = (23, 29, 411)$

▶ $(3 * 411) \% (22 * 28) == 1$

▶ $\text{pow}(239, 411, 23 * 29) == 190$

```
static prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;

        /* If bits is so small that it fits into a single word then we
         * additionally don't want to exceed that many bits. */
        if (is_single_word) {
            BN_ULONG size_limit =
                /* (BN_ULONG)-1 is the largest BN_ULONG value */
                size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
        delta = 0;

        /* In the case that the candidate prime is a single word then
         * don't test:
         * 1) if it's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) that it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
            }
        }
    }
}
```

Euclidean division

$$\begin{array}{r}
 27 \leftarrow q \\
 3 \overline{) 82} \leftarrow x \\
 \underline{6} \\
 22 \\
 \underline{21} \\
 1 \leftarrow r
 \end{array}$$

$y \rightarrow 3$
 $x \rightarrow 82$
 $r \rightarrow 1$

- ▶ $\forall x, y \exists q, r (y * q + r = x)$
- ▶ $q = \text{quot}(x, y)$
- ▶ $r = \text{rem}(x, y)$
- ▶ $0 \leq r < y$
- ▶ $3 * 27 + 1 = 82$

```

static inline prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* 0 and 1 defined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
}
    
```

Modular congruence and primes

Divides cleanly/Is divisor of:

- ▶ $\text{divides}(x, y) \leftrightarrow \text{rem}(y, x) = 0$
- ▶ e.g. $\text{divides}(5, 10)$, since $10 \% 5 == 0$

Modular congruence:

- ▶ $x \equiv y \pmod{n} \leftrightarrow \text{divides}(x - y, n)$
- ▶ $x \equiv y \pmod{n} \leftrightarrow \text{rem}(x, n) = \text{rem}(y, n)$

Primeness:

- ▶ $\text{prime}(p) \leftrightarrow \forall k \in [2, p-1](\neg \text{divides}(k, p))$
- ▶ `def prime(p):`
 `return all([p % k != 0 for k in range(2,p)])`

`assert filter(prime, range(2, 20)) == [2, 3, 5, 7, 11, 13, 17, 19]`

Greatest Common Divisor:

- ▶ $\text{gcd}(x, y) = \max\{k | \text{divides}(k, x) \wedge \text{divides}(k, y)\}$
- ▶ `def gcd(x, y):`
 `return max([1]+[k for k in range(1, x*y) if x % k == 0 and y % k == 0])`

```
static int prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &
        return 0;
    }


    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) <= 1) {
                delta += 2;
            }
        }
    }
}
```


Modular arithmetic

- ▶ Let \mathbb{Z}_n denote $\{\text{rem}(x, n) \mid x \in \mathbb{Z}\}$, or equivalently, $[0, n)$.
- ▶ We can truncate addition and multiplication to work within \mathbb{Z}_n by calculating remainders after each operation
- ▶ "Clock arithmetic": in \mathbb{Z}_{12} , $9 + 4 = 1$, since $\text{rem}(9 + 4, 12) = \text{rem}(13, 12) = 1$



```
static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint32_t mods[NUMPRIMES];
    BN_ULONG deltas;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

main:
    if (!rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }
    /* We are going to work with a word at a time. */
    BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
    if (mod == (BN_ULONG)-1) {
        return 0;
    }
    mods[i] = (uint32_t)mod;
    /* If it's small that it fits into a single word then we
       don't really don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if ((BN_BITS2) {
            /* Good behavior. */
            (BN_ULONG)0) = get_word(rnd);
            ((BN_ULONG)1) << bits) = get_word(rnd) - 1;
        } else {
            /* prime is a single word then
               because we shouldn't reject
               because it's a multiple of
               a known prime. We don't
               prime to all the known
               many small primes where
               es[i] < rnd_word; i++) {
                   es[i] == 0) {
                       PRIMES; i++) {
                           /* It is not a prime and also
                              (rnd-1-prime) == 1 (except for 2) */ w/
                           if (((mods[i] + delta % primes[i]) <- 1) <=
                               delta % 2;
```

Addition and Multiplication mod 7

+	0	1	2	3	4	5	6
0	0	1	2	3	4	5	6
1	1	2	3	4	5	6	0
2	2	3	4	5	6	0	1
3	3	4	5	6	0	1	2
4	4	5	6	0	1	2	3
5	5	6	0	1	2	3	4
6	6	0	1	2	3	4	5

*	0	1	2	3	4	5	6
0	0	0	0	0	0	0	0
1	0	1	2	3	4	5	6
2	0	2	4	6	1	3	5
3	0	3	6	2	5	1	4
4	0	4	1	5	2	6	3
5	0	5	3	1	6	4	2
6	0	6	5	4	3	2	1

```

static int prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;
loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);
        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
}

```

Addition and Multiplication mod 8

+	0	1	2	3	4	5	6	7
0	0	1	2	3	4	5	6	7
1	1	2	3	4	5	6	7	0
2	2	3	4	5	6	7	0	1
3	3	4	5	6	7	0	1	2
4	4	5	6	7	0	1	2	3
5	5	6	7	0	1	2	3	4
6	6	7	0	1	2	3	4	5
7	7	0	1	2	3	4	5	6

*	0	1	2	3	4	5	6	7
0	0	0	0	0	0	0	0	0
1	0	1	2	3	4	5	6	7
2	0	2	4	6	0	2	4	6
3	0	3	6	1	4	7	2	5
4	0	4	0	4	0	4	0	4
5	0	5	2	7	4	1	6	3
6	0	6	4	2	0	6	4	2
7	0	7	6	5	4	3	2	1

```

static int prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

    again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &&
        return 0;
    }

    /* not a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }

    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
        delta = 0;
    }

    loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);
        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    primes using a prime number because it's a multiple of
         *    three.
         * 2) that it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
}

```

Multiplicative inverses

- ▶ In \mathbb{Q} and \mathbb{R} , inverses exist everywhere except zero: $x * \frac{1}{x} = 1$
- ▶ In \mathbb{Z} , inverses only exist at 1
- ▶ In \mathbb{Z}_p , inverses exist everywhere except zero, and can be found via Fermat's little theorem
(e.g. $3 * 4 \equiv 12 \equiv 1 \pmod{11}$)
- ▶ In \mathbb{Z}_n , multiples of factors of n act as additional zeros for the purposes of not having an inverse; when they exist, they can be found via an extension of the algorithm for euclidean division

```
static int prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = ((BN_ULONG)0) + get_word(rnd);
        } else {
            size_limit = (((BN_ULONG)1) << bits) + get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (!BN_mod_word(rnd, (BN_ULONG)maxdelta)) {
        /* In the case that the candidate prime is a single word then
         * we can't do any better than primes[i] because we shouldn't reject
         * 3 as being a prime number because it's a multiple of
         * three.
         * 2) That it's not a multiple of a known prime. We don't
         * check that rnd-1 is also coprime to all the known
         * primes because there aren't many small primes where
         * that's true. */
        for (i = 1; i < NUMPRIMES; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
            }
        }
    }
}
```

Fermat's little theorem

- ▶ $x^{p-1} \equiv 1 \pmod{p}$
- ▶ $x * x^{p-2} \equiv 1 \pmod{p}$
- ▶ $x^{p-2} = \text{invert}(x, p)$

```
static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
            }
        }
    }
}
```

Multiplication mod 13

$$x * x^{p-2} \equiv 1 \pmod{p}$$

*	0	1	2	3	4	5	6	7	8	9	10	11	12
0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	0	1	2	3	4	5	6	7	8	9	10	11	12
2	0	2	4	6	8	10	12	1	3	5	7	9	11
3	0	3	6	9	12	2	5	8	11	1	4	7	10
4	0	4	8	12	3	7	11	2	6	10	1	5	9
5	0	5	10	2	7	12	4	9	1	6	11	3	8
6	0	6	12	5	11	4	10	3	9	2	8	1	7
7	0	7	1	8	2	9	3	10	4	11	5	12	6
8	0	8	3	11	6	1	9	4	12	7	2	10	5
9	0	9	5	1	10	6	2	11	7	3	12	8	4
10	0	10	7	4	1	11	8	5	2	12	9	6	3
11	0	11	9	7	5	3	1	12	10	8	6	4	2
12	0	12	11	10	9	8	7	6	5	4	3	2	1

```

static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
            }
        }
    }
}

```

Exponentiation mod 13

$$x * x^{p-2} \equiv 1 \pmod{p}$$

x^y	0	1	2	3	4	5	6	7	8	9	10	11	12
0	1	0	0	0	0	0	0	0	0	0	0	0	0
1	1	1	1	1	1	1	1	1	1	1	1	1	1
2	1	2	4	8	3	6	12	11	9	5	10	7	1
3	1	3	9	1	3	9	1	3	9	1	3	9	1
4	1	4	3	12	9	10	1	4	3	12	9	10	1
5	1	5	12	8	1	5	12	8	1	5	12	8	1
6	1	6	10	8	9	2	12	7	3	5	4	11	1
7	1	7	10	5	9	11	12	6	3	8	4	2	1
8	1	8	12	5	1	8	12	5	1	8	12	5	1
9	1	9	3	1	9	3	1	9	3	1	9	3	1
10	1	10	9	12	3	4	1	10	9	12	3	4	1
11	1	11	4	5	3	7	12	2	9	8	10	6	1
12	1	12	1	12	1	12	1	12	1	12	1	12	1

```

static int prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
            }
        }
    }
}

```

Euler's totient theorem and phi

- ▶ $\gcd(x, n) = 1 \rightarrow x^{\varphi(n)} \equiv 1 \pmod{n}$
- ▶ $\varphi(n) = |\{k | 1 \leq k < n \wedge \gcd(k, n) = 1\}|$
- ▶ `def phi(n):`
 `return len([k for k in range(1, n) if gcd(k, n) == 1])`
- ▶ This definition is inefficient to calculate (linear in the value of n , so exponential in the bitlength of n)

```
static inline prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    clear_is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
        delta = 0;
    }
    if ((is_single_word) &
        BN_ULONG rnd_word = get_word(rnd);

    /* In the case that the candidate prime is a single word then
     * we check that:
     * 1) It's greater than primes[i] because we shouldn't reject
     * 3 as being a prime number because it's a multiple of
     * three.
     * 2) That it's not a multiple of a known prime. We don't
     * check that rnd-1 is also coprime to all the known
     * primes because there aren't many small primes where
     * that's true. */
    for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
        if ((mods[i] + delta) % primes[i] == 0) {
            delta += 2;
            if (delta > maxdelta) {
                goto again;
            }
            goto loop;
        }
    }
} else {
    for (i = 1; i < NUMPRIMES; i++) {
        /* check that rnd is not a prime and also
         * that gcd(rnd-1, primes) = 1 (except for 2) */
        if (((mods[i] + delta) % primes[i]) == 0) {
            delta += 2;
            if (delta > maxdelta) {
                goto again;
            }
            goto loop;
        }
    }
}
```


Fundamental Theorem of Arithmetic

- ▶ Any integer can be decomposed (uniquely) into a product of prime powers
- ▶ $\forall n \exists \vec{v} (n = \prod_{i=1}^{\text{len}(\vec{v})} p_i^{v_i})$
- ▶ e.g. for $n = 84 = 2 * 42 = 2^2 * 21 = 2^2 * 3 * 7$, $\vec{v} = [2, 1, 0, 1]$
- ▶ Computing \vec{v} from n is expensive (algorithms like GNFS and ECM find \vec{v} slower than polytime in the bitlength of n)
- ▶ Computing n from \vec{v} is fast (p_i can be found via sieving, and multiplication is cheap)
- ▶ When coding, a sparse representation of the prime vector is more convenient:

```

histogram = lambda s: (lambda d: [d.__setitem__(c, d.get(c, 0)+1) for c in s], d)[-1])(dict())
product = lambda xs: reduce(__import__('operator').mul, xs, 1)
assert product([2,2,3,7]) == 84
assert histogram([2,2,3,7]) == {2: 2, 3: 1, 7: 1}
    
```

```

static inline prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    clear_is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &&
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_uint16(rnd, (BN_ULONG)primes[i]);
        if (mod == 0)
            return 0;
        mods[i] = (uint16_t)mod;
    }

    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit = (BN_ULONG)1 << (bits/2);
        /* avoid undefined behavior. */
        size_limit = ((BN_ULONG)0) - get_word(rnd);
        for (;;) {
            BN_ULONG rnd_word = get_word(rnd);
            if (size_limit < maxdelta) {
                maxdelta = size_limit;
            }
        }
    }
    delta = 0;
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) it's greater than primes[i] because we shouldn't reject
         *    primes that are multiples of it.
         * 2) it's not a multiple of a known prime. We don't
         *    know if it's also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
            }
        }
    }
}
    
```

Calculating Euler's phi via FTA

If we know the factors of n , we can compute $\varphi(n)$ efficiently:

1. $\varphi(p^k) = (p - 1) * p^{k-1}$
2. $\gcd(n, m) = 1 \rightarrow \varphi(n * m) = \varphi(n) * \varphi(m)$

- ▶ $\varphi(n) = \varphi(\prod_{i=1}^{\text{len}(v)} p_i^{v_i}) = \prod_{i=1}^{\text{len}(v)} \varphi(p_i^{v_i}) = \prod_{i=1}^{\text{len}(v)} (p_i - 1) * p_i^{v_i-1}$
- ▶ e.g. $\varphi(82) = \varphi(2^2 * 3 * 7) = \varphi(2^2) * \varphi(3) * \varphi(7) = (2 - 1) * 2^1 * (3 - 1) * (7 - 1) = 1 * 2 * 2 * 6 = 24$
- ▶ `histogram = lambda s: (lambda d: [[d.__setitem__(c, d.get(c, 0)+1) for c in s], d][-1])(dict())
 product = lambda xs: reduce(__import__('operator').mul, xs, 1)
 def phi(factors_of_n):
 return product([(p-1)*(p**(k-1)) for (p, k) in histogram(factors_of_n).items()])`

`assert product([2,2,3,7]) == 84 and phi([2,2,3,7]) == 24`

```

static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (d == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = ((BN_ULONG)1) << bits - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);
        /* candidate prime is a single word then
         * we check that:
         * 1) it's greater than primes[i] because we shouldn't reject
         * 3 as being a prime number because it's a multiple of
         * three.
         * 2) it's not a multiple of a known prime. We don't
         * check that rnd-1 is also coprime to all the known
         * primes because there aren't many small primes where
         * that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
            }
        }
    }
}
    
```

Inverses modulo a composite

► from gmpy import gcd, invert

```
def eee(x, y):
```

```
    x, y = min(x, y), max(x, y)
```

```
    r, s, t = x, 1, 0
```

```
    R, S, T = y, 0, 1
```

```
    while r > 0 and R > 0:
```

```
        q = r/R
```

```
        new = r-q*R, s-q*S, t-q*T
```

```
        r, s, t = R, S, T
```

```
        R, S, T = new
```

```
    assert gcd(x, y) == r # gcd from euclidean algorithm
```

```
    assert r == x*s + y*t # s and t are the bezout coefficients
```

```
    inv = s + y*(s < 0) # modular inverse from bezout coefficient
```

```
    if r == 1:
```

```
        assert (x * inv) % y == 1
```

```
    return (r, s, t, inv)
```

```
assert [eee(i, 7)[3] for i in range(1, 7)] == [1, 4, 5, 2, 3, 6]
```

```
assert [invert(i, 7) for i in range(1, 7)] == [1, 4, 5, 2, 3, 6]
```

```
static int probable_prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &&
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;
    if (is_single_word) {
        BN_ULONG mod_word = get_word(rnd);
        /* we check that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
}
```

Correctness of RSA¹

- ▶ $e * d \equiv 1 \pmod{\varphi(n)}$
- ▶ $\text{enc}(x) \equiv x^e \pmod{n}$
- ▶ $\text{dec}(x) \equiv x^d \pmod{n}$
- ▶ $\text{dec}(\text{enc}(x)) \equiv (x^e)^d \equiv x^{e*d} \stackrel{\text{Euler}}{=} x^1 \equiv x \pmod{n}$

```
static prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) <= 1) {
                delta += 2;
            }
        }
    }
}
```

¹Assumes $\gcd(x, n) = 1$, full proof is a little bit more involved

Exploiting RSA: Cube root of small message

```
▶ from codecs import encode
from gmpy import invert, next_prime
import os
d = 0
while d == 0:
    p = next_prime(int(encode(os.urandom(1024/8), 'hex'), 16))
    q = next_prime(int(encode(os.urandom(1024/8), 'hex'), 16))
    n = p * q
    phi = (p - 1) * (q - 1)
    e = 3
    d = invert(e, phi)

message = int(encode('hello', 'hex'), 16)
ciphertext = pow(message, e, n)
assert pow(ciphertext, d, n) == message
assert round(ciphertext**(1.0/3)) == message
```

```
static inline prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if ((BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) &&
        return 0;
    )

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (is_single_word) {
        BN_ULONG size_limit;
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            maxdelta = size_limit;
        }
    }
    delta = 0;

loop:
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES && primes[i] < rnd_word; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) ||
                ((BN_mod_word(rnd, (BN_ULONG)primes[i]) - 1) % 2) == 0) {
                    delta += 2;
                    if (delta > maxdelta) {
                        goto again;
                    }
                }
            }
        }
    }
}
```

Resources

- ▶ [https://en.wikipedia.org/wiki/RSA_\(cryptosystem\)](https://en.wikipedia.org/wiki/RSA_(cryptosystem))
- ▶ https://en.wikipedia.org/wiki/Extended_Euclidean_Algorithm
- ▶ https://en.wikipedia.org/wiki/Modular_arithmetic
- ▶ <https://crypto.stanford.edu/~dabo/papers/RSA-survey.pdf>
- ▶ <https://cryptopals.com/>, Sets 5 and 6

```
static prime(BIGNUM *rnd, int bits) {
    int i;
    uint16_t mods[NUMPRIMES];
    BN_ULONG delta;
    BN_ULONG maxdelta = BN_MASK2 - primes[NUMPRIMES - 1];
    char is_single_word = bits <= BN_BITS2;

again:
    if (!BN_rand(rnd, bits, BN_RAND_TOP_TWO, BN_RAND_BOTTOM_ODD)) {
        return 0;
    }

    /* we now have a random number 'rnd' to test. */
    for (i = 1; i < NUMPRIMES; i++) {
        BN_ULONG mod = BN_mod_word(rnd, (BN_ULONG)primes[i]);
        if (mod == (BN_ULONG)-1) {
            return 0;
        }
        mods[i] = (uint16_t)mod;
    }
    /* If bits is so small that it fits into a single word then we
     * additionally don't want to exceed that many bits. */
    if (bits < BN_BITS2) {
        if (bits == BN_BITS2) {
            /* Avoid undefined behavior. */
            size_limit = (((BN_ULONG)0) - get_word(rnd));
        } else {
            size_limit = (((BN_ULONG)1) << bits) - get_word(rnd) - 1;
        }
        if (size_limit < maxdelta) {
            delta = 2;
        } else {
            delta = 0;
        }
    } else {
        delta = 0;
    }
    if (is_single_word) {
        BN_ULONG rnd_word = get_word(rnd);

        /* In the case that the candidate prime is a single word then
         * we check that:
         * 1) It's greater than primes[i] because we shouldn't reject
         *    3 as being a prime number because it's a multiple of
         *    three.
         * 2) That it's not a multiple of a known prime. We don't
         *    check that rnd-1 is also coprime to all the known
         *    primes because there aren't many small primes where
         *    that's true. */
        for (i = 1; i < NUMPRIMES; i++) {
            if ((mods[i] + delta) % primes[i] == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
                goto loop;
            }
        }
    } else {
        for (i = 1; i < NUMPRIMES; i++) {
            /* check that rnd is not a prime and also
             * that gcd(rnd-1, primes) = 1 (except for 2) */
            if (((mods[i] + delta) % primes[i]) == 0) {
                delta += 2;
                if (delta > maxdelta) {
                    goto again;
                }
            }
        }
    }
}
```