

✓ Introduction to Big Data

- Developed by Dr. Keungoui KIM
- <https://awekim.github.io/portfolio/>

Lecture 7. Relational Database

Join

- merging or integrating two Data Frame

Pandas functions; merge, concat, append

- (row reference) join by column name: merge
- (row reference) join by index name: merge, concat
- (column reference) join by row: concat, append

Methods

- Inner: Intersect
- Left: Join to left DataFrame
- Right: Join to right DataFrame
- Outer: Join all

pd.merge

`pd.merge('left', 'right', 'how', 'on', 'left_on', 'right_on', 'left_index', 'right_index')`

- left : DataFrame positioned on the left
- right : DataFrame positioned on the right

- how : inner, left, right, outer
- on : Name of reference column for Join
- left_on : Name of reference column of left - DataFrame
- right_on : Name of reference column of right DataFrame
- left_index : True if join with left DataFrame index
- right_index : True if join with right DataFrame index

pd.concat

pd.concat([left,right], axis, join,...)

- [left,right] : a list of left DataFrame and right DataFrame
- axis = 0 if join by row reference, 1 if join by column reference

✓ Pandas Exercise

✓ Create DataFrame

```
import pandas as pd

df1 = pd.DataFrame(
    {
        "A": ["A0", "A1", "A2", "A3"],
        "B": ["B0", "B1", "B2", "B3"],
        "C": ["C0", "C1", "C2", "C3"],
        "D": ["D0", "D1", "D2", "D3"]},
    index=[0, 1, 2, 3])

df11 = pd.DataFrame(
    {
        "A": ["A0", "A1", "A21", "A31"],
        "E": ["E0", "E11", "E21", "E31"],
        "F": ["F0", "F11", "F21", "F31"],
        "G": ["G0", "G11", "G21", "G31"]},
    index=[0, 1, 2, 3])

df2 = pd.DataFrame(
    {
        "A": ["A4", "A5", "A6", "A7"],
        "B": ["B4", "B5", "B6", "B7"],
        "C": ["C4", "C5", "C6", "C7"],
        "D": ["D4", "D5", "D6", "D7"]},
    index=[4, 5, 6, 7])

df3 = pd.DataFrame(
    {
        "A": ["A8", "A9", "A10", "A11"],
        "B": ["B8", "B9", "B10", "B11"],
        "C": ["C8", "C9", "C10", "C11"],
        "D": ["D8", "D9", "D10", "D11"]},
    index=[8, 9, 10, 11])
```

df1

```
df11
```

```
df2
```

```
df3
```

▼ .merge

```
pd.merge(df1, df11, how='left', on='A')
```

```
pd.merge(df1,df11,how='left')
```

```
pd.merge(df1,df11,how='left',on='B')
```

```
pd.merge(df1,df11,how='right',on='A')
```

```
pd.merge(df1,df11,how='inner',on='A')
```

```
pd.merge(df1,df11,how='outer',on='A')
```

▼ .concat

- .concat: The `concat()` function (in the main pandas namespace) does all of the heavy lifting of performing concatenation operations along an axis while performing optional set logic (union or intersection) of the indexes (if any) on the other axes.

```
frames = [df1, df2, df3]
frames
```

```
type(frames)
```

```
len(frames)
```

```
pd.concat([df1, df2, df3])
```

```
pd.concat([df1, df2, df3], axis=0)
```

```
pd.concat([df1, df2, df3], axis=1)
```

```
pd.concat([df1, df2, df3], join='inner', axis=1)
```

```
pd.concat([df1, df2], keys=['df1', 'df2'])
```

```
pd.concat([df1, df2],
          keys=['df1', 'df2'],
          names=['dfname', 'index'])
```

```
(pd.concat([df1, df2],
          keys=['df1', 'df2'],
          names=['dfname', 'index']).
  reset_index())
```

- What is the average salary of award winning player in 2016?

```
bb_ap_df['year ID']==2016
```

```
bb_ap_df[bb_ap_df['year ID']==2016].head()
```

```
bb_ap_sal_df = (  
    pd.merge(bb_ap_df[bb_ap_df['year ID']==2016],  
             bb_sal_df,  
             how='inner', on=['player ID', 'year ID', 'lg ID'])  
bb_ap_sal_df
```

```
bb_ap_sal_df['salary'].mean()
```

```
bb_ap_sal_df.value_counts('player ID').head()
```

```
# Option 1  
bb_ap_sal_df_idgr = (  
    bb_ap_sal_df.groupby('player ID')  
)
```

```
(bb_ap_sal_df_idgr['salary'].  
mean()).head())
```

```
bb_ap_sal_df_idgr['salary'].mean().mean()
```

```
# Option 2
(bb_ap_sal_df.
 drop_duplicates(subset='playerID').
 salary.mean())
```

✓ Compare the average salary of award winning players between AL and NL in 2016

```
bb_ap_sal_df.groupby('lgID').playerID.nunique()
```

```
(bb_ap_sal_df.groupby('lgID').
 salary.mean().
 reset_index())
```

```
# Option 1
bb_ap_sal_df_idlggr = (
    bb_ap_sal_df.groupby(['playerID', 'lgID'])
)
```

```
bb_ap_sal_df_idlggr_m = (
    bb_ap_sal_df_idlggr['salary'].mean().reset_index()
)
bb_ap_sal_df_idlggr_m.head()
```



```
(
    bb_ap_sal_df_idlggr_m.groupby('lgID').
    salary.mean().reset_index()
)
```

✓ In 2016, is top salary player the award winning player ?

```
(pd.merge(bb_sal_df[bb_sal_df['yearID']==2016],
          bb_ap_df[bb_ap_df['yearID']==2016], how='left').
sort_values('salary', ascending=False))
```

✓ What is the name of player with the top salary in 2016?

```
bb_pp_sal_df = pd.merge(bb_pp_df, bb_sal_df[bb_sal_df['yearID']==2016],
                        how='left', on='playerID')
bb_pp_sal_df.sort_values('salary', ascending=False)[['nameLast', 'nameFirst']]
```

```
pd.concat([df1, df2, df3], axis=1, keys=['x', 'y', 'z'])
```

```
result = pd.concat([df1, df2, df3], axis=0, keys=['x', 'y', 'z'])
result
```

```
# check first 5 rows
result.head()
```

```
# check first 10 rows  
result.head(10)
```

```
# check last 5 rows  
result.tail()
```

```
# Filter specific column  
result['A']
```

```
# Filter specific key  
result.loc["x"]
```

```
# inner join  
# result is different because concat matches by index  
# It is not often recommended because it returns the duplicated data.  
inner_result = pd.concat([df1, df4], axis=1, join = 'inner') # column reference  
inner_result
```

```
# outer join  
# result is different because concat matches by index  
# It is not often recommended because it returns the duplicated data.  
outer_result = pd.concat([df1, df4], axis=1, join = 'outer') # column reference  
outer_result
```

▼ Vertical join

```
df4 = pd.DataFrame(  
    {"B": ["B2", "B3", "B6", "B7"],  
     "D": ["D2", "D3", "D6", "D7"],  
     "F": ["F2", "F3", "F6", "F7"],  
     },  
    index=[2, 3, 6, 7]  
)  
df4
```

```
# outer join  
outer_result = pd.concat([df1, df4], axis=0, join='outer') # raw reference  
outer_result
```

```
df1.append(df4)
```

```
# outer join  
inner_result = pd.concat([df1, df4], axis=0, join='inner') # raw reference  
inner_result
```

▼ Horizontal join

```
# left join  
left_result = pd.merge(df1, df4, 'left')  
left_result
```

```
# right join
right_result = pd.merge(df1, df4, 'right')
# inner join
inner_result = pd.merge(df1, df4, 'inner')
inner_result
```

```
# outer join
outer_result = pd.merge(df1, df4, 'outer')
outer_result
```