

Platform User Interface Guide

Unified navigation, workspaces, ITIL workflows, accessibility,
self-service, and administration

Version 1.0 · 25 July 2026

Contents

Chapter	Topic
1	Platform overview
2	Sign in and account roles
3	Unified navigation
4	Landing page and dashboard
5	Global search
6	Favorites and history
7	Lists, filters, and queues
8	Record forms and activity
9	Attachments and checklists
10	Visual task board
11	Personalization and accessibility
12	Notifications
13	Employee self-service
14	Request fulfillment
15	Incident and problem work
16	Change and CCB governance
17	Service levels
18	CMDB and service mapping
19	Enterprise workspaces
20	ITIL administration
21	Help and onboarding
22	Security and audit
23	Docker deployment and operations
24	Source-guide mapping and boundaries
25	Kubernetes deployment
26	Production operations
27	Custom visual system

1. Platform overview

ServiceOps is a Docker-deployable enterprise service-management platform that connects IT service management, operations, employee self-service, governance, security work, customer cases, HR cases, portfolio work, and field service through shared records and role-aware workspaces.

Experience principles

- One navigation shell across all workspaces
- Role-aware access and landing pages
- Persistent work context through favorites and history
- Auditable changes and governed approvals
- Responsive and accessible interaction

Primary experiences

- Employee self-service portal
- Agent and manager workspaces
- Change and CCB governance
- ITIL administration
- Operational analytics and visual work board

This guide documents the behavior of the running ServiceOps product. It is an original work and does not reproduce third-party manual text or imagery.

2. Sign in and account roles

Sign in at the deployment URL with an active ServiceOps account. The navigation and available actions change with the assigned role and team membership.

Roles

- Requester: self-service requests, own tickets, knowledge, notifications, and attachments
- Agent: fulfillment queues, operational records, task updates, knowledge authoring, and analytics
- Manager: agent capabilities plus team management and approval authority
- Administrator: users, configuration, audit, CMDB, assets, and platform-wide governance

Manager accounts

- CoreApps, Database, Network, Windows, Unix, and SSD each have a dedicated manager
- Every team manager is synchronized into the Change Control Board

3. Unified navigation

The unified shell combines persistent application navigation with a global top bar so users can move between workspaces without losing context.

Top bar

- Global search
- Favorites
- History
- Unread notifications
- Favorite-this-page action
- Help Center
- Display and accessibility preferences

Application navigation

- Dashboard
- Visual task board
- ITSM queues
- Catalog and knowledge
- Enterprise workspaces
- Operations
- Analytics
- Administration

Responsive behavior

- Collapse the sidebar to free horizontal space
- Mobile layouts convert navigation to a compact shell

4. Landing page and dashboard

The dashboard provides a role-aware start-of-day view with volume indicators and recently updated work. Users can choose Dashboard, Visual Task Board, or All Workspaces as their start page.

Operational indicators

- Incident, request, and change totals
- Open-work total
- Recently updated records

Role behavior

- Requesters see their own work
- Fulfillers and managers see operational queues
- Administrators receive platform-wide visibility

5. Global search

Use the search field in the unified navigation to search across major ServiceOps record families from one place.

Indexed experiences

- Incident, request, and change numbers and content
- Knowledge articles
- Enterprise records
- Configuration items

Result design

- Record-type badge
- Primary label
- State or category context
- Direct navigation

6. Favorites and history

Favorites and recent history are stored per user in PostgreSQL and follow the user across browsers and sessions.

Favorites

- Select the star on any page
- Open saved pages from the top-bar menu
- Select the star again to remove the favorite

History

- Authenticated page visits are recorded automatically
- The most recent pages appear first
- Static assets and internal service endpoints are excluded

7. Lists, filters, and queues

Queue pages provide consistent table structures for scanning and opening records. ITSM and enterprise queues support query and state filtering.

List conventions

- Record number links
- State badges
- Priority indicators
- Requester and assignee context
- Responsive horizontal scrolling
- Purposeful empty states

Queue access

- Requesters are restricted to their records
- Agents and managers access fulfillment work
- Administrators receive complete access

8. Record forms and activity

Record pages combine operational facts, lifecycle controls, activity, governed decisions, service-level targets, checklists, and files.

Activity

- Chronological comments
- Author and timestamp
- New comment composer

Record controls

- State, priority, risk, assignment, and team ownership
- Role-enforced updates
- Audit events for meaningful changes

9. Attachments and checklists

Ticket attachments are saved in a dedicated Docker volume while metadata and access rules remain in PostgreSQL. Checklists provide small, auditable execution steps.

Attachments

- 20 MB request limit
- Secure generated storage names
- Original-name downloads
- Requester ownership validation
- Persistent serviceops_uploads volume

Checklists

- Ordered ticket steps
- Complete/incomplete toggling
- Manager and fulfiller editing

10. Visual task board

The task board renders live ticket states as lifecycle lanes. Authorized users drag cards between lanes; the source ticket, audit history, and SLA stage update together.

Lanes

- New
- In Progress
- Pending
- Resolved
- Closed

Cards

- Priority
- record number
- summary
- assignee

Governance

- Drag actions require agent, manager, or administrator role
- Requesters receive a read-only board

11. Personalization and accessibility

Display preferences are stored per user and applied by the server on every authenticated page.

Preferences

- System, light, or dark theme
- Comfortable or compact density
- 80–140% font scaling
- High contrast
- Reduced motion
- Pinned navigation
- Preferred start page

Accessibility foundation

- Semantic labels
- Keyboard-accessible native controls
- Responsive reflow
- Reduced-motion override
- High-contrast design tokens

12. Notifications

The notification inbox brings approval requests and workflow outcomes into the unified shell. An unread counter indicates pending messages.

Lifecycle

- Notifications are user-specific
- Opening the inbox marks messages read
- Approval-chain activation creates approver notifications
- Approval outcomes notify requesters

13. Employee self-service

The self-service experience combines catalog ordering, knowledge search, request tracking, comments, and file exchange.

Catalog

- Category, description, delivery estimate, and approval requirement
- Request-detail variables
- Direct transition into REQ/RITM/SCTASK fulfillment

Knowledge

- Full-text title and body search
- Category context
- Role-restricted publishing

14. Request fulfillment

ServiceOps follows the REQ → RITM → SCTASK hierarchy. Requested items carry variables, due dates, approvals, and SLAs; catalog tasks carry assignment and work notes.

State roll-up

- SCTASK completion updates RITM
- All completed RITMs close the REQ
- Incomplete work propagates incomplete state

Approval path

- Manager approval
- Fulfillment authorization
- Task creation after final approval

15. Incident and problem work

Incident queues support classification, priority, assignment, activity, SLA tracking, and resolution. Problem workspaces capture root-cause and known-error work for recurring disruption.

Incident lifecycle

- New
- In Progress
- Pending
- Resolved
- Closed

Operational context

- Priority-based SLAs
- Assignee and requester
- Checklist and evidence
- Audit history

16. Change and CCB governance

Change records capture the implementation evidence required for controlled delivery and route decisions through the owning team and Change Control Board.

Change detail

- Normal, Standard, or Emergency type
- Owning IT team
- Impact and numeric risk
- Affected CI
- Planned dates
- Implementation, test, and backout plans

Approval chain

- Owning-team manager assessment
- Weekly CCB authorization for Normal and Emergency changes
- Six CCB manager votes
- Four-of-six majority
- Immediate rejection behavior

Conflict detection

- Overlapping schedules
- Same affected configuration item
- Recorded conflict outcome

17. Service levels

SLA definitions attach task-SLA instances by record type and priority. ServiceOps retains start, pause, resume, completion, breach target, and accumulated pause duration.

Default commitments

- P1 response
- P1/P2/P3 resolution
- Catalog fulfillment

Clock behavior

- Pending and On Hold pause clocks
- Resume shifts breach target
- Resolution and closure complete the timer

18. CMDB and service mapping

The CMDB workspace stores configuration items, operational state, ownership, environment, addresses, and typed dependencies.

Configuration context

- Business applications
- Application services
- Databases and infrastructure classes
- Operational, degraded, down, maintenance, and retired states

Relationships

- Parent/child dependencies
- Service-impact context for change and operations

19. Enterprise workspaces

Shared enterprise records provide consistent lifecycle, risk, priority, assignment, due-date, and approval behavior across additional domains.

Domains

- Customer service
- HR service delivery
- Security operations
- Risk and compliance
- Strategic portfolio
- Field service
- IT operations events
- Releases

20. ITIL administration

Administrators manage the service-management foundation from one workspace.

Configuration views

- IT fulfillment teams
- Team managers
- CCB membership and chair
- Support and approval groups
- Service offerings
- SLA definitions

Current IT organization

- CoreApps
- Database
- Network
- Windows
- Unix
- SSD

21. Help and onboarding

The Help Center provides task-oriented guidance and a short interactive tour of unified navigation.

Guidance topics

- Search and navigation
- Governed change submission
- Visual board usage
- Accessibility and personalization

22. Security and audit

Authentication, active-account checks, role decorators, ownership restrictions, protected downloads, and server-side validation enforce access.

Audit coverage

- Login
- record creation and update
- approvals and rejection
- board movement
- attachment upload
- change conflict checks
- preference updates

Deployment controls

- Password hashing
- non-root application process
- private database network
- health checks
- external HTTPS proxy recommendation

23. Docker deployment and operations

The production stack uses a hardened Gunicorn application service with either bundled PostgreSQL 16 or a separately managed PostgreSQL server. The first-install menu generates secrets, validates the host, starts the selected architecture, and waits for readiness.

Installation modes

- Bundled database for a simple single-server deployment
- External database for managed PostgreSQL and separated infrastructure ownership

Operations CLI

- Health and diagnostics
- Logs and restart
- Bundled database and upload backups
- Guarded restore
- Health-gated updates

Resources

- serviceops-app image
- serviceops-app-1 and optional serviceops-db-1 containers
- serviceops_postgres_data in bundled mode
- serviceops_uploads

Verification

- Preflight and Compose validation
- GET /health
- database query
- upload-volume write test
- application logs
- automated pytest suite

24. Source-guide mapping and boundaries

The Australia UI guide was reviewed as a feature reference. ServiceOps implements independent equivalents where they map to this product and classifies vendor-specific runtimes honestly.

Implemented equivalents

- Unified navigation
- workspaces
- lists and forms
- portal
- favorites and history
- notifications
- themes
- accessibility
- attachments
- task boards
- help and onboarding

Vendor-specific or external

- UI Builder and proprietary widget runtime
- Jelly and vendor scripting APIs
- native mobile publishing
- telephony and chat routing
- voice guidance
- predictive and generative AI services

25. Kubernetes deployment

ServiceOps includes a production-oriented Helm chart. Enterprise Production uses replicated application pods, an external highly available PostgreSQL service, shared upload storage, TLS ingress, and cluster observability.

Workload safeguards

- Restricted Pod Security
- non-root process
- read-only root filesystem
- startup, readiness, and liveness probes
- rolling update
- PodDisruptionBudget
- topology spread
- resource controls
- NetworkPolicy
- optional HPA

Installation

- Immutable registry image
- production values file
- Kubernetes preflight
- atomic Helm upgrade
- rollout wait
- packaged Helm health test

26. Production operations

The complete operations manual covers deployment decisions, identity, backups, recovery, upgrades, rollback, monitoring, incident response, and production acceptance.

Recovery

- PostgreSQL point-in-time recovery
- matching upload recovery set
- off-cluster encrypted retention
- quarterly restore evidence

Release assurance

- staging regression
- manifest lint and render
- load and soak testing
- database failover
- node drain
- atomic rollout
- tested data rollback

27. Custom visual system

The interface retains the unified enterprise patterns documented in the source UI guide while applying the company palette consistently.

Palette

- Deep teal #003E4C for navigation, identity, links, and focus context
- Warm amber #F9AA3C for selected emphasis, workflow cues, and warnings

Interaction

- persistent application navigator
- unified search bar
- dense operational tables
- workspaces and panels
- visible keyboard focus
- responsive and accessible themes

Appendix A. Capability summary

Capability family	ServiceOps status
Unified navigation, landing pages, lists, forms	Implemented
Favorites, history, notifications, global search	Implemented
Themes, density, accessibility, responsive UI	Implemented
Service portal, knowledge, catalog, requests	Implemented
Visual task board, attachments, checklists	Implemented
Guided help and onboarding	Implemented
Vendor UI Builder, Jelly, proprietary widget APIs	Not applicable; independent Flask/Jinja stack
Telephony, chat routing, native mobile, hosted AI	External integration required

For the maintained implementation matrix, see docs/UI_CAPABILITY_MAPPING.md in the ServiceOps repository.