

DATA SCIENCE WITH R

Class 4 – Data Manipulation in R

Topic 5

★ Missing Value Treatment ★

INDEX

Manipulating data using base R

Using dplyr to manipulate data

Working with date objects

Merging tables



Missing value treatment

Using reshape2() to transpose data

Manipulating Character Strings

Using sqldf

Missing Values

Missing Values

- Identifying missing values in a column
- Imputing missing values

Missing Values

- Using `is.na()` to find out the total number of missing values

```
> a<-c(1,2,3,4,5,6,NA,NA,NA,7,8,9)
> is.na(a)
[1] FALSE FALSE FALSE FALSE FALSE TRUE  TRUE  TRUE FALSE FALSE FALSE
> sum(is.na(a))
[1] 3
```

Missing Values

- Using is.na() to find out the total number of missing values

```
> air<-airquality
> head(air)
```

	Ozone	Solar.R	wind	Temp	Month	Day
1	41	190	7.4	67	5	1
2	36	118	8.0	72	5	2
3	12	149	12.6	74	5	3
4	18	313	11.5	62	5	4
5	NA	NA	14.3	56	5	5
6	28	NA	14.9	66	5	6

Missing Values

- Using `is.na()` to find out the total number of missing values

```
> sum(is.na(air$Ozone))
```

```
[1] 37
```

```
> sum(is.na(air$Solar.R))
```

```
[1] 7
```

```
> summary(air)
```

Ozone	Solar.R	wind	Temp	Month	Day
Min. : 1.00	Min. : 7.0	Min. : 1.700	Min. :56.00	Min. :5.000	Min. : 1.0
1st Qu.: 18.00	1st Qu.:115.8	1st Qu.: 7.400	1st Qu.:72.00	1st Qu.:6.000	1st Qu.: 8.0
Median : 31.50	Median :205.0	Median : 9.700	Median :79.00	Median :7.000	Median :16.0
Mean : 42.13	Mean :185.9	Mean : 9.958	Mean :77.88	Mean :6.993	Mean :15.8
3rd Qu.: 63.25	3rd Qu.:258.8	3rd Qu.:11.500	3rd Qu.:85.00	3rd Qu.:8.000	3rd Qu.:23.0
Max. :168.00	Max. :334.0	Max. :20.700	Max. :97.00	Max. :9.000	Max. :31.0
NA's :37	NA's :7				

Missing Values

- Imputing missing values

```
> #Imputing Missing values  
> air$Ozone[is.na(air$Ozone)]<-45  
> summary(air)
```

Ozone	Solar.R	wind	Temp	Month	Day
Min. : 1.00	Min. : 7.0	Min. : 1.700	Min. :56.00	Min. :5.000	Min. : 1.0
1st Qu.: 21.00	1st Qu.:115.8	1st Qu.: 7.400	1st Qu.:72.00	1st Qu.:6.000	1st Qu.: 8.0
Median : 45.00	Median :205.0	Median : 9.700	Median :79.00	Median :7.000	Median :16.0
Mean : 42.82	Mean :185.9	Mean : 9.958	Mean :77.88	Mean :6.993	Mean :15.8
3rd Qu.: 46.00	3rd Qu.:258.8	3rd Qu.:11.500	3rd Qu.:85.00	3rd Qu.:8.000	3rd Qu.:23.0
Max. :168.00	Max. :334.0	Max. :20.700	Max. :97.00	Max. :9.000	Max. :31.0
	NA's :7				

Missing Values

- Imputing missing values

```
> #Imputing Missing values  
> air$Solar.R[is.na(air$Solar.R)]<-mean(air$Solar.R,na.rm=TRUE)  
> summary(air)
```

Ozone	Solar.R	wind	Temp	Month	Day
Min. : 1.00	Min. : 7.0	Min. : 1.700	Min. :56.00	Min. :5.000	Min. : 1.0
1st Qu.: 21.00	1st Qu.:120.0	1st Qu.: 7.400	1st Qu.:72.00	1st Qu.:6.000	1st Qu.: 8.0
Median : 45.00	Median :194.0	Median : 9.700	Median :79.00	Median :7.000	Median :16.0
Mean : 42.82	Mean :185.9	Mean : 9.958	Mean :77.88	Mean :6.993	Mean :15.8
3rd Qu.: 46.00	3rd Qu.:256.0	3rd Qu.:11.500	3rd Qu.:85.00	3rd Qu.:8.000	3rd Qu.:23.0
Max. :168.00	Max. :334.0	Max. :20.700	Max. :97.00	Max. :9.000	Max. :31.0

RECAP

- Identifying missing values in a column
- Imputing missing values