# Information Retrieval Assignment 1 Vector-Space Model

Andrew McIsaac

December 7, 2021

#### Index Construction

- Czech tags: [Geography, Title, Heading, Text]
- English tags: [PH, KH, HD, DH, SE, DL, LD, TE, CP, DC, CR, DP, SM]
- ► Inverted Index
  - (docID, term) pairs for every document and every term
  - Invert with SPIMI-Index
  - Sorted terms and postings list for documents of every file
  - Merge to final inverted index and write to disk

#### Baseline Results

► Czech: 0.0597 MAP, 0.084 *P*<sub>10</sub>

► English: 0.0445 MAP, 0.084 P<sub>10</sub>

## Preprocessing

- Lemmas spacy, spacy\_udpipe
- Stemming Porter Stemmer
- Stopwords from spacy

Table 1: Mean average precision (MAP) and  $P_{10}$  precision of the first 10 documents training performance with different preprocessing techniques. wf: word forms, sw: stopwords, I: lemmatization, s: stemming

Language		wf	SW	sw+l	sw+s
English	$oxed{MAP} P_{10}$	0.0445	0.1244	0.0834 0.136	<b>0.1751</b> 0.252
Czech	$MAP$ $P_{10}$	0.0597 0.084	0.0770 0.100	<b>0.1553</b> 0.148	0.0672 0.060

## Term/Document Frequency Weighting

Table 2: Mean average precision (MAP) and  $P_{10}$  precision of the first 10 documents training performance with different tf-idf weightings. SMART notation tags are applied to both query and document in all cases.

Language		nnc	ntc	npc	ltc	арс
English	MAP	0.1751	0.2244	0.2248	0.1320	0.0469
	$P_{10}$	0.252	0.328	0.328	0.172	0.092
Czech	MAP	0.1553	0.1933	0.1947	0.0879	0.0922
	$P_{10}$	0.148	0.224	0.228	0.096	0.100

## Pivoted Document Length Normalization




Figure 1: Document lengths for retrieval using cosine normalization compared to relevance.

## Pivoted Document Length Normalization

Table 3: MAP training performance of pivoted document length normalization with different values of scaling factor *a* 

	0.6	0.7	0.8	0.85	0.9	cosine
English	0.2428	0.2442	0.2446	0.2453	0.2450	0.2248
Czech	0.1830	0.1869	0.1932	0.1938	0.2053	0.1947

## Pivoted Document Length Normalization




Figure 2: Document lengths for retrieval using pivoted document length normalization compared to relevance.

▶ Not enough RAM so index construction would crash

- ▶ Not enough RAM so index construction would crash
  - ► Close Firefox, Spotify

- ▶ Not enough RAM so index construction would crash
  - Close Firefox, Spotify
- ▶ Queries took a very long time (>20 minutes)

- ▶ Not enough RAM so index construction would crash
  - Close Firefox, Spotify
- Queries took a very long time (>20 minutes)
  - Use pd.DataFrame to index by doc name instead
  - Now much quicker

- Not enough RAM so index construction would crash
  - Close Firefox, Spotify
- Queries took a very long time (>20 minutes)
  - Use pd.DataFrame to index by doc name instead
  - Now much quicker
- nltk has no Czech stemmer

- Not enough RAM so index construction would crash
  - Close Firefox, Spotify
- Queries took a very long time (>20 minutes)
  - Use pd.DataFrame to index by doc name instead
  - Now much quicker
- nltk has no Czech stemmer
  - ► Find it online
  - But maybe it wasn't very good...

- Not enough RAM so index construction would crash
  - Close Firefox, Spotify
- Queries took a very long time (>20 minutes)
  - Use pd.DataFrame to index by doc name instead
  - Now much quicker
- nltk has no Czech stemmer
  - ► Find it online
  - But maybe it wasn't very good...
- spacy has no Czech lemmatizer

- Not enough RAM so index construction would crash
  - Close Firefox, Spotify
- Queries took a very long time (>20 minutes)
  - Use pd.DataFrame to index by doc name instead
  - Now much quicker
- nltk has no Czech stemmer
  - Find it online
  - But maybe it wasn't very good...
- spacy has no Czech lemmatizer
  - Use spacy\_udpipe
  - But it was much slower...