

# Package ‘psymetlab’

April 7, 2016

**Title** Provides useful functions for APA formatting and writing output to Excel

**Version** 1.0.1

## Description

Package includes a variety of functions to tag significant correlations, write data to excel, etc.

**Depends** R (>= 3.1.3)

**License** General Public License >= 3.0

**LazyData** true

**RoxygenNote** 5.0.1

**Imports** psych, xlsx

## R topics documented:

f.corstar . . . . .	1
f.get.reg.output . . . . .	2
f.screen.outliers . . . . .	3
f.write.corrs . . . . .	3
<b>Index</b>	<b>5</b>

---

f.corstar	<i>Add asterisk(s) to significant correlations</i>
-----------	--

---

## Description

Uses an output object from the Psych package and adds 1 or 2 askterisks (stars) to the correlation for APA table output. Returns object as dataframe.

## Usage

```
f.corstar(corr.obj, is.triangle = TRUE, p.val.1 = 0.05, p.val.2 = 0.01)
```

**Arguments**

corr.obj	is the output list object from the corr.test function in the Psych package
is.triangle	is whether the correlation is a symetric matrix (default) or a rectangular matrix in which one set of variables is correlated with a different set.
p.val.1	is the p-value desired to trigger a single astrisk (default = .05)
p.val.2	is the p-value desired to trigger a second astrisk added to the first default = .01. p.val.2 should be a smaller p val than p.val.1. set p.val.2 = FALSE if no second astrisk is desired

**Author(s)**

Adam Meade <awmeade@ncsu.edu>

**Examples**

```
## Not run:
require('psych')
corrs.1 = corr.test(sat.act)
f.corstar(corrs.1)
f.corstar(corrs.1, p.val.1 = .01, p.val.2 = FALSE)
corrs.2 = corr.test(sat.act[3:5],sat.act[6])
f.corstar(corrs.2,is.triangle = FALSE)

## End(Not run)
```

---

f.get.reg.output

---

*Take output from lm function and put relevant info into a dataframe*


---

**Description**

Returns a dataframe with predictors and coefficients listed along with model statistics F,df,p, and r-squared values.

**Usage**

```
f.get.reg.output(out.lm)
```

**Arguments**

out.lm	results of a linear regression from lm()
--------	--

**Author(s)**

Adam Meade <awmeade@ncsu.edu>

**Examples**

```
## Not run:
model.out <- lm(sat.act[,1]~sat.act[,2]+sat.act[,3])
f.get.reg.output(model.out)

## End(Not run)
```

---

f.screen.outliers	<i>Deletes multivariate outliers using Mahalanobis distance</i>
-------------------	---

---

### Description

Accepts a dataframe and optional list of variables within that dataframe for which to screen the data. The function computes mahalanobis distace and associated chi-square on the screening data and then returns a dataframe that is a subset of the original all.data dataframe based on non-significant chi-square values.

### Usage

```
f.screen.outliers(all.data, screening.vars = NULL, p.val = 0.05)
```

### Arguments

screening.vars is an optional array of variable names on which the screening should be based.  
 p.val is the cutoff value of the chi-square distribution to use. default is .05.  
 add.data is the database from which to remove outliers

### Author(s)

Adam Meade <awmeade@ncsu.edu>

### Examples

```
## Not run:
nrow(trees)
new.data <- f.screen.outliers(trees)
nrow(new.data)

## End(Not run)
```

---

f.write.corrs	<i>Formats in APA format and writes correlation matrices to an excel sheet</i>
---------------	--

---

### Description

Uses an output object from the Psych package and adds 1 or 2 askterisks (stars) to the correlation for APA table output. Returns object as dataframe. Writes correlational data for r, n, and pvalues to three consecutively named Excel sheets.

### Usage

```
f.write.corrs(f.name = "output.xlsx", s.name, obj.corrs, print.p = TRUE,
  print.n = TRUE, ...)
```

**Arguments**

<code>f.name</code>	is the file name to which to write the data. default = 'output.xlsx'
<code>s.name</code>	is the name of the Excel sheet(s) to which to write the data
<code>obj.corrs</code>	is the correlation object from the <code>corr.test</code> function in the Psych package
<code>print.p</code>	requests printing of p values. default = TRUE
<code>print.n</code>	requests printing of sample size (n). default = TRUE
<code>...</code>	parameters passed to the <code>f.corstar</code> function

**Author(s)**

Adam Meade <awmeade@ncsu.edu>

**Examples**

```
## Not run:
corrs = corr.test(sat.act)
f.write.corrs(s.name='example',obj.corrs=corrs)
f.write.corrs(f.name='example.xlsx',s.name='example',obj.corrs=corrs,p.val.2=FALSE)

## End(Not run)
```

# Index

f.corstar, [1](#)  
f.get.reg.output, [2](#)  
f.screen.outliers, [3](#)  
f.write.corrs, [3](#)