

iOS → Amazon Connect Demo Runbook

iOS VSACompanion → Amazon Connect (CCP) Demo Runbook

Audience: Whoever is showing the demo — you do not need to be a CMS engineer. **Time to present:** ~5 min prep, ~5 min demo. **What the audience sees:** a driver on iPhone speaks into an assistant → an agent's browser rings → the agent picks up and lands on the exact vehicle in trouble.

What is this demo showing?

Two apps working together:

1. **VSACompanion** — a companion iPhone app for a driver. Has a voice assistant; the driver can say things like "check engine light is on" or "I want to talk to someone".
2. **CMS UI** — a web app for a fleet-support agent. It has a small phone widget (Amazon Connect CCP) in the corner that rings when a driver asks to escalate.

When the driver says "**speak with agent**", the assistant escalates the call to Amazon Connect. The agent's CCP widget rings, they pick up, and the CMS UI **auto-opens the exact vehicle** the driver is calling about, with a side panel showing the triage summary (severity, DTC, VIN, driver name).

You do **not** need to type anything into either app during the demo — the iPhone plays pre-recorded voice clips via the on-screen "Demo Phrases" drawer.

Prerequisites (do these once, 20 min before showtime)

You need three things running at the same time:

-  iPhone Simulator on your Mac (with VSACompanion installed)
-  CMS UI open in a browser (signed in as a Connect Agent)
-  Amazon Connect CCP signed in (inside the CMS UI's floating widget)

Two audiences on the iPhone side:

- **Developer** — someone who builds the demo app once from source. Needs **full Xcode.app** installed (the iOS Simulator SDK is not included in `xcode-select --install` CLT-only installs) and follows the "First-time setup" callout under Step 2 below. Produces a redistributable `.app.zip` under `clients/ios/build/`.
- **Presenter** — everyone else who just runs the demo. Only needs the iPhone Simulator runtime (bundled with Xcode.app, or downloadable standalone) and the `.app.zip` from a developer. Executes Steps 1-4 below. Never opens Xcode.

Step 1 — Boot the iPhone Simulator

Terminal (any Mac with Xcode installed):

```
xcrun simctl list devices booted | grep -qE 'iPhone.*Booted' \
|| xcrun simctl boot "iPhone 15 Pro" \
|| xcrun simctl boot "iPhone 15"
open -a Simulator
```

Wait until the iPhone home screen is visible.

Step 2 — Install and launch VSACompanion on the simulator

From the CMS repo root, run:

```
clients/ios/scripts/install_ios_sim_demo_app.sh
```

The script:

- reuses your already-booted simulator (from Step 1) or boots `iPhone 15 Pro` if none is booted,
- finds the newest prebuilt `.app.zip` under `clients/ios/build/`,
- installs it via `xcrun simctl install`,
- launches it via `xcrun simctl launch`, and
- brings the Simulator window to the front.

On success you'll see a line like `com.aws.vsa.companion: 12345` (the process ID) and the VSACompanion app opens on the simulator. No Xcode window, no Run button, no signing team, no Apple ID prompt.

First-time setup (developer, once per source change): the `.app` zip has to exist under `clients/ios/build/` before the install script can find it. If you see `No VSACompanion-ios-sim-*.app.zip found`, run the build script once — but on a **fresh clone**, first populate `clients/ios/VSACompanion/Config/Staging.local.xcconfig` per `clients/ios/README.md` \$ `Configuration`. Without it, the `.app.zip` is built against the tracked-file placeholders (`<REPLACE_WITH_...> / YOUR_...`) and the installed app fails at Cognito sign-in with `ResourceNotFoundException`.

```
clients/ios/scripts/build_ios_simulator_app.sh
```

Sanity check after build (before you install) — confirm the xcconfig substitution actually landed in the built `.app`'s Info.plist. Runs in a second; catches "I filled in `Staging.local.xcconfig` but the build didn't pick it up" before you sink time into debugging a Cognito 400 from the installed app:

```
APP=clients/ios/build/DerivedData/Build/Products/Debug-iphonesimulator/VSACompanion.app
/usr/libexec/PlistBuddy -c "Print :VSAUserPoolId" "$APP/Info.plist"
# Expected: your real pool ID (e.g. us-west-2_XXXXXXXXXX)
# If you see <REPLACE_WITH_USER_POOL_ID>, your Staging.local.xcconfig
# was not picked up – check that the file exists and is next to
# Staging.xcconfig.
```

This produces `clients/ios/build/VSACompanion-ios-sim-<version>-<date>-<sha>.app.zip` in ~30-90 seconds (no signing needed — Simulator builds are unsigned). Re-run only when Swift source or `Staging.xcconfig` changes; the zip is reusable across as many demos as you want.

If the install script complains that no simulator is bootable, revisit Step 1 — the simulator must be running before Step 2.

Step 3 — Open the CMS UI in a browser

Go to <https://connected-mobility.aws.aws.dev>.

Sign in with the connect-agent demo user:

Field	Value
Email	Agent@example.com
Password	Demo-1234

If that account is not yet in the `connect-agent` Cognito group, the Agent Workspace nav item and the floating CCP widget will not appear. See [Troubleshooting](#) → "CCP pill doesn't show up".

You should see:

- Left-nav items: **Fleet, Vehicles, Vehicle Map, Agent Workspace**
- Bottom-right corner: **two floating pills** — a blue chat pill (VFO assistant) and, staggered to its left, an **orange phone pill** (CCP).

Step 4 — Sign the CCP widget into Amazon Connect

Click the **orange phone pill** in the bottom-right. A panel expands and loads the Amazon Connect login page inside it.

Sign in to the Connect instance:

Field	Value
URL	<code>https://cms-vsa-demo-use1.my.connect.aws/</code>
Username	<code>demo-agent</code> (or the agent user you were given)
Password	(ask the demo owner; not committed to this repo)

Once signed in, set your **status to Available** in the CCP header (top-right of the panel — dropdown that starts at "Offline"). The pill in the corner turns **green**.

Minimize the CCP pill by clicking its minimize button — it collapses back to a green pill and stays ready for incoming contacts. **Do not sign out** and do not refresh the tab; a refresh drops the Streams session.

You are now ready to demo. Keep this browser window visible during the demo — the CCP will ring in-page.

The demo (numbered — this is what to click, in order)

You are running the fleet-driver persona (Samantha Carter, Michelin). Two screens are visible to the audience: the **iPhone simulator** (the driver's phone) and the **browser** (the agent's console).

Step 1 — Open the Assistant on the phone

On the iPhone simulator, tap the **Assistant** tab (mic icon in the tab bar). Wait 2-4 seconds until the status pill under the header reads **"Ready"**.

Step 2 — Open the Demo Phrases drawer

Tap the **chevron** at the top of the "Demo Phrases" card to expand it. You should see a horizontal scroll of pre-recorded phrases: "Check engine", "Tire pressure low", "Find service center", "Speak with agent", etc.

Point out to the audience: *"These are pre-recorded so I don't have to talk to my laptop. The app streams them through the same pipeline as the real microphone — the assistant thinks I'm speaking."*

Step 3 — Play a triage phrase

Tap **"Check engine"**. The assistant will:

1. Show the transcript: *"my check engine light just came on."*
2. Respond in voice + text with a triage question — e.g. asking whether the engine feels rough or the temp gauge is climbing.

You can play one or two follow-up phrases (e.g. **"Engine rough"**, then **"DTC explain P0420"**) to show the triage flow branching. The assistant reads back vehicle context (VIN, model, active DTCs) from the CMS backend.

Step 4 — Escalate to a human agent

Tap **"Speak with agent"**. The assistant confirms the escalation verbally ("I'll connect you with an agent now") and creates an Amazon Connect chat contact.

Step 5 — Watch the browser ring

In the browser, **within 3-5 seconds**:

- The orange CCP pill in the corner turns **red** and pulses
- The CCP panel **auto-expands** and shows an incoming chat contact
- A ringtone plays

Step 6 — Accept the contact

In the CCP panel, click **"Accept"** on the incoming chat card.

The moment you accept:

- The URL changes to `/vehicle-management/{vehicleId}` — the specific vehicle the driver was calling about
- The **Escalation Context Panel** slides in from the side, showing:
 - Driver name (Samantha Carter)
 - Severity (e.g. MEDIUM / HIGH)
 - Active DTC code + description
 - One-line triage summary
- The chat pane in the CCP shows the conversation transcript with the driver's phrasing

Point out to the audience: *"The agent did zero navigation — they clicked Accept and the console teleported them to the exact vehicle, with the driver's story already summarized. This is the shift from 'agent hunts for context' to 'context arrives with the call'."*

Step 7 — Have a short exchange, then end

Type a reply in the CCP chat pane (something like *"Hi Samantha, I see your check-engine light — I'm looking at the DTC now"*). The driver sees it appear as a text bubble in the iPhone's assistant view.

When done, click **End Chat** in the CCP header. The pill returns to green (available). The iPhone assistant remains open for the next demo.

Troubleshooting

Symptom	Likely cause	Fix
CCP pill doesn't show up in the CMS UI corner	Your Cognito user is not in the <code>connect-agent</code> group	Sign in as platform-admin first (<code>Admin@example.com / Demo-1234</code>), go to Admin → User Management , find your agent user, click Edit → check Connect Agent group → Save. Sign out, sign back in as the agent.
CCP panel shows a login screen, not a phone	You are not signed in to the Amazon Connect instance yet	Click the pill to expand; sign in with the <code>demo-agent</code> Connect user (this is a separate credential from the CMS UI login). Session cookies persist ~12h — you usually only sign in once per browser.
CCP fails with "Attempted to call initCCP when an iframe already exists"	You navigated away and back to a page that mounts the CCP twice; a known Amazon Connect Streams SDK quirk. v0.2.7 fix (df40507) hardens this — check re-init before calling <code>initCCP</code> .	Hard-refresh the tab (⌘⇧R). If the fix is deployed, this should not recur.
Assistant on iPhone says "Not ready"	Voice WebSocket not authenticated / staging cognito misconfig	Sign out of VSACompanion (Assistant → gear icon → Sign Out), sign back in with the driver persona (<code>Samantha.Carter@example.com / Demo-1234</code>). If it still fails, tail the app's unified log while you retry (see "Viewing app logs" below) and look for a Cognito 4xx or an empty <code>jwt acquired len=0</code> .
"Speak with agent" plays but no ring on browser	Chat routing profile / queue not attached to the agent, or the agent status is Offline / ACW	In CCP header, confirm status = Available . If it stays silent, the demo Connect instance may be missing the chat routing profile — page the demo owner.
Simulator won't boot / is black	Simulator daemon stuck	<code>killall -9 Simulator; xcrun simctl shutdown all; xcrun simctl erase all; xcrun simctl boot "iPhone 15 Pro"; open -a Simulator</code> . The <code>simctl erase all</code> step wipes ALL simulator data — safe for demo simulators, do NOT run if you have work-in-progress in another simulator.

Viewing app logs (when debugging a demo hiccup)

The simulator emits all app logs to macOS's unified log. Tail them live with `xcrun simctl — no Xcode UI needed`:

```
# Follow the app's log stream in another terminal while you reproduce
# the issue in the simulator.
xcrun simctl spawn booted log stream \
  --predicate 'process == "VSACompanion"' \
  --style compact
```

The app tags network + voice events with prefixes like `🎤 VOICE:`, `🎤 BIDI:`, `🎤 CRED:`. Filter to a specific subsystem by adjusting the predicate — e.g. add `AND eventMessage CONTAINS "🎤"` to see only voice-session events. `Ctrl-C` to stop.

For a static capture (for a bug report), redirect to a file:

```
xcrun simctl spawn booted log stream \
  --predicate 'process == "VSACompanion"' \
  --style compact > /tmp/vsa-companion-$(date +%s).log
```

Reset between demos

Between back-to-back demos, do these on the iPhone simulator to avoid transcript / audio state carrying over:

1. iPhone Assistant tab → gear icon → **New session**
2. On the browser, **End Chat** in CCP if a previous contact is still open, and make sure status returns to **Available**.

You do **not** need to sign out of either app between demos.

Cross-references

- Full deployment/config runbook: `docs/DEPLOYMENT.md`
- iOS build / simulator log capture: `~/ .kiro/skills/ios-debug/SKILL.md`
- CCPPanel component contract:
`modules/cms_ui/source/frontend/src/components/connect/CCPPanel.tsx`
- Demo-clip catalog: `clients/ios/VSACompanion/Voice/DemoClip.swift`
- Escalation side-panel:
`modules/cms_ui/source/frontend/src/components/connect/EscalationContextPanel.tsx`