Configure SSL encryption on an SAP ASE source endpoint in AWS DMS

by Ashish Mathur, Amardeep Kumar, and Kapoor Raghavendra Rao | on 07 JUN 2024 | in AWS Database Migration Service, Intermediate (200), RDS for SQL Server, Technical How-to | Permalink | Comments | Share

AWS Database Migration Service (AWS DMS) helps you migrate your databases to AWS in a secure and efficient way. AWS DMS supports a wide range of source and target database engines, including SAP Adaptive Server Enterprise (ASE) (formerly known as Sybase ASE). To learn more about AWS DMS supported source and target database engines, refer to Sources for data migration and Targets for data migration.

In this post we walk you through how to configure Secure Socket Layer (SSL) encryption between the source endpoint in AWS DMS and an on-premises SAP ASE source for secure data transfer. We also show you the steps for enabling SSL on an SAP ASE source endpoint using the SAP ASE command line utility and for secure endpoint creation and testing steps to ensure during the database migration process the connectivity to the SAP ASE source endpoint is secure.

Solution overview

To secure data in transit when migrating from an on-premises SAP ASE database to the AWS Cloud using AWS DMS, you can use various SSL modes (see Endpoints) and mutual TLS for the source database and the AWS DMS. For the use case, you configure SSL encryption for the source endpoint, and test connectivity over SSL. You use AWS Secrets Manager to store database credentials.

The following diagram illustrates the solution architecture.

The architecture consists of the following main components.

- A source on-premises SAP ASE database.
- AWS DMS components (source endpoint, replication instance, target endpoint) in a VPC.
- A target Amazon RDS for SQL Server instance in a VPC.

The solution contains the following steps.

1. Generate the certificate using the OpenSSL utility.
2. Configure the source SAP ASE database endpoint with the SSL certificate.
3. Configure the source SAP ASE database endpoint with SSL on the AWS DMS console.
4. Test and troubleshoot the source endpoint connection.

Prerequisites

To get started, you need the following prerequisites:

- An active AWS account.
- SAP ASE installed and OpenSSL installed (We are using 15.7 version and with SAP ASE installed and OpenSSL installed on the same Amazon EC2 instance).
- An SAP ASE test database (`pubs` database).
- An AWS DMS replication instance.

Generate SSL Certificates with OpenSSL on an SAP ASE instance

To create your own self-signed certificate, you need to connect to an instance where OpenSSL is installed. In this post, you use SAP ASE hosted on an EC2 instance and OpenSSL installed. Complete the following steps:

1. Generate a private key using the following command:

```
openssl genrsa -out <server-key>.pem 2048
```

The following screenshot shows `SAP_ASE_SERVER.pem` is generated.

2. Generate the self-signed certificate using the following command:

```
openssl req -x509 -config <ssl.cnf> -new -nodes -key <server-key.pem> -days 9999 -out <server.crt>
```

The following screenshot shows the `SAP_ASE_SERVER.crt` certificate file is generated. Enter the input parameters of your choice while running the command.

3. The functional fields (CN of the subject certificate must match the exact case of the server's name in the interfaces file. In this example, the CN is `SAP_ASE_SERVER`. Review the SAP ASE documentation for more details on the attributes used in the `SAP_ASE_SERVER.crt`.
4. To convert the certificate and key to a .der file, run the following command and provide a password when prompted:

```
openssl pkcs12 -export -in <server.crt> -inkey <server-key.pem> -out <new-cert>
```

You use the same password later to export the certificate file.

The following screenshot shows the `SAP_ASE_SERVER.pfx` file is generated.

5. To convert the .pfx file back to a .pem file, which contains the certificate and key, run the following command and enter the password you used earlier when prompted:

```
openssl pkcs12 -in <new-cert.pfx> -out <new-cert.pem> -nodes
```

The following screenshot shows that the new certificate file `SAP_ASE_SERVER.pfx` is generated.

Configure the CA certificate on the SAP ASE database

At this point, the SAP ASE source database server name is `SAP_ASE_SERVER`, so we name the next certificate `SAP_ASE_SERVER_CA`. Complete the following steps to configure the CA certificate:

1. Copy the next certificate to the SAP ASE installation directory:

```
cp <SAP_ASE_SERVER_CA> /opt/sap/SAP_ASE_ASE15_0/certificates/SAP_ASE_SERVER_CA
cp <SAP_ASE_SERVER_CA> /opt/sap/SAP_ASE_ASE15_0/certificates/SAP_ASE_SERVER_CA.crt
```

The following screenshot shows the next certificate copied to the SAP ASE certificates installation path (`/opt/sap/SAP_ASE_ASE15_0/certificates`).

2. Log in to the SAP ASE database server with system administrator (`sa`) access login to enable SSL as the database server and add the certificate to the SAP ASE database, using the following SQL command. Run `sa_config` as the other database client tool to access the database. Use the certificate file import password (`Test1234567#`):

```
sp_configure 'enable ssl', 1
go
sp_configure 'ssl cert', 'cert=/opt/SAP_ASE_ASE15_0/certificates/SAP_ASE_SERVER_CA.crt', 'cert=<cert-password
go
```

The following screenshot shows the SQL commands were run using `isql` to modify the database configuration and add the certificate file.

3. When the configuration changes are complete, shut down the database server for the configuration changes to take effect.
4. After SAP ASE database, the restart loads the numerous a lot of processes and creates the `log.ldo` file. Check the `log.ldo` file, but it only contains certificate file for that are trusted by client applications, servers, network resources, and so on.
5. Copy the content of the next certificate file the `SYBASE.OCS` file:

```
cat /opt/sap/SAP_ASE_ASE15_0/certificates/SAP_ASE_SERVER_CA.crt >>
/opt/sap/SAP_ASE_ASE15_0/OCS-15_0/SYBASE.OCS
```

6. Modify the SAP ASE `SYBASE.OCS` file (`/opt/sap/SAP_ASE_ASE15_0`) to add the SSL security mechanism as a filter on the `ASLOCAL` and `ASCS` lines:

```
ASLOCAL
    master tli_sdmr 5000/ssl:ase01 u="TM-COMMAND-name"
    query tli_sdmr 5000/ssl:ase01 u="TM-COMMAND-name"

ASCS
```

7. Start the database server after you complete the preceding steps.

Configure the source SAP ASE database endpoint with SSL

To set up your source endpoint, you need to import the certificate (`SAP_ASE_SERVER_CA.pem`) that created into AWS DMS. Then you can configure SSL using complete the following steps:

1. On the AWS DMS console, choose **Certificates** in the navigation pane.
2. Choose **Import certificate**.

3. For **Certificate identifier**, enter a name (for example, `SAPASECERT`).
4. For **Import certificate file**, choose **Choose file** to browse your files.
5. Locate `SAP_ASE_SERVER_CA.pem` on your local machine.
6. Choose **Import certificate** to add a new cert to certificate.

When the certificate is imported successfully, you can see it listed as shown in the following screenshot.

The next step is to configure the source endpoint with SSL mode enabled as `VERIFY-CA`.

1. On the AWS DMS console, choose **Endpoints** in the navigation pane.
2. Choose **Create endpoint**.

3. For **Endpoint type** select **Source endpoint**.

4. Enter a name for your endpoint (for example, `sap-ase-source`) and an optional Amazon Resource Name (ARN).
5. For **Source engine**, choose **SAP Sybase ASE**.

6. For **Access to endpoint database**, select your preferred method of authentication to the SAP ASE source. Secure Storage or manual authentication. For this post, we select **AWS Secrets Manager**.
7. For **Secret manager access role ARN**, enter the ARN of the role that you created for accessing the secret. Also, for **Secret name**, enter the name of the secret where secret for your environment is stored in secrets.

```
{
    "username": "db_username",
    "password": "db_password",
    "port": "db_port",
    "host": "db_server_name"
}
```

Here, `db_username` is the name of the user accessing the database, `db_user_password` is the password of the database user, `db_port` is the port number on which the SAP ASE database server, `db_server_name` is the database server name (reference as the web or an IP address).

8. For **AWS ASE**, enter your AWS ASE Key Encryption Key (KEK) ID or use an existing one that grants AWS DMS permission to access the server.

9. For **Secure Socket Layer (SSL) mode**, choose **verify-ca**.
This mode makes sure the connection to source is encrypted. It also verifies the server certificate and verifies that the server name matches the hostname address for the certificate.
SAP ASE as a source database engine only supports `verify-ca` SSL mode to enable SSL. For more information about SSL support for SAP ASE endpoints, see Using SSL with AWS Database Migration Service.
10. For the **certificate**, choose the certificate you imported (`SAPSECERT`).
11. For **Database name**, enter a database name (for example, `pubs2`).

12. Choose **Create endpoint** to finalize the setup of the source endpoint.
When a successful configuration, the endpoint is listed on the AWS DMS console.

Test the source endpoint connection

Now you can test the connection to the source database using the endpoint you created.

1. On the AWS DMS console, choose **Endpoints** in the navigation pane.
2. Select the endpoint to test (`sap-ase-source`).
3. On the **Actions** menu, choose **Test connection**.

4. For **Replication instance**, choose the replication instance to test (`sap-testdemo-repl-ase-ase1`).
5. Choose **Run test** and wait for the status to **successful**.

These steps validate the data migration from the on-premises SAP ASE database to the AWS Cloud using AWS DMS and confirm the connectivity is secure.

To create a target endpoint for the SQL Server database engine, refer to Creating source and target endpoints.

After you have created both the source and target endpoints, refer to Working with AWS DMS tasks to create AWS DMS tasks and migrate the data.

Clean up

When you're done running this solution, delete the resources you created to avoid unexpected charges.

1. On the Amazon EC2 console, select the instance that hosts the SAP ASE database.
2. On the **Instance state** menu, choose **Terminate instance**.
3. On the AWS RDS console, in the navigation pane, choose **Replication instances**.
4. Select the instance to delete and on the **Actions** menu, choose **Delete**.

Conclusion

In this post, we demonstrated how you can set up SSL encryption for AWS DMS with an SAP ASE database as source. Configuring SSL for your database protects your database data while it is being transferred from an on-premises to the AWS Cloud, helping you fulfill compliance with your organization's security policies and procedures.

Consider implementing SSL configurations in your own AWS environment and ask questions or feedback about this approach in the comments.

About the Authors

Ashish Mathur is a Cloud Architect (Database) with AWS Professional Services India. He helps diverse set of customers to migrate and modernize their databases on AWS Cloud platform. With expertise in database technologies such as SQL Server, SAP ASE, and PostgreSQL, he builds cutting-edge solutions that help customers succeed.

Amardeep Kumar is a Lead Database Migration Consultant at AWS with over 20 years of working experience in enterprise database (MS-SQL, SAP ASE, and Oracle). Services. He focuses on helping customers integrate and modernize their workloads to AWS.

Kapoora Raghavendra is a Database Consultant with AWS Professional Services based out of Pune, India. With good knowledge on relational database setting itself up as a homogeneous and heterogeneous database migrations, helps customers migrating to AWS cloud and their optimizations.

Views: 1,647,128

Like | Share

Comments

Log in to comment
Log in

Resources

Analytics Services
Amazon Aurora DSQL
Amazon Aurora Serverless
Amazon DocumentDB
Amazon DocumentDB Elastic Clusters
Amazon Neptune
Amazon Neptune Analytics
Amazon RDS Blue/Green
Amazon Timestream
AWS Database Migration Service

© 2026, Amazon Web Services, Inc. or its affiliates. All rights reserved.