How to create your first custom Helm Chart

Agenda:

1. Why Helm ?
2. What is Helm ?
3. Helm basic commands
4. How Helm communicates with your Kubernetes Cluster
5. How to find chart's details
6. Create a custom helm chart

How Kubernetes deployment works ?

In Kubernetes, if you have to deploy any application then at a minimum you need to create a these below components

- **secrets** for database and admin console authentication
- A **ConfigMap** for externalized database configuration
- **services** for networking
- A **PersistentVolumeClaim** for database storage
- A **StatefulSet** for deploying the database in a stateful fashion
- A **Deployment** for deploying the frontend

To create all these components you need to create a yaml file and provide all the configuration inside that. Maintaining this can be a tedious work and to solve this we use the concept of Helm.

What is Helm ?

Helm is an open source tool used for packaging and deploying applications on Kubernetes.

It is often referred to as the **Kubernetes Package Manager**

Helm Hub is a place where you can find all the known public chart repositories and it provide a search functionality.

How to search for a particular chart in Helm Hub

Below command will provide you information about all the charts which are available to use

```
helm search hub wordpress
```



So if you need to use a bitnami charts then you can use that url from the output above and that will provide you all the information about the charts as shown below:



Add repository

Now you can add this repository on your local workstation using below command

```
helm repo add bitnami https://charts.bitnami.com/bitnami
```

Once its added, you can search all the repository which are available in this `bitnami` chart

```
helm search repo bitnami
```

```
nidhi@Nidhis-MacBook-Air cache % helm search repo bitnami
ERRO[0000] failure getting variant                       error="getCPUInfo for OS darwin: not implemented"
NAME                                    CHART VERSION   APP VERSION     DESCRIPTION
bitnami/bitnami-common                  0.0.9           0.0.9           DEPRECATED Chart with custom templates used in ...
bitnami/airflow                         8.0.2           2.0.0           Apache Airflow is a platform to programmaticall...
bitnami/apache                          8.2.3           2.4.46          Chart for Apache HTTP Server
bitnami/aspnet-core                     1.2.3           3.1.9           ASP.NET Core is an open-source framework create...
bitnami/cassandra                       7.3.2           3.11.10         Apache Cassandra is a free and open-source dist...
bitnami/common                          1.3.8           1.3.8           A Library Helm Chart for grouping common logic ...
bitnami/consul                          9.2.3           1.9.3           Highly available and distributed service discov...
bitnami/contour                         4.1.2           1.12.0          Contour Ingress controller for Kubernetes
bitnami/discourse                       2.2.1           2.6.1           A Helm chart for deploying Discourse to Kubernetes
bitnami/dokuwiki                        11.1.0          20200729.0.0    DokuWiki is a standards-compliant, simple to us...
bitnami/drupal                          10.2.1          9.1.4           One of the most versatile open source content m...
bitnami/ejbca                           2.2.0           6.15.2-6        Enterprise class PKI Certificate Authority buil...
bitnami/elasticsearch                   14.2.1          7.10.2          A highly scalable open-source full-text search ...
bitnami/etcd                            5.6.0           3.4.14          etcd is a distributed key value store that prov...
bitnami/external-dns                    4.6.0           0.7.6           ExternalDNS is a Kubernetes addon that configur...
bitnami/fluentd                         3.5.1           1.12.0          Fluentd is an open source data collector for un...
bitnami/ghost                           12.1.2          3.41.3          A simple, powerful publishing platform that all...
bitnami/grafana                         5.2.1           7.4.0           Grafana is an open source, feature rich metrics...
bitnami/grafana-operator                0.3.0           3.8.1           Kubernetes Operator based on the Operator SDK f...
bitnami/harbor                          9.4.5           2.1.3           Harbor is an an open source trusted cloud nativ...
bitnami/influxdb                        2.0.2           2.0.3           InfluxDB(TM) is an open source time-series data...
bitnami/jasperreports                   10.2.1          7.8.0           The JasperReports server can be used as a stand...
bitnami/jenkins                         7.3.3           2.263.3         The leading open source automation server
bitnami/joomla                          10.1.0          3.9.24          PHP content management system (CMS) for publish...
bitnami/kafka                           12.7.4          2.7.0           Apache Kafka is a distributed streaming platform.
bitnami/keycloak                        2.0.0           12.0.2          Keycloak is a high performance Java-based ident...
bitnami/kiam                            0.3.0           3.6.0           kiam is a proxy that captures AWS Metadata API ...
```

Helm provides the **repo** subcommand to allow users to manage configured chart repositories.

Here are the five **repo** subcommands:

- **add**: To add a chart repository
- **list**: To list chart repositories
- **remove**: To remove a chart repository
- **update**: To update information on available charts locally from chart repositories
- **index**: To generate an index file given a directory containing packaged charts

List repository

This will show all the repository which is added on your local workstation

```
helm repo list
```

```
NAME    URL
bitnami https://charts.bitnami.com/bitnami
gitlab  https://charts.gitlab.io
```

Update a chart

Over time, updates to charts will be published and released to these repositories.

Repository metadata is cached locally. As a result, Helm is not automatically aware when a chart is updated. You can run the below command

This command will update all the local repository which are present in your local workstation

```
helm repo update
```



Remove a repository

This command will remove the repository from your local workstation

```
helm repo remove bitnami
```

How Helm communicates with your Kubernetes Cluster

Helm needs to be able to authenticate with a Kubernetes cluster in order to deploy and manage applications.

It authenticates by referencing a **kubeconfig** file, which specifies different Kubernetes clusters and how to authenticate against them.

A **kubeconfig** file can be created by leveraging three different **kubectl** commands:

1. **kubectl config set-cluster**

The **set-cluster** command will define a **cluster** entry in the **kubeconfig** file. It determines the Kubernetes cluster's hostname or IP address, along with its certificate authority.

2. kubectl config set-credentials

3. kubectl config set-context

How to find chart's details

If you need to find any information of charts you can run the below command which will shows the chart's metadata (or chart definition)/values/readme

```
helm show chart bitnami/wordpress
helm show readme bitnami/wordpress
helm show values bitnami/wordpress
```

```
annotations:
  category: CMS
apiVersion: v2
appVersion: 5.6.1
dependencies:
- condition: mariadb.enabled
  name: mariadb
  repository: https://charts.bitnami.com/bitnami
  version: 9.x.x
- name: common
  repository: https://charts.bitnami.com/bitnami
  tags:
  - bitnami-common
  version: 1.x.x
description: Web publishing platform for building blogs and websites.
home: https://github.com/bitnami/charts/tree/master/bitnami/wordpress
icon: https://bitnami.com/assets/stacks/wordpress/img/wordpress-stack-220x234.png
keywords:
- application
- blog
- cms
- http
- php
- web
- wordpress
maintainers:
- email: containers@bitnami.com
  name: Bitnami
name: wordpress
sources:
- https://github.com/bitnami/bitnami-docker-wordpress
- http://www.wordpress.com/
version: 10.6.3
```

Let’s create a custom chart and then deploy it on GKE

```
helm create demo-helm
```

Inside the directory, you will see the following four files and folders:

- **charts/**
- **Chart.yaml**
- **templates/**
- **values.yaml**


FOLDERS
demo-helm
charts
templates
tests
_helpers.tpl
deployment.yaml
hpa.yaml
ingress.yaml
NOTES.txt
service.yaml
serviceaccount.yaml
.helmignore
Chart.yaml
values.yaml

Chart.yaml

- contain the metadata of a Helm chart

```
apiVersion: v2
name: demo-helm
description: A Helm chart for Kubernetes

# A chart can be either an 'application' or a 'library' chart.
#
# Application charts are a collection of templates that can be packaged into version
# to be deployed.
#
# Library charts provide useful utilities or functions for the chart developer. They
# a dependency of application charts to inject those utilities and functions into th
# pipeline. Library charts do not define any templates and therefore cannot be deplo
type: application

# This is the chart version. This version number should be incremented each time you
# to the chart and its templates, including the app version.
# Versions are expected to follow Semantic Versioning (https://semver.org/)
version: 0.1.0

# This is the version number of the application being deployed. This version number
# incremented each time you make changes to the application. Versions are not expect
# follow Semantic Versioning. They should reflect the version the application is usi
appVersion: 1.16.0
```

Application charts are used to deploy a specific application.

Library charts contain a set of helper functions (also called ‘named templates’) that can be used across other charts to reduce boilerplate.

values.yaml: Used to define default chart values

templates/: Used to define chart templates and Kubernetes resources to be created

Let’s run this helm chart

```
helm install demo --dry-run --debug ./demo-helm
helm install demo ./demo-helm --set service.type=NodePort
```

```
nidhi@Nidhis-MacBook-Air gitcode % helm install demo ./mychart --set service.type=NodePort
ERRO[0000] failure getting variant                       error="getCPUInfo for OS darwin: not implemented"
NAME: demo
LAST DEPLOYED: Fri Feb 12 14:20:17 2021
NAMESPACE: default
STATUS: deployed
REVISION: 1
NOTES:
1. Get the application URL by running these commands:
  export NODE_PORT=$(kubectl get --namespace default -o jsonpath="{.spec.ports[0].nodePort}" services demo-mychart)
  export NODE_IP=$(kubectl get nodes --namespace default -o jsonpath="{.items[0].status.addresses[0].address}")
  echo http://$NODE_IP:$NODE_PORT
nidhi@Nidhis-MacBook-Air gitcode %
```

```
nidhi@Nidhis-MacBook-Air gitcode % kubectl get svc
NAME           TYPE        CLUSTER-IP     EXTERNAL-IP   PORT(S)        AGE
demo-mychart   NodePort    10.35.254.45   <none>        80:32301/TCP   56s
kubernetes     ClusterIP   10.35.240.1    <none>        443/TCP        3h42m
sampleweb      NodePort    10.35.252.2    <none>        82:31259/TCP   3h14m
nidhi@Nidhis-MacBook-Air gitcode %
```

I can access it using node external IP and node port



This is the basic template that helm provides for nginx service.