

AWS Certified Solutions Architect Associate SAA-C03 Exam

Question #1

A company collects data for temperature, humidity, and atmospheric pressure in cities across multiple continents. The average volume of data that the company collects from each site daily is 500 GB. Each site has a high-speed Internet connection.

The company wants to aggregate the data from all these global sites as quickly as possible in a single Amazon S3 bucket. The solution must minimize operational complexity.

Which solution meets these requirements?

- A. Turn on S3 Transfer Acceleration on the destination S3 bucket. Use multipart uploads to directly upload site data to the destination S3 bucket. **Most Voted**
- B. Upload the data from each site to an S3 bucket in the closest Region. Use S3 Cross-Region Replication to copy objects to the destination S3 bucket. Then remove the data from the origin S3 bucket.
- C. Schedule AWS Snowball Edge Storage Optimized device jobs daily to transfer data from each site to the closest Region. Use S3 Cross-Region Replication to copy objects to the destination S3 bucket.
- D. Upload the data from each site to an Amazon EC2 instance in the closest Region. Store the data in an Amazon Elastic Block Store (Amazon EBS) volume. At regular intervals, take an EBS snapshot and copy it to the Region that contains the destination S3 bucket. Restore the EBS volume in that Region.

Correct Answer: A

Question #2

A company needs the ability to analyze the log files of its proprietary application. The logs are stored in JSON format in an Amazon S3 bucket. Queries will be simple and will run on-demand. A solutions architect needs to perform the analysis with minimal changes to the existing architecture.

What should the solutions architect do to meet these requirements with the LEAST amount of operational overhead?

- A. Use Amazon Redshift to load all the content into one place and run the SQL queries as needed.
- B. Use Amazon CloudWatch Logs to store the logs. Run SQL queries as needed from the Amazon CloudWatch console.
- C. Use Amazon Athena directly with Amazon S3 to run the queries as needed. **Most Voted**
- D. Use AWS Glue to catalog the logs. Use a transient Apache Spark cluster on Amazon EMR to run the SQL queries as needed.

Correct Answer: C

Question #3

A company uses AWS Organizations to manage multiple AWS accounts for different departments. The management account has an Amazon S3 bucket that contains project reports. The company wants to limit access to this S3 bucket to only users of accounts within the organization in AWS Organizations. Which solution meets these requirements with the LEAST amount of operational overhead?

- A. Add the aws:PrincipalOrgID global condition key with a reference to the organization ID to the S3 bucket policy. **Most Voted**
- B. Create an organizational unit (OU) for each department. Add the aws:PrincipalOrgPaths global condition key to the S3 bucket policy.
- C. Use AWS CloudTrail to monitor the CreateAccount, InviteAccountToOrganization, LeaveOrganization, and RemoveAccountFromOrganization events. Update the S3 bucket policy accordingly.
- D. Tag each user that needs access to the S3 bucket. Add the aws:PrincipalTag global condition key to the S3 bucket policy.

Correct Answer: A

Question #4

An application runs on an Amazon EC2 instance in a VPC. The application processes logs that are stored in an Amazon S3 bucket. The EC2 instance needs to access the S3 bucket without connectivity to the internet. Which solution will provide private network connectivity to Amazon S3?

- A. Create a gateway VPC endpoint to the S3 bucket. **Most Voted**
- B. Stream the logs to Amazon CloudWatch Logs. Export the logs to the S3 bucket.
- C. Create an instance profile on Amazon EC2 to allow S3 access.
- D. Create an Amazon API Gateway API with a private link to access the S3 endpoint.

Correct Answer: A

Question #5

A company is hosting a web application on AWS using a single Amazon EC2 instance that stores user-uploaded documents in an Amazon EBS volume. For better scalability and availability, the company duplicated the architecture and created a second EC2 instance and EBS volume in another Availability Zone, placing both behind an Application Load Balancer. After completing this change, users reported that, each time they refreshed the website, they could see one subset of their documents or the other, but never all of the documents at the same time.

What should a solutions architect propose to ensure users see all of their documents at once?

- A. Copy the data so both EBS volumes contain all the documents
- B. Configure the Application Load Balancer to direct a user to the server with the documents
- C. Copy the data from both EBS volumes to Amazon EFS. Modify the application to save new documents to Amazon EFS **Most Voted**
- D. Configure the Application Load Balancer to send the request to both servers. Return each document from the correct server

Correct Answer: C

Question #6

A company uses NFS to store large video files in on-premises network attached storage. Each video file ranges in size from 1 MB to 500 GB. The total storage is 70 TB and is no longer growing. The company decides to migrate the video files to Amazon S3. The company must migrate the video files as soon as possible while using the least possible network bandwidth.

Which solution will meet these requirements?

- A. Create an S3 bucket. Create an IAM role that has permissions to write to the S3 bucket. Use the AWS CLI to copy all files locally to the S3 bucket.
- B. Create an AWS Snowball Edge job. Receive a Snowball Edge device on premises. Use the Snowball Edge client to transfer data to the device. Return the device so that AWS can import the data into Amazon S3. **Most Voted**
- C. Deploy an S3 File Gateway on premises. Create a public service endpoint to connect to the S3 File Gateway. Create an S3 bucket. Create a new NFS file share on the S3 File Gateway. Point the new file share to the S3 bucket. Transfer the data from the existing NFS file share to the S3 File Gateway.
- D. Set up an AWS Direct Connect connection between the on-premises network and AWS. Deploy an S3 File Gateway on premises. Create a public virtual interface (VIF) to connect to the S3 File Gateway. Create an S3 bucket. Create a new NFS file share on the S3 File Gateway. Point the new file share to the S3 bucket. Transfer the data from the existing NFS file share to the S3 File Gateway.

Correct Answer: B

Question #7

A company has an application that ingests incoming messages. Dozens of other applications and microservices then quickly consume these messages. The number of messages varies drastically and sometimes increases suddenly to 100,000 each second. The company wants to decouple the solution and increase scalability.

Which solution meets these requirements?

- A. Persist the messages to Amazon Kinesis Data Analytics. Configure the consumer applications to read and process the messages.
- B. Deploy the ingestion application on Amazon EC2 instances in an Auto Scaling group to scale the number of EC2 instances based on CPU metrics.
- C. Write the messages to Amazon Kinesis Data Streams with a single shard. Use an AWS Lambda function to preprocess messages and store them in Amazon DynamoDB. Configure the consumer applications to read from DynamoDB to process the messages.
- D. Publish the messages to an Amazon Simple Notification Service (Amazon SNS) topic with multiple Amazon Simple Queue Service (Amazon SQS) subscriptions. Configure the consumer applications to process the messages from the queues. **Most Voted**

Correct Answer: D

Question #8

A company is migrating a distributed application to AWS. The application serves variable workloads. The legacy platform consists of a primary server that coordinates jobs across multiple compute nodes. The company wants to modernize the application with a solution that maximizes resiliency and scalability. How should a solutions architect design the architecture to meet these requirements?

- A. Configure an Amazon Simple Queue Service (Amazon SQS) queue as a destination for the jobs. Implement the compute nodes with Amazon EC2 instances that are managed in an Auto Scaling group. Configure EC2 Auto Scaling to use scheduled scaling.
- B. Configure an Amazon Simple Queue Service (Amazon SQS) queue as a destination for the jobs. Implement the compute nodes with Amazon EC2 instances that are managed in an Auto Scaling group. Configure EC2 Auto Scaling based on the size of the queue. **Most Voted**
- C. Implement the primary server and the compute nodes with Amazon EC2 instances that are managed in an Auto Scaling group. Configure AWS CloudTrail as a destination for the jobs. Configure EC2 Auto Scaling based on the load on the primary server.
- D. Implement the primary server and the compute nodes with Amazon EC2 instances that are managed in an Auto Scaling group. Configure Amazon EventBridge (Amazon CloudWatch Events) as a destination for the jobs. Configure EC2 Auto Scaling based on the load on the compute nodes.

Correct Answer: B

Question #9

A company is running an SMB file server in its data center. The file server stores large files that are accessed frequently for the first few days after the files are created. After 7 days the files are rarely accessed. The total data size is increasing and is close to the company's total storage capacity. A solutions architect must increase the company's available storage space without losing low-latency access to the most recently accessed files. The solutions architect must also provide file lifecycle management to avoid future storage issues. Which solution will meet these requirements?

- A. Use AWS DataSync to copy data that is older than 7 days from the SMB file server to AWS.

- B. Create an Amazon S3 File Gateway to extend the company's storage space. Create an S3 Lifecycle policy to transition the data to S3 Glacier Deep Archive after 7 days. **Most Voted**
- C. Create an Amazon FSx for Windows File Server file system to extend the company's storage space.
- D. Install a utility on each user's computer to access Amazon S3. Create an S3 Lifecycle policy to transition the data to S3 Glacier Flexible Retrieval after 7 days.

Correct Answer: B

Question #10

A company is building an ecommerce web application on AWS. The application sends information about new orders to an Amazon API Gateway REST API to process. The company wants to ensure that orders are processed in the order that they are received.

Which solution will meet these requirements?

- A. Use an API Gateway integration to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic when the application receives an order. Subscribe an AWS Lambda function to the topic to perform processing.
- B. Use an API Gateway integration to send a message to an Amazon Simple Queue Service (Amazon SQS) FIFO queue when the application receives an order. Configure the SQS FIFO queue to invoke an AWS Lambda function for processing. **Most Voted**
- C. Use an API Gateway authorizer to block any requests while the application processes an order.
- D. Use an API Gateway integration to send a message to an Amazon Simple Queue Service (Amazon SQS) standard queue when the application receives an order. Configure the SQS standard queue to invoke an AWS Lambda function for processing.

Correct Answer: B

Question #11

A company has an application that runs on Amazon EC2 instances and uses an Amazon Aurora database. The EC2 instances connect to the database by using user names and passwords that are stored locally in a file. The

company wants to minimize the operational overhead of credential management. What should a solutions architect do to accomplish this goal?

- A. Use AWS Secrets Manager. Turn on automatic rotation. **Most Voted**
- B. Use AWS Systems Manager Parameter Store. Turn on automatic rotation.
- C. Create an Amazon S3 bucket to store objects that are encrypted with an AWS Key Management Service (AWS KMS) encryption key. Migrate the credential file to the S3 bucket. Point the application to the S3 bucket.
- D. Create an encrypted Amazon Elastic Block Store (Amazon EBS) volume for each EC2 instance. Attach the new EBS volume to each EC2 instance. Migrate the credential file to the new EBS volume. Point the application to the new EBS volume.

Correct Answer: A

Question #12

A global company hosts its web application on Amazon EC2 instances behind an Application Load Balancer (ALB). The web application has static data and dynamic data. The company stores its static data in an Amazon S3 bucket. The company wants to improve performance and reduce latency for the static data and dynamic data. The company is using its own domain name registered with Amazon Route 53.

What should a solutions architect do to meet these requirements?

- A. Create an Amazon CloudFront distribution that has the S3 bucket and the ALB as origins. Configure Route 53 to route traffic to the CloudFront distribution. **Most Voted**
- B. Create an Amazon CloudFront distribution that has the ALB as an origin. Create an AWS Global Accelerator standard accelerator that has the S3 bucket as an endpoint. Configure Route 53 to route traffic to the CloudFront distribution.
- C. Create an Amazon CloudFront distribution that has the S3 bucket as an origin. Create an AWS Global Accelerator standard accelerator that has the ALB and the CloudFront distribution as endpoints. Create a custom domain name that points to the accelerator DNS name. Use the custom domain name as an endpoint for the web application.
- D. Create an Amazon CloudFront distribution that has the ALB as an origin. Create an AWS Global Accelerator standard accelerator that has the S3 bucket as an endpoint. Create two domain names. Point one domain name

to the CloudFront DNS name for dynamic content. Point the other domain name to the accelerator DNS name for static content. Use the domain names as endpoints for the web application.

Correct Answer: A

Question #13

A company performs monthly maintenance on its AWS infrastructure. During these maintenance activities, the company needs to rotate the credentials for its Amazon RDS for MySQL databases across multiple AWS Regions.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the credentials as secrets in AWS Secrets Manager. Use multi-Region secret replication for the required Regions. Configure Secrets Manager to rotate the secrets on a schedule. **Most Voted**
- B. Store the credentials as secrets in AWS Systems Manager by creating a secure string parameter. Use multi-Region secret replication for the required Regions. Configure Systems Manager to rotate the secrets on a schedule.
- C. Store the credentials in an Amazon S3 bucket that has server-side encryption (SSE) enabled. Use Amazon EventBridge (Amazon CloudWatch Events) to invoke an AWS Lambda function to rotate the credentials.
- D. Encrypt the credentials as secrets by using AWS Key Management Service (AWS KMS) multi-Region customer managed keys. Store the secrets in an Amazon DynamoDB global table. Use an AWS Lambda function to retrieve the secrets from DynamoDB. Use the RDS API to rotate the secrets.

Correct Answer: A

Question #14

A company runs an ecommerce application on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Amazon EC2 Auto Scaling group across multiple Availability Zones. The Auto Scaling group scales based on CPU utilization metrics. The ecommerce application stores the transaction data in a MySQL 8.0 database that is hosted on a large EC2 instance.

The database's performance degrades quickly as application load increases. The application handles more read requests than write transactions. The company wants a solution that will automatically scale the database to

meet the demand of unpredictable read workloads while maintaining high availability.
Which solution will meet these requirements?

- A. Use Amazon Redshift with a single node for leader and compute functionality.
- B. Use Amazon RDS with a Single-AZ deployment. Configure Amazon RDS to add reader instances in a different Availability Zone.
- C. Use Amazon Aurora with a Multi-AZ deployment. Configure Aurora Auto Scaling with Aurora Replicas. **Most Voted**
- D. Use Amazon ElastiCache for Memcached with EC2 Spot Instances.

Correct Answer: C

Question #15

A company recently migrated to AWS and wants to implement a solution to protect the traffic that flows in and out of the production VPC. The company had an inspection server in its on-premises data center. The inspection server performed specific operations such as traffic flow inspection and traffic filtering. The company wants to have the same functionalities in the AWS Cloud.
Which solution will meet these requirements?

- A. Use Amazon GuardDuty for traffic inspection and traffic filtering in the production VPC.
- B. Use Traffic Mirroring to mirror traffic from the production VPC for traffic inspection and filtering.
- C. Use AWS Network Firewall to create the required rules for traffic inspection and traffic filtering for the production VPC. **Most Voted**
- D. Use AWS Firewall Manager to create the required rules for traffic inspection and traffic filtering for the production VPC.

Correct Answer: C

Question #16

A company hosts a data lake on AWS. The data lake consists of data in Amazon S3 and Amazon RDS for PostgreSQL. The company needs a reporting solution that provides data visualization and includes all the data sources within the data lake. Only the company's management team should have full access to all the

visualizations. The rest of the company should have only limited access.
Which solution will meet these requirements?

- A. Create an analysis in Amazon QuickSight. Connect all the data sources and create new datasets. Publish dashboards to visualize the data. Share the dashboards with the appropriate IAM roles.
- B. Create an analysis in Amazon QuickSight. Connect all the data sources and create new datasets. Publish dashboards to visualize the data. Share the dashboards with the appropriate users and groups. **Most Voted**
- C. Create an AWS Glue table and crawler for the data in Amazon S3. Create an AWS Glue extract, transform, and load (ETL) job to produce reports. Publish the reports to Amazon S3. Use S3 bucket policies to limit access to the reports.
- D. Create an AWS Glue table and crawler for the data in Amazon S3. Use Amazon Athena Federated Query to access data within Amazon RDS for PostgreSQL. Generate reports by using Amazon Athena. Publish the reports to Amazon S3. Use S3 bucket policies to limit access to the reports.

Correct Answer: B

Question #17

A company is implementing a new business application. The application runs on two Amazon EC2 instances and uses an Amazon S3 bucket for document storage. A solutions architect needs to ensure that the EC2 instances can access the S3 bucket.

What should the solutions architect do to meet this requirement?

- A. Create an IAM role that grants access to the S3 bucket. Attach the role to the EC2 instances. **Most Voted**
- B. Create an IAM policy that grants access to the S3 bucket. Attach the policy to the EC2 instances.
- C. Create an IAM group that grants access to the S3 bucket. Attach the group to the EC2 instances.
- D. Create an IAM user that grants access to the S3 bucket. Attach the user account to the EC2 instances.

Correct Answer: A

Question #18

An application development team is designing a microservice that will convert large images to smaller, compressed images. When a user uploads an image through the web interface, the microservice should store

the image in an Amazon S3 bucket, process and compress the image with an AWS Lambda function, and store the image in its compressed form in a different S3 bucket.

A solutions architect needs to design a solution that uses durable, stateless components to process the images automatically.

Which combination of actions will meet these requirements? (Choose two.)

- A. Create an Amazon Simple Queue Service (Amazon SQS) queue. Configure the S3 bucket to send a notification to the SQS queue when an image is uploaded to the S3 bucket. **Most Voted**
- B. Configure the Lambda function to use the Amazon Simple Queue Service (Amazon SQS) queue as the invocation source. When the SQS message is successfully processed, delete the message in the queue. **Most Voted**
- C. Configure the Lambda function to monitor the S3 bucket for new uploads. When an uploaded image is detected, write the file name to a text file in memory and use the text file to keep track of the images that were processed.
- D. Launch an Amazon EC2 instance to monitor an Amazon Simple Queue Service (Amazon SQS) queue. When items are added to the queue, log the file name in a text file on the EC2 instance and invoke the Lambda function.
- E. Configure an Amazon EventBridge (Amazon CloudWatch Events) event to monitor the S3 bucket. When an image is uploaded, send an alert to an Amazon Simple Notification Service (Amazon SNS) topic with the application owner's email address for further processing.

Correct Answer: AB

Question #19

A company has a three-tier web application that is deployed on AWS. The web servers are deployed in a public subnet in a VPC. The application servers and database servers are deployed in private subnets in the same VPC. The company has deployed a third-party virtual firewall appliance from AWS Marketplace in an inspection VPC. The appliance is configured with an IP interface that can accept IP packets.

A solutions architect needs to integrate the web application with the appliance to inspect all traffic to the application before the traffic reaches the web server.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a Network Load Balancer in the public subnet of the application's VPC to route the traffic to the appliance for packet inspection.
- B. Create an Application Load Balancer in the public subnet of the application's VPC to route the traffic to the appliance for packet inspection.
- C. Deploy a transit gateway in the inspection VPC. Configure route tables to route the incoming packets through the transit gateway.
- D. Deploy a Gateway Load Balancer in the inspection VPC. Create a Gateway Load Balancer endpoint to receive the incoming packets and forward the packets to the appliance. **Most Voted**

Correct Answer: D

Question #20

A company wants to improve its ability to clone large amounts of production data into a test environment in the same AWS Region. The data is stored in Amazon EC2 instances on Amazon Elastic Block Store (Amazon EBS) volumes. Modifications to the cloned data must not affect the production environment. The software that accesses this data requires consistently high I/O performance.

A solutions architect needs to minimize the time that is required to clone the production data into the test environment.

Which solution will meet these requirements?

- A. Take EBS snapshots of the production EBS volumes. Restore the snapshots onto EC2 instance store volumes in the test environment.
- B. Configure the production EBS volumes to use the EBS Multi-Attach feature. Take EBS snapshots of the production EBS volumes. Attach the production EBS volumes to the EC2 instances in the test environment.
- C. Take EBS snapshots of the production EBS volumes. Create and initialize new EBS volumes. Attach the new EBS volumes to EC2 instances in the test environment before restoring the volumes from the production EBS snapshots.
- D. Take EBS snapshots of the production EBS volumes. Turn on the EBS fast snapshot restore feature on the EBS snapshots. Restore the snapshots into new EBS volumes. Attach the new EBS volumes to EC2 instances in the test environment. **Most Voted**

Correct Answer: D

Question #21

An ecommerce company wants to launch a one-deal-a-day website on AWS. Each day will feature exactly one product on sale for a period of 24 hours. The company wants to be able to handle millions of requests each hour with millisecond latency during peak hours.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon S3 to host the full website in different S3 buckets. Add Amazon CloudFront distributions. Set the S3 buckets as origins for the distributions. Store the order data in Amazon S3.
- B. Deploy the full website on Amazon EC2 instances that run in Auto Scaling groups across multiple Availability Zones. Add an Application Load Balancer (ALB) to distribute the website traffic. Add another ALB for the backend APIs. Store the data in Amazon RDS for MySQL.
- C. Migrate the full application to run in containers. Host the containers on Amazon Elastic Kubernetes Service (Amazon EKS). Use the Kubernetes Cluster Autoscaler to increase and decrease the number of pods to process bursts in traffic. Store the data in Amazon RDS for MySQL.
- D. Use an Amazon S3 bucket to host the website's static content. Deploy an Amazon CloudFront distribution. Set the S3 bucket as the origin. Use Amazon API Gateway and AWS Lambda functions for the backend APIs. Store the data in Amazon DynamoDB. **Most Voted**

Correct Answer: D

Question #22

A solutions architect is using Amazon S3 to design the storage architecture of a new digital media application. The media files must be resilient to the loss of an Availability Zone. Some files are accessed frequently while other files are rarely accessed in an unpredictable pattern. The solutions architect must minimize the costs of storing and retrieving the media files.

Which storage option meets these requirements?

- A. S3 Standard
- B. S3 Intelligent-Tiering **Most Voted**
- C. S3 Standard-Infrequent Access (S3 Standard-IA)

- D. S3 One Zone-Infrequent Access (S3 One Zone-IA)

Correct Answer: B

Question #23

A company is storing backup files by using Amazon S3 Standard storage. The files are accessed frequently for 1 month. However, the files are not accessed after 1 month. The company must keep the files indefinitely. Which storage solution will meet these requirements MOST cost-effectively?

- A. Configure S3 Intelligent-Tiering to automatically migrate objects.
- B. Create an S3 Lifecycle configuration to transition objects from S3 Standard to S3 Glacier Deep Archive after 1 month. **Most Voted**
- C. Create an S3 Lifecycle configuration to transition objects from S3 Standard to S3 Standard-Infrequent Access (S3 Standard-IA) after 1 month.
- D. Create an S3 Lifecycle configuration to transition objects from S3 Standard to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 1 month.

Correct Answer: B

Question #24

A company observes an increase in Amazon EC2 costs in its most recent bill. The billing team notices unwanted vertical scaling of instance types for a couple of EC2 instances. A solutions architect needs to create a graph comparing the last 2 months of EC2 costs and perform an in-depth analysis to identify the root cause of the vertical scaling.

How should the solutions architect generate the information with the LEAST operational overhead?

- A. Use AWS Budgets to create a budget report and compare EC2 costs based on instance types.
- B. Use Cost Explorer's granular filtering feature to perform an in-depth analysis of EC2 costs based on instance types. **Most Voted**
- C. Use graphs from the AWS Billing and Cost Management dashboard to compare EC2 costs based on instance types for the last 2 months.

- D. Use AWS Cost and Usage Reports to create a report and send it to an Amazon S3 bucket. Use Amazon QuickSight with Amazon S3 as a source to generate an interactive graph based on instance types.

Correct Answer: B

Question #25

A company is designing an application. The application uses an AWS Lambda function to receive information through Amazon API Gateway and to store the information in an Amazon Aurora PostgreSQL database. During the proof-of-concept stage, the company has to increase the Lambda quotas significantly to handle the high volumes of data that the company needs to load into the database. A solutions architect must recommend a new design to improve scalability and minimize the configuration effort.

Which solution will meet these requirements?

- A. Refactor the Lambda function code to Apache Tomcat code that runs on Amazon EC2 instances. Connect the database by using native Java Database Connectivity (JDBC) drivers.
- B. Change the platform from Aurora to Amazon DynamoDB Provision a DynamoDB Accelerator (DAX) cluster. Use the DAX client SDK to point the existing DynamoDB API calls at the DAX cluster.
- C. Set up two Lambda functions. Configure one function to receive the information. Configure the other function to load the information into the database. Integrate the Lambda functions by using Amazon Simple Notification Service (Amazon SNS).
- D. Set up two Lambda functions. Configure one function to receive the information. Configure the other function to load the information into the database. Integrate the Lambda functions by using an Amazon Simple Queue Service (Amazon SQS) queue. **Most Voted**

Correct Answer: D

Question #26

A company needs to review its AWS Cloud deployment to ensure that its Amazon S3 buckets do not have unauthorized configuration changes.

What should a solutions architect do to accomplish this goal?

- A. Turn on AWS Config with the appropriate rules. **Most Voted**

- B. Turn on AWS Trusted Advisor with the appropriate checks.
- C. Turn on Amazon Inspector with the appropriate assessment template.
- D. Turn on Amazon S3 server access logging. Configure Amazon EventBridge (Amazon Cloud Watch Events).

Correct Answer: A

Question #27

A company is launching a new application and will display application metrics on an Amazon CloudWatch dashboard. The company's product manager needs to access this dashboard periodically. The product manager does not have an AWS account. A solutions architect must provide access to the product manager by following the principle of least privilege.

Which solution will meet these requirements?

- A. Share the dashboard from the CloudWatch console. Enter the product manager's email address, and complete the sharing steps. Provide a shareable link for the dashboard to the product manager. **Most Voted**
- B. Create an IAM user specifically for the product manager. Attach the CloudWatchReadOnlyAccess AWS managed policy to the user. Share the new login credentials with the product manager. Share the browser URL of the correct dashboard with the product manager.
- C. Create an IAM user for the company's employees. Attach the ViewOnlyAccess AWS managed policy to the IAM user. Share the new login credentials with the product manager. Ask the product manager to navigate to the CloudWatch console and locate the dashboard by name in the Dashboards section.
- D. Deploy a bastion server in a public subnet. When the product manager requires access to the dashboard, start the server and share the RDP credentials. On the bastion server, ensure that the browser is configured to open the dashboard URL with cached AWS credentials that have appropriate permissions to view the dashboard.

Correct Answer: A

Question #28

A company is migrating applications to AWS. The applications are deployed in different accounts. The company manages the accounts centrally by using AWS Organizations. The company's security team needs a single sign-on (SSO) solution across all the company's accounts. The company must continue managing the users and

groups in its on-premises self-managed Microsoft Active Directory.
Which solution will meet these requirements?

- A. Enable AWS Single Sign-On (AWS SSO) from the AWS SSO console. Create a one-way forest trust or a one-way domain trust to connect the company's self-managed Microsoft Active Directory with AWS SSO by using AWS Directory Service for Microsoft Active Directory.
- B. Enable AWS Single Sign-On (AWS SSO) from the AWS SSO console. Create a two-way forest trust to connect the company's self-managed Microsoft Active Directory with AWS SSO by using AWS Directory Service for Microsoft Active Directory. **Most Voted**
- C. Use AWS Directory Service. Create a two-way trust relationship with the company's self-managed Microsoft Active Directory.
- D. Deploy an identity provider (IdP) on premises. Enable AWS Single Sign-On (AWS SSO) from the AWS SSO console.

Correct Answer: B

Question #29

A company provides a Voice over Internet Protocol (VoIP) service that uses UDP connections. The service consists of Amazon EC2 instances that run in an Auto Scaling group. The company has deployments across multiple AWS Regions.

The company needs to route users to the Region with the lowest latency. The company also needs automated failover between Regions.

Which solution will meet these requirements?

- A. Deploy a Network Load Balancer (NLB) and an associated target group. Associate the target group with the Auto Scaling group. Use the NLB as an AWS Global Accelerator endpoint in each Region. **Most Voted**
- B. Deploy an Application Load Balancer (ALB) and an associated target group. Associate the target group with the Auto Scaling group. Use the ALB as an AWS Global Accelerator endpoint in each Region.
- C. Deploy a Network Load Balancer (NLB) and an associated target group. Associate the target group with the Auto Scaling group. Create an Amazon Route 53 latency record that points to aliases for each NLB. Create an Amazon CloudFront distribution that uses the latency record as an origin.

- D. Deploy an Application Load Balancer (ALB) and an associated target group. Associate the target group with the Auto Scaling group. Create an Amazon Route 53 weighted record that points to aliases for each ALB. Deploy an Amazon CloudFront distribution that uses the weighted record as an origin.

Correct Answer: A

Question #30

A development team runs monthly resource-intensive tests on its general purpose Amazon RDS for MySQL DB instance with Performance Insights enabled. The testing lasts for 48 hours once a month and is the only process that uses the database. The team wants to reduce the cost of running the tests without reducing the compute and memory attributes of the DB instance.

Which solution meets these requirements MOST cost-effectively?

- A. Stop the DB instance when tests are completed. Restart the DB instance when required.
- B. Use an Auto Scaling policy with the DB instance to automatically scale when tests are completed.
- C. Create a snapshot when tests are completed. Terminate the DB instance and restore the snapshot when required. **Most Voted**
- D. Modify the DB instance to a low-capacity instance when tests are completed. Modify the DB instance again when required.

Correct Answer: C

Question #31

A company that hosts its web application on AWS wants to ensure all Amazon EC2 instances, Amazon RDS DB instances, and Amazon Redshift clusters are configured with tags. The company wants to minimize the effort of configuring and operating this check.

What should a solutions architect do to accomplish this?

- A. Use AWS Config rules to define and detect resources that are not properly tagged. **Most Voted**
- B. Use Cost Explorer to display resources that are not properly tagged. Tag those resources manually.
- C. Write API calls to check all resources for proper tag allocation. Periodically run the code on an EC2 instance.

- D. Write API calls to check all resources for proper tag allocation. Schedule an AWS Lambda function through Amazon CloudWatch to periodically run the code.

Correct Answer: A

Question #32

A development team needs to host a website that will be accessed by other teams. The website contents consist of HTML, CSS, client-side JavaScript, and images.

Which method is the MOST cost-effective for hosting the website?

- A. Containerize the website and host it in AWS Fargate.
- B. Create an Amazon S3 bucket and host the website there. **Most Voted**
- C. Deploy a web server on an Amazon EC2 instance to host the website.
- D. Configure an Application Load Balancer with an AWS Lambda target that uses the Express.js framework.

Correct Answer: B

Question #33

A company runs an online marketplace web application on AWS. The application serves hundreds of thousands of users during peak hours. The company needs a scalable, near-real-time solution to share the details of millions of financial transactions with several other internal applications. Transactions also need to be processed to remove sensitive data before being stored in a document database for low-latency retrieval.

What should a solutions architect recommend to meet these requirements?

- A. Store the transactions data into Amazon DynamoDB. Set up a rule in DynamoDB to remove sensitive data from every transaction upon write. Use DynamoDB Streams to share the transactions data with other applications.
- B. Stream the transactions data into Amazon Kinesis Data Firehose to store data in Amazon DynamoDB and Amazon S3. Use AWS Lambda integration with Kinesis Data Firehose to remove sensitive data. Other applications can consume the data stored in Amazon S3.

- C. Stream the transactions data into Amazon Kinesis Data Streams. Use AWS Lambda integration to remove sensitive data from every transaction and then store the transactions data in Amazon DynamoDB. Other applications can consume the transactions data off the Kinesis data stream. **Most Voted**
- D. Store the batched transactions data in Amazon S3 as files. Use AWS Lambda to process every file and remove sensitive data before updating the files in Amazon S3. The Lambda function then stores the data in Amazon DynamoDB. Other applications can consume transaction files stored in Amazon S3.

Correct Answer: C

Question #34

A company hosts its multi-tier applications on AWS. For compliance, governance, auditing, and security, the company must track configuration changes on its AWS resources and record a history of API calls made to these resources.

What should a solutions architect do to meet these requirements?

- A. Use AWS CloudTrail to track configuration changes and AWS Config to record API calls.
- B. Use AWS Config to track configuration changes and AWS CloudTrail to record API calls. **Most Voted**
- C. Use AWS Config to track configuration changes and Amazon CloudWatch to record API calls.
- D. Use AWS CloudTrail to track configuration changes and Amazon CloudWatch to record API calls.

Correct Answer: B

Question #35

A company is preparing to launch a public-facing web application in the AWS Cloud. The architecture consists of Amazon EC2 instances within a VPC behind an Elastic Load Balancer (ELB). A third-party service is used for the DNS. The company's solutions architect must recommend a solution to detect and protect against large-scale DDoS attacks.

Which solution meets these requirements?

- A. Enable Amazon GuardDuty on the account.
- B. Enable Amazon Inspector on the EC2 instances.
- C. Enable AWS Shield and assign Amazon Route 53 to it.

- D. Enable AWS Shield Advanced and assign the ELB to it. **Most Voted**

Correct Answer: D

Question #36

A company is building an application in the AWS Cloud. The application will store data in Amazon S3 buckets in two AWS Regions. The company must use an AWS Key Management Service (AWS KMS) customer managed key to encrypt all data that is stored in the S3 buckets. The data in both S3 buckets must be encrypted and decrypted with the same KMS key. The data and the key must be stored in each of the two Regions. Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an S3 bucket in each Region. Configure the S3 buckets to use server-side encryption with Amazon S3 managed encryption keys (SSE-S3). Configure replication between the S3 buckets.
- B. Create a customer managed multi-Region KMS key. Create an S3 bucket in each Region. Configure replication between the S3 buckets. Configure the application to use the KMS key with client-side encryption. **Most Voted**
- C. Create a customer managed KMS key and an S3 bucket in each Region. Configure the S3 buckets to use server-side encryption with Amazon S3 managed encryption keys (SSE-S3). Configure replication between the S3 buckets.
- D. Create a customer managed KMS key and an S3 bucket in each Region. Configure the S3 buckets to use server-side encryption with AWS KMS keys (SSE-KMS). Configure replication between the S3 buckets.

Correct Answer: B

Question #37

A company recently launched a variety of new workloads on Amazon EC2 instances in its AWS account. The company needs to create a strategy to access and administer the instances remotely and securely. The company needs to implement a repeatable process that works with native AWS services and follows the AWS Well-Architected Framework.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use the EC2 serial console to directly access the terminal interface of each instance for administration.

- B. Attach the appropriate IAM role to each existing instance and new instance. Use AWS Systems Manager Session Manager to establish a remote SSH session. **Most Voted**
- C. Create an administrative SSH key pair. Load the public key into each EC2 instance. Deploy a bastion host in a public subnet to provide a tunnel for administration of each instance.
- D. Establish an AWS Site-to-Site VPN connection. Instruct administrators to use their local on-premises machines to connect directly to the instances by using SSH keys across the VPN tunnel.

Correct Answer: B

Question #38

A company is hosting a static website on Amazon S3 and is using Amazon Route 53 for DNS. The website is experiencing increased demand from around the world. The company must decrease latency for users who access the website.

Which solution meets these requirements MOST cost-effectively?

- A. Replicate the S3 bucket that contains the website to all AWS Regions. Add Route 53 geolocation routing entries.
- B. Provision accelerators in AWS Global Accelerator. Associate the supplied IP addresses with the S3 bucket. Edit the Route 53 entries to point to the IP addresses of the accelerators.
- C. Add an Amazon CloudFront distribution in front of the S3 bucket. Edit the Route 53 entries to point to the CloudFront distribution. **Most Voted**
- D. Enable S3 Transfer Acceleration on the bucket. Edit the Route 53 entries to point to the new endpoint.

Correct Answer: C

Question #39

A company maintains a searchable repository of items on its website. The data is stored in an Amazon RDS for MySQL database table that contains more than 10 million rows. The database has 2 TB of General Purpose SSD storage. There are millions of updates against this data every day through the company's website.

The company has noticed that some insert operations are taking 10 seconds or longer. The company has determined that the database storage performance is the problem.

Which solution addresses this performance issue?

- A. Change the storage type to Provisioned IOPS SSD. **Most Voted**
- B. Change the DB instance to a memory optimized instance class.
- C. Change the DB instance to a burstable performance instance class.
- D. Enable Multi-AZ RDS read replicas with MySQL native asynchronous replication.

Correct Answer: A

Question #40

A company has thousands of edge devices that collectively generate 1 TB of status alerts each day. Each alert is approximately 2 KB in size. A solutions architect needs to implement a solution to ingest and store the alerts for future analysis.

The company wants a highly available solution. However, the company needs to minimize costs and does not want to manage additional infrastructure. Additionally, the company wants to keep 14 days of data available for immediate analysis and archive any data older than 14 days.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create an Amazon Kinesis Data Firehose delivery stream to ingest the alerts. Configure the Kinesis Data Firehose stream to deliver the alerts to an Amazon S3 bucket. Set up an S3 Lifecycle configuration to transition data to Amazon S3 Glacier after 14 days. **Most Voted**
- B. Launch Amazon EC2 instances across two Availability Zones and place them behind an Elastic Load Balancer to ingest the alerts. Create a script on the EC2 instances that will store the alerts in an Amazon S3 bucket. Set up an S3 Lifecycle configuration to transition data to Amazon S3 Glacier after 14 days.
- C. Create an Amazon Kinesis Data Firehose delivery stream to ingest the alerts. Configure the Kinesis Data Firehose stream to deliver the alerts to an Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster. Set up the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster to take manual snapshots every day and delete data from the cluster that is older than 14 days.
- D. Create an Amazon Simple Queue Service (Amazon SQS) standard queue to ingest the alerts, and set the message retention period to 14 days. Configure consumers to poll the SQS queue, check the age of the message, and analyze the message data as needed. If the message is 14 days old, the consumer should copy the message to an Amazon S3 bucket and delete the message from the SQS queue.

Correct Answer: A

Question #41

A company's application integrates with multiple software-as-a-service (SaaS) sources for data collection. The company runs Amazon EC2 instances to receive the data and to upload the data to an Amazon S3 bucket for analysis. The same EC2 instance that receives and uploads the data also sends a notification to the user when an upload is complete. The company has noticed slow application performance and wants to improve the performance as much as possible.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an Auto Scaling group so that EC2 instances can scale out. Configure an S3 event notification to send events to an Amazon Simple Notification Service (Amazon SNS) topic when the upload to the S3 bucket is complete.
- B. Create an Amazon AppFlow flow to transfer data between each SaaS source and the S3 bucket. Configure an S3 event notification to send events to an Amazon Simple Notification Service (Amazon SNS) topic when the upload to the S3 bucket is complete. **Most Voted**
- C. Create an Amazon EventBridge (Amazon CloudWatch Events) rule for each SaaS source to send output data. Configure the S3 bucket as the rule's target. Create a second EventBridge (Cloud Watch Events) rule to send events when the upload to the S3 bucket is complete. Configure an Amazon Simple Notification Service (Amazon SNS) topic as the second rule's target.
- D. Create a Docker container to use instead of an EC2 instance. Host the containerized application on Amazon Elastic Container Service (Amazon ECS). Configure Amazon CloudWatch Container Insights to send events to an Amazon Simple Notification Service (Amazon SNS) topic when the upload to the S3 bucket is complete.

Correct Answer: B

Question #42

A company runs a highly available image-processing application on Amazon EC2 instances in a single VPC. The EC2 instances run inside several subnets across multiple Availability Zones. The EC2 instances do not communicate with each other. However, the EC2 instances download images from Amazon S3 and upload images to Amazon S3 through a single NAT gateway. The company is concerned about data transfer charges. What is the MOST cost-effective way for the company to avoid Regional data transfer charges?

- A. Launch the NAT gateway in each Availability Zone.

- B. Replace the NAT gateway with a NAT instance.
- C. Deploy a gateway VPC endpoint for Amazon S3. **Most Voted**
- D. Provision an EC2 Dedicated Host to run the EC2 instances.

Correct Answer: C

Question #43

A company has an on-premises application that generates a large amount of time-sensitive data that is backed up to Amazon S3. The application has grown and there are user complaints about internet bandwidth limitations. A solutions architect needs to design a long-term solution that allows for both timely backups to Amazon S3 and with minimal impact on internet connectivity for internal users.

Which solution meets these requirements?

- A. Establish AWS VPN connections and proxy all traffic through a VPC gateway endpoint.
- B. Establish a new AWS Direct Connect connection and direct backup traffic through this new connection. **Most Voted**
- C. Order daily AWS Snowball devices. Load the data onto the Snowball devices and return the devices to AWS each day.
- D. Submit a support ticket through the AWS Management Console. Request the removal of S3 service limits from the account.

Correct Answer: B

Question #44

A company has an Amazon S3 bucket that contains critical data. The company must protect the data from accidental deletion.

Which combination of steps should a solutions architect take to meet these requirements? (Choose two.)

- A. Enable versioning on the S3 bucket. **Most Voted**
- B. Enable MFA Delete on the S3 bucket. **Most Voted**
- C. Create a bucket policy on the S3 bucket.

- D. Enable default encryption on the S3 bucket.
- E. Create a lifecycle policy for the objects in the S3 bucket.

Correct Answer: AB

Question #45

A company has a data ingestion workflow that consists of the following:

- An Amazon Simple Notification Service (Amazon SNS) topic for notifications about new data deliveries
- An AWS Lambda function to process the data and record metadata

The company observes that the ingestion workflow fails occasionally because of network connectivity issues. When such a failure occurs, the Lambda function does not ingest the corresponding data unless the company manually reruns the job.

Which combination of actions should a solutions architect take to ensure that the Lambda function ingests all data in the future? (Choose two.)

- A. Deploy the Lambda function in multiple Availability Zones.
- B. Create an Amazon Simple Queue Service (Amazon SQS) queue, and subscribe it to the SNS topic. **Most Voted**
- C. Increase the CPU and memory that are allocated to the Lambda function.
- D. Increase provisioned throughput for the Lambda function.
- E. Modify the Lambda function to read from an Amazon Simple Queue Service (Amazon SQS) queue. **Most Voted**

Correct Answer: BE

Question #46

A company has an application that provides marketing services to stores. The services are based on previous purchases by store customers. The stores upload transaction data to the company through SFTP, and the data is processed and analyzed to generate new marketing offers. Some of the files can exceed 200 GB in size.

Recently, the company discovered that some of the stores have uploaded files that contain personally identifiable information (PII) that should not have been included. The company wants administrators to be

alerted if PII is shared again. The company also wants to automate remediation.
What should a solutions architect do to meet these requirements with the LEAST development effort?

- A. Use an Amazon S3 bucket as a secure transfer point. Use Amazon Inspector to scan the objects in the bucket. If objects contain PII, trigger an S3 Lifecycle policy to remove the objects that contain PII.
- B. Use an Amazon S3 bucket as a secure transfer point. Use Amazon Macie to scan the objects in the bucket. If objects contain PII, use Amazon Simple Notification Service (Amazon SNS) to trigger a notification to the administrators to remove the objects that contain PII. **Most Voted**
- C. Implement custom scanning algorithms in an AWS Lambda function. Trigger the function when objects are loaded into the bucket. If objects contain PII, use Amazon Simple Notification Service (Amazon SNS) to trigger a notification to the administrators to remove the objects that contain PII.
- D. Implement custom scanning algorithms in an AWS Lambda function. Trigger the function when objects are loaded into the bucket. If objects contain PII, use Amazon Simple Email Service (Amazon SES) to trigger a notification to the administrators and trigger an S3 Lifecycle policy to remove the objects that contain PII.

Correct Answer: B

Question #47

A company needs guaranteed Amazon EC2 capacity in three specific Availability Zones in a specific AWS Region for an upcoming event that will last 1 week.
What should the company do to guarantee the EC2 capacity?

- A. Purchase Reserved Instances that specify the Region needed.
- B. Create an On-Demand Capacity Reservation that specifies the Region needed.
- C. Purchase Reserved Instances that specify the Region and three Availability Zones needed.
- D. Create an On-Demand Capacity Reservation that specifies the Region and three Availability Zones needed. **Most Voted**

Correct Answer: D

Question #48

A company's website uses an Amazon EC2 instance store for its catalog of items. The company wants to make sure that the catalog is highly available and that the catalog is stored in a durable location. What should a solutions architect do to meet these requirements?

- A. Move the catalog to Amazon ElastiCache for Redis.
- B. Deploy a larger EC2 instance with a larger instance store.
- C. Move the catalog from the instance store to Amazon S3 Glacier Deep Archive.
- D. Move the catalog to an Amazon Elastic File System (Amazon EFS) file system. **Most Voted**

Correct Answer: D

Question #49

A company stores call transcript files on a monthly basis. Users access the files randomly within 1 year of the call, but users access the files infrequently after 1 year. The company wants to optimize its solution by giving users the ability to query and retrieve files that are less than 1-year-old as quickly as possible. A delay in retrieving older files is acceptable.

Which solution will meet these requirements MOST cost-effectively?

- A. Store individual files with tags in Amazon S3 Glacier Instant Retrieval. Query the tags to retrieve the files from S3 Glacier Instant Retrieval.
- B. Store individual files in Amazon S3 Intelligent-Tiering. Use S3 Lifecycle policies to move the files to S3 Glacier Flexible Retrieval after 1 year. Query and retrieve the files that are in Amazon S3 by using Amazon Athena. Query and retrieve the files that are in S3 Glacier by using S3 Glacier Select. **Most Voted**
- C. Store individual files with tags in Amazon S3 Standard storage. Store search metadata for each archive in Amazon S3 Standard storage. Use S3 Lifecycle policies to move the files to S3 Glacier Instant Retrieval after 1 year. Query and retrieve the files by searching for metadata from Amazon S3.
- D. Store individual files in Amazon S3 Standard storage. Use S3 Lifecycle policies to move the files to S3 Glacier Deep Archive after 1 year. Store search metadata in Amazon RDS. Query the files from Amazon RDS. Retrieve the files from S3 Glacier Deep Archive.

Correct Answer: B

Question #50

A company has a production workload that runs on 1,000 Amazon EC2 Linux instances. The workload is powered by third-party software. The company needs to patch the third-party software on all EC2 instances as quickly as possible to remediate a critical security vulnerability.

What should a solutions architect do to meet these requirements?

- A. Create an AWS Lambda function to apply the patch to all EC2 instances.
- B. Configure AWS Systems Manager Patch Manager to apply the patch to all EC2 instances.
- C. Schedule an AWS Systems Manager maintenance window to apply the patch to all EC2 instances.
- D. Use AWS Systems Manager Run Command to run a custom command that applies the patch to all EC2 instances. **Most Voted**

Correct Answer: D

Question #51

A company is developing an application that provides order shipping statistics for retrieval by a REST API. The company wants to extract the shipping statistics, organize the data into an easy-to-read HTML format, and send the report to several email addresses at the same time every morning.

Which combination of steps should a solutions architect take to meet these requirements? (Choose two.)

- A. Configure the application to send the data to Amazon Kinesis Data Firehose.
- B. Use Amazon Simple Email Service (Amazon SES) to format the data and to send the report by email. **Most Voted**
- C. Create an Amazon EventBridge (Amazon CloudWatch Events) scheduled event that invokes an AWS Glue job to query the application's API for the data.
- D. Create an Amazon EventBridge (Amazon CloudWatch Events) scheduled event that invokes an AWS Lambda function to query the application's API for the data. **Most Voted**
- E. Store the application data in Amazon S3. Create an Amazon Simple Notification Service (Amazon SNS) topic as an S3 event destination to send the report by email.

Correct Answer: BD

Question #52

A company wants to migrate its on-premises application to AWS. The application produces output files that vary in size from tens of gigabytes to hundreds of terabytes. The application data must be stored in a standard file system structure. The company wants a solution that scales automatically, is highly available, and requires minimum operational overhead.

Which solution will meet these requirements?

- A. Migrate the application to run as containers on Amazon Elastic Container Service (Amazon ECS). Use Amazon S3 for storage.
- B. Migrate the application to run as containers on Amazon Elastic Kubernetes Service (Amazon EKS). Use Amazon Elastic Block Store (Amazon EBS) for storage.
- C. Migrate the application to Amazon EC2 instances in a Multi-AZ Auto Scaling group. Use Amazon Elastic File System (Amazon EFS) for storage. **Most Voted**
- D. Migrate the application to Amazon EC2 instances in a Multi-AZ Auto Scaling group. Use Amazon Elastic Block Store (Amazon EBS) for storage.

Correct Answer: C

Question #53

A company needs to store its accounting records in Amazon S3. The records must be immediately accessible for 1 year and then must be archived for an additional 9 years. No one at the company, including administrative users and root users, can be able to delete the records during the entire 10-year period. The records must be stored with maximum resiliency.

Which solution will meet these requirements?

- A. Store the records in S3 Glacier for the entire 10-year period. Use an access control policy to deny deletion of the records for a period of 10 years.
- B. Store the records by using S3 Intelligent-Tiering. Use an IAM policy to deny deletion of the records. After 10 years, change the IAM policy to allow deletion.

- C. Use an S3 Lifecycle policy to transition the records from S3 Standard to S3 Glacier Deep Archive after 1 year. Use S3 Object Lock in compliance mode for a period of 10 years. **Most Voted**
- D. Use an S3 Lifecycle policy to transition the records from S3 Standard to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 1 year. Use S3 Object Lock in governance mode for a period of 10 years.

Correct Answer: C

Question #54

A company runs multiple Windows workloads on AWS. The company's employees use Windows file shares that are hosted on two Amazon EC2 instances. The file shares synchronize data between themselves and maintain duplicate copies. The company wants a highly available and durable storage solution that preserves how users currently access the files.

What should a solutions architect do to meet these requirements?

- A. Migrate all the data to Amazon S3. Set up IAM authentication for users to access files.
- B. Set up an Amazon S3 File Gateway. Mount the S3 File Gateway on the existing EC2 instances.
- C. Extend the file share environment to Amazon FSx for Windows File Server with a Multi-AZ configuration. Migrate all the data to FSx for Windows File Server. **Most Voted**
- D. Extend the file share environment to Amazon Elastic File System (Amazon EFS) with a Multi-AZ configuration. Migrate all the data to Amazon EFS.

Correct Answer: C

Question #55

A solutions architect is developing a VPC architecture that includes multiple subnets. The architecture will host applications that use Amazon EC2 instances and Amazon RDS DB instances. The architecture consists of six subnets in two Availability Zones. Each Availability Zone includes a public subnet, a private subnet, and a dedicated subnet for databases. Only EC2 instances that run in the private subnets can have access to the RDS databases.

Which solution will meet these requirements?

- A. Create a new route table that excludes the route to the public subnets' CIDR blocks. Associate the route table with the database subnets.
- B. Create a security group that denies inbound traffic from the security group that is assigned to instances in the public subnets. Attach the security group to the DB instances.
- C. Create a security group that allows inbound traffic from the security group that is assigned to instances in the private subnets. Attach the security group to the DB instances. **Most Voted**
- D. Create a new peering connection between the public subnets and the private subnets. Create a different peering connection between the private subnets and the database subnets.

Correct Answer: C

Question #56

A company has registered its domain name with Amazon Route 53. The company uses Amazon API Gateway in the ca-central-1 Region as a public interface for its backend microservice APIs. Third-party services consume the APIs securely. The company wants to design its API Gateway URL with the company's domain name and corresponding certificate so that the third-party services can use HTTPS.

Which solution will meet these requirements?

- A. Create stage variables in API Gateway with Name="Endpoint-URL" and Value="Company Domain Name" to overwrite the default URL. Import the public certificate associated with the company's domain name into AWS Certificate Manager (ACM).
- B. Create Route 53 DNS records with the company's domain name. Point the alias record to the Regional API Gateway stage endpoint. Import the public certificate associated with the company's domain name into AWS Certificate Manager (ACM) in the us-east-1 Region.
- C. Create a Regional API Gateway endpoint. Associate the API Gateway endpoint with the company's domain name. Import the public certificate associated with the company's domain name into AWS Certificate Manager (ACM) in the same Region. Attach the certificate to the API Gateway endpoint. Configure Route 53 to route traffic to the API Gateway endpoint. **Most Voted**
- D. Create a Regional API Gateway endpoint. Associate the API Gateway endpoint with the company's domain name. Import the public certificate associated with the company's domain name into AWS Certificate Manager (ACM) in the us-east-1 Region. Attach the certificate to the API Gateway APIs. Create Route 53 DNS records with the company's domain name. Point an A record to the company's domain name.

Correct Answer: C

Question #57

A company is running a popular social media website. The website gives users the ability to upload images to share with other users. The company wants to make sure that the images do not contain inappropriate content. The company needs a solution that minimizes development effort. What should a solutions architect do to meet these requirements?

- A. Use Amazon Comprehend to detect inappropriate content. Use human review for low-confidence predictions.
- B. Use Amazon Rekognition to detect inappropriate content. Use human review for low-confidence predictions. **Most Voted**
- C. Use Amazon SageMaker to detect inappropriate content. Use ground truth to label low-confidence predictions.
- D. Use AWS Fargate to deploy a custom machine learning model to detect inappropriate content. Use ground truth to label low-confidence predictions.

Correct Answer: B

Question #58

A company wants to run its critical applications in containers to meet requirements for scalability and availability. The company prefers to focus on maintenance of the critical applications. The company does not want to be responsible for provisioning and managing the underlying infrastructure that runs the containerized workload. What should a solutions architect do to meet these requirements?

- A. Use Amazon EC2 instances, and install Docker on the instances.
- B. Use Amazon Elastic Container Service (Amazon ECS) on Amazon EC2 worker nodes.
- C. Use Amazon Elastic Container Service (Amazon ECS) on AWS Fargate. **Most Voted**
- D. Use Amazon EC2 instances from an Amazon Elastic Container Service (Amazon ECS)-optimized Amazon Machine Image (AMI).

Correct Answer: C

Question #59

A company hosts more than 300 global websites and applications. The company requires a platform to analyze more than 30 TB of clickstream data each day.

What should a solutions architect do to transmit and process the clickstream data?

- A. Design an AWS Data Pipeline to archive the data to an Amazon S3 bucket and run an Amazon EMR cluster with the data to generate analytics.
- B. Create an Auto Scaling group of Amazon EC2 instances to process the data and send it to an Amazon S3 data lake for Amazon Redshift to use for analysis.
- C. Cache the data to Amazon CloudFront. Store the data in an Amazon S3 bucket. When an object is added to the S3 bucket, run an AWS Lambda function to process the data for analysis.
- D. Collect the data from Amazon Kinesis Data Streams. Use Amazon Kinesis Data Firehose to transmit the data to an Amazon S3 data lake. Load the data in Amazon Redshift for analysis. **Most Voted**

Correct Answer: D

Question #60

A company has a website hosted on AWS. The website is behind an Application Load Balancer (ALB) that is configured to handle HTTP and HTTPS separately. The company wants to forward all requests to the website so that the requests will use HTTPS.

What should a solutions architect do to meet this requirement?

- A. Update the ALB's network ACL to accept only HTTPS traffic.
- B. Create a rule that replaces the HTTP in the URL with HTTPS.
- C. Create a listener rule on the ALB to redirect HTTP traffic to HTTPS. **Most Voted**
- D. Replace the ALB with a Network Load Balancer configured to use Server Name Indication (SNI).

Correct Answer: C

Question #61

A company is developing a two-tier web application on AWS. The company's developers have deployed the application on an Amazon EC2 instance that connects directly to a backend Amazon RDS database. The company must not hardcode database credentials in the application. The company must also implement a solution to automatically rotate the database credentials on a regular basis.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the database credentials in the instance metadata. Use Amazon EventBridge (Amazon CloudWatch Events) rules to run a scheduled AWS Lambda function that updates the RDS credentials and instance metadata at the same time.
- B. Store the database credentials in a configuration file in an encrypted Amazon S3 bucket. Use Amazon EventBridge (Amazon CloudWatch Events) rules to run a scheduled AWS Lambda function that updates the RDS credentials and the credentials in the configuration file at the same time. Use S3 Versioning to ensure the ability to fall back to previous values.
- C. Store the database credentials as a secret in AWS Secrets Manager. Turn on automatic rotation for the secret. Attach the required permission to the EC2 role to grant access to the secret. **Most Voted**
- D. Store the database credentials as encrypted parameters in AWS Systems Manager Parameter Store. Turn on automatic rotation for the encrypted parameters. Attach the required permission to the EC2 role to grant access to the encrypted parameters.

Correct Answer: C

Question #62

A company is deploying a new public web application to AWS. The application will run behind an Application Load Balancer (ALB). The application needs to be encrypted at the edge with an SSL/TLS certificate that is issued by an external certificate authority (CA). The certificate must be rotated each year before the certificate expires.

What should a solutions architect do to meet these requirements?

- A. Use AWS Certificate Manager (ACM) to issue an SSL/TLS certificate. Apply the certificate to the ALB. Use the managed renewal feature to automatically rotate the certificate.
- B. Use AWS Certificate Manager (ACM) to issue an SSL/TLS certificate. Import the key material from the certificate. Apply the certificate to the ALB. Use the managed renewal feature to automatically rotate the certificate.

- C. Use AWS Certificate Manager (ACM) Private Certificate Authority to issue an SSL/TLS certificate from the root CA. Apply the certificate to the ALB. Use the managed renewal feature to automatically rotate the certificate.
- D. Use AWS Certificate Manager (ACM) to import an SSL/TLS certificate. Apply the certificate to the ALB. Use Amazon EventBridge (Amazon CloudWatch Events) to send a notification when the certificate is nearing expiration. Rotate the certificate manually. **Most Voted**

Correct Answer: D

Question #63

A company runs its infrastructure on AWS and has a registered base of 700,000 users for its document management application. The company intends to create a product that converts large .pdf files to .jpg image files. The .pdf files average 5 MB in size. The company needs to store the original files and the converted files. A solutions architect must design a scalable solution to accommodate demand that will grow rapidly over time. Which solution meets these requirements MOST cost-effectively?

- A. Save the .pdf files to Amazon S3. Configure an S3 PUT event to invoke an AWS Lambda function to convert the files to .jpg format and store them back in Amazon S3. **Most Voted**
- B. Save the .pdf files to Amazon DynamoDB. Use the DynamoDB Streams feature to invoke an AWS Lambda function to convert the files to .jpg format and store them back in DynamoDB.
- C. Upload the .pdf files to an AWS Elastic Beanstalk application that includes Amazon EC2 instances, Amazon Elastic Block Store (Amazon EBS) storage, and an Auto Scaling group. Use a program in the EC2 instances to convert the files to .jpg format. Save the .pdf files and the .jpg files in the EBS store.
- D. Upload the .pdf files to an AWS Elastic Beanstalk application that includes Amazon EC2 instances, Amazon Elastic File System (Amazon EFS) storage, and an Auto Scaling group. Use a program in the EC2 instances to convert the file to .jpg format. Save the .pdf files and the .jpg files in the EBS store.

Correct Answer: A

Question #64

A company has more than 5 TB of file data on Windows file servers that run on premises. Users and applications interact with the data each day.

The company is moving its Windows workloads to AWS. As the company continues this process, the company

requires access to AWS and on-premises file storage with minimum latency. The company needs a solution that minimizes operational overhead and requires no significant changes to the existing file access patterns. The company uses an AWS Site-to-Site VPN connection for connectivity to AWS. What should a solutions architect do to meet these requirements?

- A. Deploy and configure Amazon FSx for Windows File Server on AWS. Move the on-premises file data to FSx for Windows File Server. Reconfigure the workloads to use FSx for Windows File Server on AWS.
- B. Deploy and configure an Amazon S3 File Gateway on premises. Move the on-premises file data to the S3 File Gateway. Reconfigure the on-premises workloads and the cloud workloads to use the S3 File Gateway.
- C. Deploy and configure an Amazon S3 File Gateway on premises. Move the on-premises file data to Amazon S3. Reconfigure the workloads to use either Amazon S3 directly or the S3 File Gateway, depending on each workload's location.
- D. Deploy and configure Amazon FSx for Windows File Server on AWS. Deploy and configure an Amazon FSx File Gateway on premises. Move the on-premises file data to the FSx File Gateway. Configure the cloud workloads to use FSx for Windows File Server on AWS. Configure the on-premises workloads to use the FSx File Gateway. **Most Voted**

Correct Answer: D

Question #65

A hospital recently deployed a RESTful API with Amazon API Gateway and AWS Lambda. The hospital uses API Gateway and Lambda to upload reports that are in PDF format and JPEG format. The hospital needs to modify the Lambda code to identify protected health information (PHI) in the reports.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use existing Python libraries to extract the text from the reports and to identify the PHI from the extracted text.
- B. Use Amazon Textract to extract the text from the reports. Use Amazon SageMaker to identify the PHI from the extracted text.
- C. Use Amazon Textract to extract the text from the reports. Use Amazon Comprehend Medical to identify the PHI from the extracted text. **Most Voted**
- D. Use Amazon Rekognition to extract the text from the reports. Use Amazon Comprehend Medical to identify the PHI from the extracted text.

Correct Answer: C

Question #66

A company has an application that generates a large number of files, each approximately 5 MB in size. The files are stored in Amazon S3. Company policy requires the files to be stored for 4 years before they can be deleted. Immediate accessibility is always required as the files contain critical business data that is not easy to reproduce. The files are frequently accessed in the first 30 days of the object creation but are rarely accessed after the first 30 days.

Which storage solution is MOST cost-effective?

- A. Create an S3 bucket lifecycle policy to move files from S3 Standard to S3 Glacier 30 days from object creation. Delete the files 4 years after object creation. **Most Voted**
- B. Create an S3 bucket lifecycle policy to move files from S3 Standard to S3 One Zone-Infrequent Access (S3 One Zone-IA) 30 days from object creation. Delete the files 4 years after object creation.
- C. Create an S3 bucket lifecycle policy to move files from S3 Standard to S3 Standard-Infrequent Access (S3 Standard-IA) 30 days from object creation. Delete the files 4 years after object creation. **Most Voted**
- D. Create an S3 bucket lifecycle policy to move files from S3 Standard to S3 Standard-Infrequent Access (S3 Standard-IA) 30 days from object creation. Move the files to S3 Glacier 4 years after object creation.

Correct Answer: C

Question #67

A company hosts an application on multiple Amazon EC2 instances. The application processes messages from an Amazon SQS queue, writes to an Amazon RDS table, and deletes the message from the queue. Occasional duplicate records are found in the RDS table. The SQS queue does not contain any duplicate messages.

What should a solutions architect do to ensure messages are being processed once only?

- A. Use the CreateQueue API call to create a new queue.
- B. Use the AddPermission API call to add appropriate permissions.
- C. Use the ReceiveMessage API call to set an appropriate wait time.
- D. Use the ChangeMessageVisibility API call to increase the visibility timeout. **Most Voted**

Correct Answer: D

Question #68

A solutions architect is designing a new hybrid architecture to extend a company's on-premises infrastructure to AWS. The company requires a highly available connection with consistent low latency to an AWS Region. The company needs to minimize costs and is willing to accept slower traffic if the primary connection fails. What should the solutions architect do to meet these requirements?

- A. Provision an AWS Direct Connect connection to a Region. Provision a VPN connection as a backup if the primary Direct Connect connection fails. **Most Voted**
- B. Provision a VPN tunnel connection to a Region for private connectivity. Provision a second VPN tunnel for private connectivity and as a backup if the primary VPN connection fails.
- C. Provision an AWS Direct Connect connection to a Region. Provision a second Direct Connect connection to the same Region as a backup if the primary Direct Connect connection fails.
- D. Provision an AWS Direct Connect connection to a Region. Use the Direct Connect failover attribute from the AWS CLI to automatically create a backup connection if the primary Direct Connect connection fails.

Correct Answer: A

Question #69

A company is running a business-critical web application on Amazon EC2 instances behind an Application Load Balancer. The EC2 instances are in an Auto Scaling group. The application uses an Amazon Aurora PostgreSQL database that is deployed in a single Availability Zone. The company wants the application to be highly available with minimum downtime and minimum loss of data. Which solution will meet these requirements with the LEAST operational effort?

- A. Place the EC2 instances in different AWS Regions. Use Amazon Route 53 health checks to redirect traffic. Use Aurora PostgreSQL Cross-Region Replication.
- B. Configure the Auto Scaling group to use multiple Availability Zones. Configure the database as Multi-AZ. Configure an Amazon RDS Proxy instance for the database. **Most Voted**
- C. Configure the Auto Scaling group to use one Availability Zone. Generate hourly snapshots of the database. Recover the database from the snapshots in the event of a failure.

- D. Configure the Auto Scaling group to use multiple AWS Regions. Write the data from the application to Amazon S3. Use S3 Event Notifications to launch an AWS Lambda function to write the data to the database.

Correct Answer: B

Question #70

A company's HTTP application is behind a Network Load Balancer (NLB). The NLB's target group is configured to use an Amazon EC2 Auto Scaling group with multiple EC2 instances that run the web service.

The company notices that the NLB is not detecting HTTP errors for the application. These errors require a manual restart of the EC2 instances that run the web service. The company needs to improve the application's availability without writing custom scripts or code.

What should a solutions architect do to meet these requirements?

- A. Enable HTTP health checks on the NLB, supplying the URL of the company's application.
- B. Add a cron job to the EC2 instances to check the local application's logs once each minute. If HTTP errors are detected, the application will restart.
- C. Replace the NLB with an Application Load Balancer. Enable HTTP health checks by supplying the URL of the company's application. Configure an Auto Scaling action to replace unhealthy instances. **Most Voted**
- D. Create an Amazon Cloud Watch alarm that monitors the UnhealthyHostCount metric for the NLB. Configure an Auto Scaling action to replace unhealthy instances when the alarm is in the ALARM state.

Correct Answer: C

Question #71

A company runs a shopping application that uses Amazon DynamoDB to store customer information. In case of data corruption, a solutions architect needs to design a solution that meets a recovery point objective (RPO) of 15 minutes and a recovery time objective (RTO) of 1 hour.

What should the solutions architect recommend to meet these requirements?

- A. Configure DynamoDB global tables. For RPO recovery, point the application to a different AWS Region.
- B. Configure DynamoDB point-in-time recovery. For RPO recovery, restore to the desired point in time. **Most Voted**

- C. Export the DynamoDB data to Amazon S3 Glacier on a daily basis. For RPO recovery, import the data from S3 Glacier to DynamoDB.
- D. Schedule Amazon Elastic Block Store (Amazon EBS) snapshots for the DynamoDB table every 15 minutes. For RPO recovery, restore the DynamoDB table by using the EBS snapshot.

Correct Answer: B

Question #72

A company runs a photo processing application that needs to frequently upload and download pictures from Amazon S3 buckets that are located in the same AWS Region. A solutions architect has noticed an increased cost in data transfer fees and needs to implement a solution to reduce these costs.

How can the solutions architect meet this requirement?

- A. Deploy Amazon API Gateway into a public subnet and adjust the route table to route S3 calls through it.
- B. Deploy a NAT gateway into a public subnet and attach an endpoint policy that allows access to the S3 buckets.
- C. Deploy the application into a public subnet and allow it to route through an internet gateway to access the S3 buckets.
- D. Deploy an S3 VPC gateway endpoint into the VPC and attach an endpoint policy that allows access to the S3 buckets. **Most Voted**

Correct Answer: D

Question #73

A company recently launched Linux-based application instances on Amazon EC2 in a private subnet and launched a Linux-based bastion host on an Amazon EC2 instance in a public subnet of a VPC. A solutions architect needs to connect from the on-premises network, through the company's internet connection, to the bastion host, and to the application servers. The solutions architect must make sure that the security groups of all the EC2 instances will allow that access.

Which combination of steps should the solutions architect take to meet these requirements? (Choose two.)

- A. Replace the current security group of the bastion host with one that only allows inbound access from the application instances.
- B. Replace the current security group of the bastion host with one that only allows inbound access from the internal IP range for the company.
- C. Replace the current security group of the bastion host with one that only allows inbound access from the external IP range for the company. **Most Voted**
- D. Replace the current security group of the application instances with one that allows inbound SSH access from only the private IP address of the bastion host. **Most Voted**
- E. Replace the current security group of the application instances with one that allows inbound SSH access from only the public IP address of the bastion host.

Correct Answer: CD

Question #74

A solutions architect is designing a two-tier web application. The application consists of a public-facing web tier hosted on Amazon EC2 in public subnets. The database tier consists of Microsoft SQL Server running on Amazon EC2 in a private subnet. Security is a high priority for the company. How should security groups be configured in this situation? (Choose two.)

- A. Configure the security group for the web tier to allow inbound traffic on port 443 from 0.0.0.0/0. **Most Voted**
- B. Configure the security group for the web tier to allow outbound traffic on port 443 from 0.0.0.0/0.
- C. Configure the security group for the database tier to allow inbound traffic on port 1433 from the security group for the web tier. **Most Voted**
- D. Configure the security group for the database tier to allow outbound traffic on ports 443 and 1433 to the security group for the web tier.
- E. Configure the security group for the database tier to allow inbound traffic on ports 443 and 1433 from the security group for the web tier.

Correct Answer: AC

Question #75

A company wants to move a multi-tiered application from on premises to the AWS Cloud to improve the application's performance. The application consists of application tiers that communicate with each other by way of RESTful services. Transactions are dropped when one tier becomes overloaded. A solutions architect must design a solution that resolves these issues and modernizes the application.

Which solution meets these requirements and is the MOST operationally efficient?

- A. Use Amazon API Gateway and direct transactions to the AWS Lambda functions as the application layer. Use Amazon Simple Queue Service (Amazon SQS) as the communication layer between application services. **Most Voted**
- B. Use Amazon CloudWatch metrics to analyze the application performance history to determine the servers' peak utilization during the performance failures. Increase the size of the application server's Amazon EC2 instances to meet the peak requirements.
- C. Use Amazon Simple Notification Service (Amazon SNS) to handle the messaging between application servers running on Amazon EC2 in an Auto Scaling group. Use Amazon CloudWatch to monitor the SNS queue length and scale up and down as required.
- D. Use Amazon Simple Queue Service (Amazon SQS) to handle the messaging between application servers running on Amazon EC2 in an Auto Scaling group. Use Amazon CloudWatch to monitor the SQS queue length and scale up when communication failures are detected.

Correct Answer: A

Question #76

A company receives 10 TB of instrumentation data each day from several machines located at a single factory. The data consists of JSON files stored on a storage area network (SAN) in an on-premises data center located within the factory. The company wants to send this data to Amazon S3 where it can be accessed by several additional systems that provide critical near-real-time analytics. A secure transfer is important because the data is considered sensitive.

Which solution offers the MOST reliable data transfer?

- A. AWS DataSync over public internet
- B. AWS DataSync over AWS Direct Connect **Most Voted**
- C. AWS Database Migration Service (AWS DMS) over public internet

- D. AWS Database Migration Service (AWS DMS) over AWS Direct Connect

Correct Answer: B

Question #77

A company needs to configure a real-time data ingestion architecture for its application. The company needs an API, a process that transforms data as the data is streamed, and a storage solution for the data. Which solution will meet these requirements with the LEAST operational overhead?

- A. Deploy an Amazon EC2 instance to host an API that sends data to an Amazon Kinesis data stream. Create an Amazon Kinesis Data Firehose delivery stream that uses the Kinesis data stream as a data source. Use AWS Lambda functions to transform the data. Use the Kinesis Data Firehose delivery stream to send the data to Amazon S3.
- B. Deploy an Amazon EC2 instance to host an API that sends data to AWS Glue. Stop source/destination checking on the EC2 instance. Use AWS Glue to transform the data and to send the data to Amazon S3.
- C. Configure an Amazon API Gateway API to send data to an Amazon Kinesis data stream. Create an Amazon Kinesis Data Firehose delivery stream that uses the Kinesis data stream as a data source. Use AWS Lambda functions to transform the data. Use the Kinesis Data Firehose delivery stream to send the data to Amazon S3. **Most Voted**
- D. Configure an Amazon API Gateway API to send data to AWS Glue. Use AWS Lambda functions to transform the data. Use AWS Glue to send the data to Amazon S3.

Correct Answer: C

Question #78

A company needs to keep user transaction data in an Amazon DynamoDB table. The company must retain the data for 7 years.

What is the MOST operationally efficient solution that meets these requirements?

- A. Use DynamoDB point-in-time recovery to back up the table continuously.
- B. Use AWS Backup to create backup schedules and retention policies for the table. **Most Voted**

- C. Create an on-demand backup of the table by using the DynamoDB console. Store the backup in an Amazon S3 bucket. Set an S3 Lifecycle configuration for the S3 bucket.
- D. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function. Configure the Lambda function to back up the table and to store the backup in an Amazon S3 bucket. Set an S3 Lifecycle configuration for the S3 bucket.

Correct Answer: B

Question #79

A company is planning to use an Amazon DynamoDB table for data storage. The company is concerned about cost optimization. The table will not be used on most mornings. In the evenings, the read and write traffic will often be unpredictable. When traffic spikes occur, they will happen very quickly. What should a solutions architect recommend?

- A. Create a DynamoDB table in on-demand capacity mode. **Most Voted**
- B. Create a DynamoDB table with a global secondary index.
- C. Create a DynamoDB table with provisioned capacity and auto scaling.
- D. Create a DynamoDB table in provisioned capacity mode, and configure it as a global table.

Correct Answer: A

Question #80

A company recently signed a contract with an AWS Managed Service Provider (MSP) Partner for help with an application migration initiative. A solutions architect needs to share an Amazon Machine Image (AMI) from an existing AWS account with the MSP Partner's AWS account. The AMI is backed by Amazon Elastic Block Store (Amazon EBS) and uses an AWS Key Management Service (AWS KMS) customer managed key to encrypt EBS volume snapshots.

What is the MOST secure way for the solutions architect to share the AMI with the MSP Partner's AWS account?

- A. Make the encrypted AMI and snapshots publicly available. Modify the key policy to allow the MSP Partner's AWS account to use the key.

- B. Modify the launchPermission property of the AMI. Share the AMI with the MSP Partner's AWS account only. Modify the key policy to allow the MSP Partner's AWS account to use the key. **Most Voted**
- C. Modify the launchPermission property of the AMI. Share the AMI with the MSP Partner's AWS account only. Modify the key policy to trust a new KMS key that is owned by the MSP Partner for encryption.
- D. Export the AMI from the source account to an Amazon S3 bucket in the MSP Partner's AWS account, Encrypt the S3 bucket with a new KMS key that is owned by the MSP Partner. Copy and launch the AMI in the MSP Partner's AWS account.

Correct Answer: B

Question #81

A solutions architect is designing the cloud architecture for a new application being deployed on AWS. The process should run in parallel while adding and removing application nodes as needed based on the number of jobs to be processed. The processor application is stateless. The solutions architect must ensure that the application is loosely coupled and the job items are durably stored.

Which design should the solutions architect use?

- A. Create an Amazon SNS topic to send the jobs that need to be processed. Create an Amazon Machine Image (AMI) that consists of the processor application. Create a launch configuration that uses the AMI. Create an Auto Scaling group using the launch configuration. Set the scaling policy for the Auto Scaling group to add and remove nodes based on CPU usage.
- B. Create an Amazon SQS queue to hold the jobs that need to be processed. Create an Amazon Machine Image (AMI) that consists of the processor application. Create a launch configuration that uses the AMI. Create an Auto Scaling group using the launch configuration. Set the scaling policy for the Auto Scaling group to add and remove nodes based on network usage.
- C. Create an Amazon SQS queue to hold the jobs that need to be processed. Create an Amazon Machine Image (AMI) that consists of the processor application. Create a launch template that uses the AMI. Create an Auto Scaling group using the launch template. Set the scaling policy for the Auto Scaling group to add and remove nodes based on the number of items in the SQS queue. **Most Voted**
- D. Create an Amazon SNS topic to send the jobs that need to be processed. Create an Amazon Machine Image (AMI) that consists of the processor application. Create a launch template that uses the AMI. Create an Auto

Scaling group using the launch template. Set the scaling policy for the Auto Scaling group to add and remove nodes based on the number of messages published to the SNS topic.

Correct Answer: C

Question #82

A company hosts its web applications in the AWS Cloud. The company configures Elastic Load Balancers to use certificates that are imported into AWS Certificate Manager (ACM). The company's security team must be notified 30 days before the expiration of each certificate.

What should a solutions architect recommend to meet this requirement?

- A. Add a rule in ACM to publish a custom message to an Amazon Simple Notification Service (Amazon SNS) topic every day, beginning 30 days before any certificate will expire.
- B. Create an AWS Config rule that checks for certificates that will expire within 30 days. Configure Amazon EventBridge (Amazon CloudWatch Events) to invoke a custom alert by way of Amazon Simple Notification Service (Amazon SNS) when AWS Config reports a noncompliant resource. **Most Voted**
- C. Use AWS Trusted Advisor to check for certificates that will expire within 30 days. Create an Amazon CloudWatch alarm that is based on Trusted Advisor metrics for check status changes. Configure the alarm to send a custom alert by way of Amazon Simple Notification Service (Amazon SNS).
- D. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to detect any certificates that will expire within 30 days. Configure the rule to invoke an AWS Lambda function. Configure the Lambda function to send a custom alert by way of Amazon Simple Notification Service (Amazon SNS). **Most Voted**

Correct Answer: D

Question #83

A company's dynamic website is hosted using on-premises servers in the United States. The company is launching its product in Europe, and it wants to optimize site loading times for new European users. The site's backend must remain in the United States. The product is being launched in a few days, and an immediate solution is needed.

What should the solutions architect recommend?

- A. Launch an Amazon EC2 instance in us-east-1 and migrate the site to it.
- B. Move the website to Amazon S3. Use Cross-Region Replication between Regions.
- C. Use Amazon CloudFront with a custom origin pointing to the on-premises servers. **Most Voted**
- D. Use an Amazon Route 53 geoproximity routing policy pointing to on-premises servers.

Correct Answer: C

Question #84

A company wants to reduce the cost of its existing three-tier web architecture. The web, application, and database servers are running on Amazon EC2 instances for the development, test, and production environments. The EC2 instances average 30% CPU utilization during peak hours and 10% CPU utilization during non-peak hours.

The production EC2 instances run 24 hours a day. The development and test EC2 instances run for at least 8 hours each day. The company plans to implement automation to stop the development and test EC2 instances when they are not in use.

Which EC2 instance purchasing solution will meet the company's requirements MOST cost-effectively?

- A. Use Spot Instances for the production EC2 instances. Use Reserved Instances for the development and test EC2 instances.
- B. Use Reserved Instances for the production EC2 instances. Use On-Demand Instances for the development and test EC2 instances. **Most Voted**
- C. Use Spot blocks for the production EC2 instances. Use Reserved Instances for the development and test EC2 instances.
- D. Use On-Demand Instances for the production EC2 instances. Use Spot blocks for the development and test EC2 instances.

Correct Answer: B

Question #85

A company has a production web application in which users upload documents through a web interface or a mobile app. According to a new regulatory requirement, new documents cannot be modified or deleted after they

are stored.

What should a solutions architect do to meet this requirement?

- A. Store the uploaded documents in an Amazon S3 bucket with S3 Versioning and S3 Object Lock enabled. **Most Voted**
- B. Store the uploaded documents in an Amazon S3 bucket. Configure an S3 Lifecycle policy to archive the documents periodically.
- C. Store the uploaded documents in an Amazon S3 bucket with S3 Versioning enabled. Configure an ACL to restrict all access to read-only.
- D. Store the uploaded documents on an Amazon Elastic File System (Amazon EFS) volume. Access the data by mounting the volume in read-only mode.

Correct Answer: A

Question #86

A company has several web servers that need to frequently access a common Amazon RDS MySQL Multi-AZ DB instance. The company wants a secure method for the web servers to connect to the database while meeting a security requirement to rotate user credentials frequently.

Which solution meets these requirements?

- A. Store the database user credentials in AWS Secrets Manager. Grant the necessary IAM permissions to allow the web servers to access AWS Secrets Manager. **Most Voted**
- B. Store the database user credentials in AWS Systems Manager OpsCenter. Grant the necessary IAM permissions to allow the web servers to access OpsCenter.
- C. Store the database user credentials in a secure Amazon S3 bucket. Grant the necessary IAM permissions to allow the web servers to retrieve credentials and access the database.
- D. Store the database user credentials in files encrypted with AWS Key Management Service (AWS KMS) on the web server file system. The web server should be able to decrypt the files and access the database.

Correct Answer: A

Question #87

A company hosts an application on AWS Lambda functions that are invoked by an Amazon API Gateway API. The Lambda functions save customer data to an Amazon Aurora MySQL database. Whenever the company upgrades the database, the Lambda functions fail to establish database connections until the upgrade is complete. The result is that customer data is not recorded for some of the event.

A solutions architect needs to design a solution that stores customer data that is created during database upgrades.

Which solution will meet these requirements?

- A. Provision an Amazon RDS proxy to sit between the Lambda functions and the database. Configure the Lambda functions to connect to the RDS proxy.
- B. Increase the run time of the Lambda functions to the maximum. Create a retry mechanism in the code that stores the customer data in the database.
- C. Persist the customer data to Lambda local storage. Configure new Lambda functions to scan the local storage to save the customer data to the database.
- D. Store the customer data in an Amazon Simple Queue Service (Amazon SQS) FIFO queue. Create a new Lambda function that polls the queue and stores the customer data in the database. **Most Voted**

Correct Answer: D

Question #88

A survey company has gathered data for several years from areas in the United States. The company hosts the data in an Amazon S3 bucket that is 3 TB in size and growing. The company has started to share the data with a European marketing firm that has S3 buckets. The company wants to ensure that its data transfer costs remain as low as possible.

Which solution will meet these requirements?

- A. Configure the Requester Pays feature on the company's S3 bucket. **Most Voted**
- B. Configure S3 Cross-Region Replication from the company's S3 bucket to one of the marketing firm's S3 buckets.
- C. Configure cross-account access for the marketing firm so that the marketing firm has access to the company's S3 bucket.

- D. Configure the company's S3 bucket to use S3 Intelligent-Tiering. Sync the S3 bucket to one of the marketing firm's S3 buckets.

Correct Answer: A

Question #89

A company uses Amazon S3 to store its confidential audit documents. The S3 bucket uses bucket policies to restrict access to audit team IAM user credentials according to the principle of least privilege. Company managers are worried about accidental deletion of documents in the S3 bucket and want a more secure solution. What should a solutions architect do to secure the audit documents?

- A. Enable the versioning and MFA Delete features on the S3 bucket. **Most Voted**
- B. Enable multi-factor authentication (MFA) on the IAM user credentials for each audit team IAM user account.
- C. Add an S3 Lifecycle policy to the audit team's IAM user accounts to deny the s3:DeleteObject action during audit dates.
- D. Use AWS Key Management Service (AWS KMS) to encrypt the S3 bucket and restrict audit team IAM user accounts from accessing the KMS key.

Correct Answer: A

Question #90

A company is using a SQL database to store movie data that is publicly accessible. The database runs on an Amazon RDS Single-AZ DB instance. A script runs queries at random intervals each day to record the number of new movies that have been added to the database. The script must report a final total during business hours. The company's development team notices that the database performance is inadequate for development tasks when the script is running. A solutions architect must recommend a solution to resolve this issue. Which solution will meet this requirement with the LEAST operational overhead?

- A. Modify the DB instance to be a Multi-AZ deployment.
- B. Create a read replica of the database. Configure the script to query only the read replica. **Most Voted**
- C. Instruct the development team to manually export the entries in the database at the end of each day.
- D. Use Amazon ElastiCache to cache the common queries that the script runs against the database.

Correct Answer: B

Question #91

A company has applications that run on Amazon EC2 instances in a VPC. One of the applications needs to call the Amazon S3 API to store and read objects. According to the company's security regulations, no traffic from the applications is allowed to travel across the internet. Which solution will meet these requirements?

- A. Configure an S3 gateway endpoint. **Most Voted**
- B. Create an S3 bucket in a private subnet.
- C. Create an S3 bucket in the same AWS Region as the EC2 instances.
- D. Configure a NAT gateway in the same subnet as the EC2 instances.

Correct Answer: A

Question #92

A company is storing sensitive user information in an Amazon S3 bucket. The company wants to provide secure access to this bucket from the application tier running on Amazon EC2 instances inside a VPC. Which combination of steps should a solutions architect take to accomplish this? (Choose two.)

- A. Configure a VPC gateway endpoint for Amazon S3 within the VPC. **Most Voted**
- B. Create a bucket policy to make the objects in the S3 bucket public.
- C. Create a bucket policy that limits access to only the application tier running in the VPC. **Most Voted**
- D. Create an IAM user with an S3 access policy and copy the IAM credentials to the EC2 instance.
- E. Create a NAT instance and have the EC2 instances use the NAT instance to access the S3 bucket.

Correct Answer: AC

Question #93

A company runs an on-premises application that is powered by a MySQL database. The company is migrating the application to AWS to increase the application's elasticity and availability.

The current architecture shows heavy read activity on the database during times of normal operation. Every 4 hours, the company's development team pulls a full export of the production database to populate a database in the staging environment. During this period, users experience unacceptable application latency. The development team is unable to use the staging environment until the procedure completes. A solutions architect must recommend replacement architecture that alleviates the application latency issue. The replacement architecture also must give the development team the ability to continue using the staging environment without delay.

Which solution meets these requirements?

- A. Use Amazon Aurora MySQL with Multi-AZ Aurora Replicas for production. Populate the staging database by implementing a backup and restore process that uses the mysqldump utility.
- B. Use Amazon Aurora MySQL with Multi-AZ Aurora Replicas for production. Use database cloning to create the staging database on-demand. **Most Voted**
- C. Use Amazon RDS for MySQL with a Multi-AZ deployment and read replicas for production. Use the standby instance for the staging database.
- D. Use Amazon RDS for MySQL with a Multi-AZ deployment and read replicas for production. Populate the staging database by implementing a backup and restore process that uses the mysqldump utility.

Correct Answer: B

Question #94

A company is designing an application where users upload small files into Amazon S3. After a user uploads a file, the file requires one-time simple processing to transform the data and save the data in JSON format for later analysis.

Each file must be processed as quickly as possible after it is uploaded. Demand will vary. On some days, users will upload a high number of files. On other days, users will upload a few files or no files.

Which solution meets these requirements with the LEAST operational overhead?

- A. Configure Amazon EMR to read text files from Amazon S3. Run processing scripts to transform the data. Store the resulting JSON file in an Amazon Aurora DB cluster.

- B. Configure Amazon S3 to send an event notification to an Amazon Simple Queue Service (Amazon SQS) queue. Use Amazon EC2 instances to read from the queue and process the data. Store the resulting JSON file in Amazon DynamoDB.
- C. Configure Amazon S3 to send an event notification to an Amazon Simple Queue Service (Amazon SQS) queue. Use an AWS Lambda function to read from the queue and process the data. Store the resulting JSON file in Amazon DynamoDB. **Most Voted**
- D. Configure Amazon EventBridge (Amazon CloudWatch Events) to send an event to Amazon Kinesis Data Streams when a new file is uploaded. Use an AWS Lambda function to consume the event from the stream and process the data. Store the resulting JSON file in an Amazon Aurora DB cluster.

Correct Answer: C

Question #95

An application allows users at a company's headquarters to access product data. The product data is stored in an Amazon RDS MySQL DB instance. The operations team has isolated an application performance slowdown and wants to separate read traffic from write traffic. A solutions architect needs to optimize the application's performance quickly.

What should the solutions architect recommend?

- A. Change the existing database to a Multi-AZ deployment. Serve the read requests from the primary Availability Zone.
- B. Change the existing database to a Multi-AZ deployment. Serve the read requests from the secondary Availability Zone.
- C. Create read replicas for the database. Configure the read replicas with half of the compute and storage resources as the source database.
- D. Create read replicas for the database. Configure the read replicas with the same compute and storage resources as the source database. **Most Voted**

Correct Answer: D

Question #96

An Amazon EC2 administrator created the following policy associated with an IAM group containing several users:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "ec2:TerminateInstances",
      "Resource": "*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "10.100.100.0/24"
        }
      }
    },
    {
      "Effect": "Deny",
      "Action": "ec2:*",
      "Resource": "*",
      "Condition": {
        "StringNotEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    }
  ]
}
```

What is the effect of this policy?

- A. Users can terminate an EC2 instance in any AWS Region except us-east-1.

- B. Users can terminate an EC2 instance with the IP address 10.100.100.1 in the us-east-1 Region.
- C. Users can terminate an EC2 instance in the us-east-1 Region when the user's source IP is 10.100.100.254. **Most Voted**
- D. Users cannot terminate an EC2 instance in the us-east-1 Region when the user's source IP is 10.100.100.254.

Correct Answer: C

Question #97

A company has a large Microsoft SharePoint deployment running on-premises that requires Microsoft Windows shared file storage. The company wants to migrate this workload to the AWS Cloud and is considering various storage options. The storage solution must be highly available and integrated with Active Directory for access control.

Which solution will satisfy these requirements?

- A. Configure Amazon EFS storage and set the Active Directory domain for authentication.
- B. Create an SMB file share on an AWS Storage Gateway file gateway in two Availability Zones.
- C. Create an Amazon S3 bucket and configure Microsoft Windows Server to mount it as a volume.
- D. Create an Amazon FSx for Windows File Server file system on AWS and set the Active Directory domain for authentication. **Most Voted**

Correct Answer: D

Question #98

An image-processing company has a web application that users use to upload images. The application uploads the images into an Amazon S3 bucket. The company has set up S3 event notifications to publish the object creation events to an Amazon Simple Queue Service (Amazon SQS) standard queue. The SQS queue serves as the event source for an AWS Lambda function that processes the images and sends the results to users through email.

Users report that they are receiving multiple email messages for every uploaded image. A solutions architect determines that SQS messages are invoking the Lambda function more than once, resulting in multiple email

messages.

What should the solutions architect do to resolve this issue with the LEAST operational overhead?

- A. Set up long polling in the SQS queue by increasing the ReceiveMessage wait time to 30 seconds.
- B. Change the SQS standard queue to an SQS FIFO queue. Use the message deduplication ID to discard duplicate messages.
- C. Increase the visibility timeout in the SQS queue to a value that is greater than the total of the function timeout and the batch window timeout. **Most Voted**
- D. Modify the Lambda function to delete each message from the SQS queue immediately after the message is read before processing.

Correct Answer: C

Question #99

A company is implementing a shared storage solution for a gaming application that is hosted in an on-premises data center. The company needs the ability to use Lustre clients to access data. The solution must be fully managed.

Which solution meets these requirements?

- A. Create an AWS Storage Gateway file gateway. Create a file share that uses the required client protocol. Connect the application server to the file share.
- B. Create an Amazon EC2 Windows instance. Install and configure a Windows file share role on the instance. Connect the application server to the file share.
- C. Create an Amazon Elastic File System (Amazon EFS) file system, and configure it to support Lustre. Attach the file system to the origin server. Connect the application server to the file system.
- D. Create an Amazon FSx for Lustre file system. Attach the file system to the origin server. Connect the application server to the file system. **Most Voted**

Correct Answer: D

Question #100

A company's containerized application runs on an Amazon EC2 instance. The application needs to download security certificates before it can communicate with other business applications. The company wants a highly secure solution to encrypt and decrypt the certificates in near real time. The solution also needs to store data in highly available storage after the data is encrypted.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create AWS Secrets Manager secrets for encrypted certificates. Manually update the certificates as needed. Control access to the data by using fine-grained IAM access.
- B. Create an AWS Lambda function that uses the Python cryptography library to receive and perform encryption operations. Store the function in an Amazon S3 bucket.
- C. Create an AWS Key Management Service (AWS KMS) customer managed key. Allow the EC2 role to use the KMS key for encryption operations. Store the encrypted data on Amazon S3. **Most Voted**
- D. Create an AWS Key Management Service (AWS KMS) customer managed key. Allow the EC2 role to use the KMS key for encryption operations. Store the encrypted data on Amazon Elastic Block Store (Amazon EBS) volumes.

Correct Answer: C

Question #101

A solutions architect is designing a VPC with public and private subnets. The VPC and subnets use IPv4 CIDR blocks. There is one public subnet and one private subnet in each of three Availability Zones (AZs) for high availability. An internet gateway is used to provide internet access for the public subnets. The private subnets require access to the internet to allow Amazon EC2 instances to download software updates.

What should the solutions architect do to enable Internet access for the private subnets?

- A. Create three NAT gateways, one for each public subnet in each AZ. Create a private route table for each AZ that forwards non-VPC traffic to the NAT gateway in its AZ. **Most Voted**
- B. Create three NAT instances, one for each private subnet in each AZ. Create a private route table for each AZ that forwards non-VPC traffic to the NAT instance in its AZ.
- C. Create a second internet gateway on one of the private subnets. Update the route table for the private subnets that forward non-VPC traffic to the private internet gateway.

- D. Create an egress-only internet gateway on one of the public subnets. Update the route table for the private subnets that forward non-VPC traffic to the egress-only Internet gateway.

Correct Answer: A

Question #102

A company wants to migrate an on-premises data center to AWS. The data center hosts an SFTP server that stores its data on an NFS-based file system. The server holds 200 GB of data that needs to be transferred. The server must be hosted on an Amazon EC2 instance that uses an Amazon Elastic File System (Amazon EFS) file system.

Which combination of steps should a solutions architect take to automate this task? (Choose two.)

- A. Launch the EC2 instance into the same Availability Zone as the EFS file system.
- B. Install an AWS DataSync agent in the on-premises data center. **Most Voted**
- C. Create a secondary Amazon Elastic Block Store (Amazon EBS) volume on the EC2 instance for the data.
- D. Manually use an operating system copy command to push the data to the EC2 instance.
- E. Use AWS DataSync to create a suitable location configuration for the on-premises SFTP server. **Most Voted**

Correct Answer: BE

Question #103

A company has an AWS Glue extract, transform, and load (ETL) job that runs every day at the same time. The job processes XML data that is in an Amazon S3 bucket. New data is added to the S3 bucket every day. A solutions architect notices that AWS Glue is processing all the data during each run.

What should the solutions architect do to prevent AWS Glue from reprocessing old data?

- A. Edit the job to use job bookmarks. **Most Voted**
- B. Edit the job to delete data after the data is processed.
- C. Edit the job by setting the NumberOfWorkers field to 1.
- D. Use a FindMatches machine learning (ML) transform.

Correct Answer: A

Question #104

A solutions architect must design a highly available infrastructure for a website. The website is powered by Windows web servers that run on Amazon EC2 instances. The solutions architect must implement a solution that can mitigate a large-scale DDoS attack that originates from thousands of IP addresses. Downtime is not acceptable for the website.

Which actions should the solutions architect take to protect the website from such an attack? (Choose two.)

- A. Use AWS Shield Advanced to stop the DDoS attack. **Most Voted**
- B. Configure Amazon GuardDuty to automatically block the attackers.
- C. Configure the website to use Amazon CloudFront for both static and dynamic content. **Most Voted**
- D. Use an AWS Lambda function to automatically add attacker IP addresses to VPC network ACLs.
- E. Use EC2 Spot Instances in an Auto Scaling group with a target tracking scaling policy that is set to 80% CPU utilization.

Correct Answer: AC

Question #105

A company is preparing to deploy a new serverless workload. A solutions architect must use the principle of least privilege to configure permissions that will be used to run an AWS Lambda function. An Amazon EventBridge (Amazon CloudWatch Events) rule will invoke the function.

Which solution meets these requirements?

- A. Add an execution role to the function with `lambda:InvokeFunction` as the action and `*` as the principal.
- B. Add an execution role to the function with `lambda:InvokeFunction` as the action and `Service: lambda.amazonaws.com` as the principal.
- C. Add a resource-based policy to the function with `lambda:*` as the action and `Service: events.amazonaws.com` as the principal.
- D. Add a resource-based policy to the function with `lambda:InvokeFunction` as the action and `Service: events.amazonaws.com` as the principal. **Most Voted**

Correct Answer: D

Question #106

A company is preparing to store confidential data in Amazon S3. For compliance reasons, the data must be encrypted at rest. Encryption key usage must be logged for auditing purposes. Keys must be rotated every year. Which solution meets these requirements and is the MOST operationally efficient?

- A. Server-side encryption with customer-provided keys (SSE-C)
- B. Server-side encryption with Amazon S3 managed keys (SSE-S3)
- C. Server-side encryption with AWS KMS keys (SSE-KMS) with manual rotation
- D. Server-side encryption with AWS KMS keys (SSE-KMS) with automatic rotation **Most Voted**

Correct Answer: D

Question #107

A bicycle sharing company is developing a multi-tier architecture to track the location of its bicycles during peak operating hours. The company wants to use these data points in its existing analytics platform. A solutions architect must determine the most viable multi-tier option to support this architecture. The data points must be accessible from the REST API.

Which action meets these requirements for storing and retrieving location data?

- A. Use Amazon Athena with Amazon S3.
- B. Use Amazon API Gateway with AWS Lambda. **Most Voted**
- C. Use Amazon QuickSight with Amazon Redshift.
- D. Use Amazon API Gateway with Amazon Kinesis Data Analytics.

Correct Answer: B

Question #108

A company has an automobile sales website that stores its listings in a database on Amazon RDS. When an automobile is sold, the listing needs to be removed from the website and the data must be sent to multiple target

systems.

Which design should a solutions architect recommend?

- A. Create an AWS Lambda function triggered when the database on Amazon RDS is updated to send the information to an Amazon Simple Queue Service (Amazon SQS) queue for the targets to consume. **Most Voted**
- B. Create an AWS Lambda function triggered when the database on Amazon RDS is updated to send the information to an Amazon Simple Queue Service (Amazon SQS) FIFO queue for the targets to consume.
- C. Subscribe to an RDS event notification and send an Amazon Simple Queue Service (Amazon SQS) queue fanned out to multiple Amazon Simple Notification Service (Amazon SNS) topics. Use AWS Lambda functions to update the targets.
- D. Subscribe to an RDS event notification and send an Amazon Simple Notification Service (Amazon SNS) topic fanned out to multiple Amazon Simple Queue Service (Amazon SQS) queues. Use AWS Lambda functions to update the targets.

Correct Answer: A

Question #109

A company needs to store data in Amazon S3 and must prevent the data from being changed. The company wants new objects that are uploaded to Amazon S3 to remain unchangeable for a nonspecific amount of time until the company decides to modify the objects. Only specific users in the company's AWS account can have the ability to delete the objects.

What should a solutions architect do to meet these requirements?

- A. Create an S3 Glacier vault. Apply a write-once, read-many (WORM) vault lock policy to the objects.
- B. Create an S3 bucket with S3 Object Lock enabled. Enable versioning. Set a retention period of 100 years. Use governance mode as the S3 bucket's default retention mode for new objects.
- C. Create an S3 bucket. Use AWS CloudTrail to track any S3 API events that modify the objects. Upon notification, restore the modified objects from any backup versions that the company has.
- D. Create an S3 bucket with S3 Object Lock enabled. Enable versioning. Add a legal hold to the objects. Add the s3:PutObjectLegalHold permission to the IAM policies of users who need to delete the objects. **Most Voted**

Correct Answer: D

Question #110

A social media company allows users to upload images to its website. The website runs on Amazon EC2 instances. During upload requests, the website resizes the images to a standard size and stores the resized images in Amazon S3. Users are experiencing slow upload requests to the website.

The company needs to reduce coupling within the application and improve website performance. A solutions architect must design the most operationally efficient process for image uploads.

Which combination of actions should the solutions architect take to meet these requirements? (Choose two.)

- A. Configure the application to upload images to S3 Glacier.
- B. Configure the web server to upload the original images to Amazon S3. **Most Voted**
- C. Configure the application to upload images directly from each user's browser to Amazon S3 through the use of a presigned URL **Most Voted**
- D. Configure S3 Event Notifications to invoke an AWS Lambda function when an image is uploaded. Use the function to resize the image. **Most VotedMost Voted**
- E. Create an Amazon EventBridge (Amazon CloudWatch Events) rule that invokes an AWS Lambda function on a schedule to resize uploaded images.

Correct Answer: BD

Question #111

A company recently migrated a message processing system to AWS. The system receives messages into an ActiveMQ queue running on an Amazon EC2 instance. Messages are processed by a consumer application running on Amazon EC2. The consumer application processes the messages and writes results to a MySQL database running on Amazon EC2. The company wants this application to be highly available with low operational complexity.

Which architecture offers the HIGHEST availability?

- A. Add a second ActiveMQ server to another Availability Zone. Add an additional consumer EC2 instance in another Availability Zone. Replicate the MySQL database to another Availability Zone.
- B. Use Amazon MQ with active/standby brokers configured across two Availability Zones. Add an additional consumer EC2 instance in another Availability Zone. Replicate the MySQL database to another Availability Zone.
- C. Use Amazon MQ with active/standby brokers configured across two Availability Zones. Add an additional consumer EC2 instance in another Availability Zone. Use Amazon RDS for MySQL with Multi-AZ enabled.
- D. Use Amazon MQ with active/standby brokers configured across two Availability Zones. Add an Auto Scaling group for the consumer EC2 instances across two Availability Zones. Use Amazon RDS for MySQL with Multi-AZ enabled. **Most Voted**

Correct Answer: D

Question #112

A company hosts a containerized web application on a fleet of on-premises servers that process incoming requests. The number of requests is growing quickly. The on-premises servers cannot handle the increased number of requests. The company wants to move the application to AWS with minimum code changes and minimum development effort.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Fargate on Amazon Elastic Container Service (Amazon ECS) to run the containerized web application with Service Auto Scaling. Use an Application Load Balancer to distribute the incoming requests. **Most Voted**

- B. Use two Amazon EC2 instances to host the containerized web application. Use an Application Load Balancer to distribute the incoming requests.
- C. Use AWS Lambda with a new code that uses one of the supported languages. Create multiple Lambda functions to support the load. Use Amazon API Gateway as an entry point to the Lambda functions.
- D. Use a high performance computing (HPC) solution such as AWS ParallelCluster to establish an HPC cluster that can process the incoming requests at the appropriate scale.

Correct Answer: A

Question #113

A company uses 50 TB of data for reporting. The company wants to move this data from on premises to AWS. A custom application in the company's data center runs a weekly data transformation job. The company plans to pause the application until the data transfer is complete and needs to begin the transfer process as soon as possible.

The data center does not have any available network bandwidth for additional workloads. A solutions architect must transfer the data and must configure the transformation job to continue to run in the AWS Cloud.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS DataSync to move the data. Create a custom transformation job by using AWS Glue.
- B. Order an AWS Snowcone device to move the data. Deploy the transformation application to the device.
- C. Order an AWS Snowball Edge Storage Optimized device. Copy the data to the device. Create a custom transformation job by using AWS Glue. **Most Voted**
- D. Order an AWS Snowball Edge Storage Optimized device that includes Amazon EC2 compute. Copy the data to the device. Create a new EC2 instance on AWS to run the transformation application.

Correct Answer: C

Question #114

A company has created an image analysis application in which users can upload photos and add photo frames to their images. The users upload images and metadata to indicate which photo frames they want to add to their images. The application uses a single Amazon EC2 instance and Amazon DynamoDB to store the metadata. The application is becoming more popular, and the number of users is increasing. The company expects the number of concurrent users to vary significantly depending on the time of day and day of week. The company must ensure that the application can scale to meet the needs of the growing user base.

Which solution meets these requirements?

- A. Use AWS Lambda to process the photos. Store the photos and metadata in DynamoDB.
- B. Use Amazon Kinesis Data Firehose to process the photos and to store the photos and metadata.
- C. Use AWS Lambda to process the photos. Store the photos in Amazon S3. Retain DynamoDB to store the metadata. **Most Voted**

- D. Increase the number of EC2 instances to three. Use Provisioned IOPS SSD (io2) Amazon Elastic Block Store (Amazon EBS) volumes to store the photos and metadata.

Correct Answer: C

Question #115

A medical records company is hosting an application on Amazon EC2 instances. The application processes customer data files that are stored on Amazon S3. The EC2 instances are hosted in public subnets. The EC2 instances access Amazon S3 over the internet, but they do not require any other network access.

A new requirement mandates that the network traffic for file transfers take a private route and not be sent over the internet.

Which change to the network architecture should a solutions architect recommend to meet this requirement?

- A. Create a NAT gateway. Configure the route table for the public subnets to send traffic to Amazon S3 through the NAT gateway.
- B. Configure the security group for the EC2 instances to restrict outbound traffic so that only traffic to the S3 prefix list is permitted.
- C. Move the EC2 instances to private subnets. Create a VPC endpoint for Amazon S3, and link the endpoint to the route table for the private subnets. **Most Voted**
- D. Remove the internet gateway from the VPC. Set up an AWS Direct Connect connection, and route traffic to Amazon S3 over the Direct Connect connection.

Correct Answer: C

Question #116

A company uses a popular content management system (CMS) for its corporate website. However, the required patching and maintenance are burdensome. The company is redesigning its website and wants a new solution.

The website will be updated four times a year and does not need to have any dynamic content available. The solution must provide high scalability and enhanced security.

Which combination of changes will meet these requirements with the LEAST operational overhead? (Choose two.)

- A. Configure Amazon CloudFront in front of the website to use HTTPS functionality. **Most Voted**
- B. Deploy an AWS WAF web ACL in front of the website to provide HTTPS functionality.
- C. Create and deploy an AWS Lambda function to manage and serve the website content.

- D. Create the new website and an Amazon S3 bucket. Deploy the website on the S3 bucket with static website hosting enabled. **Most Voted**
- E. Create the new website. Deploy the website by using an Auto Scaling group of Amazon EC2 instances behind an Application Load Balancer.

Correct Answer: AD

Question #117

A company stores its application logs in an Amazon CloudWatch Logs log group. A new policy requires the company to store all application logs in Amazon OpenSearch Service (Amazon Elasticsearch Service) in near-real time.

Which solution will meet this requirement with the LEAST operational overhead?

- A. Configure a CloudWatch Logs subscription to stream the logs to Amazon OpenSearch Service (Amazon Elasticsearch Service). **Most Voted**
- B. Create an AWS Lambda function. Use the log group to invoke the function to write the logs to Amazon OpenSearch Service (Amazon Elasticsearch Service).
- C. Create an Amazon Kinesis Data Firehose delivery stream. Configure the log group as the delivery stream's source. Configure Amazon OpenSearch Service (Amazon Elasticsearch Service) as the delivery stream's destination.
- D. Install and configure Amazon Kinesis Agent on each application server to deliver the logs to Amazon Kinesis Data Streams. Configure Kinesis Data Streams to deliver the logs to Amazon OpenSearch Service (Amazon Elasticsearch Service).

Correct Answer: A

Question #118

A company is building a web-based application running on Amazon EC2 instances in multiple Availability Zones. The web application will provide access to a repository of text documents totaling about 900 TB in size. The company anticipates that the web application will experience periods of high demand. A solutions architect must ensure that the storage component for the text documents can scale to meet the demand of the application at all

times. The company is concerned about the overall cost of the solution.
Which storage solution meets these requirements MOST cost-effectively?

- A. Amazon Elastic Block Store (Amazon EBS)
- B. Amazon Elastic File System (Amazon EFS)
- C. Amazon OpenSearch Service (Amazon Elasticsearch Service)
- D. Amazon S3 **Most Voted**

Correct Answer: D

Question #119

A global company is using Amazon API Gateway to design REST APIs for its loyalty club users in the us-east-1 Region and the ap-southeast-2 Region. A solutions architect must design a solution to protect these API Gateway managed REST APIs across multiple accounts from SQL injection and cross-site scripting attacks. Which solution will meet these requirements with the LEAST amount of administrative effort?

- A. Set up AWS WAF in both Regions. Associate Regional web ACLs with an API stage.
- B. Set up AWS Firewall Manager in both Regions. Centrally configure AWS WAF rules. **Most Voted**
- C. Set up AWS Shield in both Regions. Associate Regional web ACLs with an API stage.
- D. Set up AWS Shield in one of the Regions. Associate Regional web ACLs with an API stage.

Correct Answer: B

Question #120

A company has implemented a self-managed DNS solution on three Amazon EC2 instances behind a Network Load Balancer (NLB) in the us-west-2 Region. Most of the company's users are located in the United States and Europe. The company wants to improve the performance and availability of the solution. The company launches and configures three EC2 instances in the eu-west-1 Region and adds the EC2 instances as targets for a new NLB.

Which solution can the company use to route traffic to all the EC2 instances?

- A. Create an Amazon Route 53 geolocation routing policy to route requests to one of the two NLBs. Create an Amazon CloudFront distribution. Use the Route 53 record as the distribution's origin.
- B. Create a standard accelerator in AWS Global Accelerator. Create endpoint groups in us-west-2 and eu-west-1. Add the two NLBs as endpoints for the endpoint groups. **Most Voted**
- C. Attach Elastic IP addresses to the six EC2 instances. Create an Amazon Route 53 geolocation routing policy to route requests to one of the six EC2 instances. Create an Amazon CloudFront distribution. Use the Route 53 record as the distribution's origin.
- D. Replace the two NLBs with two Application Load Balancers (ALBs). Create an Amazon Route 53 latency routing policy to route requests to one of the two ALBs. Create an Amazon CloudFront distribution. Use the Route 53 record as the distribution's origin.

Correct Answer: B

Question #121

A company is running an online transaction processing (OLTP) workload on AWS. This workload uses an unencrypted Amazon RDS DB instance in a Multi-AZ deployment. Daily database snapshots are taken from this instance.

What should a solutions architect do to ensure the database and snapshots are always encrypted moving forward?

- A. Encrypt a copy of the latest DB snapshot. Replace existing DB instance by restoring the encrypted snapshot. **Most Voted**
- B. Create a new encrypted Amazon Elastic Block Store (Amazon EBS) volume and copy the snapshots to it. Enable encryption on the DB instance.
- C. Copy the snapshots and enable encryption using AWS Key Management Service (AWS KMS) Restore encrypted snapshot to an existing DB instance.
- D. Copy the snapshots to an Amazon S3 bucket that is encrypted using server-side encryption with AWS Key Management Service (AWS KMS) managed keys (SSE-KMS).

Correct Answer: A

Question #122

A company wants to build a scalable key management infrastructure to support developers who need to encrypt data in their applications.

What should a solutions architect do to reduce the operational burden?

- A. Use multi-factor authentication (MFA) to protect the encryption keys.
- B. Use AWS Key Management Service (AWS KMS) to protect the encryption keys. **Most Voted**
- C. Use AWS Certificate Manager (ACM) to create, store, and assign the encryption keys.
- D. Use an IAM policy to limit the scope of users who have access permissions to protect the encryption keys.

Correct Answer: B

Question #123

A company has a dynamic web application hosted on two Amazon EC2 instances. The company has its own SSL certificate, which is on each instance to perform SSL termination.

There has been an increase in traffic recently, and the operations team determined that SSL encryption and decryption is causing the compute capacity of the web servers to reach their maximum limit.

What should a solutions architect do to increase the application's performance?

- A. Create a new SSL certificate using AWS Certificate Manager (ACM). Install the ACM certificate on each instance.
- B. Create an Amazon S3 bucket. Migrate the SSL certificate to the S3 bucket. Configure the EC2 instances to reference the bucket for SSL termination.
- C. Create another EC2 instance as a proxy server. Migrate the SSL certificate to the new instance and configure it to direct connections to the existing EC2 instances.
- D. Import the SSL certificate into AWS Certificate Manager (ACM). Create an Application Load Balancer with an HTTPS listener that uses the SSL certificate from ACM. **Most Voted**

Correct Answer: D

Question #124

A company has a highly dynamic batch processing job that uses many Amazon EC2 instances to complete it. The job is stateless in nature, can be started and stopped at any given time with no negative impact, and typically takes upwards of 60 minutes total to complete. The company has asked a solutions architect to design a scalable and cost-effective solution that meets the requirements of the job. What should the solutions architect recommend?

- A. Implement EC2 Spot Instances. **Most Voted**
- B. Purchase EC2 Reserved Instances.
- C. Implement EC2 On-Demand Instances.
- D. Implement the processing on AWS Lambda.

Correct Answer: A

Question #125

A company runs its two-tier ecommerce website on AWS. The web tier consists of a load balancer that sends traffic to Amazon EC2 instances. The database tier uses an Amazon RDS DB instance. The EC2 instances and the RDS DB instance should not be exposed to the public internet. The EC2 instances require internet access to complete payment processing of orders through a third-party web service. The application must be highly available.

Which combination of configuration options will meet these requirements? (Choose two.)

- A. Use an Auto Scaling group to launch the EC2 instances in private subnets. Deploy an RDS Multi-AZ DB instance in private subnets. **Most VotedMost Voted**
- B. Configure a VPC with two private subnets and two NAT gateways across two Availability Zones. Deploy an Application Load Balancer in the private subnets.
- C. Use an Auto Scaling group to launch the EC2 instances in public subnets across two Availability Zones. Deploy an RDS Multi-AZ DB instance in private subnets.
- D. Configure a VPC with one public subnet, one private subnet, and two NAT gateways across two Availability Zones. Deploy an Application Load Balancer in the public subnet.
- D. Configure a VPC with two public subnets, two private subnets, and two NAT gateways across two Availability Zones. Deploy an Application Load Balancer in the public subnets. **Most Voted**

Correct Answer: AD

Question #126

A solutions architect needs to implement a solution to reduce a company's storage costs. All the company's data is in the Amazon S3 Standard storage class. The company must keep all data for at least 25 years. Data from the most recent 2 years must be highly available and immediately retrievable.

Which solution will meet these requirements?

- A. Set up an S3 Lifecycle policy to transition objects to S3 Glacier Deep Archive immediately.
- B. Set up an S3 Lifecycle policy to transition objects to S3 Glacier Deep Archive after 2 years. **Most Voted**
- C. Use S3 Intelligent-Tiering. Activate the archiving option to ensure that data is archived in S3 Glacier Deep Archive.
- D. Set up an S3 Lifecycle policy to transition objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) immediately and to S3 Glacier Deep Archive after 2 years.

Correct Answer: B

Question #127

A media company is evaluating the possibility of moving its systems to the AWS Cloud. The company needs at least 10 TB of storage with the maximum possible I/O performance for video processing, 300 TB of very durable storage for storing media content, and 900 TB of storage to meet requirements for archival media that is not in use anymore.

Which set of services should a solutions architect recommend to meet these requirements?

- A. Amazon EBS for maximum performance, Amazon S3 for durable data storage, and Amazon S3 Glacier for archival storage
- B. Amazon EBS for maximum performance, Amazon EFS for durable data storage, and Amazon S3 Glacier for archival storage
- C. Amazon EC2 instance store for maximum performance, Amazon EFS for durable data storage, and Amazon S3 for archival storage
- D. Amazon EC2 instance store for maximum performance, Amazon S3 for durable data storage, and Amazon S3 Glacier for archival storage **Most Voted**

Correct Answer: D

Question #128

A company wants to run applications in containers in the AWS Cloud. These applications are stateless and can tolerate disruptions within the underlying infrastructure. The company needs a solution that minimizes cost and operational overhead.

What should a solutions architect do to meet these requirements?

- A. Use Spot Instances in an Amazon EC2 Auto Scaling group to run the application containers.
- B. Use Spot Instances in an Amazon Elastic Kubernetes Service (Amazon EKS) managed node group. **Most Voted**
- C. Use On-Demand Instances in an Amazon EC2 Auto Scaling group to run the application containers.
- D. Use On-Demand Instances in an Amazon Elastic Kubernetes Service (Amazon EKS) managed node group.

Correct Answer: B

Question #129

A company is running a multi-tier web application on premises. The web application is containerized and runs on a number of Linux hosts connected to a PostgreSQL database that contains user records. The operational overhead of maintaining the infrastructure and capacity planning is limiting the company's growth. A solutions architect must improve the application's infrastructure.

Which combination of actions should the solutions architect take to accomplish this? (Choose two.)

- A. Migrate the PostgreSQL database to Amazon Aurora. **Most Voted**
- B. Migrate the web application to be hosted on Amazon EC2 instances.
- C. Set up an Amazon CloudFront distribution for the web application content.
- D. Set up Amazon ElastiCache between the web application and the PostgreSQL database.
- E. Migrate the web application to be hosted on AWS Fargate with Amazon Elastic Container Service (Amazon ECS). **Most Voted**

Correct Answer: AE

Question #130

An application runs on Amazon EC2 instances across multiple Availability Zones. The instances run in an Amazon EC2 Auto Scaling group behind an Application Load Balancer. The application performs best when the CPU utilization of the EC2 instances is at or near 40%.

What should a solutions architect do to maintain the desired performance across all instances in the group?

- A. Use a simple scaling policy to dynamically scale the Auto Scaling group.
- B. Use a target tracking policy to dynamically scale the Auto Scaling group. **Most Voted**
- C. Use an AWS Lambda function to update the desired Auto Scaling group capacity.
- D. Use scheduled scaling actions to scale up and scale down the Auto Scaling group.

Correct Answer: B

Question #131

A company is developing a file-sharing application that will use an Amazon S3 bucket for storage. The company wants to serve all the files through an Amazon CloudFront distribution. The company does not want the files to be accessible through direct navigation to the S3 URL.

What should a solutions architect do to meet these requirements?

- A. Write individual policies for each S3 bucket to grant read permission for only CloudFront access.
- B. Create an IAM user. Grant the user read permission to objects in the S3 bucket. Assign the user to CloudFront.
- C. Write an S3 bucket policy that assigns the CloudFront distribution ID as the Principal and assigns the target S3 bucket as the Amazon Resource Name (ARN).
- D. Create an origin access identity (OAI). Assign the OAI to the CloudFront distribution. Configure the S3 bucket permissions so that only the OAI has read permission. **Most Voted**

Correct Answer: D

Question #132

A company's website provides users with downloadable historical performance reports. The website needs a solution that will scale to meet the company's website demands globally. The solution should be cost-effective, limit the provisioning of infrastructure resources, and provide the fastest possible response time. Which combination should a solutions architect recommend to meet these requirements?

- A. Amazon CloudFront and Amazon S3 **Most Voted**
- B. AWS Lambda and Amazon DynamoDB
- C. Application Load Balancer with Amazon EC2 Auto Scaling
- D. Amazon Route 53 with internal Application Load Balancers

Correct Answer: A

Question #133

A company runs an Oracle database on premises. As part of the company's migration to AWS, the company wants to upgrade the database to the most recent available version. The company also wants to set up disaster recovery (DR) for the database. The company needs to minimize the operational overhead for normal operations and DR setup. The company also needs to maintain access to the database's underlying operating system. Which solution will meet these requirements?

- A. Migrate the Oracle database to an Amazon EC2 instance. Set up database replication to a different AWS Region.
- B. Migrate the Oracle database to Amazon RDS for Oracle. Activate Cross-Region automated backups to replicate the snapshots to another AWS Region.
- C. Migrate the Oracle database to Amazon RDS Custom for Oracle. Create a read replica for the database in another AWS Region. **Most Voted**
- D. Migrate the Oracle database to Amazon RDS for Oracle. Create a standby database in another Availability Zone.

Correct Answer: C

Question #134

A company wants to move its application to a serverless solution. The serverless solution needs to analyze existing and new data by using SL. The company stores the data in an Amazon S3 bucket. The data requires encryption and must be replicated to a different AWS Region. Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a new S3 bucket. Load the data into the new S3 bucket. Use S3 Cross-Region Replication (CRR) to replicate encrypted objects to an S3 bucket in another Region. Use server-side encryption with AWS KMS multi-Region keys (SSE-KMS). Use Amazon Athena to query the data. **Most Voted**
- B. Create a new S3 bucket. Load the data into the new S3 bucket. Use S3 Cross-Region Replication (CRR) to replicate encrypted objects to an S3 bucket in another Region. Use server-side encryption with AWS KMS multi-Region keys (SSE-KMS). Use Amazon RDS to query the data.
- C. Load the data into the existing S3 bucket. Use S3 Cross-Region Replication (CRR) to replicate encrypted objects to an S3 bucket in another Region. Use server-side encryption with Amazon S3 managed encryption keys (SSE-S3). Use Amazon Athena to query the data.
- D. Load the data into the existing S3 bucket. Use S3 Cross-Region Replication (CRR) to replicate encrypted objects to an S3 bucket in another Region. Use server-side encryption with Amazon S3 managed encryption keys (SSE-S3). Use Amazon RDS to query the data.

Correct Answer: A

Question #135

A company runs workloads on AWS. The company needs to connect to a service from an external provider. The service is hosted in the provider's VPC. According to the company's security team, the connectivity must be private and must be restricted to the target service. The connection must be initiated only from the company's VPC.

Which solution will mast these requirements?

- A. Create a VPC peering connection between the company's VPC and the provider's VPC. Update the route table to connect to the target service.
- B. Ask the provider to create a virtual private gateway in its VPC. Use AWS PrivateLink to connect to the target service.

- C. Create a NAT gateway in a public subnet of the company's VPC. Update the route table to connect to the target service.
- D. Ask the provider to create a VPC endpoint for the target service. Use AWS PrivateLink to connect to the target service. **Most Voted**

Correct Answer: D

Question #136

A company is migrating its on-premises PostgreSQL database to Amazon Aurora PostgreSQL. The on-premises database must remain online and accessible during the migration. The Aurora database must remain synchronized with the on-premises database.

Which combination of actions must a solutions architect take to meet these requirements? (Choose two.)

- A. Create an ongoing replication task. **Most Voted**
- B. Create a database backup of the on-premises database.
- C. Create an AWS Database Migration Service (AWS DMS) replication server. **Most Voted**
- D. Convert the database schema by using the AWS Schema Conversion Tool (AWS SCT).
- E. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to monitor the database synchronization.

Correct Answer: AC

Question #137

A company uses AWS Organizations to create dedicated AWS accounts for each business unit to manage each business unit's account independently upon request. The root email recipient missed a notification that was sent to the root user email address of one account. The company wants to ensure that all future notifications are not missed. Future notifications must be limited to account administrators.

Which solution will meet these requirements?

- A. Configure the company's email server to forward notification email messages that are sent to the AWS account root user email address to all users in the organization.

- B. Configure all AWS account root user email addresses as distribution lists that go to a few administrators who can respond to alerts. Configure AWS account alternate contacts in the AWS Organizations console or programmatically. **Most Voted**
- C. Configure all AWS account root user email messages to be sent to one administrator who is responsible for monitoring alerts and forwarding those alerts to the appropriate groups.
- D. Configure all existing AWS accounts and all newly created accounts to use the same root user email address. Configure AWS account alternate contacts in the AWS Organizations console or programmatically.

Correct Answer: B

Question #138

A company runs its ecommerce application on AWS. Every new order is published as a message in a RabbitMQ queue that runs on an Amazon EC2 instance in a single Availability Zone. These messages are processed by a different application that runs on a separate EC2 instance. This application stores the details in a PostgreSQL database on another EC2 instance. All the EC2 instances are in the same Availability Zone.

The company needs to redesign its architecture to provide the highest availability with the least operational overhead.

What should a solutions architect do to meet these requirements?

- A. Migrate the queue to a redundant pair (active/standby) of RabbitMQ instances on Amazon MQ. Create a Multi-AZ Auto Scaling group for EC2 instances that host the application. Create another Multi-AZ Auto Scaling group for EC2 instances that host the PostgreSQL database.
- B. Migrate the queue to a redundant pair (active/standby) of RabbitMQ instances on Amazon MQ. Create a Multi-AZ Auto Scaling group for EC2 instances that host the application. Migrate the database to run on a Multi-AZ deployment of Amazon RDS for PostgreSQL. **Most Voted**
- C. Create a Multi-AZ Auto Scaling group for EC2 instances that host the RabbitMQ queue. Create another Multi-AZ Auto Scaling group for EC2 instances that host the application. Migrate the database to run on a Multi-AZ deployment of Amazon RDS for PostgreSQL.
- D. Create a Multi-AZ Auto Scaling group for EC2 instances that host the RabbitMQ queue. Create another Multi-AZ Auto Scaling group for EC2 instances that host the application. Create a third Multi-AZ Auto Scaling group for EC2 instances that host the PostgreSQL database

Correct Answer: B

Question #139

A reporting team receives files each day in an Amazon S3 bucket. The reporting team manually reviews and copies the files from this initial S3 bucket to an analysis S3 bucket each day at the same time to use with Amazon QuickSight. Additional teams are starting to send more files in larger sizes to the initial S3 bucket. The reporting team wants to move the files automatically analysis S3 bucket as the files enter the initial S3 bucket. The reporting team also wants to use AWS Lambda functions to run pattern-matching code on the copied data. In addition, the reporting team wants to send the data files to a pipeline in Amazon SageMaker Pipelines.

What should a solutions architect do to meet these requirements with the LEAST operational overhead?

- A. Create a Lambda function to copy the files to the analysis S3 bucket. Create an S3 event notification for the analysis S3 bucket. Configure Lambda and SageMaker Pipelines as destinations of the event notification. Configure s3:ObjectCreated:Put as the event type.
- B. Create a Lambda function to copy the files to the analysis S3 bucket. Configure the analysis S3 bucket to send event notifications to Amazon EventBridge (Amazon CloudWatch Events). Configure an ObjectCreated rule in EventBridge (CloudWatch Events). Configure Lambda and SageMaker Pipelines as targets for the rule.
- C. Configure S3 replication between the S3 buckets. Create an S3 event notification for the analysis S3 bucket. Configure Lambda and SageMaker Pipelines as destinations of the event notification. Configure s3:ObjectCreated:Put as the event type.
- D. Configure S3 replication between the S3 buckets. Configure the analysis S3 bucket to send event notifications to Amazon EventBridge (Amazon CloudWatch Events). Configure an ObjectCreated rule in EventBridge (CloudWatch Events). Configure Lambda and SageMaker Pipelines as targets for the rule. **Most Voted**

Correct Answer: D

Question #140

A solutions architect needs to help a company optimize the cost of running an application on AWS. The application will use Amazon EC2 instances, AWS Fargate, and AWS Lambda for compute within the architecture.

The EC2 instances will run the data ingestion layer of the application. EC2 usage will be sporadic and unpredictable. Workloads that run on EC2 instances can be interrupted at any time. The application front end will run on Fargate, and Lambda will serve the API layer. The front-end utilization and API layer utilization will be predictable over the course of the next year.

Which combination of purchasing options will provide the MOST cost-effective solution for hosting this application? (Choose two.)

- A. Use Spot Instances for the data ingestion layer **Most Voted**
- B. Use On-Demand Instances for the data ingestion layer
- C. Purchase a 1-year Compute Savings Plan for the front end and API layer. **Most Voted**
- D. Purchase 1-year All Upfront Reserved instances for the data ingestion layer.
- E. Purchase a 1-year EC2 instance Savings Plan for the front end and API layer.

Correct Answer: AC

Question #141

A company runs a web-based portal that provides users with global breaking news, local alerts, and weather updates. The portal delivers each user a personalized view by using mixture of static and dynamic content. Content is served over HTTPS through an API server running on an Amazon EC2 instance behind an Application Load Balancer (ALB). The company wants the portal to provide this content to its users across the world as quickly as possible.

How should a solutions architect design the application to ensure the LEAST amount of latency for all users?

- A. Deploy the application stack in a single AWS Region. Use Amazon CloudFront to serve all static and dynamic content by specifying the ALB as an origin. **Most Voted**
- B. Deploy the application stack in two AWS Regions. Use an Amazon Route 53 latency routing policy to serve all content from the ALB in the closest Region.
- C. Deploy the application stack in a single AWS Region. Use Amazon CloudFront to serve the static content. Serve the dynamic content directly from the ALB.
- D. Deploy the application stack in two AWS Regions. Use an Amazon Route 53 geolocation routing policy to serve all content from the ALB in the closest Region.

Correct Answer: A

Question #142

A gaming company is designing a highly available architecture. The application runs on a modified Linux kernel and supports only UDP-based traffic. The company needs the front-end tier to provide the best possible user experience. That tier must have low latency, route traffic to the nearest edge location, and provide static IP addresses for entry into the application endpoints.

What should a solutions architect do to meet these requirements?

- A. Configure Amazon Route 53 to forward requests to an Application Load Balancer. Use AWS Lambda for the application in AWS Application Auto Scaling.
- B. Configure Amazon CloudFront to forward requests to a Network Load Balancer. Use AWS Lambda for the application in an AWS Application Auto Scaling group.
- C. Configure AWS Global Accelerator to forward requests to a Network Load Balancer. Use Amazon EC2 instances for the application in an EC2 Auto Scaling group. **Most Voted**
- D. Configure Amazon API Gateway to forward requests to an Application Load Balancer. Use Amazon EC2 instances for the application in an EC2 Auto Scaling group.

Correct Answer: C

Question #143

A company wants to migrate its existing on-premises monolithic application to AWS. The company wants to keep as much of the front-end code and the backend code as possible. However, the company wants to break the application into smaller applications. A different team will manage each application. The company needs a highly scalable solution that minimizes operational overhead.

Which solution will meet these requirements?

- A. Host the application on AWS Lambda. Integrate the application with Amazon API Gateway.
- B. Host the application with AWS Amplify. Connect the application to an Amazon API Gateway API that is integrated with AWS Lambda.
- C. Host the application on Amazon EC2 instances. Set up an Application Load Balancer with EC2 instances in an Auto Scaling group as targets.

- D. Host the application on Amazon Elastic Container Service (Amazon ECS). Set up an Application Load Balancer with Amazon ECS as the target. **Most Voted**

Correct Answer: D

Question #144

A company recently started using Amazon Aurora as the data store for its global ecommerce application. When large reports are run, developers report that the ecommerce application is performing poorly. After reviewing metrics in Amazon CloudWatch, a solutions architect finds that the ReadIOPS and CPUUtilization metrics are spiking when monthly reports run.

What is the MOST cost-effective solution?

- A. Migrate the monthly reporting to Amazon Redshift.
- B. Migrate the monthly reporting to an Aurora Replica. **Most Voted**
- C. Migrate the Aurora database to a larger instance class.
- D. Increase the Provisioned IOPS on the Aurora instance.

Correct Answer: B

Question #145

A company hosts a website analytics application on a single Amazon EC2 On-Demand Instance. The analytics software is written in PHP and uses a MySQL database. The analytics software, the web server that provides PHP, and the database server are all hosted on the EC2 instance. The application is showing signs of performance degradation during busy times and is presenting 5xx errors. The company needs to make the application scale seamlessly.

Which solution will meet these requirements MOST cost-effectively?

- A. Migrate the database to an Amazon RDS for MySQL DB instance. Create an AMI of the web application. Use the AMI to launch a second EC2 On-Demand Instance. Use an Application Load Balancer to distribute the load to each EC2 instance.

- B. Migrate the database to an Amazon RDS for MySQL DB instance. Create an AMI of the web application. Use the AMI to launch a second EC2 On-Demand Instance. Use Amazon Route 53 weighted routing to distribute the load across the two EC2 instances.
- C. Migrate the database to an Amazon Aurora MySQL DB instance. Create an AWS Lambda function to stop the EC2 instance and change the instance type. Create an Amazon CloudWatch alarm to invoke the Lambda function when CPU utilization surpasses 75%.
- D. Migrate the database to an Amazon Aurora MySQL DB instance. Create an AMI of the web application. Apply the AMI to a launch template. Create an Auto Scaling group with the launch template. Configure the launch template to use a Spot Fleet. Attach an Application Load Balancer to the Auto Scaling group. **Most Voted**

Correct Answer: D

Question #146

A company runs a stateless web application in production on a group of Amazon EC2 On-Demand Instances behind an Application Load Balancer. The application experiences heavy usage during an 8-hour period each business day. Application usage is moderate and steady overnight. Application usage is low during weekends. The company wants to minimize its EC2 costs without affecting the availability of the application. Which solution will meet these requirements?

- A. Use Spot Instances for the entire workload.
- B. Use Reserved Instances for the baseline level of usage. Use Spot instances for any additional capacity that the application needs. **Most Voted**
- C. Use On-Demand Instances for the baseline level of usage. Use Spot Instances for any additional capacity that the application needs.
- D. Use Dedicated Instances for the baseline level of usage. Use On-Demand Instances for any additional capacity that the application needs.

Correct Answer: B

Question #147

A company needs to retain application log files for a critical application for 10 years. The application team regularly accesses logs from the past month for troubleshooting, but logs older than 1 month are rarely

accessed. The application generates more than 10 TB of logs per month.
Which storage option meets these requirements MOST cost-effectively?

- A. Store the logs in Amazon S3. Use AWS Backup to move logs more than 1 month old to S3 Glacier Deep Archive.
- B. Store the logs in Amazon S3. Use S3 Lifecycle policies to move logs more than 1 month old to S3 Glacier Deep Archive. **Most Voted**
- C. Store the logs in Amazon CloudWatch Logs. Use AWS Backup to move logs more than 1 month old to S3 Glacier Deep Archive.
- D. Store the logs in Amazon CloudWatch Logs. Use Amazon S3 Lifecycle policies to move logs more than 1 month old to S3 Glacier Deep Archive.

Correct Answer: B

Question #148

A company has a data ingestion workflow that includes the following components:

An Amazon Simple Notification Service (Amazon SNS) topic that receives notifications about new data deliveries

An AWS Lambda function that processes and stores the data

The ingestion workflow occasionally fails because of network connectivity issues. When failure occurs, the corresponding data is not ingested unless the company manually reruns the job.

What should a solutions architect do to ensure that all notifications are eventually processed?

- A. Configure the Lambda function for deployment across multiple Availability Zones.
- B. Modify the Lambda function's configuration to increase the CPU and memory allocations for the function.
- C. Configure the SNS topic's retry strategy to increase both the number of retries and the wait time between retries.
- D. Configure an Amazon Simple Queue Service (Amazon SQS) queue as the on-failure destination. Modify the Lambda function to process messages in the queue. **Most Voted**

Correct Answer: D

Question #149

A company has a service that produces event data. The company wants to use AWS to process the event data as it is received. The data is written in a specific order that must be maintained throughout processing. The company wants to implement a solution that minimizes operational overhead. How should a solutions architect accomplish this?

- A. Create an Amazon Simple Queue Service (Amazon SQS) FIFO queue to hold messages. Set up an AWS Lambda function to process messages from the queue. **Most Voted**
- B. Create an Amazon Simple Notification Service (Amazon SNS) topic to deliver notifications containing payloads to process. Configure an AWS Lambda function as a subscriber.
- C. Create an Amazon Simple Queue Service (Amazon SQS) standard queue to hold messages. Set up an AWS Lambda function to process messages from the queue independently.
- D. Create an Amazon Simple Notification Service (Amazon SNS) topic to deliver notifications containing payloads to process. Configure an Amazon Simple Queue Service (Amazon SQS) queue as a subscriber.

Correct Answer: A

Question #150

A company is migrating an application from on-premises servers to Amazon EC2 instances. As part of the migration design requirements, a solutions architect must implement infrastructure metric alarms. The company does not need to take action if CPU utilization increases to more than 50% for a short burst of time. However, if the CPU utilization increases to more than 50% and read IOPS on the disk are high at the same time, the company needs to act as soon as possible. The solutions architect also must reduce false alarms. What should the solutions architect do to meet these requirements?

- A. Create Amazon CloudWatch composite alarms where possible. **Most Voted**
- B. Create Amazon CloudWatch dashboards to visualize the metrics and react to issues quickly.
- C. Create Amazon CloudWatch Synthetics canaries to monitor the application and raise an alarm.
- D. Create single Amazon CloudWatch metric alarms with multiple metric thresholds where possible.

Correct Answer: A

Question #151

A company wants to migrate its on-premises data center to AWS. According to the company's compliance requirements, the company can use only the ap-northeast-3 Region. Company administrators are not permitted to connect VPCs to the internet.

Which solutions will meet these requirements? (Choose two.)

- A. Use AWS Control Tower to implement data residency guardrails to deny internet access and deny access to all AWS Regions except ap-northeast-3. **Most Voted**
- B. Use rules in AWS WAF to prevent internet access. Deny access to all AWS Regions except ap-northeast-3 in the AWS account settings.
- C. Use AWS Organizations to configure service control policies (SCPS) that prevent VPCs from gaining internet access. Deny access to all AWS Regions except ap-northeast-3. **Most Voted**
- D. Create an outbound rule for the network ACL in each VPC to deny all traffic from 0.0.0.0/0. Create an IAM policy for each user to prevent the use of any AWS Region other than ap-northeast-3.
- E. Use AWS Config to activate managed rules to detect and alert for internet gateways and to detect and alert for new resources deployed outside of ap-northeast-3.

Correct Answer: AC

Question #152

A company uses a three-tier web application to provide training to new employees. The application is accessed for only 12 hours every day. The company is using an Amazon RDS for MySQL DB instance to store information and wants to minimize costs.

What should a solutions architect do to meet these requirements?

- A. Configure an IAM policy for AWS Systems Manager Session Manager. Create an IAM role for the policy. Update the trust relationship of the role. Set up automatic start and stop for the DB instance.
- B. Create an Amazon ElastiCache for Redis cache cluster that gives users the ability to access the data from the cache when the DB instance is stopped. Invalidate the cache after the DB instance is started.
- C. Launch an Amazon EC2 instance. Create an IAM role that grants access to Amazon RDS. Attach the role to the EC2 instance. Configure a cron job to start and stop the EC2 instance on the desired schedule.

- D. Create AWS Lambda functions to start and stop the DB instance. Create Amazon EventBridge (Amazon CloudWatch Events) scheduled rules to invoke the Lambda functions. Configure the Lambda functions as event targets for the rules. **Most Voted**

Correct Answer: D

Question #153

A company sells ringtones created from clips of popular songs. The files containing the ringtones are stored in Amazon S3 Standard and are at least 128 KB in size. The company has millions of files, but downloads are infrequent for ringtones older than 90 days. The company needs to save money on storage while keeping the most accessed files readily available for its users.

Which action should the company take to meet these requirements MOST cost-effectively?

- A. Configure S3 Standard-Infrequent Access (S3 Standard-IA) storage for the initial storage tier of the objects.
- B. Move the files to S3 Intelligent-Tiering and configure it to move objects to a less expensive storage tier after 90 days.
- C. Configure S3 inventory to manage objects and move them to S3 Standard-Infrequent Access (S3 Standard-1A) after 90 days.
- D. Implement an S3 Lifecycle policy that moves the objects from S3 Standard to S3 Standard-Infrequent Access (S3 Standard-1A) after 90 days. **Most Voted**

Correct Answer: D

Question #154

A company needs to save the results from a medical trial to an Amazon S3 repository. The repository must allow a few scientists to add new files and must restrict all other users to read-only access. No users can have the ability to modify or delete any files in the repository. The company must keep every file in the repository for a minimum of 1 year after its creation date.

Which solution will meet these requirements?

- A. Use S3 Object Lock in governance mode with a legal hold of 1 year.
- B. Use S3 Object Lock in compliance mode with a retention period of 365 days. **Most Voted**

- C. Use an IAM role to restrict all users from deleting or changing objects in the S3 bucket. Use an S3 bucket policy to only allow the IAM role.
- D. Configure the S3 bucket to invoke an AWS Lambda function every time an object is added. Configure the function to track the hash of the saved object so that modified objects can be marked accordingly.

Correct Answer: B

Question #155

A large media company hosts a web application on AWS. The company wants to start caching confidential media files so that users around the world will have reliable access to the files. The content is stored in Amazon S3 buckets. The company must deliver the content quickly, regardless of where the requests originate geographically.

Which solution will meet these requirements?

- A. Use AWS DataSync to connect the S3 buckets to the web application.
- B. Deploy AWS Global Accelerator to connect the S3 buckets to the web application.
- C. Deploy Amazon CloudFront to connect the S3 buckets to CloudFront edge servers. **Most Voted**
- D. Use Amazon Simple Queue Service (Amazon SQS) to connect the S3 buckets to the web application.

Correct Answer: C

Question #156

A company produces batch data that comes from different databases. The company also produces live stream data from network sensors and application APIs. The company needs to consolidate all the data into one place for business analytics. The company needs to process the incoming data and then stage the data in different Amazon S3 buckets. Teams will later run one-time queries and import the data into a business intelligence tool to show key performance indicators (KPIs).

Which combination of steps will meet these requirements with the LEAST operational overhead? (Choose two.)

- A. Use Amazon Athena for one-time queries. Use Amazon QuickSight to create dashboards for KPIs. **Most Voted**

- B. Use Amazon Kinesis Data Analytics for one-time queries. Use Amazon QuickSight to create dashboards for KPIs.
- C. Create custom AWS Lambda functions to move the individual records from the databases to an Amazon Redshift cluster.
- D. Use an AWS Glue extract, transform, and load (ETL) job to convert the data into JSON format. Load the data into multiple Amazon OpenSearch Service (Amazon Elasticsearch Service) clusters.
- E. Use blueprints in AWS Lake Formation to identify the data that can be ingested into a data lake. Use AWS Glue to crawl the source, extract the data, and load the data into Amazon S3 in Apache Parquet format. **Most Voted**

Correct Answer: AE

Question #157

A company stores data in an Amazon Aurora PostgreSQL DB cluster. The company must store all the data for 5 years and must delete all the data after 5 years. The company also must indefinitely keep audit logs of actions that are performed within the database. Currently, the company has automated backups configured for Aurora.

Which combination of steps should a solutions architect take to meet these requirements? (Choose two.)

- A. Take a manual snapshot of the DB cluster.
- B. Create a lifecycle policy for the automated backups.
- C. Configure automated backup retention for 5 years.
- D. Configure an Amazon CloudWatch Logs export for the DB cluster. **Most VotedMost Voted**
- E. Use AWS Backup to take the backups and to keep the backups for 5 years. **Most Voted**

Correct Answer: DE

Question #158

A solutions architect is optimizing a website for an upcoming musical event. Videos of the performances will be streamed in real time and then will be available on demand. The event is expected to attract a global online audience.

Which service will improve the performance of both the real-time and on-demand streaming?

- A. Amazon CloudFront **Most Voted**
- B. AWS Global Accelerator
- C. Amazon Route 53
- D. Amazon S3 Transfer Acceleration

Correct Answer: A

Question #159

A company is running a publicly accessible serverless application that uses Amazon API Gateway and AWS Lambda. The application's traffic recently spiked due to fraudulent requests from botnets.

Which steps should a solutions architect take to block requests from unauthorized users? (Choose two.)

- A. Create a usage plan with an API key that is shared with genuine users only. **Most Voted**
- B. Integrate logic within the Lambda function to ignore the requests from fraudulent IP addresses.
- C. Implement an AWS WAF rule to target malicious requests and trigger actions to filter them out. **Most Voted**
- D. Convert the existing public API to a private API. Update the DNS records to redirect users to the new API endpoint.
- E. Create an IAM role for each user attempting to access the API. A user will assume the role when making the API call.

Correct Answer: AC

Question #160

An ecommerce company hosts its analytics application in the AWS Cloud. The application generates about 300 MB of data each month. The data is stored in JSON format. The company is evaluating a disaster recovery solution to back up the data. The data must be accessible in milliseconds if it is needed, and the data must be kept for 30 days.

Which solution meets these requirements MOST cost-effectively?

- A. Amazon OpenSearch Service (Amazon Elasticsearch Service)
- B. Amazon S3 Glacier
- C. Amazon S3 Standard **Most Voted**
- D. Amazon RDS for PostgreSQL

Correct Answer: C

Question #161

A company has a small Python application that processes JSON documents and outputs the results to an on-premises SQL database. The application runs thousands of times each day. The company wants to move the application to the AWS Cloud. The company needs a highly available solution that maximizes scalability and minimizes operational overhead.

Which solution will meet these requirements?

- A. Place the JSON documents in an Amazon S3 bucket. Run the Python code on multiple Amazon EC2 instances to process the documents. Store the results in an Amazon Aurora DB cluster.
- B. Place the JSON documents in an Amazon S3 bucket. Create an AWS Lambda function that runs the Python code to process the documents as they arrive in the S3 bucket. Store the results in an Amazon Aurora DB cluster. **Most Voted**
- C. Place the JSON documents in an Amazon Elastic Block Store (Amazon EBS) volume. Use the EBS Multi-Attach feature to attach the volume to multiple Amazon EC2 instances. Run the Python code on the EC2 instances to process the documents. Store the results on an Amazon RDS DB instance.
- D. Place the JSON documents in an Amazon Simple Queue Service (Amazon SQS) queue as messages. Deploy the Python code as a container on an Amazon Elastic Container Service (Amazon ECS) cluster that is configured with the Amazon EC2 launch type. Use the container to process the SQS messages. Store the results on an Amazon RDS DB instance.

Correct Answer: B

Question #162

A company wants to use high performance computing (HPC) infrastructure on AWS for financial risk modeling. The company's HPC workloads run on Linux. Each HPC workflow runs on hundreds of Amazon EC2 Spot Instances, is short-lived, and generates thousands of output files that are ultimately stored in persistent storage for analytics and long-term future use.

The company seeks a cloud storage solution that permits the copying of on-premises data to long-term persistent storage to make data available for processing by all EC2 instances. The solution should also be a high performance file system that is integrated with persistent storage to read and write datasets and output files.

Which combination of AWS services meets these requirements?

- A. Amazon FSx for Lustre integrated with Amazon S3 **Most Voted**
- B. Amazon FSx for Windows File Server integrated with Amazon S3
- C. Amazon S3 Glacier integrated with Amazon Elastic Block Store (Amazon EBS)
- D. Amazon S3 bucket with a VPC endpoint integrated with an Amazon Elastic Block Store (Amazon EBS) General Purpose SSD (gp2) volume

Correct Answer: A

Question #163

A company is building a containerized application on premises and decides to move the application to AWS. The application will have thousands of users soon after it is deployed. The company is unsure how to manage the deployment of containers at scale. The company needs to deploy the containerized application in a highly available architecture that minimizes operational overhead.

Which solution will meet these requirements?

- A. Store container images in an Amazon Elastic Container Registry (Amazon ECR) repository. Use an Amazon Elastic Container Service (Amazon ECS) cluster with the AWS Fargate launch type to run the containers. Use target tracking to scale automatically based on demand. **Most Voted**
- B. Store container images in an Amazon Elastic Container Registry (Amazon ECR) repository. Use an Amazon Elastic Container Service (Amazon ECS) cluster with the Amazon EC2 launch type to run the containers. Use target tracking to scale automatically based on demand.
- C. Store container images in a repository that runs on an Amazon EC2 instance. Run the containers on EC2 instances that are spread across multiple Availability Zones. Monitor the average CPU utilization in Amazon CloudWatch. Launch new EC2 instances as needed.
- D. Create an Amazon EC2 Amazon Machine Image (AMI) that contains the container image. Launch EC2 instances in an Auto Scaling group across multiple Availability Zones. Use an Amazon CloudWatch alarm to scale out EC2 instances when the average CPU utilization threshold is breached.

Correct Answer: A

Question #164

A company has two applications: a sender application that sends messages with payloads to be processed and a processing application intended to receive the messages with payloads. The company wants to implement an AWS service to handle messages between the two applications. The sender application can send about 1,000 messages each hour. The messages may take up to 2 days to be processed. If the messages fail to process, they must be retained so that they do not impact the processing of any remaining messages.

Which solution meets these requirements and is the MOST operationally efficient?

- A. Set up an Amazon EC2 instance running a Redis database. Configure both applications to use the instance. Store, process, and delete the messages, respectively.
- B. Use an Amazon Kinesis data stream to receive the messages from the sender application. Integrate the processing application with the Kinesis Client Library (KCL).
- C. Integrate the sender and processor applications with an Amazon Simple Queue Service (Amazon SQS) queue. Configure a dead-letter queue to collect the messages that failed to process. **Most Voted**
- D. Subscribe the processing application to an Amazon Simple Notification Service (Amazon SNS) topic to receive notifications to process. Integrate the sender application to write to the SNS topic.

Correct Answer: C

Question #165

A solutions architect must design a solution that uses Amazon CloudFront with an Amazon S3 origin to store a static website. The company's security policy requires that all website traffic be inspected by AWS WAF.

How should the solutions architect comply with these requirements?

- A. Configure an S3 bucket policy to accept requests coming from the AWS WAF Amazon Resource Name (ARN) only.
- B. Configure Amazon CloudFront to forward all incoming requests to AWS WAF before requesting content from the S3 origin. **Most Voted**
- C. Configure a security group that allows Amazon CloudFront IP addresses to access Amazon S3 only. Associate AWS WAF to CloudFront.
- D. Configure Amazon CloudFront and Amazon S3 to use an origin access identity (OAI) to restrict access to the S3 bucket. Enable AWS WAF on the distribution. **Most Voted**

Correct Answer: D

Question #166

Organizers for a global event want to put daily reports online as static HTML pages. The pages are expected to generate millions of views from users around the world. The files are stored in an Amazon S3 bucket. A solutions architect has been asked to design an efficient and effective solution.

Which action should the solutions architect take to accomplish this?

- A. Generate presigned URLs for the files.
- B. Use cross-Region replication to all Regions.
- C. Use the geoproximity feature of Amazon Route 53.
- D. Use Amazon CloudFront with the S3 bucket as its origin. **Most Voted**

Correct Answer: D

Question #167

A company runs a production application on a fleet of Amazon EC2 instances. The application reads the data from an Amazon SQS queue and processes the messages in parallel. The message volume is unpredictable and often has intermittent traffic. This application should continually process messages without any downtime.

Which solution meets these requirements MOST cost-effectively?

- A. Use Spot Instances exclusively to handle the maximum capacity required.
- B. Use Reserved Instances exclusively to handle the maximum capacity required.
- C. Use Reserved Instances for the baseline capacity and use Spot Instances to handle additional capacity.
- D. Use Reserved Instances for the baseline capacity and use On-Demand Instances to handle additional capacity. **Most Voted**

Correct Answer: D

Question #168

A security team wants to limit access to specific services or actions in all of the team's AWS accounts. All accounts belong to a large organization in AWS Organizations. The solution must be scalable and there must be a single point where permissions can be maintained.

What should a solutions architect do to accomplish this?

- A. Create an ACL to provide access to the services or actions.
- B. Create a security group to allow accounts and attach it to user groups.
- C. Create cross-account roles in each account to deny access to the services or actions.
- D. Create a service control policy in the root organizational unit to deny access to the services or actions. **Most Voted**

Correct Answer: D

Question #169

A company is concerned about the security of its public web application due to recent web attacks. The application uses an Application Load Balancer (ALB). A solutions architect must reduce the risk of DDoS attacks against the application.

What should the solutions architect do to meet this requirement?

- A. Add an Amazon Inspector agent to the ALB.
- B. Configure Amazon Macie to prevent attacks.
- C. Enable AWS Shield Advanced to prevent attacks. **Most Voted**
- D. Configure Amazon GuardDuty to monitor the ALB.

Correct Answer: C

Question #170

A company's web application is running on Amazon EC2 instances behind an Application Load Balancer. The company recently changed its policy, which now requires the application to be accessed from one specific country only.

Which configuration will meet this requirement?

- A. Configure the security group for the EC2 instances.
- B. Configure the security group on the Application Load Balancer.
- C. Configure AWS WAF on the Application Load Balancer in a VPC. **Most Voted**
- D. Configure the network ACL for the subnet that contains the EC2 instances.

Correct Answer: C

Question #171

A company provides an API to its users that automates inquiries for tax computations based on item prices. The company experiences a larger number of inquiries during the holiday season only that cause slower response times. A solutions architect needs to design a solution that is scalable and elastic.

What should the solutions architect do to accomplish this?

- A. Provide an API hosted on an Amazon EC2 instance. The EC2 instance performs the required computations when the API request is made.
- B. Design a REST API using Amazon API Gateway that accepts the item names. API Gateway passes item names to AWS Lambda for tax computations. **Most Voted**
- C. Create an Application Load Balancer that has two Amazon EC2 instances behind it. The EC2 instances will compute the tax on the received item names.
- D. Design a REST API using Amazon API Gateway that connects with an API hosted on an Amazon EC2 instance. API Gateway accepts and passes the item names to the EC2 instance for tax computations.

Correct Answer: B

Question #172

A solutions architect is creating a new Amazon CloudFront distribution for an application. Some of the information submitted by users is sensitive. The application uses HTTPS but needs another layer of security. The sensitive information should be protected throughout the entire application stack, and access to the information should be restricted to certain applications.

Which action should the solutions architect take?

- A. Configure a CloudFront signed URL.
- B. Configure a CloudFront signed cookie.
- C. Configure a CloudFront field-level encryption profile. **Most Voted**
- D. Configure CloudFront and set the Origin Protocol Policy setting to HTTPS Only for the Viewer Protocol Policy.

Correct Answer: C

Question #173

A gaming company hosts a browser-based application on AWS. The users of the application consume a large number of videos and images that are stored in Amazon S3. This content is the same for all users.

The application has increased in popularity, and millions of users worldwide accessing these media files. The company wants to provide the files to the users while reducing the load on the origin.

Which solution meets these requirements MOST cost-effectively?

- A. Deploy an AWS Global Accelerator accelerator in front of the web servers.
- B. Deploy an Amazon CloudFront web distribution in front of the S3 bucket. **Most Voted**
- C. Deploy an Amazon ElastiCache for Redis instance in front of the web servers.
- D. Deploy an Amazon ElastiCache for Memcached instance in front of the web servers.

Correct Answer: B

Question #174

A company has a multi-tier application that runs six front-end web servers in an Amazon EC2 Auto Scaling group in a single Availability Zone behind an Application Load Balancer (ALB). A solutions architect needs to modify the infrastructure to be highly available without modifying the application.

Which architecture should the solutions architect choose that provides high availability?

- A. Create an Auto Scaling group that uses three instances across each of two Regions.
- B. Modify the Auto Scaling group to use three instances across each of two Availability Zones. **Most Voted**
- C. Create an Auto Scaling template that can be used to quickly create more instances in another Region.
- D. Change the ALB in front of the Amazon EC2 instances in a round-robin configuration to balance traffic to the web tier.

Correct Answer: B

Question #175

An ecommerce company has an order-processing application that uses Amazon API Gateway and an AWS Lambda function. The application stores data in an Amazon Aurora PostgreSQL database. During a recent sales event, a sudden surge in customer orders occurred. Some customers experienced timeouts, and the application

did not process the orders of those customers.

A solutions architect determined that the CPU utilization and memory utilization were high on the database because of a large number of open connections. The solutions architect needs to prevent the timeout errors while making the least possible changes to the application.

Which solution will meet these requirements?

- A. Configure provisioned concurrency for the Lambda function. Modify the database to be a global database in multiple AWS Regions.
- B. Use Amazon RDS Proxy to create a proxy for the database. Modify the Lambda function to use the RDS Proxy endpoint instead of the database endpoint. **Most Voted**
- C. Create a read replica for the database in a different AWS Region. Use query string parameters in API Gateway to route traffic to the read replica.
- D. Migrate the data from Aurora PostgreSQL to Amazon DynamoDB by using AWS Database Migration Service (AWS DMS). Modify the Lambda function to use the DynamoDB table.

Correct Answer: B

Question #176

An application runs on Amazon EC2 instances in private subnets. The application needs to access an Amazon DynamoDB table.

What is the MOST secure way to access the table while ensuring that the traffic does not leave the AWS network?

- A. Use a VPC endpoint for DynamoDB. **Most Voted**
- B. Use a NAT gateway in a public subnet.
- C. Use a NAT instance in a private subnet.
- D. Use the internet gateway attached to the VPC.

Correct Answer: A

Question #177

An entertainment company is using Amazon DynamoDB to store media metadata. The application is read intensive and experiencing delays. The company does not have staff to handle additional operational overhead and needs to improve the performance efficiency of DynamoDB without reconfiguring the application.

What should a solutions architect recommend to meet this requirement?

- A. Use Amazon ElastiCache for Redis.
- B. Use Amazon DynamoDB Accelerator (DAX). **Most Voted**
- C. Replicate data by using DynamoDB global tables.
- D. Use Amazon ElastiCache for Memcached with Auto Discovery enabled.

Correct Answer: B

Question #178

A company's infrastructure consists of Amazon EC2 instances and an Amazon RDS DB instance in a single AWS Region. The company wants to back up its data in a separate Region.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Backup to copy EC2 backups and RDS backups to the separate Region. **Most Voted**
- B. Use Amazon Data Lifecycle Manager (Amazon DLM) to copy EC2 backups and RDS backups to the separate Region.
- C. Create Amazon Machine Images (AMIs) of the EC2 instances. Copy the AMIs to the separate Region. Create a read replica for the RDS DB instance in the separate Region.
- D. Create Amazon Elastic Block Store (Amazon EBS) snapshots. Copy the EBS snapshots to the separate Region. Create RDS snapshots. Export the RDS snapshots to Amazon S3. Configure S3 Cross-Region Replication (CRR) to the separate Region.

Correct Answer: A

Question #179

A solutions architect needs to securely store a database user name and password that an application uses to access an Amazon RDS DB instance. The application that accesses the database runs on an Amazon EC2 instance. The solutions architect wants to create a secure parameter in AWS Systems Manager Parameter Store.

What should the solutions architect do to meet this requirement?

- A. Create an IAM role that has read access to the Parameter Store parameter. Allow Decrypt access to an AWS Key Management Service (AWS KMS) key that is used to encrypt the parameter. Assign this IAM role to the EC2 instance. **Most Voted**
- B. Create an IAM policy that allows read access to the Parameter Store parameter. Allow Decrypt access to an AWS Key Management Service (AWS KMS) key that is used to encrypt the parameter. Assign this IAM policy to the EC2 instance.
- C. Create an IAM trust relationship between the Parameter Store parameter and the EC2 instance. Specify Amazon RDS as a principal in the trust policy.
- D. Create an IAM trust relationship between the DB instance and the EC2 instance. Specify Systems Manager as a principal in the trust policy.

Correct Answer: A

Question #180

A company is designing a cloud communications platform that is driven by APIs. The application is hosted on Amazon EC2 instances behind a Network Load Balancer (NLB). The company uses Amazon API Gateway to provide external users with access to the application through APIs. The company wants to protect the platform against web exploits like SQL injection and also wants to detect and mitigate large, sophisticated DDoS attacks.

Which combination of solutions provides the MOST protection? (Choose two.)

- A. Use AWS WAF to protect the NLB.
- B. Use AWS Shield Advanced with the NLB. **Most Voted**
- C. Use AWS WAF to protect Amazon API Gateway. **Most Voted**

- D. Use Amazon GuardDuty with AWS Shield Standard
- E. Use AWS Shield Standard with Amazon API Gateway.

Correct Answer: BC

Question #181

A company has a legacy data processing application that runs on Amazon EC2 instances. Data is processed sequentially, but the order of results does not matter. The application uses a monolithic architecture. The only way that the company can scale the application to meet increased demand is to increase the size of the instances.

The company's developers have decided to rewrite the application to use a microservices architecture on Amazon Elastic Container Service (Amazon ECS).

What should a solutions architect recommend for communication between the microservices?

- A. Create an Amazon Simple Queue Service (Amazon SQS) queue. Add code to the data producers, and send data to the queue. Add code to the data consumers to process data from the queue. **Most Voted**
- B. Create an Amazon Simple Notification Service (Amazon SNS) topic. Add code to the data producers, and publish notifications to the topic. Add code to the data consumers to subscribe to the topic.
- C. Create an AWS Lambda function to pass messages. Add code to the data producers to call the Lambda function with a data object. Add code to the data consumers to receive a data object that is passed from the Lambda function.
- D. Create an Amazon DynamoDB table. Enable DynamoDB Streams. Add code to the data producers to insert data into the table. Add code to the data consumers to use the DynamoDB Streams API to detect new table entries and retrieve the data.

Correct Answer: A

Question #182

A company wants to migrate its MySQL database from on premises to AWS. The company recently experienced a database outage that significantly impacted the business. To ensure this does not happen again, the company wants a reliable database solution on AWS that minimizes data loss and stores every transaction on at least two

nodes.

Which solution meets these requirements?

- A. Create an Amazon RDS DB instance with synchronous replication to three nodes in three Availability Zones.
- B. Create an Amazon RDS MySQL DB instance with Multi-AZ functionality enabled to synchronously replicate the data. **Most Voted**
- C. Create an Amazon RDS MySQL DB instance and then create a read replica in a separate AWS Region that synchronously replicates the data.
- D. Create an Amazon EC2 instance with a MySQL engine installed that triggers an AWS Lambda function to synchronously replicate the data to an Amazon RDS MySQL DB instance.

Correct Answer: B

Question #183

A company is building a new dynamic ordering website. The company wants to minimize server maintenance and patching. The website must be highly available and must scale read and write capacity as quickly as possible to meet changes in user demand.

Which solution will meet these requirements?

- A. Host static content in Amazon S3. Host dynamic content by using Amazon API Gateway and AWS Lambda. Use Amazon DynamoDB with on-demand capacity for the database. Configure Amazon CloudFront to deliver the website content. **Most Voted**
- B. Host static content in Amazon S3. Host dynamic content by using Amazon API Gateway and AWS Lambda. Use Amazon Aurora with Aurora Auto Scaling for the database. Configure Amazon CloudFront to deliver the website content.
- C. Host all the website content on Amazon EC2 instances. Create an Auto Scaling group to scale the EC2 instances. Use an Application Load Balancer to distribute traffic. Use Amazon DynamoDB with provisioned write capacity for the database.

- D. Host all the website content on Amazon EC2 instances. Create an Auto Scaling group to scale the EC2 instances. Use an Application Load Balancer to distribute traffic. Use Amazon Aurora with Aurora Auto Scaling for the database.

Correct Answer: A

Question #184

A company has an AWS account used for software engineering. The AWS account has access to the company's on-premises data center through a pair of AWS Direct Connect connections. All non-VPC traffic routes to the virtual private gateway.

A development team recently created an AWS Lambda function through the console. The development team needs to allow the function to access a database that runs in a private subnet in the company's data center.

Which solution will meet these requirements?

- A. Configure the Lambda function to run in the VPC with the appropriate security group. **Most Voted**
- B. Set up a VPN connection from AWS to the data center. Route the traffic from the Lambda function through the VPN.
- C. Update the route tables in the VPC to allow the Lambda function to access the on-premises data center through Direct Connect.
- D. Create an Elastic IP address. Configure the Lambda function to send traffic through the Elastic IP address without an elastic network interface.

Correct Answer: A

Question #185

A company runs an application using Amazon ECS. The application creates resized versions of an original image and then makes Amazon S3 API calls to store the resized images in Amazon S3.

How can a solutions architect ensure that the application has permission to access Amazon S3?

- A. Update the S3 role in AWS IAM to allow read/write access from Amazon ECS, and then relaunch the container.
- B. Create an IAM role with S3 permissions, and then specify that role as the taskRoleArn in the task definition. **Most Voted**
- C. Create a security group that allows access from Amazon ECS to Amazon S3, and update the launch configuration used by the ECS cluster.
- D. Create an IAM user with S3 permissions, and then relaunch the Amazon EC2 instances for the ECS cluster while logged in as this account.

Correct Answer: B

Question #186

A company has a Windows-based application that must be migrated to AWS. The application requires the use of a shared Windows file system attached to multiple Amazon EC2 Windows instances that are deployed across multiple Availability Zone:

What should a solutions architect do to meet this requirement?

- A. Configure AWS Storage Gateway in volume gateway mode. Mount the volume to each Windows instance.
- B. Configure Amazon FSx for Windows File Server. Mount the Amazon FSx file system to each Windows instance. **Most Voted**
- C. Configure a file system by using Amazon Elastic File System (Amazon EFS). Mount the EFS file system to each Windows instance.
- D. Configure an Amazon Elastic Block Store (Amazon EBS) volume with the required size. Attach each EC2 instance to the volume. Mount the file system within the volume to each Windows instance.

Correct Answer: B

Question #187

A company is developing an ecommerce application that will consist of a load-balanced front end, a container-based application, and a relational database. A solutions architect needs to create a highly available solution that operates with as little manual intervention as possible.

Which solutions meet these requirements? (Choose two.)

- A. Create an Amazon RDS DB instance in Multi-AZ mode. **Most Voted**
- B. Create an Amazon RDS DB instance and one or more replicas in another Availability Zone.
- C. Create an Amazon EC2 instance-based Docker cluster to handle the dynamic application load.
- D. Create an Amazon Elastic Container Service (Amazon ECS) cluster with a Fargate launch type to handle the dynamic application load. **Most Voted**
- E. Create an Amazon Elastic Container Service (Amazon ECS) cluster with an Amazon EC2 launch type to handle the dynamic application load.

Correct Answer: AD

Question #188

A company uses Amazon S3 as its data lake. The company has a new partner that must use SFTP to upload data files. A solutions architect needs to implement a highly available SFTP solution that minimizes operational overhead.

Which solution will meet these requirements?

- A. Use AWS Transfer Family to configure an SFTP-enabled server with a publicly accessible endpoint. Choose the S3 data lake as the destination. **Most Voted**
- B. Use Amazon S3 File Gateway as an SFTP server. Expose the S3 File Gateway endpoint URL to the new partner. Share the S3 File Gateway endpoint with the new partner.
- C. Launch an Amazon EC2 instance in a private subnet in a VPC. Instruct the new partner to upload files to the EC2 instance by using a VPN. Run a cron job script, on the EC2 instance to upload files to the S3 data lake.
- D. Launch Amazon EC2 instances in a private subnet in a VPC. Place a Network Load Balancer (NLB) in front of the EC2 instances. Create an SFTP listener port for the NLB. Share the NLB hostname with the new partner. Run a cron job script on the EC2 instances to upload files to the S3 data lake.

Correct Answer: A

Question #189

A company needs to store contract documents. A contract lasts for 5 years. During the 5-year period, the company must ensure that the documents cannot be overwritten or deleted. The company needs to encrypt the documents at rest and rotate the encryption keys automatically every year.

Which combination of steps should a solutions architect take to meet these requirements with the LEAST operational overhead? (Choose two.)

- A. Store the documents in Amazon S3. Use S3 Object Lock in governance mode.
- B. Store the documents in Amazon S3. Use S3 Object Lock in compliance mode. **Most VotedMost Voted**
- C. Use server-side encryption with Amazon S3 managed encryption keys (SSE-S3). Configure key rotation.
- D. Use server-side encryption with AWS Key Management Service (AWS KMS) customer managed keys. Configure key rotation. **Most Voted**
- E. Use server-side encryption with AWS Key Management Service (AWS KMS) customer provided (imported) keys. Configure key rotation.

Correct Answer: BD

Question #190

A company has a web application that is based on Java and PHP. The company plans to move the application from on premises to AWS. The company needs the ability to test new site features frequently. The company also needs a highly available and managed solution that requires minimum operational overhead.

Which solution will meet these requirements?

- A. Create an Amazon S3 bucket. Enable static web hosting on the S3 bucket. Upload the static content to the S3 bucket. Use AWS Lambda to process all dynamic content.
- B. Deploy the web application to an AWS Elastic Beanstalk environment. Use URL swapping to switch between multiple Elastic Beanstalk environments for feature testing. **Most Voted**
- C. Deploy the web application to Amazon EC2 instances that are configured with Java and PHP. Use Auto Scaling groups and an Application Load Balancer to manage the website's availability.

- D. Containerize the web application. Deploy the web application to Amazon EC2 instances. Use the AWS Load Balancer Controller to dynamically route traffic between containers that contain the new site features for testing.

Correct Answer: B

Question #191

A company has an ordering application that stores customer information in Amazon RDS for MySQL. During regular business hours, employees run one-time queries for reporting purposes. Timeouts are occurring during order processing because the reporting queries are taking a long time to run. The company needs to eliminate the timeouts without preventing employees from performing queries.

What should a solutions architect do to meet these requirements?

- A. Create a read replica. Move reporting queries to the read replica. **Most Voted**
- B. Create a read replica. Distribute the ordering application to the primary DB instance and the read replica.
- C. Migrate the ordering application to Amazon DynamoDB with on-demand capacity.
- D. Schedule the reporting queries for non-peak hours.

Correct Answer: A

Question #192

A hospital wants to create digital copies for its large collection of historical written records. The hospital will continue to add hundreds of new documents each day. The hospital's data team will scan the documents and will upload the documents to the AWS Cloud.

A solutions architect must implement a solution to analyze the documents, extract the medical information, and store the documents so that an application can run SQL queries on the data. The solution must maximize scalability and operational efficiency.

Which combination of steps should the solutions architect take to meet these requirements? (Choose two.)

- A. Write the document information to an Amazon EC2 instance that runs a MySQL database.
- B. Write the document information to an Amazon S3 bucket. Use Amazon Athena to query the data. **Most Voted**
- C. Create an Auto Scaling group of Amazon EC2 instances to run a custom application that processes the scanned files and extracts the medical information.
- D. Create an AWS Lambda function that runs when new documents are uploaded. Use Amazon Rekognition to convert the documents to raw text. Use Amazon Transcribe Medical to detect and extract relevant medical information from the text.
- E. Create an AWS Lambda function that runs when new documents are uploaded. Use Amazon Textract to convert the documents to raw text. Use Amazon Comprehend Medical to detect and extract relevant medical information from the text. **Most Voted**

Correct Answer: BE

Question #193

A company is running a batch application on Amazon EC2 instances. The application consists of a backend with multiple Amazon RDS databases. The application is causing a high number of reads on the databases. A solutions architect must reduce the number of database reads while ensuring high availability.

What should the solutions architect do to meet this requirement?

- A. Add Amazon RDS read replicas. **Most Voted**
- B. Use Amazon ElastiCache for Redis. **Most Voted**
- C. Use Amazon Route 53 DNS caching
- D. Use Amazon ElastiCache for Memcached.

Correct Answer: B

Question #194

A company needs to run a critical application on AWS. The company needs to use Amazon EC2 for the application's database. The database must be highly available and must fail over automatically if a disruptive event occurs.

Which solution will meet these requirements?

- A. Launch two EC2 instances, each in a different Availability Zone in the same AWS Region. Install the database on both EC2 instances. Configure the EC2 instances as a cluster. Set up database replication. **Most Voted**
- B. Launch an EC2 instance in an Availability Zone. Install the database on the EC2 instance. Use an Amazon Machine Image (AMI) to back up the data. Use AWS CloudFormation to automate provisioning of the EC2 instance if a disruptive event occurs.
- C. Launch two EC2 instances, each in a different AWS Region. Install the database on both EC2 instances. Set up database replication. Fail over the database to a second Region. **Most Voted**
- D. Launch an EC2 instance in an Availability Zone. Install the database on the EC2 instance. Use an Amazon Machine Image (AMI) to back up the data. Use EC2 automatic recovery to recover the instance if a disruptive event occurs.

Correct Answer: A

Question #195

A company's order system sends requests from clients to Amazon EC2 instances. The EC2 instances process the orders and then store the orders in a database on Amazon RDS. Users report that they must reprocess orders when the system fails. The company wants a resilient solution that can process orders automatically if a system outage occurs.

What should a solutions architect do to meet these requirements?

- A. Move the EC2 instances into an Auto Scaling group. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to target an Amazon Elastic Container Service (Amazon ECS) task.
- B. Move the EC2 instances into an Auto Scaling group behind an Application Load Balancer (ALB). Update the order system to send messages to the ALB endpoint.
- C. Move the EC2 instances into an Auto Scaling group. Configure the order system to send messages to an Amazon Simple Queue Service (Amazon SQS) queue. Configure the EC2 instances to consume messages from the queue. **Most Voted**

- D. Create an Amazon Simple Notification Service (Amazon SNS) topic. Create an AWS Lambda function, and subscribe the function to the SNS topic. Configure the order system to send messages to the SNS topic. Send a command to the EC2 instances to process the messages by using AWS Systems Manager Run Command.

Correct Answer: C

Question #196

A company runs an application on a large fleet of Amazon EC2 instances. The application reads and writes entries into an Amazon DynamoDB table. The size of the DynamoDB table continuously grows, but the application needs only data from the last 30 days. The company needs a solution that minimizes cost and development effort.

Which solution meets these requirements?

- A. Use an AWS CloudFormation template to deploy the complete solution. Redeploy the CloudFormation stack every 30 days, and delete the original stack.
- B. Use an EC2 instance that runs a monitoring application from AWS Marketplace. Configure the monitoring application to use Amazon DynamoDB Streams to store the timestamp when a new item is created in the table. Use a script that runs on the EC2 instance to delete items that have a timestamp that is older than 30 days.
- C. Configure Amazon DynamoDB Streams to invoke an AWS Lambda function when a new item is created in the table. Configure the Lambda function to delete items in the table that are older than 30 days. **Most Voted**
- D. Extend the application to add an attribute that has a value of the current timestamp plus 30 days to each new item that is created in the table. Configure DynamoDB to use the attribute as the TTL attribute. **Most Voted**

Correct Answer: D

Question #197

A company has a Microsoft .NET application that runs on an on-premises Windows Server. The application stores data by using an Oracle Database Standard Edition server. The company is planning a migration to AWS and wants to minimize development changes while moving the application. The AWS application environment should be highly available.

Which combination of actions should the company take to meet these requirements? (Choose two.)

- A. Refactor the application as serverless with AWS Lambda functions running .NET Core.
- B. Rehost the application in AWS Elastic Beanstalk with the .NET platform in a Multi-AZ deployment. **Most Voted**
- C. Replatform the application to run on Amazon EC2 with the Amazon Linux Amazon Machine Image (AMI).
- D. Use AWS Database Migration Service (AWS DMS) to migrate from the Oracle database to Amazon DynamoDB in a Multi-AZ deployment.
- E. Use AWS Database Migration Service (AWS DMS) to migrate from the Oracle database to Oracle on Amazon RDS in a Multi-AZ deployment. **Most Voted**

Correct Answer: BE

Question #198

A company runs a containerized application on a Kubernetes cluster in an on-premises data center. The company is using a MongoDB database for data storage. The company wants to migrate some of these environments to AWS, but no code changes or deployment method changes are possible at this time. The company needs a solution that minimizes operational overhead.

Which solution meets these requirements?

- A. Use Amazon Elastic Container Service (Amazon ECS) with Amazon EC2 worker nodes for compute and MongoDB on EC2 for data storage.
- B. Use Amazon Elastic Container Service (Amazon ECS) with AWS Fargate for compute and Amazon DynamoDB for data storage
- C. Use Amazon Elastic Kubernetes Service (Amazon EKS) with Amazon EC2 worker nodes for compute and Amazon DynamoDB for data storage.
- D. Use Amazon Elastic Kubernetes Service (Amazon EKS) with AWS Fargate for compute and Amazon DocumentDB (with MongoDB compatibility) for data storage. **Most Voted**

Correct Answer: D

Question #199

A telemarketing company is designing its customer call center functionality on AWS. The company needs a solution that provides multiple speaker recognition and generates transcript files. The company wants to query the transcript files to analyze the business patterns. The transcript files must be stored for 7 years for auditing purposes.

Which solution will meet these requirements?

- A. Use Amazon Rekognition for multiple speaker recognition. Store the transcript files in Amazon S3. Use machine learning models for transcript file analysis.
- B. Use Amazon Transcribe for multiple speaker recognition. Use Amazon Athena for transcript file analysis. **Most Voted**
- C. Use Amazon Translate for multiple speaker recognition. Store the transcript files in Amazon Redshift. Use SQL queries for transcript file analysis.
- D. Use Amazon Rekognition for multiple speaker recognition. Store the transcript files in Amazon S3. Use Amazon Textract for transcript file analysis.

Correct Answer: B

Question #200

A company hosts its application on AWS. The company uses Amazon Cognito to manage users. When users log in to the application, the application fetches required data from Amazon DynamoDB by using a REST API that is hosted in Amazon API Gateway. The company wants an AWS managed solution that will control access to the REST API to reduce development efforts.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Configure an AWS Lambda function to be an authorizer in API Gateway to validate which user made the request.

- B. For each user, create and assign an API key that must be sent with each request. Validate the key by using an AWS Lambda function.
- C. Send the user's email address in the header with every request. Invoke an AWS Lambda function to validate that the user with that email address has proper access.
- D. Configure an Amazon Cognito user pool authorizer in API Gateway to allow Amazon Cognito to validate each request. **Most Voted**

Correct Answer: D

Question #201

A company is developing a marketing communications service that targets mobile app users. The company needs to send confirmation messages with Short Message Service (SMS) to its users. The users must be able to reply to the SMS messages. The company must store the responses for a year for analysis.

What should a solutions architect do to meet these requirements?

- A. Create an Amazon Connect contact flow to send the SMS messages. Use AWS Lambda to process the responses.
- B. Build an Amazon Pinpoint journey. Configure Amazon Pinpoint to send events to an Amazon Kinesis data stream for analysis and archiving. **Most Voted**
- C. Use Amazon Simple Queue Service (Amazon SQS) to distribute the SMS messages. Use AWS Lambda to process the responses.
- D. Create an Amazon Simple Notification Service (Amazon SNS) FIFO topic. Subscribe an Amazon Kinesis data stream to the SNS topic for analysis and archiving.

Correct Answer: B

Question #202

A company is planning to move its data to an Amazon S3 bucket. The data must be encrypted when it is stored in the S3 bucket. Additionally, the encryption key must be automatically rotated every year.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Move the data to the S3 bucket. Use server-side encryption with Amazon S3 managed encryption keys (SSE-S3). Use the built-in key rotation behavior of SSE-S3 encryption keys. **Most Voted**
- B. Create an AWS Key Management Service (AWS KMS) customer managed key. Enable automatic key rotation. Set the S3 bucket's default encryption behavior to use the customer managed KMS key. Move the data to the S3 bucket. **Most Voted**
- C. Create an AWS Key Management Service (AWS KMS) customer managed key. Set the S3 bucket's default encryption behavior to use the customer managed KMS key. Move the data to the S3 bucket. Manually rotate the KMS key every year.
- D. Encrypt the data with customer key material before moving the data to the S3 bucket. Create an AWS Key Management Service (AWS KMS) key without key material. Import the customer key material into the KMS key. Enable automatic key rotation.

Correct Answer: B

Question #203

The customers of a finance company request appointments with financial advisors by sending text messages. A web application that runs on Amazon EC2 instances accepts the appointment requests. The text messages are published to an Amazon Simple Queue Service (Amazon SQS) queue through the web application. Another application that runs on EC2 instances then sends meeting invitations and meeting confirmation email messages to the customers. After successful scheduling, this application stores the meeting information in an Amazon DynamoDB database.

As the company expands, customers report that their meeting invitations are taking longer to arrive.

What should a solutions architect recommend to resolve this issue?

- A. Add a DynamoDB Accelerator (DAX) cluster in front of the DynamoDB database.
- B. Add an Amazon API Gateway API in front of the web application that accepts the appointment requests.
- C. Add an Amazon CloudFront distribution. Set the origin as the web application that accepts the appointment requests.
- D. Add an Auto Scaling group for the application that sends meeting invitations. Configure the Auto Scaling group to scale based on the depth of the SQS queue. **Most Voted**

Correct Answer: D

Question #204

An online retail company has more than 50 million active customers and receives more than 25,000 orders each day. The company collects purchase data for customers and stores this data in Amazon S3. Additional customer data is stored in Amazon RDS.

The company wants to make all the data available to various teams so that the teams can perform analytics. The solution must provide the ability to manage fine-grained permissions for the data and must minimize operational overhead.

Which solution will meet these requirements?

- A. Migrate the purchase data to write directly to Amazon RDS. Use RDS access controls to limit access.
- B. Schedule an AWS Lambda function to periodically copy data from Amazon RDS to Amazon S3. Create an AWS Glue crawler. Use Amazon Athena to query the data. Use S3 policies to limit access.
- C. Create a data lake by using AWS Lake Formation. Create an AWS Glue JDBC connection to Amazon RDS. Register the S3 bucket in Lake Formation. Use Lake Formation access controls to limit access. **Most Voted**
- D. Create an Amazon Redshift cluster. Schedule an AWS Lambda function to periodically copy data from Amazon S3 and Amazon RDS to Amazon Redshift. Use Amazon Redshift access controls to limit access.

Correct Answer: C

Question #205

A company hosts a marketing website in an on-premises data center. The website consists of static documents and runs on a single server. An administrator updates the website content infrequently and uses an SFTP client to upload new documents.

The company decides to host its website on AWS and to use Amazon CloudFront. The company's solutions architect creates a CloudFront distribution. The solutions architect must design the most cost-effective and resilient architecture for website hosting to serve as the CloudFront origin.

Which solution will meet these requirements?

- A. Create a virtual server by using Amazon Lightsail. Configure the web server in the Lightsail instance. Upload website content by using an SFTP client.
- B. Create an AWS Auto Scaling group for Amazon EC2 instances. Use an Application Load Balancer. Upload website content by using an SFTP client.
- C. Create a private Amazon S3 bucket. Use an S3 bucket policy to allow access from a CloudFront origin access identity (OAI). Upload website content by using the AWS CLI. **Most Voted**
- D. Create a public Amazon S3 bucket. Configure AWS Transfer for SFTP. Configure the S3 bucket for website hosting. Upload website content by using the SFTP client.

Correct Answer: C

Question #206

A company wants to manage Amazon Machine Images (AMIs). The company currently copies AMIs to the same AWS Region where the AMIs were created. The company needs to design an application that captures AWS API calls and sends alerts whenever the Amazon EC2 CreateImage API operation is called within the company's account.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS Lambda function to query AWS CloudTrail logs and to send an alert when a CreateImage API call is detected.
- B. Configure AWS CloudTrail with an Amazon Simple Notification Service (Amazon SNS) notification that occurs when updated logs are sent to Amazon S3. Use Amazon Athena to create a new table and to query on CreateImage when an API call is detected.
- C. Create an Amazon EventBridge (Amazon CloudWatch Events) rule for the CreateImage API call. Configure the target as an Amazon Simple Notification Service (Amazon SNS) topic to send an alert when a CreateImage API call is detected. **Most Voted**

- D. Configure an Amazon Simple Queue Service (Amazon SQS) FIFO queue as a target for AWS CloudTrail logs. Create an AWS Lambda function to send an alert to an Amazon Simple Notification Service (Amazon SNS) topic when a CreateImage API call is detected.

Correct Answer: C

Question #207

A company owns an asynchronous API that is used to ingest user requests and, based on the request type, dispatch requests to the appropriate microservice for processing. The company is using Amazon API Gateway to deploy the API front end, and an AWS Lambda function that invokes Amazon DynamoDB to store user requests before dispatching them to the processing microservices.

The company provisioned as much DynamoDB throughput as its budget allows, but the company is still experiencing availability issues and is losing user requests.

What should a solutions architect do to address this issue without impacting existing users?

- A. Add throttling on the API Gateway with server-side throttling limits.
- B. Use DynamoDB Accelerator (DAX) and Lambda to buffer writes to DynamoDB.
- C. Create a secondary index in DynamoDB for the table with the user requests.
- D. Use the Amazon Simple Queue Service (Amazon SQS) queue and Lambda to buffer writes to DynamoDB. **Most Voted**

Correct Answer: D

Question #208

A company needs to move data from an Amazon EC2 instance to an Amazon S3 bucket. The company must ensure that no API calls and no data are routed through public internet routes. Only the EC2 instance can have access to upload data to the S3 bucket.

Which solution will meet these requirements?

- A. Create an interface VPC endpoint for Amazon S3 in the subnet where the EC2 instance is located. Attach a resource policy to the S3 bucket to only allow the EC2 instance's IAM role for access. **Most Voted**
- B. Create a gateway VPC endpoint for Amazon S3 in the Availability Zone where the EC2 instance is located. Attach appropriate security groups to the endpoint. Attach a resource policy to the S3 bucket to only allow the EC2 instance's IAM role for access. **Most Voted**
- C. Run the nslookup tool from inside the EC2 instance to obtain the private IP address of the S3 bucket's service API endpoint. Create a route in the VPC route table to provide the EC2 instance with access to the S3 bucket. Attach a resource policy to the S3 bucket to only allow the EC2 instance's IAM role for access.
- D. Use the AWS provided, publicly available ip-ranges.json file to obtain the private IP address of the S3 bucket's service API endpoint. Create a route in the VPC route table to provide the EC2 instance with access to the S3 bucket. Attach a resource policy to the S3 bucket to only allow the EC2 instance's IAM role for access.

Correct Answer: A

Question #209

A solutions architect is designing the architecture of a new application being deployed to the AWS Cloud. The application will run on Amazon EC2 On-Demand Instances and will automatically scale across multiple Availability Zones. The EC2 instances will scale up and down frequently throughout the day. An Application Load Balancer (ALB) will handle the load distribution. The architecture needs to support distributed session data management. The company is willing to make changes to code if needed.

What should the solutions architect do to ensure that the architecture supports distributed session data management?

- A. Use Amazon ElastiCache to manage and store session data. **Most Voted**
- B. Use session affinity (sticky sessions) of the ALB to manage session data.
- C. Use Session Manager from AWS Systems Manager to manage the session.
- D. Use the GetSessionToken API operation in AWS Security Token Service (AWS STS) to manage the session.

Correct Answer: A

Question #210

A company offers a food delivery service that is growing rapidly. Because of the growth, the company's order processing system is experiencing scaling problems during peak traffic hours. The current architecture includes the following:

- A group of Amazon EC2 instances that run in an Amazon EC2 Auto Scaling group to collect orders from the application
- Another group of EC2 instances that run in an Amazon EC2 Auto Scaling group to fulfill orders

The order collection process occurs quickly, but the order fulfillment process can take longer. Data must not be lost because of a scaling event.

A solutions architect must ensure that the order collection process and the order fulfillment process can both scale properly during peak traffic hours. The solution must optimize utilization of the company's AWS resources.

Which solution meets these requirements?

- A. Use Amazon CloudWatch metrics to monitor the CPU of each instance in the Auto Scaling groups. Configure each Auto Scaling group's minimum capacity according to peak workload values.
- B. Use Amazon CloudWatch metrics to monitor the CPU of each instance in the Auto Scaling groups. Configure a CloudWatch alarm to invoke an Amazon Simple Notification Service (Amazon SNS) topic that creates additional Auto Scaling groups on demand.
- C. Provision two Amazon Simple Queue Service (Amazon SQS) queues: one for order collection and another for order fulfillment. Configure the EC2 instances to poll their respective queue. Scale the Auto Scaling groups based on notifications that the queues send.
- D. Provision two Amazon Simple Queue Service (Amazon SQS) queues: one for order collection and another for order fulfillment. Configure the EC2 instances to poll their respective queue. Create a metric based on a backlog per instance calculation. Scale the Auto Scaling groups based on this metric. **Most Voted**

Correct Answer: D

Question #211

A company hosts multiple production applications. One of the applications consists of resources from Amazon EC2, AWS Lambda, Amazon RDS, Amazon Simple Notification Service (Amazon SNS), and Amazon Simple Queue Service (Amazon SQS) across multiple AWS Regions. All company resources are tagged with a tag name of “application” and a value that corresponds to each application. A solutions architect must provide the quickest solution for identifying all of the tagged components.

Which solution meets these requirements?

- A. Use AWS CloudTrail to generate a list of resources with the application tag.
- B. Use the AWS CLI to query each service across all Regions to report the tagged components.
- C. Run a query in Amazon CloudWatch Logs Insights to report on the components with the application tag.
- D. Run a query with the AWS Resource Groups Tag Editor to report on the resources globally with the application tag. **Most Voted**

Correct Answer: D

Question #212

A company needs to export its database once a day to Amazon S3 for other teams to access. The exported object size varies between 2 GB and 5 GB. The S3 access pattern for the data is variable and changes rapidly. The data must be immediately available and must remain accessible for up to 3 months. The company needs the most cost-effective solution that will not increase retrieval time.

Which S3 storage class should the company use to meet these requirements?

- A. S3 Intelligent-Tiering **Most Voted**
- B. S3 Glacier Instant Retrieval
- C. S3 Standard
- D. S3 Standard-Infrequent Access (S3 Standard-IA)

Correct Answer: A

Question #213

A company is developing a new mobile app. The company must implement proper traffic filtering to protect its Application Load Balancer (ALB) against common application-level attacks, such as cross-site scripting or SQL injection. The company has minimal infrastructure and operational staff. The company needs to reduce its share of the responsibility in managing, updating, and securing servers for its AWS environment.

What should a solutions architect recommend to meet these requirements?

- A. Configure AWS WAF rules and associate them with the ALB. **Most Voted**
- B. Deploy the application using Amazon S3 with public hosting enabled.
- C. Deploy AWS Shield Advanced and add the ALB as a protected resource. **Most Voted**
- D. Create a new ALB that directs traffic to an Amazon EC2 instance running a third-party firewall, which then passes the traffic to the current ALB.

Correct Answer: A

Question #214

A company's reporting system delivers hundreds of .csv files to an Amazon S3 bucket each day. The company must convert these files to Apache Parquet format and must store the files in a transformed data bucket.

Which solution will meet these requirements with the LEAST development effort?

- A. Create an Amazon EMR cluster with Apache Spark installed. Write a Spark application to transform the data. Use EMR File System (EMRFS) to write files to the transformed data bucket.
- B. Create an AWS Glue crawler to discover the data. Create an AWS Glue extract, transform, and load (ETL) job to transform the data. Specify the transformed data bucket in the output step. **Most Voted**
- C. Use AWS Batch to create a job definition with Bash syntax to transform the data and output the data to the transformed data bucket. Use the job definition to submit a job. Specify an array job as the job type.
- D. Create an AWS Lambda function to transform the data and output the data to the transformed data bucket. Configure an event notification for the S3 bucket. Specify the Lambda function as the destination for the event notification.

Correct Answer: B

Question #215

A company has 700 TB of backup data stored in network attached storage (NAS) in its data center. This backup data need to be accessible for infrequent regulatory requests and must be retained 7 years. The company has decided to migrate this backup data from its data center to AWS. The migration must be complete within 1 month. The company has 500 Mbps of dedicated bandwidth on its public internet connection available for data transfer.

What should a solutions architect do to migrate and store the data at the LOWEST cost?

- A. Order AWS Snowball devices to transfer the data. Use a lifecycle policy to transition the files to Amazon S3 Glacier Deep Archive. **Most Voted**
- B. Deploy a VPN connection between the data center and Amazon VPC. Use the AWS CLI to copy the data from on premises to Amazon S3 Glacier.
- C. Provision a 500 Mbps AWS Direct Connect connection and transfer the data to Amazon S3. Use a lifecycle policy to transition the files to Amazon S3 Glacier Deep Archive.
- D. Use AWS DataSync to transfer the data and deploy a DataSync agent on premises. Use the DataSync task to copy files from the on-premises NAS storage to Amazon S3 Glacier.

Correct Answer: A

Question #216

A company has a serverless website with millions of objects in an Amazon S3 bucket. The company uses the S3 bucket as the origin for an Amazon CloudFront distribution. The company did not set encryption on the S3 bucket before the objects were loaded. A solutions architect needs to enable encryption for all existing objects and for all objects that are added to the S3 bucket in the future.

Which solution will meet these requirements with the LEAST amount of effort?

- A. Create a new S3 bucket. Turn on the default encryption settings for the new S3 bucket. Download all existing objects to temporary local storage. Upload the objects to the new S3 bucket.

- B. Turn on the default encryption settings for the S3 bucket. Use the S3 Inventory feature to create a .csv file that lists the unencrypted objects. Run an S3 Batch Operations job that uses the copy command to encrypt those objects. **Most Voted**
- C. Create a new encryption key by using AWS Key Management Service (AWS KMS). Change the settings on the S3 bucket to use server-side encryption with AWS KMS managed encryption keys (SSE-KMS). Turn on versioning for the S3 bucket.
- D. Navigate to Amazon S3 in the AWS Management Console. Browse the S3 bucket's objects. Sort by the encryption field. Select each unencrypted object. Use the Modify button to apply default encryption settings to every unencrypted object in the S3 bucket.

Correct Answer: B

Question #217

A company runs a global web application on Amazon EC2 instances behind an Application Load Balancer. The application stores data in Amazon Aurora. The company needs to create a disaster recovery solution and can tolerate up to 30 minutes of downtime and potential data loss. The solution does not need to handle the load when the primary infrastructure is healthy.

What should a solutions architect do to meet these requirements?

- A. Deploy the application with the required infrastructure elements in place. Use Amazon Route 53 to configure active-passive failover. Create an Aurora Replica in a second AWS Region. **Most Voted**
- B. Host a scaled-down deployment of the application in a second AWS Region. Use Amazon Route 53 to configure active-active failover. Create an Aurora Replica in the second Region.
- C. Replicate the primary infrastructure in a second AWS Region. Use Amazon Route 53 to configure active-active failover. Create an Aurora database that is restored from the latest snapshot.
- D. Back up data with AWS Backup. Use the backup to create the required infrastructure in a second AWS Region. Use Amazon Route 53 to configure active-passive failover. Create an Aurora second primary instance in the second Region.

Correct Answer: A

Question #218

A company has a web server running on an Amazon EC2 instance in a public subnet with an Elastic IP address. The default security group is assigned to the EC2 instance. The default network ACL has been modified to block all traffic. A solutions architect needs to make the web server accessible from everywhere on port 443.

Which combination of steps will accomplish this task? (Choose two.)

- A. Create a security group with a rule to allow TCP port 443 from source 0.0.0.0/0. **Most Voted**
- B. Create a security group with a rule to allow TCP port 443 to destination 0.0.0.0/0.
- C. Update the network ACL to allow TCP port 443 from source 0.0.0.0/0.
- D. Update the network ACL to allow inbound/outbound TCP port 443 from source 0.0.0.0/0 and to destination 0.0.0.0/0.
- E. Update the network ACL to allow inbound TCP port 443 from source 0.0.0.0/0 and outbound TCP port 32768-65535 to destination 0.0.0.0/0. **Most Voted**

Correct Answer: AE

Question #219

A company's application is having performance issues. The application is stateful and needs to complete in-memory tasks on Amazon EC2 instances. The company used AWS CloudFormation to deploy infrastructure and used the M5 EC2 instance family. As traffic increased, the application performance degraded. Users are reporting delays when the users attempt to access the application.

Which solution will resolve these issues in the MOST operationally efficient way?

- A. Replace the EC2 instances with T3 EC2 instances that run in an Auto Scaling group. Make the changes by using the AWS Management Console.
- B. Modify the CloudFormation templates to run the EC2 instances in an Auto Scaling group. Increase the desired capacity and the maximum capacity of the Auto Scaling group manually when an increase is necessary.
- C. Modify the CloudFormation templates. Replace the EC2 instances with R5 EC2 instances. Use Amazon CloudWatch built-in EC2 memory metrics to track the application performance for future capacity planning.

- D. Modify the CloudFormation templates. Replace the EC2 instances with R5 EC2 instances. Deploy the Amazon CloudWatch agent on the EC2 instances to generate custom application latency metrics for future capacity planning. **Most Voted**

Correct Answer: D

Question #220

A solutions architect is designing a new API using Amazon API Gateway that will receive requests from users. The volume of requests is highly variable; several hours can pass without receiving a single request. The data processing will take place asynchronously, but should be completed within a few seconds after a request is made.

Which compute service should the solutions architect have the API invoke to deliver the requirements at the lowest cost?

- A. An AWS Glue job
- B. An AWS Lambda function **Most Voted**
- C. A containerized service hosted in Amazon Elastic Kubernetes Service (Amazon EKS)
- D. A containerized service hosted in Amazon ECS with Amazon EC2

Correct Answer: B

Question #221

A company runs an application on a group of Amazon Linux EC2 instances. For compliance reasons, the company must retain all application log files for 7 years. The log files will be analyzed by a reporting tool that must be able to access all the files concurrently.

Which storage solution meets these requirements MOST cost-effectively?

- A. Amazon Elastic Block Store (Amazon EBS)
- B. Amazon Elastic File System (Amazon EFS)
- C. Amazon EC2 instance store

- D. Amazon S3 **Most Voted**

Correct Answer: D

Question #222

A company has hired an external vendor to perform work in the company's AWS account. The vendor uses an automated tool that is hosted in an AWS account that the vendor owns. The vendor does not have IAM access to the company's AWS account.

How should a solutions architect grant this access to the vendor?

- A. Create an IAM role in the company's account to delegate access to the vendor's IAM role. Attach the appropriate IAM policies to the role for the permissions that the vendor requires. **Most Voted**
- B. Create an IAM user in the company's account with a password that meets the password complexity requirements. Attach the appropriate IAM policies to the user for the permissions that the vendor requires.
- C. Create an IAM group in the company's account. Add the tool's IAM user from the vendor account to the group. Attach the appropriate IAM policies to the group for the permissions that the vendor requires.
- D. Create a new identity provider by choosing "AWS account" as the provider type in the IAM console. Supply the vendor's AWS account ID and user name. Attach the appropriate IAM policies to the new provider for the permissions that the vendor requires.

Correct Answer: A

Question #223

A company has deployed a Java Spring Boot application as a pod that runs on Amazon Elastic Kubernetes Service (Amazon EKS) in private subnets. The application needs to write data to an Amazon DynamoDB table. A solutions architect must ensure that the application can interact with the DynamoDB table without exposing traffic to the internet.

Which combination of steps should the solutions architect take to accomplish this goal? (Choose two.)

- A. Attach an IAM role that has sufficient privileges to the EKS pod. **Most Voted**
- B. Attach an IAM user that has sufficient privileges to the EKS pod.
- C. Allow outbound connectivity to the DynamoDB table through the private subnets' network ACLs.
- D. Create a VPC endpoint for DynamoDB. **Most Voted**
- E. Embed the access keys in the Java Spring Boot code.

Correct Answer: AD

Question #224

A company recently migrated its web application to AWS by rehosting the application on Amazon EC2 instances in a single AWS Region. The company wants to redesign its application architecture to be highly available and fault tolerant. Traffic must reach all running EC2 instances randomly.

Which combination of steps should the company take to meet these requirements? (Choose two.)

- A. Create an Amazon Route 53 failover routing policy.
- B. Create an Amazon Route 53 weighted routing policy.
- C. Create an Amazon Route 53 multivalue answer routing policy. **Most Voted**
- D. Launch three EC2 instances: two instances in one Availability Zone and one instance in another Availability Zone.
- E. Launch four EC2 instances: two instances in one Availability Zone and two instances in another Availability Zone. **Most VotedMost Voted**

Correct Answer: CE

Question #225

A media company collects and analyzes user activity data on premises. The company wants to migrate this capability to AWS. The user activity data store will continue to grow and will be petabytes in size. The company needs to build a highly available data ingestion solution that facilitates on-demand analytics of existing data and new data with SQL.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Send activity data to an Amazon Kinesis data stream. Configure the stream to deliver the data to an Amazon S3 bucket.
- B. Send activity data to an Amazon Kinesis Data Firehose delivery stream. Configure the stream to deliver the data to an Amazon Redshift cluster. **Most Voted**
- C. Place activity data in an Amazon S3 bucket. Configure Amazon S3 to run an AWS Lambda function on the data as the data arrives in the S3 bucket.
- D. Create an ingestion service on Amazon EC2 instances that are spread across multiple Availability Zones. Configure the service to forward data to an Amazon RDS Multi-AZ database.

Correct Answer: B

Question #226

A company collects data from thousands of remote devices by using a RESTful web services application that runs on an Amazon EC2 instance. The EC2 instance receives the raw data, transforms the raw data, and stores all the data in an Amazon S3 bucket. The number of remote devices will increase into the millions soon. The company needs a highly scalable solution that minimizes operational overhead.

Which combination of steps should a solutions architect take to meet these requirements? (Choose two.)

- A. Use AWS Glue to process the raw data in Amazon S3. **Most Voted**
- B. Use Amazon Route 53 to route traffic to different EC2 instances.
- C. Add more EC2 instances to accommodate the increasing amount of incoming data.
- D. Send the raw data to Amazon Simple Queue Service (Amazon SQS). Use EC2 instances to process the data.
- E. Use Amazon API Gateway to send the raw data to an Amazon Kinesis data stream. Configure Amazon Kinesis Data Firehose to use the data stream as a source to deliver the data to Amazon S3. **Most Voted**

Correct Answer: AE

Question #227

A company needs to retain its AWS CloudTrail logs for 3 years. The company is enforcing CloudTrail across a set of AWS accounts by using AWS Organizations from the parent account. The CloudTrail target S3 bucket is configured with S3 Versioning enabled. An S3 Lifecycle policy is in place to delete current objects after 3 years.

After the fourth year of use of the S3 bucket, the S3 bucket metrics show that the number of objects has continued to rise. However, the number of new CloudTrail logs that are delivered to the S3 bucket has remained consistent.

Which solution will delete objects that are older than 3 years in the MOST cost-effective manner?

- A. Configure the organization's centralized CloudTrail trail to expire objects after 3 years.
- B. Configure the S3 Lifecycle policy to delete previous versions as well as current versions. **Most Voted**
- C. Create an AWS Lambda function to enumerate and delete objects from Amazon S3 that are older than 3 years.
- D. Configure the parent account as the owner of all objects that are delivered to the S3 bucket.

Correct Answer: B

Question #228

A company has an API that receives real-time data from a fleet of monitoring devices. The API stores this data in an Amazon RDS DB instance for later analysis. The amount of data that the monitoring devices send to the API fluctuates. During periods of heavy traffic, the API often returns timeout errors.

After an inspection of the logs, the company determines that the database is not capable of processing the volume of write traffic that comes from the API. A solutions architect must minimize the number of connections to the database and must ensure that data is not lost during periods of heavy traffic.

Which solution will meet these requirements?

- A. Increase the size of the DB instance to an instance type that has more available memory.

- B. Modify the DB instance to be a Multi-AZ DB instance. Configure the application to write to all active RDS DB instances.
- C. Modify the API to write incoming data to an Amazon Simple Queue Service (Amazon SQS) queue. Use an AWS Lambda function that Amazon SQS invokes to write data from the queue to the database. **Most Voted**
- D. Modify the API to write incoming data to an Amazon Simple Notification Service (Amazon SNS) topic. Use an AWS Lambda function that Amazon SNS invokes to write data from the topic to the database.

Correct Answer: C

Question #229

A company manages its own Amazon EC2 instances that run MySQL databases. The company is manually managing replication and scaling as demand increases or decreases. The company needs a new solution that simplifies the process of adding or removing compute capacity to or from its database tier as needed. The solution also must offer improved performance, scaling, and durability with minimal effort from operations.

Which solution meets these requirements?

- A. Migrate the databases to Amazon Aurora Serverless for Aurora MySQL. **Most Voted**
- B. Migrate the databases to Amazon Aurora Serverless for Aurora PostgreSQL.
- C. Combine the databases into one larger MySQL database. Run the larger database on larger EC2 instances.
- D. Create an EC2 Auto Scaling group for the database tier. Migrate the existing databases to the new environment.

Correct Answer: A

Question #230

A company is concerned that two NAT instances in use will no longer be able to support the traffic needed for the company's application. A solutions architect wants to implement a solution that is highly available, fault tolerant, and automatically scalable.

What should the solutions architect recommend?

- A. Remove the two NAT instances and replace them with two NAT gateways in the same Availability Zone.
- B. Use Auto Scaling groups with Network Load Balancers for the NAT instances in different Availability Zones.
- C. Remove the two NAT instances and replace them with two NAT gateways in different Availability Zones. **Most Voted**
- D. Replace the two NAT instances with Spot Instances in different Availability Zones and deploy a Network Load Balancer.

Correct Answer: C

Question #231

An application runs on an Amazon EC2 instance that has an Elastic IP address in VPC A. The application requires access to a database in VPC B. Both VPCs are in the same AWS account.

Which solution will provide the required access MOST securely?

- A. Create a DB instance security group that allows all traffic from the public IP address of the application server in VPC A.
- B. Configure a VPC peering connection between VPC A and VPC B. **Most Voted**
- C. Make the DB instance publicly accessible. Assign a public IP address to the DB instance.
- D. Launch an EC2 instance with an Elastic IP address into VPC B. Proxy all requests through the new EC2 instance.

Correct Answer: B

Question #232

A company runs demonstration environments for its customers on Amazon EC2 instances. Each environment is isolated in its own VPC. The company's operations team needs to be notified when RDP or SSH access to an environment has been established.

- A. Configure Amazon CloudWatch Application Insights to create AWS Systems Manager OpsItems when RDP or SSH access is detected.

- B. Configure the EC2 instances with an IAM instance profile that has an IAM role with the AmazonSSMManagedInstanceCore policy attached.
- C. Publish VPC flow logs to Amazon CloudWatch Logs. Create required metric filters. Create an Amazon CloudWatch metric alarm with a notification action for when the alarm is in the ALARM state. **Most Voted**
- D. Configure an Amazon EventBridge rule to listen for events of type EC2 Instance State-change Notification. Configure an Amazon Simple Notification Service (Amazon SNS) topic as a target. Subscribe the operations team to the topic.

Correct Answer: C

Question #233

A solutions architect has created a new AWS account and must secure AWS account root user access.

Which combination of actions will accomplish this? (Choose two.)

- A. Ensure the root user uses a strong password. **Most Voted**
- B. Enable multi-factor authentication to the root user. **Most Voted**
- C. Store root user access keys in an encrypted Amazon S3 bucket.
- D. Add the root user to a group containing administrative permissions.
- E. Apply the required permissions to the root user with an inline policy document.

Correct Answer: AB

Question #234

A company is building a new web-based customer relationship management application. The application will use several Amazon EC2 instances that are backed by Amazon Elastic Block Store (Amazon EBS) volumes behind an Application Load Balancer (ALB). The application will also use an Amazon Aurora database. All data for the application must be encrypted at rest and in transit.

Which solution will meet these requirements?

- A. Use AWS Key Management Service (AWS KMS) certificates on the ALB to encrypt data in transit. Use AWS Certificate Manager (ACM) to encrypt the EBS volumes and Aurora database storage at rest.
- B. Use the AWS root account to log in to the AWS Management Console. Upload the company's encryption certificates. While in the root account, select the option to turn on encryption for all data at rest and in transit for the account.
- C. Use AWS Key Management Service (AWS KMS) to encrypt the EBS volumes and Aurora database storage at rest. Attach an AWS Certificate Manager (ACM) certificate to the ALB to encrypt data in transit. **Most Voted**
- D. Use BitLocker to encrypt all data at rest. Import the company's TLS certificate keys to AWS Key Management Service (AWS KMS) Attach the KMS keys to the ALB to encrypt data in transit.

Correct Answer: C

Question #235

A company is moving its on-premises Oracle database to Amazon Aurora PostgreSQL. The database has several applications that write to the same tables. The applications need to be migrated one by one with a month in between each migration. Management has expressed concerns that the database has a high number of reads and writes. The data must be kept in sync across both databases throughout the migration.

What should a solutions architect recommend?

- A. Use AWS DataSync for the initial migration. Use AWS Database Migration Service (AWS DMS) to create a change data capture (CDC) replication task and a table mapping to select all tables.
- B. Use AWS DataSync for the initial migration. Use AWS Database Migration Service (AWS DMS) to create a full load plus change data capture (CDC) replication task and a table mapping to select all tables.
- C. Use the AWS Schema Conversion Tool with AWS Database Migration Service (AWS DMS) using a memory optimized replication instance. Create a full load plus change data capture (CDC) replication task and a table mapping to select all tables. **Most Voted**
- D. Use the AWS Schema Conversion Tool with AWS Database Migration Service (AWS DMS) using a compute optimized replication instance. Create a full load plus change data capture (CDC) replication task and a table mapping to select the largest tables.

Correct Answer: C

Question #236

A company has a three-tier application for image sharing. The application uses an Amazon EC2 instance for the front-end layer, another EC2 instance for the application layer, and a third EC2 instance for a MySQL database. A solutions architect must design a scalable and highly available solution that requires the least amount of change to the application.

Which solution meets these requirements?

- A. Use Amazon S3 to host the front-end layer. Use AWS Lambda functions for the application layer. Move the database to an Amazon DynamoDB table. Use Amazon S3 to store and serve users' images.
- B. Use load-balanced Multi-AZ AWS Elastic Beanstalk environments for the front-end layer and the application layer. Move the database to an Amazon RDS DB instance with multiple read replicas to serve users' images.
- C. Use Amazon S3 to host the front-end layer. Use a fleet of EC2 instances in an Auto Scaling group for the application layer. Move the database to a memory optimized instance type to store and serve users' images.
- D. Use load-balanced Multi-AZ AWS Elastic Beanstalk environments for the front-end layer and the application layer. Move the database to an Amazon RDS Multi-AZ DB instance. Use Amazon S3 to store and serve users' images. **Most Voted**

Correct Answer: D

Question #237

An application running on an Amazon EC2 instance in VPC-A needs to access files in another EC2 instance in VPC-B. Both VPCs are in separate AWS accounts. The network administrator needs to design a solution to configure secure access to EC2 instance in VPC-B from VPC-A. The connectivity should not have a single point of failure or bandwidth concerns.

Which solution will meet these requirements?

- A. Set up a VPC peering connection between VPC-A and VPC-B. **Most Voted**
- B. Set up VPC gateway endpoints for the EC2 instance running in VPC-B.
- C. Attach a virtual private gateway to VPC-B and set up routing from VPC-A.

- D. Create a private virtual interface (VIF) for the EC2 instance running in VPC-B and add appropriate routes from VPC-A.

Correct Answer: A

Question #238

A company wants to experiment with individual AWS accounts for its engineer team. The company wants to be notified as soon as the Amazon EC2 instance usage for a given month exceeds a specific threshold for each account.

What should a solutions architect do to meet this requirement MOST cost-effectively?

- A. Use Cost Explorer to create a daily report of costs by service. Filter the report by EC2 instances. Configure Cost Explorer to send an Amazon Simple Email Service (Amazon SES) notification when a threshold is exceeded.
- B. Use Cost Explorer to create a monthly report of costs by service. Filter the report by EC2 instances. Configure Cost Explorer to send an Amazon Simple Email Service (Amazon SES) notification when a threshold is exceeded.
- C. Use AWS Budgets to create a cost budget for each account. Set the period to monthly. Set the scope to EC2 instances. Set an alert threshold for the budget. Configure an Amazon Simple Notification Service (Amazon SNS) topic to receive a notification when a threshold is exceeded. **Most Voted**
- D. Use AWS Cost and Usage Reports to create a report with hourly granularity. Integrate the report data with Amazon Athena. Use Amazon EventBridge to schedule an Athena query. Configure an Amazon Simple Notification Service (Amazon SNS) topic to receive a notification when a threshold is exceeded.

Correct Answer: C

Question #239

A solutions architect needs to design a new microservice for a company's application. Clients must be able to call an HTTPS endpoint to reach the microservice. The microservice also must use AWS Identity and Access Management (IAM) to authenticate calls. The solutions architect will write the logic for this microservice by using a single AWS Lambda function that is written in Go 1.x.

Which solution will deploy the function in the MOST operationally efficient way?

- A. Create an Amazon API Gateway REST API. Configure the method to use the Lambda function. Enable IAM authentication on the API. **Most Voted**
- B. Create a Lambda function URL for the function. Specify AWS_IAM as the authentication type.
- C. Create an Amazon CloudFront distribution. Deploy the function to Lambda@Edge. Integrate IAM authentication logic into the Lambda@Edge function.
- D. Create an Amazon CloudFront distribution. Deploy the function to CloudFront Functions. Specify AWS_IAM as the authentication type.

Correct Answer: A

Question #240

A company previously migrated its data warehouse solution to AWS. The company also has an AWS Direct Connect connection. Corporate office users query the data warehouse using a visualization tool. The average size of a query returned by the data warehouse is 50 MB and each webpage sent by the visualization tool is approximately 500 KB. Result sets returned by the data warehouse are not cached.

Which solution provides the LOWEST data transfer egress cost for the company?

- A. Host the visualization tool on premises and query the data warehouse directly over the internet.
- B. Host the visualization tool in the same AWS Region as the data warehouse. Access it over the internet.
- C. Host the visualization tool on premises and query the data warehouse directly over a Direct Connect connection at a location in the same AWS Region.
- D. Host the visualization tool in the same AWS Region as the data warehouse and access it over a Direct Connect connection at a location in the same Region. **Most Voted**

Correct Answer: D

Question #241

An online learning company is migrating to the AWS Cloud. The company maintains its student records in a PostgreSQL database. The company needs a solution in which its data is available and online across multiple AWS Regions at all times.

Which solution will meet these requirements with the LEAST amount of operational overhead?

- A. Migrate the PostgreSQL database to a PostgreSQL cluster on Amazon EC2 instances.
- B. Migrate the PostgreSQL database to an Amazon RDS for PostgreSQL DB instance with the Multi-AZ feature turned on. **Most Voted**
- C. Migrate the PostgreSQL database to an Amazon RDS for PostgreSQL DB instance. Create a read replica in another Region. **Most Voted**
- D. Migrate the PostgreSQL database to an Amazon RDS for PostgreSQL DB instance. Set up DB snapshots to be copied to another Region.

Correct Answer: C

Question #242

A company hosts its web application on AWS using seven Amazon EC2 instances. The company requires that the IP addresses of all healthy EC2 instances be returned in response to DNS queries.

Which policy should be used to meet this requirement?

- A. Simple routing policy
- B. Latency routing policy
- C. Multivalue routing policy **Most Voted**
- D. Geolocation routing policy

Correct Answer: C

Question #243

A medical research lab produces data that is related to a new study. The lab wants to make the data available with minimum latency to clinics across the country for their on-premises, file-based applications. The data files

are stored in an Amazon S3 bucket that has read-only permissions for each clinic.

What should a solutions architect recommend to meet these requirements?

- A. Deploy an AWS Storage Gateway file gateway as a virtual machine (VM) on premises at each clinic **Most Voted**
- B. Migrate the files to each clinic's on-premises applications by using AWS DataSync for processing.
- C. Deploy an AWS Storage Gateway volume gateway as a virtual machine (VM) on premises at each clinic.
- D. Attach an Amazon Elastic File System (Amazon EFS) file system to each clinic's on-premises servers.

Correct Answer: A

Question #244

A company is using a content management system that runs on a single Amazon EC2 instance. The EC2 instance contains both the web server and the database software. The company must make its website platform highly available and must enable the website to scale to meet user demand.

What should a solutions architect recommend to meet these requirements?

- A. Move the database to Amazon RDS, and enable automatic backups. Manually launch another EC2 instance in the same Availability Zone. Configure an Application Load Balancer in the Availability Zone, and set the two instances as targets.
- B. Migrate the database to an Amazon Aurora instance with a read replica in the same Availability Zone as the existing EC2 instance. Manually launch another EC2 instance in the same Availability Zone. Configure an Application Load Balancer, and set the two EC2 instances as targets.
- C. Move the database to Amazon Aurora with a read replica in another Availability Zone. Create an Amazon Machine Image (AMI) from the EC2 instance. Configure an Application Load Balancer in two Availability Zones. Attach an Auto Scaling group that uses the AMI across two Availability Zones. **Most Voted**
- D. Move the database to a separate EC2 instance, and schedule backups to Amazon S3. Create an Amazon Machine Image (AMI) from the original EC2 instance. Configure an Application Load Balancer in two Availability Zones. Attach an Auto Scaling group that uses the AMI across two Availability Zones.

Correct Answer: C

Question #245

A company is launching an application on AWS. The application uses an Application Load Balancer (ALB) to direct traffic to at least two Amazon EC2 instances in a single target group. The instances are in an Auto Scaling group for each environment. The company requires a development environment and a production environment. The production environment will have periods of high traffic.

Which solution will configure the development environment MOST cost-effectively?

- A. Reconfigure the target group in the development environment to have only one EC2 instance as a target. **Most Voted**
- B. Change the ALB balancing algorithm to least outstanding requests.
- C. Reduce the size of the EC2 instances in both environments.
- D. Reduce the maximum number of EC2 instances in the development environment's Auto Scaling group. **Most Voted**

Correct Answer: A

Question #246

A company runs a web application on Amazon EC2 instances in multiple Availability Zones. The EC2 instances are in private subnets. A solutions architect implements an internet-facing Application Load Balancer (ALB) and specifies the EC2 instances as the target group. However, the internet traffic is not reaching the EC2 instances.

How should the solutions architect reconfigure the architecture to resolve this issue?

- A. Replace the ALB with a Network Load Balancer. Configure a NAT gateway in a public subnet to allow internet traffic.
- B. Move the EC2 instances to public subnets. Add a rule to the EC2 instances' security groups to allow outbound traffic to 0.0.0.0/0.
- C. Update the route tables for the EC2 instances' subnets to send 0.0.0.0/0 traffic through the internet gateway route. Add a rule to the EC2 instances' security groups to allow outbound traffic to 0.0.0.0/0.

- D. Create public subnets in each Availability Zone. Associate the public subnets with the ALB. Update the route tables for the public subnets with a route to the private subnets. **Most Voted**

Correct Answer: D

Question #247

A company has deployed a database in Amazon RDS for MySQL. Due to increased transactions, the database support team is reporting slow reads against the DB instance and recommends adding a read replica.

Which combination of actions should a solutions architect take before implementing this change? (Choose two.)

- A. Enable binlog replication on the RDS primary node.
- B. Choose a failover priority for the source DB instance.
- C. Allow long-running transactions to complete on the source DB instance. **Most Voted**
- D. Create a global table and specify the AWS Regions where the table will be available.
- E. Enable automatic backups on the source instance by setting the backup retention period to a value other than 0. **Most Voted**

Correct Answer: CE

Question #248

A company runs analytics software on Amazon EC2 instances. The software accepts job requests from users to process data that has been uploaded to Amazon S3. Users report that some submitted data is not being processed Amazon CloudWatch reveals that the EC2 instances have a consistent CPU utilization at or near 100%. The company wants to improve system performance and scale the system based on user load.

What should a solutions architect do to meet these requirements?

- A. Create a copy of the instance. Place all instances behind an Application Load Balancer.
- B. Create an S3 VPC endpoint for Amazon S3. Update the software to reference the endpoint.
- C. Stop the EC2 instances. Modify the instance type to one with a more powerful CPU and more memory. Restart the instances.

- D. Route incoming requests to Amazon Simple Queue Service (Amazon SQS). Configure an EC2 Auto Scaling group based on queue size. Update the software to read from the queue. **Most Voted**

Correct Answer: D

Question #249

A company is implementing a shared storage solution for a media application that is hosted in the AWS Cloud. The company needs the ability to use SMB clients to access data. The solution must be fully managed.

Which AWS solution meets these requirements?

- A. Create an AWS Storage Gateway volume gateway. Create a file share that uses the required client protocol. Connect the application server to the file share.
- B. Create an AWS Storage Gateway tape gateway. Configure tapes to use Amazon S3. Connect the application server to the tape gateway.
- C. Create an Amazon EC2 Windows instance. Install and configure a Windows file share role on the instance. Connect the application server to the file share.
- D. Create an Amazon FSx for Windows File Server file system. Attach the file system to the origin server. Connect the application server to the file system. **Most Voted**

Correct Answer: D

Question #250

A company's security team requests that network traffic be captured in VPC Flow Logs. The logs will be frequently accessed for 90 days and then accessed intermittently.

What should a solutions architect do to meet these requirements when configuring the logs?

- A. Use Amazon CloudWatch as the target. Set the CloudWatch log group with an expiration of 90 days
- B. Use Amazon Kinesis as the target. Configure the Kinesis stream to always retain the logs for 90 days.

- C. Use AWS CloudTrail as the target. Configure CloudTrail to save to an Amazon S3 bucket, and enable S3 Intelligent-Tiering.
- D. Use Amazon S3 as the target. Enable an S3 Lifecycle policy to transition the logs to S3 Standard-Infrequent Access (S3 Standard-IA) after 90 days. **Most Voted**

Correct Answer: D

Question #251

An Amazon EC2 instance is located in a private subnet in a new VPC. This subnet does not have outbound internet access, but the EC2 instance needs the ability to download monthly security updates from an outside vendor.

What should a solutions architect do to meet these requirements?

- A. Create an internet gateway, and attach it to the VPC. Configure the private subnet route table to use the internet gateway as the default route.
- B. Create a NAT gateway, and place it in a public subnet. Configure the private subnet route table to use the NAT gateway as the default route. **Most Voted**
- C. Create a NAT instance, and place it in the same subnet where the EC2 instance is located. Configure the private subnet route table to use the NAT instance as the default route.
- D. Create an internet gateway, and attach it to the VPC. Create a NAT instance, and place it in the same subnet where the EC2 instance is located. Configure the private subnet route table to use the internet gateway as the default route.

Correct Answer: B

Question #252

A solutions architect needs to design a system to store client case files. The files are core company assets and are important. The number of files will grow over time.

The files must be simultaneously accessible from multiple application servers that run on Amazon EC2

instances. The solution must have built-in redundancy.

Which solution meets these requirements?

- A. Amazon Elastic File System (Amazon EFS) **Most Voted**
- B. Amazon Elastic Block Store (Amazon EBS)
- C. Amazon S3 Glacier Deep Archive
- D. AWS Backup

Correct Answer: A

Question #253

A solutions architect has created two IAM policies: Policy1 and Policy2. Both policies are attached to an IAM group.

Policy 1

```
{
  "Version": "2012-10-17",  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "iam:Get*",
        "iam:List*",
        "kms:List*",
        "ec2:*",
        "ds:*",
        "logs:Get*",
        "logs:Describe*"
      ],
      "Resource": "*"
    }
  ]
}
```

Policy 2

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "ds:Delete*",
      "Resource": "*"
    }
  ]
}
```

A cloud engineer is added as an IAM user to the IAM group. Which action will the cloud engineer be able to perform?

- A. Deleting IAM users
- B. Deleting directories
- C. Deleting Amazon EC2 instances **Most Voted**
- D. Deleting logs from Amazon CloudWatch Logs

Correct Answer: C

Question #254

A company is reviewing a recent migration of a three-tier application to a VPC. The security team discovers that the principle of least privilege is not being applied to Amazon EC2 security group ingress and egress rules between the application tiers.

What should a solutions architect do to correct this issue?

- A. Create security group rules using the instance ID as the source or destination.
- B. Create security group rules using the security group ID as the source or destination. **Most Voted**
- C. Create security group rules using the VPC CIDR blocks as the source or destination.
- D. Create security group rules using the subnet CIDR blocks as the source or destination.

Correct Answer: B

Question #255

A company has an ecommerce checkout workflow that writes an order to a database and calls a service to process the payment. Users are experiencing timeouts during the checkout process. When users resubmit the checkout form, multiple unique orders are created for the same desired transaction.

How should a solutions architect refactor this workflow to prevent the creation of multiple orders?

- A. Configure the web application to send an order message to Amazon Kinesis Data Firehose. Set the payment service to retrieve the message from Kinesis Data Firehose and process the order.
- B. Create a rule in AWS CloudTrail to invoke an AWS Lambda function based on the logged application path request. Use Lambda to query the database, call the payment service, and pass in the order information.
- C. Store the order in the database. Send a message that includes the order number to Amazon Simple Notification Service (Amazon SNS). Set the payment service to poll Amazon SNS, retrieve the message, and process the order.
- D. Store the order in the database. Send a message that includes the order number to an Amazon Simple Queue Service (Amazon SQS) FIFO queue. Set the payment service to retrieve the message and process the order. Delete the message from the queue. **Most Voted**

Correct Answer: D

Question #256

A solutions architect is implementing a document review application using an Amazon S3 bucket for storage. The solution must prevent accidental deletion of the documents and ensure that all versions of the documents are available. Users must be able to download, modify, and upload documents.

Which combination of actions should be taken to meet these requirements? (Choose two.)

- A. Enable a read-only bucket ACL.
- B. Enable versioning on the bucket. **Most Voted**
- C. Attach an IAM policy to the bucket.
- D. Enable MFA Delete on the bucket. **Most Voted**
- E. Encrypt the bucket using AWS KMS.

Correct Answer: BD

Question #257

A company is building a solution that will report Amazon EC2 Auto Scaling events across all the applications in an AWS account. The company needs to use a serverless solution to store the EC2 Auto Scaling status data in Amazon S3. The company then will use the data in Amazon S3 to provide near-real-time updates in a

dashboard. The solution must not affect the speed of EC2 instance launches.

How should the company move the data to Amazon S3 to meet these requirements?

- A. Use an Amazon CloudWatch metric stream to send the EC2 Auto Scaling status data to Amazon Kinesis Data Firehose. Store the data in Amazon S3. **Most Voted**
- B. Launch an Amazon EMR cluster to collect the EC2 Auto Scaling status data and send the data to Amazon Kinesis Data Firehose. Store the data in Amazon S3.
- C. Create an Amazon EventBridge rule to invoke an AWS Lambda function on a schedule. Configure the Lambda function to send the EC2 Auto Scaling status data directly to Amazon S3.
- D. Use a bootstrap script during the launch of an EC2 instance to install Amazon Kinesis Agent. Configure Kinesis Agent to collect the EC2 Auto Scaling status data and send the data to Amazon Kinesis Data Firehose. Store the data in Amazon S3.

Correct Answer: A

Question #258

A company has an application that places hundreds of .csv files into an Amazon S3 bucket every hour. The files are 1 GB in size. Each time a file is uploaded, the company needs to convert the file to Apache Parquet format and place the output file into an S3 bucket.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS Lambda function to download the .csv files, convert the files to Parquet format, and place the output files in an S3 bucket. Invoke the Lambda function for each S3 PUT event.
- B. Create an Apache Spark job to read the .csv files, convert the files to Parquet format, and place the output files in an S3 bucket. Create an AWS Lambda function for each S3 PUT event to invoke the Spark job.
- C. Create an AWS Glue table and an AWS Glue crawler for the S3 bucket where the application places the .csv files. Schedule an AWS Lambda function to periodically use Amazon Athena to query the AWS Glue table, convert the query results into Parquet format, and place the output files into an S3 bucket.

- D. Create an AWS Glue extract, transform, and load (ETL) job to convert the .csv files to Parquet format and place the output files into an S3 bucket. Create an AWS Lambda function for each S3 PUT event to invoke the ETL job. **Most Voted**

Correct Answer: D

Question #259

A company is implementing new data retention policies for all databases that run on Amazon RDS DB instances. The company must retain daily backups for a minimum period of 2 years. The backups must be consistent and restorable.

Which solution should a solutions architect recommend to meet these requirements?

- A. Create a backup vault in AWS Backup to retain RDS backups. Create a new backup plan with a daily schedule and an expiration period of 2 years after creation. Assign the RDS DB instances to the backup plan. **Most Voted**
- B. Configure a backup window for the RDS DB instances for daily snapshots. Assign a snapshot retention policy of 2 years to each RDS DB instance. Use Amazon Data Lifecycle Manager (Amazon DLM) to schedule snapshot deletions.
- C. Configure database transaction logs to be automatically backed up to Amazon CloudWatch Logs with an expiration period of 2 years.
- D. Configure an AWS Database Migration Service (AWS DMS) replication task. Deploy a replication instance, and configure a change data capture (CDC) task to stream database changes to Amazon S3 as the target. Configure S3 Lifecycle policies to delete the snapshots after 2 years.

Correct Answer: A

Question #260

A company's compliance team needs to move its file shares to AWS. The shares run on a Windows Server SMB file share. A self-managed on-premises Active Directory controls access to the files and folders.

The company wants to use Amazon FSx for Windows File Server as part of the solution. The company must

ensure that the on-premises Active Directory groups restrict access to the FSx for Windows File Server SMB compliance shares, folders, and files after the move to AWS. The company has created an FSx for Windows File Server file system.

Which solution will meet these requirements?

- A. Create an Active Directory Connector to connect to the Active Directory. Map the Active Directory groups to IAM groups to restrict access.
- B. Assign a tag with a Restrict tag key and a Compliance tag value. Map the Active Directory groups to IAM groups to restrict access.
- C. Create an IAM service-linked role that is linked directly to FSx for Windows File Server to restrict access.
- D. Join the file system to the Active Directory to restrict access. **Most Voted**

Correct Answer: D

Question #261

A company recently announced the deployment of its retail website to a global audience. The website runs on multiple Amazon EC2 instances behind an Elastic Load Balancer. The instances run in an Auto Scaling group across multiple Availability Zones.

The company wants to provide its customers with different versions of content based on the devices that the customers use to access the website.

Which combination of actions should a solutions architect take to meet these requirements? (Choose two.)

- A. Configure Amazon CloudFront to cache multiple versions of the content. **Most Voted**
- B. Configure a host header in a Network Load Balancer to forward traffic to different instances.
- C. Configure a Lambda@Edge function to send specific objects to users based on the User-Agent header. **Most Voted**
- D. Configure AWS Global Accelerator. Forward requests to a Network Load Balancer (NLB). Configure the NLB to set up host-based routing to different EC2 instances.

- E. Configure AWS Global Accelerator. Forward requests to a Network Load Balancer (NLB). Configure the NLB to set up path-based routing to different EC2 instances.

Correct Answer: AC

Question #262

A company plans to use Amazon ElastiCache for its multi-tier web application. A solutions architect creates a Cache VPC for the ElastiCache cluster and an App VPC for the application's Amazon EC2 instances. Both VPCs are in the us-east-1 Region.

The solutions architect must implement a solution to provide the application's EC2 instances with access to the ElastiCache cluster.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a peering connection between the VPCs. Add a route table entry for the peering connection in both VPCs. Configure an inbound rule for the ElastiCache cluster's security group to allow inbound connection from the application's security group. **Most Voted**
- B. Create a Transit VPC. Update the VPC route tables in the Cache VPC and the App VPC to route traffic through the Transit VPC. Configure an inbound rule for the ElastiCache cluster's security group to allow inbound connection from the application's security group.
- C. Create a peering connection between the VPCs. Add a route table entry for the peering connection in both VPCs. Configure an inbound rule for the peering connection's security group to allow inbound connection from the application's security group.
- D. Create a Transit VPC. Update the VPC route tables in the Cache VPC and the App VPC to route traffic through the Transit VPC. Configure an inbound rule for the Transit VPC's security group to allow inbound connection from the application's security group.

Correct Answer: A

Question #263

A company is building an application that consists of several microservices. The company has decided to use container technologies to deploy its software on AWS. The company needs a solution that minimizes the amount of ongoing effort for maintenance and scaling. The company cannot manage additional infrastructure.

Which combination of actions should a solutions architect take to meet these requirements? (Choose two.)

- A. Deploy an Amazon Elastic Container Service (Amazon ECS) cluster. **Most Voted**
- B. Deploy the Kubernetes control plane on Amazon EC2 instances that span multiple Availability Zones.
- C. Deploy an Amazon Elastic Container Service (Amazon ECS) service with an Amazon EC2 launch type. Specify a desired task number level of greater than or equal to 2.
- D. Deploy an Amazon Elastic Container Service (Amazon ECS) service with a Fargate launch type. Specify a desired task number level of greater than or equal to 2. **Most Voted**
- E. Deploy Kubernetes worker nodes on Amazon EC2 instances that span multiple Availability Zones. Create a deployment that specifies two or more replicas for each microservice.

Correct Answer: AD

Question #264

A company has a web application hosted over 10 Amazon EC2 instances with traffic directed by Amazon Route 53. The company occasionally experiences a timeout error when attempting to browse the application. The networking team finds that some DNS queries return IP addresses of unhealthy instances, resulting in the timeout error.

What should a solutions architect implement to overcome these timeout errors?

- A. Create a Route 53 simple routing policy record for each EC2 instance. Associate a health check with each record.
- B. Create a Route 53 failover routing policy record for each EC2 instance. Associate a health check with each record.
- C. Create an Amazon CloudFront distribution with EC2 instances as its origin. Associate a health check with the EC2 instances.

- D. Create an Application Load Balancer (ALB) with a health check in front of the EC2 instances. Route to the ALB from Route 53. **Most Voted**

Correct Answer: D

Question #265

A solutions architect needs to design a highly available application consisting of web, application, and database tiers. HTTPS content delivery should be as close to the edge as possible, with the least delivery time.

Which solution meets these requirements and is MOST secure?

- A. Configure a public Application Load Balancer (ALB) with multiple redundant Amazon EC2 instances in public subnets. Configure Amazon CloudFront to deliver HTTPS content using the public ALB as the origin.
- B. Configure a public Application Load Balancer with multiple redundant Amazon EC2 instances in private subnets. Configure Amazon CloudFront to deliver HTTPS content using the EC2 instances as the origin.
- C. Configure a public Application Load Balancer (ALB) with multiple redundant Amazon EC2 instances in private subnets. Configure Amazon CloudFront to deliver HTTPS content using the public ALB as the origin. **Most Voted**
- D. Configure a public Application Load Balancer with multiple redundant Amazon EC2 instances in public subnets. Configure Amazon CloudFront to deliver HTTPS content using the EC2 instances as the origin.

Correct Answer: C

Question #266

A company has a popular gaming platform running on AWS. The application is sensitive to latency because latency can impact the user experience and introduce unfair advantages to some players. The application is deployed in every AWS Region. It runs on Amazon EC2 instances that are part of Auto Scaling groups configured behind Application Load Balancers (ALBs). A solutions architect needs to implement a mechanism to monitor the health of the application and redirect traffic to healthy endpoints.

Which solution meets these requirements?

- A. Configure an accelerator in AWS Global Accelerator. Add a listener for the port that the application listens on, and attach it to a Regional endpoint in each Region. Add the ALB as the endpoint. **Most Voted**
- B. Create an Amazon CloudFront distribution and specify the ALB as the origin server. Configure the cache behavior to use origin cache headers. Use AWS Lambda functions to optimize the traffic.
- C. Create an Amazon CloudFront distribution and specify Amazon S3 as the origin server. Configure the cache behavior to use origin cache headers. Use AWS Lambda functions to optimize the traffic.
- D. Configure an Amazon DynamoDB database to serve as the data store for the application. Create a DynamoDB Accelerator (DAX) cluster to act as the in-memory cache for DynamoDB hosting the application data.

Correct Answer: A

Question #267

A company has one million users that use its mobile app. The company must analyze the data usage in near-real time. The company also must encrypt the data in near-real time and must store the data in a centralized location in Apache Parquet format for further processing.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an Amazon Kinesis data stream to store the data in Amazon S3. Create an Amazon Kinesis Data Analytics application to analyze the data. Invoke an AWS Lambda function to send the data to the Kinesis Data Analytics application.
- B. Create an Amazon Kinesis data stream to store the data in Amazon S3. Create an Amazon EMR cluster to analyze the data. Invoke an AWS Lambda function to send the data to the EMR cluster.
- C. Create an Amazon Kinesis Data Firehose delivery stream to store the data in Amazon S3. Create an Amazon EMR cluster to analyze the data.
- D. Create an Amazon Kinesis Data Firehose delivery stream to store the data in Amazon S3. Create an Amazon Kinesis Data Analytics application to analyze the data. **Most Voted**

Correct Answer: D

Question #268

A gaming company has a web application that displays scores. The application runs on Amazon EC2 instances behind an Application Load Balancer. The application stores data in an Amazon RDS for MySQL database. Users are starting to experience long delays and interruptions that are caused by database read performance. The company wants to improve the user experience while minimizing changes to the application's architecture.

What should a solutions architect do to meet these requirements?

- A. Use Amazon ElastiCache in front of the database. **Most Voted**
- B. Use RDS Proxy between the application and the database. **Most Voted**
- C. Migrate the application from EC2 instances to AWS Lambda.
- D. Migrate the database from Amazon RDS for MySQL to Amazon DynamoDB.

Correct Answer: A

Question #269

An ecommerce company has noticed performance degradation of its Amazon RDS based web application. The performance degradation is attributed to an increase in the number of read-only SQL queries triggered by business analysts. A solutions architect needs to solve the problem with minimal changes to the existing web application.

What should the solutions architect recommend?

- A. Export the data to Amazon DynamoDB and have the business analysts run their queries.
- B. Load the data into Amazon ElastiCache and have the business analysts run their queries.
- C. Create a read replica of the primary database and have the business analysts run their queries. **Most Voted**
- D. Copy the data into an Amazon Redshift cluster and have the business analysts run their queries.

Correct Answer: C

Question #270

A company is using a centralized AWS account to store log data in various Amazon S3 buckets. A solutions architect needs to ensure that the data is encrypted at rest before the data is uploaded to the S3 buckets. The

data also must be encrypted in transit.

Which solution meets these requirements?

- A. Use client-side encryption to encrypt the data that is being uploaded to the S3 buckets. **Most Voted**
- B. Use server-side encryption to encrypt the data that is being uploaded to the S3 buckets.
- C. Create bucket policies that require the use of server-side encryption with S3 managed encryption keys (SSE-S3) for S3 uploads.
- D. Enable the security option to encrypt the S3 buckets through the use of a default AWS Key Management Service (AWS KMS) key.

Correct Answer: A

Question #271

A solutions architect observes that a nightly batch processing job is automatically scaled up for 1 hour before the desired Amazon EC2 capacity is reached. The peak capacity is the 'same every night and the batch jobs always start at 1 AM. The solutions architect needs to find a cost-effective solution that will allow for the desired EC2 capacity to be reached quickly and allow the Auto Scaling group to scale down after the batch jobs are complete.

What should the solutions architect do to meet these requirements?

- A. Increase the minimum capacity for the Auto Scaling group.
- B. Increase the maximum capacity for the Auto Scaling group.
- C. Configure scheduled scaling to scale up to the desired compute level. **Most Voted**
- D. Change the scaling policy to add more EC2 instances during each scaling operation.

Correct Answer: C

Question #272

A company serves a dynamic website from a fleet of Amazon EC2 instances behind an Application Load Balancer (ALB). The website needs to support multiple languages to serve customers around the world. The website's architecture is running in the us-west-1 Region and is exhibiting high request latency for users that are

located in other parts of the world.

The website needs to serve requests quickly and efficiently regardless of a user's location. However, the company does not want to recreate the existing architecture across multiple Regions.

What should a solutions architect do to meet these requirements?

- A. Replace the existing architecture with a website that is served from an Amazon S3 bucket. Configure an Amazon CloudFront distribution with the S3 bucket as the origin. Set the cache behavior settings to cache based on the Accept-Language request header.
- B. Configure an Amazon CloudFront distribution with the ALB as the origin. Set the cache behavior settings to cache based on the Accept-Language request header. **Most Voted**
- C. Create an Amazon API Gateway API that is integrated with the ALB. Configure the API to use the HTTP integration type. Set up an API Gateway stage to enable the API cache based on the Accept-Language request header.
- D. Launch an EC2 instance in each additional Region and configure NGINX to act as a cache server for that Region. Put all the EC2 instances and the ALB behind an Amazon Route 53 record set with a geolocation routing policy.

Correct Answer: B

Question #273

A rapidly growing ecommerce company is running its workloads in a single AWS Region. A solutions architect must create a disaster recovery (DR) strategy that includes a different AWS Region. The company wants its database to be up to date in the DR Region with the least possible latency. The remaining infrastructure in the DR Region needs to run at reduced capacity and must be able to scale up if necessary.

Which solution will meet these requirements with the LOWEST recovery time objective (RTO)?

- A. Use an Amazon Aurora global database with a pilot light deployment.
- B. Use an Amazon Aurora global database with a warm standby deployment. **Most Voted**
- C. Use an Amazon RDS Multi-AZ DB instance with a pilot light deployment.

- D. Use an Amazon RDS Multi-AZ DB instance with a warm standby deployment.

Correct Answer: B

Question #274

A company runs an application on Amazon EC2 instances. The company needs to implement a disaster recovery (DR) solution for the application. The DR solution needs to have a recovery time objective (RTO) of less than 4 hours. The DR solution also needs to use the fewest possible AWS resources during normal operations.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create Amazon Machine Images (AMIs) to back up the EC2 instances. Copy the AMIs to a secondary AWS Region. Automate infrastructure deployment in the secondary Region by using AWS Lambda and custom scripts.
- B. Create Amazon Machine Images (AMIs) to back up the EC2 instances. Copy the AMIs to a secondary AWS Region. Automate infrastructure deployment in the secondary Region by using AWS CloudFormation. **Most Voted**
- C. Launch EC2 instances in a secondary AWS Region. Keep the EC2 instances in the secondary Region active at all times.
- D. Launch EC2 instances in a secondary Availability Zone. Keep the EC2 instances in the secondary Availability Zone active at all times.

Correct Answer: B

Question #275

A company runs an internal browser-based application. The application runs on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Amazon EC2 Auto Scaling group across multiple Availability Zones. The Auto Scaling group scales up to 20 instances during work hours, but scales down to 2 instances overnight. Staff are complaining that the application is very slow when the day begins, although it runs well by mid-morning.

How should the scaling be changed to address the staff complaints and keep costs to a minimum?

- A. Implement a scheduled action that sets the desired capacity to 20 shortly before the office opens.
- B. Implement a step scaling action triggered at a lower CPU threshold, and decrease the cooldown period.
- C. Implement a target tracking action triggered at a lower CPU threshold, and decrease the cooldown period. **Most Voted**
- D. Implement a scheduled action that sets the minimum and maximum capacity to 20 shortly before the office opens.

Correct Answer: C

Question #276

A company has a multi-tier application deployed on several Amazon EC2 instances in an Auto Scaling group. An Amazon RDS for Oracle instance is the application's data layer that uses Oracle-specific PL/SQL functions. Traffic to the application has been steadily increasing. This is causing the EC2 instances to become overloaded and the RDS instance to run out of storage. The Auto Scaling group does not have any scaling metrics and defines the minimum healthy instance count only. The company predicts that traffic will continue to increase at a steady but unpredictable rate before leveling off.

What should a solutions architect do to ensure the system can automatically scale for the increased traffic? (Choose two.)

- A. Configure storage Auto Scaling on the RDS for Oracle instance. **Most Voted**
- B. Migrate the database to Amazon Aurora to use Auto Scaling storage.
- C. Configure an alarm on the RDS for Oracle instance for low free storage space.
- D. Configure the Auto Scaling group to use the average CPU as the scaling metric. **Most Voted**
- E. Configure the Auto Scaling group to use the average free memory as the scaling metric.

Correct Answer: AD

Question #277

A company provides an online service for posting video content and transcoding it for use by any mobile platform. The application architecture uses Amazon Elastic File System (Amazon EFS) Standard to collect and store the videos so that multiple Amazon EC2 Linux instances can access the video content for processing. As the popularity of the service has grown over time, the storage costs have become too expensive.

Which storage solution is MOST cost-effective?

- A. Use AWS Storage Gateway for files to store and process the video content.
- B. Use AWS Storage Gateway for volumes to store and process the video content.
- C. Use Amazon EFS for storing the video content. Once processing is complete, transfer the files to Amazon Elastic Block Store (Amazon EBS).
- D. Use Amazon S3 for storing the video content. Move the files temporarily over to an Amazon Elastic Block Store (Amazon EBS) volume attached to the server for processing. **Most Voted**

Correct Answer: D

Question #278

A company wants to create an application to store employee data in a hierarchical structured relationship. The company needs a minimum-latency response to high-traffic queries for the employee data and must protect any sensitive data. The company also needs to receive monthly email messages if any financial information is present in the employee data.

Which combination of steps should a solutions architect take to meet these requirements? (Choose two.)

- A. Use Amazon Redshift to store the employee data in hierarchies. Unload the data to Amazon S3 every month.
- B. Use Amazon DynamoDB to store the employee data in hierarchies. Export the data to Amazon S3 every month. **Most Voted**
- C. Configure Amazon Macie for the AWS account. Integrate Macie with Amazon EventBridge to send monthly events to AWS Lambda.
- D. Use Amazon Athena to analyze the employee data in Amazon S3. Integrate Athena with Amazon QuickSight to publish analysis dashboards and share the dashboards with users.

- E. Configure Amazon Macie for the AWS account. Integrate Macie with Amazon EventBridge to send monthly notifications through an Amazon Simple Notification Service (Amazon SNS) subscription. **Most Voted**

Correct Answer: BE

Question #279

A company has an application that is backed by an Amazon DynamoDB table. The company's compliance requirements specify that database backups must be taken every month, must be available for 6 months, and must be retained for 7 years.

Which solution will meet these requirements?

- A. Create an AWS Backup plan to back up the DynamoDB table on the first day of each month. Specify a lifecycle policy that transitions the backup to cold storage after 6 months. Set the retention period for each backup to 7 years. **Most Voted**
- B. Create a DynamoDB on-demand backup of the DynamoDB table on the first day of each month. Transition the backup to Amazon S3 Glacier Flexible Retrieval after 6 months. Create an S3 Lifecycle policy to delete backups that are older than 7 years.
- C. Use the AWS SDK to develop a script that creates an on-demand backup of the DynamoDB table. Set up an Amazon EventBridge rule that runs the script on the first day of each month. Create a second script that will run on the second day of each month to transition DynamoDB backups that are older than 6 months to cold storage and to delete backups that are older than 7 years.
- D. Use the AWS CLI to create an on-demand backup of the DynamoDB table. Set up an Amazon EventBridge rule that runs the command on the first day of each month with a cron expression. Specify in the command to transition the backups to cold storage after 6 months and to delete the backups after 7 years.

Correct Answer: A

Question #280

A company is using Amazon CloudFront with its website. The company has enabled logging on the CloudFront distribution, and logs are saved in one of the company's Amazon S3 buckets. The company needs to perform advanced analyses on the logs and build visualizations.

What should a solutions architect do to meet these requirements?

- A. Use standard SQL queries in Amazon Athena to analyze the CloudFront logs in the S3 bucket. Visualize the results with AWS Glue.
- B. Use standard SQL queries in Amazon Athena to analyze the CloudFront logs in the S3 bucket. Visualize the results with Amazon QuickSight. **Most Voted**
- C. Use standard SQL queries in Amazon DynamoDB to analyze the CloudFront logs in the S3 bucket. Visualize the results with AWS Glue.
- D. Use standard SQL queries in Amazon DynamoDB to analyze the CloudFront logs in the S3 bucket. Visualize the results with Amazon QuickSight.

Correct Answer: B

Question #281

A company runs a fleet of web servers using an Amazon RDS for PostgreSQL DB instance. After a routine compliance check, the company sets a standard that requires a recovery point objective (RPO) of less than 1 second for all its production databases.

Which solution meets these requirements?

- A. Enable a Multi-AZ deployment for the DB instance. **Most Voted**
- B. Enable auto scaling for the DB instance in one Availability Zone.
- C. Configure the DB instance in one Availability Zone, and create multiple read replicas in a separate Availability Zone.
- D. Configure the DB instance in one Availability Zone, and configure AWS Database Migration Service (AWS DMS) change data capture (CDC) tasks.

Correct Answer: A

Question #282

A company runs a web application that is deployed on Amazon EC2 instances in the private subnet of a VPC. An Application Load Balancer (ALB) that extends across the public subnets directs web traffic to the EC2 instances. The company wants to implement new security measures to restrict inbound traffic from the ALB to the EC2 instances while preventing access from any other source inside or outside the private subnet of the EC2 instances.

Which solution will meet these requirements?

- A. Configure a route in a route table to direct traffic from the internet to the private IP addresses of the EC2 instances.
- B. Configure the security group for the EC2 instances to only allow traffic that comes from the security group for the ALB. **Most Voted**
- C. Move the EC2 instances into the public subnet. Give the EC2 instances a set of Elastic IP addresses.
- D. Configure the security group for the ALB to allow any TCP traffic on any port.

Correct Answer: B

Question #283

A research company runs experiments that are powered by a simulation application and a visualization application. The simulation application runs on Linux and outputs intermediate data to an NFS share every 5 minutes. The visualization application is a Windows desktop application that displays the simulation output and requires an SMB file system.

The company maintains two synchronized file systems. This strategy is causing data duplication and inefficient resource usage. The company needs to migrate the applications to AWS without making code changes to either application.

Which solution will meet these requirements?

- A. Migrate both applications to AWS Lambda. Create an Amazon S3 bucket to exchange data between the applications.

- B. Migrate both applications to Amazon Elastic Container Service (Amazon ECS). Configure Amazon FSx File Gateway for storage.
- C. Migrate the simulation application to Linux Amazon EC2 instances. Migrate the visualization application to Windows EC2 instances. Configure Amazon Simple Queue Service (Amazon SQS) to exchange data between the applications.
- D. Migrate the simulation application to Linux Amazon EC2 instances. Migrate the visualization application to Windows EC2 instances. Configure Amazon FSx for NetApp ONTAP for storage. **Most Voted**

Correct Answer: D

Question #284

As part of budget planning, management wants a report of AWS billed items listed by user. The data will be used to create department budgets. A solutions architect needs to determine the most efficient way to obtain this report information.

Which solution meets these requirements?

- A. Run a query with Amazon Athena to generate the report.
- B. Create a report in Cost Explorer and download the report. **Most Voted**
- C. Access the bill details from the billing dashboard and download the bill.
- D. Modify a cost budget in AWS Budgets to alert with Amazon Simple Email Service (Amazon SES).

Correct Answer: B

Question #285

A company hosts its static website by using Amazon S3. The company wants to add a contact form to its webpage. The contact form will have dynamic server-side components for users to input their name, email address, phone number, and user message. The company anticipates that there will be fewer than 100 site visits each month.

Which solution will meet these requirements MOST cost-effectively?

- A. Host a dynamic contact form page in Amazon Elastic Container Service (Amazon ECS). Set up Amazon Simple Email Service (Amazon SES) to connect to any third-party email provider.
- B. Create an Amazon API Gateway endpoint with an AWS Lambda backend that makes a call to Amazon Simple Email Service (Amazon SES). **Most Voted**
- C. Convert the static webpage to dynamic by deploying Amazon Lightsail. Use client-side scripting to build the contact form. Integrate the form with Amazon WorkMail.
- D. Create a t2.micro Amazon EC2 instance. Deploy a LAMP (Linux, Apache, MySQL, PHP/Perl/Python) stack to host the webpage. Use client-side scripting to build the contact form. Integrate the form with Amazon WorkMail.

Correct Answer: B

Question #286

A company has a static website that is hosted on Amazon CloudFront in front of Amazon S3. The static website uses a database backend. The company notices that the website does not reflect updates that have been made in the website's Git repository. The company checks the continuous integration and continuous delivery (CI/CD) pipeline between the Git repository and Amazon S3. The company verifies that the webhooks are configured properly and that the CI/CD pipeline is sending messages that indicate successful deployments.

A solutions architect needs to implement a solution that displays the updates on the website.

Which solution will meet these requirements?

- A. Add an Application Load Balancer.
- B. Add Amazon ElastiCache for Redis or Memcached to the database layer of the web application.
- C. Invalidate the CloudFront cache. **Most Voted**
- D. Use AWS Certificate Manager (ACM) to validate the website's SSL certificate.

Correct Answer: C

Question #287

A company wants to migrate a Windows-based application from on premises to the AWS Cloud. The application has three tiers: an application tier, a business tier, and a database tier with Microsoft SQL Server. The company

wants to use specific features of SQL Server such as native backups and Data Quality Services. The company also needs to share files for processing between the tiers.

How should a solutions architect design the architecture to meet these requirements?

- A. Host all three tiers on Amazon EC2 instances. Use Amazon FSx File Gateway for file sharing between the tiers.
- B. Host all three tiers on Amazon EC2 instances. Use Amazon FSx for Windows File Server for file sharing between the tiers. **Most Voted**
- C. Host the application tier and the business tier on Amazon EC2 instances. Host the database tier on Amazon RDS. Use Amazon Elastic File System (Amazon EFS) for file sharing between the tiers.
- D. Host the application tier and the business tier on Amazon EC2 instances. Host the database tier on Amazon RDS. Use a Provisioned IOPS SSD (io2) Amazon Elastic Block Store (Amazon EBS) volume for file sharing between the tiers.

Correct Answer: B

Question #288

A company is migrating a Linux-based web server group to AWS. The web servers must access files in a shared file store for some content. The company must not make any changes to the application.

What should a solutions architect do to meet these requirements?

- A. Create an Amazon S3 Standard bucket with access to the web servers.
- B. Configure an Amazon CloudFront distribution with an Amazon S3 bucket as the origin.
- C. Create an Amazon Elastic File System (Amazon EFS) file system. Mount the EFS file system on all web servers. **Most Voted**
- D. Configure a General Purpose SSD (gp3) Amazon Elastic Block Store (Amazon EBS) volume. Mount the EBS volume to all web servers.

Correct Answer: C

Question #289

A company has an AWS Lambda function that needs read access to an Amazon S3 bucket that is located in the same AWS account.

Which solution will meet these requirements in the MOST secure manner?

- A. Apply an S3 bucket policy that grants read access to the S3 bucket.
- B. Apply an IAM role to the Lambda function. Apply an IAM policy to the role to grant read access to the S3 bucket. **Most Voted**
- C. Embed an access key and a secret key in the Lambda function's code to grant the required IAM permissions for read access to the S3 bucket.
- D. Apply an IAM role to the Lambda function. Apply an IAM policy to the role to grant read access to all S3 buckets in the account.

Correct Answer: B

Question #290

A company hosts a web application on multiple Amazon EC2 instances. The EC2 instances are in an Auto Scaling group that scales in response to user demand. The company wants to optimize cost savings without making a long-term commitment.

Which EC2 instance purchasing option should a solutions architect recommend to meet these requirements?

- A. Dedicated Instances only
- B. On-Demand Instances only
- C. A mix of On-Demand Instances and Spot Instances **Most Voted**
- D. A mix of On-Demand Instances and Reserved Instances

Correct Answer: C

Question #291

A media company uses Amazon CloudFront for its publicly available streaming video content. The company wants to secure the video content that is hosted in Amazon S3 by controlling who has access. Some of the company's users are using a custom HTTP client that does not support cookies. Some of the company's users are unable to change the hardcoded URLs that they are using for access.

Which services or methods will meet these requirements with the LEAST impact to the users? (Choose two.)

- A. Signed cookies **Most Voted**
- B. Signed URLs **Most Voted**
- C. AWS AppSync
- D. JSON Web Token (JWT)
- E. AWS Secrets Manager

Correct Answer: AB

Question #292

A company is preparing a new data platform that will ingest real-time streaming data from multiple sources. The company needs to transform the data before writing the data to Amazon S3. The company needs the ability to use SQL to query the transformed data.

Which solutions will meet these requirements? (Choose two.)

- A. Use Amazon Kinesis Data Streams to stream the data. Use Amazon Kinesis Data Analytics to transform the data. Use Amazon Kinesis Data Firehose to write the data to Amazon S3. Use Amazon Athena to query the transformed data from Amazon S3. **Most Voted**
- B. Use Amazon Managed Streaming for Apache Kafka (Amazon MSK) to stream the data. Use AWS Glue to transform the data and to write the data to Amazon S3. Use Amazon Athena to query the transformed data from Amazon S3. **Most Voted**
- C. Use AWS Database Migration Service (AWS DMS) to ingest the data. Use Amazon EMR to transform the data and to write the data to Amazon S3. Use Amazon Athena to query the transformed data from Amazon S3.

- D. Use Amazon Managed Streaming for Apache Kafka (Amazon MSK) to stream the data. Use Amazon Kinesis Data Analytics to transform the data and to write the data to Amazon S3. Use the Amazon RDS query editor to query the transformed data from Amazon S3.
- E. Use Amazon Kinesis Data Streams to stream the data. Use AWS Glue to transform the data. Use Amazon Kinesis Data Firehose to write the data to Amazon S3. Use the Amazon RDS query editor to query the transformed data from Amazon S3.

Correct Answer: AB

Question #293

A company has an on-premises volume backup solution that has reached its end of life. The company wants to use AWS as part of a new backup solution and wants to maintain local access to all the data while it is backed up on AWS. The company wants to ensure that the data backed up on AWS is automatically and securely transferred.

Which solution meets these requirements?

- A. Use AWS Snowball to migrate data out of the on-premises solution to Amazon S3. Configure on-premises systems to mount the Snowball S3 endpoint to provide local access to the data.
- B. Use AWS Snowball Edge to migrate data out of the on-premises solution to Amazon S3. Use the Snowball Edge file interface to provide on-premises systems with local access to the data.
- C. Use AWS Storage Gateway and configure a cached volume gateway. Run the Storage Gateway software appliance on premises and configure a percentage of data to cache locally. Mount the gateway storage volumes to provide local access to the data.
- D. Use AWS Storage Gateway and configure a stored volume gateway. Run the Storage Gateway software appliance on premises and map the gateway storage volumes to on-premises storage. Mount the gateway storage volumes to provide local access to the data. **Most Voted**

Correct Answer: D

Question #294

An application that is hosted on Amazon EC2 instances needs to access an Amazon S3 bucket. Traffic must not traverse the internet.

How should a solutions architect configure access to meet these requirements?

- A. Create a private hosted zone by using Amazon Route 53.
- B. Set up a gateway VPC endpoint for Amazon S3 in the VPC. **Most Voted**
- C. Configure the EC2 instances to use a NAT gateway to access the S3 bucket.
- D. Establish an AWS Site-to-Site VPN connection between the VPC and the S3 bucket.

Correct Answer: B

Question #295

An ecommerce company stores terabytes of customer data in the AWS Cloud. The data contains personally identifiable information (PII). The company wants to use the data in three applications. Only one of the applications needs to process the PII. The PII must be removed before the other two applications process the data.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the data in an Amazon DynamoDB table. Create a proxy application layer to intercept and process the data that each application requests.
- B. Store the data in an Amazon S3 bucket. Process and transform the data by using S3 Object Lambda before returning the data to the requesting application. **Most Voted**
- C. Process the data and store the transformed data in three separate Amazon S3 buckets so that each application has its own custom dataset. Point each application to its respective S3 bucket.
- D. Process the data and store the transformed data in three separate Amazon DynamoDB tables so that each application has its own custom dataset. Point each application to its respective DynamoDB table.

Correct Answer: B

Question #296

A development team has launched a new application that is hosted on Amazon EC2 instances inside a development VPC. A solutions architect needs to create a new VPC in the same account. The new VPC will be peered with the development VPC. The VPC CIDR block for the development VPC is 192.168.0.0/24. The solutions architect needs to create a CIDR block for the new VPC. The CIDR block must be valid for a VPC peering connection to the development VPC.

What is the SMALLEST CIDR block that meets these requirements?

- A. 10.0.1.0/32
- B. 192.168.0.0/24
- C. 192.168.1.0/32
- D. 10.0.1.0/24 **Most Voted**

Correct Answer: D

Question #297

A company deploys an application on five Amazon EC2 instances. An Application Load Balancer (ALB) distributes traffic to the instances by using a target group. The average CPU usage on each of the instances is below 10% most of the time, with occasional surges to 65%.

A solutions architect needs to implement a solution to automate the scalability of the application. The solution must optimize the cost of the architecture and must ensure that the application has enough CPU resources when surges occur.

Which solution will meet these requirements?

- A. Create an Amazon CloudWatch alarm that enters the ALARM state when the CPUUtilization metric is less than 20%. Create an AWS Lambda function that the CloudWatch alarm invokes to terminate one of the EC2 instances in the ALB target group.
- B. Create an EC2 Auto Scaling group. Select the existing ALB as the load balancer and the existing target group as the target group. Set a target tracking scaling policy that is based on the ASGAverageCPUUtilization metric.

Set the minimum instances to 2, the desired capacity to 3, the maximum instances to 6, and the target value to 50%. Add the EC2 instances to the Auto Scaling group. **Most Voted**

- C. Create an EC2 Auto Scaling group. Select the existing ALB as the load balancer and the existing target group as the target group. Set the minimum instances to 2, the desired capacity to 3, and the maximum instances to 6. Add the EC2 instances to the Auto Scaling group.
- D. Create two Amazon CloudWatch alarms. Configure the first CloudWatch alarm to enter the ALARM state when the average CPUUtilization metric is below 20%. Configure the second CloudWatch alarm to enter the ALARM state when the average CPUUtilization matric is above 50%. Configure the alarms to publish to an Amazon Simple Notification Service (Amazon SNS) topic to send an email message. After receiving the message, log in to decrease or increase the number of EC2 instances that are running.

Correct Answer: B

Question #298

A company is running a critical business application on Amazon EC2 instances behind an Application Load Balancer. The EC2 instances run in an Auto Scaling group and access an Amazon RDS DB instance.

The design did not pass an operational review because the EC2 instances and the DB instance are all located in a single Availability Zone. A solutions architect must update the design to use a second Availability Zone.

Which solution will make the application highly available?

- A. Provision a subnet in each Availability Zone. Configure the Auto Scaling group to distribute the EC2 instances across both Availability Zones. Configure the DB instance with connections to each network.
- B. Provision two subnets that extend across both Availability Zones. Configure the Auto Scaling group to distribute the EC2 instances across both Availability Zones. Configure the DB instance with connections to each network.
- C. Provision a subnet in each Availability Zone. Configure the Auto Scaling group to distribute the EC2 instances across both Availability Zones. Configure the DB instance for Multi-AZ deployment. **Most Voted**
- D. Provision a subnet that extends across both Availability Zones. Configure the Auto Scaling group to distribute the EC2 instances across both Availability Zones. Configure the DB instance for Multi-AZ deployment.

Correct Answer: C

Question #299

A research laboratory needs to process approximately 8 TB of data. The laboratory requires sub-millisecond latencies and a minimum throughput of 6 GBps for the storage subsystem. Hundreds of Amazon EC2 instances that run Amazon Linux will distribute and process the data.

Which solution will meet the performance requirements?

- A. Create an Amazon FSx for NetApp ONTAP file system. Set each volume's tiering policy to ALL. Import the raw data into the file system. Mount the file system on the EC2 instances.
- B. Create an Amazon S3 bucket to store the raw data. Create an Amazon FSx for Lustre file system that uses persistent SSD storage. Select the option to import data from and export data to Amazon S3. Mount the file system on the EC2 instances. **Most Voted**
- C. Create an Amazon S3 bucket to store the raw data. Create an Amazon FSx for Lustre file system that uses persistent HDD storage. Select the option to import data from and export data to Amazon S3. Mount the file system on the EC2 instances.
- D. Create an Amazon FSx for NetApp ONTAP file system. Set each volume's tiering policy to NONE. Import the raw data into the file system. Mount the file system on the EC2 instances.

Correct Answer: B

Question #300

A company needs to migrate a legacy application from an on-premises data center to the AWS Cloud because of hardware capacity constraints. The application runs 24 hours a day, 7 days a week. The application's database storage continues to grow over time.

What should a solutions architect do to meet these requirements MOST cost-effectively?

- A. Migrate the application layer to Amazon EC2 Spot Instances. Migrate the data storage layer to Amazon S3.
- B. Migrate the application layer to Amazon EC2 Reserved Instances. Migrate the data storage layer to Amazon RDS On-Demand Instances.

- C. Migrate the application layer to Amazon EC2 Reserved Instances. Migrate the data storage layer to Amazon Aurora Reserved Instances. **Most Voted**
- D. Migrate the application layer to Amazon EC2 On-Demand Instances. Migrate the data storage layer to Amazon RDS Reserved Instances.

Correct Answer: C

Question #301

A university research laboratory needs to migrate 30 TB of data from an on-premises Windows file server to Amazon FSx for Windows File Server. The laboratory has a 1 Gbps network link that many other departments in the university share.

The laboratory wants to implement a data migration service that will maximize the performance of the data transfer. However, the laboratory needs to be able to control the amount of bandwidth that the service uses to minimize the impact on other departments. The data migration must take place within the next 5 days.

Which AWS solution will meet these requirements?

- A. AWS Snowcone
- B. Amazon FSx File Gateway
- C. AWS DataSync **Most Voted**
- D. AWS Transfer Family

Correct Answer: C

Question #302

A company wants to create a mobile app that allows users to stream slow-motion video clips on their mobile devices. Currently, the app captures video clips and uploads the video clips in raw format into an Amazon S3 bucket. The app retrieves these video clips directly from the S3 bucket. However, the videos are large in their raw format.

Users are experiencing issues with buffering and playback on mobile devices. The company wants to implement solutions to maximize the performance and scalability of the app while minimizing operational overhead.

Which combination of solutions will meet these requirements? (Choose two.)

- A. Deploy Amazon CloudFront for content delivery and caching. **Most Voted**
- B. Use AWS DataSync to replicate the video files across AWS Regions in other S3 buckets.
- C. Use Amazon Elastic Transcoder to convert the video files to more appropriate formats. **Most Voted**
- D. Deploy an Auto Scaling group of Amazon EC2 instances in Local Zones for content delivery and caching.
- E. Deploy an Auto Scaling group of Amazon EC2 instances to convert the video files to more appropriate formats.

Correct Answer: A

Question #303

A company is launching a new application deployed on an Amazon Elastic Container Service (Amazon ECS) cluster and is using the Fargate launch type for ECS tasks. The company is monitoring CPU and memory usage because it is expecting high traffic to the application upon its launch. However, the company wants to reduce costs when utilization decreases.

What should a solutions architect recommend?

- A. Use Amazon EC2 Auto Scaling to scale at certain periods based on previous traffic patterns.
- B. Use an AWS Lambda function to scale Amazon ECS based on metric breaches that trigger an Amazon CloudWatch alarm.
- C. Use Amazon EC2 Auto Scaling with simple scaling policies to scale when ECS metric breaches trigger an Amazon CloudWatch alarm.
- D. Use AWS Application Auto Scaling with target tracking policies to scale when ECS metric breaches trigger an Amazon CloudWatch alarm. **Most Voted**

Correct Answer: D

Question #304

A company recently created a disaster recovery site in a different AWS Region. The company needs to transfer large amounts of data back and forth between NFS file systems in the two Regions on a periodic basis.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS DataSync. **Most Voted**
- B. Use AWS Snowball devices.
- C. Set up an SFTP server on Amazon EC2.
- D. Use AWS Database Migration Service (AWS DMS).

Correct Answer: A

Question #305

A company is designing a shared storage solution for a gaming application that is hosted in the AWS Cloud. The company needs the ability to use SMB clients to access data. The solution must be fully managed.

Which AWS solution meets these requirements?

- A. Create an AWS DataSync task that shares the data as a mountable file system. Mount the file system to the application server.
- B. Create an Amazon EC2 Windows instance. Install and configure a Windows file share role on the instance. Connect the application server to the file share.
- C. Create an Amazon FSx for Windows File Server file system. Attach the file system to the origin server. Connect the application server to the file system. **Most Voted**
- D. Create an Amazon S3 bucket. Assign an IAM role to the application to grant access to the S3 bucket. Mount the S3 bucket to the application server.

Correct Answer: C

Question #306

A company wants to run an in-memory database for a latency-sensitive application that runs on Amazon EC2 instances. The application processes more than 100,000 transactions each minute and requires high network throughput. A solutions architect needs to provide a cost-effective network design that minimizes data transfer charges.

Which solution meets these requirements?

- A. Launch all EC2 instances in the same Availability Zone within the same AWS Region. Specify a placement group with cluster strategy when launching EC2 instances. **Most Voted**
- B. Launch all EC2 instances in different Availability Zones within the same AWS Region. Specify a placement group with partition strategy when launching EC2 instances.
- C. Deploy an Auto Scaling group to launch EC2 instances in different Availability Zones based on a network utilization target.
- D. Deploy an Auto Scaling group with a step scaling policy to launch EC2 instances in different Availability Zones.

Correct Answer: A

Question #307

A company that primarily runs its application servers on premises has decided to migrate to AWS. The company wants to minimize its need to scale its Internet Small Computer Systems Interface (iSCSI) storage on premises. The company wants only its recently accessed data to remain stored locally.

Which AWS solution should the company use to meet these requirements?

- A. Amazon S3 File Gateway
- B. AWS Storage Gateway Tape Gateway
- C. AWS Storage Gateway Volume Gateway stored volumes

- D. AWS Storage Gateway Volume Gateway cached volumes **Most Voted**

Correct Answer: D

Question #308

A company has multiple AWS accounts that use consolidated billing. The company runs several active high performance Amazon RDS for Oracle On-Demand DB instances for 90 days. The company's finance team has access to AWS Trusted Advisor in the consolidated billing account and all other AWS accounts.

The finance team needs to use the appropriate AWS account to access the Trusted Advisor check recommendations for RDS. The finance team must review the appropriate Trusted Advisor check to reduce RDS costs.

Which combination of steps should the finance team take to meet these requirements? (Choose two.)

- A. Use the Trusted Advisor recommendations from the account where the RDS instances are running.
- B. Use the Trusted Advisor recommendations from the consolidated billing account to see all RDS instance checks at the same time. **Most Voted**
- C. Review the Trusted Advisor check for Amazon RDS Reserved Instance Optimization.
- D. Review the Trusted Advisor check for Amazon RDS Idle DB Instances. **Most Voted**
- E. Review the Trusted Advisor check for Amazon Redshift Reserved Node Optimization.

Correct Answer: BD

Question #309

A solutions architect needs to optimize storage costs. The solutions architect must identify any Amazon S3 buckets that are no longer being accessed or are rarely accessed.

Which solution will accomplish this goal with the LEAST operational overhead?

- A. Analyze bucket access patterns by using the S3 Storage Lens dashboard for advanced activity metrics. **Most Voted**
- B. Analyze bucket access patterns by using the S3 dashboard in the AWS Management Console.
- C. Turn on the Amazon CloudWatch BucketSizeBytes metric for buckets. Analyze bucket access patterns by using the metrics data with Amazon Athena.
- D. Turn on AWS CloudTrail for S3 object monitoring. Analyze bucket access patterns by using CloudTrail logs that are integrated with Amazon CloudWatch Logs.

Correct Answer: A

Question #310

A company sells datasets to customers who do research in artificial intelligence and machine learning (AI/ML). The datasets are large, formatted files that are stored in an Amazon S3 bucket in the us-east-1 Region. The company hosts a web application that the customers use to purchase access to a given dataset. The web application is deployed on multiple Amazon EC2 instances behind an Application Load Balancer. After a purchase is made, customers receive an S3 signed URL that allows access to the files.

The customers are distributed across North America and Europe. The company wants to reduce the cost that is associated with data transfers and wants to maintain or improve performance.

What should a solutions architect do to meet these requirements?

- A. Configure S3 Transfer Acceleration on the existing S3 bucket. Direct customer requests to the S3 Transfer Acceleration endpoint. Continue to use S3 signed URLs for access control.
- B. Deploy an Amazon CloudFront distribution with the existing S3 bucket as the origin. Direct customer requests to the CloudFront URL. Switch to CloudFront signed URLs for access control. **Most Voted**
- C. Set up a second S3 bucket in the eu-central-1 Region with S3 Cross-Region Replication between the buckets. Direct customer requests to the closest Region. Continue to use S3 signed URLs for access control.
- D. Modify the web application to enable streaming of the datasets to end users. Configure the web application to read the data from the existing S3 bucket. Implement access control directly in the application.

Correct Answer: B

Question #311

A company is using AWS to design a web application that will process insurance quotes. Users will request quotes from the application. Quotes must be separated by quote type, must be responded to within 24 hours, and must not get lost. The solution must maximize operational efficiency and must minimize maintenance.

Which solution meets these requirements?

- A. Create multiple Amazon Kinesis data streams based on the quote type. Configure the web application to send messages to the proper data stream. Configure each backend group of application servers to use the Kinesis Client Library (KCL) to pool messages from its own data stream.
- B. Create an AWS Lambda function and an Amazon Simple Notification Service (Amazon SNS) topic for each quote type. Subscribe the Lambda function to its associated SNS topic. Configure the application to publish requests for quotes to the appropriate SNS topic.
- C. Create a single Amazon Simple Notification Service (Amazon SNS) topic. Subscribe Amazon Simple Queue Service (Amazon SQS) queues to the SNS topic. Configure SNS message filtering to publish messages to the proper SQS queue based on the quote type. Configure each backend application server to use its own SQS queue. **Most Voted**
- D. Create multiple Amazon Kinesis Data Firehose delivery streams based on the quote type to deliver data streams to an Amazon OpenSearch Service cluster. Configure the application to send messages to the proper delivery stream. Configure each backend group of application servers to search for the messages from OpenSearch Service and process them accordingly.

Correct Answer: C

Question #312

A company has an application that runs on several Amazon EC2 instances. Each EC2 instance has multiple Amazon Elastic Block Store (Amazon EBS) data volumes attached to it. The application's EC2 instance configuration and data need to be backed up nightly. The application also needs to be recoverable in a different

AWS Region.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Write an AWS Lambda function that schedules nightly snapshots of the application's EBS volumes and copies the snapshots to a different Region.
- B. Create a backup plan by using AWS Backup to perform nightly backups. Copy the backups to another Region. Add the application's EC2 instances as resources. **Most Voted**
- C. Create a backup plan by using AWS Backup to perform nightly backups. Copy the backups to another Region. Add the application's EBS volumes as resources.
- D. Write an AWS Lambda function that schedules nightly snapshots of the application's EBS volumes and copies the snapshots to a different Availability Zone.

Correct Answer: B

Question #313

A company is building a mobile app on AWS. The company wants to expand its reach to millions of users. The company needs to build a platform so that authorized users can watch the company's content on their mobile devices.

What should a solutions architect recommend to meet these requirements?

- A. Publish content to a public Amazon S3 bucket. Use AWS Key Management Service (AWS KMS) keys to stream content.
- B. Set up IPsec VPN between the mobile app and the AWS environment to stream content.
- C. Use Amazon CloudFront. Provide signed URLs to stream content. **Most Voted**
- D. Set up AWS Client VPN between the mobile app and the AWS environment to stream content.

Correct Answer: C

Question #314

A company has an on-premises MySQL database used by the global sales team with infrequent access patterns. The sales team requires the database to have minimal downtime. A database administrator wants to migrate this database to AWS without selecting a particular instance type in anticipation of more users in the future.

Which service should a solutions architect recommend?

- A. Amazon Aurora MySQL
- B. Amazon Aurora Serverless for MySQL **Most Voted**
- C. Amazon Redshift Spectrum
- D. Amazon RDS for MySQL

Correct Answer: B

Question #315

A company experienced a breach that affected several applications in its on-premises data center. The attacker took advantage of vulnerabilities in the custom applications that were running on the servers. The company is now migrating its applications to run on Amazon EC2 instances. The company wants to implement a solution that actively scans for vulnerabilities on the EC2 instances and sends a report that details the findings.

Which solution will meet these requirements?

- A. Deploy AWS Shield to scan the EC2 instances for vulnerabilities. Create an AWS Lambda function to log any findings to AWS CloudTrail.
- B. Deploy Amazon Macie and AWS Lambda functions to scan the EC2 instances for vulnerabilities. Log any findings to AWS CloudTrail.
- C. Turn on Amazon GuardDuty. Deploy the GuardDuty agents to the EC2 instances. Configure an AWS Lambda function to automate the generation and distribution of reports that detail the findings.
- D. Turn on Amazon Inspector. Deploy the Amazon Inspector agent to the EC2 instances. Configure an AWS Lambda function to automate the generation and distribution of reports that detail the findings. **Most Voted**

Correct Answer: D

Question #316

A company uses an Amazon EC2 instance to run a script to poll for and process messages in an Amazon Simple Queue Service (Amazon SQS) queue. The company wants to reduce operational costs while maintaining its ability to process a growing number of messages that are added to the queue.

What should a solutions architect recommend to meet these requirements?

- A. Increase the size of the EC2 instance to process messages faster.
- B. Use Amazon EventBridge to turn off the EC2 instance when the instance is underutilized.
- C. Migrate the script on the EC2 instance to an AWS Lambda function with the appropriate runtime. **Most Voted**
- D. Use AWS Systems Manager Run Command to run the script on demand.

Correct Answer: C

Question #317

A company uses a legacy application to produce data in CSV format. The legacy application stores the output data in Amazon S3. The company is deploying a new commercial off-the-shelf (COTS) application that can perform complex SQL queries to analyze data that is stored in Amazon Redshift and Amazon S3 only. However, the COTS application cannot process the .csv files that the legacy application produces.

The company cannot update the legacy application to produce data in another format. The company needs to implement a solution so that the COTS application can use the data that the legacy application produces.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS Glue extract, transform, and load (ETL) job that runs on a schedule. Configure the ETL job to process the .csv files and store the processed data in Amazon Redshift. **Most Voted**

- B. Develop a Python script that runs on Amazon EC2 instances to convert the .csv files to .sql files. Invoke the Python script on a cron schedule to store the output files in Amazon S3.
- C. Create an AWS Lambda function and an Amazon DynamoDB table. Use an S3 event to invoke the Lambda function. Configure the Lambda function to perform an extract, transform, and load (ETL) job to process the .csv files and store the processed data in the DynamoDB table.
- D. Use Amazon EventBridge to launch an Amazon EMR cluster on a weekly schedule. Configure the EMR cluster to perform an extract, transform, and load (ETL) job to process the .csv files and store the processed data in an Amazon Redshift table.

Correct Answer: A

Question #318

A company recently migrated its entire IT environment to the AWS Cloud. The company discovers that users are provisioning oversized Amazon EC2 instances and modifying security group rules without using the appropriate change control process. A solutions architect must devise a strategy to track and audit these inventory and configuration changes.

Which actions should the solutions architect take to meet these requirements? (Choose two.)

- A. Enable AWS CloudTrail and use it for auditing. **Most Voted**
- B. Use data lifecycle policies for the Amazon EC2 instances.
- C. Enable AWS Trusted Advisor and reference the security dashboard.
- D. Enable AWS Config and create rules for auditing and compliance purposes. **Most Voted**
- E. Restore previous resource configurations with an AWS CloudFormation template.

Correct Answer: AD

Question #319

A company has hundreds of Amazon EC2 Linux-based instances in the AWS Cloud. Systems administrators have used shared SSH keys to manage the instances. After a recent audit, the company's security team is mandating the removal of all shared keys. A solutions architect must design a solution that provides secure

access to the EC2 instances.

Which solution will meet this requirement with the LEAST amount of administrative overhead?

- A. Use AWS Systems Manager Session Manager to connect to the EC2 instances. **Most Voted**
- B. Use AWS Security Token Service (AWS STS) to generate one-time SSH keys on demand.
- C. Allow shared SSH access to a set of bastion instances. Configure all other instances to allow only SSH access from the bastion instances.
- D. Use an Amazon Cognito custom authorizer to authenticate users. Invoke an AWS Lambda function to generate a temporary SSH key.

Correct Answer: A

Question #320

A company is using a fleet of Amazon EC2 instances to ingest data from on-premises data sources. The data is in JSON format and ingestion rates can be as high as 1 MB/s. When an EC2 instance is rebooted, the data in-flight is lost. The company's data science team wants to query ingested data in near-real time.

Which solution provides near-real-time data querying that is scalable with minimal data loss?

- A. Publish data to Amazon Kinesis Data Streams, Use Kinesis Data Analytics to query the data. **Most Voted**
- B. Publish data to Amazon Kinesis Data Firehose with Amazon Redshift as the destination. Use Amazon Redshift to query the data.
- C. Store ingested data in an EC2 instance store. Publish data to Amazon Kinesis Data Firehose with Amazon S3 as the destination. Use Amazon Athena to query the data.
- D. Store ingested data in an Amazon Elastic Block Store (Amazon EBS) volume. Publish data to Amazon ElastiCache for Redis. Subscribe to the Redis channel to query the data.

Correct Answer: A

Question #321

What should a solutions architect do to ensure that all objects uploaded to an Amazon S3 bucket are encrypted?

- A. Update the bucket policy to deny if the PutObject does not have an s3:x-amz-acl header set.
- B. Update the bucket policy to deny if the PutObject does not have an s3:x-amz-acl header set to private.
- C. Update the bucket policy to deny if the PutObject does not have an aws:SecureTransport header set to true.
- D. Update the bucket policy to deny if the PutObject does not have an x-amz-server-side-encryption header set. **Most Voted**

Correct Answer: D

Question #322

A solutions architect is designing a multi-tier application for a company. The application's users upload images from a mobile device. The application generates a thumbnail of each image and returns a message to the user to confirm that the image was uploaded successfully.

The thumbnail generation can take up to 60 seconds, but the company wants to provide a faster response time to its users to notify them that the original image was received. The solutions architect must design the application to asynchronously dispatch requests to the different application tiers.

What should the solutions architect do to meet these requirements?

- A. Write a custom AWS Lambda function to generate the thumbnail and alert the user. Use the image upload process as an event source to invoke the Lambda function.
- B. Create an AWS Step Functions workflow. Configure Step Functions to handle the orchestration between the application tiers and alert the user when thumbnail generation is complete.
- C. Create an Amazon Simple Queue Service (Amazon SQS) message queue. As images are uploaded, place a message on the SQS queue for thumbnail generation. Alert the user through an application message that the image was received. **Most Voted**
- D. Create Amazon Simple Notification Service (Amazon SNS) notification topics and subscriptions. Use one subscription with the application to generate the thumbnail after the image upload is complete. Use a second

subscription to message the user's mobile app by way of a push notification after thumbnail generation is complete.

Correct Answer: C

Question #323

A company's facility has badge readers at every entrance throughout the building. When badges are scanned, the readers send a message over HTTPS to indicate who attempted to access that particular entrance.

A solutions architect must design a system to process these messages from the sensors. The solution must be highly available, and the results must be made available for the company's security team to analyze.

Which system architecture should the solutions architect recommend?

- A. Launch an Amazon EC2 instance to serve as the HTTPS endpoint and to process the messages. Configure the EC2 instance to save the results to an Amazon S3 bucket.
- B. Create an HTTPS endpoint in Amazon API Gateway. Configure the API Gateway endpoint to invoke an AWS Lambda function to process the messages and save the results to an Amazon DynamoDB table. **Most Voted**
- C. Use Amazon Route 53 to direct incoming sensor messages to an AWS Lambda function. Configure the Lambda function to process the messages and save the results to an Amazon DynamoDB table.
- D. Create a gateway VPC endpoint for Amazon S3. Configure a Site-to-Site VPN connection from the facility network to the VPC so that sensor data can be written directly to an S3 bucket by way of the VPC endpoint.

Correct Answer: B

Question #324

A company wants to implement a disaster recovery plan for its primary on-premises file storage volume. The file storage volume is mounted from an Internet Small Computer Systems Interface (iSCSI) device on a local storage server. The file storage volume holds hundreds of terabytes (TB) of data.

The company wants to ensure that end users retain immediate access to all file types from the on-premises

systems without experiencing latency.

Which solution will meet these requirements with the LEAST amount of change to the company's existing infrastructure?

- A. Provision an Amazon S3 File Gateway as a virtual machine (VM) that is hosted on premises. Set the local cache to 10 TB. Modify existing applications to access the files through the NFS protocol. To recover from a disaster, provision an Amazon EC2 instance and mount the S3 bucket that contains the files.
- B. Provision an AWS Storage Gateway tape gateway. Use a data backup solution to back up all existing data to a virtual tape library. Configure the data backup solution to run nightly after the initial backup is complete. To recover from a disaster, provision an Amazon EC2 instance and restore the data to an Amazon Elastic Block Store (Amazon EBS) volume from the volumes in the virtual tape library.
- C. Provision an AWS Storage Gateway Volume Gateway cached volume. Set the local cache to 10 TB. Mount the Volume Gateway cached volume to the existing file server by using iSCSI, and copy all files to the storage volume. Configure scheduled snapshots of the storage volume. To recover from a disaster, restore a snapshot to an Amazon Elastic Block Store (Amazon EBS) volume and attach the EBS volume to an Amazon EC2 instance.
- D. Provision an AWS Storage Gateway Volume Gateway stored volume with the same amount of disk space as the existing file storage volume. Mount the Volume Gateway stored volume to the existing file server by using iSCSI, and copy all files to the storage volume. Configure scheduled snapshots of the storage volume. To recover from a disaster, restore a snapshot to an Amazon Elastic Block Store (Amazon EBS) volume and attach the EBS volume to an Amazon EC2 instance. **Most Voted**

Correct Answer: D

Question #325

A company is hosting a web application from an Amazon S3 bucket. The application uses Amazon Cognito as an identity provider to authenticate users and return a JSON Web Token (JWT) that provides access to protected resources that are stored in another S3 bucket.

Upon deployment of the application, users report errors and are unable to access the protected content. A

solutions architect must resolve this issue by providing proper permissions so that users can access the protected content.

Which solution meets these requirements?

- A. Update the Amazon Cognito identity pool to assume the proper IAM role for access to the protected content. **Most Voted**
- B. Update the S3 ACL to allow the application to access the protected content.
- C. Redeploy the application to Amazon S3 to prevent eventually consistent reads in the S3 bucket from affecting the ability of users to access the protected content.
- D. Update the Amazon Cognito pool to use custom attribute mappings within the identity pool and grant users the proper permissions to access the protected content.

Correct Answer: A

Question #326

An image hosting company uploads its large assets to Amazon S3 Standard buckets. The company uses multipart upload in parallel by using S3 APIs and overwrites if the same object is uploaded again. For the first 30 days after upload, the objects will be accessed frequently. The objects will be used less frequently after 30 days, but the access patterns for each object will be inconsistent. The company must optimize its S3 storage costs while maintaining high availability and resiliency of stored assets.

Which combination of actions should a solutions architect recommend to meet these requirements? (Choose two.)

- A. Move assets to S3 Intelligent-Tiering after 30 days. **Most Voted**
- B. Configure an S3 Lifecycle policy to clean up incomplete multipart uploads. **Most VotedMost Voted**
- C. Configure an S3 Lifecycle policy to clean up expired object delete markers.
- D. Move assets to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days. **Most Voted**
- E. Move assets to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 30 days.

Correct Answer: AB

Question #327

A solutions architect must secure a VPC network that hosts Amazon EC2 instances. The EC2 instances contain highly sensitive data and run in a private subnet. According to company policy, the EC2 instances that run in the VPC can access only approved third-party software repositories on the internet for software product updates that use the third party's URL. Other internet traffic must be blocked.

Which solution meets these requirements?

- A. Update the route table for the private subnet to route the outbound traffic to an AWS Network Firewall firewall. Configure domain list rule groups. **Most Voted**
- B. Set up an AWS WAF web ACL. Create a custom set of rules that filter traffic requests based on source and destination IP address range sets.
- C. Implement strict inbound security group rules. Configure an outbound rule that allows traffic only to the authorized software repositories on the internet by specifying the URLs.
- D. Configure an Application Load Balancer (ALB) in front of the EC2 instances. Direct all outbound traffic to the ALB. Use a URL-based rule listener in the ALB's target group for outbound access to the internet.

Correct Answer: A

Question #328

A company is hosting a three-tier ecommerce application in the AWS Cloud. The company hosts the website on Amazon S3 and integrates the website with an API that handles sales requests. The company hosts the API on three Amazon EC2 instances behind an Application Load Balancer (ALB). The API consists of static and dynamic front-end content along with backend workers that process sales requests asynchronously.

The company is expecting a significant and sudden increase in the number of sales requests during events for the launch of new products.

What should a solutions architect recommend to ensure that all the requests are processed successfully?

- A. Add an Amazon CloudFront distribution for the dynamic content. Increase the number of EC2 instances to handle the increase in traffic.
- B. Add an Amazon CloudFront distribution for the static content. Place the EC2 instances in an Auto Scaling group to launch new instances based on network traffic. **Most Voted**
- C. Add an Amazon CloudFront distribution for the dynamic content. Add an Amazon ElastiCache instance in front of the ALB to reduce traffic for the API to handle.
- D. Add an Amazon CloudFront distribution for the static content. Add an Amazon Simple Queue Service (Amazon SQS) queue to receive requests from the website for later processing by the EC2 instances. **Most Voted**

Correct Answer: D

Question #329

A security audit reveals that Amazon EC2 instances are not being patched regularly. A solutions architect needs to provide a solution that will run regular security scans across a large fleet of EC2 instances. The solution should also patch the EC2 instances on a regular schedule and provide a report of each instance's patch status.

Which solution will meet these requirements?

- A. Set up Amazon Macie to scan the EC2 instances for software vulnerabilities. Set up a cron job on each EC2 instance to patch the instance on a regular schedule.
- B. Turn on Amazon GuardDuty in the account. Configure GuardDuty to scan the EC2 instances for software vulnerabilities. Set up AWS Systems Manager Session Manager to patch the EC2 instances on a regular schedule.
- C. Set up Amazon Detective to scan the EC2 instances for software vulnerabilities. Set up an Amazon EventBridge scheduled rule to patch the EC2 instances on a regular schedule.
- D. Turn on Amazon Inspector in the account. Configure Amazon Inspector to scan the EC2 instances for software vulnerabilities. Set up AWS Systems Manager Patch Manager to patch the EC2 instances on a regular schedule. **Most Voted**

Correct Answer: D

Question #330

A company is planning to store data on Amazon RDS DB instances. The company must encrypt the data at rest.

What should a solutions architect do to meet this requirement?

- A. Create a key in AWS Key Management Service (AWS KMS). Enable encryption for the DB instances. **Most Voted**
- B. Create an encryption key. Store the key in AWS Secrets Manager. Use the key to encrypt the DB instances.
- C. Generate a certificate in AWS Certificate Manager (ACM). Enable SSL/TLS on the DB instances by using the certificate.
- D. Generate a certificate in AWS Identity and Access Management (IAM). Enable SSL/TLS on the DB instances by using the certificate.

Correct Answer: A

Question #331

A company must migrate 20 TB of data from a data center to the AWS Cloud within 30 days. The company's network bandwidth is limited to 15 Mbps and cannot exceed 70% utilization.

What should a solutions architect do to meet these requirements?

- A. Use AWS Snowball. **Most Voted**
- B. Use AWS DataSync.
- C. Use a secure VPN connection.
- D. Use Amazon S3 Transfer Acceleration.

Correct Answer: A

Question #332

A company needs to provide its employees with secure access to confidential and sensitive files. The company wants to ensure that the files can be accessed only by authorized users. The files must be downloaded securely to the employees' devices.

The files are stored in an on-premises Windows file server. However, due to an increase in remote usage, the file server is running out of capacity.

Which solution will meet these requirements?

- A. Migrate the file server to an Amazon EC2 instance in a public subnet. Configure the security group to limit inbound traffic to the employees' IP addresses.
- B. Migrate the files to an Amazon FSx for Windows File Server file system. Integrate the Amazon FSx file system with the on-premises Active Directory. Configure AWS Client VPN. **Most Voted**
- C. Migrate the files to Amazon S3, and create a private VPC endpoint. Create a signed URL to allow download.
- D. Migrate the files to Amazon S3, and create a public VPC endpoint. Allow employees to sign on with AWS IAM Identity Center (AWS Single Sign-On).

Correct Answer: B

Question #333

A company's application runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The instances run in an Amazon EC2 Auto Scaling group across multiple Availability Zones. On the first day of every month at midnight, the application becomes much slower when the month-end financial calculation batch runs. This causes the CPU utilization of the EC2 instances to immediately peak to 100%, which disrupts the application.

What should a solutions architect recommend to ensure the application is able to handle the workload and avoid downtime?

- A. Configure an Amazon CloudFront distribution in front of the ALB.
- B. Configure an EC2 Auto Scaling simple scaling policy based on CPU utilization.

- C. Configure an EC2 Auto Scaling scheduled scaling policy based on the monthly schedule. **Most Voted**
- D. Configure Amazon ElastiCache to remove some of the workload from the EC2 instances.

Correct Answer: C

Question #334

A company wants to give a customer the ability to use on-premises Microsoft Active Directory to download files that are stored in Amazon S3. The customer's application uses an SFTP client to download the files.

Which solution will meet these requirements with the LEAST operational overhead and no changes to the customer's application?

- A. Set up AWS Transfer Family with SFTP for Amazon S3. Configure integrated Active Directory authentication. **Most Voted**
- B. Set up AWS Database Migration Service (AWS DMS) to synchronize the on-premises client with Amazon S3. Configure integrated Active Directory authentication.
- C. Set up AWS DataSync to synchronize between the on-premises location and the S3 location by using AWS IAM Identity Center (AWS Single Sign-On).
- D. Set up a Windows Amazon EC2 instance with SFTP to connect the on-premises client with Amazon S3. Integrate AWS Identity and Access Management (IAM).

Correct Answer: A

Question #335

A company is experiencing sudden increases in demand. The company needs to provision large Amazon EC2 instances from an Amazon Machine Image (AMI). The instances will run in an Auto Scaling group. The company needs a solution that provides minimum initialization latency to meet the demand.

Which solution meets these requirements?

- A. Use the `aws ec2 register-image` command to create an AMI from a snapshot. Use AWS Step Functions to replace the AMI in the Auto Scaling group.
- B. Enable Amazon Elastic Block Store (Amazon EBS) fast snapshot restore on a snapshot. Provision an AMI by using the snapshot. Replace the AMI in the Auto Scaling group with the new AMI. **Most Voted**
- C. Enable AMI creation and define lifecycle rules in Amazon Data Lifecycle Manager (Amazon DLM). Create an AWS Lambda function that modifies the AMI in the Auto Scaling group.
- D. Use Amazon EventBridge to invoke AWS Backup lifecycle policies that provision AMIs. Configure Auto Scaling group capacity limits as an event source in EventBridge.

Correct Answer: B

Question #336

A company hosts a multi-tier web application that uses an Amazon Aurora MySQL DB cluster for storage. The application tier is hosted on Amazon EC2 instances. The company's IT security guidelines mandate that the database credentials be encrypted and rotated every 14 days.

What should a solutions architect do to meet this requirement with the LEAST operational effort?

- A. Create a new AWS Key Management Service (AWS KMS) encryption key. Use AWS Secrets Manager to create a new secret that uses the KMS key with the appropriate credentials. Associate the secret with the Aurora DB cluster. Configure a custom rotation period of 14 days. **Most Voted**
- B. Create two parameters in AWS Systems Manager Parameter Store: one for the user name as a string parameter and one that uses the SecureString type for the password. Select AWS Key Management Service (AWS KMS) encryption for the password parameter, and load these parameters in the application tier. Implement an AWS Lambda function that rotates the password every 14 days.
- C. Store a file that contains the credentials in an AWS Key Management Service (AWS KMS) encrypted Amazon Elastic File System (Amazon EFS) file system. Mount the EFS file system in all EC2 instances of the application tier. Restrict the access to the file on the file system so that the application can read the file and that only super users can modify the file. Implement an AWS Lambda function that rotates the key in Aurora every 14 days and writes new credentials into the file.

- D. Store a file that contains the credentials in an AWS Key Management Service (AWS KMS) encrypted Amazon S3 bucket that the application uses to load the credentials. Download the file to the application regularly to ensure that the correct credentials are used. Implement an AWS Lambda function that rotates the Aurora credentials every 14 days and uploads these credentials to the file in the S3 bucket.

Correct Answer: A

Question #337

A company has deployed a web application on AWS. The company hosts the backend database on Amazon RDS for MySQL with a primary DB instance and five read replicas to support scaling needs. The read replicas must lag no more than 1 second behind the primary DB instance. The database routinely runs scheduled stored procedures.

As traffic on the website increases, the replicas experience additional lag during periods of peak load. A solutions architect must reduce the replication lag as much as possible. The solutions architect must minimize changes to the application code and must minimize ongoing operational overhead.

Which solution will meet these requirements?

- A. Migrate the database to Amazon Aurora MySQL. Replace the read replicas with Aurora Replicas, and configure Aurora Auto Scaling. Replace the stored procedures with Aurora MySQL native functions. **Most Voted**
- B. Deploy an Amazon ElastiCache for Redis cluster in front of the database. Modify the application to check the cache before the application queries the database. Replace the stored procedures with AWS Lambda functions.
- C. Migrate the database to a MySQL database that runs on Amazon EC2 instances. Choose large, compute optimized EC2 instances for all replica nodes. Maintain the stored procedures on the EC2 instances.
- D. Migrate the database to Amazon DynamoDB. Provision a large number of read capacity units (RCUs) to support the required throughput, and configure on-demand capacity scaling. Replace the stored procedures with DynamoDB streams.

Correct Answer: A

Question #338

A solutions architect must create a disaster recovery (DR) plan for a high-volume software as a service (SaaS) platform. All data for the platform is stored in an Amazon Aurora MySQL DB cluster.

The DR plan must replicate data to a secondary AWS Region.

Which solution will meet these requirements MOST cost-effectively?

- A. Use MySQL binary log replication to an Aurora cluster in the secondary Region. Provision one DB instance for the Aurora cluster in the secondary Region.
- B. Set up an Aurora global database for the DB cluster. When setup is complete, remove the DB instance from the secondary Region.
- C. Use AWS Database Migration Service (AWS DMS) to continuously replicate data to an Aurora cluster in the secondary Region. Remove the DB instance from the secondary Region.
- D. Set up an Aurora global database for the DB cluster. Specify a minimum of one DB instance in the secondary Region. **Most Voted**

Correct Answer: D

Question #339

A company has a custom application with embedded credentials that retrieves information from an Amazon RDS MySQL DB instance. Management says the application must be made more secure with the least amount of programming effort.

What should a solutions architect do to meet these requirements?

- A. Use AWS Key Management Service (AWS KMS) to create keys. Configure the application to load the database credentials from AWS KMS. Enable automatic key rotation.
- B. Create credentials on the RDS for MySQL database for the application user and store the credentials in AWS Secrets Manager. Configure the application to load the database credentials from Secrets Manager. Create an AWS Lambda function that rotates the credentials in Secret Manager.

- C. Create credentials on the RDS for MySQL database for the application user and store the credentials in AWS Secrets Manager. Configure the application to load the database credentials from Secrets Manager. Set up a credentials rotation schedule for the application user in the RDS for MySQL database using Secrets Manager. **Most Voted**
- D. Create credentials on the RDS for MySQL database for the application user and store the credentials in AWS Systems Manager Parameter Store. Configure the application to load the database credentials from Parameter Store. Set up a credentials rotation schedule for the application user in the RDS for MySQL database using Parameter Store.

Correct Answer: C

Question #340

A media company hosts its website on AWS. The website application's architecture includes a fleet of Amazon EC2 instances behind an Application Load Balancer (ALB) and a database that is hosted on Amazon Aurora. The company's cybersecurity team reports that the application is vulnerable to SQL injection.

How should the company resolve this issue?

- A. Use AWS WAF in front of the ALB. Associate the appropriate web ACLs with AWS WAF. **Most Voted**
- B. Create an ALB listener rule to reply to SQL injections with a fixed response.
- C. Subscribe to AWS Shield Advanced to block all SQL injection attempts automatically.
- D. Set up Amazon Inspector to block all SQL injection attempts automatically.

Correct Answer: A

Question #: 341

A company has an Amazon S3 data lake that is governed by AWS Lake Formation. The company wants to create a visualization in Amazon QuickSight by joining the data in the data lake with operational data that is stored in an Amazon Aurora MySQL database. The company wants to enforce column-level authorization so that the company's marketing team can access only a subset of columns in the database.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon EMR to ingest the data directly from the database to the QuickSight SPICE engine. Include only the required columns.
- B. Use AWS Glue Studio to ingest the data from the database to the S3 data lake. Attach an IAM policy to the QuickSight users to enforce column-level access control. Use Amazon S3 as the data source in QuickSight.
- C. Use AWS Glue Elastic Views to create a materialized view for the database in Amazon S3. Create an S3 bucket policy to enforce column-level access control for the QuickSight users. Use Amazon S3 as the data source in QuickSight.
- D. Use a Lake Formation blueprint to ingest the data from the database to the S3 data lake. Use Lake Formation to enforce column-level access control for the QuickSight users. Use Amazon Athena as the data source in QuickSight. **Most Voted**

Suggested Answer: D

Question #: 342

A transaction processing company has weekly scripted batch jobs that run on Amazon EC2 instances. The EC2 instances are in an Auto Scaling group. The number of transactions can vary, but the baseline CPU utilization that is noted on each run is at least 60%. The company needs to provision the capacity 30 minutes before the jobs run.

Currently, engineers complete this task by manually modifying the Auto Scaling group parameters. The company does not have the resources to analyze the required capacity trends for the Auto Scaling group counts. The company needs an automated way to modify the Auto Scaling group's desired capacity.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a dynamic scaling policy for the Auto Scaling group. Configure the policy to scale based on the CPU utilization metric. Set the target value for the metric to 60%.
- B. Create a scheduled scaling policy for the Auto Scaling group. Set the appropriate desired capacity, minimum capacity, and maximum capacity. Set the recurrence to weekly. Set the start time to 30 minutes before the batch jobs run.
- C. Create a predictive scaling policy for the Auto Scaling group. Configure the policy to scale based on forecast. Set the scaling metric to CPU utilization. Set the target value for the metric to 60%. In the policy, set the instances to pre-launch 30 minutes before the jobs run. **Most Voted**
- D. Create an Amazon EventBridge event to invoke an AWS Lambda function when the CPU utilization metric value for the Auto Scaling group reaches 60%. Configure the Lambda function to increase the Auto Scaling group's desired capacity and maximum capacity by 20%.

Suggested Answer: C

Question #: 343

A solutions architect is designing a company's disaster recovery (DR) architecture. The company has a MySQL database that runs on an Amazon EC2 instance in a private subnet with scheduled backup. The DR design needs to include multiple AWS Regions.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Migrate the MySQL database to multiple EC2 instances. Configure a standby EC2 instance in the DR Region. Turn on replication.
- B. Migrate the MySQL database to Amazon RDS. Use a Multi-AZ deployment. Turn on read replication for the primary DB instance in the different Availability Zones.
- C. Migrate the MySQL database to an Amazon Aurora global database. Host the primary DB cluster in the primary Region. Host the secondary DB cluster in the DR Region. **Most Voted**
- D. Store the scheduled backup of the MySQL database in an Amazon S3 bucket that is configured for S3 Cross-Region Replication (CRR). Use the data backup to restore the database in the DR Region.

Suggested Answer: C

Question #: 344

A company has a Java application that uses Amazon Simple Queue Service (Amazon SQS) to parse messages. The application cannot parse messages that are larger than 256 KB in size. The company wants to implement a solution to give the application the ability to parse messages as large as 50 MB.

Which solution will meet these requirements with the FEWEST changes to the code?

- A. Use the Amazon SQS Extended Client Library for Java to host messages that are larger than 256 KB in Amazon S3. **Most Voted**
- B. Use Amazon EventBridge to post large messages from the application instead of Amazon SQS.
- C. Change the limit in Amazon SQS to handle messages that are larger than 256 KB.
- D. Store messages that are larger than 256 KB in Amazon Elastic File System (Amazon EFS). Configure Amazon SQS to reference this location in the messages.

Suggested Answer: A

Question #: 345

A company wants to restrict access to the content of one of its main web applications and to protect the content by using authorization techniques available on AWS. The company wants to implement a serverless architecture and an authentication solution for fewer than 100 users. The solution needs to integrate with the main web application and serve web content globally. The solution must also scale as the company's user base grows while providing the lowest login latency possible.

Which solution will meet these requirements MOST cost-effectively?

- A. Use Amazon Cognito for authentication. Use Lambda@Edge for authorization. Use Amazon CloudFront to serve the web application globally. **Most Voted**

- B. Use AWS Directory Service for Microsoft Active Directory for authentication. Use AWS Lambda for authorization. Use an Application Load Balancer to serve the web application globally.
- C. Use Amazon Cognito for authentication. Use AWS Lambda for authorization. Use Amazon S3 Transfer Acceleration to serve the web application globally.
- D. Use AWS Directory Service for Microsoft Active Directory for authentication. Use Lambda@Edge for authorization. Use AWS Elastic Beanstalk to serve the web application globally.

Suggested Answer: A

Question #: 346

A company has an aging network-attached storage (NAS) array in its data center. The NAS array presents SMB shares and NFS shares to client workstations. The company does not want to purchase a new NAS array. The company also does not want to incur the cost of renewing the NAS array's support contract. Some of the data is accessed frequently, but much of the data is inactive.

A solutions architect needs to implement a solution that migrates the data to Amazon S3, uses S3 Lifecycle policies, and maintains the same look and feel for the client workstations. The solutions architect has identified AWS Storage Gateway as part of the solution.

Which type of storage gateway should the solutions architect provision to meet these requirements?

- A. Volume Gateway
- B. Tape Gateway
- C. Amazon FSx File Gateway
- D. Amazon S3 File Gateway **Most Voted**

Suggested Answer: D

Question #: 347

A company has an application that is running on Amazon EC2 instances. A solutions architect has standardized the company on a particular instance family and various instance sizes based on the current needs of the company.

The company wants to maximize cost savings for the application over the next 3 years. The company needs to be able to change the instance family and sizes in the next 6 months based on application popularity and usage.

Which solution will meet these requirements MOST cost-effectively?

- A. Compute Savings Plan **Most Voted**
- B. EC2 Instance Savings Plan
- C. Zonal Reserved Instances
- D. Standard Reserved Instances

Suggested Answer: A

Question #: 348

A company collects data from a large number of participants who use wearable devices. The company stores the data in an Amazon DynamoDB table and uses applications to analyze the data. The data workload is constant and predictable. The company wants to stay at or below its forecasted budget for DynamoDB.

Which solution will meet these requirements MOST cost-effectively?

- A. Use provisioned mode and DynamoDB Standard-Infrequent Access (DynamoDB Standard-IA). Reserve capacity for the forecasted workload.
- B. Use provisioned mode. Specify the read capacity units (RCUs) and write capacity units (WCUs). **Most Voted**
- C. Use on-demand mode. Set the read capacity units (RCUs) and write capacity units (WCUs) high enough to accommodate changes in the workload.
- D. Use on-demand mode. Specify the read capacity units (RCUs) and write capacity units (WCUs) with reserved capacity.

Suggested Answer: B

Question #: 349

A company stores confidential data in an Amazon Aurora PostgreSQL database in the ap-southeast-3 Region. The database is encrypted with an AWS Key Management Service (AWS KMS) customer managed key. The company was recently acquired and must securely share a backup of the database with the acquiring company's AWS account in ap-southeast-3.

What should a solutions architect do to meet these requirements?

- A. Create a database snapshot. Copy the snapshot to a new unencrypted snapshot. Share the new snapshot with the acquiring company's AWS account.
- B. Create a database snapshot. Add the acquiring company's AWS account to the KMS key policy. Share the snapshot with the acquiring company's AWS account. **Most Voted**
- C. Create a database snapshot that uses a different AWS managed KMS key. Add the acquiring company's AWS account to the KMS key alias. Share the snapshot with the acquiring company's AWS account.
- D. Create a database snapshot. Download the database snapshot. Upload the database snapshot to an Amazon S3 bucket. Update the S3 bucket policy to allow access from the acquiring company's AWS account.

Suggested Answer: B

Question #: 350

A company uses a 100 GB Amazon RDS for Microsoft SQL Server Single-AZ DB instance in the us-east-1 Region to store customer transactions. The company needs high availability and automatic recovery for the DB instance.

The company must also run reports on the RDS database several times a year. The report process causes transactions to take longer than usual to post to the customers' accounts. The company needs a solution that will improve the performance of the report process.

Which combination of steps will meet these requirements? (Choose two.)

- A. Modify the DB instance from a Single-AZ DB instance to a Multi-AZ deployment. **Most Voted**
- B. Take a snapshot of the current DB instance. Restore the snapshot to a new RDS deployment in another Availability Zone.
- C. Create a read replica of the DB instance in a different Availability Zone. Point all requests for reports to the read replica. **Most Voted**
- D. Migrate the database to RDS Custom.
- E. Use RDS Proxy to limit reporting requests to the maintenance window.

Suggested Answer: AC

Question #: 351

A company is moving its data management application to AWS. The company wants to transition to an event-driven architecture. The architecture needs to be more distributed and to use serverless concepts while performing the different aspects of the workflow. The company also wants to minimize operational overhead.

Which solution will meet these requirements?

- A. Build out the workflow in AWS Glue. Use AWS Glue to invoke AWS Lambda functions to process the workflow steps.
- B. Build out the workflow in AWS Step Functions. Deploy the application on Amazon EC2 instances. Use Step Functions to invoke the workflow steps on the EC2 instances.
- C. Build out the workflow in Amazon EventBridge. Use EventBridge to invoke AWS Lambda functions on a schedule to process the workflow steps.
- D. Build out the workflow in AWS Step Functions. Use Step Functions to create a state machine. Use the state machine to invoke AWS Lambda functions to process the workflow steps. **Most Voted**

Suggested Answer: D

Question #: 352

A company is designing the network for an online multi-player game. The game uses the UDP networking protocol and will be deployed in eight AWS Regions. The network architecture needs to minimize latency and packet loss to give end users a high-quality gaming experience.

Which solution will meet these requirements?

- A. Setup a transit gateway in each Region. Create inter-Region peering attachments between each transit gateway.
- B. Set up AWS Global Accelerator with UDP listeners and endpoint groups in each Region. **Most Voted**
- C. Set up Amazon CloudFront with UDP turned on. Configure an origin in each Region.
- D. Set up a VPC peering mesh between each Region. Turn on UDP for each VPC.

Suggested Answer: B

Question #: 353

A company hosts a three-tier web application on Amazon EC2 instances in a single Availability Zone. The web application uses a self-managed MySQL database that is hosted on an EC2 instance to store data in an Amazon Elastic Block Store (Amazon EBS) volume. The MySQL database currently uses a 1 TB Provisioned IOPS SSD (io2) EBS volume. The company expects traffic of 1,000 IOPS for both reads and writes at peak traffic.

The company wants to minimize any disruptions, stabilize performance, and reduce costs while retaining the capacity for double the IOPS. The company wants to move the database tier to a fully managed solution that is highly available and fault tolerant.

Which solution will meet these requirements MOST cost-effectively?

- A. Use a Multi-AZ deployment of an Amazon RDS for MySQL DB instance with an io2 Block Express EBS volume.
- B. Use a Multi-AZ deployment of an Amazon RDS for MySQL DB instance with a General Purpose SSD (gp2) EBS volume. **Most Voted**
- C. Use Amazon S3 Intelligent-Tiering access tiers.
- D. Use two large EC2 instances to host the database in active-passive mode.

Suggested Answer: B

Question #: 354

A company hosts a serverless application on AWS. The application uses Amazon API Gateway, AWS Lambda, and an Amazon RDS for PostgreSQL database. The company notices an increase in application errors that result from database connection timeouts during times of peak traffic or unpredictable traffic. The company needs a solution that reduces the application failures with the least amount of change to the code.

What should a solutions architect do to meet these requirements?

- A. Reduce the Lambda concurrency rate.
- B. Enable RDS Proxy on the RDS DB instance. **Most Voted**
- C. Resize the RDS DB instance class to accept more connections.
- D. Migrate the database to Amazon DynamoDB with on-demand scaling.

Suggested Answer: B

Question #: 355

A company is migrating an old application to AWS. The application runs a batch job every hour and is CPU intensive. The batch job takes 15 minutes on average with an on-premises server. The server has 64 virtual CPU (vCPU) and 512 GiB of memory.

Which solution will run the batch job within 15 minutes with the LEAST operational overhead?

- A. Use AWS Lambda with functional scaling.
- B. Use Amazon Elastic Container Service (Amazon ECS) with AWS Fargate.
- C. Use Amazon Lightsail with AWS Auto Scaling.
- D. Use AWS Batch on Amazon EC2. **Most Voted**

Suggested Answer: D

Question #: 356

A company stores its data objects in Amazon S3 Standard storage. A solutions architect has found that 75% of the data is rarely accessed after 30 days. The company needs all the data to remain immediately accessible with the same high availability and resiliency, but the company wants to minimize storage costs.

Which storage solution will meet these requirements?

- A. Move the data objects to S3 Glacier Deep Archive after 30 days.
- B. Move the data objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days. **Most Voted**
- C. Move the data objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 30 days.
- D. Move the data objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) immediately.

Suggested Answer: B

Question #: 357

A gaming company is moving its public scoreboard from a data center to the AWS Cloud. The company uses Amazon EC2 Windows Server instances behind an Application Load Balancer to host its dynamic application. The company needs a highly available storage solution for the application. The application consists of static files and dynamic server-side code.

Which combination of steps should a solutions architect take to meet these requirements? (Choose two.)

- A. Store the static files on Amazon S3. Use Amazon CloudFront to cache objects at the edge. **Most Voted**
- B. Store the static files on Amazon S3. Use Amazon ElastiCache to cache objects at the edge.
- C. Store the server-side code on Amazon Elastic File System (Amazon EFS). Mount the EFS volume on each EC2 instance to share the files.
- D. Store the server-side code on Amazon FSx for Windows File Server. Mount the FSx for Windows File Server volume on each EC2 instance to share the files. **Most Voted**
- E. Store the server-side code on a General Purpose SSD (gp2) Amazon Elastic Block Store (Amazon EBS) volume. Mount the EBS volume on each EC2 instance to share the files.

Suggested Answer: AD

Question #: 358

A social media company runs its application on Amazon EC2 instances behind an Application Load Balancer (ALB). The ALB is the origin for an Amazon CloudFront distribution. The application has more than a billion images stored in an Amazon S3 bucket and processes thousands of images each second. The company wants to resize the images dynamically and serve appropriate formats to clients.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Install an external image management library on an EC2 instance. Use the image management library to process the images.
- B. Create a CloudFront origin request policy. Use the policy to automatically resize images and to serve the appropriate format based on the User-Agent HTTP header in the request.
- C. Use a Lambda@Edge function with an external image management library. Associate the Lambda@Edge function with the CloudFront behaviors that serve the images. **Most Voted**
- D. Create a CloudFront response headers policy. Use the policy to automatically resize images and to serve the appropriate format based on the User-Agent HTTP header in the request.

Suggested Answer: C

Question #: 359

A hospital needs to store patient records in an Amazon S3 bucket. The hospital's compliance team must ensure that all protected health information (PHI) is encrypted in transit and at rest. The compliance team must administer the encryption key for data at rest.

Which solution will meet these requirements?

- A. Create a public SSL/TLS certificate in AWS Certificate Manager (ACM). Associate the certificate with Amazon S3. Configure default encryption for each S3 bucket to use server-side encryption with AWS KMS keys (SSE-KMS). Assign the compliance team to manage the KMS keys.
- B. Use the aws:SecureTransport condition on S3 bucket policies to allow only encrypted connections over HTTPS (TLS). Configure default encryption for each S3 bucket to use server-side encryption with S3 managed encryption keys (SSE-S3). Assign the compliance team to manage the SSE-S3 keys.
- C. Use the aws:SecureTransport condition on S3 bucket policies to allow only encrypted connections over HTTPS (TLS). Configure default encryption for each S3 bucket to use server-side encryption with AWS KMS keys (SSE-KMS). Assign the compliance team to manage the KMS keys. **Most Voted**
- D. Use the aws:SecureTransport condition on S3 bucket policies to allow only encrypted connections over HTTPS (TLS). Use Amazon Macie to protect the sensitive data that is stored in Amazon S3. Assign the compliance team to manage Macie.

Suggested Answer: C

Question #: 360

A company uses Amazon API Gateway to run a private gateway with two REST APIs in the same VPC. The BuyStock RESTful web service calls the CheckFunds RESTful web service to ensure that enough funds are available before a stock can be purchased. The company has noticed in the VPC flow logs that the BuyStock RESTful web service calls the CheckFunds RESTful web service over the internet instead of through the VPC. A solutions architect must implement a solution so that the APIs communicate through the VPC.

Which solution will meet these requirements with the FEWEST changes to the code?

- A. Add an X-API-Key header in the HTTP header for authorization.
- B. Use an interface endpoint. **Most Voted**
- C. Use a gateway endpoint.
- D. Add an Amazon Simple Queue Service (Amazon SQS) queue between the two REST APIs.

Suggested Answer: B

Question #: 361

A company hosts a multiplayer gaming application on AWS. The company wants the application to read data with sub-millisecond latency and run one-time queries on historical data.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon RDS for data that is frequently accessed. Run a periodic custom script to export the data to an Amazon S3 bucket.
- B. Store the data directly in an Amazon S3 bucket. Implement an S3 Lifecycle policy to move older data to S3 Glacier Deep Archive for long-term storage. Run one-time queries on the data in Amazon S3 by using Amazon Athena.
- C. Use Amazon DynamoDB with DynamoDB Accelerator (DAX) for data that is frequently accessed. Export the data to an Amazon S3 bucket by using DynamoDB table export. Run one-time queries on the data in Amazon S3 by using Amazon Athena. **Most Voted**
- D. Use Amazon DynamoDB for data that is frequently accessed. Turn on streaming to Amazon Kinesis Data Streams. Use Amazon Kinesis Data Firehose to read the data from Kinesis Data Streams. Store the records in an Amazon S3 bucket.

Suggested Answer: C

Question #: 362

A company uses a payment processing system that requires messages for a particular payment ID to be received in the same order that they were sent. Otherwise, the payments might be processed incorrectly.

Which actions should a solutions architect take to meet this requirement? (Choose two.)

- A. Write the messages to an Amazon DynamoDB table with the payment ID as the partition key.
- B. Write the messages to an Amazon Kinesis data stream with the payment ID as the partition key. **Most Voted**
- C. Write the messages to an Amazon ElastiCache for Memcached cluster with the payment ID as the key.
- D. Write the messages to an Amazon Simple Queue Service (Amazon SQS) queue. Set the message attribute to use the payment ID.
- E. Write the messages to an Amazon Simple Queue Service (Amazon SQS) FIFO queue. Set the message group to use the payment ID. **Most VotedMost Voted**

Suggested Answer: BE

Question #: 363

A company is building a game system that needs to send unique events to separate leaderboard, matchmaking, and authentication services concurrently. The company needs an AWS event-driven system that guarantees the order of the events.

Which solution will meet these requirements?

- A. Amazon EventBridge event bus
- B. Amazon Simple Notification Service (Amazon SNS) FIFO topics **Most Voted**
- C. Amazon Simple Notification Service (Amazon SNS) standard topics
- D. Amazon Simple Queue Service (Amazon SQS) FIFO queues

Suggested Answer: B

Question #: 364

A hospital is designing a new application that gathers symptoms from patients. The hospital has decided to use Amazon Simple Queue Service (Amazon SQS) and Amazon Simple Notification Service (Amazon SNS) in the architecture.

A solutions architect is reviewing the infrastructure design. Data must be encrypted at rest and in transit. Only authorized personnel of the hospital should be able to access the data.

Which combination of steps should the solutions architect take to meet these requirements? (Choose two.)

- A. Turn on server-side encryption on the SQS components. Update the default key policy to restrict key usage to a set of authorized principals.
- B. Turn on server-side encryption on the SNS components by using an AWS Key Management Service (AWS KMS) customer managed key. Apply a key policy to restrict key usage to a set of authorized principals. **Most Voted**
- C. Turn on encryption on the SNS components. Update the default key policy to restrict key usage to a set of authorized principals. Set a condition in the topic policy to allow only encrypted connections over TLS.
- D. Turn on server-side encryption on the SQS components by using an AWS Key Management Service (AWS KMS) customer managed key. Apply a key policy to restrict key usage to a set of authorized principals. Set a condition in the queue policy to allow only encrypted connections over TLS. **Most Voted**

- E. Turn on server-side encryption on the SQS components by using an AWS Key Management Service (AWS KMS) customer managed key. Apply an IAM policy to restrict key usage to a set of authorized principals. Set a condition in the queue policy to allow only encrypted connections over TLS.

Suggested Answer: BD

Question #: 365

A company runs a web application that is backed by Amazon RDS. A new database administrator caused data loss by accidentally editing information in a database table. To help recover from this type of incident, the company wants the ability to restore the database to its state from 5 minutes before any change within the last 30 days.

Which feature should the solutions architect include in the design to meet this requirement?

- A. Read replicas
- B. Manual snapshots
- C. Automated backups **Most Voted**
- D. Multi-AZ deployments

Suggested Answer: C

Question #: 366

A company's web application consists of an Amazon API Gateway API in front of an AWS Lambda function and an Amazon DynamoDB database. The Lambda function handles the business logic, and the DynamoDB table hosts the data. The application uses Amazon Cognito user pools to identify the individual users of the application. A solutions architect needs to update the application so that only users who have a subscription can access premium content.

Which solution will meet this requirement with the LEAST operational overhead?

- A. Enable API caching and throttling on the API Gateway API.
- B. Set up AWS WAF on the API Gateway API. Create a rule to filter users who have a subscription.

- C. Apply fine-grained IAM permissions to the premium content in the DynamoDB table.
- D. Implement API usage plans and API keys to limit the access of users who do not have a subscription. **Most Voted**

Suggested Answer: D

Question #: 367

A company is using Amazon Route 53 latency-based routing to route requests to its UDP-based application for users around the world. The application is hosted on redundant servers in the company's on-premises data centers in the United States, Asia, and Europe. The company's compliance requirements state that the application must be hosted on premises. The company wants to improve the performance and availability of the application.

What should a solutions architect do to meet these requirements?

- A. Configure three Network Load Balancers (NLBs) in the three AWS Regions to address the on-premises endpoints. Create an accelerator by using AWS Global Accelerator, and register the NLBs as its endpoints. Provide access to the application by using a CNAME that points to the accelerator DNS. **Most Voted**
- B. Configure three Application Load Balancers (ALBs) in the three AWS Regions to address the on-premises endpoints. Create an accelerator by using AWS Global Accelerator, and register the ALBs as its endpoints. Provide access to the application by using a CNAME that points to the accelerator DNS.
- C. Configure three Network Load Balancers (NLBs) in the three AWS Regions to address the on-premises endpoints. In Route 53, create a latency-based record that points to the three NLBs, and use it as an origin for an Amazon CloudFront distribution. Provide access to the application by using a CNAME that points to the CloudFront DNS.
- D. Configure three Application Load Balancers (ALBs) in the three AWS Regions to address the on-premises endpoints. In Route 53, create a latency-based record that points to the three ALBs, and use it as an origin for an Amazon CloudFront distribution. Provide access to the application by using a CNAME that points to the CloudFront DNS.

Suggested Answer: A

Question #: 368

A solutions architect wants all new users to have specific complexity requirements and mandatory rotation periods for IAM user passwords.

What should the solutions architect do to accomplish this?

- A. Set an overall password policy for the entire AWS account. **Most Voted**
- B. Set a password policy for each IAM user in the AWS account.
- C. Use third-party vendor software to set password requirements.
- D. Attach an Amazon CloudWatch rule to the Create_newuser event to set the password with the appropriate requirements.

Suggested Answer: A

Question #: 369

A company has migrated an application to Amazon EC2 Linux instances. One of these EC2 instances runs several 1-hour tasks on a schedule. These tasks were written by different teams and have no common programming language. The company is concerned about performance and scalability while these tasks run on a single instance. A solutions architect needs to implement a solution to resolve these concerns.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Batch to run the tasks as jobs. Schedule the jobs by using Amazon EventBridge (Amazon CloudWatch Events). **Most Voted**
- B. Convert the EC2 instance to a container. Use AWS App Runner to create the container on demand to run the tasks as jobs.
- C. Copy the tasks into AWS Lambda functions. Schedule the Lambda functions by using Amazon EventBridge (Amazon CloudWatch Events). **Most Voted**
- D. Create an Amazon Machine Image (AMI) of the EC2 instance that runs the tasks. Create an Auto Scaling group with the AMI to run multiple copies of the instance.

Suggested Answer: A

Question #: 370

A company runs a public three-tier web application in a VPC. The application runs on Amazon EC2 instances across multiple Availability Zones. The EC2 instances that run in private subnets need to communicate with a license server over the internet. The company needs a managed solution that minimizes operational maintenance.

Which solution meets these requirements?

- A. Provision a NAT instance in a public subnet. Modify each private subnet's route table with a default route that points to the NAT instance.
- B. Provision a NAT instance in a private subnet. Modify each private subnet's route table with a default route that points to the NAT instance.
- C. Provision a NAT gateway in a public subnet. Modify each private subnet's route table with a default route that points to the NAT gateway. **Most Voted**
- D. Provision a NAT gateway in a private subnet. Modify each private subnet's route table with a default route that points to the NAT gateway.

Suggested Answer: C

Question #: 371

A company needs to create an Amazon Elastic Kubernetes Service (Amazon EKS) cluster to host a digital media streaming application. The EKS cluster will use a managed node group that is backed by Amazon Elastic Block Store (Amazon EBS) volumes for storage. The company must encrypt all data at rest by using a customer managed key that is stored in AWS Key Management Service (AWS KMS).

Which combination of actions will meet this requirement with the LEAST operational overhead? (Choose two.)

- A. Use a Kubernetes plugin that uses the customer managed key to perform data encryption.

- B. After creation of the EKS cluster, locate the EBS volumes. Enable encryption by using the customer managed key.
- C. Enable EBS encryption by default in the AWS Region where the EKS cluster will be created. Select the customer managed key as the default key. **Most Voted**
- D. Create the EKS cluster. Create an IAM role that has a policy that grants permission to the customer managed key. Associate the role with the EKS cluster. **Most VotedMost Voted**
- E. Store the customer managed key as a Kubernetes secret in the EKS cluster. Use the customer managed key to encrypt the EBS volumes.

Suggested Answer: CD

Question #: 372

A company wants to migrate an Oracle database to AWS. The database consists of a single table that contains millions of geographic information systems (GIS) images that are high resolution and are identified by a geographic code.

When a natural disaster occurs, tens of thousands of images get updated every few minutes. Each geographic code has a single image or row that is associated with it. The company wants a solution that is highly available and scalable during such events.

Which solution meets these requirements MOST cost-effectively?

- A. Store the images and geographic codes in a database table. Use Oracle running on an Amazon RDS Multi-AZ DB instance.
- B. Store the images in Amazon S3 buckets. Use Amazon DynamoDB with the geographic code as the key and the image S3 URL as the value. **Most Voted**
- C. Store the images and geographic codes in an Amazon DynamoDB table. Configure DynamoDB Accelerator (DAX) during times of high load.
- D. Store the images in Amazon S3 buckets. Store geographic codes and image S3 URLs in a database table. Use Oracle running on an Amazon RDS Multi-AZ DB instance. **Most Voted**

Suggested Answer: B

Question #: 373

A company has an application that collects data from IoT sensors on automobiles. The data is streamed and stored in Amazon S3 through Amazon Kinesis Data Firehose. The data produces trillions of S3 objects each year. Each morning, the company uses the data from the previous 30 days to retrain a suite of machine learning (ML) models.

Four times each year, the company uses the data from the previous 12 months to perform analysis and train other ML models. The data must be available with minimal delay for up to 1 year. After 1 year, the data must be retained for archival purposes.

Which storage solution meets these requirements MOST cost-effectively?

- A. Use the S3 Intelligent-Tiering storage class. Create an S3 Lifecycle policy to transition objects to S3 Glacier Deep Archive after 1 year.
- B. Use the S3 Intelligent-Tiering storage class. Configure S3 Intelligent-Tiering to automatically move objects to S3 Glacier Deep Archive after 1 year.
- C. Use the S3 Standard-Infrequent Access (S3 Standard-IA) storage class. Create an S3 Lifecycle policy to transition objects to S3 Glacier Deep Archive after 1 year.
- D. Use the S3 Standard storage class. Create an S3 Lifecycle policy to transition objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days, and then to S3 Glacier Deep Archive after 1 year. **Most Voted**

Suggested Answer: D

Question #: 374

A company is running several business applications in three separate VPCs within the us-east-1 Region. The applications must be able to communicate between VPCs. The applications also must be able to consistently send hundreds of gigabytes of data each day to a latency-sensitive application that runs in a single on-premises data center.

A solutions architect needs to design a network connectivity solution that maximizes cost-effectiveness.

Which solution meets these requirements?

- A. Configure three AWS Site-to-Site VPN connections from the data center to AWS. Establish connectivity by configuring one VPN connection for each VPC.
- B. Launch a third-party virtual network appliance in each VPC. Establish an IPsec VPN tunnel between the data center and each virtual appliance.
- C. Set up three AWS Direct Connect connections from the data center to a Direct Connect gateway in us-east-1. Establish connectivity by configuring each VPC to use one of the Direct Connect connections.
- D. Set up one AWS Direct Connect connection from the data center to AWS. Create a transit gateway, and attach each VPC to the transit gateway. Establish connectivity between the Direct Connect connection and the transit gateway. **Most Voted**

Suggested Answer: D

Question #: 375

An ecommerce company is building a distributed application that involves several serverless functions and AWS services to complete order-processing tasks. These tasks require manual approvals as part of the workflow. A solutions architect needs to design an architecture for the order-processing application. The solution must be able to combine multiple AWS Lambda functions into responsive serverless applications. The solution also must orchestrate data and services that run on Amazon EC2 instances, containers, or on-premises servers.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Step Functions to build the application. **Most Voted**
- B. Integrate all the application components in an AWS Glue job.
- C. Use Amazon Simple Queue Service (Amazon SQS) to build the application.
- D. Use AWS Lambda functions and Amazon EventBridge events to build the application.

Suggested Answer: A

Question #: 376

A company has launched an Amazon RDS for MySQL DB instance. Most of the connections to the database come from serverless applications. Application traffic to the database changes significantly at random intervals. At times of high demand, users report that their applications experience database connection rejection errors.

Which solution will resolve this issue with the LEAST operational overhead?

- A. Create a proxy in RDS Proxy. Configure the users' applications to use the DB instance through RDS Proxy. **Most Voted**
- B. Deploy Amazon ElastiCache for Memcached between the users' applications and the DB instance.
- C. Migrate the DB instance to a different instance class that has higher I/O capacity. Configure the users' applications to use the new DB instance.
- D. Configure Multi-AZ for the DB instance. Configure the users' applications to switch between the DB instances.

Suggested Answer: A

Question #: 377

A company recently deployed a new auditing system to centralize information about operating system versions, patching, and installed software for Amazon EC2 instances. A solutions architect must ensure all instances provisioned through EC2 Auto Scaling groups successfully send reports to the auditing system as soon as they are launched and terminated.

Which solution achieves these goals MOST efficiently?

- A. Use a scheduled AWS Lambda function and run a script remotely on all EC2 instances to send data to the audit system.
- B. Use EC2 Auto Scaling lifecycle hooks to run a custom script to send data to the audit system when instances are launched and terminated. **Most Voted**
- C. Use an EC2 Auto Scaling launch configuration to run a custom script through user data to send data to the audit system when instances are launched and terminated.
- D. Run a custom script on the instance operating system to send data to the audit system. Configure the script to be invoked by the EC2 Auto Scaling group when the instance starts and is terminated.

Suggested Answer: B

Question #: 378

A company is developing a real-time multiplayer game that uses UDP for communications between the client and servers in an Auto Scaling group. Spikes in demand are anticipated during the day, so the game server platform must adapt accordingly. Developers want to store gamer scores and other non-relational data in a database solution that will scale without intervention.

Which solution should a solutions architect recommend?

- A. Use Amazon Route 53 for traffic distribution and Amazon Aurora Serverless for data storage.
- B. Use a Network Load Balancer for traffic distribution and Amazon DynamoDB on-demand for data storage. **Most Voted**
- C. Use a Network Load Balancer for traffic distribution and Amazon Aurora Global Database for data storage.
- D. Use an Application Load Balancer for traffic distribution and Amazon DynamoDB global tables for data storage.

Suggested Answer: B

Question #: 379

A company hosts a frontend application that uses an Amazon API Gateway API backend that is integrated with AWS Lambda. When the API receives requests, the Lambda function loads many libraries. Then the Lambda function connects to an Amazon RDS database, processes the data, and returns the data to the frontend application. The company wants to ensure that response latency is as low as possible for all its users with the fewest number of changes to the company's operations.

Which solution will meet these requirements?

- A. Establish a connection between the frontend application and the database to make queries faster by bypassing the API.
- B. Configure provisioned concurrency for the Lambda function that handles the requests. **Most Voted**

- C. Cache the results of the queries in Amazon S3 for faster retrieval of similar datasets.
- D. Increase the size of the database to increase the number of connections Lambda can establish at one time.

Suggested Answer: B

Question #: 380

A company is migrating its on-premises workload to the AWS Cloud. The company already uses several Amazon EC2 instances and Amazon RDS DB instances. The company wants a solution that automatically starts and stops the EC2 instances and DB instances outside of business hours. The solution must minimize cost and infrastructure maintenance.

Which solution will meet these requirements?

- A. Scale the EC2 instances by using elastic resize. Scale the DB instances to zero outside of business hours.
- B. Explore AWS Marketplace for partner solutions that will automatically start and stop the EC2 instances and DB instances on a schedule.
- C. Launch another EC2 instance. Configure a crontab schedule to run shell scripts that will start and stop the existing EC2 instances and DB instances on a schedule.
- D. Create an AWS Lambda function that will start and stop the EC2 instances and DB instances. Configure Amazon EventBridge to invoke the Lambda function on a schedule. **Most Voted**

Suggested Answer: D

Question #: 381

A company hosts a three-tier web application that includes a PostgreSQL database. The database stores the metadata from documents. The company searches the metadata for key terms to retrieve documents that the company reviews in a report each month. The documents are stored in Amazon S3. The documents are usually written only once, but they are updated frequently.

The reporting process takes a few hours with the use of relational queries. The reporting process must not prevent any document modifications or the addition of new documents. A solutions architect needs to implement a solution to speed up the reporting process.

Which solution will meet these requirements with the LEAST amount of change to the application code?

- A. Set up a new Amazon DocumentDB (with MongoDB compatibility) cluster that includes a read replica. Scale the read replica to generate the reports.
- B. Set up a new Amazon Aurora PostgreSQL DB cluster that includes an Aurora Replica. Issue queries to the Aurora Replica to generate the reports. **Most Voted**
- C. Set up a new Amazon RDS for PostgreSQL Multi-AZ DB instance. Configure the reporting module to query the secondary RDS node so that the reporting module does not affect the primary node.
- D. Set up a new Amazon DynamoDB table to store the documents. Use a fixed write capacity to support new document entries. Automatically scale the read capacity to support the reports.

Suggested Answer: B

Question #: 382

A company has a three-tier application on AWS that ingests sensor data from its users' devices. The traffic flows through a Network Load Balancer (NLB), then to Amazon EC2 instances for the web tier, and finally to EC2 instances for the application tier. The application tier makes calls to a database.

What should a solutions architect do to improve the security of the data in transit?

- A. Configure a TLS listener. Deploy the server certificate on the NLB. **Most Voted**
- B. Configure AWS Shield Advanced. Enable AWS WAF on the NLB.
- C. Change the load balancer to an Application Load Balancer (ALB). Enable AWS WAF on the ALB.
- D. Encrypt the Amazon Elastic Block Store (Amazon EBS) volume on the EC2 instances by using AWS Key Management Service (AWS KMS).

Suggested Answer: A

Question #: 383

A company is planning to migrate a commercial off-the-shelf application from its on-premises data center to AWS. The software has a software licensing model using sockets and cores with predictable capacity and uptime requirements. The company wants to use its existing licenses, which were purchased earlier this year.

Which Amazon EC2 pricing option is the MOST cost-effective?

- A. Dedicated Reserved Hosts **Most Voted**
- B. Dedicated On-Demand Hosts
- C. Dedicated Reserved Instances
- D. Dedicated On-Demand Instances

Suggested Answer: A

Question #: 384

A company runs an application on Amazon EC2 Linux instances across multiple Availability Zones. The application needs a storage layer that is highly available and Portable Operating System Interface (POSIX)-compliant. The storage layer must provide maximum data durability and must be shareable across the EC2 instances. The data in the storage layer will be accessed frequently for the first 30 days and will be accessed infrequently after that time.

Which solution will meet these requirements MOST cost-effectively?

- A. Use the Amazon S3 Standard storage class. Create an S3 Lifecycle policy to move infrequently accessed data to S3 Glacier.
- B. Use the Amazon S3 Standard storage class. Create an S3 Lifecycle policy to move infrequently accessed data to S3 Standard-Infrequent Access (S3 Standard-IA).

- C. Use the Amazon Elastic File System (Amazon EFS) Standard storage class. Create a lifecycle management policy to move infrequently accessed data to EFS Standard-Infrequent Access (EFS Standard-IA). **Most Voted**
- D. Use the Amazon Elastic File System (Amazon EFS) One Zone storage class. Create a lifecycle management policy to move infrequently accessed data to EFS One Zone-Infrequent Access (EFS One Zone-IA).

Suggested Answer: C

Question #: 385

A solutions architect is creating a new VPC design. There are two public subnets for the load balancer, two private subnets for web servers, and two private subnets for MySQL. The web servers use only HTTPS. The solutions architect has already created a security group for the load balancer allowing port 443 from 0.0.0.0/0. Company policy requires that each resource has the least access required to still be able to perform its tasks.

Which additional configuration strategy should the solutions architect use to meet these requirements?

- A. Create a security group for the web servers and allow port 443 from 0.0.0.0/0. Create a security group for the MySQL servers and allow port 3306 from the web servers security group.
- B. Create a network ACL for the web servers and allow port 443 from 0.0.0.0/0. Create a network ACL for the MySQL servers and allow port 3306 from the web servers security group.
- C. Create a security group for the web servers and allow port 443 from the load balancer. Create a security group for the MySQL servers and allow port 3306 from the web servers security group. **Most Voted**
- D. Create a network ACL for the web servers and allow port 443 from the load balancer. Create a network ACL for the MySQL servers and allow port 3306 from the web servers security group.

Suggested Answer: C

Question #: 386

An ecommerce company is running a multi-tier application on AWS. The front-end and backend tiers both run on Amazon EC2, and the database runs on Amazon RDS for MySQL. The backend tier communicates with the RDS instance. There are frequent calls to return identical datasets from the database that are causing performance slowdowns.

Which action should be taken to improve the performance of the backend?

- A. Implement Amazon SNS to store the database calls.
- B. Implement Amazon ElastiCache to cache the large datasets. **Most Voted**
- C. Implement an RDS for MySQL read replica to cache database calls.
- D. Implement Amazon Kinesis Data Firehose to stream the calls to the database.

Suggested Answer: B

Question #: 387

A new employee has joined a company as a deployment engineer. The deployment engineer will be using AWS CloudFormation templates to create multiple AWS resources. A solutions architect wants the deployment engineer to perform job activities while following the principle of least privilege.

Which combination of actions should the solutions architect take to accomplish this goal? (Choose two.)

- A. Have the deployment engineer use AWS account root user credentials for performing AWS CloudFormation stack operations.
- B. Create a new IAM user for the deployment engineer and add the IAM user to a group that has the PowerUsers IAM policy attached.
- C. Create a new IAM user for the deployment engineer and add the IAM user to a group that has the AdministratorAccess IAM policy attached.
- D. Create a new IAM user for the deployment engineer and add the IAM user to a group that has an IAM policy that allows AWS CloudFormation actions only. **Most Voted**
- E. Create an IAM role for the deployment engineer to explicitly define the permissions specific to the AWS CloudFormation stack and launch stacks using that IAM role. **Most Voted**

Suggested Answer: DE

Question #: 388

A company is deploying a two-tier web application in a VPC. The web tier is using an Amazon EC2 Auto Scaling group with public subnets that span multiple Availability Zones. The database tier consists of an Amazon RDS for MySQL DB instance in separate private subnets. The web tier requires access to the database to retrieve product information.

The web application is not working as intended. The web application reports that it cannot connect to the database. The database is confirmed to be up and running. All configurations for the network ACLs, security groups, and route tables are still in their default states.

What should a solutions architect recommend to fix the application?

- A. Add an explicit rule to the private subnet's network ACL to allow traffic from the web tier's EC2 instances.
- B. Add a route in the VPC route table to allow traffic between the web tier's EC2 instances and the database tier.
- C. Deploy the web tier's EC2 instances and the database tier's RDS instance into two separate VPCs, and configure VPC peering.
- D. Add an inbound rule to the security group of the database tier's RDS instance to allow traffic from the web tiers security group. **Most Voted**

Suggested Answer: D

Question #: 389

A company has a large dataset for its online advertising business stored in an Amazon RDS for MySQL DB instance in a single Availability Zone. The company wants business reporting queries to run without impacting the write operations to the production DB instance.

Which solution meets these requirements?

- A. Deploy RDS read replicas to process the business reporting queries. **Most Voted**
- B. Scale out the DB instance horizontally by placing it behind an Elastic Load Balancer.
- C. Scale up the DB instance to a larger instance type to handle write operations and queries.
- D. Deploy the DB instance in multiple Availability Zones to process the business reporting queries.

Suggested Answer:A

Question #: 390

A company hosts a three-tier ecommerce application on a fleet of Amazon EC2 instances. The instances run in an Auto Scaling group behind an Application Load Balancer (ALB). All ecommerce data is stored in an Amazon RDS for MariaDB Multi-AZ DB instance.

The company wants to optimize customer session management during transactions. The application must store session data durably.

Which solutions will meet these requirements? (Choose two.)

- A. Turn on the sticky sessions feature (session affinity) on the ALB. **Most Voted**
- B. Use an Amazon DynamoDB table to store customer session information.
- C. Deploy an Amazon Cognito user pool to manage user session information.
- D. Deploy an Amazon ElastiCache for Redis cluster to store customer session information. **Most Voted**
- E. Use AWS Systems Manager Application Manager in the application to manage user session information.

Suggested Answer: AD

Question #: 391

A company needs a backup strategy for its three-tier stateless web application. The web application runs on Amazon EC2 instances in an Auto Scaling group with a dynamic scaling policy that is configured to respond to scaling events. The database tier runs on Amazon RDS for PostgreSQL. The web application does not require temporary local storage on the EC2 instances. The company's recovery point objective (RPO) is 2 hours.

The backup strategy must maximize scalability and optimize resource utilization for this environment.

Which solution will meet these requirements?

- A. Take snapshots of Amazon Elastic Block Store (Amazon EBS) volumes of the EC2 instances and database every 2 hours to meet the RPO.
- B. Configure a snapshot lifecycle policy to take Amazon Elastic Block Store (Amazon EBS) snapshots. Enable automated backups in Amazon RDS to meet the RPO. **Most Voted**
- C. Retain the latest Amazon Machine Images (AMIs) of the web and application tiers. Enable automated backups in Amazon RDS and use point-in-time recovery to meet the RPO. **Most Voted**
- D. Take snapshots of Amazon Elastic Block Store (Amazon EBS) volumes of the EC2 instances every 2 hours. Enable automated backups in Amazon RDS and use point-in-time recovery to meet the RPO.

Suggested Answer: C

Question #: 392

A company wants to deploy a new public web application on AWS. The application includes a web server tier that uses Amazon EC2 instances. The application also includes a database tier that uses an Amazon RDS for MySQL DB instance.

The application must be secure and accessible for global customers that have dynamic IP addresses.

How should a solutions architect configure the security groups to meet these requirements?

- A. Configure the security group for the web servers to allow inbound traffic on port 443 from 0.0.0.0/0. Configure the security group for the DB instance to allow inbound traffic on port 3306 from the security group of the web servers. **Most Voted**
- B. Configure the security group for the web servers to allow inbound traffic on port 443 from the IP addresses of the customers. Configure the security group for the DB instance to allow inbound traffic on port 3306 from the security group of the web servers.
- C. Configure the security group for the web servers to allow inbound traffic on port 443 from the IP addresses of the customers. Configure the security group for the DB instance to allow inbound traffic on port 3306 from the IP addresses of the customers.
- D. Configure the security group for the web servers to allow inbound traffic on port 443 from 0.0.0.0/0. Configure the security group for the DB instance to allow inbound traffic on port 3306 from 0.0.0.0/0.

Suggested Answer: A

Question #: 393

A payment processing company records all voice communication with its customers and stores the audio files in an Amazon S3 bucket. The company needs to capture the text from the audio files. The company must remove from the text any personally identifiable information (PII) that belongs to customers.

What should a solutions architect do to meet these requirements?

- A. Process the audio files by using Amazon Kinesis Video Streams. Use an AWS Lambda function to scan for known PII patterns.
- B. When an audio file is uploaded to the S3 bucket, invoke an AWS Lambda function to start an Amazon Textract task to analyze the call recordings.
- C. Configure an Amazon Transcribe transcription job with PII redaction turned on. When an audio file is uploaded to the S3 bucket, invoke an AWS Lambda function to start the transcription job. Store the output in a separate S3 bucket. **Most Voted**
- D. Create an Amazon Connect contact flow that ingests the audio files with transcription turned on. Embed an AWS Lambda function to scan for known PII patterns. Use Amazon EventBridge to start the contact flow when an audio file is uploaded to the S3 bucket.

Suggested Answer: C

Question #: 394

A company is running a multi-tier ecommerce web application in the AWS Cloud. The application runs on Amazon EC2 instances with an Amazon RDS for MySQL Multi-AZ DB instance. Amazon RDS is configured with the latest generation DB instance with 2,000 GB of storage in a General Purpose SSD (gp3) Amazon Elastic Block Store (Amazon EBS) volume. The database performance affects the application during periods of high demand.

A database administrator analyzes the logs in Amazon CloudWatch Logs and discovers that the application performance always degrades when the number of read and write IOPS is higher than 20,000.

What should a solutions architect do to improve the application performance?

- A. Replace the volume with a magnetic volume.
- B. Increase the number of IOPS on the gp3 volume.
- C. Replace the volume with a Provisioned IOPS SSD (io2) volume.
- D. Replace the 2,000 GB gp3 volume with two 1,000 GB gp3 volumes. **Most Voted**

Suggested Answer: D

Question #: 395

An IAM user made several configuration changes to AWS resources in their company's account during a production deployment last week. A solutions architect learned that a couple of security group rules are not configured as desired. The solutions architect wants to confirm which IAM user was responsible for making changes.

Which service should the solutions architect use to find the desired information?

- A. Amazon GuardDuty
- B. Amazon Inspector
- C. AWS CloudTrail **Most Voted**
- D. AWS Config

Suggested Answer: C

Question #: 396

A company has implemented a self-managed DNS service on AWS. The solution consists of the following:

- Amazon EC2 instances in different AWS Regions
- Endpoints of a standard accelerator in AWS Global Accelerator

The company wants to protect the solution against DDoS attacks.

What should a solutions architect do to meet this requirement?

- A. Subscribe to AWS Shield Advanced. Add the accelerator as a resource to protect. **Most Voted**
- B. Subscribe to AWS Shield Advanced. Add the EC2 instances as resources to protect.
- C. Create an AWS WAF web ACL that includes a rate-based rule. Associate the web ACL with the accelerator.
- D. Create an AWS WAF web ACL that includes a rate-based rule. Associate the web ACL with the EC2 instances.

Suggested Answer: A

Question #: 397

An ecommerce company needs to run a scheduled daily job to aggregate and filter sales records for analytics. The company stores the sales records in an Amazon S3 bucket. Each object can be up to 10 GB in size. Based on the number of sales events, the job can take up to an hour to complete. The CPU and memory usage of the job are constant and are known in advance.

A solutions architect needs to minimize the amount of operational effort that is needed for the job to run.

Which solution meets these requirements?

- A. Create an AWS Lambda function that has an Amazon EventBridge notification. Schedule the EventBridge event to run once a day.
- B. Create an AWS Lambda function. Create an Amazon API Gateway HTTP API, and integrate the API with the function. Create an Amazon EventBridge scheduled event that calls the API and invokes the function.
- C. Create an Amazon Elastic Container Service (Amazon ECS) cluster with an AWS Fargate launch type. Create an Amazon EventBridge scheduled event that launches an ECS task on the cluster to run the job. **Most Voted**

- D. Create an Amazon Elastic Container Service (Amazon ECS) cluster with an Amazon EC2 launch type and an Auto Scaling group with at least one EC2 instance. Create an Amazon EventBridge scheduled event that launches an ECS task on the cluster to run the job.

Suggested Answer: C

Question #: 398

A company needs to transfer 600 TB of data from its on-premises network-attached storage (NAS) system to the AWS Cloud. The data transfer must be complete within 2 weeks. The data is sensitive and must be encrypted in transit. The company's internet connection can support an upload speed of 100 Mbps.

Which solution meets these requirements MOST cost-effectively?

- A. Use Amazon S3 multi-part upload functionality to transfer the files over HTTPS.
- B. Create a VPN connection between the on-premises NAS system and the nearest AWS Region. Transfer the data over the VPN connection.
- C. Use the AWS Snow Family console to order several AWS Snowball Edge Storage Optimized devices. Use the devices to transfer the data to Amazon S3. **Most Voted**
- D. Set up a 10 Gbps AWS Direct Connect connection between the company location and the nearest AWS Region. Transfer the data over a VPN connection into the Region to store the data in Amazon S3.

Suggested Answer: C

Question #: 399

A financial company hosts a web application on AWS. The application uses an Amazon API Gateway Regional API endpoint to give users the ability to retrieve current stock prices. The company's security team has noticed an increase in the number of API requests. The security team is concerned that HTTP flood attacks might take the application offline.

A solutions architect must design a solution to protect the application from this type of attack.

Which solution meets these requirements with the LEAST operational overhead?

- A. Create an Amazon CloudFront distribution in front of the API Gateway Regional API endpoint with a maximum TTL of 24 hours.
- B. Create a Regional AWS WAF web ACL with a rate-based rule. Associate the web ACL with the API Gateway stage. **Most Voted**
- C. Use Amazon CloudWatch metrics to monitor the Count metric and alert the security team when the predefined rate is reached.
- D. Create an Amazon CloudFront distribution with Lambda@Edge in front of the API Gateway Regional API endpoint. Create an AWS Lambda function to block requests from IP addresses that exceed the predefined rate.

Suggested Answer: B

Question #: 400

A meteorological startup company has a custom web application to sell weather data to its users online. The company uses Amazon DynamoDB to store its data and wants to build a new service that sends an alert to the managers of four internal teams every time a new weather event is recorded. The company does not want this new service to affect the performance of the current application.

What should a solutions architect do to meet these requirements with the LEAST amount of operational overhead?

- A. Use DynamoDB transactions to write new event data to the table. Configure the transactions to notify internal teams.
- B. Have the current application publish a message to four Amazon Simple Notification Service (Amazon SNS) topics. Have each team subscribe to one topic.
- C. Enable Amazon DynamoDB Streams on the table. Use triggers to write to a single Amazon Simple Notification Service (Amazon SNS) topic to which the teams can subscribe. **Most Voted**
- D. Add a custom attribute to each record to flag new items. Write a cron job that scans the table every minute for items that are new and notifies an Amazon Simple Queue Service (Amazon SQS) queue to which the teams can subscribe.

Suggested Answer: C

Question #: 401

A company wants to use the AWS Cloud to make an existing application highly available and resilient. The current version of the application resides in the company's data center. The application recently experienced data loss after a database server crashed because of an unexpected power outage.

The company needs a solution that avoids any single points of failure. The solution must give the application the ability to scale to meet user demand.

Which solution will meet these requirements?

- A. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group across multiple Availability Zones. Use an Amazon RDS DB instance in a Multi-AZ configuration. **Most Voted**
- B. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group in a single Availability Zone. Deploy the database on an EC2 instance. Enable EC2 Auto Recovery.
- C. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group across multiple Availability Zones. Use an Amazon RDS DB instance with a read replica in a single Availability Zone. Promote the read replica to replace the primary DB instance if the primary DB instance fails.
- D. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group across multiple Availability Zones. Deploy the primary and secondary database servers on EC2 instances across multiple Availability Zones. Use Amazon Elastic Block Store (Amazon EBS) Multi-Attach to create shared storage between the instances.

Suggested Answer: A

Question #: 401

A company wants to use the AWS Cloud to make an existing application highly available and resilient. The current version of the application resides in the company's data center. The application recently experienced data loss after a database server crashed because of an unexpected power outage.

The company needs a solution that avoids any single points of failure. The solution must give the application the ability to scale to meet user demand.

Which solution will meet these requirements?

- A. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group across multiple Availability Zones. Use an Amazon RDS DB instance in a Multi-AZ configuration. **Most Voted**
- B. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group in a single Availability Zone. Deploy the database on an EC2 instance. Enable EC2 Auto Recovery.
- C. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group across multiple Availability Zones. Use an Amazon RDS DB instance with a read replica in a single Availability Zone. Promote the read replica to replace the primary DB instance if the primary DB instance fails.
- D. Deploy the application servers by using Amazon EC2 instances in an Auto Scaling group across multiple Availability Zones. Deploy the primary and secondary database servers on EC2 instances across multiple Availability Zones. Use Amazon Elastic Block Store (Amazon EBS) Multi-Attach to create shared storage between the instances.

Suggested Answer: A

Question #: 403

A developer has an application that uses an AWS Lambda function to upload files to Amazon S3 and needs the required permissions to perform the task. The developer already has an IAM user with valid IAM credentials required for Amazon S3.

What should a solutions architect do to grant the permissions?

- A. Add required IAM permissions in the resource policy of the Lambda function.
- B. Create a signed request using the existing IAM credentials in the Lambda function.
- C. Create a new IAM user and use the existing IAM credentials in the Lambda function.
- D. Create an IAM execution role with the required permissions and attach the IAM role to the Lambda function. **Most Voted**

Suggested Answer: D

Question #: 404

A company has deployed a serverless application that invokes an AWS Lambda function when new documents are uploaded to an Amazon S3 bucket. The application uses the Lambda function to process the documents. After a recent marketing campaign, the company noticed that the application did not process many of the documents.

What should a solutions architect do to improve the architecture of this application?

- A. Set the Lambda function's runtime timeout value to 15 minutes.
- B. Configure an S3 bucket replication policy. Stage the documents in the S3 bucket for later processing.
- C. Deploy an additional Lambda function. Load balance the processing of the documents across the two Lambda functions.
- D. Create an Amazon Simple Queue Service (Amazon SQS) queue. Send the requests to the queue. Configure the queue as an event source for Lambda. **Most Voted**

Suggested Answer: D

Question #: 405

A solutions architect is designing the architecture for a software demonstration environment. The environment will run on Amazon EC2 instances in an Auto Scaling group behind an Application Load Balancer (ALB). The system will experience significant increases in traffic during working hours but is not required to operate on weekends.

Which combination of actions should the solutions architect take to ensure that the system can scale to meet demand? (Choose two.)

- A. Use AWS Auto Scaling to adjust the ALB capacity based on request rate. **Most Voted**
- B. Use AWS Auto Scaling to scale the capacity of the VPC internet gateway.
- C. Launch the EC2 instances in multiple AWS Regions to distribute the load across Regions.
- D. Use a target tracking scaling policy to scale the Auto Scaling group based on instance CPU utilization. **Most Voted**

- E. Use scheduled scaling to change the Auto Scaling group minimum, maximum, and desired capacity to zero for weekends. Revert to the default values at the start of the week. **Most VotedMost Voted**

Suggested Answer: D E

Question #: 406

A solutions architect is designing a two-tiered architecture that includes a public subnet and a database subnet. The web servers in the public subnet must be open to the internet on port 443. The Amazon RDS for MySQL DB instance in the database subnet must be accessible only to the web servers on port 3306.

Which combination of steps should the solutions architect take to meet these requirements? (Choose two.)

- A. Create a network ACL for the public subnet. Add a rule to deny outbound traffic to 0.0.0.0/0 on port 3306.
- B. Create a security group for the DB instance. Add a rule to allow traffic from the public subnet CIDR block on port 3306.
- C. Create a security group for the web servers in the public subnet. Add a rule to allow traffic from 0.0.0.0/0 on port 443. **Most Voted**
- D. Create a security group for the DB instance. Add a rule to allow traffic from the web servers' security group on port 3306. **Most Voted**
- E. Create a security group for the DB instance. Add a rule to deny all traffic except traffic from the web servers' security group on port 3306.

Suggested Answer: CD

Question #: 407

A company is implementing a shared storage solution for a gaming application that is hosted in the AWS Cloud. The company needs the ability to use Lustre clients to access data. The solution must be fully managed.

Which solution meets these requirements?

- A. Create an AWS DataSync task that shares the data as a mountable file system. Mount the file system to the application server.

- B. Create an AWS Storage Gateway file gateway. Create a file share that uses the required client protocol. Connect the application server to the file share.
- C. Create an Amazon Elastic File System (Amazon EFS) file system, and configure it to support Lustre. Attach the file system to the origin server. Connect the application server to the file system.
- D. Create an Amazon FSx for Lustre file system. Attach the file system to the origin server. Connect the application server to the file system. **Most Voted**

Suggested Answer: D

Question #: 408

A company runs an application that receives data from thousands of geographically dispersed remote devices that use UDP. The application processes the data immediately and sends a message back to the device if necessary. No data is stored.

The company needs a solution that minimizes latency for the data transmission from the devices. The solution also must provide rapid failover to another AWS Region.

Which solution will meet these requirements?

- A. Configure an Amazon Route 53 failover routing policy. Create a Network Load Balancer (NLB) in each of the two Regions. Configure the NLB to invoke an AWS Lambda function to process the data.
- B. Use AWS Global Accelerator. Create a Network Load Balancer (NLB) in each of the two Regions as an endpoint. Create an Amazon Elastic Container Service (Amazon ECS) cluster with the Fargate launch type. Create an ECS service on the cluster. Set the ECS service as the target for the NLB to process the data in Amazon ECS. **Most Voted**
- C. Use AWS Global Accelerator. Create an Application Load Balancer (ALB) in each of the two Regions as an endpoint. Create an Amazon Elastic Container Service (Amazon ECS) cluster with the Fargate launch type. Create an ECS service on the cluster. Set the ECS service as the target for the ALB. Process the data in Amazon ECS.
- D. Configure an Amazon Route 53 failover routing policy. Create an Application Load Balancer (ALB) in each of the two Regions. Create an Amazon Elastic Container Service (Amazon ECS) cluster with the Fargate launch

type. Create an ECS service on the cluster. Set the ECS service as the target for the ALB. Process the data in Amazon ECS.

Suggested Answer: B

Question #: 409

A solutions architect must migrate a Windows Internet Information Services (IIS) web application to AWS. The application currently relies on a file share hosted in the user's on-premises network-attached storage (NAS). The solutions architect has proposed migrating the IIS web servers to Amazon EC2 instances in multiple Availability Zones that are connected to the storage solution, and configuring an Elastic Load Balancer attached to the instances.

Which replacement to the on-premises file share is MOST resilient and durable?

- A. Migrate the file share to Amazon RDS.
- B. Migrate the file share to AWS Storage Gateway.
- C. Migrate the file share to Amazon FSx for Windows File Server. **Most Voted**
- D. Migrate the file share to Amazon Elastic File System (Amazon EFS).

Suggested Answer: C

Question #: 410

A company is deploying a new application on Amazon EC2 instances. The application writes data to Amazon Elastic Block Store (Amazon EBS) volumes. The company needs to ensure that all data that is written to the EBS volumes is encrypted at rest.

Which solution will meet this requirement?

- A. Create an IAM role that specifies EBS encryption. Attach the role to the EC2 instances.
- B. Create the EBS volumes as encrypted volumes. Attach the EBS volumes to the EC2 instances. **Most Voted**

- C. Create an EC2 instance tag that has a key of Encrypt and a value of True. Tag all instances that require encryption at the EBS level.
- D. Create an AWS Key Management Service (AWS KMS) key policy that enforces EBS encryption in the account. Ensure that the key policy is active.

Suggested Answer: B

Question #: 411

A company has a web application with sporadic usage patterns. There is heavy usage at the beginning of each month, moderate usage at the start of each week, and unpredictable usage during the week. The application consists of a web server and a MySQL database server running inside the data center. The company would like to move the application to the AWS Cloud, and needs to select a cost-effective database platform that will not require database modifications.

Which solution will meet these requirements?

- A. Amazon DynamoDB
- B. Amazon RDS for MySQL
- C. MySQL-compatible Amazon Aurora Serverless **Most Voted**
- D. MySQL deployed on Amazon EC2 in an Auto Scaling group

Suggested Answer: C

Question #: 412

An image-hosting company stores its objects in Amazon S3 buckets. The company wants to avoid accidental exposure of the objects in the S3 buckets to the public. All S3 objects in the entire AWS account need to remain private.

Which solution will meet these requirements?

- A. Use Amazon GuardDuty to monitor S3 bucket policies. Create an automatic remediation action rule that uses an AWS Lambda function to remediate any change that makes the objects public.

- B. Use AWS Trusted Advisor to find publicly accessible S3 buckets. Configure email notifications in Trusted Advisor when a change is detected. Manually change the S3 bucket policy if it allows public access.
- C. Use AWS Resource Access Manager to find publicly accessible S3 buckets. Use Amazon Simple Notification Service (Amazon SNS) to invoke an AWS Lambda function when a change is detected. Deploy a Lambda function that programmatically remediates the change.
- D. Use the S3 Block Public Access feature on the account level. Use AWS Organizations to create a service control policy (SCP) that prevents IAM users from changing the setting. Apply the SCP to the account. **Most Voted**

Suggested Answer: D

Question #: 413

An ecommerce company is experiencing an increase in user traffic. The company's store is deployed on Amazon EC2 instances as a two-tier web application consisting of a web tier and a separate database tier. As traffic increases, the company notices that the architecture is causing significant delays in sending timely marketing and order confirmation email to users. The company wants to reduce the time it spends resolving complex email delivery issues and minimize operational overhead.

What should a solutions architect do to meet these requirements?

- A. Create a separate application tier using EC2 instances dedicated to email processing.
- B. Configure the web instance to send email through Amazon Simple Email Service (Amazon SES). **Most Voted**
- C. Configure the web instance to send email through Amazon Simple Notification Service (Amazon SNS).
- D. Create a separate application tier using EC2 instances dedicated to email processing. Place the instances in an Auto Scaling group.

Suggested Answer: B

Question #: 414

A company has a business system that generates hundreds of reports each day. The business system saves the reports to a network share in CSV format. The company needs to store this data in the AWS Cloud in near-real time for analysis.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Use AWS DataSync to transfer the files to Amazon S3. Create a scheduled task that runs at the end of each day.
- B. Create an Amazon S3 File Gateway. Update the business system to use a new network share from the S3 File Gateway. **Most Voted**
- C. Use AWS DataSync to transfer the files to Amazon S3. Create an application that uses the DataSync API in the automation workflow.
- D. Deploy an AWS Transfer for SFTP endpoint. Create a script that checks for new files on the network share and uploads the new files by using SFTP.

Suggested Answer: B

Question #: 415

A company is storing petabytes of data in Amazon S3 Standard. The data is stored in multiple S3 buckets and is accessed with varying frequency. The company does not know access patterns for all the data. The company needs to implement a solution for each S3 bucket to optimize the cost of S3 usage.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Create an S3 Lifecycle configuration with a rule to transition the objects in the S3 bucket to S3 Intelligent-Tiering. **Most Voted**
- B. Use the S3 storage class analysis tool to determine the correct tier for each object in the S3 bucket. Move each object to the identified storage tier.
- C. Create an S3 Lifecycle configuration with a rule to transition the objects in the S3 bucket to S3 Glacier Instant Retrieval.
- D. Create an S3 Lifecycle configuration with a rule to transition the objects in the S3 bucket to S3 One Zone-Infrequent Access (S3 One Zone-IA).

Suggested Answer: A

Question #: 416

A rapidly growing global ecommerce company is hosting its web application on AWS. The web application includes static content and dynamic content. The website stores online transaction processing (OLTP) data in an Amazon RDS database. The website's users are experiencing slow page loads.

Which combination of actions should a solutions architect take to resolve this issue? (Choose two.)

- A. Configure an Amazon Redshift cluster.
- B. Set up an Amazon CloudFront distribution. **Most Voted**
- C. Host the dynamic web content in Amazon S3.
- D. Create a read replica for the RDS DB instance. **Most Voted**
- E. Configure a Multi-AZ deployment for the RDS DB instance.

Suggested Answer: BD

Question #: 417

A company uses Amazon EC2 instances and AWS Lambda functions to run its application. The company has VPCs with public subnets and private subnets in its AWS account. The EC2 instances run in a private subnet in one of the VPCs. The Lambda functions need direct network access to the EC2 instances for the application to work.

The application will run for at least 1 year. The company expects the number of Lambda functions that the application uses to increase during that time. The company wants to maximize its savings on all application resources and to keep network latency between the services low.

Which solution will meet these requirements?

- A. Purchase an EC2 Instance Savings Plan. Optimize the Lambda functions' duration and memory usage and the number of invocations. Connect the Lambda functions to the private subnet that contains the EC2 instances.

- B. Purchase an EC2 Instance Savings Plan Optimize the Lambda functions' duration and memory usage, the number of invocations, and the amount of data that is transferred. Connect the Lambda functions to a public subnet in the same VPC where the EC2 instances run.
- C. Purchase a Compute Savings Plan. Optimize the Lambda functions' duration and memory usage, the number of invocations, and the amount of data that is transferred. Connect the Lambda functions to the private subnet that contains the EC2 instances. **Most Voted**
- D. Purchase a Compute Savings Plan. Optimize the Lambda functions' duration and memory usage, the number of invocations, and the amount of data that is transferred. Keep the Lambda functions in the Lambda service VPC.

Suggested Answer: C

Question #: 418

A solutions architect needs to allow team members to access Amazon S3 buckets in two different AWS accounts: a development account and a production account. The team currently has access to S3 buckets in the development account by using unique IAM users that are assigned to an IAM group that has appropriate permissions in the account.

The solutions architect has created an IAM role in the production account. The role has a policy that grants access to an S3 bucket in the production account.

Which solution will meet these requirements while complying with the principle of least privilege?

- A. Attach the Administrator Access policy to the development account users.
- B. Add the development account as a principal in the trust policy of the role in the production account. **Most Voted**
- C. Turn off the S3 Block Public Access feature on the S3 bucket in the production account.
- D. Create a user in the production account with unique credentials for each team member.

Suggested Answer: B

Question #: 419

A company uses AWS Organizations with all features enabled and runs multiple Amazon EC2 workloads in the ap-southeast-2 Region. The company has a service control policy (SCP) that prevents any resources from being created in any other Region. A security policy requires the company to encrypt all data at rest.

An audit discovers that employees have created Amazon Elastic Block Store (Amazon EBS) volumes for EC2 instances without encrypting the volumes. The company wants any new EC2 instances that any IAM user or root user launches in ap-southeast-2 to use encrypted EBS volumes. The company wants a solution that will have minimal effect on employees who create EBS volumes.

Which combination of steps will meet these requirements? (Choose two.)

- A. In the Amazon EC2 console, select the EBS encryption account attribute and define a default encryption key.
- B. Create an IAM permission boundary. Attach the permission boundary to the root organizational unit (OU). Define the boundary to deny the ec2:CreateVolume action when the ec2:Encrypted condition equals false.
- C. Create an SCP. Attach the SCP to the root organizational unit (OU). Define the SCP to deny the ec2:CreateVolume action when the ec2:Encrypted condition equals false. **Most Voted**
- D. Update the IAM policies for each account to deny the ec2:CreateVolume action when the ec2:Encrypted condition equals false.
- E. In the Organizations management account, specify the Default EBS volume encryption setting. **Most Voted**

Suggested Answer: CE

Question #: 420

A company wants to use an Amazon RDS for PostgreSQL DB cluster to simplify time-consuming database administrative tasks for production database workloads. The company wants to ensure that its database is highly available and will provide automatic failover support in most scenarios in less than 40 seconds. The company wants to offload reads off of the primary instance and keep costs as low as possible.

Which solution will meet these requirements?

- A. Use an Amazon RDS Multi-AZ DB instance deployment. Create one read replica and point the read workload to the read replica. **Most Voted**
- B. Use an Amazon RDS Multi-AZ DB cluster deployment. Create two read replicas and point the read workload to the read replicas.
- C. Use an Amazon RDS Multi-AZ DB instance deployment. Point the read workload to the secondary instances in the Multi-AZ pair.
- D. Use an Amazon RDS Multi-AZ DB cluster deployment. Point the read workload to the reader endpoint. **Most Voted**

Suggested Answer: D

Question #: 421

A company runs a highly available SFTP service. The SFTP service uses two Amazon EC2 Linux instances that run with elastic IP addresses to accept traffic from trusted IP sources on the internet. The SFTP service is backed by shared storage that is attached to the instances. User accounts are created and managed as Linux users in the SFTP servers.

The company wants a serverless option that provides high IOPS performance and highly configurable security. The company also wants to maintain control over user permissions.

Which solution will meet these requirements?

- A. Create an encrypted Amazon Elastic Block Store (Amazon EBS) volume. Create an AWS Transfer Family SFTP service with a public endpoint that allows only trusted IP addresses. Attach the EBS volume to the SFTP service endpoint. Grant users access to the SFTP service.
- B. Create an encrypted Amazon Elastic File System (Amazon EFS) volume. Create an AWS Transfer Family SFTP service with elastic IP addresses and a VPC endpoint that has internet-facing access. Attach a security

group to the endpoint that allows only trusted IP addresses. Attach the EFS volume to the SFTP service endpoint. Grant users access to the SFTP service. **Most Voted**

- C. Create an Amazon S3 bucket with default encryption enabled. Create an AWS Transfer Family SFTP service with a public endpoint that allows only trusted IP addresses. Attach the S3 bucket to the SFTP service endpoint. Grant users access to the SFTP service.
- D. Create an Amazon S3 bucket with default encryption enabled. Create an AWS Transfer Family SFTP service with a VPC endpoint that has internal access in a private subnet. Attach a security group that allows only trusted IP addresses. Attach the S3 bucket to the SFTP service endpoint. Grant users access to the SFTP service.

Suggested Answer: B

Question #: 422

A company is developing a new machine learning (ML) model solution on AWS. The models are developed as independent microservices that fetch approximately 1 GB of model data from Amazon S3 at startup and load the data into memory. Users access the models through an asynchronous API. Users can send a request or a batch of requests and specify where the results should be sent.

The company provides models to hundreds of users. The usage patterns for the models are irregular. Some models could be unused for days or weeks. Other models could receive batches of thousands of requests at a time.

Which design should a solutions architect recommend to meet these requirements?

- A. Direct the requests from the API to a Network Load Balancer (NLB). Deploy the models as AWS Lambda functions that are invoked by the NLB.
- B. Direct the requests from the API to an Application Load Balancer (ALB). Deploy the models as Amazon Elastic Container Service (Amazon ECS) services that read from an Amazon Simple Queue Service (Amazon SQS) queue. Use AWS App Mesh to scale the instances of the ECS cluster based on the SQS queue size.
- C. Direct the requests from the API into an Amazon Simple Queue Service (Amazon SQS) queue. Deploy the models as AWS Lambda functions that are invoked by SQS events. Use AWS Auto Scaling to increase the number of vCPUs for the Lambda functions based on the SQS queue size.

- D. Direct the requests from the API into an Amazon Simple Queue Service (Amazon SQS) queue. Deploy the models as Amazon Elastic Container Service (Amazon ECS) services that read from the queue. Enable AWS Auto Scaling on Amazon ECS for both the cluster and copies of the service based on the queue size. **Most Voted**

Suggested Answer: D

Question #: 423

A solutions architect wants to use the following JSON text as an identity-based policy to grant specific permissions:

```
{  "Statement": [    {      "Action": [        "ssm:ListDocuments",        "ssm:GetDocument"      ],      "Effect": "Allow",      "Resource": "*",      "Sid": ""    }  ],  "Version": "2012-10-17"}
```

Which IAM principals can the solutions architect attach this policy to? (Choose two.)

- A. Role **Most Voted**
- B. Group **Most Voted**
- C. Organization
- D. Amazon Elastic Container Service (Amazon ECS) resource
- E. Amazon EC2 resource

Suggested Answer: AB

Question #: 424

A company is running a custom application on Amazon EC2 On-Demand Instances. The application has frontend nodes that need to run 24 hours a day, 7 days a week and backend nodes that need to run only for a short time based on workload. The number of backend nodes varies during the day.

The company needs to scale out and scale in more instances based on workload.

Which solution will meet these requirements MOST cost-effectively?

- A. Use Reserved Instances for the frontend nodes. Use AWS Fargate for the backend nodes. **Most Voted**
- B. Use Reserved Instances for the frontend nodes. Use Spot Instances for the backend nodes. **Most Voted**
- C. Use Spot Instances for the frontend nodes. Use Reserved Instances for the backend nodes.
- D. Use Spot Instances for the frontend nodes. Use AWS Fargate for the backend nodes.

Suggested Answer: B

Question #: 425

A company uses high block storage capacity to runs its workloads on premises. The company's daily peak input and output transactions per second are not more than 15,000 IOPS. The company wants to migrate the workloads to Amazon EC2 and to provision disk performance independent of storage capacity.

Which Amazon Elastic Block Store (Amazon EBS) volume type will meet these requirements MOST cost-effectively?

- A. GP2 volume type
- B. io2 volume type
- C. GP3 volume type **Most Voted**
- D. io1 volume type

Suggested Answer: C

Question #: 426

A company needs to store data from its healthcare application. The application's data frequently changes. A new regulation requires audit access at all levels of the stored data.

The company hosts the application on an on-premises infrastructure that is running out of storage capacity. A solutions architect must securely migrate the existing data to AWS while satisfying the new regulation.

Which solution will meet these requirements?

- A. Use AWS DataSync to move the existing data to Amazon S3. Use AWS CloudTrail to log data events. **Most Voted**
- B. Use AWS Snowcone to move the existing data to Amazon S3. Use AWS CloudTrail to log management events.
- C. Use Amazon S3 Transfer Acceleration to move the existing data to Amazon S3. Use AWS CloudTrail to log data events.
- D. Use AWS Storage Gateway to move the existing data to Amazon S3. Use AWS CloudTrail to log management events.

Suggested Answer: A

Question #: 427

A solutions architect is implementing a complex Java application with a MySQL database. The Java application must be deployed on Apache Tomcat and must be highly available.

What should the solutions architect do to meet these requirements?

- A. Deploy the application in AWS Lambda. Configure an Amazon API Gateway API to connect with the Lambda functions.
- B. Deploy the application by using AWS Elastic Beanstalk. Configure a load-balanced environment and a rolling deployment policy. **Most Voted**

- C. Migrate the database to Amazon ElastiCache. Configure the ElastiCache security group to allow access from the application.
- D. Launch an Amazon EC2 instance. Install a MySQL server on the EC2 instance. Configure the application on the server. Create an AMI. Use the AMI to create a launch template with an Auto Scaling group.

Suggested Answer: B

Question #: 428

A serverless application uses Amazon API Gateway, AWS Lambda, and Amazon DynamoDB. The Lambda function needs permissions to read and write to the DynamoDB table.

Which solution will give the Lambda function access to the DynamoDB table MOST securely?

- A. Create an IAM user with programmatic access to the Lambda function. Attach a policy to the user that allows read and write access to the DynamoDB table. Store the access_key_id and secret_access_key parameters as part of the Lambda environment variables. Ensure that other AWS users do not have read and write access to the Lambda function configuration.
- B. Create an IAM role that includes Lambda as a trusted service. Attach a policy to the role that allows read and write access to the DynamoDB table. Update the configuration of the Lambda function to use the new role as the execution role. **Most Voted**
- C. Create an IAM user with programmatic access to the Lambda function. Attach a policy to the user that allows read and write access to the DynamoDB table. Store the access_key_id and secret_access_key parameters in AWS Systems Manager Parameter Store as secure string parameters. Update the Lambda function code to retrieve the secure string parameters before connecting to the DynamoDB table.
- D. Create an IAM role that includes DynamoDB as a trusted service. Attach a policy to the role that allows read and write access from the Lambda function. Update the code of the Lambda function to attach to the new role as an execution role.

Suggested Answer: B

Question #: 429

The following IAM policy is attached to an IAM group. This is the only policy applied to the group.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "1",
      "Effect": "Allow",
      "Action": "ec2:*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    },
    {
      "Sid": "2",
      "Effect": "Deny",
      "Action": [
        "ec2:StopInstances",
        "ec2:TerminateInstances"
      ],
      "Resource": "*",
      "Condition": {
        "BoolIfExists": {"aws:MultiFactorAuthPresent": false}
      }
    }
  ]
}
```

What are the effective IAM permissions of this policy for group members?

- A. Group members are permitted any Amazon EC2 action within the us-east-1 Region. Statements after the Allow permission are not applied.

- B. Group members are denied any Amazon EC2 permissions in the us-east-1 Region unless they are logged in with multi-factor authentication (MFA).
- C. Group members are allowed the ec2:StopInstances and ec2:TerminateInstances permissions for all Regions when logged in with multi-factor authentication (MFA). Group members are permitted any other Amazon EC2 action.
- D. Group members are allowed the ec2:StopInstances and ec2:TerminateInstances permissions for the us-east-1 Region only when logged in with multi-factor authentication (MFA). Group members are permitted any other Amazon EC2 action within the us-east-1 Region. **Most Voted**

Suggested Answer: D

Question #: 430

A manufacturing company has machine sensors that upload .csv files to an Amazon S3 bucket. These .csv files must be converted into images and must be made available as soon as possible for the automatic generation of graphical reports.

The images become irrelevant after 1 month, but the .csv files must be kept to train machine learning (ML) models twice a year. The ML trainings and audits are planned weeks in advance.

Which combination of steps will meet these requirements MOST cost-effectively? (Choose two.)

- A. Launch an Amazon EC2 Spot Instance that downloads the .csv files every hour, generates the image files, and uploads the images to the S3 bucket.
- B. Design an AWS Lambda function that converts the .csv files into images and stores the images in the S3 bucket. Invoke the Lambda function when a .csv file is uploaded. **Most Voted**
- C. Create S3 Lifecycle rules for .csv files and image files in the S3 bucket. Transition the .csv files from S3 Standard to S3 Glacier 1 day after they are uploaded. Expire the image files after 30 days. **Most Voted**
- D. Create S3 Lifecycle rules for .csv files and image files in the S3 bucket. Transition the .csv files from S3 Standard to S3 One Zone-Infrequent Access (S3 One Zone-IA) 1 day after they are uploaded. Expire the image files after 30 days.

- E. Create S3 Lifecycle rules for .csv files and image files in the S3 bucket. Transition the .csv files from S3 Standard to S3 Standard-Infrequent Access (S3 Standard-IA) 1 day after they are uploaded. Keep the image files in Reduced Redundancy Storage (RRS).

Suggested Answer: BC

Question #: 431

A company has developed a new video game as a web application. The application is in a three-tier architecture in a VPC with Amazon RDS for MySQL in the database layer. Several players will compete concurrently online. The game's developers want to display a top-10 scoreboard in near-real time and offer the ability to stop and restore the game while preserving the current scores.

What should a solutions architect do to meet these requirements?

- A. Set up an Amazon ElastiCache for Memcached cluster to cache the scores for the web application to display.
- B. Set up an Amazon ElastiCache for Redis cluster to compute and cache the scores for the web application to display. **Most Voted**
- C. Place an Amazon CloudFront distribution in front of the web application to cache the scoreboard in a section of the application.
- D. Create a read replica on Amazon RDS for MySQL to run queries to compute the scoreboard and serve the read traffic to the web application.

Suggested Answer: B

Question #: 432

An ecommerce company wants to use machine learning (ML) algorithms to build and train models. The company will use the models to visualize complex scenarios and to detect trends in customer data. The architecture team wants to integrate its ML models with a reporting platform to analyze the augmented data and use the data directly in its business intelligence dashboards.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Glue to create an ML transform to build and train models. Use Amazon OpenSearch Service to visualize the data.
- B. Use Amazon SageMaker to build and train models. Use Amazon QuickSight to visualize the data. **Most Voted**
- C. Use a pre-built ML Amazon Machine Image (AMI) from the AWS Marketplace to build and train models. Use Amazon OpenSearch Service to visualize the data.
- D. Use Amazon QuickSight to build and train models by using calculated fields. Use Amazon QuickSight to visualize the data.

Suggested Answer: B

Question #: 433

A company is running its production and nonproduction environment workloads in multiple AWS accounts. The accounts are in an organization in AWS Organizations. The company needs to design a solution that will prevent the modification of cost usage tags.

Which solution will meet these requirements?

- A. Create a custom AWS Config rule to prevent tag modification except by authorized principals.
- B. Create a custom trail in AWS CloudTrail to prevent tag modification.
- C. Create a service control policy (SCP) to prevent tag modification except by authorized principals. **Most Voted**
- D. Create custom Amazon CloudWatch logs to prevent tag modification.

Suggested Answer: C

Question #: 434

A company hosts its application in the AWS Cloud. The application runs on Amazon EC2 instances behind an Elastic Load Balancer in an Auto Scaling group and with an Amazon DynamoDB table. The company wants to ensure the application can be made available in another AWS Region with minimal downtime.

What should a solutions architect do to meet these requirements with the LEAST amount of downtime?

- A. Create an Auto Scaling group and a load balancer in the disaster recovery Region. Configure the DynamoDB table as a global table. Configure DNS failover to point to the new disaster recovery Region's load balancer. **Most Voted**
- B. Create an AWS CloudFormation template to create EC2 instances, load balancers, and DynamoDB tables to be launched when needed. Configure DNS failover to point to the new disaster recovery Region's load balancer.
- C. Create an AWS CloudFormation template to create EC2 instances and a load balancer to be launched when needed. Configure the DynamoDB table as a global table. Configure DNS failover to point to the new disaster recovery Region's load balancer.
- D. Create an Auto Scaling group and load balancer in the disaster recovery Region. Configure the DynamoDB table as a global table. Create an Amazon CloudWatch alarm to trigger an AWS Lambda function that updates Amazon Route 53 pointing to the disaster recovery load balancer.

Suggested Answer: A

Question #: 435

A company needs to migrate a MySQL database from its on-premises data center to AWS within 2 weeks. The database is 20 TB in size. The company wants to complete the migration with minimal downtime.

Which solution will migrate the database MOST cost-effectively?

- A. Order an AWS Snowball Edge Storage Optimized device. Use AWS Database Migration Service (AWS DMS) with AWS Schema Conversion Tool (AWS SCT) to migrate the database with replication of ongoing changes. Send the Snowball Edge device to AWS to finish the migration and continue the ongoing replication. **Most Voted**
- B. Order an AWS Snowmobile vehicle. Use AWS Database Migration Service (AWS DMS) with AWS Schema Conversion Tool (AWS SCT) to migrate the database with ongoing changes. Send the Snowmobile vehicle back to AWS to finish the migration and continue the ongoing replication.
- C. Order an AWS Snowball Edge Compute Optimized with GPU device. Use AWS Database Migration Service (AWS DMS) with AWS Schema Conversion Tool (AWS SCT) to migrate the database with ongoing changes. Send the Snowball device to AWS to finish the migration and continue the ongoing replication.

- D. Order a 1 GB dedicated AWS Direct Connect connection to establish a connection with the data center. Use AWS Database Migration Service (AWS DMS) with AWS Schema Conversion Tool (AWS SCT) to migrate the database with replication of ongoing changes.

Suggested Answer: A

Question #: 436

A company moved its on-premises PostgreSQL database to an Amazon RDS for PostgreSQL DB instance. The company successfully launched a new product. The workload on the database has increased. The company wants to accommodate the larger workload without adding infrastructure.

Which solution will meet these requirements MOST cost-effectively?

- A. Buy reserved DB instances for the total workload. Make the Amazon RDS for PostgreSQL DB instance larger. **Most Voted**
- B. Make the Amazon RDS for PostgreSQL DB instance a Multi-AZ DB instance.
- C. Buy reserved DB instances for the total workload. Add another Amazon RDS for PostgreSQL DB instance.
- D. Make the Amazon RDS for PostgreSQL DB instance an on-demand DB instance.

Suggested Answer: A

Question #: 437

A company operates an ecommerce website on Amazon EC2 instances behind an Application Load Balancer (ALB) in an Auto Scaling group. The site is experiencing performance issues related to a high request rate from illegitimate external systems with changing IP addresses. The security team is worried about potential DDoS attacks against the website. The company must block the illegitimate incoming requests in a way that has a minimal impact on legitimate users.

What should a solutions architect recommend?

- A. Deploy Amazon Inspector and associate it with the ALB.

- B. Deploy AWS WAF, associate it with the ALB, and configure a rate-limiting rule. **Most Voted**
- C. Deploy rules to the network ACLs associated with the ALB to block the incoming traffic.
- D. Deploy Amazon GuardDuty and enable rate-limiting protection when configuring GuardDuty.

Suggested Answer: B

Question #: 438

A company wants to share accounting data with an external auditor. The data is stored in an Amazon RDS DB instance that resides in a private subnet. The auditor has its own AWS account and requires its own copy of the database.

What is the MOST secure way for the company to share the database with the auditor?

- A. Create a read replica of the database. Configure IAM standard database authentication to grant the auditor access.
- B. Export the database contents to text files. Store the files in an Amazon S3 bucket. Create a new IAM user for the auditor. Grant the user access to the S3 bucket.
- C. Copy a snapshot of the database to an Amazon S3 bucket. Create an IAM user. Share the user's keys with the auditor to grant access to the object in the S3 bucket.
- D. Create an encrypted snapshot of the database. Share the snapshot with the auditor. Allow access to the AWS Key Management Service (AWS KMS) encryption key. **Most Voted**

Suggested Answer: D

Question #: 439

A solutions architect configured a VPC that has a small range of IP addresses. The number of Amazon EC2 instances that are in the VPC is increasing, and there is an insufficient number of IP addresses for future workloads.

Which solution resolves this issue with the LEAST operational overhead?

- A. Add an additional IPv4 CIDR block to increase the number of IP addresses and create additional subnets in the VPC. Create new resources in the new subnets by using the new CIDR. **Most Voted**
- B. Create a second VPC with additional subnets. Use a peering connection to connect the second VPC with the first VPC. Update the routes and create new resources in the subnets of the second VPC.
- C. Use AWS Transit Gateway to add a transit gateway and connect a second VPC with the first VPC. Update the routes of the transit gateway and VPCs. Create new resources in the subnets of the second VPC.
- D. Create a second VPC. Create a Site-to-Site VPN connection between the first VPC and the second VPC by using a VPN-hosted solution on Amazon EC2 and a virtual private gateway. Update the route between VPCs to the traffic through the VPN. Create new resources in the subnets of the second VPC.

Suggested Answer: A

Question #: 440

A company used an Amazon RDS for MySQL DB instance during application testing. Before terminating the DB instance at the end of the test cycle, a solutions architect created two backups. The solutions architect created the first backup by using the mysqldump utility to create a database dump. The solutions architect created the second backup by enabling the final DB snapshot option on RDS termination.

The company is now planning for a new test cycle and wants to create a new DB instance from the most recent backup. The company has chosen a MySQL-compatible edition of Amazon Aurora to host the DB instance.

Which solutions will create the new DB instance? (Choose two.)

- A. Import the RDS snapshot directly into Aurora. **Most Voted**
- B. Upload the RDS snapshot to Amazon S3. Then import the RDS snapshot into Aurora.
- C. Upload the database dump to Amazon S3. Then import the database dump into Aurora. **Most Voted**
- D. Use AWS Database Migration Service (AWS DMS) to import the RDS snapshot into Aurora.
- E. Upload the database dump to Amazon S3. Then use AWS Database Migration Service (AWS DMS) to import the database dump into Aurora.

Suggested Answer: AC

Question #: 441

A company hosts a multi-tier web application on Amazon Linux Amazon EC2 instances behind an Application Load Balancer. The instances run in an Auto Scaling group across multiple Availability Zones. The company observes that the Auto Scaling group launches more On-Demand Instances when the application's end users access high volumes of static web content. The company wants to optimize cost.

What should a solutions architect do to redesign the application MOST cost-effectively?

- A. Update the Auto Scaling group to use Reserved Instances instead of On-Demand Instances.
- B. Update the Auto Scaling group to scale by launching Spot Instances instead of On-Demand Instances.
- C. Create an Amazon CloudFront distribution to host the static web contents from an Amazon S3 bucket. **Most Voted**
- D. Create an AWS Lambda function behind an Amazon API Gateway API to host the static website contents.

Suggested Answer: C

Question #: 442

A company stores several petabytes of data across multiple AWS accounts. The company uses AWS Lake Formation to manage its data lake. The company's data science team wants to securely share selective data from its accounts with the company's engineering team for analytical purposes.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Copy the required data to a common account. Create an IAM access role in that account. Grant access by specifying a permission policy that includes users from the engineering team accounts as trusted entities.
- B. Use the Lake Formation permissions Grant command in each account where the data is stored to allow the required engineering team users to access the data.
- C. Use AWS Data Exchange to privately publish the required data to the required engineering team accounts.
- D. Use Lake Formation tag-based access control to authorize and grant cross-account permissions for the required data to the engineering team accounts. **Most Voted**

Suggested Answer: D

Question #: 443

A company wants to host a scalable web application on AWS. The application will be accessed by users from different geographic regions of the world. Application users will be able to download and upload unique data up to gigabytes in size. The development team wants a cost-effective solution to minimize upload and download latency and maximize performance.

What should a solutions architect do to accomplish this?

- A. Use Amazon S3 with Transfer Acceleration to host the application. **Most Voted**
- B. Use Amazon S3 with CacheControl headers to host the application.
- C. Use Amazon EC2 with Auto Scaling and Amazon CloudFront to host the application. **Most Voted**
- D. Use Amazon EC2 with Auto Scaling and Amazon ElastiCache to host the application.

Suggested Answer: A

Question #: 444

A company has hired a solutions architect to design a reliable architecture for its application. The application consists of one Amazon RDS DB instance and two manually provisioned Amazon EC2 instances that run web servers. The EC2 instances are located in a single Availability Zone.

An employee recently deleted the DB instance, and the application was unavailable for 24 hours as a result. The company is concerned with the overall reliability of its environment.

What should the solutions architect do to maximize reliability of the application's infrastructure?

- A. Delete one EC2 instance and enable termination protection on the other EC2 instance. Update the DB instance to be Multi-AZ, and enable deletion protection.

- B. Update the DB instance to be Multi-AZ, and enable deletion protection. Place the EC2 instances behind an Application Load Balancer, and run them in an EC2 Auto Scaling group across multiple Availability Zones. **Most Voted**
- C. Create an additional DB instance along with an Amazon API Gateway and an AWS Lambda function. Configure the application to invoke the Lambda function through API Gateway. Have the Lambda function write the data to the two DB instances.
- D. Place the EC2 instances in an EC2 Auto Scaling group that has multiple subnets located in multiple Availability Zones. Use Spot Instances instead of On-Demand Instances. Set up Amazon CloudWatch alarms to monitor the health of the instances Update the DB instance to be Multi-AZ, and enable deletion protection.

Suggested Answer: B

Question #: 445

A company is storing 700 terabytes of data on a large network-attached storage (NAS) system in its corporate data center. The company has a hybrid environment with a 10 Gbps AWS Direct Connect connection.

After an audit from a regulator, the company has 90 days to move the data to the cloud. The company needs to move the data efficiently and without disruption. The company still needs to be able to access and update the data during the transfer window.

Which solution will meet these requirements?

- A. Create an AWS DataSync agent in the corporate data center. Create a data transfer task Start the transfer to an Amazon S3 bucket. **Most Voted**
- B. Back up the data to AWS Snowball Edge Storage Optimized devices. Ship the devices to an AWS data center. Mount a target Amazon S3 bucket on the on-premises file system.
- C. Use rsync to copy the data directly from local storage to a designated Amazon S3 bucket over the Direct Connect connection.
- D. Back up the data on tapes. Ship the tapes to an AWS data center. Mount a target Amazon S3 bucket on the on-premises file system.

Suggested Answer: A

Question #: 446

A company stores data in PDF format in an Amazon S3 bucket. The company must follow a legal requirement to retain all new and existing data in Amazon S3 for 7 years.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Turn on the S3 Versioning feature for the S3 bucket. Configure S3 Lifecycle to delete the data after 7 years. Configure multi-factor authentication (MFA) delete for all S3 objects.
- B. Turn on S3 Object Lock with governance retention mode for the S3 bucket. Set the retention period to expire after 7 years. Recopy all existing objects to bring the existing data into compliance.
- C. Turn on S3 Object Lock with compliance retention mode for the S3 bucket. Set the retention period to expire after 7 years. Recopy all existing objects to bring the existing data into compliance.
- D. Turn on S3 Object Lock with compliance retention mode for the S3 bucket. Set the retention period to expire after 7 years. Use S3 Batch Operations to bring the existing data into compliance. **Most Voted**

Suggested Answer: D

Question #: 447

A company has a stateless web application that runs on AWS Lambda functions that are invoked by Amazon API Gateway. The company wants to deploy the application across multiple AWS Regions to provide Regional failover capabilities.

What should a solutions architect do to route traffic to multiple Regions?

- A. Create Amazon Route 53 health checks for each Region. Use an active-active failover configuration. **Most Voted**
- B. Create an Amazon CloudFront distribution with an origin for each Region. Use CloudFront health checks to route traffic. **Most Voted**
- C. Create a transit gateway. Attach the transit gateway to the API Gateway endpoint in each Region. Configure the transit gateway to route requests.

- D. Create an Application Load Balancer in the primary Region. Set the target group to point to the API Gateway endpoint hostnames in each Region.

Suggested Answer: A

Question #: 448

A company has two VPCs named Management and Production. The Management VPC uses VPNs through a customer gateway to connect to a single device in the data center. The Production VPC uses a virtual private gateway with two attached AWS Direct Connect connections. The Management and Production VPCs both use a single VPC peering connection to allow communication between the applications.

What should a solutions architect do to mitigate any single point of failure in this architecture?

- A. Add a set of VPNs between the Management and Production VPCs.
- B. Add a second virtual private gateway and attach it to the Management VPC.
- C. Add a second set of VPNs to the Management VPC from a second customer gateway device. **Most Voted**
- D. Add a second VPC peering connection between the Management VPC and the Production VPC.

Suggested Answer: C

Question #: 449

A company runs its application on an Oracle database. The company plans to quickly migrate to AWS because of limited resources for the database, backup administration, and data center maintenance. The application uses third-party database features that require privileged access.

Which solution will help the company migrate the database to AWS MOST cost-effectively?

- A. Migrate the database to Amazon RDS for Oracle. Replace third-party features with cloud services.
- B. Migrate the database to Amazon RDS Custom for Oracle. Customize the database settings to support third-party features. **Most Voted**

- C. Migrate the database to an Amazon EC2 Amazon Machine Image (AMI) for Oracle. Customize the database settings to support third-party features.
- D. Migrate the database to Amazon RDS for PostgreSQL by rewriting the application code to remove dependency on Oracle APEX.

Suggested Answer: B

Question #: 450

A company has a three-tier web application that is in a single server. The company wants to migrate the application to the AWS Cloud. The company also wants the application to align with the AWS Well-Architected Framework and to be consistent with AWS recommended best practices for security, scalability, and resiliency.

Which combination of solutions will meet these requirements? (Choose three.)

- A. Create a VPC across two Availability Zones with the application's existing architecture. Host the application with existing architecture on an Amazon EC2 instance in a private subnet in each Availability Zone with EC2 Auto Scaling groups. Secure the EC2 instance with security groups and network access control lists (network ACLs).
- B. Set up security groups and network access control lists (network ACLs) to control access to the database layer. Set up a single Amazon RDS database in a private subnet.
- C. Create a VPC across two Availability Zones. Refactor the application to host the web tier, application tier, and database tier. Host each tier on its own private subnet with Auto Scaling groups for the web tier and application tier. **Most Voted**
- D. Use a single Amazon RDS database. Allow database access only from the application tier security group.
- E. Use Elastic Load Balancers in front of the web tier. Control access by using security groups containing references to each layer's security groups. **Most Voted**
- F. Use an Amazon RDS database Multi-AZ cluster deployment in private subnets. Allow database access only from application tier security groups. **Most Voted**

Suggested Answer: CEF

Question #: 451

A company is migrating its applications and databases to the AWS Cloud. The company will use Amazon Elastic Container Service (Amazon ECS), AWS Direct Connect, and Amazon RDS.

Which activities will be managed by the company's operational team? (Choose three.)

- A. Management of the Amazon RDS infrastructure layer, operating system, and platforms
- B. Creation of an Amazon RDS DB instance and configuring the scheduled maintenance window **Most Voted**
- C. Configuration of additional software components on Amazon ECS for monitoring, patch management, log management, and host intrusion detection **Most Voted**
- D. Installation of patches for all minor and major database versions for Amazon RDS
- E. Ensure the physical security of the Amazon RDS infrastructure in the data center
- F. Encryption of the data that moves in transit through Direct Connect **Most Voted**

Suggested Answer: BCF

Question #: 452

A company runs a Java-based job on an Amazon EC2 instance. The job runs every hour and takes 10 seconds to run. The job runs on a scheduled interval and consumes 1 GB of memory. The CPU utilization of the instance is low except for short surges during which the job uses the maximum CPU available. The company wants to optimize the costs to run the job.

Which solution will meet these requirements?

- A. Use AWS App2Container (A2C) to containerize the job. Run the job as an Amazon Elastic Container Service (Amazon ECS) task on AWS Fargate with 0.5 virtual CPU (vCPU) and 1 GB of memory.
- B. Copy the code into an AWS Lambda function that has 1 GB of memory. Create an Amazon EventBridge scheduled rule to run the code each hour. **Most Voted**
- C. Use AWS App2Container (A2C) to containerize the job. Install the container in the existing Amazon Machine Image (AMI). Ensure that the schedule stops the container when the task finishes.

- D. Configure the existing schedule to stop the EC2 instance at the completion of the job and restart the EC2 instance when the next job starts.

Suggested Answer: B

Question #: 453

A company wants to implement a backup strategy for Amazon EC2 data and multiple Amazon S3 buckets. Because of regulatory requirements, the company must retain backup files for a specific time period. The company must not alter the files for the duration of the retention period.

Which solution will meet these requirements?

- A. Use AWS Backup to create a backup vault that has a vault lock in governance mode. Create the required backup plan.
- B. Use Amazon Data Lifecycle Manager to create the required automated snapshot policy.
- C. Use Amazon S3 File Gateway to create the backup. Configure the appropriate S3 Lifecycle management.
- D. Use AWS Backup to create a backup vault that has a vault lock in compliance mode. Create the required backup plan. **Most Voted**

Suggested Answer: D

Question #: 454

A company has resources across multiple AWS Regions and accounts. A newly hired solutions architect discovers a previous employee did not provide details about the resources inventory. The solutions architect needs to build and map the relationship details of the various workloads across all accounts.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Use AWS Systems Manager Inventory to generate a map view from the detailed view report.
- B. Use AWS Step Functions to collect workload details. Build architecture diagrams of the workloads manually.
- C. Use Workload Discovery on AWS to generate architecture diagrams of the workloads. **Most Voted**

- D. Use AWS X-Ray to view the workload details. Build architecture diagrams with relationships.

Suggested Answer: C

Question #: 455

A company uses AWS Organizations. The company wants to operate some of its AWS accounts with different budgets. The company wants to receive alerts and automatically prevent provisioning of additional resources on AWS accounts when the allocated budget threshold is met during a specific period.

Which combination of solutions will meet these requirements? (Choose three.)

- A. Use AWS Budgets to create a budget. Set the budget amount under the Cost and Usage Reports section of the required AWS accounts.
- B. Use AWS Budgets to create a budget. Set the budget amount under the Billing dashboards of the required AWS accounts. **Most Voted**
- C. Create an IAM user for AWS Budgets to run budget actions with the required permissions.
- D. Create an IAM role for AWS Budgets to run budget actions with the required permissions. **Most Voted**
- E. Add an alert to notify the company when each account meets its budget threshold. Add a budget action that selects the IAM identity created with the appropriate config rule to prevent provisioning of additional resources.
- F. Add an alert to notify the company when each account meets its budget threshold. Add a budget action that selects the IAM identity created with the appropriate service control policy (SCP) to prevent provisioning of additional resources. **Most Voted**

Suggested Answer: BDF

Question #: 456

A company runs applications on Amazon EC2 instances in one AWS Region. The company wants to back up the EC2 instances to a second Region. The company also wants to provision EC2 resources in the second Region and manage the EC2 instances centrally from one AWS account.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a disaster recovery (DR) plan that has a similar number of EC2 instances in the second Region. Configure data replication.
- B. Create point-in-time Amazon Elastic Block Store (Amazon EBS) snapshots of the EC2 instances. Copy the snapshots to the second Region periodically.
- C. Create a backup plan by using AWS Backup. Configure cross-Region backup to the second Region for the EC2 instances. **Most Voted**
- D. Deploy a similar number of EC2 instances in the second Region. Use AWS DataSync to transfer the data from the source Region to the second Region.

Suggested Answer: C

Question #: 457

A company that uses AWS is building an application to transfer data to a product manufacturer. The company has its own identity provider (IdP). The company wants the IdP to authenticate application users while the users use the application to transfer data. The company must use Applicability Statement 2 (AS2) protocol.

Which solution will meet these requirements?

- A. Use AWS DataSync to transfer the data. Create an AWS Lambda function for IdP authentication.
- B. Use Amazon AppFlow flows to transfer the data. Create an Amazon Elastic Container Service (Amazon ECS) task for IdP authentication.
- C. Use AWS Transfer Family to transfer the data. Create an AWS Lambda function for IdP authentication. **Most Voted**
- D. Use AWS Storage Gateway to transfer the data. Create an Amazon Cognito identity pool for IdP authentication.

Suggested Answer: C

Question #: 458

A solutions architect is designing a RESTAPI in Amazon API Gateway for a cash payback service. The application requires 1 GB of memory and 2 GB of storage for its computation resources. The application will require that the data is in a relational format.

Which additional combination of AWS services will meet these requirements with the LEAST administrative effort? (Choose two.)

- A. Amazon EC2
- B. AWS Lambda **Most Voted**
- C. Amazon RDS **Most Voted**
- D. Amazon DynamoDB
- E. Amazon Elastic Kubernetes Services (Amazon EKS)

Suggested Answer: BC

Question #: 459

A company uses AWS Organizations to run workloads within multiple AWS accounts. A tagging policy adds department tags to AWS resources when the company creates tags.

An accounting team needs to determine spending on Amazon EC2 consumption. The accounting team must determine which departments are responsible for the costs regardless of AWS account. The accounting team has access to AWS Cost Explorer for all AWS accounts within the organization and needs to access all reports from Cost Explorer.

Which solution meets these requirements in the MOST operationally efficient way?

- A. From the Organizations management account billing console, activate a user-defined cost allocation tag named department. Create one cost report in Cost Explorer grouping by tag name, and filter by EC2. **Most Voted**
- B. From the Organizations management account billing console, activate an AWS-defined cost allocation tag named department. Create one cost report in Cost Explorer grouping by tag name, and filter by EC2.
- C. From the Organizations member account billing console, activate a user-defined cost allocation tag named department. Create one cost report in Cost Explorer grouping by the tag name, and filter by EC2.

- D. From the Organizations member account billing console, activate an AWS-defined cost allocation tag named department. Create one cost report in Cost Explorer grouping by tag name, and filter by EC2.

Suggested Answer: A

Question #: 460

A company wants to securely exchange data between its software as a service (SaaS) application Salesforce account and Amazon S3. The company must encrypt the data at rest by using AWS Key Management Service (AWS KMS) customer managed keys (CMKs). The company must also encrypt the data in transit. The company has enabled API access for the Salesforce account.

- A. Create AWS Lambda functions to transfer the data securely from Salesforce to Amazon S3.
- B. Create an AWS Step Functions workflow. Define the task to transfer the data securely from Salesforce to Amazon S3.
- C. Create Amazon AppFlow flows to transfer the data securely from Salesforce to Amazon S3. **Most Voted**
- D. Create a custom connector for Salesforce to transfer the data securely from Salesforce to Amazon S3.

Suggested Answer: C

Question #: 461

A company is developing a mobile gaming app in a single AWS Region. The app runs on multiple Amazon EC2 instances in an Auto Scaling group. The company stores the app data in Amazon DynamoDB. The app communicates by using TCP traffic and UDP traffic between the users and the servers. The application will be used globally. The company wants to ensure the lowest possible latency for all users.

Which solution will meet these requirements?

- A. Use AWS Global Accelerator to create an accelerator. Create an Application Load Balancer (ALB) behind an accelerator endpoint that uses Global Accelerator integration and listening on the TCP and UDP ports. Update the Auto Scaling group to register instances on the ALB.

- B. Use AWS Global Accelerator to create an accelerator. Create a Network Load Balancer (NLB) behind an accelerator endpoint that uses Global Accelerator integration and listening on the TCP and UDP ports. Update the Auto Scaling group to register instances on the NLB. **Most Voted**
- C. Create an Amazon CloudFront content delivery network (CDN) endpoint. Create a Network Load Balancer (NLB) behind the endpoint and listening on the TCP and UDP ports. Update the Auto Scaling group to register instances on the NLB. Update CloudFront to use the NLB as the origin.
- D. Create an Amazon CloudFront content delivery network (CDN) endpoint. Create an Application Load Balancer (ALB) behind the endpoint and listening on the TCP and UDP ports. Update the Auto Scaling group to register instances on the ALB. Update CloudFront to use the ALB as the origin.

Suggested Answer: B

Question #: 462

A company has an application that processes customer orders. The company hosts the application on an Amazon EC2 instance that saves the orders to an Amazon Aurora database. Occasionally when traffic is high the workload does not process orders fast enough.

What should a solutions architect do to write the orders reliably to the database as quickly as possible?

- A. Increase the instance size of the EC2 instance when traffic is high. Write orders to Amazon Simple Notification Service (Amazon SNS). Subscribe the database endpoint to the SNS topic.
- B. Write orders to an Amazon Simple Queue Service (Amazon SQS) queue. Use EC2 instances in an Auto Scaling group behind an Application Load Balancer to read from the SQS queue and process orders into the database. **Most Voted**
- C. Write orders to Amazon Simple Notification Service (Amazon SNS). Subscribe the database endpoint to the SNS topic. Use EC2 instances in an Auto Scaling group behind an Application Load Balancer to read from the SNS topic.
- D. Write orders to an Amazon Simple Queue Service (Amazon SQS) queue when the EC2 instance reaches CPU threshold limits. Use scheduled scaling of EC2 instances in an Auto Scaling group behind an Application Load Balancer to read from the SQS queue and process orders into the database.

Suggested Answer: B

Question #: 463

An IoT company is releasing a mattress that has sensors to collect data about a user's sleep. The sensors will send data to an Amazon S3 bucket. The sensors collect approximately 2 MB of data every night for each mattress. The company must process and summarize the data for each mattress. The results need to be available as soon as possible. Data processing will require 1 GB of memory and will finish within 30 seconds.

Which solution will meet these requirements MOST cost-effectively?

- A. Use AWS Glue with a Scala job
- B. Use Amazon EMR with an Apache Spark script
- C. Use AWS Lambda with a Python script **Most Voted**
- D. Use AWS Glue with a PySpark job

Suggested Answer: C

Question #: 464

A company hosts an online shopping application that stores all orders in an Amazon RDS for PostgreSQL Single-AZ DB instance. Management wants to eliminate single points of failure and has asked a solutions architect to recommend an approach to minimize database downtime without requiring any changes to the application code.

Which solution meets these requirements?

- A. Convert the existing database instance to a Multi-AZ deployment by modifying the database instance and specifying the Multi-AZ option. **Most Voted**
- B. Create a new RDS Multi-AZ deployment. Take a snapshot of the current RDS instance and restore the new Multi-AZ deployment with the snapshot.
- C. Create a read-only replica of the PostgreSQL database in another Availability Zone. Use Amazon Route 53 weighted record sets to distribute requests across the databases.
- D. Place the RDS for PostgreSQL database in an Amazon EC2 Auto Scaling group with a minimum group size of two. Use Amazon Route 53 weighted record sets to distribute requests across instances.

Suggested Answer: A

Question #: 465

A company is developing an application to support customer demands. The company wants to deploy the application on multiple Amazon EC2 Nitro-based instances within the same Availability Zone. The company also wants to give the application the ability to write to multiple block storage volumes in multiple EC2 Nitro-based instances simultaneously to achieve higher application availability.

Which solution will meet these requirements?

- A. Use General Purpose SSD (gp3) EBS volumes with Amazon Elastic Block Store (Amazon EBS) Multi-Attach
- B. Use Throughput Optimized HDD (st1) EBS volumes with Amazon Elastic Block Store (Amazon EBS) Multi-Attach
- C. Use Provisioned IOPS SSD (io2) EBS volumes with Amazon Elastic Block Store (Amazon EBS) Multi-Attach **Most Voted**
- D. Use General Purpose SSD (gp2) EBS volumes with Amazon Elastic Block Store (Amazon EBS) Multi-Attach

Suggested Answer: C

Question #: 466

A company designed a stateless two-tier application that uses Amazon EC2 in a single Availability Zone and an Amazon RDS Multi-AZ DB instance. New company management wants to ensure the application is highly available.

What should a solutions architect do to meet this requirement?

- A. Configure the application to use Multi-AZ EC2 Auto Scaling and create an Application Load Balancer **Most Voted**
- B. Configure the application to take snapshots of the EC2 instances and send them to a different AWS Region
- C. Configure the application to use Amazon Route 53 latency-based routing to feed requests to the application

- D. Configure Amazon Route 53 rules to handle incoming requests and create a Multi-AZ Application Load Balancer

Suggested Answer: A

Question #: 467

A company uses AWS Organizations. A member account has purchased a Compute Savings Plan. Because of changes in the workloads inside the member account, the account no longer receives the full benefit of the Compute Savings Plan commitment. The company uses less than 50% of its purchased compute power.

- A. Turn on discount sharing from the Billing Preferences section of the account console in the member account that purchased the Compute Savings Plan.
- B. Turn on discount sharing from the Billing Preferences section of the account console in the company's Organizations management account. **Most Voted**
- C. Migrate additional compute workloads from another AWS account to the account that has the Compute Savings Plan.
- D. Sell the excess Savings Plan commitment in the Reserved Instance Marketplace.

Suggested Answer: B

Question #: 468

A company is developing a microservices application that will provide a search catalog for customers. The company must use REST APIs to present the frontend of the application to users. The REST APIs must access the backend services that the company hosts in containers in private VPC subnets.

Which solution will meet these requirements?

- A. Design a WebSocket API by using Amazon API Gateway. Host the application in Amazon Elastic Container Service (Amazon ECS) in a private subnet. Create a private VPC link for API Gateway to access Amazon ECS.

- B. Design a REST API by using Amazon API Gateway. Host the application in Amazon Elastic Container Service (Amazon ECS) in a private subnet. Create a private VPC link for API Gateway to access Amazon ECS. **Most Voted**
- C. Design a WebSocket API by using Amazon API Gateway. Host the application in Amazon Elastic Container Service (Amazon ECS) in a private subnet. Create a security group for API Gateway to access Amazon ECS.
- D. Design a REST API by using Amazon API Gateway. Host the application in Amazon Elastic Container Service (Amazon ECS) in a private subnet. Create a security group for API Gateway to access Amazon ECS.

Suggested Answer: B

Question #: 469

A company stores raw collected data in an Amazon S3 bucket. The data is used for several types of analytics on behalf of the company's customers. The type of analytics requested determines the access pattern on the S3 objects.

The company cannot predict or control the access pattern. The company wants to reduce its S3 costs.

Which solution will meet these requirements?

- A. Use S3 replication to transition infrequently accessed objects to S3 Standard-Infrequent Access (S3 Standard-IA)
- B. Use S3 Lifecycle rules to transition objects from S3 Standard to Standard-Infrequent Access (S3 Standard-IA)
- C. Use S3 Lifecycle rules to transition objects from S3 Standard to S3 Intelligent-Tiering **Most Voted**
- D. Use S3 Inventory to identify and transition objects that have not been accessed from S3 Standard to S3 Intelligent-Tiering

Suggested Answer: C

Question #: 470

A company has applications hosted on Amazon EC2 instances with IPv6 addresses. The applications must initiate communications with other external applications using the internet. However the company's security policy states that any external service cannot initiate a connection to the EC2 instances.

What should a solutions architect recommend to resolve this issue?

- A. Create a NAT gateway and make it the destination of the subnet's route table
- B. Create an internet gateway and make it the destination of the subnet's route table
- C. Create a virtual private gateway and make it the destination of the subnet's route table
- D. Create an egress-only internet gateway and make it the destination of the subnet's route table **Most Voted**

Suggested Answer: D

Question #: 471

A company is creating an application that runs on containers in a VPC. The application stores and accesses data in an Amazon S3 bucket. During the development phase, the application will store and access 1 TB of data in Amazon S3 each day. The company wants to minimize costs and wants to prevent traffic from traversing the internet whenever possible.

Which solution will meet these requirements?

- A. Enable S3 Intelligent-Tiering for the S3 bucket
- B. Enable S3 Transfer Acceleration for the S3 bucket
- C. Create a gateway VPC endpoint for Amazon S3. Associate this endpoint with all route tables in the VPC **Most Voted**
- D. Create an interface endpoint for Amazon S3 in the VPC. Associate this endpoint with all route tables in the VPC

Suggested Answer: C

Question #: 472

A company has a mobile chat application with a data store based in Amazon DynamoDB. Users would like new messages to be read with as little latency as possible. A solutions architect needs to design an optimal solution that requires minimal application changes.

Which method should the solutions architect select?

- A. Configure Amazon DynamoDB Accelerator (DAX) for the new messages table. Update the code to use the DAX endpoint. **Most Voted**
- B. Add DynamoDB read replicas to handle the increased read load. Update the application to point to the read endpoint for the read replicas.
- C. Double the number of read capacity units for the new messages table in DynamoDB. Continue to use the existing DynamoDB endpoint.
- D. Add an Amazon ElastiCache for Redis cache to the application stack. Update the application to point to the Redis cache endpoint instead of DynamoDB.

Suggested Answer: A

Question #: 473

A company hosts a website on Amazon EC2 instances behind an Application Load Balancer (ALB). The website serves static content. Website traffic is increasing, and the company is concerned about a potential increase in cost.

- A. Create an Amazon CloudFront distribution to cache static files at edge locations **Most Voted**
- B. Create an Amazon ElastiCache cluster. Connect the ALB to the ElastiCache cluster to serve cached files
- C. Create an AWS WAF web ACL and associate it with the ALB. Add a rule to the web ACL to cache static files
- D. Create a second ALB in an alternative AWS Region. Route user traffic to the closest Region to minimize data transfer costs

Suggested Answer: A

Question #: 474

A company has multiple VPCs across AWS Regions to support and run workloads that are isolated from workloads in other Regions. Because of a recent application launch requirement, the company's VPCs must communicate with all other VPCs across all Regions.

Which solution will meet these requirements with the LEAST amount of administrative effort?

- A. Use VPC peering to manage VPC communication in a single Region. Use VPC peering across Regions to manage VPC communications.
- B. Use AWS Direct Connect gateways across all Regions to connect VPCs across regions and manage VPC communications.
- C. Use AWS Transit Gateway to manage VPC communication in a single Region and Transit Gateway peering across Regions to manage VPC communications. **Most Voted**
- D. Use AWS PrivateLink across all Regions to connect VPCs across Regions and manage VPC communications

Suggested Answer: C

Question #: 475

A company is designing a containerized application that will use Amazon Elastic Container Service (Amazon ECS). The application needs to access a shared file system that is highly durable and can recover data to another AWS Region with a recovery point objective (RPO) of 8 hours. The file system needs to provide a mount target in each Availability Zone within a Region.

A solutions architect wants to use AWS Backup to manage the replication to another Region.

Which solution will meet these requirements?

- A. Amazon FSx for Windows File Server with a Multi-AZ deployment
- B. Amazon FSx for NetApp ONTAP with a Multi-AZ deployment
- C. Amazon Elastic File System (Amazon EFS) with the Standard storage class **Most Voted**
- D. Amazon FSx for OpenZFS

Suggested Answer: C

Question #: 476

A company is expecting rapid growth in the near future. A solutions architect needs to configure existing users and grant permissions to new users on AWS. The solutions architect has decided to create IAM groups. The solutions architect will add the new users to IAM groups based on department.

Which additional action is the MOST secure way to grant permissions to the new users?

- A. Apply service control policies (SCPs) to manage access permissions
- B. Create IAM roles that have least privilege permission. Attach the roles to the IAM groups
- C. Create an IAM policy that grants least privilege permission. Attach the policy to the IAM groups **Most Voted**
- D. Create IAM roles. Associate the roles with a permissions boundary that defines the maximum permissions

Suggested Answer: C

Question #: 475

A company is designing a containerized application that will use Amazon Elastic Container Service (Amazon ECS). The application needs to access a shared file system that is highly durable and can recover data to another AWS Region with a recovery point objective (RPO) of 8 hours. The file system needs to provide a mount target in each Availability Zone within a Region.

A solutions architect wants to use AWS Backup to manage the replication to another Region.

Which solution will meet these requirements?

- A. Amazon FSx for Windows File Server with a Multi-AZ deployment
- B. Amazon FSx for NetApp ONTAP with a Multi-AZ deployment
- C. Amazon Elastic File System (Amazon EFS) with the Standard storage class **Most Voted**
- D. Amazon FSx for OpenZFS

Suggested Answer: C

Question #: 476

A company is expecting rapid growth in the near future. A solutions architect needs to configure existing users and grant permissions to new users on AWS. The solutions architect has decided to create IAM groups. The solutions architect will add the new users to IAM groups based on department.

Which additional action is the MOST secure way to grant permissions to the new users?

- A. Apply service control policies (SCPs) to manage access permissions
- B. Create IAM roles that have least privilege permission. Attach the roles to the IAM groups
- C. Create an IAM policy that grants least privilege permission. Attach the policy to the IAM groups **Most Voted**
- D. Create IAM roles. Associate the roles with a permissions boundary that defines the maximum permissions

Suggested Answer: C

Question #: 477

A group requires permissions to list an Amazon S3 bucket and delete objects from that bucket. An administrator has created the following IAM policy to provide access to the bucket and applied that policy to the group. The group is not able to delete objects in the bucket. The company follows least-privilege access rules.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Action": [
        "s3:ListBucket",
        "s3:DeleteObject"
      ],
      "Resource": [
        "arn:aws:s3:::bucket-name"
      ],
      "Effect": "Allow"
    }
  ]
}
```

Which statement should a solutions architect add to the policy to correct bucket access?

```
  "Action": [
    "s3:*Object"
  ],
  "Resource": [
    "arn:aws:s3:::bucket-name/*"
  ],
  "Effect": "Allow"
```

- A.

```
"Action": [
    "s3:*"
],
"Resource": [
    "arn:aws:s3:::bucket-name/*"
],
"Effect": "Allow"
```

• B.

```
"Action": [
    "s3:DeleteObject"
],
"Resource": [
    "arn:aws:s3:::bucket-name*"
],
"Effect": "Allow"
```

• C.

```
"Action": [
    "s3:DeleteObject"
],
"Resource": [
    "arn:aws:s3:::bucket-name/*"
],
"Effect": "Allow"
```

• D.

Most Voted

Suggested Answer: D Question #: 478

A law firm needs to share information with the public. The information includes hundreds of files that must be publicly readable. Modifications or deletions of the files by anyone before a designated future date are prohibited.

Which solution will meet these requirements in the MOST secure way?

- A. Upload all files to an Amazon S3 bucket that is configured for static website hosting. Grant read-only IAM permissions to any AWS principals that access the S3 bucket until the designated date.
- B. Create a new Amazon S3 bucket with S3 Versioning enabled. Use S3 Object Lock with a retention period in accordance with the designated date. Configure the S3 bucket for static website hosting. Set an S3 bucket policy to allow read-only access to the objects. **Most Voted**
- C. Create a new Amazon S3 bucket with S3 Versioning enabled. Configure an event trigger to run an AWS Lambda function in case of object modification or deletion. Configure the Lambda function to replace the objects with the original versions from a private S3 bucket.
- D. Upload all files to an Amazon S3 bucket that is configured for static website hosting. Select the folder that contains the files. Use S3 Object Lock with a retention period in accordance with the designated date. Grant read-only IAM permissions to any AWS principals that access the S3 bucket.

Suggested Answer: B

Question #: 479

A company is making a prototype of the infrastructure for its new website by manually provisioning the necessary infrastructure. This infrastructure includes an Auto Scaling group, an Application Load Balancer and an Amazon RDS database. After the configuration has been thoroughly validated, the company wants the capability to immediately deploy the infrastructure for development and production use in two Availability Zones in an automated fashion.

What should a solutions architect recommend to meet these requirements?

- A. Use AWS Systems Manager to replicate and provision the prototype infrastructure in two Availability Zones
- B. Define the infrastructure as a template by using the prototype infrastructure as a guide. Deploy the infrastructure with AWS CloudFormation. **Most Voted**

- C. Use AWS Config to record the inventory of resources that are used in the prototype infrastructure. Use AWS Config to deploy the prototype infrastructure into two Availability Zones.
- D. Use AWS Elastic Beanstalk and configure it to use an automated reference to the prototype infrastructure to automatically deploy new environments in two Availability Zones.

Suggested Answer: B

Question #: 480

A business application is hosted on Amazon EC2 and uses Amazon S3 for encrypted object storage. The chief information security officer has directed that no application traffic between the two services should traverse the public internet.

Which capability should the solutions architect use to meet the compliance requirements?

- A. AWS Key Management Service (AWS KMS)
- B. VPC endpoint **Most Voted**
- C. Private subnet
- D. Virtual private gateway

Suggested Answer: B

Question #: 481

A company hosts a three-tier web application in the AWS Cloud. A Multi-AZ Amazon RDS for MySQL server forms the database layer Amazon ElastiCache forms the cache layer. The company wants a caching strategy that adds or updates data in the cache when a customer adds an item to the database. The data in the cache must always match the data in the database.

Which solution will meet these requirements?

- A. Implement the lazy loading caching strategy
- B. Implement the write-through caching strategy **Most Voted**

- C. Implement the adding TTL caching strategy
- D. Implement the AWS AppConfig caching strategy

Suggested Answer: B

Question #: 482

A company wants to migrate 100 GB of historical data from an on-premises location to an Amazon S3 bucket. The company has a 100 megabits per second (Mbps) internet connection on premises. The company needs to encrypt the data in transit to the S3 bucket. The company will store new data directly in Amazon S3.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use the s3 sync command in the AWS CLI to move the data directly to an S3 bucket
- B. Use AWS DataSync to migrate the data from the on-premises location to an S3 bucket **Most Voted**
- C. Use AWS Snowball to move the data to an S3 bucket
- D. Set up an IPsec VPN from the on-premises location to AWS. Use the s3 cp command in the AWS CLI to move the data directly to an S3 bucket

Suggested Answer: B

Question #: 483

A company containerized a Windows job that runs on .NET 6 Framework under a Windows container. The company wants to run this job in the AWS Cloud. The job runs every 10 minutes. The job's runtime varies between 1 minute and 3 minutes.

Which solution will meet these requirements MOST cost-effectively?

- A. Create an AWS Lambda function based on the container image of the job. Configure Amazon EventBridge to invoke the function every 10 minutes.
- B. Use AWS Batch to create a job that uses AWS Fargate resources. Configure the job scheduling to run every 10 minutes.

- C. Use Amazon Elastic Container Service (Amazon ECS) on AWS Fargate to run the job. Create a scheduled task based on the container image of the job to run every 10 minutes. **Most Voted**
- D. Use Amazon Elastic Container Service (Amazon ECS) on AWS Fargate to run the job. Create a standalone task based on the container image of the job. Use Windows task scheduler to run the job every 10 minutes.

Suggested Answer: C

Question #: 484

A company wants to move from many standalone AWS accounts to a consolidated, multi-account architecture. The company plans to create many new AWS accounts for different business units. The company needs to authenticate access to these AWS accounts by using a centralized corporate directory service.

Which combination of actions should a solutions architect recommend to meet these requirements? (Choose two.)

- A. Create a new organization in AWS Organizations with all features turned on. Create the new AWS accounts in the organization. **Most Voted**
- B. Set up an Amazon Cognito identity pool. Configure AWS IAM Identity Center (AWS Single Sign-On) to accept Amazon Cognito authentication.
- C. Configure a service control policy (SCP) to manage the AWS accounts. Add AWS IAM Identity Center (AWS Single Sign-On) to AWS Directory Service.
- D. Create a new organization in AWS Organizations. Configure the organization's authentication mechanism to use AWS Directory Service directly.
- E. Set up AWS IAM Identity Center (AWS Single Sign-On) in the organization. Configure IAM Identity Center, and integrate it with the company's corporate directory service. **Most Voted**

Suggested Answer: AE

Question #: 485

A company is looking for a solution that can store video archives in AWS from old news footage. The company needs to minimize costs and will rarely need to restore these files. When the files are needed, they must be

available in a maximum of five minutes.

What is the MOST cost-effective solution?

- A. Store the video archives in Amazon S3 Glacier and use Expedited retrievals. **Most Voted**
- B. Store the video archives in Amazon S3 Glacier and use Standard retrievals.
- C. Store the video archives in Amazon S3 Standard-Infrequent Access (S3 Standard-IA).
- D. Store the video archives in Amazon S3 One Zone-Infrequent Access (S3 One Zone-IA).

Suggested Answer: A

Question #: 486

A company is building a three-tier application on AWS. The presentation tier will serve a static website. The logic tier is a containerized application. This application will store data in a relational database. The company wants to simplify deployment and to reduce operational costs.

Which solution will meet these requirements?

- A. Use Amazon S3 to host static content. Use Amazon Elastic Container Service (Amazon ECS) with AWS Fargate for compute power. Use a managed Amazon RDS cluster for the database. **Most Voted**
- B. Use Amazon CloudFront to host static content. Use Amazon Elastic Container Service (Amazon ECS) with Amazon EC2 for compute power. Use a managed Amazon RDS cluster for the database.
- C. Use Amazon S3 to host static content. Use Amazon Elastic Kubernetes Service (Amazon EKS) with AWS Fargate for compute power. Use a managed Amazon RDS cluster for the database.
- D. Use Amazon EC2 Reserved Instances to host static content. Use Amazon Elastic Kubernetes Service (Amazon EKS) with Amazon EC2 for compute power. Use a managed Amazon RDS cluster for the database.

Suggested Answer: A

Question #: 487

A company seeks a storage solution for its application. The solution must be highly available and scalable. The solution also must function as a file system be mountable by multiple Linux instances in AWS and on premises through native protocols, and have no minimum size requirements. The company has set up a Site-to-Site VPN for access from its on-premises network to its VPC.

Which storage solution meets these requirements?

- A. Amazon FSx Multi-AZ deployments
- B. Amazon Elastic Block Store (Amazon EBS) Multi-Attach volumes
- C. Amazon Elastic File System (Amazon EFS) with multiple mount targets **Most Voted**
- D. Amazon Elastic File System (Amazon EFS) with a single mount target and multiple access points

Suggested Answer: C

Exam question from Amazon's AWS Certified Solutions Architect - Associate SAA-C03

Question #: 488

A 4-year-old media company is using the AWS Organizations all features feature set to organize its AWS accounts. According to the company's finance team, the billing information on the member accounts must not be accessible to anyone, including the root user of the member accounts.

Which solution will meet these requirements?

- A. Add all finance team users to an IAM group. Attach an AWS managed policy named Billing to the group.
- B. Attach an identity-based policy to deny access to the billing information to all users, including the root user.
- C. Create a service control policy (SCP) to deny access to the billing information. Attach the SCP to the root organizational unit (OU). **Most Voted**
- D. Convert from the Organizations all features feature set to the Organizations consolidated billing feature set.

Suggested Answer: C

Question #: 489

An ecommerce company runs an application in the AWS Cloud that is integrated with an on-premises warehouse solution. The company uses Amazon Simple Notification Service (Amazon SNS) to send order messages to an on-premises HTTPS endpoint so the warehouse application can process the orders. The local data center team has detected that some of the order messages were not received.

A solutions architect needs to retain messages that are not delivered and analyze the messages for up to 14 days.

Which solution will meet these requirements with the LEAST development effort?

- A. Configure an Amazon SNS dead letter queue that has an Amazon Kinesis Data Stream target with a retention period of 14 days.
- B. Add an Amazon Simple Queue Service (Amazon SQS) queue with a retention period of 14 days between the application and Amazon SNS. **Most Voted**
- C. Configure an Amazon SNS dead letter queue that has an Amazon Simple Queue Service (Amazon SQS) target with a retention period of 14 days. **Most Voted**
- D. Configure an Amazon SNS dead letter queue that has an Amazon DynamoDB target with a TTL attribute set for a retention period of 14 days.

Suggested Answer: C

Question #: 490

A gaming company uses Amazon DynamoDB to store user information such as geographic location, player data, and leaderboards. The company needs to configure continuous backups to an Amazon S3 bucket with a minimal amount of coding. The backups must not affect availability of the application and must not affect the read capacity units (RCUs) that are defined for the table.

Which solution meets these requirements?

- A. Use an Amazon EMR cluster. Create an Apache Hive job to back up the data to Amazon S3.

- B. Export the data directly from DynamoDB to Amazon S3 with continuous backups. Turn on point-in-time recovery for the table. **Most Voted**
- C. Configure Amazon DynamoDB Streams. Create an AWS Lambda function to consume the stream and export the data to an Amazon S3 bucket.
- D. Create an AWS Lambda function to export the data from the database tables to Amazon S3 on a regular basis. Turn on point-in-time recovery for the table.

Suggested Answer: B

Question #: 491

A solutions architect is designing an asynchronous application to process credit card data validation requests for a bank. The application must be secure and be able to process each request at least once.

Which solution will meet these requirements MOST cost-effectively?

- A. Use AWS Lambda event source mapping. Set Amazon Simple Queue Service (Amazon SQS) standard queues as the event source. Use AWS Key Management Service (SSE-KMS) for encryption. Add the kms:Decrypt permission for the Lambda execution role. **Most Voted**
- B. Use AWS Lambda event source mapping. Use Amazon Simple Queue Service (Amazon SQS) FIFO queues as the event source. Use SQS managed encryption keys (SSE-SQS) for encryption. Add the encryption key invocation permission for the Lambda function.
- C. Use the AWS Lambda event source mapping. Set Amazon Simple Queue Service (Amazon SQS) FIFO queues as the event source. Use AWS KMS keys (SSE-KMS). Add the kms:Decrypt permission for the Lambda execution role.
- D. Use the AWS Lambda event source mapping. Set Amazon Simple Queue Service (Amazon SQS) standard queues as the event source. Use AWS KMS keys (SSE-KMS) for encryption. Add the encryption key invocation permission for the Lambda function.

Suggested Answer: A

Question #: 492

A company has multiple AWS accounts for development work. Some staff consistently use oversized Amazon EC2 instances, which causes the company to exceed the yearly budget for the development accounts. The company wants to centrally restrict the creation of AWS resources in these accounts.

Which solution will meet these requirements with the LEAST development effort?

- A. Develop AWS Systems Manager templates that use an approved EC2 creation process. Use the approved Systems Manager templates to provision EC2 instances.
- B. Use AWS Organizations to organize the accounts into organizational units (OUs). Define and attach a service control policy (SCP) to control the usage of EC2 instance types. **Most Voted**
- C. Configure an Amazon EventBridge rule that invokes an AWS Lambda function when an EC2 instance is created. Stop disallowed EC2 instance types.
- D. Set up AWS Service Catalog products for the staff to create the allowed EC2 instance types. Ensure that staff can deploy EC2 instances only by using the Service Catalog products.

Suggested Answer: B

Question #: 493

A company wants to use artificial intelligence (AI) to determine the quality of its customer service calls. The company currently manages calls in four different languages, including English. The company will offer new languages in the future. The company does not have the resources to regularly maintain machine learning (ML) models.

The company needs to create written sentiment analysis reports from the customer service call recordings. The customer service call recording text must be translated into English.

Which combination of steps will meet these requirements? (Choose three.)

- A. Use Amazon Comprehend to translate the audio recordings into English.
- B. Use Amazon Lex to create the written sentiment analysis reports.

- C. Use Amazon Polly to convert the audio recordings into text.
- D. Use Amazon Transcribe to convert the audio recordings in any language into text. **Most Voted**
- E. Use Amazon Translate to translate text in any language to English. **Most Voted**
- F. Use Amazon Comprehend to create the sentiment analysis reports. **Most Voted**

Suggested Answer: DEF

Question #: 494

A company uses Amazon EC2 instances to host its internal systems. As part of a deployment operation, an administrator tries to use the AWS CLI to terminate an EC2 instance. However, the administrator receives a 403 (Access Denied) error message.

The administrator is using an IAM role that has the following IAM policy attached:

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": ["ec2:TerminateInstances"],
      "Resource": ["*"]
    },
    {
      "Effect": "Deny",
      "Action": ["ec2:TerminateInstances"],
      "Condition": {
        "NotIpAddress": {
          "aws:SourceIp": [
            "192.0.2.0/24",
            "203.0.113.0/24"
          ]
        }
      },
      "Resource": ["*"]
    }
  ]
}

```

What is the cause of the unsuccessful request?

- A. The EC2 instance has a resource-based policy with a Deny statement.
- B. The principal has not been specified in the policy statement.
- C. The "Action" field does not grant the actions that are required to terminate the EC2 instance.
- D. The request to terminate the EC2 instance does not originate from the CIDR blocks 192.0.2.0/24 or 203.0.113.0/24. **Most Voted**

Suggested Answer: D

Question #: 495

A company is conducting an internal audit. The company wants to ensure that the data in an Amazon S3 bucket that is associated with the company's AWS Lake Formation data lake does not contain sensitive customer or employee data. The company wants to discover personally identifiable information (PII) or financial information, including passport numbers and credit card numbers.

Which solution will meet these requirements?

- A. Configure AWS Audit Manager on the account. Select the Payment Card Industry Data Security Standards (PCI DSS) for auditing.
- B. Configure Amazon S3 Inventory on the S3 bucket Configure Amazon Athena to query the inventory.
- C. Configure Amazon Macie to run a data discovery job that uses managed identifiers for the required data types. **Most Voted**
- D. Use Amazon S3 Select to run a report across the S3 bucket.

Suggested Answer: C

Question #: 496

A company uses on-premises servers to host its applications. The company is running out of storage capacity. The applications use both block storage and NFS storage. The company needs a high-performing solution that supports local caching without re-architecting its existing applications.

Which combination of actions should a solutions architect take to meet these requirements? (Choose two.)

- A. Mount Amazon S3 as a file system to the on-premises servers.
- B. Deploy an AWS Storage Gateway file gateway to replace NFS storage. **Most Voted**
- C. Deploy AWS Snowball Edge to provision NFS mounts to on-premises servers.

- D. Deploy an AWS Storage Gateway volume gateway to replace the block storage. **Most Voted**
- E. Deploy Amazon Elastic File System (Amazon EFS) volumes and mount them to on-premises servers.

Suggested Answer: BD

Question #: 497

A company has a service that reads and writes large amounts of data from an Amazon S3 bucket in the same AWS Region. The service is deployed on Amazon EC2 instances within the private subnet of a VPC. The service communicates with Amazon S3 over a NAT gateway in the public subnet. However, the company wants a solution that will reduce the data output costs.

Which solution will meet these requirements MOST cost-effectively?

- A. Provision a dedicated EC2 NAT instance in the public subnet. Configure the route table for the private subnet to use the elastic network interface of this instance as the destination for all S3 traffic.
- B. Provision a dedicated EC2 NAT instance in the private subnet. Configure the route table for the public subnet to use the elastic network interface of this instance as the destination for all S3 traffic.
- C. Provision a VPC gateway endpoint. Configure the route table for the private subnet to use the gateway endpoint as the route for all S3 traffic. **Most Voted**
- D. Provision a second NAT gateway. Configure the route table for the private subnet to use this NAT gateway as the destination for all S3 traffic.

Suggested Answer: C

Question #: 498

A company uses Amazon S3 to store high-resolution pictures in an S3 bucket. To minimize application changes, the company stores the pictures as the latest version of an S3 object. The company needs to retain only the two most recent versions of the pictures.

The company wants to reduce costs. The company has identified the S3 bucket as a large expense.

Which solution will reduce the S3 costs with the LEAST operational overhead?

- A. Use S3 Lifecycle to delete expired object versions and retain the two most recent versions. **Most Voted**
- B. Use an AWS Lambda function to check for older versions and delete all but the two most recent versions.
- C. Use S3 Batch Operations to delete noncurrent object versions and retain only the two most recent versions.
- D. Deactivate versioning on the S3 bucket and retain the two most recent versions.

Suggested Answer: A

Question #: 499

A company needs to minimize the cost of its 1 Gbps AWS Direct Connect connection. The company's average connection utilization is less than 10%. A solutions architect must recommend a solution that will reduce the cost without compromising security.

Which solution will meet these requirements?

- A. Set up a new 1 Gbps Direct Connect connection. Share the connection with another AWS account.
- B. Set up a new 200 Mbps Direct Connect connection in the AWS Management Console.
- C. Contact an AWS Direct Connect Partner to order a 1 Gbps connection. Share the connection with another AWS account.
- D. Contact an AWS Direct Connect Partner to order a 200 Mbps hosted connection for an existing AWS account. **Most Voted**

Suggested Answer: D

Question #: 500

A company has multiple Windows file servers on premises. The company wants to migrate and consolidate its files into an Amazon FSx for Windows File Server file system. File permissions must be preserved to ensure that access rights do not change.

Which solutions will meet these requirements? (Choose two.)

- A. Deploy AWS DataSync agents on premises. Schedule DataSync tasks to transfer the data to the FSx for Windows File Server file system. **Most Voted**
- B. Copy the shares on each file server into Amazon S3 buckets by using the AWS CLI. Schedule AWS DataSync tasks to transfer the data to the FSx for Windows File Server file system.
- C. Remove the drives from each file server. Ship the drives to AWS for import into Amazon S3. Schedule AWS DataSync tasks to transfer the data to the FSx for Windows File Server file system.
- D. Order an AWS Snowcone device. Connect the device to the on-premises network. Launch AWS DataSync agents on the device. Schedule DataSync tasks to transfer the data to the FSx for Windows File Server file system. **Most Voted**
- E. Order an AWS Snowball Edge Storage Optimized device. Connect the device to the on-premises network. Copy data to the device by using the AWS CLI. Ship the device back to AWS for import into Amazon S3. Schedule AWS DataSync tasks to transfer the data to the FSx for Windows File Server file system.

Suggested Answer: AD

Question #: 501

A company wants to ingest customer payment data into the company's data lake in Amazon S3. The company receives payment data every minute on average. The company wants to analyze the payment data in real time. Then the company wants to ingest the data into the data lake.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Use Amazon Kinesis Data Streams to ingest data. Use AWS Lambda to analyze the data in real time.
- B. Use AWS Glue to ingest data. Use Amazon Kinesis Data Analytics to analyze the data in real time.
- C. Use Amazon Kinesis Data Firehose to ingest data. Use Amazon Kinesis Data Analytics to analyze the data in real time. **Most Voted**
- D. Use Amazon API Gateway to ingest data. Use AWS Lambda to analyze the data in real time.

Suggested Answer: C

Question #: 502

A company runs a website that uses a content management system (CMS) on Amazon EC2. The CMS runs on a single EC2 instance and uses an Amazon Aurora MySQL Multi-AZ DB instance for the data tier. Website images are stored on an Amazon Elastic Block Store (Amazon EBS) volume that is mounted inside the EC2 instance.

Which combination of actions should a solutions architect take to improve the performance and resilience of the website? (Choose two.)

- A. Move the website images into an Amazon S3 bucket that is mounted on every EC2 instance
- B. Share the website images by using an NFS share from the primary EC2 instance. Mount this share on the other EC2 instances.
- C. Move the website images onto an Amazon Elastic File System (Amazon EFS) file system that is mounted on every EC2 instance. **Most Voted**
- D. Create an Amazon Machine Image (AMI) from the existing EC2 instance. Use the AMI to provision new instances behind an Application Load Balancer as part of an Auto Scaling group. Configure the Auto Scaling group to maintain a minimum of two instances. Configure an accelerator in AWS Global Accelerator for the website
- E. Create an Amazon Machine Image (AMI) from the existing EC2 instance. Use the AMI to provision new instances behind an Application Load Balancer as part of an Auto Scaling group. Configure the Auto Scaling group to maintain a minimum of two instances. Configure an Amazon CloudFront distribution for the website. **Most Voted**

Suggested Answer: CE

Question #: 503

A company runs an infrastructure monitoring service. The company is building a new feature that will enable the service to monitor data in customer AWS accounts. The new feature will call AWS APIs in customer accounts to describe Amazon EC2 instances and read Amazon CloudWatch metrics.

What should the company do to obtain access to customer accounts in the MOST secure way?

- A. Ensure that the customers create an IAM role in their account with read-only EC2 and CloudWatch permissions and a trust policy to the company's account. **Most Voted**
- B. Create a serverless API that implements a token vending machine to provide temporary AWS credentials for a role with read-only EC2 and CloudWatch permissions.
- C. Ensure that the customers create an IAM user in their account with read-only EC2 and CloudWatch permissions. Encrypt and store customer access and secret keys in a secrets management system.
- D. Ensure that the customers create an Amazon Cognito user in their account to use an IAM role with read-only EC2 and CloudWatch permissions. Encrypt and store the Amazon Cognito user and password in a secrets management system.

Suggested Answer: A

Question #: 504

A company needs to connect several VPCs in the us-east-1 Region that span hundreds of AWS accounts. The company's networking team has its own AWS account to manage the cloud network.

What is the MOST operationally efficient solution to connect the VPCs?

- A. Set up VPC peering connections between each VPC. Update each associated subnet's route table
- B. Configure a NAT gateway and an internet gateway in each VPC to connect each VPC through the internet
- C. Create an AWS Transit Gateway in the networking team's AWS account. Configure static routes from each VPC. **Most Voted**
- D. Deploy VPN gateways in each VPC. Create a transit VPC in the networking team's AWS account to connect to each VPC.

Suggested Answer: C

Question #: 505

A company has Amazon EC2 instances that run nightly batch jobs to process data. The EC2 instances run in an Auto Scaling group that uses On-Demand billing. If a job fails on one instance, another instance will reprocess the job. The batch jobs run between 12:00 AM and 06:00 AM local time every day.

Which solution will provide EC2 instances to meet these requirements MOST cost-effectively?

- A. Purchase a 1-year Savings Plan for Amazon EC2 that covers the instance family of the Auto Scaling group that the batch job uses.
- B. Purchase a 1-year Reserved Instance for the specific instance type and operating system of the instances in the Auto Scaling group that the batch job uses.
- C. Create a new launch template for the Auto Scaling group. Set the instances to Spot Instances. Set a policy to scale out based on CPU usage. **Most Voted**
- D. Create a new launch template for the Auto Scaling group. Increase the instance size. Set a policy to scale out based on CPU usage.

Suggested Answer: C

Question #: 506

A social media company is building a feature for its website. The feature will give users the ability to upload photos. The company expects significant increases in demand during large events and must ensure that the website can handle the upload traffic from users.

Which solution meets these requirements with the MOST scalability?

- A. Upload files from the user's browser to the application servers. Transfer the files to an Amazon S3 bucket.
- B. Provision an AWS Storage Gateway file gateway. Upload files directly from the user's browser to the file gateway.
- C. Generate Amazon S3 presigned URLs in the application. Upload files directly from the user's browser into an S3 bucket. **Most Voted**
- D. Provision an Amazon Elastic File System (Amazon EFS) file system. Upload files directly from the user's browser to the file system.

Suggested Answer: C

Question #: 507

A company has a web application for travel ticketing. The application is based on a database that runs in a single data center in North America. The company wants to expand the application to serve a global user base. The company needs to deploy the application to multiple AWS Regions. Average latency must be less than 1 second on updates to the reservation database.

The company wants to have separate deployments of its web platform across multiple Regions. However, the company must maintain a single primary reservation database that is globally consistent.

Which solution should a solutions architect recommend to meet these requirements?

- A. Convert the application to use Amazon DynamoDB. Use a global table for the center reservation table. Use the correct Regional endpoint in each Regional deployment. **Most Voted**
- B. Migrate the database to an Amazon Aurora MySQL database. Deploy Aurora Read Replicas in each Region. Use the correct Regional endpoint in each Regional deployment for access to the database.
- C. Migrate the database to an Amazon RDS for MySQL database. Deploy MySQL read replicas in each Region. Use the correct Regional endpoint in each Regional deployment for access to the database.
- D. Migrate the application to an Amazon Aurora Serverless database. Deploy instances of the database to each Region. Use the correct Regional endpoint in each Regional deployment to access the database. Use AWS Lambda functions to process event streams in each Region to synchronize the databases.

Suggested Answer: A

Question #: 508

A company has migrated multiple Microsoft Windows Server workloads to Amazon EC2 instances that run in the us-west-1 Region. The company manually backs up the workloads to create an image as needed.

In the event of a natural disaster in the us-west-1 Region, the company wants to recover workloads quickly in the us-west-2 Region. The company wants no more than 24 hours of data loss on the EC2 instances. The company also wants to automate any backups of the EC2 instances.

Which solutions will meet these requirements with the LEAST administrative effort? (Choose two.)

- A. Create an Amazon EC2-backed Amazon Machine Image (AMI) lifecycle policy to create a backup based on tags. Schedule the backup to run twice daily. Copy the image on demand.
- B. Create an Amazon EC2-backed Amazon Machine Image (AMI) lifecycle policy to create a backup based on tags. Schedule the backup to run twice daily. Configure the copy to the us-west-2 Region. **Most Voted**
- C. Create backup vaults in us-west-1 and in us-west-2 by using AWS Backup. Create a backup plan for the EC2 instances based on tag values. Create an AWS Lambda function to run as a scheduled job to copy the backup data to us-west-2.
- D. Create a backup vault by using AWS Backup. Use AWS Backup to create a backup plan for the EC2 instances based on tag values. Define the destination for the copy as us-west-2. Specify the backup schedule to run twice daily. **Most Voted**
- E. Create a backup vault by using AWS Backup. Use AWS Backup to create a backup plan for the EC2 instances based on tag values. Specify the backup schedule to run twice daily. Copy on demand to us-west-2.

Suggested Answer: BD

Question #: 509

A company operates a two-tier application for image processing. The application uses two Availability Zones, each with one public subnet and one private subnet. An Application Load Balancer (ALB) for the web tier uses the public subnets. Amazon EC2 instances for the application tier use the private subnets.

Users report that the application is running more slowly than expected. A security audit of the web server log files shows that the application is receiving millions of illegitimate requests from a small number of IP addresses. A solutions architect needs to resolve the immediate performance problem while the company investigates a more permanent solution.

What should the solutions architect recommend to meet this requirement?

- A. Modify the inbound security group for the web tier. Add a deny rule for the IP addresses that are consuming resources.
- B. Modify the network ACL for the web tier subnets. Add an inbound deny rule for the IP addresses that are consuming resources. **Most Voted**

- C. Modify the inbound security group for the application tier. Add a deny rule for the IP addresses that are consuming resources.
- D. Modify the network ACL for the application tier subnets. Add an inbound deny rule for the IP addresses that are consuming resources.

Suggested Answer: B

Question #: 510

A global marketing company has applications that run in the ap-southeast-2 Region and the eu-west-1 Region. Applications that run in a VPC in eu-west-1 need to communicate securely with databases that run in a VPC in ap-southeast-2.

Which network design will meet these requirements?

- A. Create a VPC peering connection between the eu-west-1 VPC and the ap-southeast-2 VPC. Create an inbound rule in the eu-west-1 application security group that allows traffic from the database server IP addresses in the ap-southeast-2 security group.
- B. Configure a VPC peering connection between the ap-southeast-2 VPC and the eu-west-1 VPC. Update the subnet route tables. Create an inbound rule in the ap-southeast-2 database security group that references the security group ID of the application servers in eu-west-1. **Most Voted**
- C. Configure a VPC peering connection between the ap-southeast-2 VPC and the eu-west-1 VPC. Update the subnet route tables. Create an inbound rule in the ap-southeast-2 database security group that allows traffic from the eu-west-1 application server IP addresses. **Most Voted**
- D. Create a transit gateway with a peering attachment between the eu-west-1 VPC and the ap-southeast-2 VPC. After the transit gateways are properly peered and routing is configured, create an inbound rule in the database security group that references the security group ID of the application servers in eu-west-1.

Suggested Answer: C

Question #: 511

A company is developing software that uses a PostgreSQL database schema. The company needs to configure multiple development environments and databases for the company's developers. On average, each

development environment is used for half of the 8-hour workday.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure each development environment with its own Amazon Aurora PostgreSQL database
- B. Configure each development environment with its own Amazon RDS for PostgreSQL Single-AZ DB instances
- C. Configure each development environment with its own Amazon Aurora On-Demand PostgreSQL-Compatible database **Most Voted**
- D. Configure each development environment with its own Amazon S3 bucket by using Amazon S3 Object Select

Suggested Answer: C

Question #: 512

A company uses AWS Organizations with resources tagged by account. The company also uses AWS Backup to back up its AWS infrastructure resources. The company needs to back up all AWS resources.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Config to identify all untagged resources. Tag the identified resources programmatically. Use tags in the backup plan. **Most Voted**
- B. Use AWS Config to identify all resources that are not running. Add those resources to the backup vault.
- C. Require all AWS account owners to review their resources to identify the resources that need to be backed up.
- D. Use Amazon Inspector to identify all noncompliant resources.

Suggested Answer: A

Question #: 513

A social media company wants to allow its users to upload images in an application that is hosted in the AWS Cloud. The company needs a solution that automatically resizes the images so that the images can be displayed on multiple device types. The application experiences unpredictable traffic patterns throughout the day. The

company is seeking a highly available solution that maximizes scalability.

What should a solutions architect do to meet these requirements?

- A. Create a static website hosted in Amazon S3 that invokes AWS Lambda functions to resize the images and store the images in an Amazon S3 bucket. **Most Voted**
- B. Create a static website hosted in Amazon CloudFront that invokes AWS Step Functions to resize the images and store the images in an Amazon RDS database.
- C. Create a dynamic website hosted on a web server that runs on an Amazon EC2 instance. Configure a process that runs on the EC2 instance to resize the images and store the images in an Amazon S3 bucket.
- D. Create a dynamic website hosted on an automatically scaling Amazon Elastic Container Service (Amazon ECS) cluster that creates a resize job in Amazon Simple Queue Service (Amazon SQS). Set up an image-resizing program that runs on an Amazon EC2 instance to process the resize jobs.

Suggested Answer: A

Question #: 514

A company is running a microservices application on Amazon EC2 instances. The company wants to migrate the application to an Amazon Elastic Kubernetes Service (Amazon EKS) cluster for scalability. The company must configure the Amazon EKS control plane with endpoint private access set to true and endpoint public access set to false to maintain security compliance. The company must also put the data plane in private subnets. However, the company has received error notifications because the node cannot join the cluster.

Which solution will allow the node to join the cluster?

- A. Grant the required permission in AWS Identity and Access Management (IAM) to the AmazonEKSNodeRole IAM role. **Most Voted**
- B. Create interface VPC endpoints to allow nodes to access the control plane. **Most Voted**
- C. Recreate nodes in the public subnet. Restrict security groups for EC2 nodes.
- D. Allow outbound traffic in the security group of the nodes.

Suggested Answer: B

Question #: 515

A company is migrating an on-premises application to AWS. The company wants to use Amazon Redshift as a solution.

Which use cases are suitable for Amazon Redshift in this scenario? (Choose three.)

- A. Supporting data APIs to access data with traditional, containerized, and event-driven applications
- B. Supporting client-side and server-side encryption **Most Voted**
- C. Building analytics workloads during specified hours and when the application is not active **Most Voted**
- D. Caching data to reduce the pressure on the backend database
- E. Scaling globally to support petabytes of data and tens of millions of requests per minute **Most Voted**
- F. Creating a secondary replica of the cluster by using the AWS Management Console

Suggested Answer: BCE

Question #: 516

A company provides an API interface to customers so the customers can retrieve their financial information. The company expects a larger number of requests during peak usage times of the year.

The company requires the API to respond consistently with low latency to ensure customer satisfaction. The company needs to provide a compute host for the API.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use an Application Load Balancer and Amazon Elastic Container Service (Amazon ECS).
- B. Use Amazon API Gateway and AWS Lambda functions with provisioned concurrency. **Most Voted**
- C. Use an Application Load Balancer and an Amazon Elastic Kubernetes Service (Amazon EKS) cluster.
- D. Use Amazon API Gateway and AWS Lambda functions with reserved concurrency.

Suggested Answer: B

Question #: 517

A company wants to send all AWS Systems Manager Session Manager logs to an Amazon S3 bucket for archival purposes.

Which solution will meet this requirement with the MOST operational efficiency?

- A. Enable S3 logging in the Systems Manager console. Choose an S3 bucket to send the session data to. **Most Voted**
- B. Install the Amazon CloudWatch agent. Push all logs to a CloudWatch log group. Export the logs to an S3 bucket from the group for archival purposes.
- C. Create a Systems Manager document to upload all server logs to a central S3 bucket. Use Amazon EventBridge to run the Systems Manager document against all servers that are in the account daily.
- D. Install an Amazon CloudWatch agent. Push all logs to a CloudWatch log group. Create a CloudWatch logs subscription that pushes any incoming log events to an Amazon Kinesis Data Firehose delivery stream. Set Amazon S3 as the destination.

Suggested Answer: A

Question #: 518

An application uses an Amazon RDS MySQL DB instance. The RDS database is becoming low on disk space. A solutions architect wants to increase the disk space without downtime.

Which solution meets these requirements with the LEAST amount of effort?

- A. Enable storage autoscaling in RDS **Most Voted**
- B. Increase the RDS database instance size
- C. Change the RDS database instance storage type to Provisioned IOPS
- D. Back up the RDS database, increase the storage capacity, restore the database, and stop the previous instance

Suggested Answer: A

Question #: 519

A consulting company provides professional services to customers worldwide. The company provides solutions and tools for customers to expedite gathering and analyzing data on AWS. The company needs to centrally manage and deploy a common set of solutions and tools for customers to use for self-service purposes.

Which solution will meet these requirements?

- A. Create AWS CloudFormation templates for the customers.
- B. Create AWS Service Catalog products for the customers. **Most Voted**
- C. Create AWS Systems Manager templates for the customers.
- D. Create AWS Config items for the customers.

Suggested Answer: B

Question #: 520

A company is designing a new web application that will run on Amazon EC2 Instances. The application will use Amazon DynamoDB for backend data storage. The application traffic will be unpredictable. The company expects that the application read and write throughput to the database will be moderate to high. The company needs to scale in response to application traffic.

Which DynamoDB table configuration will meet these requirements MOST cost-effectively?

- A. Configure DynamoDB with provisioned read and write by using the DynamoDB Standard table class. Set DynamoDB auto scaling to a maximum defined capacity.
- B. Configure DynamoDB in on-demand mode by using the DynamoDB Standard table class. **Most Voted**
- C. Configure DynamoDB with provisioned read and write by using the DynamoDB Standard Infrequent Access (DynamoDB Standard-IA) table class. Set DynamoDB auto scaling to a maximum defined capacity.
- D. Configure DynamoDB in on-demand mode by using the DynamoDB Standard Infrequent Access (DynamoDB Standard-IA) table class.

Suggested Answer: B

Question #: 521

A retail company has several businesses. The IT team for each business manages its own AWS account. Each team account is part of an organization in AWS Organizations. Each team monitors its product inventory levels in an Amazon DynamoDB table in the team's own AWS account.

The company is deploying a central inventory reporting application into a shared AWS account. The application must be able to read items from all the teams' DynamoDB tables.

Which authentication option will meet these requirements MOST securely?

- A. Integrate DynamoDB with AWS Secrets Manager in the inventory application account. Configure the application to use the correct secret from Secrets Manager to authenticate and read the DynamoDB table. Schedule secret rotation for every 30 days.
- B. In every business account, create an IAM user that has programmatic access. Configure the application to use the correct IAM user access key ID and secret access key to authenticate and read the DynamoDB table. Manually rotate IAM access keys every 30 days.
- C. In every business account, create an IAM role named BU_ROLE with a policy that gives the role access to the DynamoDB table and a trust policy to trust a specific role in the inventory application account. In the inventory account, create a role named APP_ROLE that allows access to the STS AssumeRole API operation. Configure the application to use APP_ROLE and assume the crossaccount role BU_ROLE to read the DynamoDB table. **Most Voted**
- D. Integrate DynamoDB with AWS Certificate Manager (ACM). Generate identity certificates to authenticate DynamoDB. Configure the application to use the correct certificate to authenticate and read the DynamoDB table.

Suggested Answer: C

Question #: 522

A company runs container applications by using Amazon Elastic Kubernetes Service (Amazon EKS). The company's workload is not consistent throughout the day. The company wants Amazon EKS to scale in and out

according to the workload.

Which combination of steps will meet these requirements with the LEAST operational overhead? (Choose two.)

- A. Use an AWS Lambda function to resize the EKS cluster.
- B. Use the Kubernetes Metrics Server to activate horizontal pod autoscaling. **Most Voted**
- C. Use the Kubernetes Cluster Autoscaler to manage the number of nodes in the cluster. **Most Voted**
- D. Use Amazon API Gateway and connect it to Amazon EKS.
- E. Use AWS App Mesh to observe network activity.

Suggested Answer: BC

Question #: 523

A company runs a microservice-based serverless web application. The application must be able to retrieve data from multiple Amazon DynamoDB tables. A solutions architect needs to give the application the ability to retrieve the data with no impact on the baseline performance of the application.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. AWS AppSync pipeline resolvers
- B. Amazon CloudFront with Lambda@Edge functions **Most Voted**
- C. Edge-optimized Amazon API Gateway with AWS Lambda functions
- D. Amazon Athena Federated Query with a DynamoDB connector **Most Voted**

Suggested Answer: A

Question #: 524

A company wants to analyze and troubleshoot Access Denied errors and Unauthorized errors that are related to IAM permissions. The company has AWS CloudTrail turned on.

Which solution will meet these requirements with the LEAST effort?

- A. Use AWS Glue and write custom scripts to query CloudTrail logs for the errors.
- B. Use AWS Batch and write custom scripts to query CloudTrail logs for the errors.
- C. Search CloudTrail logs with Amazon Athena queries to identify the errors. **Most Voted**
- D. Search CloudTrail logs with Amazon QuickSight. Create a dashboard to identify the errors.

Suggested Answer: C

Question #: 525

A company wants to add its existing AWS usage cost to its operation cost dashboard. A solutions architect needs to recommend a solution that will give the company access to its usage cost programmatically. The company must be able to access cost data for the current year and forecast costs for the next 12 months.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Access usage cost-related data by using the AWS Cost Explorer API with pagination. **Most Voted**
- B. Access usage cost-related data by using downloadable AWS Cost Explorer report .csv files.
- C. Configure AWS Budgets actions to send usage cost data to the company through FTP.
- D. Create AWS Budgets reports for usage cost data. Send the data to the company through SMTP.

Suggested Answer: A

Question #: 526

A solutions architect is reviewing the resilience of an application. The solutions architect notices that a database administrator recently failed over the application's Amazon Aurora PostgreSQL database writer instance as part of a scaling exercise. The failover resulted in 3 minutes of downtime for the application.

Which solution will reduce the downtime for scaling exercises with the LEAST operational overhead?

- A. Create more Aurora PostgreSQL read replicas in the cluster to handle the load during failover.
- B. Set up a secondary Aurora PostgreSQL cluster in the same AWS Region. During failover, update the application to use the secondary cluster's writer endpoint.

- C. Create an Amazon ElastiCache for Memcached cluster to handle the load during failover.
- D. Set up an Amazon RDS proxy for the database. Update the application to use the proxy endpoint. **Most Voted**

Suggested Answer: D

Question #: 527

A company has a regional subscription-based streaming service that runs in a single AWS Region. The architecture consists of web servers and application servers on Amazon EC2 instances. The EC2 instances are in Auto Scaling groups behind Elastic Load Balancers. The architecture includes an Amazon Aurora global database cluster that extends across multiple Availability Zones.

The company wants to expand globally and to ensure that its application has minimal downtime.

Which solution will provide the MOST fault tolerance?

- A. Extend the Auto Scaling groups for the web tier and the application tier to deploy instances in Availability Zones in a second Region. Use an Aurora global database to deploy the database in the primary Region and the second Region. Use Amazon Route 53 health checks with a failover routing policy to the second Region.
- B. Deploy the web tier and the application tier to a second Region. Add an Aurora PostgreSQL cross-Region Aurora Replica in the second Region. Use Amazon Route 53 health checks with a failover routing policy to the second Region. Promote the secondary to primary as needed.
- C. Deploy the web tier and the application tier to a second Region. Create an Aurora PostgreSQL database in the second Region. Use AWS Database Migration Service (AWS DMS) to replicate the primary database to the second Region. Use Amazon Route 53 health checks with a failover routing policy to the second Region.
- D. Deploy the web tier and the application tier to a second Region. Use an Amazon Aurora global database to deploy the database in the primary Region and the second Region. Use Amazon Route 53 health checks with a failover routing policy to the second Region. Promote the secondary to primary as needed. **Most Voted**

Suggested Answer: D

Question #: 528

A data analytics company wants to migrate its batch processing system to AWS. The company receives thousands of small data files periodically during the day through FTP. An on-premises batch job processes the data files overnight. However, the batch job takes hours to finish running.

The company wants the AWS solution to process incoming data files as soon as possible with minimal changes to the FTP clients that send the files. The solution must delete the incoming data files after the files have been processed successfully. Processing for each file needs to take 3-8 minutes.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Use an Amazon EC2 instance that runs an FTP server to store incoming files as objects in Amazon S3 Glacier Flexible Retrieval. Configure a job queue in AWS Batch. Use Amazon EventBridge rules to invoke the job to process the objects nightly from S3 Glacier Flexible Retrieval. Delete the objects after the job has processed the objects.
- B. Use an Amazon EC2 instance that runs an FTP server to store incoming files on an Amazon Elastic Block Store (Amazon EBS) volume. Configure a job queue in AWS Batch. Use Amazon EventBridge rules to invoke the job to process the files nightly from the EBS volume. Delete the files after the job has processed the files.
- C. Use AWS Transfer Family to create an FTP server to store incoming files on an Amazon Elastic Block Store (Amazon EBS) volume. Configure a job queue in AWS Batch. Use an Amazon S3 event notification when each file arrives to invoke the job in AWS Batch. Delete the files after the job has processed the files.
- D. Use AWS Transfer Family to create an FTP server to store incoming files in Amazon S3 Standard. Create an AWS Lambda function to process the files and to delete the files after they are processed. Use an S3 event notification to invoke the Lambda function when the files arrive. **Most Voted**

Suggested Answer: D

Question #: 529

A company is migrating its workloads to AWS. The company has transactional and sensitive data in its databases. The company wants to use AWS Cloud solutions to increase security and reduce operational overhead for the databases.

Which solution will meet these requirements?

- A. Migrate the databases to Amazon EC2. Use an AWS Key Management Service (AWS KMS) AWS managed key for encryption.
- B. Migrate the databases to Amazon RDS Configure encryption at rest. **Most Voted**
- C. Migrate the data to Amazon S3 Use Amazon Macie for data security and protection
- D. Migrate the database to Amazon RDS. Use Amazon CloudWatch Logs for data security and protection.

Suggested Answer: B

Question #: 530

A company has an online gaming application that has TCP and UDP multiplayer gaming capabilities. The company uses Amazon Route 53 to point the application traffic to multiple Network Load Balancers (NLBs) in different AWS Regions. The company needs to improve application performance and decrease latency for the online game in preparation for user growth.

Which solution will meet these requirements?

- A. Add an Amazon CloudFront distribution in front of the NLBs. Increase the Cache-Control max-age parameter.
- B. Replace the NLBs with Application Load Balancers (ALBs). Configure Route 53 to use latency-based routing.
- C. Add AWS Global Accelerator in front of the NLBs. Configure a Global Accelerator endpoint to use the correct listener ports. **Most Voted**
- D. Add an Amazon API Gateway endpoint behind the NLBs. Enable API caching. Override method caching for the different stages.

Suggested Answer: C

Question #: 531

A company needs to integrate with a third-party data feed. The data feed sends a webhook to notify an external service when new data is ready for consumption. A developer wrote an AWS Lambda function to retrieve data when the company receives a webhook callback. The developer must make the Lambda function available for the third party to call.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Create a function URL for the Lambda function. Provide the Lambda function URL to the third party for the webhook. **Most Voted**
- B. Deploy an Application Load Balancer (ALB) in front of the Lambda function. Provide the ALB URL to the third party for the webhook.
- C. Create an Amazon Simple Notification Service (Amazon SNS) topic. Attach the topic to the Lambda function. Provide the public hostname of the SNS topic to the third party for the webhook.
- D. Create an Amazon Simple Queue Service (Amazon SQS) queue. Attach the queue to the Lambda function. Provide the public hostname of the SQS queue to the third party for the webhook.

Suggested Answer: A

Question #: 532

A company has a workload in an AWS Region. Customers connect to and access the workload by using an Amazon API Gateway REST API. The company uses Amazon Route 53 as its DNS provider. The company wants to provide individual and secure URLs for all customers.

Which combination of steps will meet these requirements with the MOST operational efficiency? (Choose three.)

- A. Register the required domain in a registrar. Create a wildcard custom domain name in a Route 53 hosted zone and record in the zone that points to the API Gateway endpoint. **Most Voted**
- B. Request a wildcard certificate that matches the domains in AWS Certificate Manager (ACM) in a different Region.
- C. Create hosted zones for each customer as required in Route 53. Create zone records that point to the API Gateway endpoint.
- D. Request a wildcard certificate that matches the custom domain name in AWS Certificate Manager (ACM) in the same Region. **Most Voted**
- E. Create multiple API endpoints for each customer in API Gateway.
- F. Create a custom domain name in API Gateway for the REST API. Import the certificate from AWS Certificate Manager (ACM). **Most Voted**

Suggested Answer: ADF

Question #: 533

A company stores data in Amazon S3. According to regulations, the data must not contain personally identifiable information (PII). The company recently discovered that S3 buckets have some objects that contain PII. The company needs to automatically detect PII in S3 buckets and to notify the company's security team.

Which solution will meet these requirements?

- A. Use Amazon Macie. Create an Amazon EventBridge rule to filter the SensitiveData event type from Macie findings and to send an Amazon Simple Notification Service (Amazon SNS) notification to the security team. **Most Voted**
- B. Use Amazon GuardDuty. Create an Amazon EventBridge rule to filter the CRITICAL event type from GuardDuty findings and to send an Amazon Simple Notification Service (Amazon SNS) notification to the security team.
- C. Use Amazon Macie. Create an Amazon EventBridge rule to filter the SensitiveData:S3Object/Personal event type from Macie findings and to send an Amazon Simple Queue Service (Amazon SQS) notification to the security team.
- D. Use Amazon GuardDuty. Create an Amazon EventBridge rule to filter the CRITICAL event type from GuardDuty findings and to send an Amazon Simple Queue Service (Amazon SQS) notification to the security team.

Suggested Answer: A

Question #: 534

A company wants to build a logging solution for its multiple AWS accounts. The company currently stores the logs from all accounts in a centralized account. The company has created an Amazon S3 bucket in the centralized account to store the VPC flow logs and AWS CloudTrail logs. All logs must be highly available for 30 days for frequent analysis, retained for an additional 60 days for backup purposes, and deleted 90 days after creation.

Which solution will meet these requirements MOST cost-effectively?

- A. Transition objects to the S3 Standard storage class 30 days after creation. Write an expiration action that directs Amazon S3 to delete objects after 90 days.
- B. Transition objects to the S3 Standard-Infrequent Access (S3 Standard-IA) storage class 30 days after creation. Move all objects to the S3 Glacier Flexible Retrieval storage class after 90 days. Write an expiration action that directs Amazon S3 to delete objects after 90 days.
- C. Transition objects to the S3 Glacier Flexible Retrieval storage class 30 days after creation. Write an expiration action that directs Amazon S3 to delete objects after 90 days. **Most Voted**
- D. Transition objects to the S3 One Zone-Infrequent Access (S3 One Zone-IA) storage class 30 days after creation. Move all objects to the S3 Glacier Flexible Retrieval storage class after 90 days. Write an expiration action that directs Amazon S3 to delete objects after 90 days.

Suggested Answer: C

Question #: 535

A company is building an Amazon Elastic Kubernetes Service (Amazon EKS) cluster for its workloads. All secrets that are stored in Amazon EKS must be encrypted in the Kubernetes etcd key-value store.

Which solution will meet these requirements?

- A. Create a new AWS Key Management Service (AWS KMS) key. Use AWS Secrets Manager to manage, rotate, and store all secrets in Amazon EKS.
- B. Create a new AWS Key Management Service (AWS KMS) key. Enable Amazon EKS KMS secrets encryption on the Amazon EKS cluster. **Most Voted**
- C. Create the Amazon EKS cluster with default options. Use the Amazon Elastic Block Store (Amazon EBS) Container Storage Interface (CSI) driver as an add-on.
- D. Create a new AWS Key Management Service (AWS KMS) key with the alias/aws/ebs alias. Enable default Amazon Elastic Block Store (Amazon EBS) volume encryption for the account.

Suggested Answer: B

Question #: 536

A company wants to provide data scientists with near real-time read-only access to the company's production Amazon RDS for PostgreSQL database. The database is currently configured as a Single-AZ database. The data scientists use complex queries that will not affect the production database. The company needs a solution that is highly available.

Which solution will meet these requirements MOST cost-effectively?

- A. Scale the existing production database in a maintenance window to provide enough power for the data scientists.
- B. Change the setup from a Single-AZ to a Multi-AZ instance deployment with a larger secondary standby instance. Provide the data scientists access to the secondary instance.
- C. Change the setup from a Single-AZ to a Multi-AZ instance deployment. Provide two additional read replicas for the data scientists.
- D. Change the setup from a Single-AZ to a Multi-AZ cluster deployment with two readable standby instances. Provide read endpoints to the data scientists. **Most Voted**

Suggested Answer: D

Question #: 537

A company runs a three-tier web application in the AWS Cloud that operates across three Availability Zones. The application architecture has an Application Load Balancer, an Amazon EC2 web server that hosts user session states, and a MySQL database that runs on an EC2 instance. The company expects sudden increases in application traffic. The company wants to be able to scale to meet future application capacity demands and to ensure high availability across all three Availability Zones.

Which solution will meet these requirements?

- A. Migrate the MySQL database to Amazon RDS for MySQL with a Multi-AZ DB cluster deployment. Use Amazon ElastiCache for Redis with high availability to store session data and to cache reads. Migrate the web server to an Auto Scaling group that is in three Availability Zones. **Most Voted**

- B. Migrate the MySQL database to Amazon RDS for MySQL with a Multi-AZ DB cluster deployment. Use Amazon ElastiCache for Memcached with high availability to store session data and to cache reads. Migrate the web server to an Auto Scaling group that is in three Availability Zones.
- C. Migrate the MySQL database to Amazon DynamoDB Use DynamoDB Accelerator (DAX) to cache reads. Store the session data in DynamoDB. Migrate the web server to an Auto Scaling group that is in three Availability Zones.
- D. Migrate the MySQL database to Amazon RDS for MySQL in a single Availability Zone. Use Amazon ElastiCache for Redis with high availability to store session data and to cache reads. Migrate the web server to an Auto Scaling group that is in three Availability Zones.

Suggested Answer: A

Question #: 538

A global video streaming company uses Amazon CloudFront as a content distribution network (CDN). The company wants to roll out content in a phased manner across multiple countries. The company needs to ensure that viewers who are outside the countries to which the company rolls out content are not able to view the content.

Which solution will meet these requirements?

- A. Add geographic restrictions to the content in CloudFront by using an allow list. Set up a custom error message. **Most Voted**
- B. Set up a new URL for restricted content. Authorize access by using a signed URL and cookies. Set up a custom error message.
- C. Encrypt the data for the content that the company distributes. Set up a custom error message.
- D. Create a new URL for restricted content. Set up a time-restricted access policy for signed URLs.

Suggested Answer: A

Question #: 539

A company wants to use the AWS Cloud to improve its on-premises disaster recovery (DR) configuration. The company's core production business application uses Microsoft SQL Server Standard, which runs on a virtual

machine (VM). The application has a recovery point objective (RPO) of 30 seconds or fewer and a recovery time objective (RTO) of 60 minutes. The DR solution needs to minimize costs wherever possible.

Which solution will meet these requirements?

- A. Configure a multi-site active/active setup between the on-premises server and AWS by using Microsoft SQL Server Enterprise with Always On availability groups.
- B. Configure a warm standby Amazon RDS for SQL Server database on AWS. Configure AWS Database Migration Service (AWS DMS) to use change data capture (CDC). **Most Voted**
- C. Use AWS Elastic Disaster Recovery configured to replicate disk changes to AWS as a pilot light.
- D. Use third-party backup software to capture backups every night. Store a secondary set of backups in Amazon S3.

Suggested Answer: B

Question #: 540

A company has an on-premises server that uses an Oracle database to process and store customer information. The company wants to use an AWS database service to achieve higher availability and to improve application performance. The company also wants to offload reporting from its primary database system.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Use AWS Database Migration Service (AWS DMS) to create an Amazon RDS DB instance in multiple AWS Regions. Point the reporting functions toward a separate DB instance from the primary DB instance.
- B. Use Amazon RDS in a Single-AZ deployment to create an Oracle database. Create a read replica in the same zone as the primary DB instance. Direct the reporting functions to the read replica.
- C. Use Amazon RDS deployed in a Multi-AZ cluster deployment to create an Oracle database. Direct the reporting functions to use the reader instance in the cluster deployment.
- D. Use Amazon RDS deployed in a Multi-AZ instance deployment to create an Amazon Aurora database. Direct the reporting functions to the reader instances. **Most Voted**

Suggested Answer: D

Question #: 541

A company wants to build a web application on AWS. Client access requests to the website are not predictable and can be idle for a long time. Only customers who have paid a subscription fee can have the ability to sign in and use the web application.

Which combination of steps will meet these requirements MOST cost-effectively? (Choose three.)

- A. Create an AWS Lambda function to retrieve user information from Amazon DynamoDB. Create an Amazon API Gateway endpoint to accept RESTful APIs. Send the API calls to the Lambda function. **Most Voted**
- B. Create an Amazon Elastic Container Service (Amazon ECS) service behind an Application Load Balancer to retrieve user information from Amazon RDS. Create an Amazon API Gateway endpoint to accept RESTful APIs. Send the API calls to the Lambda function.
- C. Create an Amazon Cognito user pool to authenticate users. **Most Voted**
- D. Create an Amazon Cognito identity pool to authenticate users.
- E. Use AWS Amplify to serve the frontend web content with HTML, CSS, and JS. Use an integrated Amazon CloudFront configuration. **Most Voted**
- F. Use Amazon S3 static web hosting with PHP, CSS, and JS. Use Amazon CloudFront to serve the frontend web content.

Suggested Answer: ACE

Question #: 542

A media company uses an Amazon CloudFront distribution to deliver content over the internet. The company wants only premium customers to have access to the media streams and file content. The company stores all content in an Amazon S3 bucket. The company also delivers content on demand to customers for a specific purpose, such as movie rentals or music downloads.

Which solution will meet these requirements?

- A. Generate and provide S3 signed cookies to premium customers.
- B. Generate and provide CloudFront signed URLs to premium customers. **Most Voted**
- C. Use origin access control (OAC) to limit the access of non-premium customers.
- D. Generate and activate field-level encryption to block non-premium customers.

Suggested Answer: B

Question #: 543

A company runs Amazon EC2 instances in multiple AWS accounts that are individually billed. The company recently purchased a Savings Plan. Because of changes in the company's business requirements, the company has decommissioned a large number of EC2 instances. The company wants to use its Savings Plan discounts on its other AWS accounts.

Which combination of steps will meet these requirements? (Choose two.)

- A. From the AWS Account Management Console of the management account, turn on discount sharing from the billing preferences section. **Most Voted**
- B. From the AWS Account Management Console of the account that purchased the existing Savings Plan, turn on discount sharing from the billing preferences section. Include all accounts.
- C. From the AWS Organizations management account, use AWS Resource Access Manager (AWS RAM) to share the Savings Plan with other accounts.
- D. Create an organization in AWS Organizations in a new payer account. Invite the other AWS accounts to join the organization from the management account.
- E. Create an organization in AWS Organizations in the existing AWS account with the existing EC2 instances and Savings Plan. Invite the other AWS accounts to join the organization from the management account. **Most Voted**

Suggested Answer: AE

Question #: 544

A retail company uses a regional Amazon API Gateway API for its public REST APIs. The API Gateway endpoint is a custom domain name that points to an Amazon Route 53 alias record. A solutions architect needs to create a solution that has minimal effects on customers and minimal data loss to release the new version of APIs.

Which solution will meet these requirements?

- A. Create a canary release deployment stage for API Gateway. Deploy the latest API version. Point an appropriate percentage of traffic to the canary stage. After API verification, promote the canary stage to the production stage. **Most Voted**
- B. Create a new API Gateway endpoint with a new version of the API in OpenAPI YAML file format. Use the import-to-update operation in merge mode into the API in API Gateway. Deploy the new version of the API to the production stage.
- C. Create a new API Gateway endpoint with a new version of the API in OpenAPI JSON file format. Use the import-to-update operation in overwrite mode into the API in API Gateway. Deploy the new version of the API to the production stage.
- D. Create a new API Gateway endpoint with new versions of the API definitions. Create a custom domain name for the new API Gateway API. Point the Route 53 alias record to the new API Gateway API custom domain name.

Suggested Answer: A

Question #: 545

A company wants to direct its users to a backup static error page if the company's primary website is unavailable. The primary website's DNS records are hosted in Amazon Route 53. The domain is pointing to an Application Load Balancer (ALB). The company needs a solution that minimizes changes and infrastructure overhead.

Which solution will meet these requirements?

- A. Update the Route 53 records to use a latency routing policy. Add a static error page that is hosted in an Amazon S3 bucket to the records so that the traffic is sent to the most responsive endpoints.

- B. Set up a Route 53 active-passive failover configuration. Direct traffic to a static error page that is hosted in an Amazon S3 bucket when Route 53 health checks determine that the ALB endpoint is unhealthy. **Most Voted**
- C. Set up a Route 53 active-active configuration with the ALB and an Amazon EC2 instance that hosts a static error page as endpoints. Configure Route 53 to send requests to the instance only if the health checks fail for the ALB.
- D. Update the Route 53 records to use a multivalue answer routing policy. Create a health check. Direct traffic to the website if the health check passes. Direct traffic to a static error page that is hosted in Amazon S3 if the health check does not pass.

Suggested Answer: B

Question #: 546

A recent analysis of a company's IT expenses highlights the need to reduce backup costs. The company's chief information officer wants to simplify the on-premises backup infrastructure and reduce costs by eliminating the use of physical backup tapes. The company must preserve the existing investment in the on-premises backup applications and workflows.

What should a solutions architect recommend?

- A. Set up AWS Storage Gateway to connect with the backup applications using the NFS interface.
- B. Set up an Amazon EFS file system that connects with the backup applications using the NFS interface.
- C. Set up an Amazon EFS file system that connects with the backup applications using the iSCSI interface.
- D. Set up AWS Storage Gateway to connect with the backup applications using the iSCSI-virtual tape library (VTL) interface. **Most Voted**

Suggested Answer: D

Question #: 547

A company has data collection sensors at different locations. The data collection sensors stream a high volume of data to the company. The company wants to design a platform on AWS to ingest and process high-volume streaming data. The solution must be scalable and support data collection in near real time. The company must store the data in Amazon S3 for future reporting.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Kinesis Data Firehose to deliver streaming data to Amazon S3. **Most Voted**
- B. Use AWS Glue to deliver streaming data to Amazon S3.
- C. Use AWS Lambda to deliver streaming data and store the data to Amazon S3.
- D. Use AWS Database Migration Service (AWS DMS) to deliver streaming data to Amazon S3.

Suggested Answer: A

Question #: 548

A company has separate AWS accounts for its finance, data analytics, and development departments. Because of costs and security concerns, the company wants to control which services each AWS account can use.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Systems Manager templates to control which AWS services each department can use.
- B. Create organization units (OUs) for each department in AWS Organizations. Attach service control policies (SCPs) to the OUs. **Most Voted**
- C. Use AWS CloudFormation to automatically provision only the AWS services that each department can use.
- D. Set up a list of products in AWS Service Catalog in the AWS accounts to manage and control the usage of specific AWS services.

Suggested Answer: B

Question #: 549

A company has created a multi-tier application for its ecommerce website. The website uses an Application Load Balancer that resides in the public subnets, a web tier in the public subnets, and a MySQL cluster hosted on Amazon EC2 instances in the private subnets. The MySQL database needs to retrieve product catalog and pricing information that is hosted on the internet by a third-party provider. A solutions architect must devise a strategy that maximizes security without increasing operational overhead.

What should the solutions architect do to meet these requirements?

- A. Deploy a NAT instance in the VPC. Route all the internet-based traffic through the NAT instance.
- B. Deploy a NAT gateway in the public subnets. Modify the private subnet route table to direct all internet-bound traffic to the NAT gateway. **Most Voted**
- C. Configure an internet gateway and attach it to the VPC. Modify the private subnet route table to direct internet-bound traffic to the internet gateway.
- D. Configure a virtual private gateway and attach it to the VPC. Modify the private subnet route table to direct internet-bound traffic to the virtual private gateway.

Suggested Answer: B

Question #: 550

A company is using AWS Key Management Service (AWS KMS) keys to encrypt AWS Lambda environment variables. A solutions architect needs to ensure that the required permissions are in place to decrypt and use the environment variables.

Which steps must the solutions architect take to implement the correct permissions? (Choose two.)

- A. Add AWS KMS permissions in the Lambda resource policy.
- B. Add AWS KMS permissions in the Lambda execution role. **Most Voted**
- C. Add AWS KMS permissions in the Lambda function policy.
- D. Allow the Lambda execution role in the AWS KMS key policy. **Most Voted**
- E. Allow the Lambda resource policy in the AWS KMS key policy.

Suggested Answer: BD

Question #: 551

A company has a financial application that produces reports. The reports average 50 KB in size and are stored in Amazon S3. The reports are frequently accessed during the first week after production and must be stored for

several years. The reports must be retrievable within 6 hours.

Which solution meets these requirements MOST cost-effectively?

- A. Use S3 Standard. Use an S3 Lifecycle rule to transition the reports to S3 Glacier after 7 days. **Most Voted**
- B. Use S3 Standard. Use an S3 Lifecycle rule to transition the reports to S3 Standard-Infrequent Access (S3 Standard-IA) after 7 days.
- C. Use S3 Intelligent-Tiering. Configure S3 Intelligent-Tiering to transition the reports to S3 Standard-Infrequent Access (S3 Standard-IA) and S3 Glacier.
- D. Use S3 Standard. Use an S3 Lifecycle rule to transition the reports to S3 Glacier Deep Archive after 7 days.

Suggested Answer: A

Question #: 552

A company needs to optimize the cost of its Amazon EC2 instances. The company also needs to change the type and family of its EC2 instances every 2-3 months.

What should the company do to meet these requirements?

- A. Purchase Partial Upfront Reserved Instances for a 3-year term.
- B. Purchase a No Upfront Compute Savings Plan for a 1-year term. **Most Voted**
- C. Purchase All Upfront Reserved Instances for a 1-year term.
- D. Purchase an All Upfront EC2 Instance Savings Plan for a 1-year term.

Suggested Answer: B

Question #: 553

A solutions architect needs to review a company's Amazon S3 buckets to discover personally identifiable information (PII). The company stores the PII data in the us-east-1 Region and us-west-2 Region.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Configure Amazon Macie in each Region. Create a job to analyze the data that is in Amazon S3. **Most Voted**
- B. Configure AWS Security Hub for all Regions. Create an AWS Config rule to analyze the data that is in Amazon S3.
- C. Configure Amazon Inspector to analyze the data that is in Amazon S3.
- D. Configure Amazon GuardDuty to analyze the data that is in Amazon S3.

Suggested Answer: A

Question #: 554

A company's SAP application has a backend SQL Server database in an on-premises environment. The company wants to migrate its on-premises application and database server to AWS. The company needs an instance type that meets the high demands of its SAP database. On-premises performance data shows that both the SAP application and the database have high memory utilization.

Which solution will meet these requirements?

- A. Use the compute optimized instance family for the application. Use the memory optimized instance family for the database.
- B. Use the storage optimized instance family for both the application and the database.
- C. Use the memory optimized instance family for both the application and the database. **Most Voted**
- D. Use the high performance computing (HPC) optimized instance family for the application. Use the memory optimized instance family for the database.

Suggested Answer: C

Question #: 555

A company runs an application in a VPC with public and private subnets. The VPC extends across multiple Availability Zones. The application runs on Amazon EC2 instances in private subnets. The application uses an Amazon Simple Queue Service (Amazon SQS) queue.

A solutions architect needs to design a secure solution to establish a connection between the EC2 instances and the SQS queue.

Which solution will meet these requirements?

- A. Implement an interface VPC endpoint for Amazon SQS. Configure the endpoint to use the private subnets. Add to the endpoint a security group that has an inbound access rule that allows traffic from the EC2 instances that are in the private subnets. **Most Voted**
- B. Implement an interface VPC endpoint for Amazon SQS. Configure the endpoint to use the public subnets. Attach to the interface endpoint a VPC endpoint policy that allows access from the EC2 instances that are in the private subnets.
- C. Implement an interface VPC endpoint for Amazon SQS. Configure the endpoint to use the public subnets. Attach an Amazon SQS access policy to the interface VPC endpoint that allows requests from only a specified VPC endpoint.
- D. Implement a gateway endpoint for Amazon SQS. Add a NAT gateway to the private subnets. Attach an IAM role to the EC2 instances that allows access to the SQS queue.

Suggested Answer: A

Question #: 556

A solutions architect is using an AWS CloudFormation template to deploy a three-tier web application. The web application consists of a web tier and an application tier that stores and retrieves user data in Amazon DynamoDB tables. The web and application tiers are hosted on Amazon EC2 instances, and the database tier is not publicly accessible. The application EC2 instances need to access the DynamoDB tables without exposing API credentials in the template.

What should the solutions architect do to meet these requirements?

- A. Create an IAM role to read the DynamoDB tables. Associate the role with the application instances by referencing an instance profile.
- B. Create an IAM role that has the required permissions to read and write from the DynamoDB tables. Add the role to the EC2 instance profile, and associate the instance profile with the application instances. **Most Voted**

- C. Use the parameter section in the AWS CloudFormation template to have the user input access and secret keys from an already-created IAM user that has the required permissions to read and write from the DynamoDB tables.
- D. Create an IAM user in the AWS CloudFormation template that has the required permissions to read and write from the DynamoDB tables. Use the GetAtt function to retrieve the access and secret keys, and pass them to the application instances through the user data.

Suggested Answer: B

Question #: 557

A solutions architect manages an analytics application. The application stores large amounts of semistructured data in an Amazon S3 bucket. The solutions architect wants to use parallel data processing to process the data more quickly. The solutions architect also wants to use information that is stored in an Amazon Redshift database to enrich the data.

Which solution will meet these requirements?

- A. Use Amazon Athena to process the S3 data. Use AWS Glue with the Amazon Redshift data to enrich the S3 data.
- B. Use Amazon EMR to process the S3 data. Use Amazon EMR with the Amazon Redshift data to enrich the S3 data. **Most Voted**
- C. Use Amazon EMR to process the S3 data. Use Amazon Kinesis Data Streams to move the S3 data into Amazon Redshift so that the data can be enriched.
- D. Use AWS Glue to process the S3 data. Use AWS Lake Formation with the Amazon Redshift data to enrich the S3 data.

Suggested Answer: B

Question #: 558

A company has two VPCs that are located in the us-west-2 Region within the same AWS account. The company needs to allow network traffic between these VPCs. Approximately 500 GB of data transfer will occur between the VPCs each month.

What is the MOST cost-effective solution to connect these VPCs?

- A. Implement AWS Transit Gateway to connect the VPCs. Update the route tables of each VPC to use the transit gateway for inter-VPC communication.
- B. Implement an AWS Site-to-Site VPN tunnel between the VPCs. Update the route tables of each VPC to use the VPN tunnel for inter-VPC communication.
- C. Set up a VPC peering connection between the VPCs. Update the route tables of each VPC to use the VPC peering connection for inter-VPC communication. **Most Voted**
- D. Set up a 1 GB AWS Direct Connect connection between the VPCs. Update the route tables of each VPC to use the Direct Connect connection for inter-VPC communication.

Suggested Answer: C

Question #: 559

A company hosts multiple applications on AWS for different product lines. The applications use different compute resources, including Amazon EC2 instances and Application Load Balancers. The applications run in different AWS accounts under the same organization in AWS Organizations across multiple AWS Regions. Teams for each product line have tagged each compute resource in the individual accounts.

The company wants more details about the cost for each product line from the consolidated billing feature in Organizations.

Which combination of steps will meet these requirements? (Choose two.)

- A. Select a specific AWS generated tag in the AWS Billing console.
- B. Select a specific user-defined tag in the AWS Billing console. **Most Voted**
- C. Select a specific user-defined tag in the AWS Resource Groups console.
- D. Activate the selected tag from each AWS account.
- E. Activate the selected tag from the Organizations management account. **Most Voted**

Suggested Answer: BE

Question #: 560

A company's solutions architect is designing an AWS multi-account solution that uses AWS Organizations. The solutions architect has organized the company's accounts into organizational units (OUs).

The solutions architect needs a solution that will identify any changes to the OU hierarchy. The solution also needs to notify the company's operations team of any changes.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Provision the AWS accounts by using AWS Control Tower. Use account drift notifications to identify the changes to the OU hierarchy. **Most Voted**
- B. Provision the AWS accounts by using AWS Control Tower. Use AWS Config aggregated rules to identify the changes to the OU hierarchy.
- C. Use AWS Service Catalog to create accounts in Organizations. Use an AWS CloudTrail organization trail to identify the changes to the OU hierarchy.
- D. Use AWS CloudFormation templates to create accounts in Organizations. Use the drift detection operation on a stack to identify the changes to the OU hierarchy.

Suggested Answer: A

Question #: 561

A company's website handles millions of requests each day, and the number of requests continues to increase. A solutions architect needs to improve the response time of the web application. The solutions architect determines that the application needs to decrease latency when retrieving product details from the Amazon DynamoDB table.

Which solution will meet these requirements with the LEAST amount of operational overhead?

- A. Set up a DynamoDB Accelerator (DAX) cluster. Route all read requests through DAX. **Most Voted**

- B. Set up Amazon ElastiCache for Redis between the DynamoDB table and the web application. Route all read requests through Redis.
- C. Set up Amazon ElastiCache for Memcached between the DynamoDB table and the web application. Route all read requests through Memcached.
- D. Set up Amazon DynamoDB Streams on the table, and have AWS Lambda read from the table and populate Amazon ElastiCache. Route all read requests through ElastiCache.

Suggested Answer: A

Question #: 562

A solutions architect needs to ensure that API calls to Amazon DynamoDB from Amazon EC2 instances in a VPC do not travel across the internet.

Which combination of steps should the solutions architect take to meet this requirement? (Choose two.)

- A. Create a route table entry for the endpoint. **Most Voted**
- B. Create a gateway endpoint for DynamoDB. **Most Voted**
- C. Create an interface endpoint for Amazon EC2.
- D. Create an elastic network interface for the endpoint in each of the subnets of the VPC.
- E. Create a security group entry in the endpoint's security group to provide access.

Suggested Answer: AB

Question #: 563

A company runs its applications on both Amazon Elastic Kubernetes Service (Amazon EKS) clusters and on-premises Kubernetes clusters. The company wants to view all clusters and workloads from a central location.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon CloudWatch Container Insights to collect and group the cluster information.
- B. Use Amazon EKS Connector to register and connect all Kubernetes clusters. **Most Voted**

- C. Use AWS Systems Manager to collect and view the cluster information.
- D. Use Amazon EKS Anywhere as the primary cluster to view the other clusters with native Kubernetes commands.

Suggested Answer: B

Question #: 564

A company is building an ecommerce application and needs to store sensitive customer information. The company needs to give customers the ability to complete purchase transactions on the website. The company also needs to ensure that sensitive customer data is protected, even from database administrators.

Which solution meets these requirements?

- A. Store sensitive data in an Amazon Elastic Block Store (Amazon EBS) volume. Use EBS encryption to encrypt the data. Use an IAM instance role to restrict access.
- B. Store sensitive data in Amazon RDS for MySQL. Use AWS Key Management Service (AWS KMS) client-side encryption to encrypt the data. **Most Voted**
- C. Store sensitive data in Amazon S3. Use AWS Key Management Service (AWS KMS) server-side encryption to encrypt the data. Use S3 bucket policies to restrict access.
- D. Store sensitive data in Amazon FSx for Windows Server. Mount the file share on application servers. Use Windows file permissions to restrict access.

Suggested Answer: B

Question #: 565

A company has an on-premises MySQL database that handles transactional data. The company is migrating the database to the AWS Cloud. The migrated database must maintain compatibility with the company's applications that use the database. The migrated database also must scale automatically during periods of increased demand.

Which migration solution will meet these requirements?

- A. Use native MySQL tools to migrate the database to Amazon RDS for MySQL. Configure elastic storage scaling.
- B. Migrate the database to Amazon Redshift by using the mysqldump utility. Turn on Auto Scaling for the Amazon Redshift cluster.
- C. Use AWS Database Migration Service (AWS DMS) to migrate the database to Amazon Aurora. Turn on Aurora Auto Scaling. **Most Voted**
- D. Use AWS Database Migration Service (AWS DMS) to migrate the database to Amazon DynamoDB. Configure an Auto Scaling policy.

Suggested Answer: C

Question #: 566

A company runs multiple Amazon EC2 Linux instances in a VPC across two Availability Zones. The instances host applications that use a hierarchical directory structure. The applications need to read and write rapidly and concurrently to shared storage.

What should a solutions architect do to meet these requirements?

- A. Create an Amazon S3 bucket. Allow access from all the EC2 instances in the VPC.
- B. Create an Amazon Elastic File System (Amazon EFS) file system. Mount the EFS file system from each EC2 instance. **Most Voted**
- C. Create a file system on a Provisioned IOPS SSD (io2) Amazon Elastic Block Store (Amazon EBS) volume. Attach the EBS volume to all the EC2 instances.
- D. Create file systems on Amazon Elastic Block Store (Amazon EBS) volumes that are attached to each EC2 instance. Synchronize the EBS volumes across the different EC2 instances.

Suggested Answer: B

Question #: 567

A solutions architect is designing a workload that will store hourly energy consumption by business tenants in a building. The sensors will feed a database through HTTP requests that will add up usage for each tenant. The solutions architect must use managed services when possible. The workload will receive more features in the

future as the solutions architect adds independent components.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon API Gateway with AWS Lambda functions to receive the data from the sensors, process the data, and store the data in an Amazon DynamoDB table. **Most Voted**
- B. Use an Elastic Load Balancer that is supported by an Auto Scaling group of Amazon EC2 instances to receive and process the data from the sensors. Use an Amazon S3 bucket to store the processed data.
- C. Use Amazon API Gateway with AWS Lambda functions to receive the data from the sensors, process the data, and store the data in a Microsoft SQL Server Express database on an Amazon EC2 instance.
- D. Use an Elastic Load Balancer that is supported by an Auto Scaling group of Amazon EC2 instances to receive and process the data from the sensors. Use an Amazon Elastic File System (Amazon EFS) shared file system to store the processed data.

Suggested Answer: A

Question #: 568

A solutions architect is designing the storage architecture for a new web application used for storing and viewing engineering drawings. All application components will be deployed on the AWS infrastructure.

The application design must support caching to minimize the amount of time that users wait for the engineering drawings to load. The application must be able to store petabytes of data.

Which combination of storage and caching should the solutions architect use?

- A. Amazon S3 with Amazon CloudFront **Most Voted**
- B. Amazon S3 Glacier with Amazon ElastiCache
- C. Amazon Elastic Block Store (Amazon EBS) volumes with Amazon CloudFront
- D. AWS Storage Gateway with Amazon ElastiCache

Suggested Answer: A

Question #: 569

An Amazon EventBridge rule targets a third-party API. The third-party API has not received any incoming traffic. A solutions architect needs to determine whether the rule conditions are being met and if the rule's target is being invoked.

Which solution will meet these requirements?

- A. Check for metrics in Amazon CloudWatch in the namespace for AWS/Events. **Most Voted**
- B. Review events in the Amazon Simple Queue Service (Amazon SQS) dead-letter queue.
- C. Check for the events in Amazon CloudWatch Logs.
- D. Check the trails in AWS CloudTrail for the EventBridge events.

Suggested Answer: A

Exam question from Amazon's [AWS Certified Solutions Architect - Associate SAA-C03](#)

Question #: 570

A company has a large workload that runs every Friday evening. The workload runs on Amazon EC2 instances that are in two Availability Zones in the us-east-1 Region. Normally, the company must run no more than two instances at all times. However, the company wants to scale up to six instances each Friday to handle a regularly repeating increased workload.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a reminder in Amazon EventBridge to scale the instances.
- B. Create an Auto Scaling group that has a scheduled action. **Most Voted**
- C. Create an Auto Scaling group that uses manual scaling.
- D. Create an Auto Scaling group that uses automatic scaling.

Suggested Answer: B

Question #: 571

A company is creating a REST API. The company has strict requirements for the use of TLS. The company requires TLSv1.3 on the API endpoints. The company also requires a specific public third-party certificate authority (CA) to sign the TLS certificate.

Which solution will meet these requirements?

- A. Use a local machine to create a certificate that is signed by the third-party CA. Import the certificate into AWS Certificate Manager (ACM). Create an HTTP API in Amazon API Gateway with a custom domain. Configure the custom domain to use the certificate. **Most Voted**
- B. Create a certificate in AWS Certificate Manager (ACM) that is signed by the third-party CA. Create an HTTP API in Amazon API Gateway with a custom domain. Configure the custom domain to use the certificate. **Most Voted**
- C. Use AWS Certificate Manager (ACM) to create a certificate that is signed by the third-party CA. Import the certificate into AWS Certificate Manager (ACM). Create an AWS Lambda function with a Lambda function URL. Configure the Lambda function URL to use the certificate.
- D. Create a certificate in AWS Certificate Manager (ACM) that is signed by the third-party CA. Create an AWS Lambda function with a Lambda function URL. Configure the Lambda function URL to use the certificate.

Suggested Answer: A

Question #: 572

A company runs an application on AWS. The application receives inconsistent amounts of usage. The application uses AWS Direct Connect to connect to an on-premises MySQL-compatible database. The on-premises database consistently uses a minimum of 2 GiB of memory.

The company wants to migrate the on-premises database to a managed AWS service. The company wants to use auto scaling capabilities to manage unexpected workload increases.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Provision an Amazon DynamoDB database with default read and write capacity settings.
- B. Provision an Amazon Aurora database with a minimum capacity of 1 Aurora capacity unit (ACU).

- C. Provision an Amazon Aurora Serverless v2 database with a minimum capacity of 1 Aurora capacity unit (ACU). **Most Voted**
- D. Provision an Amazon RDS for MySQL database with 2 GiB of memory.

Suggested Answer: C

Question #: 573

A company wants to use an event-driven programming model with AWS Lambda. The company wants to reduce startup latency for Lambda functions that run on Java 11. The company does not have strict latency requirements for the applications. The company wants to reduce cold starts and outlier latencies when a function scales up.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure Lambda provisioned concurrency.
- B. Increase the timeout of the Lambda functions.
- C. Increase the memory of the Lambda functions.
- D. Configure Lambda SnapStart. **Most Voted**

Suggested Answer: D

Question #: 574

A financial services company launched a new application that uses an Amazon RDS for MySQL database. The company uses the application to track stock market trends. The company needs to operate the application for only 2 hours at the end of each week. The company needs to optimize the cost of running the database.

Which solution will meet these requirements MOST cost-effectively?

- A. Migrate the existing RDS for MySQL database to an Aurora Serverless v2 MySQL database cluster. **Most Voted**
- B. Migrate the existing RDS for MySQL database to an Aurora MySQL database cluster.

- C. Migrate the existing RDS for MySQL database to an Amazon EC2 instance that runs MySQL. Purchase an instance reservation for the EC2 instance.
- D. Migrate the existing RDS for MySQL database to an Amazon Elastic Container Service (Amazon ECS) cluster that uses MySQL container images to run tasks.

Suggested Answer: A

Question #: 575

A company deploys its applications on Amazon Elastic Kubernetes Service (Amazon EKS) behind an Application Load Balancer in an AWS Region. The application needs to store data in a PostgreSQL database engine. The company wants the data in the database to be highly available. The company also needs increased capacity for read workloads.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Create an Amazon DynamoDB database table configured with global tables.
- B. Create an Amazon RDS database with Multi-AZ deployments.
- C. Create an Amazon RDS database with Multi-AZ DB cluster deployment. **Most Voted**
- D. Create an Amazon RDS database configured with cross-Region read replicas.

Suggested Answer: C

Question #: 576

A company is building a RESTful serverless web application on AWS by using Amazon API Gateway and AWS Lambda. The users of this web application will be geographically distributed, and the company wants to reduce the latency of API requests to these users.

Which type of endpoint should a solutions architect use to meet these requirements?

- A. Private endpoint
- B. Regional endpoint
- C. Interface VPC endpoint

- D. Edge-optimized endpoint **Most Voted**

Suggested Answer: D

Question #: 577

A company uses an Amazon CloudFront distribution to serve content pages for its website. The company needs to ensure that clients use a TLS certificate when accessing the company's website. The company wants to automate the creation and renewal of the TLS certificates.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Use a CloudFront security policy to create a certificate.
- B. Use a CloudFront origin access control (OAC) to create a certificate.
- C. Use AWS Certificate Manager (ACM) to create a certificate. Use DNS validation for the domain. **Most Voted**
- D. Use AWS Certificate Manager (ACM) to create a certificate. Use email validation for the domain.

Suggested Answer: C

Question #: 578

A company deployed a serverless application that uses Amazon DynamoDB as a database layer. The application has experienced a large increase in users. The company wants to improve database response time from milliseconds to microseconds and to cache requests to the database.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use DynamoDB Accelerator (DAX). **Most Voted**
- B. Migrate the database to Amazon Redshift.
- C. Migrate the database to Amazon RDS.
- D. Use Amazon ElastiCache for Redis.

Suggested Answer: A

Question #: 579

A company runs an application that uses Amazon RDS for PostgreSQL. The application receives traffic only on weekdays during business hours. The company wants to optimize costs and reduce operational overhead based on this usage.

Which solution will meet these requirements?

- A. Use the Instance Scheduler on AWS to configure start and stop schedules. **Most Voted**
- B. Turn off automatic backups. Create weekly manual snapshots of the database.
- C. Create a custom AWS Lambda function to start and stop the database based on minimum CPU utilization.
- D. Purchase All Upfront reserved DB instances.

Suggested Answer: A

Question #: 580

A company uses locally attached storage to run a latency-sensitive application on premises. The company is using a lift and shift method to move the application to the AWS Cloud. The company does not want to change the application architecture.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure an Auto Scaling group with an Amazon EC2 instance. Use an Amazon FSx for Lustre file system to run the application.
- B. Host the application on an Amazon EC2 instance. Use an Amazon Elastic Block Store (Amazon EBS) GP2 volume to run the application.
- C. Configure an Auto Scaling group with an Amazon EC2 instance. Use an Amazon FSx for OpenZFS file system to run the application.
- D. Host the application on an Amazon EC2 instance. Use an Amazon Elastic Block Store (Amazon EBS) GP3 volume to run the application. **Most Voted**

Suggested Answer: D

Question #: 581

A company runs a stateful production application on Amazon EC2 instances. The application requires at least two EC2 instances to always be running.

A solutions architect needs to design a highly available and fault-tolerant architecture for the application. The solutions architect creates an Auto Scaling group of EC2 instances.

Which set of additional steps should the solutions architect take to meet these requirements?

- A. Set the Auto Scaling group's minimum capacity to two. Deploy one On-Demand Instance in one Availability Zone and one On-Demand Instance in a second Availability Zone.
- B. Set the Auto Scaling group's minimum capacity to four. Deploy two On-Demand Instances in one Availability Zone and two On-Demand Instances in a second Availability Zone. **Most Voted**
- C. Set the Auto Scaling group's minimum capacity to two. Deploy four Spot Instances in one Availability Zone.
- D. Set the Auto Scaling group's minimum capacity to four. Deploy two On-Demand Instances in one Availability Zone and two Spot Instances in a second Availability Zone.

Suggested Answer: B

Question #: 582

An ecommerce company uses Amazon Route 53 as its DNS provider. The company hosts its website on premises and in the AWS Cloud. The company's on-premises data center is near the us-west-1 Region. The company uses the eu-central-1 Region to host the website. The company wants to minimize load time for the website as much as possible.

Which solution will meet these requirements?

- A. Set up a geolocation routing policy. Send the traffic that is near us-west-1 to the on-premises data center. Send the traffic that is near eu-central-1 to eu-central-1. **Most Voted**
- B. Set up a simple routing policy that routes all traffic that is near eu-central-1 to eu-central-1 and routes all traffic that is near the on-premises datacenter to the on-premises data center.

- C. Set up a latency routing policy. Associate the policy with us-west-1.
- D. Set up a weighted routing policy. Split the traffic evenly between eu-central-1 and the on-premises data center.

Suggested Answer: A

Question #: 583

A company has 5 PB of archived data on physical tapes. The company needs to preserve the data on the tapes for another 10 years for compliance purposes. The company wants to migrate to AWS in the next 6 months. The data center that stores the tapes has a 1 Gbps uplink internet connectivity.

Which solution will meet these requirements MOST cost-effectively?

- A. Read the data from the tapes on premises. Stage the data in a local NFS storage. Use AWS DataSync to migrate the data to Amazon S3 Glacier Flexible Retrieval.
- B. Use an on-premises backup application to read the data from the tapes and to write directly to Amazon S3 Glacier Deep Archive.
- C. Order multiple AWS Snowball devices that have Tape Gateway. Copy the physical tapes to virtual tapes in Snowball. Ship the Snowball devices to AWS. Create a lifecycle policy to move the tapes to Amazon S3 Glacier Deep Archive. **Most Voted**
- D. Configure an on-premises Tape Gateway. Create virtual tapes in the AWS Cloud. Use backup software to copy the physical tape to the virtual tape.

Suggested Answer: C

Question #: 584

A company is deploying an application that processes large quantities of data in parallel. The company plans to use Amazon EC2 instances for the workload. The network architecture must be configurable to prevent groups of nodes from sharing the same underlying hardware.

Which networking solution meets these requirements?

- A. Run the EC2 instances in a spread placement group. **Most Voted**
- B. Group the EC2 instances in separate accounts.
- C. Configure the EC2 instances with dedicated tenancy.
- D. Configure the EC2 instances with shared tenancy.

Suggested Answer: A

Question #: 586

A company has five organizational units (OUs) as part of its organization in AWS Organizations. Each OU correlates to the five businesses that the company owns. The company's research and development (R&D) business is separating from the company and will need its own organization. A solutions architect creates a separate new management account for this purpose.

What should the solutions architect do next in the new management account?

- A. Have the R&D AWS account be part of both organizations during the transition.
- B. Invite the R&D AWS account to be part of the new organization after the R&D AWS account has left the prior organization. **Most Voted**
- C. Create a new R&D AWS account in the new organization. Migrate resources from the prior R&D AWS account to the new R&D AWS account.
- D. Have the R&D AWS account join the new organization. Make the new management account a member of the prior organization.

Suggested Answer: B

Question #: 587

A company is designing a solution to capture customer activity in different web applications to process analytics and make predictions. Customer activity in the web applications is unpredictable and can increase suddenly. The company requires a solution that integrates with other web applications. The solution must include an authorization step for security purposes.

Which solution will meet these requirements?

- A. Configure a Gateway Load Balancer (GWLB) in front of an Amazon Elastic Container Service (Amazon ECS) container instance that stores the information that the company receives in an Amazon Elastic File System (Amazon EFS) file system. Authorization is resolved at the GWLB.
- B. Configure an Amazon API Gateway endpoint in front of an Amazon Kinesis data stream that stores the information that the company receives in an Amazon S3 bucket. Use an AWS Lambda function to resolve authorization.
- C. Configure an Amazon API Gateway endpoint in front of an Amazon Kinesis Data Firehose that stores the information that the company receives in an Amazon S3 bucket. Use an API Gateway Lambda authorizer to resolve authorization. **Most Voted**
- D. Configure a Gateway Load Balancer (GWLB) in front of an Amazon Elastic Container Service (Amazon ECS) container instance that stores the information that the company receives on an Amazon Elastic File System (Amazon EFS) file system. Use an AWS Lambda function to resolve authorization.

Suggested Answer: C

Question #: 588

An ecommerce company wants a disaster recovery solution for its Amazon RDS DB instances that run Microsoft SQL Server Enterprise Edition. The company's current recovery point objective (RPO) and recovery time objective (RTO) are 24 hours.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a cross-Region read replica and promote the read replica to the primary instance.
- B. Use AWS Database Migration Service (AWS DMS) to create RDS cross-Region replication.
- C. Use cross-Region replication every 24 hours to copy native backups to an Amazon S3 bucket.
- D. Copy automatic snapshots to another Region every 24 hours. **Most Voted**

Suggested Answer: D

Question #: 589

A company runs a web application on Amazon EC2 instances in an Auto Scaling group behind an Application Load Balancer that has sticky sessions enabled. The web server currently hosts the user session state. The

company wants to ensure high availability and avoid user session state loss in the event of a web server outage.

Which solution will meet these requirements?

- A. Use an Amazon ElastiCache for Memcached instance to store the session data. Update the application to use ElastiCache for Memcached to store the session state.
- B. Use Amazon ElastiCache for Redis to store the session state. Update the application to use ElastiCache for Redis to store the session state. **Most Voted**
- C. Use an AWS Storage Gateway cached volume to store session data. Update the application to use AWS Storage Gateway cached volume to store the session state.
- D. Use Amazon RDS to store the session state. Update the application to use Amazon RDS to store the session state.

Suggested Answer: B

Question #: 590

A company migrated a MySQL database from the company's on-premises data center to an Amazon RDS for MySQL DB instance. The company sized the RDS DB instance to meet the company's average daily workload. Once a month, the database performs slowly when the company runs queries for a report. The company wants to have the ability to run reports and maintain the performance of the daily workloads.

Which solution will meet these requirements?

- A. Create a read replica of the database. Direct the queries to the read replica. **Most Voted**
- B. Create a backup of the database. Restore the backup to another DB instance. Direct the queries to the new database.
- C. Export the data to Amazon S3. Use Amazon Athena to query the S3 bucket.
- D. Resize the DB instance to accommodate the additional workload.

Suggested Answer: A

Question #: 591

A company runs a container application by using Amazon Elastic Kubernetes Service (Amazon EKS). The application includes microservices that manage customers and place orders. The company needs to route incoming requests to the appropriate microservices.

Which solution will meet this requirement MOST cost-effectively?

- A. Use the AWS Load Balancer Controller to provision a Network Load Balancer.
- B. Use the AWS Load Balancer Controller to provision an Application Load Balancer. **Most Voted**
- C. Use an AWS Lambda function to connect the requests to Amazon EKS.
- D. Use Amazon API Gateway to connect the requests to Amazon EKS. **Most Voted**

Suggested Answer: B

Question #: 592

A company uses AWS and sells access to copyrighted images. The company's global customer base needs to be able to access these images quickly. The company must deny access to users from specific countries. The company wants to minimize costs as much as possible.

Which solution will meet these requirements?

- A. Use Amazon S3 to store the images. Turn on multi-factor authentication (MFA) and public bucket access. Provide customers with a link to the S3 bucket.
- B. Use Amazon S3 to store the images. Create an IAM user for each customer. Add the users to a group that has permission to access the S3 bucket.
- C. Use Amazon EC2 instances that are behind Application Load Balancers (ALBs) to store the images. Deploy the instances only in the countries the company services. Provide customers with links to the ALBs for their specific country's instances.
- D. Use Amazon S3 to store the images. Use Amazon CloudFront to distribute the images with geographic restrictions. Provide a signed URL for each customer to access the data in CloudFront. **Most Voted**

Suggested Answer: D

Question #: 593

A solutions architect is designing a highly available Amazon ElastiCache for Redis based solution. The solutions architect needs to ensure that failures do not result in performance degradation or loss of data locally and within an AWS Region. The solution needs to provide high availability at the node level and at the Region level.

Which solution will meet these requirements?

- A. Use Multi-AZ Redis replication groups with shards that contain multiple nodes. **Most Voted**
- B. Use Redis shards that contain multiple nodes with Redis append only files (AOF) turned on.
- C. Use a Multi-AZ Redis cluster with more than one read replica in the replication group.
- D. Use Redis shards that contain multiple nodes with Auto Scaling turned on.

Suggested Answer: A

Question #: 594

A company plans to migrate to AWS and use Amazon EC2 On-Demand Instances for its application. During the migration testing phase, a technical team observes that the application takes a long time to launch and load memory to become fully productive.

Which solution will reduce the launch time of the application during the next testing phase?

- A. Launch two or more EC2 On-Demand Instances. Turn on auto scaling features and make the EC2 On-Demand Instances available during the next testing phase.
- B. Launch EC2 Spot Instances to support the application and to scale the application so it is available during the next testing phase.
- C. Launch the EC2 On-Demand Instances with hibernation turned on. Configure EC2 Auto Scaling warm pools during the next testing phase. **Most Voted**
- D. Launch EC2 On-Demand Instances with Capacity Reservations. Start additional EC2 instances during the next testing phase.

Suggested Answer: C

Question #: 595

A company's applications run on Amazon EC2 instances in Auto Scaling groups. The company notices that its applications experience sudden traffic increases on random days of the week. The company wants to maintain application performance during sudden traffic increases.

Which solution will meet these requirements MOST cost-effectively?

- A. Use manual scaling to change the size of the Auto Scaling group.
- B. Use predictive scaling to change the size of the Auto Scaling group.
- C. Use dynamic scaling to change the size of the Auto Scaling group. **Most Voted**
- D. Use schedule scaling to change the size of the Auto Scaling group.

Suggested Answer: C

Question #: 596

An ecommerce application uses a PostgreSQL database that runs on an Amazon EC2 instance. During a monthly sales event, database usage increases and causes database connection issues for the application. The traffic is unpredictable for subsequent monthly sales events, which impacts the sales forecast. The company needs to maintain performance when there is an unpredictable increase in traffic.

Which solution resolves this issue in the MOST cost-effective way?

- A. Migrate the PostgreSQL database to Amazon Aurora Serverless v2. **Most Voted**
- B. Enable auto scaling for the PostgreSQL database on the EC2 instance to accommodate increased usage.
- C. Migrate the PostgreSQL database to Amazon RDS for PostgreSQL with a larger instance type.
- D. Migrate the PostgreSQL database to Amazon Redshift to accommodate increased usage.

Suggested Answer: A

Question #: 597

A company hosts an internal serverless application on AWS by using Amazon API Gateway and AWS Lambda. The company's employees report issues with high latency when they begin using the application each day. The company wants to reduce latency.

Which solution will meet these requirements?

- A. Increase the API Gateway throttling limit.
- B. Set up a scheduled scaling to increase Lambda provisioned concurrency before employees begin to use the application each day. **Most Voted**
- C. Create an Amazon CloudWatch alarm to initiate a Lambda function as a target for the alarm at the beginning of each day.
- D. Increase the Lambda function memory.

Suggested Answer: B

Question #: 598

A research company uses on-premises devices to generate data for analysis. The company wants to use the AWS Cloud to analyze the data. The devices generate .csv files and support writing the data to an SMB file share. Company analysts must be able to use SQL commands to query the data. The analysts will run queries periodically throughout the day.

Which combination of steps will meet these requirements MOST cost-effectively? (Choose three.)

- A. Deploy an AWS Storage Gateway on premises in Amazon S3 File Gateway mode. **Most Voted**
- B. Deploy an AWS Storage Gateway on premises in Amazon FSx File Gateway made.
- C. Set up an AWS Glue crawler to create a table based on the data that is in Amazon S3. **Most Voted**
- D. Set up an Amazon EMR cluster with EMR File System (EMRFS) to query the data that is in Amazon S3. Provide access to analysts.
- E. Set up an Amazon Redshift cluster to query the data that is in Amazon S3. Provide access to analysts.
- F. Setup Amazon Athena to query the data that is in Amazon S3. Provide access to analysts. **Most Voted**

Suggested Answer: ACF

Question #: 599

A company wants to use Amazon Elastic Container Service (Amazon ECS) clusters and Amazon RDS DB instances to build and run a payment processing application. The company will run the application in its on-premises data center for compliance purposes.

A solutions architect wants to use AWS Outposts as part of the solution. The solutions architect is working with the company's operational team to build the application.

Which activities are the responsibility of the company's operational team? (Choose three.)

- A. Providing resilient power and network connectivity to the Outposts racks **Most VotedMost VotedMost Voted**
- B. Managing the virtualization hypervisor, storage systems, and the AWS services that run on Outposts
- C. Physical security and access controls of the data center environment **Most VotedMost VotedMost Voted**
- D. Availability of the Outposts infrastructure including the power supplies, servers, and networking equipment within the Outposts racks
- E. Physical maintenance of Outposts components
- F. Providing extra capacity for Amazon ECS clusters to mitigate server failures and maintenance events **Most Voted**

Suggested Answer: ACF

Question #: 600

A company is planning to migrate a TCP-based application into the company's VPC. The application is publicly accessible on a nonstandard TCP port through a hardware appliance in the company's data center. This public endpoint can process up to 3 million requests per second with low latency. The company requires the same level of performance for the new public endpoint in AWS.

What should a solutions architect recommend to meet this requirement?

- A. Deploy a Network Load Balancer (NLB). Configure the NLB to be publicly accessible over the TCP port that the application requires. **Most Voted**
- B. Deploy an Application Load Balancer (ALB). Configure the ALB to be publicly accessible over the TCP port that the application requires.
- C. Deploy an Amazon CloudFront distribution that listens on the TCP port that the application requires. Use an Application Load Balancer as the origin.
- D. Deploy an Amazon API Gateway API that is configured with the TCP port that the application requires. Configure AWS Lambda functions with provisioned concurrency to process the requests.

Suggested Answer: A

Question #: 601

A company runs its critical database on an Amazon RDS for PostgreSQL DB instance. The company wants to migrate to Amazon Aurora PostgreSQL with minimal downtime and data loss.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a DB snapshot of the RDS for PostgreSQL DB instance to populate a new Aurora PostgreSQL DB cluster.
- B. Create an Aurora read replica of the RDS for PostgreSQL DB instance. Promote the Aurora read replicate to a new Aurora PostgreSQL DB cluster. **Most Voted**
- C. Use data import from Amazon S3 to migrate the database to an Aurora PostgreSQL DB cluster.
- D. Use the pg_dump utility to back up the RDS for PostgreSQL database. Restore the backup to a new Aurora PostgreSQL DB cluster.

Suggested Answer: B

Question #: 602

A company's infrastructure consists of hundreds of Amazon EC2 instances that use Amazon Elastic Block Store (Amazon EBS) storage. A solutions architect must ensure that every EC2 instance can be recovered after a disaster.

What should the solutions architect do to meet this requirement with the LEAST amount of effort?

- A. Take a snapshot of the EBS storage that is attached to each EC2 instance. Create an AWS CloudFormation template to launch new EC2 instances from the EBS storage.
- B. Take a snapshot of the EBS storage that is attached to each EC2 instance. Use AWS Elastic Beanstalk to set the environment based on the EC2 template and attach the EBS storage.
- C. Use AWS Backup to set up a backup plan for the entire group of EC2 instances. Use the AWS Backup API or the AWS CLI to speed up the restore process for multiple EC2 instances. **Most Voted**
- D. Create an AWS Lambda function to take a snapshot of the EBS storage that is attached to each EC2 instance and copy the Amazon Machine Images (AMIs). Create another Lambda function to perform the restores with the copied AMIs and attach the EBS storage.

Suggested Answer: C

Question #: 603

A company recently migrated to the AWS Cloud. The company wants a serverless solution for large-scale parallel on-demand processing of a semistructured dataset. The data consists of logs, media files, sales transactions, and IoT sensor data that is stored in Amazon S3. The company wants the solution to process thousands of items in the dataset in parallel.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Use the AWS Step Functions Map state in Inline mode to process the data in parallel.
- B. Use the AWS Step Functions Map state in Distributed mode to process the data in parallel. **Most Voted**
- C. Use AWS Glue to process the data in parallel.
- D. Use several AWS Lambda functions to process the data in parallel.

Suggested Answer: B

Question #: 604

A company will migrate 10 PB of data to Amazon S3 in 6 weeks. The current data center has a 500 Mbps uplink to the internet. Other on-premises applications share the uplink. The company can use 80% of the internet bandwidth for this one-time migration task.

Which solution will meet these requirements?

- A. Configure AWS DataSync to migrate the data to Amazon S3 and to automatically verify the data.
- B. Use rsync to transfer the data directly to Amazon S3.
- C. Use the AWS CLI and multiple copy processes to send the data directly to Amazon S3.
- D. Order multiple AWS Snowball devices. Copy the data to the devices. Send the devices to AWS to copy the data to Amazon S3. **Most Voted**

Suggested Answer: D

Question #: 605

A company has several on-premises Internet Small Computer Systems Interface (iSCSI) network storage servers. The company wants to reduce the number of these servers by moving to the AWS Cloud. A solutions architect must provide low-latency access to frequently used data and reduce the dependency on on-premises servers with a minimal number of infrastructure changes.

Which solution will meet these requirements?

- A. Deploy an Amazon S3 File Gateway.
- B. Deploy Amazon Elastic Block Store (Amazon EBS) storage with backups to Amazon S3.
- C. Deploy an AWS Storage Gateway volume gateway that is configured with stored volumes.
- D. Deploy an AWS Storage Gateway volume gateway that is configured with cached volumes. **Most Voted**

Suggested Answer: D

Question #: 606

A solutions architect is designing an application that will allow business users to upload objects to Amazon S3. The solution needs to maximize object durability. Objects also must be readily available at any time and for any length of time. Users will access objects frequently within the first 30 days after the objects are uploaded, but users are much less likely to access objects that are older than 30 days.

Which solution meets these requirements MOST cost-effectively?

- A. Store all the objects in S3 Standard with an S3 Lifecycle rule to transition the objects to S3 Glacier after 30 days.
- B. Store all the objects in S3 Standard with an S3 Lifecycle rule to transition the objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days. **Most Voted**
- C. Store all the objects in S3 Standard with an S3 Lifecycle rule to transition the objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 30 days.
- D. Store all the objects in S3 Intelligent-Tiering with an S3 Lifecycle rule to transition the objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days.

Suggested Answer: B

Question #: 607

A company has migrated a two-tier application from its on-premises data center to the AWS Cloud. The data tier is a Multi-AZ deployment of Amazon RDS for Oracle with 12 TB of General Purpose SSD Amazon Elastic Block Store (Amazon EBS) storage. The application is designed to process and store documents in the database as binary large objects (blobs) with an average document size of 6 MB.

The database size has grown over time, reducing the performance and increasing the cost of storage. The company must improve the database performance and needs a solution that is highly available and resilient.

Which solution will meet these requirements MOST cost-effectively?

- A. Reduce the RDS DB instance size. Increase the storage capacity to 24 TiB. Change the storage type to Magnetic.

- B. Increase the RDS DB instance size. Increase the storage capacity to 24 TiChange the storage type to Provisioned IOPS.
- C. Create an Amazon S3 bucket. Update the application to store documents in the S3 bucket. Store the object metadata in the existing database. **Most Voted**
- D. Create an Amazon DynamoDB table. Update the application to use DynamoDB. Use AWS Database Migration Service (AWS DMS) to migrate data from the Oracle database to DynamoDB.

Suggested Answer: C

Question #: 608

A company has an application that serves clients that are deployed in more than 20,000 retail storefront locations around the world. The application consists of backend web services that are exposed over HTTPS on port 443. The application is hosted on Amazon EC2 instances behind an Application Load Balancer (ALB). The retail locations communicate with the web application over the public internet. The company allows each retail location to register the IP address that the retail location has been allocated by its local ISP.

The company's security team recommends to increase the security of the application endpoint by restricting access to only the IP addresses registered by the retail locations.

What should a solutions architect do to meet these requirements?

- A. Associate an AWS WAF web ACL with the ALB. Use IP rule sets on the ALB to filter traffic. Update the IP addresses in the rule to include the registered IP addresses. **Most Voted**
- B. Deploy AWS Firewall Manager to manage the ALB. Configure firewall rules to restrict traffic to the ALB. Modify the firewall rules to include the registered IP addresses.
- C. Store the IP addresses in an Amazon DynamoDB table. Configure an AWS Lambda authorization function on the ALB to validate that incoming requests are from the registered IP addresses.
- D. Configure the network ACL on the subnet that contains the public interface of the ALB. Update the ingress rules on the network ACL with entries for each of the registered IP addresses.

Suggested Answer: A

Question #: 609

A company is building a data analysis platform on AWS by using AWS Lake Formation. The platform will ingest data from different sources such as Amazon S3 and Amazon RDS. The company needs a secure solution to prevent access to portions of the data that contain sensitive information.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an IAM role that includes permissions to access Lake Formation tables.
- B. Create data filters to implement row-level security and cell-level security. **Most Voted**
- C. Create an AWS Lambda function that removes sensitive information before Lake Formation ingests the data.
- D. Create an AWS Lambda function that periodically queries and removes sensitive information from Lake Formation tables.

Suggested Answer: B

Question #: 610

A company deploys Amazon EC2 instances that run in a VPC. The EC2 instances load source data into Amazon S3 buckets so that the data can be processed in the future. According to compliance laws, the data must not be transmitted over the public internet. Servers in the company's on-premises data center will consume the output from an application that runs on the EC2 instances.

Which solution will meet these requirements?

- A. Deploy an interface VPC endpoint for Amazon EC2. Create an AWS Site-to-Site VPN connection between the company and the VPC.
- B. Deploy a gateway VPC endpoint for Amazon S3. Set up an AWS Direct Connect connection between the on-premises network and the VPC. **Most Voted**
- C. Set up an AWS Transit Gateway connection from the VPC to the S3 buckets. Create an AWS Site-to-Site VPN connection between the company and the VPC.
- D. Set up proxy EC2 instances that have routes to NAT gateways. Configure the proxy EC2 instances to fetch S3 data and feed the application instances.

Suggested Answer: B

A company has an application with a REST-based interface that allows data to be received in near-real time from a third-party vendor. Once received, the application processes and stores the data for further analysis. The application is running on Amazon EC2 instances.

The third-party vendor has received many 503 Service Unavailable Errors when sending data to the application. When the data volume spikes, the compute capacity reaches its maximum limit and the application is unable to process all requests.

Which design should a solutions architect recommend to provide a more scalable solution?

- A. Use Amazon Kinesis Data Streams to ingest the data. Process the data using AWS Lambda functions. **Most Voted**
- B. Use Amazon API Gateway on top of the existing application. Create a usage plan with a quota limit for the third-party vendor.
- C. Use Amazon Simple Notification Service (Amazon SNS) to ingest the data. Put the EC2 instances in an Auto Scaling group behind an Application Load Balancer.
- D. Repackage the application as a container. Deploy the application using Amazon Elastic Container Service (Amazon ECS) using the EC2 launch type with an Auto Scaling group.

Suggested Answer: A

Question #: 612

A company has an application that runs on Amazon EC2 instances in a private subnet. The application needs to process sensitive information from an Amazon S3 bucket. The application must not use the internet to connect to the S3 bucket.

Which solution will meet these requirements?

- A. Configure an internet gateway. Update the S3 bucket policy to allow access from the internet gateway. Update the application to use the new internet gateway.

- B. Configure a VPN connection. Update the S3 bucket policy to allow access from the VPN connection. Update the application to use the new VPN connection.
- C. Configure a NAT gateway. Update the S3 bucket policy to allow access from the NAT gateway. Update the application to use the new NAT gateway.
- D. Configure a VPC endpoint. Update the S3 bucket policy to allow access from the VPC endpoint. Update the application to use the new VPC endpoint. **Most Voted**

Suggested Answer: D

Question #: 613

A company uses Amazon Elastic Kubernetes Service (Amazon EKS) to run a container application. The EKS cluster stores sensitive information in the Kubernetes secrets object. The company wants to ensure that the information is encrypted.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use the container application to encrypt the information by using AWS Key Management Service (AWS KMS).
- B. Enable secrets encryption in the EKS cluster by using AWS Key Management Service (AWS KMS). **Most Voted**
- C. Implement an AWS Lambda function to encrypt the information by using AWS Key Management Service (AWS KMS).
- D. Use AWS Systems Manager Parameter Store to encrypt the information by using AWS Key Management Service (AWS KMS).

Suggested Answer: B

Question #: 614

A company is designing a new multi-tier web application that consists of the following components:

- Web and application servers that run on Amazon EC2 instances as part of Auto Scaling groups
- An Amazon RDS DB instance for data storage

A solutions architect needs to limit access to the application servers so that only the web servers can access them.

Which solution will meet these requirements?

- A. Deploy AWS PrivateLink in front of the application servers. Configure the network ACL to allow only the web servers to access the application servers.
- B. Deploy a VPC endpoint in front of the application servers. Configure the security group to allow only the web servers to access the application servers.
- C. Deploy a Network Load Balancer with a target group that contains the application servers' Auto Scaling group. Configure the network ACL to allow only the web servers to access the application servers.
- D. Deploy an Application Load Balancer with a target group that contains the application servers' Auto Scaling group. Configure the security group to allow only the web servers to access the application servers. **Most Voted**

Suggested Answer: D

Question #: 615

A company runs a critical, customer-facing application on Amazon Elastic Kubernetes Service (Amazon EKS). The application has a microservices architecture. The company needs to implement a solution that collects, aggregates, and summarizes metrics and logs from the application in a centralized location.

Which solution meets these requirements?

- A. Run the Amazon CloudWatch agent in the existing EKS cluster. View the metrics and logs in the CloudWatch console.
- B. Run AWS App Mesh in the existing EKS cluster. View the metrics and logs in the App Mesh console.
- C. Configure AWS CloudTrail to capture data events. Query CloudTrail by using Amazon OpenSearch Service.
- D. Configure Amazon CloudWatch Container Insights in the existing EKS cluster. View the metrics and logs in the CloudWatch console. **Most Voted**

Suggested Answer: D

Question #: 616

A company has deployed its newest product on AWS. The product runs in an Auto Scaling group behind a Network Load Balancer. The company stores the product's objects in an Amazon S3 bucket.

The company recently experienced malicious attacks against its systems. The company needs a solution that continuously monitors for malicious activity in the AWS account, workloads, and access patterns to the S3 bucket. The solution must also report suspicious activity and display the information on a dashboard.

Which solution will meet these requirements?

- A. Configure Amazon Macie to monitor and report findings to AWS Config.
- B. Configure Amazon Inspector to monitor and report findings to AWS CloudTrail.
- C. Configure Amazon GuardDuty to monitor and report findings to AWS Security Hub. **Most Voted**
- D. Configure AWS Config to monitor and report findings to Amazon EventBridge.

Suggested Answer: C

Question #: 617

A company wants to migrate an on-premises data center to AWS. The data center hosts a storage server that stores data in an NFS-based file system. The storage server holds 200 GB of data. The company needs to migrate the data without interruption to existing services. Multiple resources in AWS must be able to access the data by using the NFS protocol.

Which combination of steps will meet these requirements MOST cost-effectively? (Choose two.)

- A. Create an Amazon FSx for Lustre file system.
- B. Create an Amazon Elastic File System (Amazon EFS) file system. **Most Voted**
- C. Create an Amazon S3 bucket to receive the data.
- D. Manually use an operating system copy command to push the data into the AWS destination.

- E. Install an AWS DataSync agent in the on-premises data center. Use a DataSync task between the on-premises location and AWS. **Most Voted**

Suggested Answer: BE

Question #: 618

A company wants to use Amazon FSx for Windows File Server for its Amazon EC2 instances that have an SMB file share mounted as a volume in the us-east-1 Region. The company has a recovery point objective (RPO) of 5 minutes for planned system maintenance or unplanned service disruptions. The company needs to replicate the file system to the us-west-2 Region. The replicated data must not be deleted by any user for 5 years.

Which solution will meet these requirements?

- A. Create an FSx for Windows File Server file system in us-east-1 that has a Single-AZ 2 deployment type. Use AWS Backup to create a daily backup plan that includes a backup rule that copies the backup to us-west-2. Configure AWS Backup Vault Lock in compliance mode for a target vault in us-west-2. Configure a minimum duration of 5 years.
- B. Create an FSx for Windows File Server file system in us-east-1 that has a Multi-AZ deployment type. Use AWS Backup to create a daily backup plan that includes a backup rule that copies the backup to us-west-2. Configure AWS Backup Vault Lock in governance mode for a target vault in us-west-2. Configure a minimum duration of 5 years.
- C. Create an FSx for Windows File Server file system in us-east-1 that has a Multi-AZ deployment type. Use AWS Backup to create a daily backup plan that includes a backup rule that copies the backup to us-west-2. Configure AWS Backup Vault Lock in compliance mode for a target vault in us-west-2. Configure a minimum duration of 5 years. **Most Voted**
- D. Create an FSx for Windows File Server file system in us-east-1 that has a Single-AZ 2 deployment type. Use AWS Backup to create a daily backup plan that includes a backup rule that copies the backup to us-west-2. Configure AWS Backup Vault Lock in governance mode for a target vault in us-west-2. Configure a minimum duration of 5 years.

Suggested Answer: C

Question #: 619

A solutions architect is designing a security solution for a company that wants to provide developers with individual AWS accounts through AWS Organizations, while also maintaining standard security controls. Because the individual developers will have AWS account root user-level access to their own accounts, the solutions architect wants to ensure that the mandatory AWS CloudTrail configuration that is applied to new developer accounts is not modified.

Which action meets these requirements?

- A. Create an IAM policy that prohibits changes to CloudTrail. and attach it to the root user.
- B. Create a new trail in CloudTrail from within the developer accounts with the organization trails option enabled.
- C. Create a service control policy (SCP) that prohibits changes to CloudTrail, and attach it the developer accounts. **Most Voted**
- D. Create a service-linked role for CloudTrail with a policy condition that allows changes only from an Amazon Resource Name (ARN) in the management account.

Suggested Answer: C

Question #: 620

A company is planning to deploy a business-critical application in the AWS Cloud. The application requires durable storage with consistent, low-latency performance.

Which type of storage should a solutions architect recommend to meet these requirements?

- A. Instance store volume
- B. Amazon ElastiCache for Memcached cluster
- C. Provisioned IOPS SSD Amazon Elastic Block Store (Amazon EBS) volume **Most Voted**
- D. Throughput Optimized HDD Amazon Elastic Block Store (Amazon EBS) volume

Suggested Answer: C

Question #: 621

An online photo-sharing company stores its photos in an Amazon S3 bucket that exists in the us-west-1 Region. The company needs to store a copy of all new photos in the us-east-1 Region.

Which solution will meet this requirement with the LEAST operational effort?

- A. Create a second S3 bucket in us-east-1. Use S3 Cross-Region Replication to copy photos from the existing S3 bucket to the second S3 bucket. **Most Voted**
- B. Create a cross-origin resource sharing (CORS) configuration of the existing S3 bucket. Specify us-east-1 in the CORS rule's AllowedOrigin element.
- C. Create a second S3 bucket in us-east-1 across multiple Availability Zones. Create an S3 Lifecycle rule to save photos into the second S3 bucket.
- D. Create a second S3 bucket in us-east-1. Configure S3 event notifications on object creation and update events to invoke an AWS Lambda function to copy photos from the existing S3 bucket to the second S3 bucket.

Suggested Answer: A

Question #: 622

A company is creating a new web application for its subscribers. The application will consist of a static single page and a persistent database layer. The application will have millions of users for 4 hours in the morning, but the application will have only a few thousand users during the rest of the day. The company's data architects have requested the ability to rapidly evolve their schema.

Which solutions will meet these requirements and provide the MOST scalability? (Choose two.)

- A. Deploy Amazon DynamoDB as the database solution. Provision on-demand capacity. **Most Voted**
- B. Deploy Amazon Aurora as the database solution. Choose the serverless DB engine mode.
- C. Deploy Amazon DynamoDB as the database solution. Ensure that DynamoDB auto scaling is enabled.
- D. Deploy the static content into an Amazon S3 bucket. Provision an Amazon CloudFront distribution with the S3 bucket as the origin. **Most VotedMost Voted**

- E. Deploy the web servers for static content across a fleet of Amazon EC2 instances in Auto Scaling groups. Configure the instances to periodically refresh the content from an Amazon Elastic File System (Amazon EFS) volume.

Suggested Answer: AD

Question #: 623

A company uses Amazon API Gateway to manage its REST APIs that third-party service providers access. The company must protect the REST APIs from SQL injection and cross-site scripting attacks.

What is the MOST operationally efficient solution that meets these requirements?

- A. Configure AWS Shield.
- B. Configure AWS WAF. **Most Voted**
- C. Set up API Gateway with an Amazon CloudFront distribution. Configure AWS Shield in CloudFront.
- D. Set up API Gateway with an Amazon CloudFront distribution. Configure AWS WAF in CloudFront.

Suggested Answer: B

Question #: 624

A company wants to provide users with access to AWS resources. The company has 1,500 users and manages their access to on-premises resources through Active Directory user groups on the corporate network. However, the company does not want users to have to maintain another identity to access the resources. A solutions architect must manage user access to the AWS resources while preserving access to the on-premises resources.

What should the solutions architect do to meet these requirements?

- A. Create an IAM user for each user in the company. Attach the appropriate policies to each user.
- B. Use Amazon Cognito with an Active Directory user pool. Create roles with the appropriate policies attached.
- C. Define cross-account roles with the appropriate policies attached. Map the roles to the Active Directory groups.

- D. Configure Security Assertion Markup Language (SAML) 2.0-based federation. Create roles with the appropriate policies attached. Map the roles to the Active Directory groups. **Most Voted**

Suggested Answer: D

Question #: 625

A company is hosting a website behind multiple Application Load Balancers. The company has different distribution rights for its content around the world. A solutions architect needs to ensure that users are served the correct content without violating distribution rights.

Which configuration should the solutions architect choose to meet these requirements?

- A. Configure Amazon CloudFront with AWS WAF.
- B. Configure Application Load Balancers with AWS WAF
- C. Configure Amazon Route 53 with a geolocation policy **Most Voted**
- D. Configure Amazon Route 53 with a geoproximity routing policy

Suggested Answer: C

Question #: 626

A company stores its data on premises. The amount of data is growing beyond the company's available capacity.

The company wants to migrate its data from the on-premises location to an Amazon S3 bucket. The company needs a solution that will automatically validate the integrity of the data after the transfer.

Which solution will meet these requirements?

- A. Order an AWS Snowball Edge device. Configure the Snowball Edge device to perform the online data transfer to an S3 bucket

- B. Deploy an AWS DataSync agent on premises. Configure the DataSync agent to perform the online data transfer to an S3 bucket. **Most Voted**
- C. Create an Amazon S3 File Gateway on premises. Configure the S3 File Gateway to perform the online data transfer to an S3 bucket.
- D. Configure an accelerator in Amazon S3 Transfer Acceleration on premises. Configure the accelerator to perform the online data transfer to an S3 bucket.

Suggested Answer: B

Question #: 627

A company wants to migrate two DNS servers to AWS. The servers host a total of approximately 200 zones and receive 1 million requests each day on average. The company wants to maximize availability while minimizing the operational overhead that is related to the management of the two servers.

What should a solutions architect recommend to meet these requirements?

- A. Create 200 new hosted zones in the Amazon Route 53 console. Import zone files. **Most Voted**
- B. Launch a single large Amazon EC2 instance. Import zone files. Configure Amazon CloudWatch alarms and notifications to alert the company about any downtime.
- C. Migrate the servers to AWS by using AWS Server Migration Service (AWS SMS). Configure Amazon CloudWatch alarms and notifications to alert the company about any downtime.
- D. Launch an Amazon EC2 instance in an Auto Scaling group across two Availability Zones. Import zone files. Set the desired capacity to 1 and the maximum for the Auto Scaling group. Configure scaling alarms to scale based on CPU utilization.

Suggested Answer: A

Question #: 628

A global company runs its applications in multiple AWS accounts in AWS Organizations. The company's applications use multipart uploads to upload data to multiple Amazon S3 buckets across AWS Regions. The company wants to report on incomplete multipart uploads for cost compliance purposes.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Configure AWS Config with a rule to report the incomplete multipart upload object count.
- B. Create a service control policy (SCP) to report the incomplete multipart upload object count.
- C. Configure S3 Storage Lens to report the incomplete multipart upload object count. **Most Voted**
- D. Create an S3 Multi-Region Access Point to report the incomplete multipart upload object count.

Suggested Answer: C

Question #: 629

A company runs a production database on Amazon RDS for MySQL. The company wants to upgrade the database version for security compliance reasons. Because the database contains critical data, the company wants a quick solution to upgrade and test functionality without losing any data.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an RDS manual snapshot. Upgrade to the new version of Amazon RDS for MySQL.
- B. Use native backup and restore. Restore the data to the upgraded new version of Amazon RDS for MySQL.
- C. Use AWS Database Migration Service (AWS DMS) to replicate the data to the upgraded new version of Amazon RDS for MySQL.
- D. Use Amazon RDS Blue/Green Deployments to deploy and test production changes. **Most Voted**

Suggested Answer: D

Question #: 630

A solutions architect is creating a data processing job that runs once daily and can take up to 2 hours to complete. If the job is interrupted, it has to restart from the beginning.

How should the solutions architect address this issue in the MOST cost-effective manner?

- A. Create a script that runs locally on an Amazon EC2 Reserved Instance that is triggered by a cron job.
- B. Create an AWS Lambda function triggered by an Amazon EventBridge scheduled event.
- C. Use an Amazon Elastic Container Service (Amazon ECS) Fargate task triggered by an Amazon EventBridge scheduled event. **Most Voted**
- D. Use an Amazon Elastic Container Service (Amazon ECS) task running on Amazon EC2 triggered by an Amazon EventBridge scheduled event.

Suggested Answer: C

Question #: 631

A social media company wants to store its database of user profiles, relationships, and interactions in the AWS Cloud. The company needs an application to monitor any changes in the database. The application needs to analyze the relationships between the data entities and to provide recommendations to users.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Neptune to store the information. Use Amazon Kinesis Data Streams to process changes in the database.
- B. Use Amazon Neptune to store the information. Use Neptune Streams to process changes in the database. **Most Voted**
- C. Use Amazon Quantum Ledger Database (Amazon QLDB) to store the information. Use Amazon Kinesis Data Streams to process changes in the database.
- D. Use Amazon Quantum Ledger Database (Amazon QLDB) to store the information. Use Neptune Streams to process changes in the database.

Suggested Answer: B

Question #: 632

A company is creating a new application that will store a large amount of data. The data will be analyzed hourly and will be modified by several Amazon EC2 Linux instances that are deployed across multiple Availability Zones. The needed amount of storage space will continue to grow for the next 6 months.

Which storage solution should a solutions architect recommend to meet these requirements?

- A. Store the data in Amazon S3 Glacier. Update the S3 Glacier vault policy to allow access to the application instances.
- B. Store the data in an Amazon Elastic Block Store (Amazon EBS) volume. Mount the EBS volume on the application instances.
- C. Store the data in an Amazon Elastic File System (Amazon EFS) file system. Mount the file system on the application instances.
- D. Store the data in an Amazon Elastic Block Store (Amazon EBS) Provisioned IOPS volume shared between the application instances.

Suggested Answer: C

Question #: 633

A company manages an application that stores data on an Amazon RDS for PostgreSQL Multi-AZ DB instance. Increases in traffic are causing performance problems. The company determines that database queries are the primary reason for the slow performance.

What should a solutions architect do to improve the application's performance?

- A. Serve read traffic from the Multi-AZ standby replica.
- B. Configure the DB instance to use Transfer Acceleration.
- C. Create a read replica from the source DB instance. Serve read traffic from the read replica.
- D. Use Amazon Kinesis Data Firehose between the application and Amazon RDS to increase the concurrency of database requests.

Suggested Answer: C

Question #: 634

A company collects 10 GB of telemetry data daily from various machines. The company stores the data in an Amazon S3 bucket in a source data account.

The company has hired several consulting agencies to use this data for analysis. Each agency needs read access to the data for its analysts. The company must share the data from the source data account by choosing a solution that maximizes security and operational efficiency.

Which solution will meet these requirements?

- A. Configure S3 global tables to replicate data for each agency.
- B. Make the S3 bucket public for a limited time. Inform only the agencies.
- C. Configure cross-account access for the S3 bucket to the accounts that the agencies own. **Most Voted**
- D. Set up an IAM user for each analyst in the source data account. Grant each user access to the S3 bucket.

Suggested Answer: C

Question #: 635

A company uses Amazon FSx for NetApp ONTAP in its primary AWS Region for CIFS and NFS file shares. Applications that run on Amazon EC2 instances access the file shares. The company needs a storage disaster recovery (DR) solution in a secondary Region. The data that is replicated in the secondary Region needs to be accessed by using the same protocols as the primary Region.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS Lambda function to copy the data to an Amazon S3 bucket. Replicate the S3 bucket to the secondary Region.
- B. Create a backup of the FSx for ONTAP volumes by using AWS Backup. Copy the volumes to the secondary Region. Create a new FSx for ONTAP instance from the backup.
- C. Create an FSx for ONTAP instance in the secondary Region. Use NetApp SnapMirror to replicate data from the primary Region to the secondary Region. **Most Voted**

- D. Create an Amazon Elastic File System (Amazon EFS) volume. Migrate the current data to the volume. Replicate the volume to the secondary Region.

Suggested Answer: C

Question #: 636

A development team is creating an event-based application that uses AWS Lambda functions. Events will be generated when files are added to an Amazon S3 bucket. The development team currently has Amazon Simple Notification Service (Amazon SNS) configured as the event target from Amazon S3.

What should a solutions architect do to process the events from Amazon S3 in a scalable way?

- A. Create an SNS subscription that processes the event in Amazon Elastic Container Service (Amazon ECS) before the event runs in Lambda.
- B. Create an SNS subscription that processes the event in Amazon Elastic Kubernetes Service (Amazon EKS) before the event runs in Lambda
- C. Create an SNS subscription that sends the event to Amazon Simple Queue Service (Amazon SQS). Configure the SOS queue to trigger a Lambda function. **Most Voted**
- D. Create an SNS subscription that sends the event to AWS Server Migration Service (AWS SMS). Configure the Lambda function to poll from the SMS event.

Suggested Answer: C

Question #: 637

A solutions architect is designing a new service behind Amazon API Gateway. The request patterns for the service will be unpredictable and can change suddenly from 0 requests to over 500 per second. The total size of the data that needs to be persisted in a backend database is currently less than 1 GB with unpredictable future growth. Data can be queried using simple key-value requests.

Which combination of AWS services would meet these requirements? (Choose two.)

- A. AWS Fargate

- B. AWS Lambda **Most Voted**
- C. Amazon DynamoDB **Most Voted**
- D. Amazon EC2 Auto Scaling
- E. MySQL-compatible Amazon Aurora

Suggested Answer: BC

Question #: 638

A company collects and shares research data with the company's employees all over the world. The company wants to collect and store the data in an Amazon S3 bucket and process the data in the AWS Cloud. The company will share the data with the company's employees. The company needs a secure solution in the AWS Cloud that minimizes operational overhead.

Which solution will meet these requirements?

- A. Use an AWS Lambda function to create an S3 presigned URL. Instruct employees to use the URL. **Most Voted**
- B. Create an IAM user for each employee. Create an IAM policy for each employee to allow S3 access. Instruct employees to use the AWS Management Console.
- C. Create an S3 File Gateway. Create a share for uploading and a share for downloading. Allow employees to mount shares on their local computers to use S3 File Gateway.
- D. Configure AWS Transfer Family SFTP endpoints. Select the custom identity provider options. Use AWS Secrets Manager to manage the user credentials. Instruct employees to use Transfer Family. **Most Voted**

Suggested Answer: A

Question #: 639

A company is building a new furniture inventory application. The company has deployed the application on a fleet of Amazon EC2 instances across multiple Availability Zones. The EC2 instances run behind an Application Load Balancer (ALB) in their VPC.

A solutions architect has observed that incoming traffic seems to favor one EC2 instance, resulting in latency for

some requests.

What should the solutions architect do to resolve this issue?

- A. Disable session affinity (sticky sessions) on the ALB
- B. Replace the ALB with a Network Load Balancer
- C. Increase the number of EC2 instances in each Availability Zone
- D. Adjust the frequency of the health checks on the ALB's target group

Suggested Answer: A

Question #: 640

A company has an application workflow that uses an AWS Lambda function to download and decrypt files from Amazon S3. These files are encrypted using AWS Key Management Service (AWS KMS) keys. A solutions architect needs to design a solution that will ensure the required permissions are set correctly.

Which combination of actions accomplish this? (Choose two.)

- A. Attach the kms:decrypt permission to the Lambda function's resource policy
- B. Grant the decrypt permission for the Lambda IAM role in the KMS key's policy **Most Voted**
- C. Grant the decrypt permission for the Lambda resource policy in the KMS key's policy.
- D. Create a new IAM policy with the kms:decrypt permission and attach the policy to the Lambda function.
- E. Create a new IAM role with the kms:decrypt permission and attach the execution role to the Lambda function. **Most Voted**

Suggested Answer: BE

Question #: 641

A company wants to monitor its AWS costs for financial review. The cloud operations team is designing an architecture in the AWS Organizations management account to query AWS Cost and Usage Reports for all member accounts. The team must run this query once a month and provide a detailed analysis of the bill.

Which solution is the MOST scalable and cost-effective way to meet these requirements?

- A. Enable Cost and Usage Reports in the management account. Deliver reports to Amazon Kinesis. Use Amazon EMR for analysis.
- B. Enable Cost and Usage Reports in the management account. Deliver the reports to Amazon S3 Use Amazon Athena for analysis. **Most Voted**
- C. Enable Cost and Usage Reports for member accounts. Deliver the reports to Amazon S3 Use Amazon Redshift for analysis.
- D. Enable Cost and Usage Reports for member accounts. Deliver the reports to Amazon Kinesis. Use Amazon QuickSight for analysis.

Suggested Answer: B

Question #: 642

A company wants to run a gaming application on Amazon EC2 instances that are part of an Auto Scaling group in the AWS Cloud. The application will transmit data by using UDP packets. The company wants to ensure that the application can scale out and in as traffic increases and decreases.

What should a solutions architect do to meet these requirements?

- A. Attach a Network Load Balancer to the Auto Scaling group. **Most Voted**
- B. Attach an Application Load Balancer to the Auto Scaling group.
- C. Deploy an Amazon Route 53 record set with a weighted policy to route traffic appropriately.
- D. Deploy a NAT instance that is configured with port forwarding to the EC2 instances in the Auto Scaling group.

Suggested Answer: A

Question #: 643

A company runs several websites on AWS for its different brands. Each website generates tens of gigabytes of web traffic logs each day. A solutions architect needs to design a scalable solution to give the company's

developers the ability to analyze traffic patterns across all the company's websites. This analysis by the developers will occur on demand once a week over the course of several months. The solution must support queries with standard SQL.

Which solution will meet these requirements MOST cost-effectively?

- A. Store the logs in Amazon S3. Use Amazon Athena for analysis. **Most Voted**
- B. Store the logs in Amazon RDS. Use a database client for analysis.
- C. Store the logs in Amazon OpenSearch Service. Use OpenSearch Service for analysis.
- D. Store the logs in an Amazon EMR cluster. Use a supported open-source framework for SQL-based analysis.

Suggested Answer: A

Question #: 644

An international company has a subdomain for each country that the company operates in. The subdomains are formatted as example.com, country1.example.com, and country2.example.com. The company's workloads are behind an Application Load Balancer. The company wants to encrypt the website data that is in transit.

Which combination of steps will meet these requirements? (Choose two.)

- A. Use the AWS Certificate Manager (ACM) console to request a public certificate for the apex top domain example.com and a wildcard certificate for *.example.com. **Most Voted**
- B. Use the AWS Certificate Manager (ACM) console to request a private certificate for the apex top domain example.com and a wildcard certificate for *.example.com.
- C. Use the AWS Certificate Manager (ACM) console to request a public and private certificate for the apex top domain example.com.
- D. Validate domain ownership by email address. Switch to DNS validation by adding the required DNS records to the DNS provider.
- E. Validate domain ownership for the domain by adding the required DNS records to the DNS provider. **Most Voted**

Suggested Answer: AE

Question #: 645

A company is required to use cryptographic keys in its on-premises key manager. The key manager is outside of the AWS Cloud because of regulatory and compliance requirements. The company wants to manage encryption and decryption by using cryptographic keys that are retained outside of the AWS Cloud and that support a variety of external key managers from different vendors.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS CloudHSM key store backed by a CloudHSM cluster.
- B. Use an AWS Key Management Service (AWS KMS) external key store backed by an external key manager. **Most Voted**
- C. Use the default AWS Key Management Service (AWS KMS) managed key store.
- D. Use a custom key store backed by an AWS CloudHSM cluster.

Suggested Answer: B

Question #: 646

A solutions architect needs to host a high performance computing (HPC) workload in the AWS Cloud. The workload will run on hundreds of Amazon EC2 instances and will require parallel access to a shared file system to enable distributed processing of large datasets. Datasets will be accessed across multiple instances simultaneously. The workload requires access latency within 1 ms. After processing has completed, engineers will need access to the dataset for manual postprocessing.

Which solution will meet these requirements?

- A. Use Amazon Elastic File System (Amazon EFS) as a shared file system. Access the dataset from Amazon EFS.
- B. Mount an Amazon S3 bucket to serve as the shared file system. Perform postprocessing directly from the S3 bucket.

- C. Use Amazon FSx for Lustre as a shared file system. Link the file system to an Amazon S3 bucket for postprocessing. **Most Voted**
- D. Configure AWS Resource Access Manager to share an Amazon S3 bucket so that it can be mounted to all instances for processing and postprocessing.

Suggested Answer: C

Question #: 647

A gaming company is building an application with Voice over IP capabilities. The application will serve traffic to users across the world. The application needs to be highly available with an automated failover across AWS Regions. The company wants to minimize the latency of users without relying on IP address caching on user devices.

What should a solutions architect do to meet these requirements?

- A. Use AWS Global Accelerator with health checks. **Most Voted**
- B. Use Amazon Route 53 with a geolocation routing policy.
- C. Create an Amazon CloudFront distribution that includes multiple origins.
- D. Create an Application Load Balancer that uses path-based routing.

Suggested Answer: A

Question #: 648

A weather forecasting company needs to process hundreds of gigabytes of data with sub-millisecond latency. The company has a high performance computing (HPC) environment in its data center and wants to expand its forecasting capabilities.

A solutions architect must identify a highly available cloud storage solution that can handle large amounts of sustained throughput. Files that are stored in the solution should be accessible to thousands of compute instances that will simultaneously access and process the entire dataset.

What should the solutions architect do to meet these requirements?

- A. Use Amazon FSx for Lustre scratch file systems.
- B. Use Amazon FSx for Lustre persistent file systems. **Most Voted**
- C. Use Amazon Elastic File System (Amazon EFS) with Bursting Throughput mode.
- D. Use Amazon Elastic File System (Amazon EFS) with Provisioned Throughput mode.

Suggested Answer: B

Question #: 649

An ecommerce company runs a PostgreSQL database on premises. The database stores data by using high IOPS Amazon Elastic Block Store (Amazon EBS) block storage. The daily peak I/O transactions per second do not exceed 15,000 IOPS. The company wants to migrate the database to Amazon RDS for PostgreSQL and provision disk IOPS performance independent of disk storage capacity.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure the General Purpose SSD (gp2) EBS volume storage type and provision 15,000 IOPS.
- B. Configure the Provisioned IOPS SSD (io1) EBS volume storage type and provision 15,000 IOPS.
- C. Configure the General Purpose SSD (gp3) EBS volume storage type and provision 15,000 IOPS. **Most Voted**
- D. Configure the EBS magnetic volume type to achieve maximum IOPS.

Suggested Answer: C

Question #: 650

A company wants to migrate its on-premises Microsoft SQL Server Enterprise edition database to AWS. The company's online application uses the database to process transactions. The data analysis team uses the same production database to run reports for analytical processing. The company wants to reduce operational overhead by moving to managed services wherever possible.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Migrate to Amazon RDS for Microsoft SQL Server. Use read replicas for reporting purposes **Most Voted**

- B. Migrate to Microsoft SQL Server on Amazon EC2. Use Always On read replicas for reporting purposes
- C. Migrate to Amazon DynamoDB. Use DynamoDB on-demand replicas for reporting purposes
- D. Migrate to Amazon Aurora MySQL. Use Aurora read replicas for reporting purposes

Suggested Answer: A

Question #: 651

A company stores a large volume of image files in an Amazon S3 bucket. The images need to be readily available for the first 180 days. The images are infrequently accessed for the next 180 days. After 360 days, the images need to be archived but must be available instantly upon request. After 5 years, only auditors can access the images. The auditors must be able to retrieve the images within 12 hours. The images cannot be lost during this process.

A developer will use S3 Standard storage for the first 180 days. The developer needs to configure an S3 Lifecycle rule.

Which solution will meet these requirements MOST cost-effectively?

- A. Transition the objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 180 days. S3 Glacier Instant Retrieval after 360 days, and S3 Glacier Deep Archive after 5 years.
- B. Transition the objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 180 days. S3 Glacier Flexible Retrieval after 360 days, and S3 Glacier Deep Archive after 5 years.
- C. Transition the objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 180 days, S3 Glacier Instant Retrieval after 360 days, and S3 Glacier Deep Archive after 5 years. **Most Voted**
- D. Transition the objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 180 days, S3 Glacier Flexible Retrieval after 360 days, and S3 Glacier Deep Archive after 5 years.

Suggested Answer: C

Question #: 652

A company has a large data workload that runs for 6 hours each day. The company cannot lose any data while the process is running. A solutions architect is designing an Amazon EMR cluster configuration to support this

critical data workload.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure a long-running cluster that runs the primary node and core nodes on On-Demand Instances and the task nodes on Spot Instances.
- B. Configure a transient cluster that runs the primary node and core nodes on On-Demand Instances and the task nodes on Spot Instances. **Most Voted**
- C. Configure a transient cluster that runs the primary node on an On-Demand Instance and the core nodes and task nodes on Spot Instances.
- D. Configure a long-running cluster that runs the primary node on an On-Demand Instance, the core nodes on Spot Instances, and the task nodes on Spot Instances.

Suggested Answer: B

Question #: 653

A company maintains an Amazon RDS database that maps users to cost centers. The company has accounts in an organization in AWS Organizations. The company needs a solution that will tag all resources that are created in a specific AWS account in the organization. The solution must tag each resource with the cost center ID of the user who created the resource.

Which solution will meet these requirements?

- A. Move the specific AWS account to a new organizational unit (OU) in Organizations from the management account. Create a service control policy (SCP) that requires all existing resources to have the correct cost center tag before the resources are created. Apply the SCP to the new OU.
- B. Create an AWS Lambda function to tag the resources after the Lambda function looks up the appropriate cost center from the RDS database. Configure an Amazon EventBridge rule that reacts to AWS CloudTrail events to invoke the Lambda function. **Most Voted**

- C. Create an AWS CloudFormation stack to deploy an AWS Lambda function. Configure the Lambda function to look up the appropriate cost center from the RDS database and to tag resources. Create an Amazon EventBridge scheduled rule to invoke the CloudFormation stack.
- D. Create an AWS Lambda function to tag the resources with a default value. Configure an Amazon EventBridge rule that reacts to AWS CloudTrail events to invoke the Lambda function when a resource is missing the cost center tag.

Suggested Answer: B

Question #: 654

A company recently migrated its web application to the AWS Cloud. The company uses an Amazon EC2 instance to run multiple processes to host the application. The processes include an Apache web server that serves static content. The Apache web server makes requests to a PHP application that uses a local Redis server for user sessions.

The company wants to redesign the architecture to be highly available and to use AWS managed solutions.

Which solution will meet these requirements?

- A. Use AWS Elastic Beanstalk to host the static content and the PHP application. Configure Elastic Beanstalk to deploy its EC2 instance into a public subnet. Assign a public IP address.
- B. Use AWS Lambda to host the static content and the PHP application. Use an Amazon API Gateway REST API to proxy requests to the Lambda function. Set the API Gateway CORS configuration to respond to the domain name. Configure Amazon ElastiCache for Redis to handle session information.
- C. Keep the backend code on the EC2 instance. Create an Amazon ElastiCache for Redis cluster that has Multi-AZ enabled. Configure the ElastiCache for Redis cluster in cluster mode. Copy the frontend resources to Amazon S3. Configure the backend code to reference the EC2 instance.
- D. Configure an Amazon CloudFront distribution with an Amazon S3 endpoint to an S3 bucket that is configured to host the static content. Configure an Application Load Balancer that targets an Amazon Elastic Container Service (Amazon ECS) service that runs AWS Fargate tasks for the PHP application. Configure the PHP application to use an Amazon ElastiCache for Redis cluster that runs in multiple Availability Zones.

Suggested Answer: D

Question #: 655

A company runs a web application on Amazon EC2 instances in an Auto Scaling group that has a target group. The company designed the application to work with session affinity (sticky sessions) for a better user experience.

The application must be available publicly over the internet as an endpoint. A WAF must be applied to the endpoint for additional security. Session affinity (sticky sessions) must be configured on the endpoint.

Which combination of steps will meet these requirements? (Choose two.)

- A. Create a public Network Load Balancer. Specify the application target group.
- B. Create a Gateway Load Balancer. Specify the application target group.
- C. Create a public Application Load Balancer. Specify the application target group.
- D. Create a second target group. Add Elastic IP addresses to the EC2 instances.
- E. Create a web ACL in AWS WAF. Associate the web ACL with the endpoint

Suggested Answer: CE

Question #: 656

A company runs a website that stores images of historical events. Website users need the ability to search and view images based on the year that the event in the image occurred. On average, users request each image only once or twice a year. The company wants a highly available solution to store and deliver the images to users.

Which solution will meet these requirements MOST cost-effectively?

- A. Store images in Amazon Elastic Block Store (Amazon EBS). Use a web server that runs on Amazon EC2.
- B. Store images in Amazon Elastic File System (Amazon EFS). Use a web server that runs on Amazon EC2.
- C. Store images in Amazon S3 Standard. Use S3 Standard to directly deliver images by using a static website.

- D. Store images in Amazon S3 Standard-Infrequent Access (S3 Standard-IA). Use S3 Standard-IA to directly deliver images by using a static website. **Most Voted**

Suggested Answer: D

Question #: 657

A company has multiple AWS accounts in an organization in AWS Organizations that different business units use. The company has multiple offices around the world. The company needs to update security group rules to allow new office CIDR ranges or to remove old CIDR ranges across the organization. The company wants to centralize the management of security group rules to minimize the administrative overhead that updating CIDR ranges requires.

Which solution will meet these requirements MOST cost-effectively?

- A. Create VPC security groups in the organization's management account. Update the security groups when a CIDR range update is necessary.
- B. Create a VPC customer managed prefix list that contains the list of CIDRs. Use AWS Resource Access Manager (AWS RAM) to share the prefix list across the organization. Use the prefix list in the security groups across the organization. **Most Voted**
- C. Create an AWS managed prefix list. Use an AWS Security Hub policy to enforce the security group update across the organization. Use an AWS Lambda function to update the prefix list automatically when the CIDR ranges change.
- D. Create security groups in a central administrative AWS account. Create an AWS Firewall Manager common security group policy for the whole organization. Select the previously created security groups as primary groups in the policy.

Suggested Answer: B

Question #: 658

A company uses an on-premises network-attached storage (NAS) system to provide file shares to its high performance computing (HPC) workloads. The company wants to migrate its latency-sensitive HPC workloads and its storage to the AWS Cloud. The company must be able to provide NFS and SMB multi-protocol access

from the file system.

Which solution will meet these requirements with the LEAST latency? (Choose two.)

- A. Deploy compute optimized EC2 instances into a cluster placement group. **Most VotedMost Voted**
- B. Deploy compute optimized EC2 instances into a partition placement group.
- C. Attach the EC2 instances to an Amazon FSx for Lustre file system. **Most Voted**
- D. Attach the EC2 instances to an Amazon FSx for OpenZFS file system.
- E. Attach the EC2 instances to an Amazon FSx for NetApp ONTAP file system. **Most Voted**

Suggested Answer: AE

Question #: 659

A company is relocating its data center and wants to securely transfer 50 TB of data to AWS within 2 weeks. The existing data center has a Site-to-Site VPN connection to AWS that is 90% utilized.

Which AWS service should a solutions architect use to meet these requirements?

- A. AWS DataSync with a VPC endpoint
- B. AWS Direct Connect
- C. AWS Snowball Edge Storage Optimized **Most Voted**
- D. AWS Storage Gateway

Suggested Answer: C

Question #: 660

A company hosts an application on Amazon EC2 On-Demand Instances in an Auto Scaling group. Application peak hours occur at the same time each day. Application users report slow application performance at the start of peak hours. The application performs normally 2-3 hours after peak hours begin. The company wants to ensure that the application works properly at the start of peak hours.

Which solution will meet these requirements?

- A. Configure an Application Load Balancer to distribute traffic properly to the instances.
- B. Configure a dynamic scaling policy for the Auto Scaling group to launch new instances based on memory utilization.
- C. Configure a dynamic scaling policy for the Auto Scaling group to launch new instances based on CPU utilization.
- D. Configure a scheduled scaling policy for the Auto Scaling group to launch new instances before peak hours. **Most Voted**

Suggested Answer: D

Question #: 661

A company runs applications on AWS that connect to the company's Amazon RDS database. The applications scale on weekends and at peak times of the year. The company wants to scale the database more effectively for its applications that connect to the database.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon DynamoDB with connection pooling with a target group configuration for the database. Change the applications to use the DynamoDB endpoint.
- B. Use Amazon RDS Proxy with a target group for the database. Change the applications to use the RDS Proxy endpoint. **Most Voted**
- C. Use a custom proxy that runs on Amazon EC2 as an intermediary to the database. Change the applications to use the custom proxy endpoint.
- D. Use an AWS Lambda function to provide connection pooling with a target group configuration for the database. Change the applications to use the Lambda function.

Suggested Answer: B

Question #: 662

A company uses AWS Cost Explorer to monitor its AWS costs. The company notices that Amazon Elastic Block Store (Amazon EBS) storage and snapshot costs increase every month. However, the company does not purchase additional EBS storage every month. The company wants to optimize monthly costs for its current storage usage.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use logs in Amazon CloudWatch Logs to monitor the storage utilization of Amazon EBS. Use Amazon EBS Elastic Volumes to reduce the size of the EBS volumes.
- B. Use a custom script to monitor space usage. Use Amazon EBS Elastic Volumes to reduce the size of the EBS volumes.
- C. Delete all expired and unused snapshots to reduce snapshot costs.
- D. Delete all nonessential snapshots. Use Amazon Data Lifecycle Manager to create and manage the snapshots according to the company's snapshot policy requirements. **Most Voted**

Suggested Answer: D

Question #: 663

A company is developing a new application on AWS. The application consists of an Amazon Elastic Container Service (Amazon ECS) cluster, an Amazon S3 bucket that contains assets for the application, and an Amazon RDS for MySQL database that contains the dataset for the application. The dataset contains sensitive information. The company wants to ensure that only the ECS cluster can access the data in the RDS for MySQL database and the data in the S3 bucket.

Which solution will meet these requirements?

- A. Create a new AWS Key Management Service (AWS KMS) customer managed key to encrypt both the S3 bucket and the RDS for MySQL database. Ensure that the KMS key policy includes encrypt and decrypt permissions for the ECS task execution role.
- B. Create an AWS Key Management Service (AWS KMS) AWS managed key to encrypt both the S3 bucket and the RDS for MySQL database. Ensure that the S3 bucket policy specifies the ECS task execution role as a user.

- C. Create an S3 bucket policy that restricts bucket access to the ECS task execution role. Create a VPC endpoint for Amazon RDS for MySQL. Update the RDS for MySQL security group to allow access from only the subnets that the ECS cluster will generate tasks in.
- D. Create a VPC endpoint for Amazon RDS for MySQL. Update the RDS for MySQL security group to allow access from only the subnets that the ECS cluster will generate tasks in. Create a VPC endpoint for Amazon S3. Update the S3 bucket policy to allow access from only the S3 VPC endpoint. **Most Voted**

Suggested Answer: D

Question #: 664

A company has a web application that runs on premises. The application experiences latency issues during peak hours. The latency issues occur twice each month. At the start of a latency issue, the application's CPU utilization immediately increases to 10 times its normal amount.

The company wants to migrate the application to AWS to improve latency. The company also wants to scale the application automatically when application demand increases. The company will use AWS Elastic Beanstalk for application deployment.

Which solution will meet these requirements?

- A. Configure an Elastic Beanstalk environment to use burstable performance instances in unlimited mode. Configure the environment to scale based on requests.
- B. Configure an Elastic Beanstalk environment to use compute optimized instances. Configure the environment to scale based on requests.
- C. Configure an Elastic Beanstalk environment to use compute optimized instances. Configure the environment to scale on a schedule.
- D. Configure an Elastic Beanstalk environment to use burstable performance instances in unlimited mode. Configure the environment to scale on predictive metrics. **Most Voted**

Suggested Answer: D

Question #: 665

A company has customers located across the world. The company wants to use automation to secure its systems and network infrastructure. The company's security team must be able to track and audit all incremental changes to the infrastructure.

Which solution will meet these requirements?

- A. Use AWS Organizations to set up the infrastructure. Use AWS Config to track changes.
- B. Use AWS CloudFormation to set up the infrastructure. Use AWS Config to track changes. **Most Voted**
- C. Use AWS Organizations to set up the infrastructure. Use AWS Service Catalog to track changes.
- D. Use AWS CloudFormation to set up the infrastructure. Use AWS Service Catalog to track changes.

Suggested Answer: B

Question #: 666

A startup company is hosting a website for its customers on an Amazon EC2 instance. The website consists of a stateless Python application and a MySQL database. The website serves only a small amount of traffic. The company is concerned about the reliability of the instance and needs to migrate to a highly available architecture. The company cannot modify the application code.

Which combination of actions should a solutions architect take to achieve high availability for the website? (Choose two.)

- A. Provision an internet gateway in each Availability Zone in use.
- B. Migrate the database to an Amazon RDS for MySQL Multi-AZ DB instance.
- C. Migrate the database to Amazon DynamoDB, and enable DynamoDB auto scaling.
- D. Use AWS DataSync to synchronize the database data across multiple EC2 instances.
- E. Create an Application Load Balancer to distribute traffic to an Auto Scaling group of EC2 instances that are distributed across two Availability Zones.

Suggested Answer: BE

Question #: 667

A company is moving its data and applications to AWS during a multiyear migration project. The company wants to securely access data on Amazon S3 from the company's AWS Region and from the company's on-premises location. The data must not traverse the internet. The company has established an AWS Direct Connect connection between its Region and its on-premises location.

Which solution will meet these requirements?

- A. Create gateway endpoints for Amazon S3. Use the gateway endpoints to securely access the data from the Region and the on-premises location.
- B. Create a gateway in AWS Transit Gateway to access Amazon S3 securely from the Region and the on-premises location.
- C. Create interface endpoints for Amazon S3. Use the interface endpoints to securely access the data from the Region and the on-premises location. **Most Voted**
- D. Use an AWS Key Management Service (AWS KMS) key to access the data securely from the Region and the on-premises location.

Suggested Answer: C

Question #: 668

A company created a new organization in AWS Organizations. The organization has multiple accounts for the company's development teams. The development team members use AWS IAM Identity Center (AWS Single Sign-On) to access the accounts. For each of the company's applications, the development teams must use a predefined application name to tag resources that are created.

A solutions architect needs to design a solution that gives the development team the ability to create resources only if the application name tag has an approved value.

Which solution will meet these requirements?

- A. Create an IAM group that has a conditional Allow policy that requires the application name tag to be specified for resources to be created.
- B. Create a cross-account role that has a Deny policy for any resource that has the application name tag.

- C. Create a resource group in AWS Resource Groups to validate that the tags are applied to all resources in all accounts.
- D. Create a tag policy in Organizations that has a list of allowed application names. **Most Voted**

Suggested Answer: D

Question #: 669

A company runs its databases on Amazon RDS for PostgreSQL. The company wants a secure solution to manage the master user password by rotating the password every 30 days.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon EventBridge to schedule a custom AWS Lambda function to rotate the password every 30 days.
- B. Use the modify-db-instance command in the AWS CLI to change the password.
- C. Integrate AWS Secrets Manager with Amazon RDS for PostgreSQL to automate password rotation. **Most Voted**
- D. Integrate AWS Systems Manager Parameter Store with Amazon RDS for PostgreSQL to automate password rotation.

Suggested Answer: C

Question #: 670

A company performs tests on an application that uses an Amazon DynamoDB table. The tests run for 4 hours once a week. The company knows how many read and write operations the application performs to the table each second during the tests. The company does not currently use DynamoDB for any other use case. A solutions architect needs to optimize the costs for the table.

Which solution will meet these requirements?

- A. Choose on-demand mode. Update the read and write capacity units appropriately.
- B. Choose provisioned mode. Update the read and write capacity units appropriately.

- C. Purchase DynamoDB reserved capacity for a 1-year term.
- D. Purchase DynamoDB reserved capacity for a 3-year term.

Suggested Answer: A

Question #: 671

A company runs its applications on Amazon EC2 instances. The company performs periodic financial assessments of its AWS costs. The company recently identified unusual spending.

The company needs a solution to prevent unusual spending. The solution must monitor costs and notify responsible stakeholders in the event of unusual spending.

Which solution will meet these requirements?

- A. Use an AWS Budgets template to create a zero spend budget.
- B. Create an AWS Cost Anomaly Detection monitor in the AWS Billing and Cost Management console. **Most Voted**
- C. Create AWS Pricing Calculator estimates for the current running workload pricing details.
- D. Use Amazon CloudWatch to monitor costs and to identify unusual spending.

Suggested Answer: B

Question #: 672

A marketing company receives a large amount of new clickstream data in Amazon S3 from a marketing campaign. The company needs to analyze the clickstream data in Amazon S3 quickly. Then the company needs to determine whether to process the data further in the data pipeline.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create external tables in a Spark catalog. Configure jobs in AWS Glue to query the data.
- B. Configure an AWS Glue crawler to crawl the data. Configure Amazon Athena to query the data. **Most Voted**
- C. Create external tables in a Hive metastore. Configure Spark jobs in Amazon EMR to query the data.

- D. Configure an AWS Glue crawler to crawl the data. Configure Amazon Kinesis Data Analytics to use SQL to query the data.

Suggested Answer: B

Question #: 673

A company runs an SMB file server in its data center. The file server stores large files that the company frequently accesses for up to 7 days after the file creation date. After 7 days, the company needs to be able to access the files with a maximum retrieval time of 24 hours.

Which solution will meet these requirements?

- A. Use AWS DataSync to copy data that is older than 7 days from the SMB file server to AWS.
- B. Create an Amazon S3 File Gateway to increase the company's storage space. Create an S3 Lifecycle policy to transition the data to S3 Glacier Deep Archive after 7 days. **Most Voted**
- C. Create an Amazon FSx File Gateway to increase the company's storage space. Create an Amazon S3 Lifecycle policy to transition the data after 7 days.
- D. Configure access to Amazon S3 for each user. Create an S3 Lifecycle policy to transition the data to S3 Glacier Flexible Retrieval after 7 days.

Suggested Answer: B

Question #: 674

A company runs a web application on Amazon EC2 instances in an Auto Scaling group. The application uses a database that runs on an Amazon RDS for PostgreSQL DB instance. The application performs slowly when traffic increases. The database experiences a heavy read load during periods of high traffic.

Which actions should a solutions architect take to resolve these performance issues? (Choose two.)

- A. Turn on auto scaling for the DB instance.

- B. Create a read replica for the DB instance. Configure the application to send read traffic to the read replica. **Most Voted**
- C. Convert the DB instance to a Multi-AZ DB instance deployment. Configure the application to send read traffic to the standby DB instance.
- D. Create an Amazon ElastiCache cluster. Configure the application to cache query results in the ElastiCache cluster. **Most Voted**
- E. Configure the Auto Scaling group subnets to ensure that the EC2 instances are provisioned in the same Availability Zone as the DB instance.

Suggested Answer: BD

Question #: 675

A company uses Amazon EC2 instances and Amazon Elastic Block Store (Amazon EBS) volumes to run an application. The company creates one snapshot of each EBS volume every day to meet compliance requirements. The company wants to implement an architecture that prevents the accidental deletion of EBS volume snapshots. The solution must not change the administrative rights of the storage administrator user.

Which solution will meet these requirements with the LEAST administrative effort?

- A. Create an IAM role that has permission to delete snapshots. Attach the role to a new EC2 instance. Use the AWS CLI from the new EC2 instance to delete snapshots.
- B. Create an IAM policy that denies snapshot deletion. Attach the policy to the storage administrator user.
- C. Add tags to the snapshots. Create retention rules in Recycle Bin for EBS snapshots that have the tags.
- D. Lock the EBS snapshots to prevent deletion. **Most Voted**

Suggested Answer: D

Question #: 676

A company's application uses Network Load Balancers, Auto Scaling groups, Amazon EC2 instances, and databases that are deployed in an Amazon VPC. The company wants to capture information about traffic to and from the network interfaces in near real time in its Amazon VPC. The company wants to send the information to Amazon OpenSearch Service for analysis.

Which solution will meet these requirements?

- A. Create a log group in Amazon CloudWatch Logs. Configure VPC Flow Logs to send the log data to the log group. Use Amazon Kinesis Data Streams to stream the logs from the log group to OpenSearch Service.
- B. Create a log group in Amazon CloudWatch Logs. Configure VPC Flow Logs to send the log data to the log group. Use Amazon Kinesis Data Firehose to stream the logs from the log group to OpenSearch Service. **Most Voted**
- C. Create a trail in AWS CloudTrail. Configure VPC Flow Logs to send the log data to the trail. Use Amazon Kinesis Data Streams to stream the logs from the trail to OpenSearch Service.
- D. Create a trail in AWS CloudTrail. Configure VPC Flow Logs to send the log data to the trail. Use Amazon Kinesis Data Firehose to stream the logs from the trail to OpenSearch Service.

Suggested Answer: B

Question #: 677

A company is developing an application that will run on a production Amazon Elastic Kubernetes Service (Amazon EKS) cluster. The EKS cluster has managed node groups that are provisioned with On-Demand Instances.

The company needs a dedicated EKS cluster for development work. The company will use the development cluster infrequently to test the resiliency of the application. The EKS cluster must manage all the nodes.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a managed node group that contains only Spot Instances.
- B. Create two managed node groups. Provision one node group with On-Demand Instances. Provision the second node group with Spot Instances.
- C. Create an Auto Scaling group that has a launch configuration that uses Spot Instances. Configure the user data to add the nodes to the EKS cluster.
- D. Create a managed node group that contains only On-Demand Instances.

Suggested Answer: A

Question #: 678

A company stores sensitive data in Amazon S3. A solutions architect needs to create an encryption solution. The company needs to fully control the ability of users to create, rotate, and disable encryption keys with minimal effort for any data that must be encrypted.

Which solution will meet these requirements?

- A. Use default server-side encryption with Amazon S3 managed encryption keys (SSE-S3) to store the sensitive data.
- B. Create a customer managed key by using AWS Key Management Service (AWS KMS). Use the new key to encrypt the S3 objects by using server-side encryption with AWS KMS keys (SSE-KMS). **Most Voted**
- C. Create an AWS managed key by using AWS Key Management Service (AWS KMS). Use the new key to encrypt the S3 objects by using server-side encryption with AWS KMS keys (SSE-KMS).
- D. Download S3 objects to an Amazon EC2 instance. Encrypt the objects by using customer managed keys. Upload the encrypted objects back into Amazon S3.

Suggested Answer: B

Question #: 679

A company wants to back up its on-premises virtual machines (VMs) to AWS. The company's backup solution exports on-premises backups to an Amazon S3 bucket as objects. The S3 backups must be retained for 30 days and must be automatically deleted after 30 days.

Which combination of steps will meet these requirements? (Choose three.)

- A. Create an S3 bucket that has S3 Object Lock enabled. **Most Voted**
- B. Create an S3 bucket that has object versioning enabled.
- C. Configure a default retention period of 30 days for the objects. **Most Voted**
- D. Configure an S3 Lifecycle policy to protect the objects for 30 days.

- E. Configure an S3 Lifecycle policy to expire the objects after 30 days. **Most Voted**
- F. Configure the backup solution to tag the objects with a 30-day retention period

Suggested Answer: ACE Question #: 680

A solutions architect needs to copy files from an Amazon S3 bucket to an Amazon Elastic File System (Amazon EFS) file system and another S3 bucket. The files must be copied continuously. New files are added to the original S3 bucket consistently. The copied files should be overwritten only if the source file changes.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS DataSync location for both the destination S3 bucket and the EFS file system. Create a task for the destination S3 bucket and the EFS file system. Set the transfer mode to transfer only data that has changed.
- B. Create an AWS Lambda function. Mount the file system to the function. Set up an S3 event notification to invoke the function when files are created and changed in Amazon S3. Configure the function to copy files to the file system and the destination S3 bucket.
- C. Create an AWS DataSync location for both the destination S3 bucket and the EFS file system. Create a task for the destination S3 bucket and the EFS file system. Set the transfer mode to transfer all data.
- D. Launch an Amazon EC2 instance in the same VPC as the file system. Mount the file system. Create a script to routinely synchronize all objects that changed in the origin S3 bucket to the destination S3 bucket and the mounted file system.

Suggested Answer: A

Question #: 681

A company uses Amazon EC2 instances and stores data on Amazon Elastic Block Store (Amazon EBS) volumes. The company must ensure that all data is encrypted at rest by using AWS Key Management Service (AWS KMS). The company must be able to control rotation of the encryption keys.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a customer managed key. Use the key to encrypt the EBS volumes. **Most Voted**
- B. Use an AWS managed key to encrypt the EBS volumes. Use the key to configure automatic key rotation.
- C. Create an external KMS key with imported key material. Use the key to encrypt the EBS volumes.
- D. Use an AWS owned key to encrypt the EBS volumes.

Suggested Answer: A

Question #: 682

A company needs a solution to enforce data encryption at rest on Amazon EC2 instances. The solution must automatically identify noncompliant resources and enforce compliance policies on findings.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Use an IAM policy that allows users to create only encrypted Amazon Elastic Block Store (Amazon EBS) volumes. Use AWS Config and AWS Systems Manager to automate the detection and remediation of unencrypted EBS volumes. **Most Voted**
- B. Use AWS Key Management Service (AWS KMS) to manage access to encrypted Amazon Elastic Block Store (Amazon EBS) volumes. Use AWS Lambda and Amazon EventBridge to automate the detection and remediation of unencrypted EBS volumes.
- C. Use Amazon Macie to detect unencrypted Amazon Elastic Block Store (Amazon EBS) volumes. Use AWS Systems Manager Automation rules to automatically encrypt existing and new EBS volumes.
- D. Use Amazon Inspector to detect unencrypted Amazon Elastic Block Store (Amazon EBS) volumes. Use AWS Systems Manager Automation rules to automatically encrypt existing and new EBS volumes.

Suggested Answer: A

Question #: 684

A company wants to migrate its web applications from on premises to AWS. The company is located close to the eu-central-1 Region. Because of regulations, the company cannot launch some of its applications in eu-central-1. The company wants to achieve single-digit millisecond latency.

Which solution will meet these requirements?

- A. Deploy the applications in eu-central-1. Extend the company's VPC from eu-central-1 to an edge location in Amazon CloudFront.
- B. Deploy the applications in AWS Local Zones by extending the company's VPC from eu-central-1 to the chosen Local Zone. **Most Voted**
- C. Deploy the applications in eu-central-1. Extend the company's VPC from eu-central-1 to the regional edge caches in Amazon CloudFront.
- D. Deploy the applications in AWS Wavelength Zones by extending the company's VPC from eu-central-1 to the chosen Wavelength Zone.

Suggested Answer: B

A company is deploying a critical application by using Amazon RDS for MySQL. The application must be highly available and must recover automatically. The company needs to support interactive users (transactional queries) and batch reporting (analytical queries) with no more than a 4-hour lag. The analytical queries must not affect the performance of the transactional queries.

Which solution will meet these requirements?

A. Configure Amazon RDS for MySQL in a Multi-AZ DB instance deployment with one standby instance. Point the transactional queries to the primary DB

instance. Point the analytical queries to a secondary DB instance that runs in a different Availability Zone.

B. Configure Amazon RDS for MySQL in a Multi-AZ DB cluster deployment with two standby instances. Point the transactional queries to the primary DB instance. Point the analytical queries to the reader endpoint.

C. Configure Amazon RDS for MySQL to use multiple read replicas across multiple Availability Zones. Point the transactional queries to the primary DB instance. Point the analytical queries to one of the replicas in a different Availability Zone.

D. Configure Amazon RDS for MySQL as the primary database for the transactional queries with automated backups enabled. Configure automated backups. Each night, create a read-only database from the most recent snapshot to support the analytical queries. Terminate the previously created database.

Suggested Answer: B

An ecommerce company wants to collect user clickstream data from the company's website for real-time analysis. The website experiences fluctuating traffic patterns throughout the day. The company needs a scalable solution that can adapt to varying levels of traffic.

Which solution will meet these requirements?

- A. Use a data stream in Amazon Kinesis Data Streams in on-demand mode to capture the clickstream data. Use AWS Lambda to process the data in real time
- B. Use Amazon Kinesis Data Firehose to capture the clickstream data. Use AWS Glue to process the data in real time
- C. Use Amazon Kinesis Video Streams to capture the clickstream data. Use AWS Glue to process the data in real time.
- D. Use Amazon Managed Service for Apache Flink (previously known as Amazon Kinesis Data Analytics) to capture the clickstream data. Use AWS Lambda to process the data in real time.

Suggested Answer: B

A company needs to design a solution that will give clients the ability to send data to the company securely. The data must be collected and stored in an Amazon S3 bucket. Incoming files must be renamed based on the client that sent the files. The solution must be scalable and must use serverless technology where possible

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Create a presigned URL of the S3 bucket. Share the URL with each client. Use S3 Event Notifications to invoke an AWS Lambda function that renames the files when the files are delivered to the S3 bucket.
- B. Set up AWS Transfer Family SFTP endpoints. Create credentials for each client. Use Transfer Family managed workflows to rename the incoming client files and to store the files in the S3 bucket.

C. Create an IAM user for each client. Allow only S3 bucket access in the IAM policy. Share the IAM user credential with each client. Use S3 Event Notifications to invoke an AWS Lambda function that renames the incoming client files.

D. Create an IAM role for each client. Allow only S3 bucket access in the IAM policy. Share the IAM role credential with each client. Use S3 Event Notifications to send messages to an Amazon Simple Queue Service (Amazon SQS) queue that initiates a client file rename job. Run an hourly AWS Batch job on the SQS queue to rename the files

Suggested Answer: B

A company has multiple Amazon RDS DB instances that run in a development AWS account. All the instances have tags to identify them as development resources. The company needs the development DB instances to run on a schedule only during business hours.

Which solution will meet these requirements with the LEAST operational overhead?

A. Create an Amazon CloudWatch alarm to identify RDS instances that need to be stopped. Create an AWS Lambda function to start and stop the RDS instances.

B. Create an AWS Trusted Advisor report to identify RDS instances to be started and stopped. Create an AWS Lambda function to start and stop the RDS instances.

C. Create AWS Systems Manager State Manager associations to start and stop the RDS instances.

D. Create an Amazon EventBridge rule that invokes AWS Lambda functions to start and stop the RDS instances.

Suggested Answer: C

A company is migrating a document management application to AWS. The application runs on Linux servers. The company will migrate the application to Amazon EC2 instances in an Auto Scaling group. The company stores 7 TiB of documents in a shared storage file system. An external relational database tracks the documents.

Documents are stored once and can be retrieved multiple times for reference at any time. The company cannot modify the application during the migration. The storage solution must be highly available and must support scaling over time.

Which solution will meet these requirements MOST cost-effectively?

- A. Deploy an EC2 instance with enhanced networking as a shared NFS storage system. Export the NFS share. Mount the NFS share on the EC2 instances in the Auto Scaling group.
- B. Create an Amazon S3 bucket that uses the S3 Standard-Infrequent Access (S3 Standard-IA) storage class. Mount the S3 bucket on the EC2 instances in the Auto Scaling group.
- C. Deploy an SFTP server endpoint by using AWS Transfer for SFTP and an Amazon S3 bucket. Configure the EC2 instances in the Auto Scaling group to connect to the SFTP server
- D. Create an Amazon Elastic File System (Amazon EFS) file system with mount points in multiple Availability Zones. Use the EFS Standard-Infrequent Access (Standard-IA) storage class. Mount the NFS share on the EC2 instances in the Auto Scaling group.

Suggested Answer: D

A company has released a new version of its production application. The company's workload uses Amazon EC2, AWS Lambda, AWS Fargate, and Amazon SageMaker.

A Flag for Review Color Scheme

The company wants to cost optimize the workload now that usage is at a steady state. The company wants to cover the most services with the fewest savings plans Which combination of savings plans will meet these requirements? (Select TWO.)

- A. Purchase an EC2 Instance Savings Plan for Amazon EC2 and SageMaker.
- B. Purchase a Compute Savings Plan for Amazon EC2, Lambda, and SageMaker.
- C. Purchase a SageMaker Savings Plan.
- D. Purchase a Compute Savings Plan for Lambda, Fargate, and Amazon EC2.

E Purchase an EC2 Instance Savings Plan for Amazon EC2 and Fargate.

Suggested Answer: BD

Question #: 683

A company is migrating its multi-tier on-premises application to AWS. The application consists of a single-node MySQL database and a multi-node web tier. The company must minimize changes to the application during the migration. The company wants to improve application resiliency after the migration.

Which combination of steps will meet these requirements? (Choose two.)

- A. Migrate the web tier to Amazon EC2 instances in an Auto Scaling group behind an Application Load Balancer. **Most Voted**
- B. Migrate the database to Amazon EC2 instances in an Auto Scaling group behind a Network Load Balancer.
- C. Migrate the database to an Amazon RDS Multi-AZ deployment. **Most Voted**
- D. Migrate the web tier to an AWS Lambda function.
- E. Migrate the database to an Amazon DynamoDB table.

Suggested Answer: AC

Question #: 684

A company wants to migrate its web applications from on premises to AWS. The company is located close to the eu-central-1 Region. Because of regulations, the company cannot launch some of its applications in eu-central-1. The company wants to achieve single-digit millisecond latency.

Which solution will meet these requirements?

- A. Deploy the applications in eu-central-1. Extend the company's VPC from eu-central-1 to an edge location in Amazon CloudFront.
- B. Deploy the applications in AWS Local Zones by extending the company's VPC from eu-central-1 to the chosen Local Zone. **Most Voted**
- C. Deploy the applications in eu-central-1. Extend the company's VPC from eu-central-1 to the regional edge caches in Amazon CloudFront.
- D. Deploy the applications in AWS Wavelength Zones by extending the company's VPC from eu-central-1 to the chosen Wavelength Zone.

Suggested Answer: B

Question #: 684

A company wants to migrate its web applications from on premises to AWS. The company is located close to the eu-central-1 Region. Because of regulations, the company cannot launch some of its applications in eu-central-1. The company wants to achieve single-digit millisecond latency.

Which solution will meet these requirements?

- A. Deploy the applications in eu-central-1. Extend the company's VPC from eu-central-1 to an edge location in Amazon CloudFront.
- B. Deploy the applications in AWS Local Zones by extending the company's VPC from eu-central-1 to the chosen Local Zone. **Most Voted**
- C. Deploy the applications in eu-central-1. Extend the company's VPC from eu-central-1 to the regional edge caches in Amazon CloudFront.

- D. Deploy the applications in AWS Wavelength Zones by extending the company's VPC from eu-central-1 to the chosen Wavelength Zone.

Suggested Answer: B

Question #: 685

A company's ecommerce website has unpredictable traffic and uses AWS Lambda functions to directly access a private Amazon RDS for PostgreSQL DB instance. The company wants to maintain predictable database performance and ensure that the Lambda invocations do not overload the database with too many connections.

What should a solutions architect do to meet these requirements?

- A. Point the client driver at an RDS custom endpoint. Deploy the Lambda functions inside a VPC.
- B. Point the client driver at an RDS proxy endpoint. Deploy the Lambda functions inside a VPC. **Most Voted**
- C. Point the client driver at an RDS custom endpoint. Deploy the Lambda functions outside a VPC.
- D. Point the client driver at an RDS proxy endpoint. Deploy the Lambda functions outside a VPC.

Suggested Answer: B

Question #: 686

A company is creating an application. The company stores data from tests of the application in multiple on-premises locations.

The company needs to connect the on-premises locations to VPCs in an AWS Region in the AWS Cloud. The number of accounts and VPCs will increase during the next year. The network architecture must simplify the administration of new connections and must provide the ability to scale.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Create a peering connection between the VPCs. Create a VPN connection between the VPCs and the on-premises locations.
- B. Launch an Amazon EC2 instance. On the instance, include VPN software that uses a VPN connection to connect all VPCs and on-premises locations.
- C. Create a transit gateway. Create VPC attachments for the VPC connections. Create VPN attachments for the on-premises connections. **Most Voted**
- D. Create an AWS Direct Connect connection between the on-premises locations and a central VPC. Connect the central VPC to other VPCs by using peering connections.

Suggested Answer: C

Question #: 687

A company that uses AWS needs a solution to predict the resources needed for manufacturing processes each month. The solution must use historical values that are currently stored in an Amazon S3 bucket. The company has no machine learning (ML) experience and wants to use a managed service for the training and predictions.

Which combination of steps will meet these requirements? (Choose two.)

- A. Deploy an Amazon SageMaker model. Create a SageMaker endpoint for inference.
- B. Use Amazon SageMaker to train a model by using the historical data in the S3 bucket.

- C. Configure an AWS Lambda function with a function URL that uses Amazon SageMaker endpoints to create predictions based on the inputs.
- D. Configure an AWS Lambda function with a function URL that uses an Amazon Forecast predictor to create a prediction based on the inputs. **Most Voted**
- E. Train an Amazon Forecast predictor by using the historical data in the S3 bucket. **Most Voted**

Suggested Answer: DE

Question #: 688

A company manages AWS accounts in AWS Organizations. AWS IAM Identity Center (AWS Single Sign-On) and AWS Control Tower are configured for the accounts. The company wants to manage multiple user permissions across all the accounts.

The permissions will be used by multiple IAM users and must be split between the developer and administrator teams. Each team requires different permissions. The company wants a solution that includes new users that are hired on both teams.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create individual users in IAM Identity Center for each account. Create separate developer and administrator groups in IAM Identity Center. Assign the users to the appropriate groups. Create a custom IAM policy for each group to set fine-grained permissions.
- B. Create individual users in IAM Identity Center for each account. Create separate developer and administrator groups in IAM Identity Center. Assign the users to the appropriate groups. Attach AWS managed IAM policies to each user as needed for fine-grained permissions.
- C. Create individual users in IAM Identity Center. Create new developer and administrator groups in IAM Identity Center. Create new permission sets that include the appropriate IAM policies for each group. Assign the new

groups to the appropriate accounts. Assign the new permission sets to the new groups. When new users are hired, add them to the appropriate group. **Most Voted**

- D. Create individual users in IAM Identity Center. Create new permission sets that include the appropriate IAM policies for each user. Assign the users to the appropriate accounts. Grant additional IAM permissions to the users from within specific accounts. When new users are hired, add them to IAM Identity Center and assign them to the accounts.

Suggested Answer: C

Question #: 689

A company wants to standardize its Amazon Elastic Block Store (Amazon EBS) volume encryption strategy. The company also wants to minimize the cost and configuration effort required to operate the volume encryption check.

Which solution will meet these requirements?

- A. Write API calls to describe the EBS volumes and to confirm the EBS volumes are encrypted. Use Amazon EventBridge to schedule an AWS Lambda function to run the API calls.
- B. Write API calls to describe the EBS volumes and to confirm the EBS volumes are encrypted. Run the API calls on an AWS Fargate task.
- C. Create an AWS Identity and Access Management (IAM) policy that requires the use of tags on EBS volumes. Use AWS Cost Explorer to display resources that are not properly tagged. Encrypt the untagged resources manually.
- D. Create an AWS Config rule for Amazon EBS to evaluate if a volume is encrypted and to flag the volume if it is not encrypted. **Most Voted**

Suggested Answer: D

Question #: 690

A company regularly uploads GB-sized files to Amazon S3. After the company uploads the files, the company uses a fleet of Amazon EC2 Spot Instances to transcode the file format. The company needs to scale throughput when the company uploads data from the on-premises data center to Amazon S3 and when the company downloads data from Amazon S3 to the EC2 instances.

Which solutions will meet these requirements? (Choose two.)

- A. Use the S3 bucket access point instead of accessing the S3 bucket directly.
- B. Upload the files into multiple S3 buckets.
- C. Use S3 multipart uploads. **Most Voted**
- D. Fetch multiple byte-ranges of an object in parallel. **Most Voted**
- E. Add a random prefix to each object when uploading the files.

Suggested Answer: CD

Question #: 691

A solutions architect is designing a shared storage solution for a web application that is deployed across multiple Availability Zones. The web application runs on Amazon EC2 instances that are in an Auto Scaling group. The company plans to make frequent changes to the content. The solution must have strong consistency in returning the new content as soon as the changes occur.

Which solutions meet these requirements? (Choose two.)

- A. Use AWS Storage Gateway Volume Gateway Internet Small Computer Systems Interface (iSCSI) block storage that is mounted to the individual EC2 instances.
- B. Create an Amazon Elastic File System (Amazon EFS) file system. Mount the EFS file system on the individual EC2 instances. **Most Voted**
- C. Create a shared Amazon Elastic Block Store (Amazon EBS) volume. Mount the EBS volume on the individual EC2 instances.
- D. Use AWS DataSync to perform continuous synchronization of data between EC2 hosts in the Auto Scaling group.
- E. Create an Amazon S3 bucket to store the web content. Set the metadata for the Cache-Control header to no-cache. Use Amazon CloudFront to deliver the content. **Most Voted**

Suggested Answer: BE

Question #: 692

A company is deploying an application in three AWS Regions using an Application Load Balancer. Amazon Route 53 will be used to distribute traffic between these Regions.

Which Route 53 configuration should a solutions architect use to provide the MOST high-performing experience?

- A. Create an A record with a latency policy. **Most Voted**
- B. Create an A record with a geolocation policy.
- C. Create a CNAME record with a failover policy.
- D. Create a CNAME record with a geoproximity policy.

Suggested Answer: A

Question #: 693

A company has a web application that includes an embedded NoSQL database. The application runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The instances run in an Amazon EC2 Auto Scaling group in a single Availability Zone.

A recent increase in traffic requires the application to be highly available and for the database to be eventually consistent.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Replace the ALB with a Network Load Balancer. Maintain the embedded NoSQL database with its replication service on the EC2 instances.
- B. Replace the ALB with a Network Load Balancer. Migrate the embedded NoSQL database to Amazon DynamoDB by using AWS Database Migration Service (AWS DMS).
- C. Modify the Auto Scaling group to use EC2 instances across three Availability Zones. Maintain the embedded NoSQL database with its replication service on the EC2 instances.
- D. Modify the Auto Scaling group to use EC2 instances across three Availability Zones. Migrate the embedded NoSQL database to Amazon DynamoDB by using AWS Database Migration Service (AWS DMS). **Most Voted**

Suggested Answer: D

Question #: 694

A company is building a shopping application on AWS. The application offers a catalog that changes once each month and needs to scale with traffic volume. The company wants the lowest possible latency from the

application. Data from each user's shopping cart needs to be highly available. User session data must be available even if the user is disconnected and reconnects.

What should a solutions architect do to ensure that the shopping cart data is preserved at all times?

- A. Configure an Application Load Balancer to enable the sticky sessions feature (session affinity) for access to the catalog in Amazon Aurora.
- B. Configure Amazon ElastiCache for Redis to cache catalog data from Amazon DynamoDB and shopping cart data from the user's session.
- C. Configure Amazon OpenSearch Service to cache catalog data from Amazon DynamoDB and shopping cart data from the user's session.
- D. Configure an Amazon EC2 instance with Amazon Elastic Block Store (Amazon EBS) storage for the catalog and shopping cart. Configure automated snapshots.

Suggested Answer: B

Question #: 695

A company is building a microservices-based application that will be deployed on Amazon Elastic Kubernetes Service (Amazon EKS). The microservices will interact with each other. The company wants to ensure that the application is observable to identify performance issues in the future.

Which solution will meet these requirements?

- A. Configure the application to use Amazon ElastiCache to reduce the number of requests that are sent to the microservices.
- B. Configure Amazon CloudWatch Container Insights to collect metrics from the EKS clusters. Configure AWS X-Ray to trace the requests between the microservices. **Most Voted**

- C. Configure AWS CloudTrail to review the API calls. Build an Amazon QuickSight dashboard to observe the microservice interactions.
- D. Use AWS Trusted Advisor to understand the performance of the application.

Suggested Answer: B

Question #: 696

A company needs to provide customers with secure access to its data. The company processes customer data and stores the results in an Amazon S3 bucket.

All the data is subject to strong regulations and security requirements. The data must be encrypted at rest. Each customer must be able to access only their data from their AWS account. Company employees must not be able to access the data.

Which solution will meet these requirements?

- A. Provision an AWS Certificate Manager (ACM) certificate for each customer. Encrypt the data client-side. In the private certificate policy, deny access to the certificate for all principals except an IAM role that the customer provides.
- B. Provision a separate AWS Key Management Service (AWS KMS) key for each customer. Encrypt the data server-side. In the S3 bucket policy, deny decryption of data for all principals except an IAM role that the customer provides.
- C. Provision a separate AWS Key Management Service (AWS KMS) key for each customer. Encrypt the data server-side. In each KMS key policy, deny decryption of data for all principals except an IAM role that the customer provides.
- D. Provision an AWS Certificate Manager (ACM) certificate for each customer. Encrypt the data client-side. In the public certificate policy, deny access to the certificate for all principals except an IAM role that the customer provides.

Suggested Answer: C

Question #: 697

A solutions architect creates a VPC that includes two public subnets and two private subnets. A corporate security mandate requires the solutions architect to launch all Amazon EC2 instances in a private subnet. However, when the solutions architect launches an EC2 instance that runs a web server on ports 80 and 443 in a private subnet, no external internet traffic can connect to the server.

What should the solutions architect do to resolve this issue?

- A. Attach the EC2 instance to an Auto Scaling group in a private subnet. Ensure that the DNS record for the website resolves to the Auto Scaling group identifier.
- B. Provision an internet-facing Application Load Balancer (ALB) in a public subnet. Add the EC2 instance to the target group that is associated with the ALB. Ensure that the DNS record for the website resolves to the ALB. **Most Voted**
- C. Launch a NAT gateway in a private subnet. Update the route table for the private subnets to add a default route to the NAT gateway. Attach a public Elastic IP address to the NAT gateway.
- D. Ensure that the security group that is attached to the EC2 instance allows HTTP traffic on port 80 and HTTPS traffic on port 443. Ensure that the DNS record for the website resolves to the public IP address of the EC2 instance.

Suggested Answer: B

Question #: 698

A company is deploying a new application to Amazon Elastic Kubernetes Service (Amazon EKS) with an AWS Fargate cluster. The application needs a storage solution for data persistence. The solution must be highly available and fault tolerant. The solution also must be shared between multiple application containers.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create Amazon Elastic Block Store (Amazon EBS) volumes in the same Availability Zones where EKS worker nodes are placed. Register the volumes in a StorageClass object on an EKS cluster. Use EBS Multi-Attach to share the data between containers.
- B. Create an Amazon Elastic File System (Amazon EFS) file system. Register the file system in a StorageClass object on an EKS cluster. Use the same file system for all containers.
- C. Create an Amazon Elastic Block Store (Amazon EBS) volume. Register the volume in a StorageClass object on an EKS cluster. Use the same volume for all containers.
- D. Create Amazon Elastic File System (Amazon EFS) file systems in the same Availability Zones where EKS worker nodes are placed. Register the file systems in a StorageClass object on an EKS cluster. Create an AWS Lambda function to synchronize the data between file systems.

Suggested Answer: B

Question #: 699

A company has an application that uses Docker containers in its local data center. The application runs on a container host that stores persistent data in a volume on the host. The container instances use the stored persistent data.

The company wants to move the application to a fully managed service because the company does not want to manage any servers or storage infrastructure.

Which solution will meet these requirements?

- A. Use Amazon Elastic Kubernetes Service (Amazon EKS) with self-managed nodes. Create an Amazon Elastic Block Store (Amazon EBS) volume attached to an Amazon EC2 instance. Use the EBS volume as a persistent volume mounted in the containers.
- B. Use Amazon Elastic Container Service (Amazon ECS) with an AWS Fargate launch type. Create an Amazon Elastic File System (Amazon EFS) volume. Add the EFS volume as a persistent storage volume mounted in the containers. **Most Voted**
- C. Use Amazon Elastic Container Service (Amazon ECS) with an AWS Fargate launch type. Create an Amazon S3 bucket. Map the S3 bucket as a persistent storage volume mounted in the containers.
- D. Use Amazon Elastic Container Service (Amazon ECS) with an Amazon EC2 launch type. Create an Amazon Elastic File System (Amazon EFS) volume. Add the EFS volume as a persistent storage volume mounted in the containers.

Suggested Answer: B

Question #: 701

A city has deployed a web application running on Amazon EC2 instances behind an Application Load Balancer (ALB). The application's users have reported sporadic performance, which appears to be related to DDoS attacks originating from random IP addresses. The city needs a solution that requires minimal configuration changes and provides an audit trail for the DDoS sources.

Which solution meets these requirements?

- A. Enable an AWS WAF web ACL on the ALB, and configure rules to block traffic from unknown sources.
- B. Subscribe to Amazon Inspector. Engage the AWS DDoS Response Team (DRT) to integrate mitigating controls into the service.
- C. Subscribe to AWS Shield Advanced. Engage the AWS DDoS Response Team (DRT) to integrate mitigating controls into the service.

- D. Create an Amazon CloudFront distribution for the application, and set the ALB as the origin. Enable an AWS WAF web ACL on the distribution, and configure rules to block traffic from unknown sources

Suggested Answer: C

Question #: 702

A company copies 200 TB of data from a recent ocean survey onto AWS Snowball Edge Storage Optimized devices. The company has a high performance computing (HPC) cluster that is hosted on AWS to look for oil and gas deposits. A solutions architect must provide the cluster with consistent sub-millisecond latency and high-throughput access to the data on the Snowball Edge Storage Optimized devices. The company is sending the devices back to AWS.

Which solution will meet these requirements?

- A. Create an Amazon S3 bucket. Import the data into the S3 bucket. Configure an AWS Storage Gateway file gateway to use the S3 bucket. Access the file gateway from the HPC cluster instances.
- B. Create an Amazon S3 bucket. Import the data into the S3 bucket. Configure an Amazon FSx for Lustre file system, and integrate it with the S3 bucket. Access the FSx for Lustre file system from the HPC cluster instances.
- C. Create an Amazon S3 bucket and an Amazon Elastic File System (Amazon EFS) file system. Import the data into the S3 bucket. Copy the data from the S3 bucket to the EFS file system. Access the EFS file system from the HPC cluster instances.
- D. Create an Amazon FSx for Lustre file system. Import the data directly into the FSx for Lustre file system. Access the FSx for Lustre file system from the HPC cluster instances. **Most Voted**

Suggested Answer: D

Question #: 703

A company has NFS servers in an on-premises data center that need to periodically back up small amounts of data to Amazon S3.

Which solution meets these requirements and is MOST cost-effective?

- A. Set up AWS Glue to copy the data from the on-premises servers to Amazon S3.
- B. Set up an AWS DataSync agent on the on-premises servers, and sync the data to Amazon S3. **Most Voted**
- C. Set up an SFTP sync using AWS Transfer for SFTP to sync data from on premises to Amazon S3.
- D. Set up an AWS Direct Connect connection between the on-premises data center and a VPC, and copy the data to Amazon S3.

Suggested Answer: B

Question #: 704

An online video game company must maintain ultra-low latency for its game servers. The game servers run on Amazon EC2 instances. The company needs a solution that can handle millions of UDP internet traffic requests each second.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure an Application Load Balancer with the required protocol and ports for the internet traffic. Specify the EC2 instances as the targets.
- B. Configure a Gateway Load Balancer for the internet traffic. Specify the EC2 instances as the targets.

- C. Configure a Network Load Balancer with the required protocol and ports for the internet traffic. Specify the EC2 instances as the targets. **Most Voted**
- D. Launch an identical set of game servers on EC2 instances in separate AWS Regions. Route internet traffic to both sets of EC2 instances.

Suggested Answer: C

Question #: 705

A company runs a three-tier application in a VPC. The database tier uses an Amazon RDS for MySQL DB instance.

The company plans to migrate the RDS for MySQL DB instance to an Amazon Aurora PostgreSQL DB cluster. The company needs a solution that replicates the data changes that happen during the migration to the new database.

Which combination of steps will meet these requirements? (Choose two.)

- A. Use AWS Database Migration Service (AWS DMS) Schema Conversion to transform the database objects.
- B. Use AWS Database Migration Service (AWS DMS) Schema Conversion to create an Aurora PostgreSQL read replica on the RDS for MySQL DB instance.
- C. Configure an Aurora MySQL read replica for the RDS for MySQL DB instance.
- D. Define an AWS Database Migration Service (AWS DMS) task with change data capture (CDC) to migrate the data.
- E. Promote the Aurora PostgreSQL read replica to a standalone Aurora PostgreSQL DB cluster when the replica lag is zero.

Suggested Answer: AD

Question #: 706

A company hosts a database that runs on an Amazon RDS instance that is deployed to multiple Availability Zones. The company periodically runs a script against the database to report new entries that are added to the database. The script that runs against the database negatively affects the performance of a critical application. The company needs to improve application performance with minimal costs.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Add functionality to the script to identify the instance that has the fewest active connections. Configure the script to read from that instance to report the total new entries.
- B. Create a read replica of the database. Configure the script to query only the read replica to report the total new entries. **Most Voted**
- C. Instruct the development team to manually export the new entries for the day in the database at the end of each day.
- D. Use Amazon ElastiCache to cache the common queries that the script runs against the database.

Suggested Answer: B

Question #: 707

A company is using an Application Load Balancer (ALB) to present its application to the internet. The company finds abnormal traffic access patterns across the application. A solutions architect needs to improve visibility into the infrastructure to help the company understand these abnormalities better.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create a table in Amazon Athena for AWS CloudTrail logs. Create a query for the relevant information.
- B. Enable ALB access logging to Amazon S3. Create a table in Amazon Athena, and query the logs.
- C. Enable ALB access logging to Amazon S3. Open each file in a text editor, and search each line for the relevant information.
- D. Use Amazon EMR on a dedicated Amazon EC2 instance to directly query the ALB to acquire traffic access log information.

Suggested Answer: B

Question #: 708

A company wants to use NAT gateways in its AWS environment. The company's Amazon EC2 instances in private subnets must be able to connect to the public internet through the NAT gateways.

Which solution will meet these requirements?

- A. Create public NAT gateways in the same private subnets as the EC2 instances.
- B. Create private NAT gateways in the same private subnets as the EC2 instances.
- C. Create public NAT gateways in public subnets in the same VPCs as the EC2 instances. **Most Voted**
- D. Create private NAT gateways in public subnets in the same VPCs as the EC2 instances.

Suggested Answer: C

Question #: 709

A company has an organization in AWS Organizations. The company runs Amazon EC2 instances across four AWS accounts in the root organizational unit (OU). There are three nonproduction accounts and one production account. The company wants to prohibit users from launching EC2 instances of a certain size in the nonproduction accounts. The company has created a service control policy (SCP) to deny access to launch instances that use the prohibited types.

Which solutions to deploy the SCP will meet these requirements? (Choose two.)

- A. Attach the SCP to the root OU for the organization.
- B. Attach the SCP to the three nonproduction Organizations member accounts. **Most Voted**
- C. Attach the SCP to the Organizations management account.
- D. Create an OU for the production account. Attach the SCP to the OU. Move the production member account into the new OU.
- E. Create an OU for the required accounts. Attach the SCP to the OU. Move the nonproduction member accounts into the new OU. **Most Voted**

Suggested Answer: BE

Question #: 710

A company's website hosted on Amazon EC2 instances processes classified data stored in Amazon S3. Due to security concerns, the company requires a private and secure connection between its EC2 resources and Amazon S3.

Which solution meets these requirements?

- A. Set up S3 bucket policies to allow access from a VPC endpoint. **Most Voted**
- B. Set up an IAM policy to grant read-write access to the S3 bucket.
- C. Set up a NAT gateway to access resources outside the private subnet.
- D. Set up an access key ID and a secret access key to access the S3 bucket.

Suggested Answer: A

Question #: 711

An ecommerce company runs its application on AWS. The application uses an Amazon Aurora PostgreSQL cluster in Multi-AZ mode for the underlying database. During a recent promotional campaign, the application experienced heavy read load and write load. Users experienced timeout issues when they attempted to access the application.

A solutions architect needs to make the application architecture more scalable and highly available.

Which solution will meet these requirements with the LEAST downtime?

- A. Create an Amazon EventBridge rule that has the Aurora cluster as a source. Create an AWS Lambda function to log the state change events of the Aurora cluster. Add the Lambda function as a target for the EventBridge rule. Add additional reader nodes to fail over to.
- B. Modify the Aurora cluster and activate the zero-downtime restart (ZDR) feature. Use Database Activity Streams on the cluster to track the cluster status.
- C. Add additional reader instances to the Aurora cluster. Create an Amazon RDS Proxy target group for the Aurora cluster. **Most Voted**

- D. Create an Amazon ElastiCache for Redis cache. Replicate data from the Aurora cluster to Redis by using AWS Database Migration Service (AWS DMS) with a write-around approach.

Suggested Answer: C

Question #: 712

A company is designing a web application on AWS. The application will use a VPN connection between the company's existing data centers and the company's VPCs.

The company uses Amazon Route 53 as its DNS service. The application must use private DNS records to communicate with the on-premises services from a VPC.

Which solution will meet these requirements in the MOST secure manner?

- A. Create a Route 53 Resolver outbound endpoint. Create a resolver rule. Associate the resolver rule with the VPC. **Most Voted**
- B. Create a Route 53 Resolver inbound endpoint. Create a resolver rule. Associate the resolver rule with the VPC.
- C. Create a Route 53 private hosted zone. Associate the private hosted zone with the VPC.
- D. Create a Route 53 public hosted zone. Create a record for each service to allow service communication

Suggested Answer: A

Question #: 713

A company is running a photo hosting service in the us-east-1 Region. The service enables users across multiple countries to upload and view photos. Some photos are heavily viewed for months, and others are viewed for less than a week. The application allows uploads of up to 20 MB for each photo. The service uses the photo metadata to determine which photos to display to each user.

Which solution provides the appropriate user access MOST cost-effectively?

- A. Store the photos in Amazon DynamoDB. Turn on DynamoDB Accelerator (DAX) to cache frequently viewed items.
- B. Store the photos in the Amazon S3 Intelligent-Tiering storage class. Store the photo metadata and its S3 location in DynamoDB. **Most Voted**
- C. Store the photos in the Amazon S3 Standard storage class. Set up an S3 Lifecycle policy to move photos older than 30 days to the S3 Standard-Infrequent Access (S3 Standard-IA) storage class. Use the object tags to keep track of metadata.
- D. Store the photos in the Amazon S3 Glacier storage class. Set up an S3 Lifecycle policy to move photos older than 30 days to the S3 Glacier Deep Archive storage class. Store the photo metadata and its S3 location in Amazon OpenSearch Service.

Suggested Answer: B

Question #: 714

A company runs a highly available web application on Amazon EC2 instances behind an Application Load Balancer. The company uses Amazon CloudWatch metrics.

As the traffic to the web application increases, some EC2 instances become overloaded with many outstanding requests. The CloudWatch metrics show that the number of requests processed and the time to receive the responses from some EC2 instances are both higher compared to other EC2 instances. The company does not want new requests to be forwarded to the EC2 instances that are already overloaded.

Which solution will meet these requirements?

- A. Use the round robin routing algorithm based on the RequestCountPerTarget and ActiveConnectionCount CloudWatch metrics.
- B. Use the least outstanding requests algorithm based on the RequestCountPerTarget and ActiveConnectionCount CloudWatch metrics. **Most Voted**
- C. Use the round robin routing algorithm based on the RequestCount and TargetResponseTime CloudWatch metrics.
- D. Use the least outstanding requests algorithm based on the RequestCount and TargetResponseTime CloudWatch metrics.

Suggested Answer: B

Exam question from Amazon's AWS Certified Solutions Architect - Associate SAA-C03

Question #: 715

A company uses Amazon EC2, AWS Fargate, and AWS Lambda to run multiple workloads in the company's AWS account. The company wants to fully make use of its Compute Savings Plans. The company wants to receive notification when coverage of the Compute Savings Plans drops.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Create a daily budget for the Savings Plans by using AWS Budgets. Configure the budget with a coverage threshold to send notifications to the appropriate email message recipients. **Most Voted**
- B. Create a Lambda function that runs a coverage report against the Savings Plans. Use Amazon Simple Email Service (Amazon SES) to email the report to the appropriate email message recipients.
- C. Create an AWS Budgets report for the Savings Plans budget. Set the frequency to daily.

- D. Create a Savings Plans alert subscription. Enable all notification options. Enter an email address to receive notifications.

Suggested Answer: A

Question #: 716

A company runs a real-time data ingestion solution on AWS. The solution consists of the most recent version of Amazon Managed Streaming for Apache Kafka (Amazon MSK). The solution is deployed in a VPC in private subnets across three Availability Zones.

A solutions architect needs to redesign the data ingestion solution to be publicly available over the internet. The data in transit must also be encrypted.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Configure public subnets in the existing VPC. Deploy an MSK cluster in the public subnets. Update the MSK cluster security settings to enable mutual TLS authentication. **Most Voted**
- B. Create a new VPC that has public subnets. Deploy an MSK cluster in the public subnets. Update the MSK cluster security settings to enable mutual TLS authentication.
- C. Deploy an Application Load Balancer (ALB) that uses private subnets. Configure an ALB security group inbound rule to allow inbound traffic from the VPC CIDR block for HTTPS protocol.
- D. Deploy a Network Load Balancer (NLB) that uses private subnets. Configure an NLB listener for HTTPS communication over the internet.

Suggested Answer: A

Question #: 717

A company wants to migrate an on-premises legacy application to AWS. The application ingests customer order files from an on-premises enterprise resource planning (ERP) system. The application then uploads the files to an SFTP server. The application uses a scheduled job that checks for order files every hour.

The company already has an AWS account that has connectivity to the on-premises network. The new application on AWS must support integration with the existing ERP system. The new application must be secure and resilient and must use the SFTP protocol to process orders from the ERP system immediately.

Which solution will meet these requirements?

- A. Create an AWS Transfer Family SFTP internet-facing server in two Availability Zones. Use Amazon S3 storage. Create an AWS Lambda function to process order files. Use S3 Event Notifications to send s3:ObjectCreated:* events to the Lambda function.
- B. Create an AWS Transfer Family SFTP internet-facing server in one Availability Zone. Use Amazon Elastic File System (Amazon EFS) storage. Create an AWS Lambda function to process order files. Use a Transfer Family managed workflow to invoke the Lambda function.
- C. Create an AWS Transfer Family SFTP internal server in two Availability Zones. Use Amazon Elastic File System (Amazon EFS) storage. Create an AWS Step Functions state machine to process order files. Use Amazon EventBridge Scheduler to invoke the state machine to periodically check Amazon EFS for order files.
- D. Create an AWS Transfer Family SFTP internal server in two Availability Zones. Use Amazon S3 storage. Create an AWS Lambda function to process order files. Use a Transfer Family managed workflow to invoke the Lambda function. **Most Voted**

Suggested Answer: D

Question #: 718

A company's applications use Apache Hadoop and Apache Spark to process data on premises. The existing infrastructure is not scalable and is complex to manage.

A solutions architect must design a scalable solution that reduces operational complexity. The solution must keep the data processing on premises.

Which solution will meet these requirements?

- A. Use AWS Site-to-Site VPN to access the on-premises Hadoop Distributed File System (HDFS) data and application. Use an Amazon EMR cluster to process the data.
- B. Use AWS DataSync to connect to the on-premises Hadoop Distributed File System (HDFS) cluster. Create an Amazon EMR cluster to process the data.
- C. Migrate the Apache Hadoop application and the Apache Spark application to Amazon EMR clusters on AWS Outposts. Use the EMR clusters to process the data. **Most Voted**
- D. Use an AWS Snowball device to migrate the data to an Amazon S3 bucket. Create an Amazon EMR cluster to process the data.

Suggested Answer: C

Question #: 719

A company is migrating a large amount of data from on-premises storage to AWS. Windows, Mac, and Linux based Amazon EC2 instances in the same AWS Region will access the data by using SMB and NFS storage protocols. The company will access a portion of the data routinely. The company will access the remaining data infrequently.

The company needs to design a solution to host the data.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an Amazon Elastic File System (Amazon EFS) volume that uses EFS Intelligent-Tiering. Use AWS DataSync to migrate the data to the EFS volume.
- B. Create an Amazon FSx for ONTAP instance. Create an FSx for ONTAP file system with a root volume that uses the auto tiering policy. Migrate the data to the FSx for ONTAP volume. **Most Voted**
- C. Create an Amazon S3 bucket that uses S3 Intelligent-Tiering. Migrate the data to the S3 bucket by using an AWS Storage Gateway Amazon S3 File Gateway.
- D. Create an Amazon FSx for OpenZFS file system. Migrate the data to the new volume.

Suggested Answer: B

Question #: 720

A manufacturing company runs its report generation application on AWS. The application generates each report in about 20 minutes. The application is built as a monolith that runs on a single Amazon EC2 instance. The application requires frequent updates to its tightly coupled modules. The application becomes complex to maintain as the company adds new features.

Each time the company patches a software module, the application experiences downtime. Report generation must restart from the beginning after any interruptions. The company wants to redesign the application so that the application can be flexible, scalable, and gradually improved. The company wants to minimize application downtime.

Which solution will meet these requirements?

- A. Run the application on AWS Lambda as a single function with maximum provisioned concurrency.

- B. Run the application on Amazon EC2 Spot Instances as microservices with a Spot Fleet default allocation strategy.
- C. Run the application on Amazon Elastic Container Service (Amazon ECS) as microservices with service auto scaling. **Most Voted**
- D. Run the application on AWS Elastic Beanstalk as a single application environment with an all-at-once deployment strategy.

Suggested Answer: C

Question #: 721

A company wants to rearchitect a large-scale web application to a serverless microservices architecture. The application uses Amazon EC2 instances and is written in Python.

The company selected one component of the web application to test as a microservice. The component supports hundreds of requests each second. The company wants to create and test the microservice on an AWS solution that supports Python. The solution must also scale automatically and require minimal infrastructure and minimal operational support.

Which solution will meet these requirements?

- A. Use a Spot Fleet with auto scaling of EC2 instances that run the most recent Amazon Linux operating system.
- B. Use an AWS Elastic Beanstalk web server environment that has high availability configured.
- C. Use Amazon Elastic Kubernetes Service (Amazon EKS). Launch Auto Scaling groups of self-managed EC2 instances.
- D. Use an AWS Lambda function that runs custom developed code. **Most Voted**

Suggested Answer: D

Question #: 723

A company has applications that run on Amazon EC2 instances. The EC2 instances connect to Amazon RDS databases by using an IAM role that has associated policies. The company wants to use AWS Systems Manager to patch the EC2 instances without disrupting the running applications.

Which solution will meet these requirements?

- A. Create a new IAM role. Attach the AmazonSSMManagedInstanceCore policy to the new IAM role. Attach the new IAM role to the EC2 instances and the existing IAM role.
- B. Create an IAM user. Attach the AmazonSSMManagedInstanceCore policy to the IAM user. Configure Systems Manager to use the IAM user to manage the EC2 instances.
- C. Enable Default Host Configuration Management in Systems Manager to manage the EC2 instances.
- D. Remove the existing policies from the existing IAM role. Add the AmazonSSMManagedInstanceCore policy to the existing IAM role.

Suggested Answer: C

Question #: 725

A company maintains about 300 TB in Amazon S3 Standard storage month after month. The S3 objects are each typically around 50 GB in size and are frequently replaced with multipart uploads by their global application. The number and size of S3 objects remain constant, but the company's S3 storage costs are increasing each month.

How should a solutions architect reduce costs in this situation?

- A. Switch from multipart uploads to Amazon S3 Transfer Acceleration.
- B. Enable an S3 Lifecycle policy that deletes incomplete multipart uploads. **Most Voted**
- C. Configure S3 inventory to prevent objects from being archived too quickly.
- D. Configure Amazon CloudFront to reduce the number of objects stored in Amazon S3.

Suggested Answer: B

Question #: 726

A company has deployed a multiplayer game for mobile devices. The game requires live location tracking of players based on latitude and longitude. The data store for the game must support rapid updates and retrieval of locations.

The game uses an Amazon RDS for PostgreSQL DB instance with read replicas to store the location data. During peak usage periods, the database is unable to maintain the performance that is needed for reading and writing updates. The game's user base is increasing rapidly.

What should a solutions architect do to improve the performance of the data tier?

- A. Take a snapshot of the existing DB instance. Restore the snapshot with Multi-AZ enabled.
- B. Migrate from Amazon RDS to Amazon OpenSearch Service with OpenSearch Dashboards.
- C. Deploy Amazon DynamoDB Accelerator (DAX) in front of the existing DB instance. Modify the game to use DAX.
- D. Deploy an Amazon ElastiCache for Redis cluster in front of the existing DB instance. Modify the game to use Redis.

Suggested Answer: D

Question #: 727

A company stores critical data in Amazon DynamoDB tables in the company's AWS account. An IT administrator accidentally deleted a DynamoDB table. The deletion caused a significant loss of data and disrupted the company's operations. The company wants to prevent this type of disruption in the future.

Which solution will meet this requirement with the LEAST operational overhead?

- A. Configure a trail in AWS CloudTrail. Create an Amazon EventBridge rule for delete actions. Create an AWS Lambda function to automatically restore deleted DynamoDB tables.
- B. Create a backup and restore plan for the DynamoDB tables. Recover the DynamoDB tables manually.
- C. Configure deletion protection on the DynamoDB tables. **Most Voted**
- D. Enable point-in-time recovery on the DynamoDB tables.

Suggested Answer: C

Question #: 728

A company has an on-premises data center that is running out of storage capacity. The company wants to migrate its storage infrastructure to AWS while minimizing bandwidth costs. The solution must allow for immediate retrieval of data at no additional cost.

How can these requirements be met?

- A. Deploy Amazon S3 Glacier Vault and enable expedited retrieval. Enable provisioned retrieval capacity for the workload.
- B. Deploy AWS Storage Gateway using cached volumes. Use Storage Gateway to store data in Amazon S3 while retaining copies of frequently accessed data subsets locally. **Most Voted**
- C. Deploy AWS Storage Gateway using stored volumes to store data locally. Use Storage Gateway to asynchronously back up point-in-time snapshots of the data to Amazon S3.
- D. Deploy AWS Direct Connect to connect with the on-premises data center. Configure AWS Storage Gateway to store data locally. Use Storage Gateway to asynchronously back up point-in-time snapshots of the data to Amazon S3.

Suggested Answer: B

Question #: 729

A company runs a three-tier web application in a VPC across multiple Availability Zones. Amazon EC2 instances run in an Auto Scaling group for the application tier.

The company needs to make an automated scaling plan that will analyze each resource's daily and weekly historical workload trends. The configuration must scale resources appropriately according to both the forecast and live changes in utilization.

Which scaling strategy should a solutions architect recommend to meet these requirements?

- A. Implement dynamic scaling with step scaling based on average CPU utilization from the EC2 instances.
- B. Enable predictive scaling to forecast and scale. Configure dynamic scaling with target tracking **Most Voted**
- C. Create an automated scheduled scaling action based on the traffic patterns of the web application.
- D. Set up a simple scaling policy. Increase the cooldown period based on the EC2 instance startup time.

Suggested Answer: B

Question #: 730

A package delivery company has an application that uses Amazon EC2 instances and an Amazon Aurora MySQL DB cluster. As the application becomes more popular, EC2 instance usage increases only slightly. DB cluster usage increases at a much faster rate.

The company adds a read replica, which reduces the DB cluster usage for a short period of time. However, the load continues to increase. The operations that cause the increase in DB cluster usage are all repeated read statements that are related to delivery details. The company needs to alleviate the effect of repeated reads on the DB cluster.

Which solution will meet these requirements MOST cost-effectively?

- A. Implement an Amazon ElastiCache for Redis cluster between the application and the DB cluster. **Most Voted**
- B. Add an additional read replica to the DB cluster.
- C. Configure Aurora Auto Scaling for the Aurora read replicas.
- D. Modify the DB cluster to have multiple writer instances.

Suggested Answer: A

Question #: 731

A company has an application that uses an Amazon DynamoDB table for storage. A solutions architect discovers that many requests to the table are not returning the latest data. The company's users have not reported any other issues with database performance. Latency is in an acceptable range.

Which design change should the solutions architect recommend?

- A. Add read replicas to the table.
- B. Use a global secondary index (GSI).
- C. Request strongly consistent reads for the table. **Most Voted**
- D. Request eventually consistent reads for the table.

Suggested Answer: C

Question #: 732

A company has deployed its application on Amazon EC2 instances with an Amazon RDS database. The company used the principle of least privilege to configure the database access credentials. The company's security team wants to protect the application and the database from SQL injection and other web-based attacks.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use security groups and network ACLs to secure the database and application servers.
- B. Use AWS WAF to protect the application. Use RDS parameter groups to configure the security settings. **Most Voted**
- C. Use AWS Network Firewall to protect the application and the database.
- D. Use different database accounts in the application code for different functions. Avoid granting excessive privileges to the database users.

Suggested Answer: B

Question #: 733

An ecommerce company runs applications in AWS accounts that are part of an organization in AWS Organizations. The applications run on Amazon Aurora PostgreSQL databases across all the accounts. The company needs to prevent malicious activity and must identify abnormal failed and incomplete login attempts to the databases.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Attach service control policies (SCPs) to the root of the organization to identify the failed login attempts.
- B. Enable the Amazon RDS Protection feature in Amazon GuardDuty for the member accounts of the organization.
- C. Publish the Aurora general logs to a log group in Amazon CloudWatch Logs. Export the log data to a central Amazon S3 bucket.
- D. Publish all the Aurora PostgreSQL database events in AWS CloudTrail to a central Amazon S3 bucket.

Suggested Answer: B

Question #: 734

A company has an AWS Direct Connect connection from its corporate data center to its VPC in the us-east-1 Region. The company recently acquired a corporation that has several VPCs and a Direct Connect connection between its on-premises data center and the eu-west-2 Region. The CIDR blocks for the VPCs of the company

and the corporation do not overlap. The company requires connectivity between two Regions and the data centers. The company needs a solution that is scalable while reducing operational overhead.

What should a solutions architect do to meet these requirements?

- A. Set up inter-Region VPC peering between the VPC in us-east-1 and the VPCs in eu-west-2.
- B. Create private virtual interfaces from the Direct Connect connection in us-east-1 to the VPCs in eu-west-2.
- C. Establish VPN appliances in a fully meshed VPN network hosted by Amazon EC2. Use AWS VPN CloudHub to send and receive data between the data centers and each VPC.
- D. Connect the existing Direct Connect connection to a Direct Connect gateway. Route traffic from the virtual private gateways of the VPCs in each Region to the Direct Connect gateway.

Suggested Answer: D

Question #: 735

A company is developing a mobile game that streams score updates to a backend processor and then posts results on a leaderboard. A solutions architect needs to design a solution that can handle large traffic spikes, process the mobile game updates in order of receipt, and store the processed updates in a highly available database. The company also wants to minimize the management overhead required to maintain the solution.

What should the solutions architect do to meet these requirements?

- A. Push score updates to Amazon Kinesis Data Streams. Process the updates in Kinesis Data Streams with AWS Lambda. Store the processed updates in Amazon DynamoDB. **Most Voted**
- B. Push score updates to Amazon Kinesis Data Streams. Process the updates with a fleet of Amazon EC2 instances set up for Auto Scaling. Store the processed updates in Amazon Redshift.

- C. Push score updates to an Amazon Simple Notification Service (Amazon SNS) topic. Subscribe an AWS Lambda function to the SNS topic to process the updates. Store the processed updates in a SQL database running on Amazon EC2.
- D. Push score updates to an Amazon Simple Queue Service (Amazon SQS) queue. Use a fleet of Amazon EC2 instances with Auto Scaling to process the updates in the SQS queue. Store the processed updates in an Amazon RDS Multi-AZ DB instance.

Suggested Answer: A

Question #: 738

A company has a new mobile app. Anywhere in the world, users can see local news on topics they choose. Users also can post photos and videos from inside the app.

Users access content often in the first minutes after the content is posted. New content quickly replaces older content, and then the older content disappears. The local nature of the news means that users consume 90% of the content within the AWS Region where it is uploaded.

Which solution will optimize the user experience by providing the LOWEST latency for content uploads?

- A. Upload and store content in Amazon S3. Use Amazon CloudFront for the uploads.
- B. Upload and store content in Amazon S3. Use S3 Transfer Acceleration for the uploads. **Most Voted**
- C. Upload content to Amazon EC2 instances in the Region that is closest to the user. Copy the data to Amazon S3.
- D. Upload and store content in Amazon S3 in the Region that is closest to the user. Use multiple distributions of Amazon CloudFront.

Suggested Answer: B

Question #: 839

A company runs an AWS Lambda function in private subnets in a VPC. The subnets have a default route to the internet through an Amazon EC2 NAT instance. The Lambda function processes input data and saves its output as an object to Amazon S3.

Intermittently, the Lambda function times out while trying to upload the object because of saturated traffic on the NAT instance's network. The company wants to access Amazon S3 without traversing the internet.

Which solution will meet these requirements?

- A. Replace the EC2 NAT instance with an AWS managed NAT gateway.
- B. Increase the size of the EC2 NAT instance in the VPC to a network optimized instance type.
- C. Provision a gateway endpoint for Amazon S3 in the VPC and update the route tables of the subnets accordingly.
- D. Provision a transit gateway. Place transit gateway attachments in the private subnets where the Lambda function is running.

Suggested Answer: C

Question #: 740

A company migrated millions of archival files to Amazon S3. A solutions architect needs to implement a solution that will encrypt all the archival data by using a customer-provided key. The solution must encrypt existing unencrypted objects and future objects.

Which solution will meet these requirements?

- A. Create a list of unencrypted objects by filtering an Amazon S3 Inventory report. Configure an S3 Batch Operations job to encrypt the objects from the list with a server-side encryption with a customer-provided key (SSE-C). Configure the S3 default encryption feature to use a server-side encryption with a customer-provided key (SSE-C). **Most Voted**
- B. Use S3 Storage Lens metrics to identify unencrypted S3 buckets. Configure the S3 default encryption feature to use a server-side encryption with AWS KMS keys (SSE-KMS).
- C. Create a list of unencrypted objects by filtering the AWS usage report for Amazon S3. Configure an AWS Batch job to encrypt the objects from the list with a server-side encryption with AWS KMS keys (SSE-KMS). Configure the S3 default encryption feature to use a server-side encryption with AWS KMS keys (SSE-KMS).
- D. Create a list of unencrypted objects by filtering the AWS usage report for Amazon S3. Configure the S3 default encryption feature to use a server-side encryption with a customer-provided key (SSE-C).

Suggested Answer: A

Question #: 741

The DNS provider that hosts a company's domain name records is experiencing outages that cause service disruption for a website running on AWS. The company needs to migrate to a more resilient managed DNS service and wants the service to run on AWS.

What should a solutions architect do to rapidly migrate the DNS hosting service?

- A. Create an Amazon Route 53 public hosted zone for the domain name. Import the zone file containing the domain records hosted by the previous provider. **Most Voted**

- B. Create an Amazon Route 53 private hosted zone for the domain name. Import the zone file containing the domain records hosted by the previous provider.
- C. Create a Simple AD directory in AWS. Enable zone transfer between the DNS provider and AWS Directory Service for Microsoft Active Directory for the domain records.
- D. Create an Amazon Route 53 Resolver inbound endpoint in the VPC. Specify the IP addresses that the provider's DNS will forward DNS queries to. Configure the provider's DNS to forward DNS queries for the domain to the IP addresses that are specified in the inbound endpoint.

Suggested Answer: A

Question #: 742

A company is building an application on AWS that connects to an Amazon RDS database. The company wants to manage the application configuration and to securely store and retrieve credentials for the database and other services.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Use AWS AppConfig to store and manage the application configuration. Use AWS Secrets Manager to store and retrieve the credentials. **Most Voted**
- B. Use AWS Lambda to store and manage the application configuration. Use AWS Systems Manager Parameter Store to store and retrieve the credentials.
- C. Use an encrypted application configuration file. Store the file in Amazon S3 for the application configuration. Create another S3 file to store and retrieve the credentials.
- D. Use AWS AppConfig to store and manage the application configuration. Use Amazon RDS to store and retrieve the credentials.

Suggested Answer: A

Question #: 743

To meet security requirements, a company needs to encrypt all of its application data in transit while communicating with an Amazon RDS MySQL DB instance. A recent security audit revealed that encryption at rest is enabled using AWS Key Management Service (AWS KMS), but data in transit is not enabled.

What should a solutions architect do to satisfy the security requirements?

- A. Enable IAM database authentication on the database.
- B. Provide self-signed certificates. Use the certificates in all connections to the RDS instance.
- C. Take a snapshot of the RDS instance. Restore the snapshot to a new instance with encryption enabled.
- D. Download AWS-provided root certificates. Provide the certificates in all connections to the RDS instance. **Most Voted**

Suggested Answer: D

Question #: 774

A solutions architect must provide an automated solution for a company's compliance policy that states security groups cannot include a rule that allows SSH from 0.0.0.0/0. The company needs to be notified if there is any breach in the policy. A solution is needed as soon as possible.

What should the solutions architect do to meet these requirements with the LEAST operational overhead?

- A. Write an AWS Lambda script that monitors security groups for SSH being open to 0.0.0.0/0 addresses and creates a notification every time it finds one.
- B. Enable the restricted-ssh AWS Config managed rule and generate an Amazon Simple Notification Service (Amazon SNS) notification when a noncompliant rule is created. **Most Voted**
- C. Create an IAM role with permissions to globally open security groups and network ACLs. Create an Amazon Simple Notification Service (Amazon SNS) topic to generate a notification every time the role is assumed by a user.
- D. Configure a service control policy (SCP) that prevents non-administrative users from creating or editing security groups. Create a notification in the ticketing system when a user requests a rule that needs administrator permissions.

Suggested Answer: B

Question #: 745

A company has established a new AWS account. The account is newly provisioned and no changes have been made to the default settings. The company is concerned about the security of the AWS account root user.

What should be done to secure the root user?

- A. Create IAM users for daily administrative tasks. Disable the root user.
- B. Create IAM users for daily administrative tasks. Enable multi-factor authentication on the root user. **Most Voted**
- C. Generate an access key for the root user. Use the access key for daily administration tasks instead of the AWS Management Console.
- D. Provide the root user credentials to the most senior solutions architect. Have the solutions architect use the root user for daily administration tasks.

Suggested Answer: B

Question #: 746

A company is deploying an application that processes streaming data in near-real time. The company plans to use Amazon EC2 instances for the workload. The network architecture must be configurable to provide the lowest possible latency between nodes.

Which combination of network solutions will meet these requirements? (Choose two.)

- A. Enable and configure enhanced networking on each EC2 instance. **Most Voted**
- B. Group the EC2 instances in separate accounts.
- C. Run the EC2 instances in a cluster placement group. **Most Voted**
- D. Attach multiple elastic network interfaces to each EC2 instance.
- E. Use Amazon Elastic Block Store (Amazon EBS) optimized instance types.

Suggested Answer: AC

Question #: 747

A financial services company wants to shut down two data centers and migrate more than 100 TB of data to AWS. The data has an intricate directory structure with millions of small files stored in deep hierarchies of subfolders. Most of the data is unstructured, and the company's file storage consists of SMB-based storage types from multiple vendors. The company does not want to change its applications to access the data after migration.

What should a solutions architect do to meet these requirements with the LEAST operational overhead?

- A. Use AWS Direct Connect to migrate the data to Amazon S3.
- B. Use AWS DataSync to migrate the data to Amazon FSx for Lustre.
- C. Use AWS DataSync to migrate the data to Amazon FSx for Windows File Server. **Most Voted**
- D. Use AWS Direct Connect to migrate the data on-premises file storage to an AWS Storage Gateway volume gateway.

Suggested Answer: C

Question #: 748

A company uses an organization in AWS Organizations to manage AWS accounts that contain applications. The company sets up a dedicated monitoring member account in the organization. The company wants to query and visualize observability data across the accounts by using Amazon CloudWatch.

Which solution will meet these requirements?

- A. Enable CloudWatch cross-account observability for the monitoring account. Deploy an AWS CloudFormation template provided by the monitoring account in each AWS account to share the data with the monitoring account. **Most Voted**
- B. Set up service control policies (SCPs) to provide access to CloudWatch in the monitoring account under the Organizations root organizational unit (OU).
- C. Configure a new IAM user in the monitoring account. In each AWS account, configure an IAM policy to have access to query and visualize the CloudWatch data in the account. Attach the new IAM policy to the new IAM user.

- D. Create a new IAM user in the monitoring account. Create cross-account IAM policies in each AWS account. Attach the IAM policies to the new IAM user.

Suggested Answer: A

Question #: 749

A company's website is used to sell products to the public. The site runs on Amazon EC2 instances in an Auto Scaling group behind an Application Load Balancer (ALB). There is also an Amazon CloudFront distribution, and AWS WAF is being used to protect against SQL injection attacks. The ALB is the origin for the CloudFront distribution. A recent review of security logs revealed an external malicious IP that needs to be blocked from accessing the website.

What should a solutions architect do to protect the application?

- A. Modify the network ACL on the CloudFront distribution to add a deny rule for the malicious IP address.
- B. Modify the configuration of AWS WAF to add an IP match condition to block the malicious IP address. **Most Voted**
- C. Modify the network ACL for the EC2 instances in the target groups behind the ALB to deny the malicious IP address.
- D. Modify the security groups for the EC2 instances in the target groups behind the ALB to deny the malicious IP address.

Suggested Answer: B

Question #: 750

A company sets up an organization in AWS Organizations that contains 10 AWS accounts. A solutions architect must design a solution to provide access to the accounts for several thousand employees. The company has an existing identity provider (IdP). The company wants to use the existing IdP for authentication to AWS.

Which solution will meet these requirements?

- A. Create IAM users for the employees in the required AWS accounts. Connect IAM users to the existing IdP. Configure federated authentication for the IAM users.
- B. Set up AWS account root users with user email addresses and passwords that are synchronized from the existing IdP.
- C. Configure AWS IAM Identity Center (AWS Single Sign-On). Connect IAM Identity Center to the existing IdP. Provision users and groups from the existing IdP. **Most Voted**
- D. Use AWS Resource Access Manager (AWS RAM) to share access to the AWS accounts with the users in the existing IdP.

Suggested Answer: C

Question #: 751

A solutions architect is designing an AWS Identity and Access Management (IAM) authorization model for a company's AWS account. The company has designated five specific employees to have full access to AWS services and resources in the AWS account.

The solutions architect has created an IAM user for each of the five designated employees and has created an IAM user group.

Which solution will meet these requirements?

- A. Attach the AdministratorAccess resource-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.
- B. Attach the SystemAdministrator identity-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.
- C. Attach the AdministratorAccess identity-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.
- D. Attach the SystemAdministrator resource-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.

Suggested Answer: C

Question #: 752

A company has a multi-tier payment processing application that is based on virtual machines (VMs). The communication between the tiers occurs asynchronously through a third-party middleware solution that guarantees exactly-once delivery.

The company needs a solution that requires the least amount of infrastructure management. The solution must guarantee exactly-once delivery for application messaging.

Which combination of actions will meet these requirements? (Choose two.)

- A. Use AWS Lambda for the compute layers in the architecture.
- B. Use Amazon EC2 instances for the compute layers in the architecture.
- C. Use Amazon Simple Notification Service (Amazon SNS) as the messaging component between the compute layers.
- D. Use Amazon Simple Queue Service (Amazon SQS) FIFO queues as the messaging component between the compute layers.

- E. Use containers that are based on Amazon Elastic Kubernetes Service (Amazon EKS) for the compute layers in the architecture.

Suggested Answer: AD

Question #: 751

A solutions architect is designing an AWS Identity and Access Management (IAM) authorization model for a company's AWS account. The company has designated five specific employees to have full access to AWS services and resources in the AWS account.

The solutions architect has created an IAM user for each of the five designated employees and has created an IAM user group.

Which solution will meet these requirements?

- A. Attach the AdministratorAccess resource-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.
- B. Attach the SystemAdministrator identity-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.
- C. Attach the AdministratorAccess identity-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.
- D. Attach the SystemAdministrator resource-based policy to the IAM user group. Place each of the five designated employee IAM users in the IAM user group.

Suggested Answer: C

Question #: 754

A company has users all around the world accessing its HTTP-based application deployed on Amazon EC2 instances in multiple AWS Regions. The company wants to improve the availability and performance of the application. The company also wants to protect the application against common web exploits that may affect availability, compromise security, or consume excessive resources. Static IP addresses are required.

What should a solutions architect recommend to accomplish this?

- A. Put the EC2 instances behind Network Load Balancers (NLBs) in each Region. Deploy AWS WAF on the NLBs. Create an accelerator using AWS Global Accelerator and register the NLBs as endpoints.
- B. Put the EC2 instances behind Application Load Balancers (ALBs) in each Region. Deploy AWS WAF on the ALBs. Create an accelerator using AWS Global Accelerator and register the ALBs as endpoints. **Most Voted**
- C. Put the EC2 instances behind Network Load Balancers (NLBs) in each Region. Deploy AWS WAF on the NLBs. Create an Amazon CloudFront distribution with an origin that uses Amazon Route 53 latency-based routing to route requests to the NLBs.
- D. Put the EC2 instances behind Application Load Balancers (ALBs) in each Region. Create an Amazon CloudFront distribution with an origin that uses Amazon Route 53 latency-based routing to route requests to the ALBs. Deploy AWS WAF on the CloudFront distribution.

Suggested Answer: B

Question #: 755

A company's data platform uses an Amazon Aurora MySQL database. The database has multiple read replicas and multiple DB instances across different Availability Zones. Users have recently reported errors from the

database that indicate that there are too many connections. The company wants to reduce the failover time by 20% when a read replica is promoted to primary writer.

Which solution will meet this requirement?

- A. Switch from Aurora to Amazon RDS with Multi-AZ cluster deployment.
- B. Use Amazon RDS Proxy in front of the Aurora database. **Most Voted**
- C. Switch to Amazon DynamoDB with DynamoDB Accelerator (DAX) for read connections.
- D. Switch to Amazon Redshift with relocation capability.

Suggested Answer: B

Question #: 756

A company stores text files in Amazon S3. The text files include customer chat messages, date and time information, and customer personally identifiable information (PII).

The company needs a solution to provide samples of the conversations to an external service provider for quality control. The external service provider needs to randomly pick sample conversations up to the most recent conversation. The company must not share the customer PII with the external service provider. The solution must scale when the number of customer conversations increases.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an Object Lambda Access Point. Create an AWS Lambda function that redacts the PII when the function reads the file. Instruct the external service provider to access the Object Lambda Access Point. **Most Voted**

- B. Create a batch process on an Amazon EC2 instance that regularly reads all new files, redacts the PII from the files, and writes the redacted files to a different S3 bucket. Instruct the external service provider to access the bucket that does not contain the PII.
- B. Create a web application on an Amazon EC2 instance that presents a list of the files, redacts the PII from the files, and allows the external service provider to download new versions of the files that have the PII redacted.
- D. Create an Amazon DynamoDB table. Create an AWS Lambda function that reads only the data in the files that does not contain PII. Configure the Lambda function to store the non-PII data in the DynamoDB table when a new file is written to Amazon S3. Grant the external service provider access to the DynamoDB table.

Suggested Answer: A

Question #: 757

A company is running a legacy system on an Amazon EC2 instance. The application code cannot be modified, and the system cannot run on more than one instance. A solutions architect must design a resilient solution that can improve the recovery time for the system.

What should the solutions architect recommend to meet these requirements?

- A. Enable termination protection for the EC2 instance.
- B. Configure the EC2 instance for Multi-AZ deployment.
- C. Create an Amazon CloudWatch alarm to recover the EC2 instance in case of failure. **Most Voted**
- D. Launch the EC2 instance with two Amazon Elastic Block Store (Amazon EBS) volumes that use RAID configurations for storage redundancy.

Suggested Answer: C

Question #: 759

A media company stores movies in Amazon S3. Each movie is stored in a single video file that ranges from 1 GB to 10 GB in size.

The company must be able to provide the streaming content of a movie within 5 minutes of a user purchase. There is higher demand for movies that are less than 20 years old than for movies that are more than 20 years old. The company wants to minimize hosting service costs based on demand.

Which solution will meet these requirements?

- A. Store all media content in Amazon S3. Use S3 Lifecycle policies to move media data into the Infrequent Access tier when the demand for a movie decreases.
- B. Store newer movie video files in S3 Standard. Store older movie video files in S3 Standard-infrequent Access (S3 Standard-IA). When a user orders an older movie, retrieve the video file by using standard retrieval.
- C. Store newer movie video files in S3 Intelligent-Tiering. Store older movie video files in S3 Glacier Flexible Retrieval. When a user orders an older movie, retrieve the video file by using expedited retrieval. **Most Voted**
- D. Store newer movie video files in S3 Standard. Store older movie video files in S3 Glacier Flexible Retrieval. When a user orders an older movie, retrieve the video file by using bulk retrieval.

Suggested Answer: C

Question #: 760

A solutions architect needs to design the architecture for an application that a vendor provides as a Docker container image. The container needs 50 GB of storage available for temporary files. The infrastructure must be

serverless.

Which solution meets these requirements with the LEAST operational overhead?

- A. Create an AWS Lambda function that uses the Docker container image with an Amazon S3 mounted volume that has more than 50 GB of space.
- B. Create an AWS Lambda function that uses the Docker container image with an Amazon Elastic Block Store (Amazon EBS) volume that has more than 50 GB of space.
- C. Create an Amazon Elastic Container Service (Amazon ECS) cluster that uses the AWS Fargate launch type. Create a task definition for the container image with an Amazon Elastic File System (Amazon EFS) volume. Create a service with that task definition. **Most Voted**
- D. Create an Amazon Elastic Container Service (Amazon ECS) cluster that uses the Amazon EC2 launch type with an Amazon Elastic Block Store (Amazon EBS) volume that has more than 50 GB of space. Create a task definition for the container image. Create a service with that task definition.

Suggested Answer: C

Question #: 761

A company needs to use its on-premises LDAP directory service to authenticate its users to the AWS Management Console. The directory service is not compatible with Security Assertion Markup Language (SAML).

Which solution meets these requirements?

- A. Enable AWS IAM Identity Center (AWS Single Sign-On) between AWS and the on-premises LDAP.
- B. Create an IAM policy that uses AWS credentials, and integrate the policy into LDAP.
- C. Set up a process that rotates the IAM credentials whenever LDAP credentials are updated.

- D. Develop an on-premises custom identity broker application or process that uses AWS Security Token Service (AWS STS) to get short-lived credentials. **Most Voted**

Suggested Answer: D

Question #: 762

A company stores multiple Amazon Machine Images (AMIs) in an AWS account to launch its Amazon EC2 instances. The AMIs contain critical data and configurations that are necessary for the company's operations. The company wants to implement a solution that will recover accidentally deleted AMIs quickly and efficiently.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create Amazon Elastic Block Store (Amazon EBS) snapshots of the AMIs. Store the snapshots in a separate AWS account.
- B. Copy all AMIs to another AWS account periodically.
- C. Create a retention rule in Recycle Bin. **Most Voted**
- D. Upload the AMIs to an Amazon S3 bucket that has Cross-Region Replication.

Suggested Answer: C

Question #: 763

A company has 150 TB of archived image data stored on-premises that needs to be moved to the AWS Cloud within the next month. The company's current network connection allows up to 100 Mbps uploads for this

purpose during the night only.

What is the MOST cost-effective mechanism to move this data and meet the migration deadline?

- A. Use AWS Snowmobile to ship the data to AWS.
- B. Order multiple AWS Snowball devices to ship the data to AWS. **Most Voted**
- C. Enable Amazon S3 Transfer Acceleration and securely upload the data.
- D. Create an Amazon S3 VPC endpoint and establish a VPN to upload the data.

Suggested Answer: B

Question #: 764

A company wants to migrate its three-tier application from on premises to AWS. The web tier and the application tier are running on third-party virtual machines (VMs). The database tier is running on MySQL.

The company needs to migrate the application by making the fewest possible changes to the architecture. The company also needs a database solution that can restore data to a specific point in time.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Migrate the web tier and the application tier to Amazon EC2 instances in private subnets. Migrate the database tier to Amazon RDS for MySQL in private subnets.
- B. Migrate the web tier to Amazon EC2 instances in public subnets. Migrate the application tier to EC2 instances in private subnets. Migrate the database tier to Amazon Aurora MySQL in private subnets. **Most Voted**
- C. Migrate the web tier to Amazon EC2 instances in public subnets. Migrate the application tier to EC2 instances in private subnets. Migrate the database tier to Amazon RDS for MySQL in private subnets.

- D. Migrate the web tier and the application tier to Amazon EC2 instances in public subnets. Migrate the database tier to Amazon Aurora MySQL in public subnets.

Suggested Answer: B

Question #: 766

A company's developers want a secure way to gain SSH access on the company's Amazon EC2 instances that run the latest version of Amazon Linux. The developers work remotely and in the corporate office.

The company wants to use AWS services as a part of the solution. The EC2 instances are hosted in a VPC private subnet and access the internet through a NAT gateway that is deployed in a public subnet.

What should a solutions architect do to meet these requirements MOST cost-effectively?

- A. Create a bastion host in the same subnet as the EC2 instances. Grant the `ec2:CreateVpnConnection` IAM permission to the developers. Install EC2 Instance Connect so that the developers can connect to the EC2 instances.
- B. Create an AWS Site-to-Site VPN connection between the corporate network and the VPC. Instruct the developers to use the Site-to-Site VPN connection to access the EC2 instances when the developers are on the corporate network. Instruct the developers to set up another VPN connection for access when they work remotely.
- C. Create a bastion host in the public subnet of the VPC. Configure the security groups and SSH keys of the bastion host to only allow connections and SSH authentication from the developers' corporate and remote networks. Instruct the developers to connect through the bastion host by using SSH to reach the EC2 instances.
- D. Attach the `AmazonSSMManagedInstanceCore` IAM policy to an IAM role that is associated with the EC2 instances. Instruct the developers to use AWS Systems Manager Session Manager to access the EC2 instances. **Most Voted**

Suggested Answer: D

Question #: 767

A pharmaceutical company is developing a new drug. The volume of data that the company generates has grown exponentially over the past few months. The company's researchers regularly require a subset of the entire dataset to be immediately available with minimal lag. However, the entire dataset does not need to be accessed on a daily basis. All the data currently resides in on-premises storage arrays, and the company wants to reduce ongoing capital expenses.

Which storage solution should a solutions architect recommend to meet these requirements?

- A. Run AWS DataSync as a scheduled cron job to migrate the data to an Amazon S3 bucket on an ongoing basis.
- B. Deploy an AWS Storage Gateway file gateway with an Amazon S3 bucket as the target storage. Migrate the data to the Storage Gateway appliance.
- C. Deploy an AWS Storage Gateway volume gateway with cached volumes with an Amazon S3 bucket as the target storage. Migrate the data to the Storage Gateway appliance. **Most Voted**
- D. Configure an AWS Site-to-Site VPN connection from the on-premises environment to AWS. Migrate data to an Amazon Elastic File System (Amazon EFS) file system.

Suggested Answer: C

Question #: 768

A company has a business-critical application that runs on Amazon EC2 instances. The application stores data in an Amazon DynamoDB table. The company must be able to revert the table to any point within the last 24 hours.

Which solution meets these requirements with the LEAST operational overhead?

- A. Configure point-in-time recovery for the table. **Most Voted**
- B. Use AWS Backup for the table.
- C. Use an AWS Lambda function to make an on-demand backup of the table every hour.
- D. Turn on streams on the table to capture a log of all changes to the table in the last 24 hours. Store a copy of the stream in an Amazon S3 bucket.

Suggested Answer: A

Question #: 769

A company hosts an application used to upload files to an Amazon S3 bucket. Once uploaded, the files are processed to extract metadata, which takes less than 5 seconds. The volume and frequency of the uploads varies from a few files each hour to hundreds of concurrent uploads. The company has asked a solutions architect to design a cost-effective architecture that will meet these requirements.

What should the solutions architect recommend?

- A. Configure AWS CloudTrail trails to log S3 API calls. Use AWS AppSync to process the files.
- B. Configure an object-created event notification within the S3 bucket to invoke an AWS Lambda function to process the files. **Most Voted**
- C. Configure Amazon Kinesis Data Streams to process and send data to Amazon S3. Invoke an AWS Lambda function to process the files.

- D. Configure an Amazon Simple Notification Service (Amazon SNS) topic to process the files uploaded to Amazon S3. Invoke an AWS Lambda function to process the files.

Suggested Answer: B

Question #: 770

A company's application is deployed on Amazon EC2 instances and uses AWS Lambda functions for an event-driven architecture. The company uses nonproduction development environments in a different AWS account to test new features before the company deploys the features to production.

The production instances show constant usage because of customers in different time zones. The company uses nonproduction instances only during business hours on weekdays. The company does not use the nonproduction instances on the weekends. The company wants to optimize the costs to run its application on AWS.

Which solution will meet these requirements MOST cost-effectively?

- A. Use On-Demand Instances for the production instances. Use Dedicated Hosts for the nonproduction instances on weekends only.
- B. Use Reserved Instances for the production instances and the nonproduction instances. Shut down the nonproduction instances when not in use.
- C. Use Compute Savings Plans for the production instances. Use On-Demand Instances for the nonproduction instances. Shut down the nonproduction instances when not in use. **Most Voted**
- D. Use Dedicated Hosts for the production instances. Use EC2 Instance Savings Plans for the nonproduction instances.

Suggested Answer: C

Question #: 771

A company stores data in an on-premises Oracle relational database. The company needs to make the data available in Amazon Aurora PostgreSQL for analysis. The company uses an AWS Site-to-Site VPN connection to connect its on-premises network to AWS.

The company must capture the changes that occur to the source database during the migration to Aurora PostgreSQL.

Which solution will meet these requirements?

- A. Use the AWS Schema Conversion Tool (AWS SCT) to convert the Oracle schema to Aurora PostgreSQL schema. Use the AWS Database Migration Service (AWS DMS) full-load migration task to migrate the data.
- B. Use AWS DataSync to migrate the data to an Amazon S3 bucket. Import the S3 data to Aurora PostgreSQL by using the Aurora PostgreSQL `aws_s3` extension.
- C. Use the AWS Schema Conversion Tool (AWS SCT) to convert the Oracle schema to Aurora PostgreSQL schema. Use AWS Database Migration Service (AWS DMS) to migrate the existing data and replicate the ongoing changes. **Most Voted**
- D. Use an AWS Snowball device to migrate the data to an Amazon S3 bucket. Import the S3 data to Aurora PostgreSQL by using the Aurora PostgreSQL `aws_s3` extension.

Suggested Answer: C

Question #: 773

An ecommerce company is running a seasonal online sale. The company hosts its website on Amazon EC2 instances spanning multiple Availability Zones. The company wants its website to manage sudden traffic increases during the sale.

Which solution will meet these requirements MOST cost-effectively?

- A. Create an Auto Scaling group that is large enough to handle peak traffic load. Stop half of the Amazon EC2 instances. Configure the Auto Scaling group to use the stopped instances to scale out when traffic increases.
- B. Create an Auto Scaling group for the website. Set the minimum size of the Auto Scaling group so that it can handle high traffic volumes without the need to scale out.
- C. Use Amazon CloudFront and Amazon ElastiCache to cache dynamic content with an Auto Scaling group set as the origin. Configure the Auto Scaling group with the instances necessary to populate CloudFront and ElastiCache. Scale in after the cache is fully populated.
- D. Configure an Auto Scaling group to scale out as traffic increases. Create a launch template to start new instances from a preconfigured Amazon Machine Image (AMI).

Suggested Answer: D

Question #: 775

Use Amazon Elastic Kubernetes Service (Amazon EKS) with Amazon EC2 worker nodes.

A company has deployed an application in an AWS account. The application consists of microservices that run on AWS Lambda and Amazon Elastic Kubernetes Service (Amazon EKS). A separate team supports each microservice. The company has multiple AWS accounts and wants to give each team its own account for its microservices.

A solutions architect needs to design a solution that will provide service-to-service communication over HTTPS (port 443). The solution also must provide a service registry for service discovery.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Create an inspection VPC. Deploy an AWS Network Firewall firewall to the inspection VPC. Attach the inspection VPC to a new transit gateway. Route VPC-to-VPC traffic to the inspection VPC. Apply firewall rules to allow only HTTPS communication.
- B. Create a VPC Lattice service network. Associate the microservices with the service network. Define HTTPS listeners for each service. Register microservice compute resources as targets. Identify VPCs that need to communicate with the services. Associate those VPCs with the service network. **Most Voted**
- C. Create a Network Load Balancer (NLB) with an HTTPS listener and target groups for each microservice. Create an AWS PrivateLink endpoint service for each microservice. Create an interface VPC endpoint in each VPC that needs to consume that microservice.
- D. Create peering connections between VPCs that contain microservices. Create a prefix list for each service that requires a connection to a client. Create route tables to route traffic to the appropriate VPC. Create security groups to allow only HTTPS communication.

Suggested Answer: B

Question #: 776

A company has a mobile game that reads most of its metadata from an Amazon RDS DB instance. As the game increased in popularity, developers noticed slowdowns related to the game's metadata load times. Performance metrics indicate that simply scaling the database will not help. A solutions architect must explore all options that include capabilities for snapshots, replication, and sub-millisecond response times.

What should the solutions architect recommend to solve these issues?

- A. Migrate the database to Amazon Aurora with Aurora Replicas.
- B. Migrate the database to Amazon DynamoDB with global tables.
- C. Add an Amazon ElastiCache for Redis layer in front of the database.
- D. Add an Amazon ElastiCache for Memcached layer in front of the database.

Suggested Answer: C

Question #: 777

A company uses AWS Organizations for its multi-account AWS setup. The security organizational unit (OU) of the company needs to share approved Amazon Machine Images (AMIs) with the development OU. The AMIs are created by using AWS Key Management Service (AWS KMS) encrypted snapshots.

Which solution will meet these requirements? (Choose two.)

- A. Add the development team's OU Amazon Resource Name (ARN) to the launch permission list for the AMIs.
- B. Add the Organizations root Amazon Resource Name (ARN) to the launch permission list for the AMIs.
- C. Update the key policy to allow the development team's OU to use the AWS KMS keys that are used to decrypt the snapshots.
- D. Add the development team's account Amazon Resource Name (ARN) to the launch permission list for the AMIs.
- E. Recreate the AWS KMS key. Add a key policy to allow the Organizations root Amazon Resource Name (ARN) to use the AWS KMS key.

Suggested Answer: AC

Question #: 778

A data analytics company has 80 offices that are distributed globally. Each office hosts 1 PB of data and has between 1 and 2 Gbps of internet bandwidth.

The company needs to perform a one-time migration of a large amount of data from its offices to Amazon S3. The company must complete the migration within 4 weeks.

Which solution will meet these requirements MOST cost-effectively?

- A. Establish a new 10 Gbps AWS Direct Connect connection to each office. Transfer the data to Amazon S3.
- B. Use multiple AWS Snowball Edge storage-optimized devices to store and transfer the data to Amazon S3. **Most Voted**
- C. Use an AWS Snowmobile to store and transfer the data to Amazon S3.
- D. Set up an AWS Storage Gateway Volume Gateway to transfer the data to Amazon S3.

Suggested Answer: B

Question #: 779

A company has an Amazon Elastic File System (Amazon EFS) file system that contains a reference dataset. The company has applications on Amazon EC2 instances that need to read the dataset. However, the applications must not be able to change the dataset. The company wants to use IAM access control to prevent the applications from being able to modify or delete the dataset.

Which solution will meet these requirements?

- A. Mount the EFS file system in read-only mode from within the EC2 instances.
- B. Create a resource policy for the EFS file system that denies the elasticfilesystem:ClientWrite action to the IAM roles that are attached to the EC2 instances. **Most Voted**
- C. Create an identity policy for the EFS file system that denies the elasticfilesystem:ClientWrite action on the EFS file system.
- D. Create an EFS access point for each application. Use Portable Operating System Interface (POSIX) file permissions to allow read-only access to files in the root directory.

Suggested Answer: B

Question #: 780

A company has hired an external vendor to perform work in the company's AWS account. The vendor uses an automated tool that is hosted in an AWS account that the vendor owns. The vendor does not have IAM access to the company's AWS account. The company needs to grant the vendor access to the company's AWS account.

Which solution will meet these requirements MOST securely?

- A. Create an IAM role in the company's account to delegate access to the vendor's IAM role. Attach the appropriate IAM policies to the role for the permissions that the vendor requires. **Most Voted**

- B. Create an IAM user in the company's account with a password that meets the password complexity requirements. Attach the appropriate IAM policies to the user for the permissions that the vendor requires.
- C. Create an IAM group in the company's account. Add the automated tool's IAM user from the vendor account to the group. Attach the appropriate IAM policies to the group for the permissions that the vendor requires.
- D. Create an IAM user in the company's account that has a permission boundary that allows the vendor's account. Attach the appropriate IAM policies to the user for the permissions that the vendor requires.

Suggested Answer: A

Question #: 781

A company wants to run its experimental workloads in the AWS Cloud. The company has a budget for cloud spending. The company's CFO is concerned about cloud spending accountability for each department. The CFO wants to receive notification when the spending threshold reaches 60% of the budget. Which solution will meet these requirements?

- A. Use cost allocation tags on AWS resources to label owners. Create usage budgets in AWS Budgets. Add an alert threshold to receive notification when spending exceeds 60% of the budget. **Most Voted**
- B. Use AWS Cost Explorer forecasts to determine resource owners. Use AWS Cost Anomaly Detection to create alert threshold notifications when spending exceeds 60% of the budget.
- C. Use cost allocation tags on AWS resources to label owners. Use AWS Support API on AWS Trusted Advisor to create alert threshold notifications when spending exceeds 60% of the budget.
- D. Use AWS Cost Explorer forecasts to determine resource owners. Create usage budgets in AWS Budgets. Add an alert threshold to receive notification when spending exceeds 60% of the budget.

Suggested Answer: A

Question #: 782

A company wants to deploy an internal web application on AWS. The web application must be accessible only from the company's office. The company needs to download security patches for the web application from the

internet.

The company has created a VPC and has configured an AWS Site-to-Site VPN connection to the company's office. A solutions architect must design a secure architecture for the web application.

Which solution will meet these requirements?

- A. Deploy the web application on Amazon EC2 instances in public subnets behind a public Application Load Balancer (ALB). Attach an internet gateway to the VPC. Set the inbound source of the ALB's security group to 0.0.0.0/0.
- B. Deploy the web application on Amazon EC2 instances in private subnets behind an internal Application Load Balancer (ALB). Deploy NAT gateways in public subnets. Attach an internet gateway to the VPC. Set the inbound source of the ALB's security group to the company's office network CIDR block. **Most Voted**
- C. Deploy the web application on Amazon EC2 instances in public subnets behind an internal Application Load Balancer (ALB). Deploy NAT gateways in private subnets. Attach an internet gateway to the VPC. Set the outbound destination of the ALB's security group to the company's office network CIDR block.
- D. Deploy the web application on Amazon EC2 instances in private subnets behind a public Application Load Balancer (ALB). Attach an internet gateway to the VPC. Set the outbound destination of the ALB's security group to 0.0.0.0/0.

Suggested Answer: B

Question #: 783

A company maintains its accounting records in a custom application that runs on Amazon EC2 instances. The company needs to migrate the data to an AWS managed service for development and maintenance of the application data. The solution must require minimal operational support and provide immutable, cryptographically verifiable logs of data changes.

Which solution will meet these requirements MOST cost-effectively?

- A. Copy the records from the application into an Amazon Redshift cluster.
- B. Copy the records from the application into an Amazon Neptune cluster.
- C. Copy the records from the application into an Amazon Timestream database.

- D. Copy the records from the application into an Amazon Quantum Ledger Database (Amazon QLDB) ledger. **Most Voted**

Suggested Answer: D

Question #: 784

A company's marketing data is uploaded from multiple sources to an Amazon S3 bucket. A series of data preparation jobs aggregate the data for reporting. The data preparation jobs need to run at regular intervals in parallel. A few jobs need to run in a specific order later.

The company wants to remove the operational overhead of job error handling, retry logic, and state management.

Which solution will meet these requirements?

- A. Use an AWS Lambda function to process the data as soon as the data is uploaded to the S3 bucket. Invoke other Lambda functions at regularly scheduled intervals.
- B. Use Amazon Athena to process the data. Use Amazon EventBridge Scheduler to invoke Athena on a regular interval.
- C. Use AWS Glue DataBrew to process the data. Use an AWS Step Functions state machine to run the DataBrew data preparation jobs. **Most Voted**
- D. Use AWS Data Pipeline to process the data. Schedule Data Pipeline to process the data once at midnight.

Suggested Answer: C

Question #: 785

A solutions architect is designing a payment processing application that runs on AWS Lambda in private subnets across multiple Availability Zones. The application uses multiple Lambda functions and processes millions of transactions each day.

The architecture must ensure that the application does not process duplicate payments.

Which solution will meet these requirements?

- A. Use Lambda to retrieve all due payments. Publish the due payments to an Amazon S3 bucket. Configure the S3 bucket with an event notification to invoke another Lambda function to process the due payments.
- B. Use Lambda to retrieve all due payments. Publish the due payments to an Amazon Simple Queue Service (Amazon SQS) queue. Configure another Lambda function to poll the SQS queue and to process the due payments.
- C. Use Lambda to retrieve all due payments. Publish the due payments to an Amazon Simple Queue Service (Amazon SQS) FIFO queue. Configure another Lambda function to poll the FIFO queue and to process the due payments. **Most Voted**
- D. Use Lambda to retrieve all due payments. Store the due payments in an Amazon DynamoDB table. Configure streams on the DynamoDB table to invoke another Lambda function to process the due payments.

Suggested Answer: C

Question #: 786

A company runs multiple workloads in its on-premises data center. The company's data center cannot scale fast enough to meet the company's expanding business needs. The company wants to collect usage and configuration data about the on-premises servers and workloads to plan a migration to AWS.

Which solution will meet these requirements?

- A. Set the home AWS Region in AWS Migration Hub. Use AWS Systems Manager to collect data about the on-premises servers.
- B. Set the home AWS Region in AWS Migration Hub. Use AWS Application Discovery Service to collect data about the on-premises servers.
- C. Use the AWS Schema Conversion Tool (AWS SCT) to create the relevant templates. Use AWS Trusted Advisor to collect data about the on-premises servers.
- D. Use the AWS Schema Conversion Tool (AWS SCT) to create the relevant templates. Use AWS Database Migration Service (AWS DMS) to collect data about the on-premises servers.

Suggested Answer: B

Question #: 788

A company has stored 10 TB of log files in Apache Parquet format in an Amazon S3 bucket. The company occasionally needs to use SQL to analyze the log files.

Which solution will meet these requirements MOST cost-effectively?

- A. Create an Amazon Aurora MySQL database. Migrate the data from the S3 bucket into Aurora by using AWS Database Migration Service (AWS DMS). Issue SQL statements to the Aurora database.
- B. Create an Amazon Redshift cluster. Use Redshift Spectrum to run SQL statements directly on the data in the S3 bucket.
- C. Create an AWS Glue crawler to store and retrieve table metadata from the S3 bucket. Use Amazon Athena to run SQL statements directly on the data in the S3 bucket. **Most Voted**
- D. Create an Amazon EMR cluster. Use Apache Spark SQL to run SQL statements directly on the data in the S3 bucket.

Suggested Answer: C

Question #: 789

A company needs a solution to prevent AWS CloudFormation stacks from deploying AWS Identity and Access Management (IAM) resources that include an inline policy or “*” in the statement. The solution must also prohibit deployment of Amazon EC2 instances with public IP addresses. The company has AWS Control Tower enabled in its organization in AWS Organizations.

Which solution will meet these requirements?

- A. Use AWS Control Tower proactive controls to block deployment of EC2 instances with public IP addresses and inline policies with elevated access or “*”. **Most Voted**
- B. Use AWS Control Tower detective controls to block deployment of EC2 instances with public IP addresses and inline policies with elevated access or “*”.
- C. Use AWS Config to create rules for EC2 and IAM compliance. Configure the rules to run an AWS Systems Manager Session Manager automation to delete a resource when it is not compliant.

- D. Use a service control policy (SCP) to block actions for the EC2 instances and IAM resources if the actions lead to noncompliance. **Most Voted**

Suggested Answer: A

Question #: 790

A company's web application that is hosted in the AWS Cloud recently increased in popularity. The web application currently exists on a single Amazon EC2 instance in a single public subnet. The web application has not been able to meet the demand of the increased web traffic.

The company needs a solution that will provide high availability and scalability to meet the increased user demand without rewriting the web application.

Which combination of steps will meet these requirements? (Choose two.)

- A. Replace the EC2 instance with a larger compute optimized instance.
- B. Configure Amazon EC2 Auto Scaling with multiple Availability Zones in private subnets. **Most Voted**
- C. Configure a NAT gateway in a public subnet to handle web requests.
- D. Replace the EC2 instance with a larger memory optimized instance.
- E. Configure an Application Load Balancer in a public subnet to distribute web traffic. **Most Voted**

Suggested Answer: BE

Question #: 791

A company has AWS Lambda functions that use environment variables. The company does not want its developers to see environment variables in plaintext.

Which solution will meet these requirements?

- A. Deploy code to Amazon EC2 instances instead of using Lambda functions.
- B. Configure SSL encryption on the Lambda functions to use AWS CloudHSM to store and encrypt the environment variables.

- C. Create a certificate in AWS Certificate Manager (ACM). Configure the Lambda functions to use the certificate to encrypt the environment variables.
- D. Create an AWS Key Management Service (AWS KMS) key. Enable encryption helpers on the Lambda functions to use the KMS key to store and encrypt the environment variables.

Suggested Answer: D

Question #: 792

An analytics company uses Amazon VPC to run its multi-tier services. The company wants to use RESTful APIs to offer a web analytics service to millions of users. Users must be verified by using an authentication service to access the APIs.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Configure an Amazon Cognito user pool for user authentication. Implement Amazon API Gateway REST APIs with a Cognito authorizer. **Most Voted**
- B. Configure an Amazon Cognito identity pool for user authentication. Implement Amazon API Gateway HTTP APIs with a Cognito authorizer.
- C. Configure an AWS Lambda function to handle user authentication. Implement Amazon API Gateway REST APIs with a Lambda authorizer.
- D. Configure an IAM user to handle user authentication. Implement Amazon API Gateway HTTP APIs with an IAM authorizer.

Suggested Answer: A

Question #: 793

A company has a mobile app for customers. The app's data is sensitive and must be encrypted at rest. The company uses AWS Key Management Service (AWS KMS).

The company needs a solution that prevents the accidental deletion of KMS keys. The solution must use Amazon Simple Notification Service (Amazon SNS) to send an email notification to administrators when a user

attempts to delete a KMS key.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an Amazon EventBridge rule that reacts when a user tries to delete a KMS key. Configure an AWS Config rule that cancels any deletion of a KMS key. Add the AWS Config rule as a target of the EventBridge rule. Create an SNS topic that notifies the administrators.
- B. Create an AWS Lambda function that has custom logic to prevent KMS key deletion. Create an Amazon CloudWatch alarm that is activated when a user tries to delete a KMS key. Create an Amazon EventBridge rule that invokes the Lambda function when the DeleteKey operation is performed. Create an SNS topic. Configure the EventBridge rule to publish an SNS message that notifies the administrators.
- C. Create an Amazon EventBridge rule that reacts when the KMS DeleteKey operation is performed. Configure the rule to initiate an AWS Systems Manager Automation runbook. Configure the runbook to cancel the deletion of the KMS key. Create an SNS topic. Configure the EventBridge rule to publish an SNS message that notifies the administrators.
- D. Create an AWS CloudTrail trail. Configure the trail to deliver logs to a new Amazon CloudWatch log group. Create a CloudWatch alarm based on the metric filter for the CloudWatch log group. Configure the alarm to use Amazon SNS to notify the administrators when the KMS DeleteKey operation is performed.

Suggested Answer: C

Question #: 794

A company wants to analyze and generate reports to track the usage of its mobile app. The app is popular and has a global user base. The company uses a custom report building program to analyze application usage.

The program generates multiple reports during the last week of each month. The program takes less than 10 minutes to produce each report. The company rarely uses the program to generate reports outside of the last week of each month. The company wants to generate reports in the least amount of time when the reports are requested.

Which solution will meet these requirements MOST cost-effectively?

- A. Run the program by using Amazon EC2 On-Demand Instances. Create an Amazon EventBridge rule to start the EC2 instances when reports are requested. Run the EC2 instances continuously during the last week of each month.
- B. Run the program in AWS Lambda. Create an Amazon EventBridge rule to run a Lambda function when reports are requested.
- C. Run the program in Amazon Elastic Container Service (Amazon ECS). Schedule Amazon ECS to run the program when reports are requested.
- D. Run the program by using Amazon EC2 Spot Instances. Create an Amazon EventBridge rule to start the EC2 instances when reports are requested. Run the EC2 instances continuously during the last week of each month.

Suggested Answer: B

Question #: 795

A company is designing a tightly coupled high performance computing (HPC) environment in the AWS Cloud. The company needs to include features that will optimize the HPC environment for networking and storage.

Which combination of solutions will meet these requirements? (Choose two.)

- A. Create an accelerator in AWS Global Accelerator. Configure custom routing for the accelerator.
- B. Create an Amazon FSx for Lustre file system. Configure the file system with scratch storage.
- C. Create an Amazon CloudFront distribution. Configure the viewer protocol policy to be HTTP and HTTPS.
- D. Launch Amazon EC2 instances. Attach an Elastic Fabric Adapter (EFA) to the instances.
- E. Create an AWS Elastic Beanstalk deployment to manage the environment.

Suggested Answer: BD

Question #: 796

A company needs a solution to prevent photos with unwanted content from being uploaded to the company's web application. The solution must not involve training a machine learning (ML) model.

Which solution will meet these requirements?

- A. Create and deploy a model by using Amazon SageMaker Autopilot. Create a real-time endpoint that the web application invokes when new photos are uploaded.
- B. Create an AWS Lambda function that uses Amazon Rekognition to detect unwanted content. Create a Lambda function URL that the web application invokes when new photos are uploaded. **Most Voted**
- C. Create an Amazon CloudFront function that uses Amazon Comprehend to detect unwanted content. Associate the function with the web application.
- D. Create an AWS Lambda function that uses Amazon Rekognition Video to detect unwanted content. Create a Lambda function URL that the web application invokes when new photos are uploaded.

Suggested Answer: B

Question #: 797

A company uses AWS to run its ecommerce platform. The platform is critical to the company's operations and has a high volume of traffic and transactions. The company configures a multi-factor authentication (MFA) device to secure its AWS account root user credentials. The company wants to ensure that it will not lose access to the root user account if the MFA device is lost.

Which solution will meet these requirements?

- A. Set up a backup administrator account that the company can use to log in if the company loses the MFA device.
- B. Add multiple MFA devices for the root user account to handle the disaster scenario.
- C. Create a new administrator account when the company cannot access the root account.
- D. Attach the administrator policy to another IAM user when the company cannot access the root account.

Suggested Answer: B

Question #: 798

A social media company is creating a rewards program website for its users. The company gives users points when users create and upload videos to the website. Users redeem their points for gifts or discounts from the

company's affiliated partners. A unique ID identifies users. The partners refer to this ID to verify user eligibility for rewards.

The partners want to receive notification of user IDs through an HTTP endpoint when the company gives users points. Hundreds of vendors are interested in becoming affiliated partners every day. The company wants to design an architecture that gives the website the ability to add partners rapidly in a scalable way.

Which solution will meet these requirements with the LEAST implementation effort?

- A. Create an Amazon Timestream database to keep a list of affiliated partners. Implement an AWS Lambda function to read the list. Configure the Lambda function to send user IDs to each partner when the company gives users points.
- B. Create an Amazon Simple Notification Service (Amazon SNS) topic. Choose an endpoint protocol. Subscribe the partners to the topic. Publish user IDs to the topic when the company gives users points. **Most Voted**
- C. Create an AWS Step Functions state machine. Create a task for every affiliated partner. Invoke the state machine with user IDs as input when the company gives users points.
- D. Create a data stream in Amazon Kinesis Data Streams. Implement producer and consumer applications. Store a list of affiliated partners in the data stream. Send user IDs when the company gives users points.

Suggested Answer: B

Question #: 799

A company needs to extract the names of ingredients from recipe records that are stored as text files in an Amazon S3 bucket. A web application will use the ingredient names to query an Amazon DynamoDB table and determine a nutrition score.

The application can handle non-food records and errors. The company does not have any employees who have machine learning knowledge to develop this solution.

Which solution will meet these requirements MOST cost-effectively?

- A. Use S3 Event Notifications to invoke an AWS Lambda function when PutObject requests occur. Program the Lambda function to analyze the object and extract the ingredient names by using Amazon Comprehend. Store the Amazon Comprehend output in the DynamoDB table. **Most Voted**
- B. Use an Amazon EventBridge rule to invoke an AWS Lambda function when PutObject requests occur. Program the Lambda function to analyze the object by using Amazon Forecast to extract the ingredient names. Store the Forecast output in the DynamoDB table.
- C. Use S3 Event Notifications to invoke an AWS Lambda function when PutObject requests occur. Use Amazon Polly to create audio recordings of the recipe records. Save the audio files in the S3 bucket. Use Amazon Simple Notification Service (Amazon SNS) to send a URL as a message to employees. Instruct the employees to listen to the audio files and calculate the nutrition score. Store the ingredient names in the DynamoDB table.
- D. Use an Amazon EventBridge rule to invoke an AWS Lambda function when a PutObject request occurs. Program the Lambda function to analyze the object and extract the ingredient names by using Amazon SageMaker. Store the inference output from the SageMaker endpoint in the DynamoDB table.

Suggested Answer: A

Question #: 800

A company needs to create an AWS Lambda function that will run in a VPC in the company's primary AWS account. The Lambda function needs to access files that the company stores in an Amazon Elastic File System (Amazon EFS) file system. The EFS file system is located in a secondary AWS account. As the company adds files to the file system, the solution must scale to meet the demand.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a new EFS file system in the primary account. Use AWS DataSync to copy the contents of the original EFS file system to the new EFS file system.
- B. Create a VPC peering connection between the VPCs that are in the primary account and the secondary account. **Most Voted**
- C. Create a second Lambda function in the secondary account that has a mount that is configured for the file system. Use the primary account's Lambda function to invoke the secondary account's Lambda function.
- D. Move the contents of the file system to a Lambda layer. Configure the Lambda layer's permissions to allow the company's secondary account to use the Lambda layer.

Suggested Answer: B

Question #: 801

A financial company needs to handle highly sensitive data. The company will store the data in an Amazon S3 bucket. The company needs to ensure that the data is encrypted in transit and at rest. The company must manage the encryption keys outside the AWS Cloud.

Which solution will meet these requirements?

- A. Encrypt the data in the S3 bucket with server-side encryption (SSE) that uses an AWS Key Management Service (AWS KMS) customer managed key.
- B. Encrypt the data in the S3 bucket with server-side encryption (SSE) that uses an AWS Key Management Service (AWS KMS) AWS managed key.
- C. Encrypt the data in the S3 bucket with the default server-side encryption (SSE).
- D. Encrypt the data at the company's data center before storing the data in the S3 bucket. **Most Voted**

Suggested Answer: D

Question #: 802

A company wants to run its payment application on AWS. The application receives payment notifications from mobile devices. Payment notifications require a basic validation before they are sent for further processing.

The backend processing application is long running and requires compute and memory to be adjusted. The company does not want to manage the infrastructure.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an Amazon Simple Queue Service (Amazon SQS) queue. Integrate the queue with an Amazon EventBridge rule to receive payment notifications from mobile devices. Configure the rule to validate payment

notifications and send the notifications to the backend application. Deploy the backend application on Amazon Elastic Kubernetes Service (Amazon EKS) Anywhere. Create a standalone cluster.

- B. Create an Amazon API Gateway API. Integrate the API with an AWS Step Functions state machine to receive payment notifications from mobile devices. Invoke the state machine to validate payment notifications and send the notifications to the backend application. Deploy the backend application on Amazon Elastic Kubernetes Service (Amazon EKS). Configure an EKS cluster with self-managed nodes.
- C. Create an Amazon Simple Queue Service (Amazon SQS) queue. Integrate the queue with an Amazon EventBridge rule to receive payment notifications from mobile devices. Configure the rule to validate payment notifications and send the notifications to the backend application. Deploy the backend application on Amazon EC2 Spot Instances. Configure a Spot Fleet with a default allocation strategy.
- D. Create an Amazon API Gateway API. Integrate the API with AWS Lambda to receive payment notifications from mobile devices. Invoke a Lambda function to validate payment notifications and send the notifications to the backend application. Deploy the backend application on Amazon Elastic Container Service (Amazon ECS). Configure Amazon ECS with an AWS Fargate launch type. **Most Voted**

Suggested Answer: D

Question #: 803

A solutions architect is designing a user authentication solution for a company. The solution must invoke two-factor authentication for users that log in from inconsistent geographical locations, IP addresses, or devices. The solution must also be able to scale up to accommodate millions of users.

Which solution will meet these requirements?

- A. Configure Amazon Cognito user pools for user authentication. Enable the risk-based adaptive authentication feature with multifactor authentication (MFA). **Most Voted**
- B. Configure Amazon Cognito identity pools for user authentication. Enable multi-factor authentication (MFA).
- C. Configure AWS Identity and Access Management (IAM) users for user authentication. Attach an IAM policy that allows the AllowManageOwnUserMFA action.

- D. Configure AWS IAM Identity Center (AWS Single Sign-On) authentication for user authentication. Configure the permission sets to require multi-factor authentication (MFA).

Suggested Answer: A

Question #: 804

A company has an Amazon S3 data lake. The company needs a solution that transforms the data from the data lake and loads the data into a data warehouse every day. The data warehouse must have massively parallel processing (MPP) capabilities.

Data analysts then need to create and train machine learning (ML) models by using SQL commands on the data. The solution must use serverless AWS services wherever possible.

Which solution will meet these requirements?

- A. Run a daily Amazon EMR job to transform the data and load the data into Amazon Redshift. Use Amazon Redshift ML to create and train the ML models.
- B. Run a daily Amazon EMR job to transform the data and load the data into Amazon Aurora Serverless. Use Amazon Aurora ML to create and train the ML models.
- C. Run a daily AWS Glue job to transform the data and load the data into Amazon Redshift Serverless. Use Amazon Redshift ML to create and train the ML models. **Most Voted**
- D. Run a daily AWS Glue job to transform the data and load the data into Amazon Athena tables. Use Amazon Athena ML to create and train the ML models.

Suggested Answer: C

Question #: 805

A company runs containers in a Kubernetes environment in the company's local data center. The company wants to use Amazon Elastic Kubernetes Service (Amazon EKS) and other AWS managed services. Data must remain locally in the company's data center and cannot be stored in any remote site or cloud to maintain compliance.

Which solution will meet these requirements?

- A. Deploy AWS Local Zones in the company's data center.
- B. Use an AWS Snowmobile in the company's data center.
- C. Install an AWS Outposts rack in the company's data center. **Most Voted**
- D. Install an AWS Snowball Edge Storage Optimized node in the data center.

Suggested Answer: C

Question #: 806

A social media company has workloads that collect and process data. The workloads store the data in on-premises NFS storage. The data store cannot scale fast enough to meet the company's expanding business needs. The company wants to migrate the current data store to AWS.

Which solution will meet these requirements MOST cost-effectively?

- A. Set up an AWS Storage Gateway Volume Gateway. Use an Amazon S3 Lifecycle policy to transition the data to the appropriate storage class.
- B. Set up an AWS Storage Gateway Amazon S3 File Gateway. Use an Amazon S3 Lifecycle policy to transition the data to the appropriate storage class. **Most Voted**
- C. Use the Amazon Elastic File System (Amazon EFS) Standard-Infrequent Access (Standard-IA) storage class. Activate the infrequent access lifecycle policy.
- D. Use the Amazon Elastic File System (Amazon EFS) One Zone-Infrequent Access (One Zone-IA) storage class. Activate the infrequent access lifecycle policy.

Suggested Answer: B

Question #: 807

A company uses high concurrency AWS Lambda functions to process a constantly increasing number of messages in a message queue during marketing events. The Lambda functions use CPU intensive code to process the messages. The company wants to reduce the compute costs and to maintain service latency for its customers.

Which solution will meet these requirements?

- A. Configure reserved concurrency for the Lambda functions. Decrease the memory allocated to the Lambda functions.
- B. Configure reserved concurrency for the Lambda functions. Increase the memory according to AWS Compute Optimizer recommendations.
- C. Configure provisioned concurrency for the Lambda functions. Decrease the memory allocated to the Lambda functions.
- D. Configure provisioned concurrency for the Lambda functions. Increase the memory according to AWS Compute Optimizer recommendations. **Most Voted**

Suggested Answer: D

Question #: 808

A company runs its workloads on Amazon Elastic Container Service (Amazon ECS). The container images that the ECS task definition uses need to be scanned for Common Vulnerabilities and Exposures (CVEs). New container images that are created also need to be scanned.

Which solution will meet these requirements with the FEWEST changes to the workloads?

- A. Use Amazon Elastic Container Registry (Amazon ECR) as a private image repository to store the container images. Specify scan on push filters for the ECR basic scan. **Most Voted**
- B. Store the container images in an Amazon S3 bucket. Use Amazon Macie to scan the images. Use an S3 Event Notification to initiate a Macie scan for every event with an s3:ObjectCreated:Put event type.
- C. Deploy the workloads to Amazon Elastic Kubernetes Service (Amazon EKS). Use Amazon Elastic Container Registry (Amazon ECR) as a private image repository. Specify scan on push filters for the ECR enhanced scan.

- D. Store the container images in an Amazon S3 bucket that has versioning enabled. Configure an S3 Event Notification for s3:ObjectCreated:* events to invoke an AWS Lambda function. Configure the Lambda function to initiate an Amazon Inspector scan.

Suggested Answer: A

Question #: 809

A company uses an AWS Batch job to run its end-of-day sales process. The company needs a serverless solution that will invoke a third-party reporting application when the AWS Batch job is successful. The reporting application has an HTTP API interface that uses username and password authentication.

Which solution will meet these requirements?

- A. Configure an Amazon EventBridge rule to match incoming AWS Batch job SUCCEEDED events. Configure the third-party API as an EventBridge API destination with a username and password. Set the API destination as the EventBridge rule target. **Most Voted**
- B. Configure Amazon EventBridge Scheduler to match incoming AWS Batch job SUCCEEDED events. Configure an AWS Lambda function to invoke the third-party API by using a username and password. Set the Lambda function as the EventBridge rule target. **Most Voted**
- C. Configure an AWS Batch job to publish job SUCCEEDED events to an Amazon API Gateway REST API. Configure an HTTP proxy integration on the API Gateway REST API to invoke the third-party API by using a username and password.
- D. Configure an AWS Batch job to publish job SUCCEEDED events to an Amazon API Gateway REST API. Configure a proxy integration on the API Gateway REST API to an AWS Lambda function. Configure the Lambda function to invoke the third-party API by using a username and password.

Suggested Answer: A

Question #: 810

A company collects and processes data from a vendor. The vendor stores its data in an Amazon RDS for MySQL database in the vendor's own AWS account. The company's VPC does not have an internet gateway, an AWS Direct Connect connection, or an AWS Site-to-Site VPN connection. The company needs to access the data that is in the vendor database.

Which solution will meet this requirement?

- A. Instruct the vendor to sign up for the AWS Hosted Connection Direct Connect Program. Use VPC peering to connect the company's VPC and the vendor's VPC.
- B. Configure a client VPN connection between the company's VPC and the vendor's VPC. Use VPC peering to connect the company's VPC and the vendor's VPC.
- C. Instruct the vendor to create a Network Load Balancer (NLB). Place the NLB in front of the Amazon RDS for MySQL database. Use AWS PrivateLink to integrate the company's VPC and the vendor's VPC. **Most Voted**
- D. Use AWS Transit Gateway to integrate the company's VPC and the vendor's VPC. Use VPC peering to connect the company's VPC and the vendor's VPC.

Suggested Answer: C

Question #: 811

A company wants to set up Amazon Managed Grafana as its visualization tool. The company wants to visualize data from its Amazon RDS database as one data source. The company needs a secure solution that will not expose the data over the internet.

Which solution will meet these requirements?

- A. Create an Amazon Managed Grafana workspace without a VPC. Create a public endpoint for the RDS database. Configure the public endpoint as a data source in Amazon Managed Grafana.
- B. Create an Amazon Managed Grafana workspace in a VPC. Create a private endpoint for the RDS database. Configure the private endpoint as a data source in Amazon Managed Grafana. **Most Voted**

- C. Create an Amazon Managed Grafana workspace without a VPC. Create an AWS PrivateLink endpoint to establish a connection between Amazon Managed Grafana and Amazon RDS. Set up Amazon RDS as a data source in Amazon Managed Grafana. **Most Voted**
- D. Create an Amazon Managed Grafana workspace in a VPC. Create a public endpoint for the RDS database. Configure the public endpoint as a data source in Amazon Managed Grafana.

Suggested Answer: B

Question #: 812

A company hosts a data lake on Amazon S3. The data lake ingests data in Apache Parquet format from various data sources. The company uses multiple transformation steps to prepare the ingested data. The steps include filtering of anomalies, normalizing of data to standard date and time values, and generation of aggregates for analyses.

The company must store the transformed data in S3 buckets that data analysts access. The company needs a prebuilt solution for data transformation that does not require code. The solution must provide data lineage and data profiling. The company needs to share the data transformation steps with employees throughout the company.

Which solution will meet these requirements?

- A. Configure an AWS Glue Studio visual canvas to transform the data. Share the transformation steps with employees by using AWS Glue jobs.
- B. Configure Amazon EMR Serverless to transform the data. Share the transformation steps with employees by using EMR Serverless jobs.
- C. Configure AWS Glue DataBrew to transform the data. Share the transformation steps with employees by using DataBrew recipes.
- D. Create Amazon Athena tables for the data. Write Athena SQL queries to transform the data. Share the Athena SQL queries with employees.

Suggested Answer: C

Question #: 813

A solutions architect runs a web application on multiple Amazon EC2 instances that are in individual target groups behind an Application Load Balancer (ALB). Users can reach the application through a public website.

The solutions architect wants to allow engineers to use a development version of the website to access one specific development EC2 instance to test new features for the application. The solutions architect wants to use an Amazon Route 53 hosted zone to give the engineers access to the development instance. The solution must automatically route to the development instance even if the development instance is replaced.

Which solution will meet these requirements?

- A. Create an A Record for the development website that has the value set to the ALB. Create a listener rule on the ALB that forwards requests for the development website to the target group that contains the development instance. **Most Voted**
- B. Recreate the development instance with a public IP address. Create an A Record for the development website that has the value set to the public IP address of the development instance.
- C. Create an A Record for the development website that has the value set to the ALB. Create a listener rule on the ALB to redirect requests for the development website to the public IP address of the development instance.
- D. Place all the instances in the same target group. Create an A Record for the development website. Set the value to the ALB. Create a listener rule on the ALB that forwards requests for the development website to the target group.

Suggested Answer: A

Question #: 814

A company runs a container application on a Kubernetes cluster in the company's data center. The application uses Advanced Message Queuing Protocol (AMQP) to communicate with a message queue. The data center cannot scale fast enough to meet the company's expanding business needs. The company wants to migrate the workloads to AWS.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Migrate the container application to Amazon Elastic Container Service (Amazon ECS). Use Amazon Simple Queue Service (Amazon SQS) to retrieve the messages.
- B. Migrate the container application to Amazon Elastic Kubernetes Service (Amazon EKS). Use Amazon MQ to retrieve the messages. **Most Voted**
- C. Use highly available Amazon EC2 instances to run the application. Use Amazon MQ to retrieve the messages.
- D. Use AWS Lambda functions to run the application. Use Amazon Simple Queue Service (Amazon SQS) to retrieve the messages.

Suggested Answer: B

Question #: 815

An online gaming company hosts its platform on Amazon EC2 instances behind Network Load Balancers (NLBs) across multiple AWS Regions. The NLBs can route requests to targets over the internet. The company wants to improve the customer playing experience by reducing end-to-end load time for its global customer base.

Which solution will meet these requirements?

- A. Create Application Load Balancers (ALBs) in each Region to replace the existing NLBs. Register the existing EC2 instances as targets for the ALBs in each Region.
- B. Configure Amazon Route 53 to route equally weighted traffic to the NLBs in each Region.
- C. Create additional NLBs and EC2 instances in other Regions where the company has large customer bases.
- D. Create a standard accelerator in AWS Global Accelerator. Configure the existing NLBs as target endpoints. **Most Voted**

Suggested Answer: D

Question #: 816

A company has an on-premises application that uses SFTP to collect financial data from multiple vendors. The company is migrating to the AWS Cloud. The company has created an application that uses Amazon S3 APIs to upload files from vendors.

Some vendors run their systems on legacy applications that do not support S3 APIs. The vendors want to continue to use SFTP-based applications to upload data. The company wants to use managed services for the needs of the vendors that use legacy applications.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS Database Migration Service (AWS DMS) instance to replicate data from the storage of the vendors that use legacy applications to Amazon S3. Provide the vendors with the credentials to access the AWS DMS instance.
- B. Create an AWS Transfer Family endpoint for vendors that use legacy applications. **Most Voted**
- C. Configure an Amazon EC2 instance to run an SFTP server. Instruct the vendors that use legacy applications to use the SFTP server to upload data.
- D. Configure an Amazon S3 File Gateway for vendors that use legacy applications to upload files to an SMB file share.

Suggested Answer: B

Question #: 817

A marketing team wants to build a campaign for an upcoming multi-sport event. The team has news reports from the past five years in PDF format. The team needs a solution to extract insights about the content and the sentiment of the news reports. The solution must use Amazon Textract to process the news reports.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Provide the extracted insights to Amazon Athena for analysis. Store the extracted insights and analysis in an Amazon S3 bucket.
- B. Store the extracted insights in an Amazon DynamoDB table. Use Amazon SageMaker to build a sentiment model.
- C. Provide the extracted insights to Amazon Comprehend for analysis. Save the analysis to an Amazon S3 bucket. **Most Voted**
- D. Store the extracted insights in an Amazon S3 bucket. Use Amazon QuickSight to visualize and analyze the data.

Suggested Answer: C

Question #: 818

A company's application runs on Amazon EC2 instances that are in multiple Availability Zones. The application needs to ingest real-time data from third-party applications.

The company needs a data ingestion solution that places the ingested raw data in an Amazon S3 bucket.

Which solution will meet these requirements?

- A. Create Amazon Kinesis data streams for data ingestion. Create Amazon Kinesis Data Firehose delivery streams to consume the Kinesis data streams. Specify the S3 bucket as the destination of the delivery streams. **Most Voted**
- B. Create database migration tasks in AWS Database Migration Service (AWS DMS). Specify replication instances of the EC2 instances as the source endpoints. Specify the S3 bucket as the target endpoint. Set the migration type to migrate existing data and replicate ongoing changes.
- C. Create and configure AWS DataSync agents on the EC2 instances. Configure DataSync tasks to transfer data from the EC2 instances to the S3 bucket.
- D. Create an AWS Direct Connect connection to the application for data ingestion. Create Amazon Kinesis Data Firehose delivery streams to consume direct PUT operations from the application. Specify the S3 bucket as the destination of the delivery streams.

Suggested Answer: A

Question #: 819

A company's application is receiving data from multiple data sources. The size of the data varies and is expected to increase over time. The current maximum size is 700 KB. The data volume and data size continue to grow as more data sources are added.

The company decides to use Amazon DynamoDB as the primary database for the application. A solutions architect needs to identify a solution that handles the large data sizes.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create an AWS Lambda function to filter the data that exceeds DynamoDB item size limits. Store the larger data in an Amazon DocumentDB (with MongoDB compatibility) database.
- B. Store the large data as objects in an Amazon S3 bucket. In a DynamoDB table, create an item that has an attribute that points to the S3 URL of the data. **Most Voted**
- C. Split all incoming large data into a collection of items that have the same partition key. Write the data to a DynamoDB table in a single operation by using the BatchWriteItem API operation.
- D. Create an AWS Lambda function that uses gzip compression to compress the large objects as they are written to a DynamoDB table.

Suggested Answer: B

Question #: 821

A company uses Salesforce. The company needs to load existing data and ongoing data changes from Salesforce to Amazon Redshift for analysis. The company does not want the data to travel over the public internet.

Which solution will meet these requirements with the LEAST development effort?

- A. Establish a VPN connection from the VPC to Salesforce. Use AWS Glue DataBrew to transfer data.
- B. Establish an AWS Direct Connect connection from the VPC to Salesforce. Use AWS Glue DataBrew to transfer data.
- C. Create an AWS PrivateLink connection in the VPC to Salesforce. Use Amazon AppFlow to transfer data.
- D. Create a VPC peering connection to Salesforce. Use Amazon AppFlow to transfer data.

Suggested Answer: C

Question #: 822

A company recently migrated its application to AWS. The application runs on Amazon EC2 Linux instances in an Auto Scaling group across multiple Availability Zones. The application stores data in an Amazon Elastic File System (Amazon EFS) file system that uses EFS Standard-Infrequent Access storage. The application indexes the company's files. The index is stored in an Amazon RDS database.

The company needs to optimize storage costs with some application and services changes.

Which solution will meet these requirements MOST cost-effectively?

- A. Create an Amazon S3 bucket that uses an Intelligent-Tiering lifecycle policy. Copy all files to the S3 bucket. Update the application to use Amazon S3 API to store and retrieve files. **Most Voted**
- B. Deploy Amazon FSx for Windows File Server file shares. Update the application to use CIFS protocol to store and retrieve files.
- C. Deploy Amazon FSx for OpenZFS file system shares. Update the application to use the new mount point to store and retrieve files.
- D. Create an Amazon S3 bucket that uses S3 Glacier Flexible Retrieval. Copy all files to the S3 bucket. Update the application to use Amazon S3 API to store and retrieve files as standard retrievals.

Suggested Answer: A

Question #: 823

A robotics company is designing a solution for medical surgery. The robots will use advanced sensors, cameras, and AI algorithms to perceive their environment and to complete surgeries.

The company needs a public load balancer in the AWS Cloud that will ensure seamless communication with backend services. The load balancer must be capable of routing traffic based on the query strings to different target groups. The traffic must also be encrypted.

Which solution will meet these requirements?

- A. Use a Network Load Balancer with a certificate attached from AWS Certificate Manager (ACM). Use query parameter-based routing.
- B. Use a Gateway Load Balancer. Import a generated certificate in AWS Identity and Access Management (IAM). Attach the certificate to the load balancer. Use HTTP path-based routing.
- C. Use an Application Load Balancer with a certificate attached from AWS Certificate Manager (ACM). Use query parameter-based routing.
- D. Use a Network Load Balancer. Import a generated certificate in AWS Identity and Access Management (IAM). Attach the certificate to the load balancer. Use query parameter-based routing.

Suggested Answer: C

Question #: 824

A company has an application that runs on a single Amazon EC2 instance. The application uses a MySQL database that runs on the same EC2 instance. The company needs a highly available and automatically scalable solution to handle increased traffic.

Which solution will meet these requirements?

- A. Deploy the application to EC2 instances that run in an Auto Scaling group behind an Application Load Balancer. Create an Amazon Redshift cluster that has multiple MySQL-compatible nodes.

- B. Deploy the application to EC2 instances that are configured as a target group behind an Application Load Balancer. Create an Amazon RDS for MySQL cluster that has multiple instances.
- C. Deploy the application to EC2 instances that run in an Auto Scaling group behind an Application Load Balancer. Create an Amazon Aurora Serverless MySQL cluster for the database layer.
- D. Deploy the application to EC2 instances that are configured as a target group behind an Application Load Balancer. Create an Amazon ElastiCache for Redis cluster that uses the MySQL connector.

Suggested Answer: C

Question #: 825

A company is planning to migrate data to an Amazon S3 bucket. The data must be encrypted at rest within the S3 bucket. The encryption key must be rotated automatically every year.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Migrate the data to the S3 bucket. Use server-side encryption with Amazon S3 managed keys (SSE-S3). Use the built-in key rotation behavior of SSE-S3 encryption keys.
- B. Create an AWS Key Management Service (AWS KMS) customer managed key. Enable automatic key rotation. Set the S3 bucket's default encryption behavior to use the customer managed KMS key. Migrate the data to the S3 bucket.
- C. Create an AWS Key Management Service (AWS KMS) customer managed key. Set the S3 bucket's default encryption behavior to use the customer managed KMS key. Migrate the data to the S3 bucket. Manually rotate the KMS key every year.
- D. Use customer key material to encrypt the data. Migrate the data to the S3 bucket. Create an AWS Key Management Service (AWS KMS) key without key material. Import the customer key material into the KMS key. Enable automatic key rotation.

Suggested Answer: A

Question #: 827

A company is planning to deploy its application on an Amazon Aurora PostgreSQL Serverless v2 cluster. The application will receive large amounts of traffic. The company wants to optimize the storage performance of the

cluster as the load on the application increases.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure the cluster to use the Aurora Standard storage configuration.
- B. Configure the cluster storage type as Provisioned IOPS.
- C. Configure the cluster storage type as General Purpose.
- D. Configure the cluster to use the Aurora I/O-Optimized storage configuration. **Most Voted**

Suggested Answer: D

Question #: 828

A financial services company that runs on AWS has designed its security controls to meet industry standards. The industry standards include the National Institute of Standards and Technology (NIST) and the Payment Card Industry Data Security Standard (PCI DSS).

The company's third-party auditors need proof that the designed controls have been implemented and are functioning correctly. The company has hundreds of AWS accounts in a single organization in AWS Organizations. The company needs to monitor the current state of the controls across accounts.

Which solution will meet these requirements?

- A. Designate one account as the Amazon Inspector delegated administrator account from the Organizations management account. Integrate Inspector with Organizations to discover and scan resources across all AWS accounts. Enable Inspector industry standards for NIST and PCI DSS.
- B. Designate one account as the Amazon GuardDuty delegated administrator account from the Organizations management account. In the designated GuardDuty administrator account, enable GuardDuty to protect all member accounts. Enable GuardDuty industry standards for NIST and PCI DSS.
- C. Configure an AWS CloudTrail organization trail in the Organizations management account. Designate one account as the compliance account. Enable CloudTrail security standards for NIST and PCI DSS in the compliance account.

- D. Designate one account as the AWS Security Hub delegated administrator account from the Organizations management account. In the designated Security Hub administrator account, enable Security Hub for all member accounts. Enable Security Hub standards for NIST and PCI DSS.

Suggested Answer: D

Question #: 829

A company uses an Amazon S3 bucket as its data lake storage platform. The S3 bucket contains a massive amount of data that is accessed randomly by multiple teams and hundreds of applications. The company wants to reduce the S3 storage costs and provide immediate availability for frequently accessed objects.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create an S3 Lifecycle rule to transition objects to the S3 Intelligent-Tiering storage class.
- B. Store objects in Amazon S3 Glacier. Use S3 Select to provide applications with access to the data.
- C. Use data from S3 storage class analysis to create S3 Lifecycle rules to automatically transition objects to the S3 Standard-Infrequent Access (S3 Standard-IA) storage class.
- D. Transition objects to the S3 Standard-Infrequent Access (S3 Standard-IA) storage class. Create an AWS Lambda function to transition objects to the S3 Standard storage class when they are accessed by an application.

Suggested Answer: A

Question #: 830

A company has 5 TB of datasets. The datasets consist of 1 million user profiles and 10 million connections. The user profiles have connections as many-to-many relationships. The company needs a performance efficient way to find mutual connections up to five levels.

Which solution will meet these requirements?

- A. Use an Amazon S3 bucket to store the datasets. Use Amazon Athena to perform SQL JOIN queries to find connections.
- B. Use Amazon Neptune to store the datasets with edges and vertices. Query the data to find connections.
- C. Use an Amazon S3 bucket to store the datasets. Use Amazon QuickSight to visualize connections.
- D. Use Amazon RDS to store the datasets with multiple tables. Perform SQL JOIN queries to find connections.

Suggested Answer: B

Question #: 831

A company needs a secure connection between its on-premises environment and AWS. This connection does not need high bandwidth and will handle a small amount of traffic. The connection should be set up quickly.

What is the MOST cost-effective method to establish this type of connection?

- A. Implement a client VPN.
- B. Implement AWS Direct Connect.
- C. Implement a bastion host on Amazon EC2.
- D. Implement an AWS Site-to-Site VPN connection.

Suggested Answer: D

Question #: 832

A company has an on-premises SFTP file transfer solution. The company is migrating to the AWS Cloud to scale the file transfer solution and to optimize costs by using Amazon S3. The company's employees will use their credentials for the on-premises Microsoft Active Directory (AD) to access the new solution. The company wants to keep the current authentication and file access mechanisms.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Configure an S3 File Gateway. Create SMB file shares on the file gateway that use the existing Active Directory to authenticate.

- B. Configure an Auto Scaling group with Amazon EC2 instances to run an SFTP solution. Configure the group to scale up at 60% CPU utilization.
- C. Create an AWS Transfer Family server with SFTP endpoints. Choose the AWS Directory Service option as the identity provider. Use AD Connector to connect the on-premises Active Directory.
- D. Create an AWS Transfer Family SFTP endpoint. Configure the endpoint to use the AWS Directory Service option as the identity provider to connect to the existing Active Directory.

Suggested Answer: C

Question #: 833

A company is designing an event-driven order processing system. Each order requires multiple validation steps after the order is created. An idempotent AWS Lambda function performs each validation step. Each validation step is independent from the other validation steps. Individual validation steps need only a subset of the order event information.

The company wants to ensure that each validation step Lambda function has access to only the information from the order event that the function requires. The components of the order processing system should be loosely coupled to accommodate future business changes.

Which solution will meet these requirements?

- A. Create an Amazon Simple Queue Service (Amazon SQS) queue for each validation step. Create a new Lambda function to transform the order data to the format that each validation step requires and to publish the messages to the appropriate SQS queues. Subscribe each validation step Lambda function to its corresponding SQS queue.
- B. Create an Amazon Simple Notification Service (Amazon SNS) topic. Subscribe the validation step Lambda functions to the SNS topic. Use message body filtering to send only the required data to each subscribed Lambda function.
- C. Create an Amazon EventBridge event bus. Create an event rule for each validation step. Configure the input transformer to send only the required data to each target validation step Lambda function.
- D. Create an Amazon Simple Queue Service (Amazon SQS) queue. Create a new Lambda function to subscribe to the SQS queue and to transform the order data to the format that each validation step requires. Use the new

Lambda function to perform synchronous invocations of the validation step Lambda functions in parallel on separate threads.

Suggested Answer: C

Question #: 834

A company is migrating a three-tier application to AWS. The application requires a MySQL database. In the past, the application users reported poor application performance when creating new entries. These performance issues were caused by users generating different real-time reports from the application during working hours.

Which solution will improve the performance of the application when it is moved to AWS?

- A. Import the data into an Amazon DynamoDB table with provisioned capacity. Refactor the application to use DynamoDB for reports.
- B. Create the database on a compute optimized Amazon EC2 instance. Ensure compute resources exceed the on-premises database.
- C. Create an Amazon Aurora MySQL Multi-AZ DB cluster with multiple read replicas. Configure the application to use the reader endpoint for reports.
- D. Create an Amazon Aurora MySQL Multi-AZ DB cluster. Configure the application to use the backup instance of the cluster as an endpoint for the reports.

Suggested Answer: C

Question #: 835

A company is expanding a secure on-premises network to the AWS Cloud by using an AWS Direct Connect connection. The on-premises network has no direct internet access. An application that runs on the on-premises network needs to use an Amazon S3 bucket.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a public virtual interface (VIF). Route the AWS traffic over the public VIF.
- B. Create a VPC and a NAT gateway. Route the AWS traffic from the on-premises network to the NAT gateway.

- C. Create a VPC and an Amazon S3 interface endpoint. Route the AWS traffic from the on-premises network to the S3 interface endpoint.
- D. Create a VPC peering connection between the on-premises network and Direct Connect. Route the AWS traffic over the peering connection.

Suggested Answer: C

Question #: 836

A company serves its website by using an Auto Scaling group of Amazon EC2 instances in a single AWS Region. The website does not require a database.

The company is expanding, and the company's engineering team deploys the website to a second Region. The company wants to distribute traffic across both Regions to accommodate growth and for disaster recovery purposes. The solution should not serve traffic from a Region in which the website is unhealthy.

Which policy or resource should the company use to meet these requirements?

- A. An Amazon Route 53 simple routing policy
- B. An Amazon Route 53 multivalue answer routing policy **Most Voted**
- C. An Application Load Balancer in one Region with a target group that specifies the EC2 instance IDs from both Regions
- D. An Application Load Balancer in one Region with a target group that specifies the IP addresses of the EC2 instances from both Regions

Suggested Answer: B

Question #: 837

A company runs its applications on Amazon EC2 instances that are backed by Amazon Elastic Block Store (Amazon EBS). The EC2 instances run the most recent Amazon Linux release. The applications are experiencing availability issues when the company's employees store and retrieve files that are 25 GB or larger. The company needs a solution that does not require the company to transfer files between EC2 instances. The files must be available across many EC2 instances and across multiple Availability Zones.

Which solution will meet these requirements?

- A. Migrate all the files to an Amazon S3 bucket. Instruct the employees to access the files from the S3 bucket.
- B. Take a snapshot of the existing EBS volume. Mount the snapshot as an EBS volume across the EC2 instances. Instruct the employees to access the files from the EC2 instances.
- C. Mount an Amazon Elastic File System (Amazon EFS) file system across all the EC2 instances. Instruct the employees to access the files from the EC2 instances.
- D. Create an Amazon Machine Image (AMI) from the EC2 instances. Configure new EC2 instances from the AMI that use an instance store volume. Instruct the employees to access the files from the EC2 instances.

Suggested Answer: C

Question #: 838

A company is running a highly sensitive application on Amazon EC2 backed by an Amazon RDS database. Compliance regulations mandate that all personally identifiable information (PII) be encrypted at rest.

Which solution should a solutions architect recommend to meet this requirement with the LEAST amount of changes to the infrastructure?

- A. Deploy AWS Certificate Manager to generate certificates. Use the certificates to encrypt the database volume.
- B. Deploy AWS CloudHSM, generate encryption keys, and use the keys to encrypt database volumes.
- C. Configure SSL encryption using AWS Key Management Service (AWS KMS) keys to encrypt database volumes.
- D. Configure Amazon Elastic Block Store (Amazon EBS) encryption and Amazon RDS encryption with AWS Key Management Service (AWS KMS) keys to encrypt instance and database volumes. **Most Voted**

Suggested Answer: D

Question #: 839

A company runs an AWS Lambda function in private subnets in a VPC. The subnets have a default route to the internet through an Amazon EC2 NAT instance. The Lambda function processes input data and saves its output as an object to Amazon S3.

Intermittently, the Lambda function times out while trying to upload the object because of saturated traffic on the NAT instance's network. The company wants to access Amazon S3 without traversing the internet.

Which solution will meet these requirements?

- A. Replace the EC2 NAT instance with an AWS managed NAT gateway.
- B. Increase the size of the EC2 NAT instance in the VPC to a network optimized instance type.
- C. Provision a gateway endpoint for Amazon S3 in the VPC. Update the route tables of the subnets accordingly.
- D. Provision a transit gateway. Place transit gateway attachments in the private subnets where the Lambda function is running.

Suggested Answer: C

Question #: 840

A news company that has reporters all over the world is hosting its broadcast system on AWS. The reporters send live broadcasts to the broadcast system. The reporters use software on their phones to send live streams through the Real Time Messaging Protocol (RTMP).

A solutions architect must design a solution that gives the reporters the ability to send the highest quality streams. The solution must provide accelerated TCP connections back to the broadcast system.

What should the solutions architect use to meet these requirements?

- A. Amazon CloudFront
- B. AWS Global Accelerator **Most Voted**
- C. AWS Client VPN
- D. Amazon EC2 instances and AWS Elastic IP addresses

Suggested Answer: B

Question #: 841

A company uses Amazon EC2 instances and Amazon Elastic Block Store (Amazon EBS) to run its self-managed database. The company has 350 TB of data spread across all EBS volumes. The company takes daily EBS snapshots and keeps the snapshots for 1 month. The daily change rate is 5% of the EBS volumes.

Because of new regulations, the company needs to keep the monthly snapshots for 7 years. The company needs to change its backup strategy to comply with the new regulations and to ensure that data is available with minimal administrative effort.

Which solution will meet these requirements MOST cost-effectively?

- A. Keep the daily snapshot in the EBS snapshot standard tier for 1 month. Copy the monthly snapshot to Amazon S3 Glacier Deep Archive with a 7-year retention period.
- B. Continue with the current EBS snapshot policy. Add a new policy to move the monthly snapshot to Amazon EBS Snapshots Archive with a 7-year retention period.
- C. Keep the daily snapshot in the EBS snapshot standard tier for 1 month. Keep the monthly snapshot in the standard tier for 7 years. Use incremental snapshots.
- D. Keep the daily snapshot in the EBS snapshot standard tier. Use EBS direct APIs to take snapshots of all the EBS volumes every month. Store the snapshots in an Amazon S3 bucket in the Infrequent Access tier for 7 years.

Suggested Answer: A

Question #: 842

A company runs an application on several Amazon EC2 instances that store persistent data on an Amazon Elastic File System (Amazon EFS) file system. The company needs to replicate the data to another AWS Region by using an AWS managed service solution.

Which solution will meet these requirements MOST cost-effectively?

- A. Use the EFS-to-EFS backup solution to replicate the data to an EFS file system in another Region.
- B. Run a nightly script to copy data from the EFS file system to an Amazon S3 bucket. Enable S3 Cross-Region Replication on the S3 bucket.
- C. Create a VPC in another Region. Establish a cross-Region VPC peer. Run a nightly rsync to copy data from the original Region to the new Region.
- D. Use AWS Backup to create a backup plan with a rule that takes a daily backup and replicates it to another Region. Assign the EFS file system resource to the backup plan.

Suggested Answer: D

Question #: 843

An ecommerce company is migrating its on-premises workload to the AWS Cloud. The workload currently consists of a web application and a backend Microsoft SQL database for storage.

The company expects a high volume of customers during a promotional event. The new infrastructure in the AWS Cloud must be highly available and scalable.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Migrate the web application to two Amazon EC2 instances across two Availability Zones behind an Application Load Balancer. Migrate the database to Amazon RDS for Microsoft SQL Server with read replicas in both Availability Zones.
- B. Migrate the web application to an Amazon EC2 instance that runs in an Auto Scaling group across two Availability Zones behind an Application Load Balancer. Migrate the database to two EC2 instances across separate AWS Regions with database replication.

- C. Migrate the web application to Amazon EC2 instances that run in an Auto Scaling group across two Availability Zones behind an Application Load Balancer. Migrate the database to Amazon RDS with Multi-AZ deployment.
- D. Migrate the web application to three Amazon EC2 instances across three Availability Zones behind an Application Load Balancer. Migrate the database to three EC2 instances across three Availability Zones.

Suggested Answer: C

Question #: 844

A company has an on-premises business application that generates hundreds of files each day. These files are stored on an SMB file share and require a low-latency connection to the application servers. A new company policy states all application-generated files must be copied to AWS. There is already a VPN connection to AWS.

The application development team does not have time to make the necessary code modifications to move the application to AWS.

Which service should a solutions architect recommend to allow the application to copy files to AWS?

- A. Amazon Elastic File System (Amazon EFS)
- B. Amazon FSx for Windows File Server
- C. AWS Snowball
- D. AWS Storage Gateway

Suggested Answer: D

Question #: 845

A company has 15 employees. The company stores employee start dates in an Amazon DynamoDB table. The company wants to send an email message to each employee on the day of the employee's work anniversary.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Create a script that scans the DynamoDB table and uses Amazon Simple Notification Service (Amazon SNS) to send email messages to employees when necessary. Use a cron job to run this script every day on an Amazon EC2 instance.
- B. Create a script that scans the DynamoDB table and uses Amazon Simple Queue Service (Amazon SQS) to send email messages to employees when necessary. Use a cron job to run this script every day on an Amazon EC2 instance.
- C. Create an AWS Lambda function that scans the DynamoDB table and uses Amazon Simple Notification Service (Amazon SNS) to send email messages to employees when necessary. Schedule this Lambda function to run every day.
- D. Create an AWS Lambda function that scans the DynamoDB table and uses Amazon Simple Queue Service (Amazon SQS) to send email messages to employees when necessary. Schedule this Lambda function to run every day.

Suggested Answer: C

Question #: 846

A company's application is running on Amazon EC2 instances within an Auto Scaling group behind an Elastic Load Balancing (ELB) load balancer. Based on the application's history, the company anticipates a spike in traffic during a holiday each year. A solutions architect must design a strategy to ensure that the Auto Scaling group proactively increases capacity to minimize any performance impact on application users.

Which solution will meet these requirements?

- A. Create an Amazon CloudWatch alarm to scale up the EC2 instances when CPU utilization exceeds 90%.
- B. Create a recurring scheduled action to scale up the Auto Scaling group before the expected period of peak demand. **Most Voted**

- C. Increase the minimum and maximum number of EC2 instances in the Auto Scaling group during the peak demand period.
- D. Configure an Amazon Simple Notification Service (Amazon SNS) notification to send alerts when there are autoscaling:EC2_INSTANCE_LAUNCH events.

Suggested Answer: B

Question #: 847

A company uses Amazon RDS for PostgreSQL databases for its data tier. The company must implement password rotation for the databases.

Which solution meets this requirement with the LEAST operational overhead?

- A. Store the password in AWS Secrets Manager. Enable automatic rotation on the secret.
- B. Store the password in AWS Systems Manager Parameter Store. Enable automatic rotation on the parameter.
- C. Store the password in AWS Systems Manager Parameter Store. Write an AWS Lambda function that rotates the password.
- D. Store the password in AWS Key Management Service (AWS KMS). Enable automatic rotation on the AWS KMS key.

Suggested Answer: A

Question #: 848

A company runs its application on Oracle Database Enterprise Edition. The company needs to migrate the application and the database to AWS. The company can use the Bring Your Own License (BYOL) model while migrating to AWS. The application uses third-party database features that require privileged access.

A solutions architect must design a solution for the database migration.

Which solution will meet these requirements MOST cost-effectively?

- A. Migrate the database to Amazon RDS for Oracle by using native tools. Replace the third-party features with AWS Lambda.
- B. Migrate the database to Amazon RDS Custom for Oracle by using native tools. Customize the new database settings to support the third-party features.
- C. Migrate the database to Amazon DynamoDB by using AWS Database Migration Service (AWS DMS). Customize the new database settings to support the third-party features.
- D. Migrate the database to Amazon RDS for PostgreSQL by using AWS Database Migration Service (AWS DMS). Rewrite the application code to remove the dependency on third-party features.

Suggested Answer: B

Question #: 849

A large international university has deployed all of its compute services in the AWS Cloud. These services include Amazon EC2, Amazon RDS, and Amazon DynamoDB. The university currently relies on many custom scripts to back up its infrastructure. However, the university wants to centralize management and automate data backups as much as possible by using AWS native options.

Which solution will meet these requirements?

- A. Use third-party backup software with an AWS Storage Gateway tape gateway virtual tape library.
- B. Use AWS Backup to configure and monitor all backups for the services in use.
- C. Use AWS Config to set lifecycle management to take snapshots of all data sources on a schedule.
- D. Use AWS Systems Manager State Manager to manage the configuration and monitoring of backup tasks.

Suggested Answer: B

Question #: 850

A company wants to build a map of its IT infrastructure to identify and enforce policies on resources that pose security risks. The company's security team must be able to query data in the IT infrastructure map and quickly identify security risks.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon RDS to store the data. Use SQL to query the data to identify security risks.
- B. Use Amazon Neptune to store the data. Use SPARQL to query the data to identify security risks.
- C. Use Amazon Redshift to store the data. Use SQL to query the data to identify security risks.
- D. Use Amazon DynamoDB to store the data. Use PartiQL to query the data to identify security risks.

Suggested Answer: B

Question #: 851

A large company wants to provide its globally located developers separate, limited size, managed PostgreSQL databases for development purposes. The databases will be low volume. The developers need the databases only when they are actively working.

Which solution will meet these requirements MOST cost-effectively?

- A. Give the developers the ability to launch separate Amazon Aurora instances. Set up a process to shut down Aurora instances at the end of the workday and to start Aurora instances at the beginning of the next workday.
- B. Develop an AWS Service Catalog product that enforces size restrictions for launching Amazon Aurora instances. Give the developers access to launch the product when they need a development database.
- C. Create an Amazon Aurora Serverless cluster. Develop an AWS Service Catalog product to launch databases in the cluster with the default capacity settings. Grant the developers access to the product.
- D. Monitor AWS Trusted Advisor checks for idle Amazon RDS databases. Create a process to terminate identified idle RDS databases.

Suggested Answer: C

Question #: 852

A company is building a web application that serves a content management system. The content management system runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The EC2 instances run in an Auto Scaling group across multiple Availability Zones. Users are constantly adding and updating files, blogs, and other website assets in the content management system.

A solutions architect must implement a solution in which all the EC2 instances share up-to-date website content with the least possible lag time.

Which solution meets these requirements?

- A. Update the EC2 user data in the Auto Scaling group lifecycle policy to copy the website assets from the EC2 instance that was launched most recently. Configure the ALB to make changes to the website assets only in the newest EC2 instance.
- B. Copy the website assets to an Amazon Elastic File System (Amazon EFS) file system. Configure each EC2 instance to mount the EFS file system locally. Configure the website hosting application to reference the website assets that are stored in the EFS file system.
- C. Copy the website assets to an Amazon S3 bucket. Ensure that each EC2 instance downloads the website assets from the S3 bucket to the attached Amazon Elastic Block Store (Amazon EBS) volume. Run the S3 sync command once each hour to keep files up to date.
- D. Restore an Amazon Elastic Block Store (Amazon EBS) snapshot with the website assets. Attach the EBS snapshot as a secondary EBS volume when a new EC2 instance is launched. Configure the website hosting application to reference the website assets that are stored in the secondary EBS volume.

Suggested Answer: B

Question #: 853

A company's web application consists of multiple Amazon EC2 instances that run behind an Application Load Balancer in a VPC. An Amazon RDS for MySQL DB instance contains the data. The company needs the ability to automatically detect and respond to suspicious or unexpected behavior in its AWS environment. The company already has added AWS WAF to its architecture.

What should a solutions architect do next to protect against threats?

- A. Use Amazon GuardDuty to perform threat detection. Configure Amazon EventBridge to filter for GuardDuty findings and to invoke an AWS Lambda function to adjust the AWS WAF rules. **Most Voted**
- B. Use AWS Firewall Manager to perform threat detection. Configure Amazon EventBridge to filter for Firewall Manager findings and to invoke an AWS Lambda function to adjust the AWS WAF web ACL.
- C. Use Amazon Inspector to perform threat detection and to update the AWS WAF rules. Create a VPC network ACL to limit access to the web application.
- D. Use Amazon Macie to perform threat detection and to update the AWS WAF rules. Create a VPC network ACL to limit access to the web application.

Suggested Answer: A

Question #: 854

A company is planning to run a group of Amazon EC2 instances that connect to an Amazon Aurora database. The company has built an AWS CloudFormation template to deploy the EC2 instances and the Aurora DB cluster. The company wants to allow the instances to authenticate to the database in a secure way. The company does not want to maintain static database credentials.

Which solution meets these requirements with the LEAST operational effort?

- A. Create a database user with a user name and password. Add parameters for the database user name and password to the CloudFormation template. Pass the parameters to the EC2 instances when the instances are launched.

- B. Create a database user with a user name and password. Store the user name and password in AWS Systems Manager Parameter Store. Configure the EC2 instances to retrieve the database credentials from Parameter Store.
- C. Configure the DB cluster to use IAM database authentication. Create a database user to use with IAM authentication. Associate a role with the EC2 instances to allow applications on the instances to access the database.
- D. Configure the DB cluster to use IAM database authentication with an IAM user. Create a database user that has a name that matches the IAM user. Associate the IAM user with the EC2 instances to allow applications on the instances to access the database.

Suggested Answer: C

Question #: 855

A company wants to configure its Amazon CloudFront distribution to use SSL/TLS certificates. The company does not want to use the default domain name for the distribution. Instead, the company wants to use a different domain name for the distribution.

Which solution will deploy the certificate without incurring any additional costs?

- A. Request an Amazon issued private certificate from AWS Certificate Manager (ACM) in the us-east-1 Region.
- B. Request an Amazon issued private certificate from AWS Certificate Manager (ACM) in the us-west-1 Region.
- C. Request an Amazon issued public certificate from AWS Certificate Manager (ACM) in the us-east-1 Region. **Most Voted**
- D. Request an Amazon issued public certificate from AWS Certificate Manager (ACM) in the us-west-1 Region.

Suggested Answer: C

Question #: 856

A company creates operations data and stores the data in an Amazon S3 bucket. For the company's annual audit, an external consultant needs to access an annual report that is stored in the S3 bucket. The external consultant needs to access the report for 7 days.

The company must implement a solution to allow the external consultant access to only the report.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Create a new S3 bucket that is configured to host a public static website. Migrate the operations data to the new S3 bucket. Share the S3 website URL with the external consultant.
- B. Enable public access to the S3 bucket for 7 days. Remove access to the S3 bucket when the external consultant completes the audit.
- C. Create a new IAM user that has access to the report in the S3 bucket. Provide the access keys to the external consultant. Revoke the access keys after 7 days.
- D. Generate a presigned URL that has the required access to the location of the report on the S3 bucket. Share the presigned URL with the external consultant.

Suggested Answer: D

Question #: 857

A company plans to run a high performance computing (HPC) workload on Amazon EC2 Instances. The workload requires low-latency network performance and high network throughput with tightly coupled node-to-node communication.

Which solution will meet these requirements?

- A. Configure the EC2 instances to be part of a cluster placement group. **Most Voted**
- B. Launch the EC2 instances with Dedicated Instance tenancy.
- C. Launch the EC2 instances as Spot Instances.
- D. Configure an On-Demand Capacity Reservation when the EC2 instances are launched.

Suggested Answer: A

Question #: 1

A company collects data for temperature, humidity, and atmospheric pressure in cities across multiple continents. The average volume of data that the company collects from each site daily is 500 GB. Each site has a high-speed Internet connection.

The company wants to aggregate the data from all these global sites as quickly as possible in a single Amazon S3 bucket. The solution must minimize operational complexity.

Which solution meets these requirements?

- A. Turn on S3 Transfer Acceleration on the destination S3 bucket. Use multipart uploads to directly upload site data to the destination S3 bucket. **Most Voted**
- B. Upload the data from each site to an S3 bucket in the closest Region. Use S3 Cross-Region Replication to copy objects to the destination S3 bucket. Then remove the data from the origin S3 bucket.
- C. Schedule AWS Snowball Edge Storage Optimized device jobs daily to transfer data from each site to the closest Region. Use S3 Cross-Region Replication to copy objects to the destination S3 bucket.
- D. Upload the data from each site to an Amazon EC2 instance in the closest Region. Store the data in an Amazon Elastic Block Store (Amazon EBS) volume. At regular intervals, take an EBS snapshot and copy it to the Region that contains the destination S3 bucket. Restore the EBS volume in that Region.

Suggested Answer: A

Question #: 859

A company runs several Amazon RDS for Oracle On-Demand DB instances that have high utilization. The RDS DB instances run in member accounts that are in an organization in AWS Organizations.

The company's finance team has access to the organization's management account and member accounts. The finance team wants to find ways to optimize costs by using AWS Trusted Advisor.

Which combination of steps will meet these requirements? (Choose two.)

- A. Use the Trusted Advisor recommendations in the management account.
- B. Use the Trusted Advisor recommendations in the member accounts where the RDS DB instances are running.
- C. Review the Trusted Advisor checks for Amazon RDS Reserved Instance Optimization.
- D. Review the Trusted Advisor checks for Amazon RDS Idle DB Instances.
- E. Review the Trusted Advisor checks for compute optimization. Crosscheck the results by using AWS Compute Optimizer.

Suggested Answer: AC

Question #: 860

A solutions architect is creating an application. The application will run on Amazon EC2 instances in private subnets across multiple Availability Zones in a VPC. The EC2 instances will frequently access large files that contain confidential information. These files are stored in Amazon S3 buckets for processing. The solutions architect must optimize the network architecture to minimize data transfer costs.

What should the solutions architect do to meet these requirements?

- A. Create a gateway endpoint for Amazon S3 in the VPC. In the route tables for the private subnets, add an entry for the gateway endpoint. **Most Voted**
- B. Create a single NAT gateway in a public subnet. In the route tables for the private subnets, add a default route that points to the NAT gateway.
- C. Create an AWS PrivateLink interface endpoint for Amazon S3 in the VPC. In the route tables for the private subnets, add an entry for the interface endpoint.
- D. Create one NAT gateway for each Availability Zone in public subnets. In each of the route tables for the private subnets, add a default route that points to the NAT gateway in the same Availability Zone.

Suggested Answer: A

Question #: 861

A company wants to relocate its on-premises MySQL database to AWS. The database accepts regular imports from a client-facing application, which causes a high volume of write operations. The company is concerned that the amount of traffic might be causing performance issues within the application.

How should a solutions architect design the architecture on AWS?

- A. Provision an Amazon RDS for MySQL DB instance with Provisioned IOPS SSD storage. Monitor write operation metrics by using Amazon CloudWatch. Adjust the provisioned IOPS if necessary.
- B. Provision an Amazon RDS for MySQL DB instance with General Purpose SSD storage. Place an Amazon ElastiCache cluster in front of the DB instance. Configure the application to query ElastiCache instead.
- C. Provision an Amazon DocumentDB (with MongoDB compatibility) instance with a memory optimized instance type. Monitor Amazon CloudWatch for performance-related issues. Change the instance class if necessary.
- D. Provision an Amazon Elastic File System (Amazon EFS) file system in General Purpose performance mode. Monitor Amazon CloudWatch for IOPS bottlenecks. Change to Provisioned Throughput performance mode if necessary.

Suggested Answer: A

Question #: 862

A company runs an application in the AWS Cloud that generates sensitive archival data files. The company wants to rearchitect the application's data storage. The company wants to encrypt the data files and to ensure that third parties do not have access to the data before the data is encrypted and sent to AWS. The company has already created an Amazon S3 bucket.

Which solution will meet these requirements?

- A. Configure the S3 bucket to use client-side encryption with an Amazon S3 managed encryption key. Configure the application to use the S3 bucket to store the archival files.
- B. Configure the S3 bucket to use server-side encryption with AWS KMS keys (SSE-KMS). Configure the application to use the S3 bucket to store the archival files.
- C. Configure the S3 bucket to use dual-layer server-side encryption with AWS KMS keys (SSE-KMS). Configure the application to use the S3 bucket to store the archival files.
- D. Configure the application to use client-side encryption with a key stored in AWS Key Management Service (AWS KMS). Configure the application to store the archival files in the S3 bucket.

Suggested Answer: D

Question #: 863

A company uses Amazon RDS with default backup settings for its database tier. The company needs to make a daily backup of the database to meet regulatory requirements. The company must retain the backups for 30 days.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Write an AWS Lambda function to create an RDS snapshot every day.
- B. Modify the RDS database to have a retention period of 30 days for automated backups.
- C. Use AWS Systems Manager Maintenance Windows to modify the RDS backup retention period.
- D. Create a manual snapshot every day by using the AWS CLI. Modify the RDS backup retention period.

Suggested Answer: B

Question #: 865

A company's near-real-time streaming application is running on AWS. As the data is ingested, a job runs on the data and takes 30 minutes to complete. The workload frequently experiences high latency due to large amounts

of incoming data. A solutions architect needs to design a scalable and serverless solution to enhance performance.

Which combination of steps should the solutions architect take? (Choose two.)

- A. Use Amazon Kinesis Data Firehose to ingest the data. **Most Voted**
- B. Use AWS Lambda with AWS Step Functions to process the data.
- C. Use AWS Database Migration Service (AWS DMS) to ingest the data.
- D. Use Amazon EC2 instances in an Auto Scaling group to process the data.
- E. Use AWS Fargate with Amazon Elastic Container Service (Amazon ECS) to process the data. **Most Voted**

Suggested Answer: AE

Question #: 866

A company runs a web application on multiple Amazon EC2 instances in a VPC. The application needs to write sensitive data to an Amazon S3 bucket. The data cannot be sent over the public internet.

Which solution will meet these requirements?

- A. Create a gateway VPC endpoint for Amazon S3. Create a route in the VPC route table to the endpoint. **Most Voted**
- B. Create an internal Network Load Balancer that has the S3 bucket as the target.
- C. Deploy the S3 bucket inside the VPC. Create a route in the VPC route table to the bucket.
- D. Create an AWS Direct Connect connection between the VPC and an S3 regional endpoint.

Suggested Answer: A

Question #: 867

A company runs its production workload on Amazon EC2 instances with Amazon Elastic Block Store (Amazon EBS) volumes. A solutions architect needs to analyze the current EBS volume cost and to recommend optimizations. The recommendations need to include estimated monthly saving opportunities.

Which solution will meet these requirements?

- A. Use Amazon Inspector reporting to generate EBS volume recommendations for optimization.
- B. Use AWS Systems Manager reporting to determine EBS volume recommendations for optimization.
- C. Use Amazon CloudWatch metrics reporting to determine EBS volume recommendations for optimization.
- D. Use AWS Compute Optimizer to generate EBS volume recommendations for optimization. **Most Voted**

Suggested Answer: D

Question #: 868

A global company runs its workloads on AWS. The company's application uses Amazon S3 buckets across AWS Regions for sensitive data storage and analysis. The company stores millions of objects in multiple S3 buckets daily. The company wants to identify all S3 buckets that are not versioning-enabled.

Which solution will meet these requirements?

- B. Use Amazon S3 Storage Lens to identify all S3 buckets that are not versioning-enabled across Regions.
- C. Enable IAM Access Analyzer for S3 to identify all S3 buckets that are not versioning-enabled across Regions.
- D. Create an S3 Multi-Region Access Point to identify all S3 buckets that are not versioning-enabled across Regions.

Suggested Answer: B

Question #: 869

A company wants to enhance its ecommerce order-processing application that is deployed on AWS. The application must process each order exactly once without affecting the customer experience during unpredictable traffic surges.

Which solution will meet these requirements?

- A. Create an Amazon Simple Queue Service (Amazon SQS) FIFO queue. Put all the orders in the SQS queue. Configure an AWS Lambda function as the target to process the orders.
- B. Create an Amazon Simple Notification Service (Amazon SNS) standard topic. Publish all the orders to the SNS standard topic. Configure the application as a notification target.
- C. Create a flow by using Amazon AppFlow. Send the orders to the flow. Configure an AWS Lambda function as the target to process the orders.
- D. Configure AWS X-Ray in the application to track the order requests. Configure the application to process the orders by pulling the orders from Amazon CloudWatch.

Suggested Answer: A

Question #: 870

A company has two AWS accounts: Production and Development. The company needs to push code changes in the Development account to the Production account. In the alpha phase, only two senior developers on the development team need access to the Production account. In the beta phase, more developers will need access to perform testing.

Which solution will meet these requirements?

- A. Create two policy documents by using the AWS Management Console in each account. Assign the policy to developers who need access.
- B. Create an IAM role in the Development account. Grant the IAM role access to the Production account. Allow developers to assume the role.

- C. Create an IAM role in the Production account. Define a trust policy that specifies the Development account. Allow developers to assume the role.
- D. Create an IAM group in the Production account. Add the group as a principal in a trust policy that specifies the Production account. Add developers to the group.

Suggested Answer: C

Question #: 871

A company wants to restrict access to the content of its web application. The company needs to protect the content by using authorization techniques that are available on AWS. The company also wants to implement a serverless architecture for authorization and authentication that has low login latency.

The solution must integrate with the web application and serve web content globally. The application currently has a small user base, but the company expects the application's user base to increase.

Which solution will meet these requirements?

- A. Configure Amazon Cognito for authentication. Implement Lambda@Edge for authorization. Configure Amazon CloudFront to serve the web application globally.
- B. Configure AWS Directory Service for Microsoft Active Directory for authentication. Implement AWS Lambda for authorization. Use an Application Load Balancer to serve the web application globally.
- C. Configure Amazon Cognito for authentication. Implement AWS Lambda for authorization. Use Amazon S3 Transfer Acceleration to serve the web application globally.
- D. Configure AWS Directory Service for Microsoft Active Directory for authentication. Implement Lambda@Edge for authorization. Use AWS Elastic Beanstalk to serve the web application globally.

Suggested Answer: A

Question #: 872

A development team uses multiple AWS accounts for its development, staging, and production environments. Team members have been launching large Amazon EC2 instances that are underutilized. A solutions architect must prevent large instances from being launched in all accounts.

How can the solutions architect meet this requirement with the LEAST operational overhead?

- A. Update the IAM policies to deny the launch of large EC2 instances. Apply the policies to all users.
- B. Define a resource in AWS Resource Access Manager that prevents the launch of large EC2 instances.
- C. Create an IAM role in each account that denies the launch of large EC2 instances. Grant the developers IAM group access to the role.
- D. Create an organization in AWS Organizations in the management account with the default policy. Create a service control policy (SCP) that denies the launch of large EC2 instances, and apply it to the AWS accounts.

Suggested Answer: D

Question #: 872

A development team uses multiple AWS accounts for its development, staging, and production environments. Team members have been launching large Amazon EC2 instances that are underutilized. A solutions architect must prevent large instances from being launched in all accounts.

How can the solutions architect meet this requirement with the LEAST operational overhead?

- A. Update the IAM policies to deny the launch of large EC2 instances. Apply the policies to all users.
- B. Define a resource in AWS Resource Access Manager that prevents the launch of large EC2 instances.
- C. Create an IAM role in each account that denies the launch of large EC2 instances. Grant the developers IAM group access to the role.
- D. Create an organization in AWS Organizations in the management account with the default policy. Create a service control policy (SCP) that denies the launch of large EC2 instances, and apply it to the AWS accounts.

Suggested Answer: D

Question #: 873

A company has migrated a fleet of hundreds of on-premises virtual machines (VMs) to Amazon EC2 instances. The instances run a diverse fleet of Windows Server versions along with several Linux distributions. The company wants a solution that will automate inventory and updates of the operating systems. The company also needs a summary of common vulnerabilities of each instance for regular monthly reviews.

What should a solutions architect recommend to meet these requirements?

- A. Set up AWS Systems Manager Patch Manager to manage all the EC2 instances. Configure AWS Security Hub to produce monthly reports.
- B. Set up AWS Systems Manager Patch Manager to manage all the EC2 instances. Deploy Amazon Inspector, and configure monthly reports.
- C. Set up AWS Shield Advanced, and configure monthly reports. Deploy AWS Config to automate patch installations on the EC2 instances.
- D. Set up Amazon GuardDuty in the account to monitor all EC2 instances. Deploy AWS Config to automate patch installations on the EC2 instances.

Suggested Answer: B

Question #: 874

A company hosts its application in the AWS Cloud. The application runs on Amazon EC2 instances in an Auto Scaling group behind an Elastic Load Balancing (ELB) load balancer. The application connects to an Amazon DynamoDB table.

For disaster recovery (DR) purposes, the company wants to ensure that the application is available from another AWS Region with minimal downtime.

Which solution will meet these requirements with the LEAST downtime?

- A. Create an Auto Scaling group and an ELB in the DR Region. Configure the DynamoDB table as a global table. Configure DNS failover to point to the new DR Region's ELB. **Most Voted**
- B. Create an AWS CloudFormation template to create EC2 instances, ELBs, and DynamoDB tables to be launched when necessary. Configure DNS failover to point to the new DR Region's ELB.
- C. Create an AWS CloudFormation template to create EC2 instances and an ELB to be launched when necessary. Configure the DynamoDB table as a global table. Configure DNS failover to point to the new DR Region's ELB.
- D. Create an Auto Scaling group and an ELB in the DR Region. Configure the DynamoDB table as a global table. Create an Amazon CloudWatch alarm with an evaluation period of 10 minutes to invoke an AWS Lambda function that updates Amazon Route 53 to point to the DR Region's ELB.

Suggested Answer: A

Question #: 875

A company runs an application on Amazon EC2 instances in a private subnet. The application needs to store and retrieve data in Amazon S3 buckets. According to regulatory requirements, the data must not travel across the public internet.

What should a solutions architect do to meet these requirements MOST cost-effectively?

- A. Deploy a NAT gateway to access the S3 buckets.
- B. Deploy AWS Storage Gateway to access the S3 buckets.
- C. Deploy an S3 interface endpoint to access the S3 buckets.
- D. Deploy an S3 gateway endpoint to access the S3 buckets. **Most Voted**

Suggested Answer: D

Question #: 876

A company hosts an application on Amazon EC2 instances that run in a single Availability Zone. The application is accessible by using the transport layer of the Open Systems Interconnection (OSI) model. The company needs the application architecture to have high availability.

Which combination of steps will meet these requirements MOST cost-effectively? (Choose two.)

- A. Configure new EC2 instances in a different Availability Zone. Use Amazon Route 53 to route traffic to all instances.
- B. Configure a Network Load Balancer in front of the EC2 instances. **Most Voted**
- C. Configure a Network Load Balancer for TCP traffic to the instances. Configure an Application Load Balancer for HTTP and HTTPS traffic to the instances.
- D. Create an Auto Scaling group for the EC2 instances. Configure the Auto Scaling group to use multiple Availability Zones. Configure the Auto Scaling group to run application health checks on the instances. **Most Voted**
- E. Create an Amazon CloudWatch alarm. Configure the alarm to restart EC2 instances that transition to a stopped state.

Suggested Answer: BD

Question #: 877

A company uses Amazon S3 to host its static website. The company wants to add a contact form to the webpage. The contact form will have dynamic server-side components for users to input their name, email address, phone number, and user message.

The company expects fewer than 100 site visits each month. The contact form must notify the company by email when a customer fills out the form.

Which solution will meet these requirements MOST cost-effectively?

- A. Host the dynamic contact form in Amazon Elastic Container Service (Amazon ECS). Set up Amazon Simple Email Service (Amazon SES) to connect to a third-party email provider.
- B. Create an Amazon API Gateway endpoint that returns the contact form from an AWS Lambda function. Configure another Lambda function on the API Gateway to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.
- C. Host the website by using AWS Amplify Hosting for static content and dynamic content. Use server-side scripting to build the contact form. Configure Amazon Simple Queue Service (Amazon SQS) to deliver the message to the company.
- D. Migrate the website from Amazon S3 to Amazon EC2 instances that run Windows Server. Use Internet Information Services (IIS) for Windows Server to host the webpage. Use client-side scripting to build the contact form. Integrate the form with Amazon WorkMail.

Suggested Answer: B

Question #: 878

A company creates dedicated AWS accounts in AWS Organizations for its business units. Recently, an important notification was sent to the root user email address of a business unit account instead of the assigned account owner. The company wants to ensure that all future notifications can be sent to different employees based on the notification categories of billing, operations, or security.

Which solution will meet these requirements MOST securely?

- A. Configure each AWS account to use a single email address that the company manages. Ensure that all account owners can access the email account to receive notifications. Configure alternate contacts for each AWS account with corresponding distribution lists for the billing team, the security team, and the operations team for each business unit.
- B. Configure each AWS account to use a different email distribution list for each business unit that the company manages. Configure each distribution list with administrator email addresses that can respond to alerts. Configure alternate contacts for each AWS account with corresponding distribution lists for the billing team, the security team, and the operations team for each business unit.

- C. Configure each AWS account root user email address to be the individual company managed email address of one person from each business unit. Configure alternate contacts for each AWS account with corresponding distribution lists for the billing team, the security team, and the operations team for each business unit.
- D. Configure each AWS account root user to use email aliases that go to a centralized mailbox. Configure alternate contacts for each account by using a single business managed email distribution list each for the billing team, the security team, and the operations team.

Suggested Answer: A

Question #: 879

A company runs an ecommerce application on AWS. Amazon EC2 instances process purchases and store the purchase details in an Amazon Aurora PostgreSQL DB cluster.

Customers are experiencing application timeouts during times of peak usage. A solutions architect needs to rearchitect the application so that the application can scale to meet peak usage demands.

Which combination of actions will meet these requirements MOST cost-effectively? (Choose two.)

- A. Configure an Auto Scaling group of new EC2 instances to retry the purchases until the processing is complete. Update the applications to connect to the DB cluster by using Amazon RDS Proxy.
- B. Configure the application to use an Amazon ElastiCache cluster in front of the Aurora PostgreSQL DB cluster.
- C. Update the application to send the purchase requests to an Amazon Simple Queue Service (Amazon SQS) queue. Configure an Auto Scaling group of new EC2 instances that read from the SQS queue.
- D. Configure an AWS Lambda function to retry the ticket purchases until the processing is complete.
- E. Configure an Amazon API Gateway REST API with a usage plan.

Suggested Answer: AC

Question #: 880

A company that uses AWS Organizations runs 150 applications across 30 different AWS accounts. The company used AWS Cost and Usage Report to create a new report in the management account. The report is delivered to an Amazon S3 bucket that is replicated to a bucket in the data collection account.

The company's senior leadership wants to view a custom dashboard that provides NAT gateway costs each day starting at the beginning of the current month.

Which solution will meet these requirements?

- A. Share an Amazon QuickSight dashboard that includes the requested table visual. Configure QuickSight to use AWS DataSync to query the new report.
- B. Share an Amazon QuickSight dashboard that includes the requested table visual. Configure QuickSight to use Amazon Athena to query the new report.
- C. Share an Amazon CloudWatch dashboard that includes the requested table visual. Configure CloudWatch to use AWS DataSync to query the new report.
- D. Share an Amazon CloudWatch dashboard that includes the requested table visual. Configure CloudWatch to use Amazon Athena to query the new report.

Suggested Answer: B

Question #: 881

A company is hosting a high-traffic static website on Amazon S3 with an Amazon CloudFront distribution that has a default TTL of 0 seconds. The company wants to implement caching to improve performance for the website. However, the company also wants to ensure that stale content is not served for more than a few minutes after a deployment.

Which combination of caching methods should a solutions architect implement to meet these requirements? (Choose two.)

- A. Set the CloudFront default TTL to 2 minutes.

- B. Set a default TTL of 2 minutes on the S3 bucket.
- C. Add a Cache-Control private directive to the objects in Amazon S3.
- D. Create an AWS Lambda@Edge function to add an Expires header to HTTP responses. Configure the function to run on viewer response.
- E. Add a Cache-Control max-age directive of 24 hours to the objects in Amazon S3. On deployment, create a CloudFront invalidation to clear any changed files from edge caches.

Suggested Answer: AC

Question #: 882

A company runs its application by using Amazon EC2 instances and AWS Lambda functions. The EC2 instances run in private subnets of a VPC. The Lambda functions need direct network access to the EC2 instances for the application to work.

The application will run for 1 year. The number of Lambda functions that the application uses will increase during the 1-year period. The company must minimize costs on all application resources.

Which solution will meet these requirements?

- A. Purchase an EC2 Instance Savings Plan. Connect the Lambda functions to the private subnets that contain the EC2 instances.
- B. Purchase an EC2 Instance Savings Plan. Connect the Lambda functions to new public subnets in the same VPC where the EC2 instances run.
- C. Purchase a Compute Savings Plan. Connect the Lambda functions to the private subnets that contain the EC2 instances.
- D. Purchase a Compute Savings Plan. Keep the Lambda functions in the Lambda service VPC.

Suggested Answer: C

Question #: 883

A company has deployed a multi-account strategy on AWS by using AWS Control Tower. The company has provided individual AWS accounts to each of its developers. The company wants to implement controls to limit AWS resource costs that the developers incur.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Instruct each developer to tag all their resources with a tag that has a key of CostCenter and a value of the developer's name. Use the required-tags AWS Config managed rule to check for the tag. Create an AWS Lambda function to terminate resources that do not have the tag. Configure AWS Cost Explorer to send a daily report to each developer to monitor their spending.
- B. Use AWS Budgets to establish budgets for each developer account. Set up budget alerts for actual and forecast values to notify developers when they exceed or expect to exceed their assigned budget. Use AWS Budgets actions to apply a DenyAll policy to the developer's IAM role to prevent additional resources from being launched when the assigned budget is reached.
- C. Use AWS Cost Explorer to monitor and report on costs for each developer account. Configure Cost Explorer to send a daily report to each developer to monitor their spending. Use AWS Cost Anomaly Detection to detect anomalous spending and provide alerts.
- D. Use AWS Service Catalog to allow developers to launch resources within a limited cost range. Create AWS Lambda functions in each AWS account to stop running resources at the end of each work day. Configure the Lambda functions to resume the resources at the start of each work day.

Suggested Answer: C

Question #: 884

A solutions architect is designing a three-tier web application. The architecture consists of an internet-facing Application Load Balancer (ALB) and a web tier that is hosted on Amazon EC2 instances in private subnets. The application tier with the business logic runs on EC2 instances in private subnets. The database tier consists of Microsoft SQL Server that runs on EC2 instances in private subnets. Security is a high priority for the company.

Which combination of security group configurations should the solutions architect use? (Choose three.)

- A. Configure the security group for the web tier to allow inbound HTTPS traffic from the security group for the ALB.
- B. Configure the security group for the web tier to allow outbound HTTPS traffic to 0.0.0.0/0.
- C. Configure the security group for the database tier to allow inbound Microsoft SQL Server traffic from the security group for the application tier.
- D. Configure the security group for the database tier to allow outbound HTTPS traffic and Microsoft SQL Server traffic to the security group for the web tier.
- E. Configure the security group for the application tier to allow inbound HTTPS traffic from the security group for the web tier.
- F. Configure the security group for the application tier to allow outbound HTTPS traffic and Microsoft SQL Server traffic to the security group for the web tier.

Suggested Answer: ACE

Question #: 885

A company has released a new version of its production application. The company's workload uses Amazon EC2, AWS Lambda, AWS Fargate, and Amazon SageMaker.

The company wants to cost optimize the workload now that usage is at a steady state. The company wants to cover the most services with the fewest savings plans.

Which combination of savings plans will meet these requirements? (Choose two.)

- A. Purchase an EC2 Instance Savings Plan for Amazon EC2 and SageMaker.
- B. Purchase a Compute Savings Plan for Amazon EC2, Lambda, and SageMaker.
- C. Purchase a SageMaker Savings Plan.

- D. Purchase a Compute Savings Plan for Lambda, Fargate, and Amazon EC2.
- E. Purchase an EC2 Instance Savings Plan for Amazon EC2 and Fargate.

Suggested Answer: CD

Question #: 886

A company uses a Microsoft SQL Server database. The company's applications are connected to the database. The company wants to migrate to an Amazon Aurora PostgreSQL database with minimal changes to the application code.

Which combination of steps will meet these requirements? (Choose two.)

- A. Use the AWS Schema Conversion Tool (AWS SCT) to rewrite the SQL queries in the applications.
- B. Enable Babelfish on Aurora PostgreSQL to run the SQL queries from the applications.
- C. Migrate the database schema and data by using the AWS Schema Conversion Tool (AWS SCT) and AWS Database Migration Service (AWS DMS).
- D. Use Amazon RDS Proxy to connect the applications to Aurora PostgreSQL.
- E. Use AWS Database Migration Service (AWS DMS) to rewrite the SQL queries in the applications.

Suggested Answer: BC

Question #: 887

A company plans to rehost an application to Amazon EC2 instances that use Amazon Elastic Block Store (Amazon EBS) as the attached storage.

A solutions architect must design a solution to ensure that all newly created Amazon EBS volumes are encrypted by default. The solution must also prevent the creation of unencrypted EBS volumes.

Which solution will meet these requirements?

- A. Configure the EC2 account attributes to always encrypt new EBS volumes.
- B. Use AWS Config. Configure the encrypted-volumes identifier. Apply the default AWS Key Management Service (AWS KMS) key.
- C. Configure AWS Systems Manager to create encrypted copies of the EBS volumes. Reconfigure the EC2 instances to use the encrypted volumes.
- D. Create a customer managed key in AWS Key Management Service (AWS KMS). Configure AWS Migration Hub to use the key when the company migrates workloads.

Suggested Answer: B

Question #: 542

A company serves its website by using an Auto Scaling group of Amazon EC2 instances in a single AWS Region. The website does not require a database.

The company is expanding, and the company's engineering team deploys the website to a second Region. The company wants to distribute traffic across both Regions to accommodate growth and for disaster recovery purposes. The solution should not serve traffic from a Region in which the website is unhealthy.

Which policy or resource should the company use to meet these requirements?

- A. An Amazon Route 53 simple routing policy
- B. An Amazon Route 53 multivalue answer routing policy
- C. An Application Load Balancer in one Region with a target group that specifies the EC2 instance IDs from both Regions

- D. An Application Load Balancer in one Region with a target group that specifies the IP addresses of the EC2 instances from both Regions

Suggested Answer: B

Question #: 235

A company needs a secure connection between its on-premises environment and AWS. This connection does not need high bandwidth and will handle a small amount of traffic. The connection should be set up quickly. What is the MOST cost-effective method to establish this type of connection?

- A. Implement a client VPN.
- B. Implement AWS Direct Connect.
- C. Implement a bastion host on Amazon EC2.
- D. Implement an AWS Site-to-Site VPN connection. **Most Voted**

Suggested Answer: D

Question #: 706

A company runs an AWS Lambda function in private subnets in a VPC. The subnets have a default route to the internet through an Amazon EC2 NAT instance. The Lambda function processes input data and saves its output as an object to Amazon S3. Intermittently, the Lambda function times out while trying to upload the object because of saturated traffic on the

NAT instance's network. The company wants to access Amazon S3 without traversing the internet. Which solution will meet these requirements?

- A. Replace the EC2 NAT instance with an AWS managed NAT gateway.
- B. Increase the size of the EC2 NAT instance in the VPC to a network optimized instance type.
- C. Provision a gateway endpoint for Amazon S3 in the VPC. Update the route tables of the subnets accordingly.
- D. Provision a transit gateway. Place transit gateway attachments in the private subnets where the Lambda function is running.

Suggested Answer: C

Question #: 744

A company uses an Amazon S3 bucket as its data lake storage platform. The S3 bucket contains a massive amount of data that is accessed randomly by multiple teams and hundreds of applications. The company wants to reduce the S3 storage costs and provide immediate availability for frequently accessed objects. What is the MOST operationally efficient solution that meets these requirements?

- A. Create an S3 Lifecycle rule to transition objects to the S3 Intelligent-Tiering storage class.
- B. Store objects in Amazon S3 Glacier. Use S3 Select to provide applications with access to the data.
- C. Use data from S3 storage class analysis to create S3 Lifecycle rules to automatically transition objects to the S3 Standard-Infrequent Access (S3 Standard-IA) storage class.
- D. Transition objects to the S3 Standard-Infrequent Access (S3 Standard-IA) storage class. Create an AWS Lambda function to transition objects to the S3 Standard storage class when they are accessed by an application.

Suggested Answer: A

A company is building a cloud-based application on AWS that will handle sensitive customer data. The application uses Amazon RDS for the database, Amazon S3 for object storage, and S3 Event Notifications that invoke AWS Lambda for serverless processing.

The company uses AWS IAM Identity Center to manage user credentials. The development, testing, and operations teams need secure access to Amazon RDS and Amazon S3 while ensuring the confidentiality of sensitive customer data. The solution must comply with the principle of least privilege.

Which solution meets these requirements with the LEAST operational overhead?

- A. Use IAM roles with least privilege to grant all the teams access. Assign IAM roles to each team with customized IAM policies defining specific permission for Amazon RDS and S3 object access based on team responsibilities.
- B. Enable IAM Identity Center with an Identity Center directory. Create and configure permission sets with granular access to Amazon RDS and Amazon S3. Assign all the teams to groups that have specific access with the permission sets.
- C. Create individual IAM users for each member in all the teams with role-based permissions. Assign the IAM roles with predefined policies for RDS and S3 access to each user based on user needs. Implement IAM Access Analyzer for periodic credential evaluation.
- D. Use AWS Organizations to create separate accounts for each team. Implement cross-account IAM roles with least privilege. Grant specific permission for RDS and S3 access based on team roles and responsibilities.

Suggested Answer: D

A company uses GPS trackers to document the migration patterns of thousands of sea turtles. The trackers check every 5 minutes to see if a turtle has moved more than 100 yards (91.4 meters). If a turtle has moved, its tracker sends the new coordinates to a web application running on three Amazon EC2 instances that are in multiple Availability Zones in one AWS Region.

Recently, the web application was overwhelmed while processing an unexpected volume of tracker data. Data was lost with no way to replay the events. A solutions architect must prevent this problem from happening again and needs a solution with the least operational overhead.

What should the solutions architect do to meet these requirements?

- A. Create an Amazon S3 bucket to store the data. Configure the application to scan for new data in the bucket for processing.
- B. Create an Amazon API Gateway endpoint to handle transmitted location coordinates. Use an AWS Lambda function to process each item concurrently.
- C. Create an Amazon Simple Queue Service (Amazon SQS) queue to store the incoming data. Configure the application to poll for new messages for processing.
- D. Create an Amazon DynamoDB table to store transmitted location coordinates. Configure the application to query the table for new data for processing. Use TTL to remove data that has been processed.

Suggested Answer: D

A company currently stores 5 TB of data in on-premises block storage systems. The company's current storage solution provides limited space for additional data. The company runs applications on premises that must be able to retrieve frequently accessed data with low latency. The company requires a cloud-based storage solution.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Use Amazon S3 File Gateway. Integrate S3 File Gateway with the on-premises applications to store and directly retrieve files by using the SMB file system.
- B. Use an AWS Storage Gateway Volume Gateway with cached volumes as iSCSI targets.
- C. Use an AWS Storage Gateway Volume Gateway with stored volumes as iSCSI targets.
- D. Use an AWS Storage Gateway Tape Gateway. Integrate Tape Gateway with the on-premises applications to store virtual tapes in Amazon S3

Suggested Answer: B

A company is designing a web application with an internet-facing Application Load Balancer (ALB).

The company needs the ALB to receive HTTPS web traffic from the public internet. The ALB must send only HTTPS traffic to the web application servers hosted on the Amazon EC2 instances on port 443. The ALB must perform a health check of the web application servers over HTTPS on port 8443.

Which combination of configurations of the security group that is associated with the ALB will meet these requirements? (Select THREE.)

- A. Allow HTTPS inbound traffic from 0.0.0.0/0 for port 443.
- B. Allow all outbound traffic to 0.0.0.0/0 for port 443.
- C. Allow HTTPS outbound traffic to the web application instances for port 443.
- D. Allow HTTPS inbound traffic from the web application instances for port 443.
- E. Allow HTTPS outbound traffic to the web application instances for the health check on port 8443.
- F. Allow HTTPS inbound traffic from the web application instances for the health check on port 8443

Suggested Answer: ACF

A company hosts a video streaming web application in a VPC. The company uses a Network Load Balancer (NLB) to handle TCP traffic for real-time data processing. There have been unauthorized attempts to access the application.

The company wants to improve application security with minimal architectural change to prevent unauthorized attempts to access the application.

Which solution will meet these requirements?

- A. Implement a series of AWS WAF rules directly on the NLB to filter out unauthorized traffic.
- B. Recreate the NLB with a security group to allow only trusted IP addresses.

- C. Deploy a second NLB in parallel with the existing NLB configured with a strict IP address allow list.
- D. Use AWS Shield Advanced to provide enhanced DDoS protection and prevent unauthorized access attempts.

Suggested Answer: B

A company has an internal application that runs on Amazon EC2 instances in an Auto Scaling group. The EC2 instances are compute optimized and use Amazon Elastic Block Store (Amazon EBS) volumes.

The company wants to identify cost optimizations across the EC2 instances, the Auto Scaling group, and the EBS volumes.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Create a new AWS Cost and Usage Report. Search the report for cost recommendations for the EC2 instances, the Auto Scaling group, and the EBS volumes.
- B. Create new Amazon CloudWatch billing alerts. Check the alert statuses for cost recommendations for the EC2 instances, the Auto Scaling group, and the EBS volumes.
- C. Configure AWS Compute Optimizer for cost recommendations for the EC2 instances, the Auto Scaling group, and the EBS volumes.
- D. Configure AWS Compute Optimizer for cost recommendations for the EC2 instances. Create a new AWS Cost and Usage Report. Search the report for cost recommendations for the Auto Scaling group and the EBS volumes.

Suggested Answer: C

A company uses Amazon RDS for PostgreSQL to run its applications in the us-east-1 Region. The company also uses machine learning (ML) models to forecast annual revenue based on near real-time reports. The reports are generated by using the same RDS for PostgreSQL database. The database performance slows during business hours. The company needs to improve database performance.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a cross-Region read replica. Configure the reports to be generated from the read replica.
- B. Activate Multi-AZ DB instance deployment for RDS for PostgreSQL. Configure the reports to be generated from the standby database.
- C. Use AWS Data Migration Service (AWS DMS) to logically replicate data to a new database. Configure the reports to be generated from the new database.
- D. Create a read replica in us-east-1. Configure the reports to be generated from the read replica.

Suggested Answer: D

A media company has a multi-account AWS environment in the us-east-1 Region. The company has an Amazon Simple Notification Service (Amazon SNS) topic in a production account that publishes performance metrics. The company has an AWS Lambda function in an administrator account to process and analyze log data.

The Lambda function that is in the administrator account must be invoked by messages from the SNS topic that is in the production account when significant metrics are reported.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Create an IAM resource policy for the Lambda function that allows Amazon SNS to invoke the function.
- B. Implement an Amazon Simple Queue Service (Amazon SQS) queue in the administrator account to buffer messages from the SNS topic that is in the production account. Configure the SQS queue to invoke the Lambda function.
- C. Create an IAM policy for the SNS topic that allows the Lambda function to subscribe to the topic.
- D. Use an Amazon EventBridge rule in the production account to capture the SNS topic notifications. Configure the EventBridge rule to forward notifications to the Lambda function that is in the administrator account
- E. Store performance metrics in an Amazon S3 bucket in the production account. Use Amazon Athena to analyze the metrics from the administrator account.

Suggested Answer: AD

An online gaming company is transitioning user data storage to Amazon DynamoDB to support the company's growing user base. The current architecture includes DynamoDB tables that contain user profiles, achievements, and in-game transactions.

The company needs to design a robust, continuously available, and resilient DynamoDB architecture to maintain a seamless gaming experience for users.

Which solution will meet these requirements MOST cost-effectively?

- A. Create DynamoDB tables in a single AWS Region. Use on-demand capacity mode. Use global tables to replicate data across multiple Regions
- B. Use DynamoDB Accelerator (DAX) to cache frequently accessed data. Deploy tables in a single AWS Region and enable auto scaling. Configure Cross-Region Replication manually to additional Regions.
- C. Create DynamoDB tables in multiple AWS Regions. Use on-demand capacity mode. Use DynamoDB Streams for Cross-Region Replication between Regions
- D. Use DynamoDB global tables for automatic multi-Region replication. Deploy tables in multiple AWS Regions. Use provisioned capacity mode. Enable auto scaling.

Suggested Answer: D

A company runs an application that stores and shares photos. Users upload the photos to an Amazon S3 bucket. Every day, users upload approximately 150 photos. The company wants to design a solution that creates a thumbnail of each new photo and stores the thumbnail in a second S3 bucket.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure an Amazon EventBridge scheduled rule to invoke a script every minute on a long-running Amazon EMR cluster. Configure the script to generate thumbnails for the photos that do not have thumbnails. Configure the script to upload the thumbnails to the second S3 bucket.
- B. Configure an Amazon EventBridge scheduled rule to invoke a script every minute on a memory-optimized Amazon EC2 instance that is always on. Configure the script to generate thumbnails for the photos that do not have thumbnails. Configure the script to upload the thumbnails to the second S3 bucket.
- C. Configure an S3 event notification to invoke an AWS Lambda function each time a user uploads a new photo to the application. Configure the Lambda function to generate a thumbnail and to upload the thumbnail to the second S3 bucket.
- D. Configure S3 Storage Lens to invoke an AWS Lambda function each time a user uploads a new photo to the application. Configure the Lambda function to generate a thumbnail and to upload the thumbnail to a second S3 bucket.

Suggested Answer: C

A company has stored millions of objects across multiple prefixes in an Amazon S3 bucket by using the Amazon S3 Glacier Deep Archive storage class. The company needs to delete all data older than 3 years except for a subset of data that must be retained. The company has identified the data that must be retained and wants to implement a serverless solution.

Which solution will meet these requirements?

- A. Use S3 Inventory to list all objects. Use the AWS CLI to create a script that runs on an Amazon EC2 instance that deletes objects from the inventory list.
- B. Use AWS Batch to delete objects older than 3 years except for the data that must be retained.
- C. Provision an AWS Glue crawler to query objects older than 3 years. Save the manifest file of old objects. Create a script to delete objects in the manifest.
- D. Enable S3 Inventory. Create an AWS Lambda function to filter and delete objects. Invoke the Lambda function with S3 Batch Operations to delete objects by using the inventory reports.

Suggested Answer: D

A company runs an application in a private subnet behind an Application Load Balancer (ALB) in a VPC. The VPC has a NAT gateway and an internet gateway. The application calls the Amazon S3 API to store objects.

According to the company's security policy, traffic from the application must not travel across the internet.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure an S3 interface endpoint. Create a security group that allows outbound traffic to Amazon S3.
- B. Configure an S3 gateway endpoint. Update the VPC route table to use the endpoint.
- C. Configure an S3 bucket policy to allow traffic from the Elastic IP address that is assigned to the NAT gateway.
- D. Create a second NAT gateway in the same subnet where the legacy application is deployed. Update the VPC route table to use the second NAT gateway.

Suggested Answer: A

A digital image processing company wants to migrate its on-premises monolithic application to the AWS Cloud. The company processes thousands of images and generates large files as part of the processing workflow.

The company needs a solution to manage the growing number of image processing jobs. The solution must also reduce the manual tasks in the image processing workflow. The company does not want to manage the underlying infrastructure of the solution.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Elastic Container Service (Amazon ECS) with Amazon EC2 Spot Instances to process the images. Configure Amazon Simple Queue Service (Amazon SQS) to orchestrate the workflow. Store the processed files in Amazon Elastic File System (Amazon EFS)

B. Use AWS Batch jobs to process the images. Use AWS Step Functions to orchestrate the workflow. Store the processed files in an Amazon S3 bucket.

C. Use AWS Lambda functions and Amazon EC2 Spot Instances to process the images. Store the processed files in Amazon FSx

D. Deploy a group of Amazon EC2 instances to process the images. Use AWS Step Functions to orchestrate the workflow. Store the processed files in an Amazon Elastic Block Store (Amazon EBS) volume.

Suggested Answer: B

A company has an Amazon S3 bucket that contains sensitive data files. The company has an application that runs on virtual machines in an on-premises data center. The company currently uses AWS IAM Identity Center.

The application requires temporary access to files in the S3 bucket. The company wants to grant the application secure access to the files in the S3 bucket

Which solution will meet these requirements?

A. Create an S3 bucket policy that permits access to the bucket from the public IP address range of the company's on-premises data center

B. Use IAM Roles Anywhere to obtain security credentials in IAM Identity Center that grant access to the S3 bucket. Configure the virtual machines to assume the role by using the AWS CLI.

C. Install the AWS CLI on the virtual machine. Configure the AWS CLI with access keys from an IAM user that has access to the bucket.

D. Create an IAM user and policy that grants access to the bucket. Store the access key and secret key for the IAM user in AWS Secrets Manager. Configure the application to retrieve the access key and secret key at startup.

Suggested Answer: B

A company hosts its multi-tier, public web application in the AWS Cloud. The web application runs on Amazon EC2 instances, and its database runs on Amazon RDS. The company is anticipating a large increase in sales during an upcoming holiday weekend. A solutions architect needs to build a solution to analyze the performance of the web application with a granularity of no more than 2 minutes.

What should the solutions architect do to meet this requirement?

- A. Send Amazon CloudWatch logs to Amazon Redshift. Use Amazon QuickSight to perform further analysis.
- B. Enable detailed monitoring on all EC2 instances. Use Amazon CloudWatch metrics to perform further analysis.
- C. Create an AWS Lambda function to fetch EC2 logs from Amazon CloudWatch Logs. Use Amazon CloudWatch metrics to perform further analysis.
- D. Send EC2 logs to Amazon S3. Use Amazon Redshift to fetch logs from the S3 bucket to process raw data for further analysis with Amazon QuickSight.

Suggested Answer: B

A company hosts an application in a private subnet. The company has already integrated the application with Amazon Cognito. The company uses an Amazon Cognito user pool to authenticate users.

The company needs to modify the application so the application can securely store user documents in an Amazon S3 bucket.

Which combination of steps will securely integrate Amazon S3 with the application? (Select TWO.)

- A. Create an Amazon Cognito identity pool to generate secure Amazon S3 access tokens for users when they successfully log in.
- B. Use the existing Amazon Cognito user pool to generate Amazon S3 access tokens for users when they successfully log in.
- C. Create an Amazon S3 VPC endpoint in the same VPC where the company hosts the application.

D. Create a NAT gateway in the VPC where the company hosts the application. Assign a policy to the S3 bucket to deny any request that is not initiated from Amazon Cognito.

E. Attach a policy to the S3 bucket that allows access only from the users' IP addresses.

Suggested Answer: AC

A company has a three-tier web application that processes orders from customers. The web tier consists of Amazon EC2 instances behind an Application Load Balancer. The processing tier consists of EC2 instances. The company decoupled the web tier and processing tier by using Amazon Simple Queue Service (Amazon SQS). The storage layer uses Amazon DynamoDB.

At peak times, some users report order processing delays and halts. The company has noticed that during these delays, the EC2 instances are running at 100% CPU usage, and the SQS queue fills up. The peak times are variable and unpredictable.

The company needs to improve the performance of the application.

Which solution will meet these requirements?

A. Use scheduled scaling for Amazon EC2 Auto Scaling to scale out the processing tier instances for the duration of peak usage times. Use the CPUUtilization metric to determine when to scale.

B. Use Amazon ElastiCache for Redis in front of the DynamoDB backend tier. Use target utilization as a metric to determine when to scale.

C. Add an Amazon CloudFront distribution to cache the responses for the web tier. Use HTTP latency as a metric to determine when to scale.

D. Use an Amazon EC2 Auto Scaling target tracking policy to scale out the processing tier instances. Use the ApproximateNumberOfMessages attribute to determine when to scale.

Suggested Answer: D

A company needs a flexible compute solution and does not want to commit to multi-year contracts.

The company needs to select the most cost-effective purchasing option.

Which option will meet these requirements?

- A. Use On-Demand Instances.
- B. Purchase a 1 year Compute Savings Plan with the No Upfront option.
- C. Purchase a 1 year Compute Savings Plan with the Partial Upfront option.
- D. Purchase a 1 year Compute Savings Plan with the All Upfront option.

Suggested Answer: B

A streaming media company is rebuilding its infrastructure to accommodate increasing demand for video content that users consume daily

The company needs to process terabyte-sized videos to block some content in the videos. Video processing can take up to 20 minutes.

The company needs a solution that will scale with demand and remain cost-effective.

Which solution will meet these requirements?

- A. Use AWS Lambda functions to process videos. Store video metadata in Amazon DynamoDB. Store video content in Amazon S3 Intelligent-Tiering
- B. Use Amazon Elastic Container Service (Amazon ECS) and AWS Fargate to implement microservices to process videos. Store video metadata in Amazon Aurora. Store video content in Amazon S3 Intelligent-Tiering.

C. Use Amazon EC2 instances in an Auto Scaling group behind an Application Load Balancer (ALB) to process videos. Store video content in Amazon S3 Standard. Use Amazon Simple Queue Service (Amazon SQS) for queuing and to decouple processing tasks.

D. Deploy a containerized video processing application on Amazon Elastic Kubernetes Service (Amazon EKS) on Amazon EC2. Store video metadata in Amazon RDS in a single Availability Zone. Store video content in Amazon S3 Glacier Deep Archive.

Suggested Answer: C

A company's software development team needs an Amazon RDS Multi-AZ cluster. The RDS cluster will serve as a backend for a desktop client that is deployed on premises. The desktop client requires direct connectivity to the RDS cluster.

The company must give the development team the ability to connect to the cluster by using the client when the team is in the office.

Which solution provides the required connectivity MOST securely?

A. Create a VPC and two public subnets. Create the RDS cluster in the public subnets. Use AWS Site-to-Site VPN with a customer gateway in the company's office.

B. Create a VPC and two private subnets. Create the RDS cluster in the private subnets. Use AWS Site-to-Site VPN with a customer gateway in the company's office.

C. Create a VPC and two private subnets. Create the RDS cluster in the private subnets. Use RDS security groups to allow the company's office IP ranges to access the cluster.

D. Create a VPC and two public subnets. Create the RDS cluster in the public subnets. Create a cluster user for each developer. Use RDS security groups to allow the users to access the cluster.

Suggested Answer: C

A company is developing a new application that uses a relational database to store user data and application configurations. The company expects the application to have steady user growth. The company expects the database usage to be variable and read-heavy, with occasional writes.

The company wants to cost-optimize the database solution. The company wants to use an AWS managed database solution that will provide the necessary performance

Which solution will meet these requirements MOST cost-effectively?

- A. Deploy the database on Amazon RDS. Use Provisioned IOPS SSD storage to ensure consistent performance for read and write operations.
- B. Deploy the database on Amazon Aurora Serverless to automatically scale the database capacity based on actual usage to accommodate the workload.
- C. Deploy the database on Amazon DynamoDB. Use on-demand capacity mode to automatically scale throughput to accommodate the workload.
- D. Deploy the database on Amazon RDS. Use magnetic storage and use read replicas to accommodate the workload.

Suggested Answer: B

A company is designing the architecture for a new mobile app that uses the AWS Cloud. The company uses organizational units (OUs) in AWS Organizations to manage its accounts. The company wants to tag Amazon EC2 instances with data sensitivity by using values of sensitive and nonsensitive. IAM identities must not be able to delete a tag or create instances without a tag

Which combination of steps will meet these requirements? (Select TWO.)

- A. In Organizations, create a new tag policy that specifies the data sensitivity tag key and the required values. Enforce the tag values for the EC2 instances Attach the tag policy to the appropriate OU.
- B. In Organizations, create a new service control policy (SCP) that specifies the data sensitivity tag key and the required tag values. Enforce the tag values for the EC2 instances. Attach the SCP to the appropriate OU.

- C. Create a tag policy to deny running instances when a tag key is not specified. Create another tag policy that prevents identities from deleting tags. Attach the tag policies to the appropriate OU.
- D. Create a service control policy (SCP) to deny creating instances when a tag key is not specified. Create another SCP that prevents identities from deleting tags. Attach the SCPs to the appropriate OU
- E. Create an AWS Config rule to check if EC2 instances use the data sensitivity tag and the specified values. Configure an AWS Lambda function to delete the resource if a noncompliant resource is found.

Suggested Answer: AC

A company wants to create a high performance computing (HPC) environment in the AWS Cloud. The company will implement a cluster architecture that consists of head nodes and compute nodes for the computational resources.

The company will start the HPC environment to run computations, then stop the compute environment after 8 hours. This process will occur once a month for the next 3 years. The company needs the most cost-optimized compute solution for the Amazon EC2 instances.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Use EC2 Standard Reserved Instances with a 3-year reservation term and the All Upfront payment option for the head nodes
- B. Use EC2 On-Demand Instances for the head nodes with a tailored launch template configuration for auto scaling
- C. Use EC2 Standard Reserved Instances with a 3-year reservation term and the All Upfront payment option for the compute nodes.
- D. Use EC2 On-Demand Instances for the compute nodes with a tailored launch template configuration for auto scaling

E. Use EC2 Spot Instances for the compute nodes with a tailored launch template configuration for auto scaling

Suggested Answer: BD

A company has an AWS Direct Connect connection from its on-premises location to an AWS account. The AWS account has 30 different VPCs in the same AWS Region. The VPCs use private virtual interfaces (VIFs). Each VPC has a CIDR block that does not overlap with other networks under the company's control.

The company wants to centrally manage the networking architecture while still allowing each VPC to communicate with all other VPCs and on-premises networks.

Which solution will meet these requirements with the LEAST amount of operational overhead?

A. Create a transit gateway, and associate the Direct Connect connection with a new transit VIF. Turn on the transit gateway's route propagation feature.

B. Create a Direct Connect gateway. Recreate the private VIFs to use the new gateway. Associate each VPC by creating new virtual private gateways.

C. Create a transit VPC. Connect the Direct Connect connection to the transit VPC. Create a peering connection between all other VPCs in the Region. Update the route tables.

D. Create AWS Site-to-Site VPN connections from on-premises to each VPC. Ensure that both VPN tunnels are UP for each connection. Turn on the route propagation feature.

Suggested Answer: A

A company is building an application in the AWS Cloud. The application is hosted on Amazon EC2 instances behind an Application Load Balancer (ALB). The company uses Amazon Route 53 for the DNS.

The company needs a managed solution with proactive engagement to detect against DDoS attacks.

Which solution will meet these requirements?

- A. Enable AWS Config. Configure an AWS Config managed rule that detects DDoS attacks.
- B. Enable AWS WAF on the ALB. Create an AWS WAF web ACL with rules to detect and prevent DDoS attacks. Associate the web ACL with the ALB
- C. Store the ALB access logs in an Amazon S3 bucket. Configure Amazon GuardDuty to detect and take automated preventative actions for DDoS attacks
- D. Subscribe to AWS Shield Advanced. Configure hosted zones in Route 53. Add ALB resources as protected resources.

Suggested Answer: C

A company runs multiple workloads on virtual machines (VMs) in an on-premises data center. The company is expanding rapidly. The on-premises data center is not able to scale fast enough to meet business needs. The company wants to migrate the workloads to AWS.

The migration is time sensitive. The company wants to use a lift-and-shift strategy for non-critical workloads.

Which combination of steps will meet these requirements? (Select THREE.)

- A. Use the AWS Schema Conversion Tool (AWS SCT) to collect data about the VMs.
- B. Use AWS Application Migration Service. Install the AWS Replication Agent on the VMs.
- C. Complete the initial replication of the VMs. Launch test instances to perform acceptance tests on the VMs.
- D. Stop all operations on the VMs. Launch a cutover instance.
- E. Use AWS App2Container (A2C) to collect data about the VMs.
- F. Use AWS Database Migration Service (AWS DMS) to migrate the VMs.

Suggested Answer: BCD

A company is testing an application that runs on an Amazon EC2 Linux instance. A single 500 GB Amazon Elastic Block Store (Amazon EBS) General Purpose SSD (gp2) volume is attached to the EC2 instance.

The company will deploy the application on multiple EC2 instances in an Auto Scaling group. All instances require access to the data that is stored in the EBS volume. The company needs a highly available and resilient solution that does not introduce significant changes to the application's code.

Which solution will meet these requirements?

- A. Provision an EC2 instance that uses NFS server software. Attach a single 500 GB gp2 EBS volume to the instance.
- B. Provision an Amazon FSx for Windows File Server file system. Configure the file system as an SMB file store within a single Availability Zone
- C. Provision an EC2 instance with two 250 GB Provisioned IOPS SSD EBS volumes.
- D. Provision an Amazon Elastic File System (Amazon EFS) file system. Configure the file system to use General Purpose performance mode.

Suggested Answer: D

A company runs an environment where data is stored in an Amazon S3 bucket. The objects are accessed frequently throughout the day. The company has strict data encryption requirements for data that is stored in the S3 bucket. The company currently uses AWS Key Management Service (AWS KMS) for encryption

The company wants to optimize costs associated with encrypting S3 objects without making additional calls to AWS KMS.

Which solution will meet these requirements?

- A. Use server-side encryption with Amazon S3 managed keys (SSE-S3).
- B. Use an S3 Bucket Key for server-side encryption with AWS KMS keys (SSE-KMS) on the new objects.
- C. Use client-side encryption with AWS KMS customer managed keys.
- D. Use server-side encryption with customer-provided keys (SSE-C) stored in AWS KMS

Suggested Answer: B

A solutions architect needs to connect a company's corporate network to its VPC to allow on-premises access to its AWS resources. The solution must provide encryption of all traffic between the corporate network and the VPC at the network layer and the session layer. The solution also must provide security controls to prevent unrestricted access between AWS and the on-premises systems.

Which solution meets these requirements?

- A. Configure AWS Direct Connect to connect to the VPC. Configure the VPC route tables to allow and deny traffic between AWS and on premises as required.
- B. Create an IAM policy to allow access to the AWS Management Console only from a defined set of corporate IP addresses. Restrict user access based on job responsibility by using an IAM policy and roles.
- C. Configure AWS Site-to-Site VPN to connect to the VPC. Configure route table entries to direct traffic from on premises to the VPC. Configure instance security groups and network ACLs to allow only required traffic from on premises.
- D. Configure AWS Transit Gateway to connect to the VPC. Configure route table entries to direct traffic from on premises to the VPC. Configure instance security groups and network ACLs to allow only required traffic from on premises.

Suggested Answer: C

A company uses an Amazon DynamoDB table to store data that the company receives from devices. The DynamoDB table supports a customer-facing website to display recent activity on customer devices. The company configured the table with provisioned throughput for writes and reads.

The company wants to calculate performance metrics for customer device data on a daily basis. The solution must have minimal effect on the table's provisioned read and write capacity.

Which solution will meet these requirements?

- A. Use an Amazon Athena SQL query with the Amazon Athena DynamoDB connector to calculate performance metrics on a recurring schedule
- B. Use an AWS Glue job with the AWS Glue DynamoDB export connector to calculate performance metrics on a recurring schedule.
- C. Use an Amazon Redshift COPY command to calculate performance metrics on a recurring schedule.
- D. Use an Amazon EMR job with an Apache Hive external table to calculate performance metrics on a recurring schedule.

Suggested Answer: A

A stock trading company needs to run a multi-step business process after each transaction. The process needs to retrieve data from a proprietary software as a service (SaaS) solution through HTTPS. Then the process needs to perform conditional checks on the data and request human approval. The process must take no more than 5 minutes to run and must run exactly once.

Which solution will meet these requirements in the MOST cost-effective way?

- A. Use an AWS Step Functions Express workflow to retrieve the data and perform conditional checks. Use an Amazon Simple Notification Service (Amazon SNS) topic in the Express workflow to request human approval.
- B. Deploy Apache Airflow on Amazon Elastic Container Service (Amazon ECS) to retrieve the data and perform conditional checks. Use a ticketing system operator and a sensor to request human approval.
- C. Run Amazon Simple Workflow Service (Amazon SWF) on an Amazon EC2 instance to retrieve the data and perform conditional checks. Use a human action step to request human approval.
- D. Use an AWS Step Functions Standard workflow to retrieve the data and perform conditional checks. Use an Amazon Simple Notification Service (Amazon SNS) topic in the Standard workflow to request human approval

Suggested Answer: A

A company runs its media rendering application on premises. The company wants to reduce storage costs and has moved all data to Amazon S3. The on-premises rendering application needs low-latency access to storage.

The company needs to design a storage solution for the application. The storage solution must maintain the desired application performance

Which storage solution will meet these requirements in the MOST cost-effective way?

- A. Use Mountpoint for Amazon S3 to access the data in Amazon S3 for the on-premises application.
- B. Configure an Amazon S3 File Gateway to provide storage for the on-premises application.
- C. Copy the data from Amazon S3 to Amazon FSx for Windows File Server. Configure an Amazon FSx File Gateway to provide storage for the on-premises application.
- D. Configure an on-premises file server. Use the Amazon S3 API to connect to S3 storage. Configure the application to access the storage from the on-premises file server.

Suggested Answer: B

A company runs container applications by using Amazon Elastic Kubernetes Service (Amazon EKS) and the Kubernetes Horizontal Pod Autoscaler. The workload is not consistent throughout the day. A solutions architect notices that the number of nodes does not automatically scale out when the existing nodes have reached maximum capacity in the cluster, which causes performance issues.

Which solution will resolve this issue with the LEAST administrative overhead?

- A. Scale out the nodes by tracking the memory usage.
- B. Use the Kubernetes Cluster Autoscaler to manage the number of nodes in the cluster.
- C. Use an AWS Lambda function to resize the EKS cluster automatically.
- D. Use an Amazon EC2 Auto Scaling group to distribute the workload.

Suggested Answer: B

A company has a multi-tier web application. The application's internal service components are deployed on Amazon EC2 instances. The internal service components need to access third-party software as a service (SaaS) APIs that are hosted on AWS.

The company needs to provide secure and private connectivity from the application's internal services to the third-party SaaS application. The company needs to ensure that there is minimal public internet exposure.

Which solution will meet these requirements?

- A. Implement an AWS Site-to-Site VPN to establish a secure connection with the third-party SaaS provider.
- B. Deploy AWS Transit Gateway to manage and route traffic between the application's VPC and the third-party SaaS provider.
- C. Configure AWS PrivateLink to allow only outbound traffic from the VPC without enabling the third-party SaaS provider to establish a return path to the network
- D. Use AWS PrivateLink to create a private connection between the application's VPC and the third-party SaaS provider.

Suggested Answer: D

A company runs a Node.js function on a server in its on-premises data center. The data center stores data in a PostgreSQL database. The company stores the credentials in a connection string in an environment variable on the server. The company wants to migrate its application to AWS and to replace the Node.js application server with AWS Lambda. The company also wants to migrate to Amazon RDS for PostgreSQL and to ensure that the database credentials are securely managed

Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the database credentials as a parameter in AWS Systems Manager Parameter Store. Configure Parameter Store to automatically rotate the secrets every 30 days. Update the Lambda function to retrieve the credentials from the parameter.

- B. Store the database credentials as a secret in AWS Secrets Manager. Configure Secrets Manager to automatically rotate the credentials every 30 days. Update the Lambda function to retrieve the credentials from the secret.
- C. Store the database credentials as an encrypted Lambda environment variable. Write a custom Lambda function to rotate the credentials. Schedule the Lambda function to run every 30 days.
- D. Store the database credentials as a key in AWS Key Management Service (AWS KMS). Configure automatic rotation for the key. Update the Lambda function to retrieve the credentials from the KMS key.

Suggested Answer: B

A company has multiple Microsoft Windows SMB file servers and Linux NFS file servers for file sharing in an on-premises environment. As part of the company's AWS migration plan, the company wants to consolidate the file servers in the AWS Cloud.

The company needs a managed AWS storage service that supports both NFS and SMB access. The solution must be able to share between protocols. The solution must have redundancy at the Availability Zone level.

Which solution will meet these requirements?

- A. Use Amazon FSx for NetApp ONTAP for storage. Configure multi-protocol access.
- B. Create two Amazon EC2 instances. Use one EC2 instance for Windows SMB file server access and one EC2 instance for Linux NFS file server access
- C. Use Amazon FSx for NetApp ONTAP for SMB access. Use Amazon FSx for Lustre for NFS access.
- D. Use Amazon S3 storage. Access Amazon S3 through an Amazon S3 File Gateway.

Suggested Answer: A

A company runs its customer-facing web application on containers. The workload uses Amazon Elastic Container Service (Amazon ECS) on AWS Fargate. The web application is resource intensive.

The web application needs to be available 24 hours a day, 7 days a week for customers. The company expects the application to experience short bursts of high traffic. The workload must be highly available.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure an ECS capacity provider with Fargate. Conduct load testing by using a third-party tool. Rightsize the Fargate tasks in Amazon CloudWatch.
- B. Configure an ECS capacity provider with Fargate for steady state and Fargate Spot for burst traffic.
- C. Configure an ECS capacity provider with Fargate Spot for steady state and Fargate for burst traffic.
- D. Configure an ECS capacity provider with Fargate. Use AWS Compute Optimizer to rightsize the Fargate task.

Suggested Answer: B

A company's production environment consists of Amazon EC2 On-Demand Instances that run constantly between Monday and Saturday. The instances must run for only 12 hours on Sunday and cannot tolerate interruptions. The company wants to cost-optimize the production environment.

Which solution will meet these requirements MOST cost-effectively?

- A. Purchase Scheduled Reserved Instances for the EC2 instances that run for only 12 hours on Sunday. Purchase Standard Reserved Instances for the EC2 instances that run constantly between Monday and Saturday.
- B. instances that run constantly between Monday and Saturday. Purchase Convertible Reserved Instances for the EC2 instances that run for only 12 hours on Sunday. Purchase Standard Reserved Instances for the EC2 instances that run constantly between Monday and Saturday.
- C. Use Spot Instances for the EC2 instances that run for only 12 hours on Sunday. Purchase Standard Reserved Instances for the EC2 instances that run constantly between Monday and Saturday.
- D. Use Spot Instances for the EC2 instances that run for only 12 hours on Sunday. Purchase Convertible Reserved Instances for the EC2 instances that run constantly between Monday and Saturday.

Suggested Answer: D

A company has migrated several applications to AWS in the past 3 months. The company wants to know the breakdown of costs for each of these applications. The company wants to receive a regular report that includes this information.

Which solution will meet these requirements MOST cost-effectively?

- A. Use AWS Budgets to download data for the past 3 months into a .csv file. Look up the desired information.
- B. Load AWS Cost and Usage Reports into an Amazon RDS DB instance. Run SQL queries to get the desired information
- C. Tag all the AWS resources with a key for cost and a value of the application's name. Activate cost allocation tags. Use Cost Explorer to get the desired information.
- D. Tag all the AWS resources with a key for cost and a value of the application's name. Use the AWS Billing and Cost Management console to download bills for the past 3 months. Look up the desired information.

Suggested Answer: C

A company hosts a website analytics application on a single Amazon EC2 On-Demand Instance. The analytics application is highly resilient and is designed to run in stateless mode.

The company notices that the application is showing signs of performance degradation during busy times and is presenting 5xx errors. The company needs to make the application scale seamlessly.

Which solution will meet these requirements MOST cost-effectively?

- A. Create an Amazon Machine Image (AMI) of the web application. Use the AMI to launch a second EC2 On-Demand Instance. Use an Application Load Balancer to distribute the load across the two EC2 instances.
- B. Create an Amazon Machine Image (AMI) of the web application. Use the AMI to launch a second EC2 On-Demand Instance. Use Amazon Route 53 weighted routing to distribute the load across the two EC2 instances.

C. Create an AWS Lambda function to stop the EC2 instance and change the instance type. Create an Amazon CloudWatch alarm to invoke the Lambda function when CPU utilization is more than 75%.

D. Create an Amazon Machine Image (AMI) of the web application. Apply the AMI to a launch template. Create an Auto Scaling group that includes the launch template. Configure the launch template to use a Spot Fleet. Attach an Application Load Balancer to the Auto Scaling group.

Suggested Answer: D

A company runs a Node.js function on a server in its on-premises data center. The data center stores data in a PostgreSQL database. The company stores the credentials in a connection string in an environment variable on the server. The company wants to migrate its application to AWS and to replace the Node.js application server with AWS Lambda. The company also wants to migrate to Amazon RDS for PostgreSQL and to ensure that the database credentials are securely managed.

Which solution will meet these requirements with the LEAST operational overhead?

A. Store the database credentials as a parameter in AWS Systems Manager Parameter Store. Configure Parameter Store to automatically rotate the secrets every 30 days. Update the Lambda function to retrieve the credentials from the parameter.

B. Store the database credentials as a secret in AWS Secrets Manager. Configure Secrets Manager to automatically rotate the credentials every 30 days. Update the Lambda function to retrieve the credentials from the secret.

C. Store the database credentials as an encrypted Lambda environment variable. Write a custom Lambda function to rotate the credentials. Schedule the Lambda function to run every 30 days.

D. Store the database credentials as a key in AWS Key Management Service (AWS KMS). Configure automatic rotation for the key. Update the Lambda function to retrieve the credentials from the KMS key

Suggested Answer: B

An ecommerce company runs several internal applications in multiple AWS accounts. The company uses AWS Organizations to manage its AWS accounts.

- A. security appliance in the company's networking account must inspect interactions between applications across AWS accounts. Which solution will meet these requirements?
- B. Deploy a Network Load Balancer (NLB) in the networking account to send traffic to the security appliance. Configure the application accounts to send traffic to the NLB by using an interface VPC endpoint in the application accounts.
- C. Deploy an Application Load Balancer (ALB) in the application accounts to send traffic directly to the security appliance. Deploy a Gateway Load Balancer (GWLB) in the networking account to send traffic to the security appliance. Configure the application accounts to send traffic to the GWLB by using an interface GWLB endpoint in the application accounts.
- D. Deploy an interface VPC endpoint in the application accounts to send traffic directly to the security appliance.

Suggested Answer: D

A company needs to implement a new data retention policy for regulatory compliance. As part of this policy, sensitive documents that are stored in an Amazon S3 bucket must be protected from deletion or modification for a fixed period of time.

Which solution will meet these requirements?

- A. Activate S3 Object Lock on the required objects and enable governance mode.
- B. Activate S3 Object Lock on the required objects and enable compliance mode
- C. Enable versioning on the S3 bucket. Set a lifecycle policy to delete the objects after a specified period.
- D. Configure an S3 Lifecycle policy to transition objects to S3 Glacier Flexible Retrieval for the retention duration.

Suggested Answer: B

A company is migrating a legacy application from an on-premises data center to AWS. The application relies on hundreds of cron jobs that run between 1 and 20 minutes on different recurring schedules throughout the day.

The company wants a solution to schedule and run the cron jobs on AWS with minimal refactoring. The solution must support running the cron jobs in response to an event in the future.

Which solution will meet these requirements?

- A. Create a container image for the cron jobs. Use Amazon EventBridge Scheduler to create a recurring schedule. Run the cron job tasks as AWS Lambda functions.
- B. Create a container image for the cron jobs. Use AWS Batch on Amazon Elastic Container Service (Amazon ECS) with a scheduling policy to run the cron jobs
- C. Create a container image for the cron jobs. Use Amazon EventBridge Scheduler to create a recurring schedule. Run the cron job tasks on AWS Fargate
- D. Create a container image for the cron jobs. Create a workflow in AWS Step Functions that uses a Wait state to run the cron jobs at a specified time. Use the RunTask action to run the cron job tasks on AWS Fargate.

Suggested Answer: C

A company hosts its enterprise resource planning (ERP) system in the us-east-1 Region. The system runs on Amazon EC2 instances. Customers use a public API that is hosted on the EC2 instances to exchange information with the ERP system. International customers report slow API response times from their data centers.

Which solution will improve response times for the international customers MOST cost-effectively?

- A. Create an AWS Direct Connect connection that has a public virtual interface (VIF) to provide connectivity from each customer's data center to us-east-1. Route customer API requests by using a Direct Connect gateway to the ERP system API.
- B. Set up an Amazon CloudFront distribution in front of the API. Configure the CachingOptimized managed cache policy to provide improved cache efficiency.
- C. Set up AWS Global Accelerator. Configure listeners for the necessary ports. Configure endpoint groups for the appropriate Regions to distribute traffic. Create an endpoint in the group for the API.
- D. Use AWS Site-to-Site VPN to establish dedicated VPN tunnels between Regions and customer networks. Route traffic to the API over the VPN connections

Suggested Answer: B

A company has developed a non-production application that is composed of multiple microservices for each of the company's business units. A single development team maintains all the microservices.

The current architecture uses a static web frontend and a Java-based backend that contains the application logic. The architecture also uses a MySQL database that the company hosts on an Amazon EC2 instance.

The company needs to ensure that the application is secure and available globally.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon CloudFront and AWS Amplify to host the static web frontend. Refactor the microservices to use AWS Lambda functions that the microservices access by using Amazon API Gateway. Migrate the MySQL database to an Amazon EC2 Reserved Instance
- B. Use Amazon CloudFront and Amazon S3 to host the static web frontend. Refactor the microservices to use AWS Lambda functions that the microservices access by using Amazon API Gateway. Migrate the MySQL database to Amazon RDS for MySQL

C. Use Amazon CloudFront and Amazon S3 to host the static web frontend. Refactor the microservices to use AWS Lambda functions that are in a target group behind a Network Load Balancer. Migrate the MySQL database to Amazon RDS for MySQL

D. Use Amazon S3 to host the static web frontend. Refactor the microservices to use AWS Lambda functions that are in a target group behind an Application

Load Balancer Migrate the MySQL database to an Amazon EC2 Reserved Instance

Suggested Answer: B

A video game company is deploying a new gaming application to its global users. The company requires a solution that will provide near real-time reviews and rankings of the players

A solutions architect must design a solution to provide fast access to the data. The solution must also ensure the data persists on disks in the event that the company restarts the application.

Which solution will meet these requirements with the LEAST operational overhead?

A. Configure an Amazon CloudFront distribution with an Amazon S3 bucket as the origin. Store the player data in the S3 bucket.

B. Create Amazon EC2 instances in multiple AWS Regions. Store the player data on the EC2 instances. Configure Amazon Route 53 with geolocation records to direct users to the closest EC2 instance.

C. Deploy an Amazon ElastiCache for Redis cluster. Store the player data in the ElastiCache cluster.

D. Deploy an Amazon ElastiCache for Memcached cluster. Store the player data in the ElastiCache cluster

Suggested Answer: C

A company runs all its business applications in the AWS Cloud. The company uses AWS Organizations to manage multiple AWS accounts.

A solutions architect needs to review all permissions that are granted to IAM users to determine which IAM users have more permissions than required.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Use Network Access Analyzer to review all access permissions in the company's AWS accounts.
- B. Create an AWS CloudWatch alarm that activates when an IAM user creates or modifies resources in an AWS account.
- C. Use AWS Identity and Access Management (IAM) Access Analyzer to review all the company's resources and accounts.
- D. Use Amazon Inspector to find vulnerabilities in existing IAM policies.

Suggested Answer: C

A company needs to save confidential medical results in an Amazon S3 bucket. The repository must allow a few approved users to add new files. The repository must restrict all other users to read-only access by using a write once, read many (WORM) approach. The company must keep every file in the repository for a minimum of 1 year after its creation date.

Which solution will meet these requirements with the LEAST implementation effort?

- A. Configure the S3 bucket with multi-factor authentication (MFA) delete. Do not share the MFA secret with users to avoid deletion.
- B. Use S3 Object Lock in compliance mode with a retention period of 1 year. Use an IAM policy that restricts file access to specified approved users.
- C. Use an IAM role to restrict all users from deleting or changing objects in the S3 bucket. Use an S3 bucket policy to only allow the IAM role.
- D. Configure the S3 bucket to invoke an AWS Lambda function every time an object is added. Configure the function to track the hash of the saved object so that modified objects can be marked accordingly.

Suggested Answer: B

A company wants to implement new security compliance requirements for its development team to limit the use of approved Amazon Machine Images (AMIs)

The company wants to provide access to only the approved operating system and software for all its Amazon EC2 instances. The company wants the solution to have the least amount of lead time for launching EC2 instances.

Which solution will meet these requirements?

- A. Create a portfolio by using AWS Service Catalog that includes only EC2 instances launched with approved AMIs. Ensure that all required software is preinstalled on the AMIs. Create the necessary permissions for developers to use the portfolio.
- B. Create an AMI that contains the approved operating system and software by using EC2 Image Builder. Give developers access to that AMI to launch the EC2 instances.
- C. Create an AMI that contains the approved operating system. Tell the developers to use the approved AMI. Create an Amazon EventBridge rule to run an AWS Systems Manager script when a new EC2 instance is launched. Configure the script to install the required software from a repository.
- D. Create an AWS Config rule to detect the launch of EC2 instances with an AMI that is not approved. Associate a remediation rule to terminate those instances and launch the instances again with the approved AMI. Use AWS Systems Manager to automatically install the approved software on the launch of an EC2 instance

Suggested Answer: B

A company regularly uploads confidential data to Amazon S3 buckets for analysis.

The company's security policies mandate that the objects must be encrypted at rest. The company must automatically rotate the encryption key every year. The company must be able to track key rotation by using AWS CloudTrail. The company also must minimize costs for the encryption key.

Which solution will meet these requirements?

- A. Use server-side encryption with customer-provided keys (SSE-C).

- B. Use server-side encryption with Amazon S3 managed keys (SSE-S3).
- C. Use server-side encryption with AWS KMS keys (SSE-KMS).
- D. Use server-side encryption with customer managed AWS KMS keys

Suggested Answer: C

A company hosts its core network services, including directory services and DNS, in its on-premises data center. The data center is connected to the AWS Cloud using AWS Direct Connect (DX). Additional AWS accounts are planned that will require quick, cost-effective, and consistent access to these network services.

What should a solutions architect implement to meet these requirements with the LEAST amount of operational overhead?

- A. Create a DX connection in each new account. Route the network traffic to the on-premises servers.
- B. Configure VPC endpoints in the DX VPC for all required services. Route the network traffic to the on-premises servers.
- C. Create a VPN connection between each new account and the DX VPC. Route the network traffic to the on-premises servers.
- D. Configure AWS Transit Gateway between the accounts. Assign DX to the transit gateway and route network traffic to the on-premises servers.

Suggested Answer: D

Question #: 352

A company runs its production workload on an Amazon Aurora MySQL DB cluster that includes six Aurora Replicas. The company wants near-real-time reporting queries from one of its departments to be

automatically distributed across three of the Aurora Replicas. Those three replicas have a different compute and memory specification from the rest of the DB cluster.
Which solution meets these requirements?

- A. Create and use a custom endpoint for the workload. **Most Voted**
- B. Create a three-node cluster clone and use the reader endpoint.
- C. Use any of the instance endpoints for the selected three nodes.
- D. Use the reader endpoint to automatically distribute the read-only workload.

Suggested Answer: A

Question #: 365

A development team is collaborating with another company to create an integrated product. The other company needs to access an Amazon Simple Queue Service (Amazon SQS) queue that is contained in the development team's account. The other company wants to poll the queue without giving up its own account permissions to do so.
How should a solutions architect provide access to the SQS queue?

- A. Create an instance profile that provides the other company access to the SQS queue.
- B. Create an IAM policy that provides the other company access to the SQS queue.
- C. Create an SQS access policy that provides the other company access to the SQS queue.
- D. Create an Amazon Simple Notification Service (Amazon SNS) access policy that provides the other company access to the SQS queue.

Suggested Answer: C

Question #: 525

A company has multiple AWS accounts with applications deployed in the us-west-2 Region. Application logs are stored within Amazon S3 buckets in each account. The company wants to build a centralized log analysis solution that uses a single S3 bucket. Logs must not leave us-west-2, and the company

wants to incur minimal operational overhead.

Which solution meets these requirements and is MOST cost-effective?

- A. Create an S3 Lifecycle policy that copies the objects from one of the application S3 buckets to the centralized S3 bucket.
- B. Use S3 Same-Region Replication to replicate logs from the S3 buckets to another S3 bucket in us-west-2. Use this S3 bucket for log analysis. **Most Voted**
- C. Write a script that uses the PutObject API operation every day to copy the entire contents of the buckets to another S3 bucket in us-west-2. Use this S3 bucket for log analysis.
- D. Write AWS Lambda functions in these accounts that are triggered every time logs are delivered to the S3 buckets (s3:ObjectCreated:* event). Copy the logs to another S3 bucket in us-west-2. Use this S3 bucket for log analysis.

Suggested Answer: B

Question #: 787

A company has an organization in AWS Organizations that has all features enabled. The company requires that all API calls and logins in any existing or new AWS account must be audited. The company needs a managed solution to prevent additional work and to minimize costs. The company also needs to know when any AWS account is not compliant with the AWS Foundational Security Best Practices (FSBP) standard.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Deploy an AWS Control Tower environment in the Organizations management account. Enable AWS Security Hub and AWS Control Tower Account Factory in the environment. **Most Voted**
- B. Deploy an AWS Control Tower environment in a dedicated Organizations member account. Enable AWS Security Hub and AWS Control Tower Account Factory in the environment.
- C. Use AWS Managed Services (AMS) Accelerate to build a multi-account landing zone (MALZ). Submit an RFC to self-service provision Amazon GuardDuty in the MALZ.
- D. Use AWS Managed Services (AMS) Accelerate to build a multi-account landing zone (MALZ). Submit an RFC to self-service provision AWS Security Hub in the MALZ.

Suggested Answer: A

Question #: 653

A company built an application with Docker containers and needs to run the application in the AWS Cloud. The company wants to use a managed service to host the application.

The solution must scale in and out appropriately according to demand on the individual container services. The solution also must not result in additional operational overhead or infrastructure to manage.

Which solutions will meet these requirements? (Choose two.)

- A. Use Amazon Elastic Container Service (Amazon ECS) with AWS Fargate
- B. Use Amazon Elastic Kubernetes Service (Amazon EKS) with AWS Fargate
- C. Provision an Amazon API Gateway API. Connect the API to AWS Lambda to run the containers
- D. Use Amazon Elastic Container Service (Amazon ECS) with Amazon EC2 worker nodes
- E. Use Amazon Elastic Kubernetes Service (Amazon EKS) with Amazon EC2 worker nodes

Suggested Answer: AB

Question #: 231

A company stores user data in AWS. The data is used continuously with peak usage during business hours. Access patterns vary, with some data not being used for months at a time. A solutions architect must choose a cost-effective solution that maintains the highest level of durability while maintaining high availability.

Which storage solution meets these requirements?

- A. Amazon S3 Standard
- B. Amazon S3 Intelligent-Tiering **Most Voted**
- C. Amazon S3 Glacier Deep Archive
- D. Amazon S3 One Zone-Infrequent Access (S3 One Zone-IA)

Suggested Answer: B

Question #: 211

A solutions architect is creating an application that will handle batch processing of large amounts of data. The input data will be held in Amazon S3 and the output data will be stored in a different S3 bucket. For processing, the application will transfer the data over the network between multiple Amazon EC2 instances.

What should the solutions architect do to reduce the overall data transfer costs?

- A. Place all the EC2 instances in an Auto Scaling group.
- B. Place all the EC2 instances in the same AWS Region.
- C. Place all the EC2 instances in the same Availability Zone. **Most Voted**
- D. Place all the EC2 instances in private subnets in multiple Availability Zones.

Suggested Answer: C

Question #: 424

A company is planning to migrate a legacy application to AWS. The application currently uses NFS to communicate to an on-premises storage solution to store application data. The application cannot be modified to use any other communication protocols other than NFS for this purpose.

Which storage solution should a solutions architect recommend for use after the migration?

- A. AWS DataSync
- B. Amazon Elastic Block Store (Amazon EBS)
- C. Amazon Elastic File System (Amazon EFS)
- D. Amazon EMR File System (Amazon EMRFS)

Suggested Answer: C

Question #: 570

A company is creating a prototype of an ecommerce website on AWS. The website consists of an Application Load Balancer, an Auto Scaling group of Amazon EC2 instances for web servers, and an Amazon RDS for MySQL DB instance that runs with the Single-AZ configuration.

The website is slow to respond during searches of the product catalog. The product catalog is a group of tables in the MySQL database that the company does not update frequently. A solutions architect has determined that the CPU utilization on the DB instance is high when product catalog searches occur. What should the solutions architect recommend to improve the performance of the website during searches of the product catalog?

- A. Migrate the product catalog to an Amazon Redshift database. Use the COPY command to load the product catalog tables.
- B. Implement an Amazon ElastiCache for Redis cluster to cache the product catalog. Use lazy loading to populate the cache. **Most Voted**
- C. Add an additional scaling policy to the Auto Scaling group to launch additional EC2 instances when database response is slow.
- D. Turn on the Multi-AZ configuration for the DB instance. Configure the EC2 instances to throttle the product catalog queries that are sent to the database.

Suggested Answer: B

Question #: 664

A company has hired an external vendor to perform work in the company's AWS account. The vendor uses an automated tool that is hosted in an AWS account that the vendor owns. The vendor does not have IAM access to the company's AWS account.

How should a solutions architect grant this access to the vendor?

- A. Create a IAM role in the company's account to delegate access to the vendor's IAM role. Attach the appropriate IAM policies to the role for the permissions that the vendor requires.

- B. Create an IAM user in the company's account with a password that meets the password complexity requirements. Attach the appropriate IAM policies to the user for the permissions that the vendor requires.
- C. Create an IAM group in the company's account. Add the tool's IAM user from the vendor account to the group for the permissions that the vendor requires.
- D. Create a new identity provider by choosing "AWS account" as the provider type in the IAM console. Supply the vendor's AWS account ID and user name. Attach the appropriate IAM policies to the new provider for the permissions that the vendor requires.

Suggested Answer: A

Question #: 497

A company has primary and secondary data centers that are 500 miles (804.7 km) apart and interconnected with high-speed fiber-optic cable. The company needs a highly available and secure network connection between its data centers and a VPC on AWS for a mission-critical workload. A solutions architect must choose a connection solution that provides maximum resiliency. Which solution meets these requirements?

- A. Two AWS Direct Connect connections from the primary data center terminating at two Direct Connect locations on two separate devices
- B. A single AWS Direct Connect connection from each of the primary and secondary data centers terminating at one Direct Connect location on the same device
- C. Two AWS Direct Connect connections from each of the primary and secondary data centers terminating at two Direct Connect locations on two separate devices
- D. A single AWS Direct Connect connection from each of the primary and secondary data centers terminating at one Direct Connect location on two separate devices

Suggested Answer: C

Question #: 550

A solutions architect at a company is designing the architecture for a two-tiered web application. The web application is composed of an internet-facing Application Load Balancer (ALB) that forwards traffic to an Auto Scaling group of Amazon EC2 instances. The EC2 instances must be able to access a database that runs on Amazon RDS.

The company has requested a defense-in-depth approach to the network layout. The company does not want to rely solely on security groups or network ACLs.

Only the minimum resources that are necessary should be routable from the internet.

Which network design should the solutions architect recommend to meet these requirements?

- A. Place the ALB, EC2 instances, and RDS database in private subnets.
- B. Place the ALB in public subnets. Place the EC2 instances and RDS database in private subnets. **Most Voted**
- C. Place the ALB and EC2 instances in public subnets. Place the RDS database in private subnets.
- D. Place the ALB outside the VPC. Place the EC2 instances and RDS database in private subnets.

Suggested Answer: B

An ecommerce company is preparing to deploy a web application on AWS to ensure continuous service for customers. The architecture includes a web application that the company hosts on Amazon EC2 instances, a relational database in Amazon RDS, and static assets that the company stores in Amazon S3.

The company wants to design a robust and resilient architecture for the application.

Which solution will meet these requirements?

- A. Deploy Amazon EC2 instances in a single Availability Zone. Deploy an RDS DB instance in the same Availability Zone. Use Amazon S3 with versioning enabled to store static assets.
- B. Deploy Amazon EC2 instances in an Auto Scaling group across multiple Availability Zones. Deploy a Multi-AZ RDS DB instance. Use Amazon CloudFront to distribute static assets

C. Deploy Amazon EC2 instances in a single Availability Zone. Deploy an RDS DB instance in a second Availability Zone for cross-AZ redundancy. Serve static assets directly from the EC2 instances

D. Use AWS Lambda functions to serve the web application. Use Amazon Aurora Serverless v2 for the database. Store static assets in Amazon Elastic File System (Amazon EFS) One Zone-Infrequent Access (One Zone-IA)

Suggested Answer: B

financial services company plans to launch a new application on AWS to handle sensitive financial transactions. The company will deploy the application on Amazon EC2 instances. The company will use Amazon RDS for MySQL as the database. The company's security policies mandate that data must be encrypted at rest and in transit.

Which solution will meet these requirements with the LEAST operational overhead?

A. Configure encryption at rest for Amazon RDS for MySQL by using AWS KMS managed keys. Configure AWS Certificate Manager (ACM) SSL/TLS certificates for encryption in transit.

B. Configure encryption at rest for Amazon RDS for MySQL by using AWS KMS managed keys. Configure IPsec tunnels for encryption in transit.

C. Implement third-party application-level data encryption before storing data in Amazon RDS for MySQL. Configure AWS Certificate Manager (ACM) SSL/TLS certificates for encryption in transit

D. Configure encryption at rest for Amazon RDS for MySQL by using AWS KMS managed keys. Configure a VPN connection to enable private connectivity to encrypt data in transit

Suggested Answer: B

A company uses an Amazon RDS for MySQL instance. To prepare for end-of-year processing, the company added a read replica to accommodate extra read-only queries from the company's reporting tool. The read replica CPU usage was 60% and the primary instance CPU usage was 60%.

After end-of-year activities are complete, the read replica has a constant 25% CPU usage. The primary instance still has a constant 60% CPU usage. The company wants to rightsize the database and still provide enough performance for future growth

Which solution will meet these requirements?

- A. Delete the read replica. Do not make changes to the primary instance
- B. Resize the read replica to a smaller instance size. Do not make changes to the primary instance.
- C. Resize the read replica to a larger instance size. Resize the primary instance to a smaller instance size.
- D Delete the read replica. Resize the primary instance to a larger instance.

Suggested Answer: C

A company is building an application that runs on Amazon EC2 instances that are in multiple Availability Zones. The EC2 instances run Amazon Linux. The application parses terabytes of data every day. The application saves the output to Amazon SageMaker for further processing.

A solutions architect must implement a scalable solution to meet the storage demand of the application.

Which storage solution will meet these requirements in the MOST cost-effective way?

- A. Create an Amazon Elastic File System (Amazon EFS) file system. Mount the file system on all the EC2 instances. Configure the application to save data to the EFS file system.
- B. Create an Amazon Elastic Block Store (Amazon EBS) General Purpose SSD (gp3) volume for each EC2 instance. Attach the EBS volumes to the EC2 instances. Configure the application to save data to the EBS volumes.
- C. Create an Amazon S3 bucket and an Amazon S3 gateway endpoint. Configure an IAM role to have permissions to write to Amazon S3. Attach the IAM role to an instance profile. Attach the instance profile to each EC2 instance.

D. Create an Amazon Elastic Block Store (Amazon EBS) Provisioned IOPS SSD (io2) Block Express volume for each EC2 instance. Attach the EBS volumes to the EC2 instances. Configure the application to save data to the EBS volumes.

Suggested Answer: C

A company is designing an application on AWS that processes sensitive data. The application stores and processes financial data for multiple customers.

To meet compliance requirements, the data for each customer must be encrypted separately at rest by using a secure, centralized key management solution. The company wants to use AWS Key Management Service (AWS KMS) to implement encryption.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Generate a unique encryption key for each customer. Store the keys in an Amazon S3 bucket. Enable server-side encryption.
- B. Deploy a hardware security appliance in the AWS environment that securely stores customer-provided encryption keys. Integrate the security appliance with AWS KMS to encrypt the sensitive data in the application.
- C. Create a single AWS KMS key to encrypt all sensitive data across the application.
- D. Create separate AWS KMS keys for each customer's data that have granular access control and logging enabled

Suggested Answer: D

A company wants to deploy its containerized application workloads to a VPC across three Availability Zones. The company needs a solution that is highly available across Availability Zones. The solution must require minimal changes to the application.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Elastic Container Service (Amazon ECS). Configure Amazon ECS Service Auto Scaling to use target tracking scaling. Set the minimum capacity to 3. Set the task placement strategy type to spread with an Availability Zone attribute.

B. Use Amazon Elastic Kubernetes Service (Amazon EKS) self-managed nodes. Configure Application Auto Scaling to use target tracking scaling. Set the minimum capacity to 3

C. Use Amazon EC2 Reserved Instances. Launch three EC2 instances in a spread placement group. Configure an Auto Scaling group to use target tracking scaling. Set the minimum capacity to 3

D. Use an AWS Lambda function. Configure the Lambda function to connect to a VPC. Configure Application Auto Scaling to use Lambda as a scalable target. Set the minimum capacity to 3.

Suggested Answer: A

A company has an organization in AWS Organizations that has all features enabled. The company requires that all API calls and logins in any existing or new AWS account must be audited. The company needs a managed solution to prevent additional work and to minimize costs. The company also needs to know when any AWS account is not compliant with the AWS Foundational Security Best Practices (FSBP) standard.

Which solution will meet these requirements with the LEAST operational overhead?

A. Deploy an AWS Control Tower environment in the Organizations management account. Enable AWS Security Hub and AWS Control Tower Account Factory in the environment.

B. Deploy an AWS Control Tower environment in a dedicated Organizations member account. Enable AWS Security Hub and AWS Control Tower Account Factory in the environment

C. Use AWS Managed Services (AMS) Accelerate to build a multi-account landing zone (MALZ). Submit an RFC to self-service provision Amazon GuardDuty in the MALZ

D. Use AWS Managed Services (AMS) Accelerate to build a multi-account landing zone (MALZ). Submit an RFC to self-service provision AVVS Security Hub in the MALZ

Suggested Answer: A

A company hosts its core network services, including directory services and DNS, in its on-premises data center. The data center is connected to the AWS Cloud using AWS Direct Connect (DX) Additional AWS accounts are planned that will require quick, cost-effective, and consistent access to these network services

What should a solutions architect implement to meet these requirements with the LEAST amount of operational overhead?

- A. Create a DX connection in each new account. Route the network traffic to the on-premises servers
- B. Configure VPC endpoints in the DX VPC for all required services. Route the network traffic to the on-premises servers
- C. Create a VPN connection between each new account and the DX VPC Route the network traffic to the on-premises servers
- D. Configure AWS Transit Gateway between the accounts. Assign DX to the transit gateway and route network traffic to the on-premises servers.

Suggested Answer: D

A company has applications that run in an organization in AWS Organizations. The company outsources operational support of the applications. The company needs to provide access for the external support engineers without compromising security.

The external support engineers need access to the AWS Management Console. The external support engineers also need operating system access to the company's fleet of Amazon EC2 instances that run Amazon Linux in private subnets

Which solution will meet these requirements MOST securely?

- A. Confirm that AWS Systems Manager Agent (SSM Agent) is installed on all instances. Assign an instance profile with the necessary policy to connect to Systems Manager. Use AWS IAM Identity Center to provide the external support engineers console access Use Systems Manager Session Manager to assign the required permissions
- B. Confirm that AWS Systems Manager Agent (SSM Agent) is installed on all instances. Assign an instance profile with the necessary policy to connect to Systems Manager. Use Systems Manager Session Manager to provide local IAM user credentials in each AWS account to the external support engineers for console access

C. Confirm that all instances have a security group that allows SSH access only from the external support engineers' source IP address ranges. Provide local IAM user credentials in each AWS account to the external support engineers for console access Provide each external support engineer an SSH key pair to log in to the application instances

D. Create a bastion host in a public subnet. Set up the bastion host security group to allow access from only the external engineers IP address ranges. Ensure that all instances have a security group that allows SSH access from the bastion host. Provide each external support engineer an SSH key par to log in to the application instarices Provide local account IAM user credentials to the engineers for console access.

Suggested Answer: A

A company wants to replicate existing and ongoing data changes from an on-premises Oracle database to Amazon RDS for Oracle. The amount of data to replicate varies throughout each day. The company wants to use AWS Database Migration Service (AWS DMS) for data replication. The solution must allocate only the capacity that the replication instance requires

Which solution will meet these requirements?

A. Configure the AWS DMS replication instance with a Multi-AZ deployment to provision instances across multiple Availability Zones

B. Create an AWS DMS Serverless replication task to analyze and replicate the data while provisioning the required capacity

c. Use Amazon EC2 Auto Scaling to scale the size of the AWS DMS replication instance up or down based on the amount of data to replicate

D. Provision AWS DMS replication capacity by using Amazon Elastic Container Service (Amazon ECS) with an AWS Fargate launch type to analyze and replicate the data while provisioning the required capacity

Suggested Answer: B

A company needs a solution to automate email ingestion. The company needs to automatically parse email messages, look for email attachments, and save any attachments to an Amazon S3 bucket in near real time. Email volume varies significantly from day to day.

Which solution will meet these requirements?

- A. Set up email receiving in Amazon Simple Email Service (Amazon SES). Create a rule set and a receipt rule. Create an AWS Lambda function that Amazon SES can invoke to process the email bodies and attachments.
- B. Set up email content filtering in Amazon Simple Email Service (Amazon SES). Create a content filtering rule based on sender, recipient, message body, and attachments.
- C. Set up email receiving in Amazon Simple Email Service (Amazon SES). Configure Amazon SES and S3 Event Notifications to process the email bodies and attachments.
- D. Create an AWS Lambda function to process the email bodies and attachments. Use Amazon EventBridge to invoke the Lambda function. Configure an EventBridge rule to listen for incoming emails.

Suggested Answer: A

A company hosts an ecommerce application on AWS by using Amazon EC2 instances. The EC2 instances are spread across three Availability Zones behind an Application Load Balancer (ALB). The EC2 instances are in an Auto Scaling group. Some application users report that the application occasionally directs users who have already authenticated to the login page. The users must log in again.

The company needs a solution that will prevent the application from redirecting authenticated users to the login page.

Which solution will meet this requirement?

- A. Manually terminate the EC2 instances. Wait for the Auto Scaling group to launch new EC2 instances automatically.
- B. Configure the ALB to direct user activities to the appropriate EC2 instance through the IPv4 IP address of the instance that is registered as a target in the target group.
- C. Apply session affinity with application-based stickiness at the target group level.
- D. Configure the ALB to direct user activities to just one EC2 instance that is registered as a target in the target group.

Suggested Answer: C

A company is migrating from a monolithic architecture for a web application that is hosted on Amazon EC2 to a serverless microservices architecture. The company wants to use AWS services that support an event-driven, loosely coupled architecture. The company wants to use the publish/subscribe (pub/sub) pattern.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure an Amazon API Gateway REST API to invoke an AWS Lambda function that publishes events to an Amazon Simple Queue Service (Amazon SQS) queue. Configure one or more subscribers to read events from the SQS queue.
- B. Configure an Amazon API Gateway REST API to invoke an AWS Lambda function that publishes events to an Amazon Simple Notification Service (Amazon SNS) topic. Configure one or more subscribers to receive events from the SNS topic
- C. Configure an Amazon API Gateway WebSocket API to write to a data stream in Amazon Kinesis Data Streams with enhanced fan-out. Configure one or more subscribers to receive events from the data stream
- D. Configure an Amazon API Gateway HTTP API to invoke an AWS Lambda function that publishes events to an Amazon Simple Notification Service (Amazon SNS) topic. Configure one or more subscribers to receive events from the topic

Suggested Answer: B

A finance company uses an on-premises search application to collect streaming data from various producers. The application provides real-time updates to search and visualization features

The company is planning to migrate to AWS and wants to use an AWS native solution.

Which solution will meet these requirements?

- A. Use Amazon EC2 instances to ingest and process the data streams to Amazon S3 buckets for storage. Use Amazon Athena to search the data. Use Amazon Managed Grafana to create visualizations

B. Use Amazon EMR to ingest and process the data streams to Amazon Redshift for storage. Use Amazon Redshift Spectrum to search the data. Use Amazon QuickSight to create visualizations

C. Use Amazon Elastic Kubernetes Service (Amazon EKS) to ingest and process the data streams to Amazon DynamoDB for storage. Use Amazon Cloudwatch to create graphical dashboards to search and visualize the data

D. Use Amazon Kinesis Data Streams to ingest and process the data streams to Amazon OpenSearch Service. Use OpenSearch Service to search the data. Use Amazon QuickSight to create visualizations

Suggested Answer: D

A company is designing a new internal web application in the AWS Cloud. The new application must securely retrieve and store multiple employee usernames and passwords from an AWS managed service.

Which solution will meet these requirements with the LEAST operational overhead?

A. Store the employee credentials in AWS Systems Manager Parameter Store. Use AWS CloudFormation and the BatchGetSecretValue API to retrieve usernames and passwords from Parameter Store.

B. Store the employee credentials in AWS Secrets Manager. Use AWS CloudFormation and AWS Batch with the BatchGetSecretValue API to retrieve the usernames and passwords from Secrets Manager.

C. Store the employee credentials in AWS Systems Manager Parameter Store. Use AWS CloudFormation and AWS Batch with the BatchGetSecretValue API to retrieve the usernames and passwords from Parameter Store.

D. Store the employee credentials in AWS Secrets Manager. Use AWS CloudFormation and the BatchGetSecretValue API to retrieve the usernames and passwords from Secrets Manager.

Suggested Answer: B

A company uses AWS Systems Manager for routine management and patching of Amazon EC2 instances. The EC2 instances are in an IP address type target group behind an Application Load Balancer (ALB).

New security protocols require the company to remove EC2 instances from service during a patch. When the company attempts to follow the security protocol during the next patch, the company receives errors during the patching window.

Which combination of solutions will resolve the errors? (Select TWO)

- A. Change the target type of the target group from IP address type to instance type
- B. Continue to use the existing Systems Manager document without changes because it is already optimized to handle instances that are in an IP address type target group behind an ALB
- C. Implement the AWSEC2-PatchLoadBalancerinstance Systems Manager Automation document to manage the patching process
- D. Use Systems Manager Maintenance Windows to automatically remove the instances from service to patch the instances
- E. Configure Systems Manager State Manager to remove the instances from service and manage the patching schedule. Use ALB health checks to re-route traffic

Suggested Answer: CD

A weather forecasting company collects temperature readings from various sensors on a continuous basis. An existing data ingestion process collects the readings and aggregates the readings into larger Apache Parquet files. Then the process encrypts the files by using client-side encryption with KMS managed keys (CSE-KMS). Finally, the process writes the files to an Amazon S3 bucket with separate prefixes for each calendar day.

The company wants to run occasional SQL queries on the data to take sample moving averages for a specific calendar day.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure Amazon Athena to read the encrypted files. Run SQL queries on the data directly in Amazon S3
- B. Use Amazon S3 Select to run SQL queries on the data directly in Amazon S3
- C. Configure Amazon Redshift to read the encrypted files. Use Redshift Spectrum and Redshift query editor v2 to run SQL queries on the data directly in Amazon S3
- D. Configure Amazon EMR Serverless to read the encrypted files. Use Apache SparkSQL to run SQL queries on the data directly in Amazon S3

Suggested Answer: A

A software company needs to upgrade a critical web application. The application currently runs on a single Amazon EC2 instance that the company hosts in a public subnet. The EC2 instance runs a MySQL database. The application's DNS records are published in an Amazon Route 53 zone

A solutions architect must reconfigure the application to be scalable and highly available. The solutions architect must also reduce MySQL read latency

Which combination of solutions will meet these requirements? (Select TWO)

- A. Launch a second EC2 instance in a second AWS Region. Use a Route 53 failover routing policy to redirect the traffic to the second EC2 instance.
- B. Create and configure an Auto Scaling group to launch private EC2 instances in multiple Availability Zones. Add the instances to a target group behind a new Application Load Balancer.
- C. Migrate the database to an Amazon Aurora MySQL cluster Create the primary DB instance and master DB instance in separate Availability Zones
- D. Create and configure an Auto Scaling group to launch private EC2 instances in multiple AWS Regions. Add the instances to a target group behind a new Application Load Balancer
- E. Migrate the database to an Amazon Aurora MySQL cluster with cross-Region read replicas

Suggested Answer: BC

A company runs its legacy web application on AWS. The web application server runs on an Amazon EC2 instance in the public subnet of a VPC. The web application server collects images from customers and stores the image files in a locally attached Amazon Elastic Block Store (Amazon EBS) volume The image files are uploaded every night to an Amazon S3 bucket for backup

A solutions architect discovers that the image files are being uploaded to Amazon S3 through the public endpoint. The solutions architect needs to ensure that traffic to Amazon S3 does not use the public endpoint

Which solution will meet these requirements?

- A. Create a gateway VPC endpoint for the S3 bucket that has the necessary permissions for the VPC. Configure the subnet route table to use the gateway VPC endpoint
- B. Move the S3 bucket inside the VPC. Configure the subnet route table to access the S3 bucket through private IP addresses
- C. Create an Amazon S3 access point for the Amazon EC2 instance inside the VPC. Configure the web application to upload by using the Amazon S3 access point
- D. Configure an AWS Direct Connect connection between the VPC that has the Amazon EC2 instance and Amazon S3 to provide a dedicated network path

Suggested Answer: A

A company is migrating an on-premises application to the AWS Cloud. The application compute nodes in AWS will consist of multiple Amazon EC2 instances across multiple Availability Zones within the us-east-1 Region. The company expects the amount of application data to increase for the next 12 months. Every EC2 instance must be able to access the same data.

Which solution will meet these requirements?

- A. Store the application data in Amazon Elastic Block Store (Amazon EBS) General Purpose volumes. Mount the EBS volumes on all the EC2 instances
- B. Store the application data in Amazon Elastic Block Store (Amazon EBS) Provisioned IOPS volumes. Mount the EBS volumes on all the EC2 instances
- C. Store the application data in an Amazon Elastic File System (Amazon EFS) file system. Create a mount target in each Availability Zone. Mount the file system on all the EC2 instances
- D. Store the application data in Amazon S3 Express One Zone buckets. Mount the S3 buckets on all the EC2 instances

Suggested Answer: C

A company is building an application on AWS. The application uses multiple AWS Lambda functions to retrieve sensitive data from a single Amazon S3 bucket for processing. The company must ensure that only authorized Lambda functions can access the data. The solution must comply with the principle of least privilege.

Which solution will meet those requirements?

- A. Grant full S3 bucket access to all Lambda functions through a shared IAM role
- B. Configure the Lambda functions to run within a VPC. Configure a bucket policy to grant access based on the Lambda functions VPC endpoint IP addresses
- C. Create individual IAM roles for each Lambda function. Grant the IAM roles access to the S3 bucket. Assign each IAM role as the Lambda execution role for its corresponding Lambda function
- D. Configure a bucket policy granting access to the Lambda functions based on their function ARNs.

Suggested Answer: C

A company is designing a new internal web application in the AWS Cloud. The new application must securely retrieve and store multiple employee usernames and passwords from an AWS managed service. Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the employee credentials in AWS Systems Manager Parameter Store. Use AWS CloudFormation and the BatchGetSecretValue API to retrieve usernames and passwords from Parameter Store
- B. Store the employee credentials in AWS Secrets Manager. Use AWS CloudFormation and AWS Batch with the BatchGetSecretValue API to retrieve the usernames and passwords from Secrets Manager
- C. Store the employee credentials in AWS Systems Manager Parameter Store. Use AWS CloudFormation and AWS Batch with the BatchGetSecretValue API to retrieve the usernames and passwords from Parameter Store
- D. Store the employee credentials in AWS Secrets Manager. Use AWS CloudFormation and the BatchGetSecretValue API to retrieve the usernames and passwords from Secrets Manager

Suggested Answer: D

A company is planning to deploy a managed MySQL database solution for its non-production applications. The company plans to run the system for several years on AWS

Which solution will meet these requirements MOST cost-effectively?

- A. Create an Amazon RDS for MySQL instance. Purchase a Reserved instance
- B. Create an Amazon RDS for MySQL instance. Use the instance on an on-demand bases
- C. Create an Amazon Aurora MySQL cluster with writer and reader nodes. Use the cluster on an on-demand basas
- D. Create an Amazon EC2 instance Manually install and configure MySQL Server on the instance

Suggested Answer: A

A company hosts its main public web application in one AWS Region across multiple Availability Zones. The application uses an Amazon EC2 Auto Scaling group and an Application Load Balancer (ALB)

A web development team needs a cost-optimized compute solution to improve the company's ability to serve dynamic content globally to millions of customers

Which solution will meet these requirements?

- A. Create an Amazon CloudFront distribution. Configure the existing ALB as the origin
- B. Use Amazon Route 53 to serve traffic to the ALB and EC2 instances based on the geographic location of each customer
- C. Create an Amazon S3 bucket with public read access enabled. Migrate the web application to the S3 bucket Configure the \$3 bucket for website hosting
- D. Use AWS Direct Connect to directly serve content from the web application to the location of each customer

Suggested Answer: A

A company is using AWS DataSync to migrate millions of files from an on-premises system to AWS. The files are 10 KB in size on average

The company wants to use Amazon S3 for file storage. For the first year after the migration, the files will be accessed once or twice and must be immediately available After 1 year, the files must be archived for at least 7 years.

Which solution will meet these requirements MOST cost-effectively?

- A. Use an archive tool to group the files into large objects. Use DataSync to migrate the objects. Store the objects in S3 Glacier Instant Retrieval for the first year. Use a lifecycle configuration to transition the files to S3 Glacier Deep Archive after 1 year with a retention period of 7 years.
- B. Use an archive tool to group the files into large objects. Use DataSync to copy the objects to S3 Standard-Infrequent Access (S3 Standard-IA) Use a lifecycle configuration to transition the files to S3 Glacier Instant Retrieval after 1 year with a retention period of 7 years.
- C. Configure the destination storage class for the files as S3 Glacier Instant Retrieval. Use a lifecycle policy to transition the files to S3 Glacier Flexible Retrieval after 1 year with a retention period of 7 years.
- D. Configure a DataSync task to transfer the files to S3 Standard-Infrequent Access (S3 Standard-IA). Use a lifecycle configuration to transition the files to S3 Deep Archive after 1 year with a retention period of 7 years.

Suggested Answer: D

A company tracks customer satisfaction by using surveys that the company hosts on its website. The surveys sometimes reach thousands of customers every hour. Survey results are currently sent in email messages to the company so company employees can manually review results and assess customer sentiment.

The company wants to automate the customer survey process. Survey results must be available for the previous 12 months

Which solution will meet these requirements in the MOST scalable way?

- A. Send the survey results data to an Amazon API Gateway endpoint that is connected to an Amazon Simple Queue Service (Amazon SQS) queue. Create an AWS Lambda function to poll the SQS queue, call Amazon

Comprehend for sentiment analysis, and save the results to an Amazon DynamoDB table. Set the TTL for all records to 365 days in the future.

B. Send the survey results data to an API that is running on an Amazon EC2 instance. Configure the API to store the survey results as a new record in an Amazon DynamoDB table, call Amazon Comprehend for sentiment analysis, and save the results in a second DynamoDB table Set the TTL for all records to 365 days in the future.

C. Write the survey results data to an Amazon S3 bucket. Use S3 Event Notifications to invoke an AWS Lambda function to read the data and call Amazon Rekognition for sentiment analysis. Store the sentiment analysis results in a second S3 bucket. Use S3 Lifecycle policies on each bucket to expire objects after 365 days.

D. Send the survey results data to an Amazon API Gateway endpoint that is connected to an Amazon Simple Queue Service (Amazon SQS) queue Configure the SQS queue to invoke an AWS Lambda function that calls Amazon Lex for sentiment analysis and saves the results to an Amazon DynamoDB table. Set the TTL for all records to 365 days in the future

Suggested Answer: A

A weather forecasting company collects temperature readings from various sensors on a continuous basis. An existing data ingestion process collects the readings and aggregates the readings into larger Apache Parquet files. Then the process encrypts the files by using client-side encryption with KMS managed keys (CSE-KMS) Finally, the process writes the files to an Amazon S3 bucket with separate prefixes for each calendar day.

The company wants to run occasional SQL queries on the data to take sample moving averages for a specific calendar day.

Which solution will meet these requirements MOST cost-effectively?

A. Configure Amazon Athena to read the encrypted files. Run SQL queries on the data directly in Amazon S3.

B. Use Amazon S3 Select to run SQL queries on the data directly in Amazon S3.

C. Configure Amazon Redshift to read the encrypted files. Use Redshift Spectrum and Redshift query editor v2 to run SQL queries on the data directly in Amazon S3

D. Configure Amazon EMR Serverless to read the encrypted files. Use Apache SparkSQL to run SQL queries on the data directly in Amazon S3.

Suggested Answer: A

A company wants to deploy its containerized application workloads to a VPC across three Availability Zones. The company needs a solution that is highly available across Availability Zones. The solution must require minimal changes to the application.

Which solution will meet these requirements with the LEAST operational overhead?

A. Use Amazon Elastic Container Service (Amazon ECS). Configure Amazon ECS Service Auto Scaling to use target tracking scaling. Set the minimum capacity to 3. Set the task placement strategy type to spread with an Availability Zone attribute.

B. Use Amazon Elastic Kubernetes Service (Amazon EKS) self-managed nodes. Configure Application Auto Scaling to use target tracking scaling. Set the minimum capacity to 3.

C. Use Amazon EC2 Reserved Instances. Launch three EC2 instances in a spread placement group. Configure an Auto Scaling group to use target tracking scaling. Set the minimum capacity to 3.

D. Use an AWS Lambda function. Configure the Lambda function to connect to a VPC. Configure Application Auto Scaling to use Lambda as a scalable target. Set the minimum capacity to 3.

Suggested Answer: A

A company wants to use an AWS CloudFormation stack for its application in a test environment. The company stores the CloudFormation template in an Amazon S3 bucket that blocks public access. The company wants to grant CloudFormation access to the template in the S3 bucket based on specific user requests to create the test environment. The solution must follow security best practices.

Which solution will meet these requirements?

A. Create a gateway VPC endpoint for Amazon S3. Configure the CloudFormation stack to use the S3 object URL.

B. Create an Amazon API Gateway REST API that has the S3 bucket as the target. Configure the CloudFormation stack to use the API Gateway URL

C. Create a presigned URL for the template object. Configure the CloudFormation stack to use the presigned URL

D. Allow public access to the template object in the S3 bucket. Block the public access after the test environment is created.

Suggested Answer: C

A company runs a self-managed Microsoft SQL Server on Amazon EC2 instances and Amazon Elastic Block Store (Amazon EBS) Daily snapshots are taken of the EBS volumes.

Recently, all the company's EBS snapshots were accidentally deleted while running a snapshot cleaning script that deletes all expired EBS snapshots. A solutions architect needs to update the architecture to prevent data loss without retaining EBS snapshots indefinitely.

Which solution will meet these requirements with the LEAST development effort?

A. Change the IAM policy of the user to deny EBS snapshot deletion.

B. Copy the EBS snapshots to another AWS Region after completing the snapshots daily.

C. Create a 7-day EBS snapshot retention rule in Recycle Bin and apply the rule for all snapshots.

D. Copy EBS snapshots to Amazon S3 Standard-Infrequent Access (S3 Standard-IA).

Suggested Answer: C

A company runs an on-premises application on a Kubernetes cluster. The company recently added millions of new customers. The company's existing on-premises

infrastructure is unable to handle the large number of new customers. The company needs to migrate the on-premises application to the AWS Cloud. The company will migrate to an Amazon Elastic Kubernetes Service (Amazon EKS) cluster. The company does not want to manage the underlying compute infrastructure

for the new architecture on AWS.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use a self-managed node to supply compute capacity. Deploy the application to the new EKS cluster.
- B. Use managed node groups to supply compute capacity. Deploy the application to the new EKS cluster.
- C. Use AWS Fargate to supply compute capacity. Create a Fargate profile. Use the Fargate profile to deploy the application
- D. Use managed node groups with Karpenter to supply compute capacity. Deploy the application to the new EKS cluster

Suggested Answer: C

A company has a multi-tier web application. The application's internal service components are deployed on Amazon EC2 instances. The internal service components need to access third-party software as a service (SaaS) APIs that are hosted on AWS.

The company needs to provide secure and private connectivity from the application's internal services to the third-party SaaS application. The company needs to ensure that there is minimal public internet exposure.

Which solution will meet these requirements?

- A. Implement an AWS Site-to-Site VPN to establish a secure connection with the third-party SaaS provider.
- B. Deploy AWS Transit Gateway to manage and route traffic between the application's VPC and the third-party SaaS provider.
- C. Configure AWS PrivateLink to allow only outbound traffic from the VPC without enabling the third-party SaaS provider to establish a return path to the network.
- D. Use AWS PrivateLink to create a private connection between the application's VPC and the third-party SaaS provider.

Suggested Answer: D

A company is migrating an application from an on-premises environment to AWS. The application will store sensitive data in Amazon S3. The company must encrypt the data before storing the data in Amazon S3.

Which solution will meet these requirements?

- A. Encrypt the data by using client-side encryption with customer managed keys.
- B. Encrypt the data by using server-side encryption with AWS KMS keys (SSE-KMS).
- C. Encrypt the data by using server-side encryption with customer-provided keys (SSE-C)
- D. Encrypt the data by using client-side encryption with Amazon S3 managed keys.

Suggested Answer: A

A company has an organization in AWS Organizations that has all features enabled. The company requires that all API calls and logins in any existing or new AWS account must be audited. The company needs a managed solution to prevent additional work and to minimize costs. The company also needs to know when any AWS account is not compliant with the AWS Foundational Security Best Practices (FSBP) standard.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Deploy an AWS Control Tower environment in the Organizations management account. Enable AWS Security Hub and AWS Control Tower Account Factory in the environment.
- B. Deploy an AWS Control Tower environment in a dedicated Organizations member account. Enable AWS Security Hub and AWS Control Tower Account Factory in the environment.
- C. Use AWS Managed Services (AMS) Accelerate to build a multi-account landing zone (MALZ) Submit an RFC to self-service provision Amazon GuardDuty in the MALZ
- D. Use AWS Managed Services (AMS) Accelerate to build a multi-account landing zone (MALZ). Submit an RFC to self-service provision AWS Security Hub in the

Suggested Answer: A

A company wants to improve the availability and performance of its hybrid application. The application consists of a stateful TCP-based workload hosted on Amazon EC2 instances in different AWS Regions and a stateless UDP-based workload hosted on premises.

Which combination of actions should a solutions architect take to improve availability and performance? (Select TWO.)

- A. Create an accelerator using AWS Global Accelerator. Add the load balancers as endpoints.
- B. Create an Amazon CloudFront distribution with an origin that uses Amazon Route 53 latency-based routing to route requests to the load balancers.
- C. Configure two Application Load Balancers in each Region. The first will route to the EC2 endpoints, and the second will route to the on-premises endpoints
- D. Configure a Network Load Balancer in each Region to address the EC2 endpoints. Configure a Network Load Balancer in each Region that routes to the on- premises endpoints.
- E. Configure a Network Load Balancer in each Region to address the EC2 endpoints. Configure an Application Load Balancer in each Region that routes to the on-premises endpoints.

Suggested Answer: DE

A company hosts an ecommerce application that stores all data in a single Amazon RDS for MySQL DB instance that is fully managed by AWS The company needs to mitigate the risk of a single point of failure.

Which solution will meet these requirements with the LEAST implementation effort?

- A. Modify the RDS DB instance to use a Multi-AZ deployment. Apply the changes during the next maintenance window.
- B. Migrate the current database to a new Amazon DynamoDB Multi-AZ deployment. Use AWS Database Migration Service (AWS DMS) with a heterogeneous migration strategy to migrate the current RDS DB instance to DynamoDB tables.
- C. Create a new RDS DB instance in a Multi-AZ deployment. Manually restore the data from the existing RDS DB instance from the most recent snapshot
- D Configure the DB instance in an Amazon EC2 Auto Scaling group with a minimum group size of three Use Amazon Route 53 simple routing to distribute requests to all DB instances

Suggested Answer: A

A company has an employee web portal. Employees log in to the portal to view payroll details. The company is developing a new system to give employees the ability to upload scanned documents for reimbursement. The company runs a program to extract text-based data from the documents and attach the extracted information to each employee's reimbursement IDs for processing.

The employee web portal requires 100% uptime. The document extract program runs infrequently throughout the day on an on-demand basis. The company wants to build a scalable and cost-effective new system that will require minimal changes to the existing web portal. The company does not want to make any code changes.

Which solution will meet these requirements with the LEAST implementation effort?

A. Run Amazon EC2 On-Demand Instances in an Auto Scaling group for the web portal. Use an AWS Lambda function to run the document extract program. Invoke the Lambda function when an employee uploads a new reimbursement document.

B. Run Amazon EC2 Spot Instances in an Auto Scaling group for the web portal. Run the document extract program on EC2 Spot Instances. Start document extract program instances when an employee uploads a new reimbursement document.

C. Purchase a Savings Plan to run the web portal and the document extract program. Run the web portal and the document extract program in an Auto Scaling group.

D. Create an Amazon S3 bucket to host the web portal. Use Amazon API Gateway and an AWS Lambda function for the existing functionalities. Use the Lambda function to run the document extract program. Invoke the Lambda function when the API that is associated with a new document upload is called.

Suggested Answer: A

A company's expense tracking application gives users the ability to upload images of receipts. The application analyzes the receipts to extract information and stores the raw images in Amazon S3. The application is written in Java and runs on Amazon EC2 On-Demand Instances in an Auto Scaling group behind an Application Load Balancer.

The compute costs and storage costs have increased with the popularity of the application.

Which solution will provide the MOST cost savings without affecting application performance?

- A. Purchase a Compute Savings Plan for the maximum number of necessary EC2 instances. Store the uploaded files in Amazon Elastic File System (Amazon EFS)
- B. Decrease the minimum number of EC2 instances in the Auto Scaling group. Use On-Demand Instances for peak scaling. Store the uploaded files in Amazon Elastic File System (Amazon EFS).
- C. Decrease the maximum number of EC2 instances in the Auto Scaling group. Set up S3 Lifecycle policies to archive the raw images to lower-cost storage tiers after 30 days
- D. Purchase a Compute Savings Plan for the minimum number of necessary EC2 instances. Use On-Demand Instances for peak scaling. Set up S3 Lifecycle policies to archive the raw images to lower-cost storage tiers after 30 days.

Suggested Answer: D

A company needs to design a resilient web application to process customer orders. The web application must automatically handle increases in web traffic and application usage without affecting the customer experience or losing customer orders.

Which solution will meet these requirements?

- A. Use a NAT gateway to manage web traffic. Use Amazon EC2 Auto Scaling groups to receive, process, and store processed customer orders. Use an AWS Lambda function to capture and store unprocessed orders.
- B. Use a Network Load Balancer (NLB) to manage web traffic. Use an Application Load Balancer to receive customer orders from the NLB. Use Amazon Redshift with a Multi-AZ deployment to store unprocessed and processed customer orders
- C. Use a Gateway Load Balancer (GWLB) to manage web traffic. Use Amazon Elastic Container Service (Amazon ECS) to receive and process customer orders. Use the GWLB to capture and store unprocessed orders. Use Amazon DynamoDB to store processed customer orders.

D. Use an Application Load Balancer to manage web traffic. Use Amazon EC2 Auto Scaling groups to receive and process customer orders. Use Amazon Simple Queue Service (Amazon SQS) to store unprocessed orders. Use Amazon RDS with a Multi-AZ deployment to store processed customer orders

Suggested Answer: D

A company has an application that runs on an Amazon Elastic Kubernetes Service (Amazon EKS) cluster on Amazon EC2 instances. The application has a UI that uses Amazon DynamoDB and data services that use Amazon S3 as part of the application deployment.

The company must ensure that the EKS Pods for the UI can access only Amazon DynamoDB and that the EKS Pods for the data services can access only Amazon S3. The company uses AWS Identity and Access Management (IAM).

Which solution meets these requirements?

A. Create separate IAM policies for Amazon S3 and DynamoDB access with the required permissions. Attach both IAM policies to the EC2 instance profile. Use role-based access control (RBAC) to control access to Amazon S3 or DynamoDB for the respective EKS Pods

B. Create separate IAM policies for Amazon S3 and DynamoDB access with the required permissions. Attach the Amazon S3 IAM policy directly to the EKS Pods for the data services and the DynamoDB policy to the EKS Pods for the UI.

C. Create separate Kubernetes service accounts for the UI and data services to assume an IAM role. Attach the AmazonS3FullAccess policy to the data services account and the AmazonDynamoDBFullAccess policy to the UI service account

D. Create separate Kubernetes service accounts for the UI and data services to assume an IAM role. Use IAM Role for Service Accounts (IRSA) to provide access to the EKS Pods for the UI to Amazon S3 and the EKS Pods for the data services to DynamoDB

Suggested Answer: D

A company is launching a new application that requires a structured database to store user profiles, application settings, and transactional data. The database must be scalable with application traffic and must offer backups.

Which solution will meet these requirements MOST cost-effectively?

- A. Deploy a self-managed database on Amazon EC2 instances by using open source software. Use Spot Instances for cost optimization. Configure automated backups to Amazon S3.
- B. Use Amazon RDS. Use on-demand capacity mode for the database with General Purpose SSD storage. Configure automatic backups with a retention period of 7 days.
- C. Use Amazon Aurora Serverless for the database. Use serverless capacity scaling. Configure automated backups to Amazon S3.
- D. Deploy a self-managed NoSQL database on Amazon EC2 instances. Use Reserved Instances for cost optimization. Configure automated backups directly to Amazon S3 Glacier Flexible Retrieval.

Suggested Answer: C

A company recently launched a new application for its customers. The application runs on multiple Amazon EC2 instances across two Availability Zones. End users use TCP to communicate with the application.

The application must be highly available and must automatically scale as the number of users increases.

Which combination of steps will meet these requirements MOST cost-effectively? (Select TWO.)

- A. Add a Network Load Balancer in front of the EC2 instances.
- B. Configure an Auto Scaling group for the EC2 instances.
- C. Add an Application Load Balancer in front of the EC2 instances.
- D. Manually add more EC2 instances for the application.
- E. Add a Gateway Load Balancer in front of the EC2 instances.

Suggested Answer: BE

A company runs thousands of AWS Lambda functions. The company needs a solution to securely store sensitive information that all the Lambda functions use. The solution must also manage the automatic rotation of the sensitive information.

Which combination of steps will meet these requirements with the LEAST operational overhead? (Select TWO.)

- A. Create HTTP security headers by using Lambda@Edge to retrieve and create sensitive information.
- B. Create a Lambda layer that retrieves sensitive information.
- C. Store sensitive information in AWS Secrets Manager.
- D. Store sensitive information in AWS Systems Manager Parameter Store.
- E. Create a Lambda consumer with dedicated throughput to retrieve sensitive information and create environmental variables.

Suggested Answer: CD

A healthcare company is developing an AWS Lambda function that publishes notifications to an encrypted Amazon Simple Notification Service (Amazon SNS) topic. The

The SNS topic uses AWS Key Management Service (AWS KMS) customer managed keys for encryption. The company must ensure that the application has the necessary permissions to publish messages securely to the SNS topic.

Which combination of steps will meet these requirements? (Select THREE.)

- A. Create a resource policy for the SNS topic that allows the Lambda function to publish messages to the topic.
- B. Use server-side encryption with AWS KMS keys (SSE-KMS) for the SNS topic instead of customer managed keys.
- C. Create a resource policy for the encryption key that the SNS topic uses that has the necessary AWS KMS permissions.
- D. Specify the Lambda function's Amazon Resource Name (ARN) in the SNS topic's resource policy.

E. Associate an Amazon API Gateway HTTP API with the SNS topic to control access to the topic by using API Gateway resource policies

F. Configure a Lambda execution role that has the necessary IAM permissions to use a customer managed key in AWS KMS.

Suggested Answer: BCF

A company uses AWS to host a public website. The load on the web servers recently increased.

The company wants to learn more about the traffic flow and traffic sources. The company also wants to increase the overall security of the website.

Which solution will meet these requirements?

A. Deploy AWS WAF and set up logging. Use Amazon Kinesis Data Firehose to deliver the log files to an Amazon S3 bucket for analysis.

B. Deploy Amazon API Gateway and set up logging. Use Amazon Kinesis Data Streams to deliver the log files to an Amazon S3 bucket for analysis.

C. Deploy a Network Load Balancer and set up logging. Use Amazon Kinesis Data Firehose to deliver the log files to an Amazon S3 bucket for analysis

D. Deploy an Application Load Balancer and set up logging. Use Amazon Kinesis Data Streams to deliver the log files to an Amazon S3 bucket for analysis

Suggested Answer: D

A company is developing software that uses a PostgreSQL database schema. The company needs to configure development environments and test environments for its developers.

Each developer at the company uses their own development environment, which includes a PostgreSQL database. On average, each development environment is used for an 8-hour workday. The test environments will be used for load testing that can take up to 2 hours each day.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure development environments and test environments with their own Amazon Aurora Serverless v2 PostgreSQL database.
- B. For each development environment, configure an Amazon RDS for PostgreSQL Single-AZ DB instance. For the test environment, configure a single Amazon RDS for PostgreSQL Multi-AZ DB instance.
- C. Configure development environments and test environments with their own Amazon Aurora PostgreSQL DB cluster.
- D. Configure an Amazon Aurora global database. Allow developers to connect to the database with their own credentials

Suggested Answer: B

A company wants to use Amazon Elastic Container Service (Amazon ECS) to run its on-premises application in a hybrid environment. The application currently runs on containers on premises.

The company needs a single container solution that can scale in an on-premises, hybrid, or cloud environment. The company must run new application containers in the AWS Cloud and must use a load balancer for HTTP traffic.

Which combination of actions will meet these requirements? (Select TWO.)

- A. Set up an ECS cluster that uses the AWS Fargate launch type for the cloud application containers. Use an Amazon ECS Anywhere external launch type for the on-premises application containers.
- B. Set up an Application Load Balancer for cloud ECS services.
- C. Set up a Network Load Balancer for cloud ECS services.
- D. Set up an ECS cluster that uses the AWS Fargate launch type. Use Fargate for the cloud application containers and the on-premises application containers.
- E. Set up an ECS cluster that uses the Amazon EC2 launch type for the cloud application containers. Use Amazon ECS Anywhere with an AWS Fargate launch type for the on-premises application containers.

Suggested Answer: AB

A company is migrating five on-premises applications to VPCs in the AWS Cloud. Each application is currently deployed in isolated virtual networks on premises and should be deployed similarly in the AWS Cloud. The applications need to reach a shared services VPC. All the applications must be able to communicate with each other.

If the migration is successful, the company will repeat the migration process for more than 100 applications.

Which solution will meet these requirements with the LEAST administrative overhead?

- A. Deploy software VPN tunnels between the application VPCs and the shared services VPC. Add routes between the application VPCs in their subnets to the shared services VPC.
- B. Deploy VPC peering connections between the application VPCs and the shared services VPC. Add routes between the application VPCs in their subnets to the shared services VPC through the peering connection.
- C. Deploy an AWS Direct Connect connection between the application VPCs and the shared services VPC. Add routes from the application VPCs in their subnets to the shared services VPC and the applications VPCs. Add routes from the shared services VPC subnets to the applications VPCs.
- D. Deploy a transit gateway with associations between the transit gateway and the application VPCs and the shared services VPC. Add routes between the application VPCs in their subnets and the application VPCs to the shared services VPC through the transit gateway

Suggested Answer: D

A company wants to move its application to a serverless solution. The serverless solution needs to analyze existing data and new data by using SQL. The company stores the data in an Amazon S3 bucket. The data must be encrypted at rest and replicated to a different AWS Region.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a new S3 bucket that uses server-side encryption with AWS KMS multi-Region keys (SSE-KMS). Configure Cross-Region Replication (CRR). Load the data into the new S3 bucket. Use Amazon Athena to query the data.

B. Create a new S3 bucket that uses server-side encryption with Amazon S3 managed keys (SSE-S3). Configure Cross-Region Replication (CRR). Load the data into the new S3 bucket. Use Amazon RDS to query the data.

C. Configure Cross-Region Replication (CRR) on the existing S3 bucket. Use server-side encryption with Amazon S3 managed keys (SSE-S3). Use Amazon Athena to query the data.

D. Configure S3 Cross-Region Replication (CRR) on the existing S3 bucket. Use server-side encryption with AWS KMS multi-Region keys (SSE-KMS). Use Amazon RDS to query the data.

Suggested Answer: A

A company has released a new version of its production application. The company's workload uses Amazon EC2, AWS Lambda, AWS Fargate, and Amazon SageMaker.

A Flag for Review Color Scheme

The company wants to cost optimize the workload now that usage is at a steady state. The company wants to cover the most services with the fewest savings plans Which combination of savings plans will meet these requirements? (Select TWO.)

A. Purchase an EC2 Instance Savings Plan for Amazon EC2 and SageMaker.

B. Purchase a Compute Savings Plan for Amazon EC2, Lambda, and SageMaker.

C. Purchase a SageMaker Savings Plan.

D. Purchase a Compute Savings Plan for Lambda, Fargate, and Amazon EC2.

E. Purchase an EC2 Instance Savings Plan for Amazon EC2 and Fargate.

Suggested Answer: B

A company is migrating a daily Microsoft Windows batch job from the company's on-premises environment to AWS. The current batch job runs for up to 1 hour. The company wants to modernize the batch job process for the cloud environment

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a fleet of Amazon EC2 instances in an Auto Scaling group to handle the Windows batch job processing.
- B. Implement an AWS Lambda function to process the Windows batch job. Use an Amazon EventBridge rule to invoke the Lambda function.
- C. Use AWS Fargate to deploy the Windows batch job as a container. Use AWS Batch to manage the batch job processing.
- D. Use Amazon Elastic Kubernetes Service (Amazon EKS) on Amazon EC2 instances to orchestrate Windows containers for the batch job processing.

Suggested Answer: B

A global ecommerce company uses a monolithic architecture. The company needs a solution to manage the increasing volume of product data. The solution must be scalable and have a modular service architecture. The company needs to maintain its structured database schemas. The company also needs a storage solution to store product data and product images.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use an Amazon EC2 instance in an Auto Scaling group to deploy a containerized application. Use an Application Load Balancer to distribute web traffic. Use an Amazon RDS DB instance to store product data and product images.
- B. Use AWS Lambda functions to manage the existing monolithic application. Use Amazon DynamoDB to store product data and product images. Use Amazon Simple Notification Service (Amazon SNS) for event-driven communication between the Lambda functions.
- C. Use Amazon Elastic Kubernetes Service (Amazon EKS) with an Amazon EC2 deployment to deploy a containerized application. Use an Amazon Aurora cluster to store the product data. Use AWS Step Functions to manage workflows. Store the product images in Amazon S3 Glacier Deep Archive.
- D. Use Amazon Elastic Container Service (Amazon ECS) with AWS Fargate to deploy a containerized application. Use Amazon RDS with a Multi-AZ deployment to store the product data. Store the product images in an Amazon S3 bucket.

Suggested Answer: D

A company operates a food delivery service. Because of recent growth, the company's order processing system is experiencing scaling problems during peak traffic hours. The current architecture includes Amazon EC2 instances in an Auto Scaling group that collect orders from an application. A second group of EC2 instances in an Auto Scaling group fulfills the orders.

The order collection process occurs quickly, but the order fulfillment process can take longer. Data must not be lost because of a scaling event.

A solutions architect must ensure that the order collection process and the order fulfillment process can both scale adequately during peak traffic hours.

Which solution will meet these requirements?

- A. Use Amazon CloudWatch to monitor the CPUUtilization metric for each instance in both Auto Scaling groups. Configure each Auto Scaling group's minimum capacity to meet its peak workload value.
- B. Use Amazon CloudWatch to monitor the CPUUtilization metric for each instance in both Auto Scaling groups. Configure a CloudWatch alarm to invoke an Amazon Simple Notification Service (Amazon SNS) topic to create additional Auto Scaling groups on demand.
- C. Provision two Amazon Simple Queue Service (Amazon SQS) queues. Use one SQS queue for order collection. Use the second SQS queue for order fulfillment. Configure the EC2 instances to poll their respective queues. Scale the Auto Scaling groups based on notifications that the queues send.
- D. Provision two Amazon Simple Queue Service (Amazon SQS) queues. Use one SQS queue for order collection. Use the second SQS queue for order fulfillment. Configure the EC2 instances to poll their respective queues. Scale the Auto Scaling groups based on the number of messages in each queue.

Suggested Answer: D

A company is implementing a new application on AWS. The company will run the application on multiple Amazon EC2 instances across multiple Availability Zones within multiple AWS Regions. The application will be available through the internet. Users will access the application from around the world.

The company wants to ensure that each user who accesses the application is sent to the EC2 instances that are closest to the user's location.

Which solution will meet these requirements?

- A. Implement an Amazon Route 53 geolocation routing policy. Use an internet-facing Application Load Balancer to distribute the traffic, across all Availability Zones within the same Region
- B. Implement an Amazon Route 53 geoproximity routing policy. Use an internet-facing Network Load Balancer to distribute the traffic across all Availability Zones within the same Region
- C. Implement an Amazon Route 53 multivalue answer routing policy. Use an internet-facing Application Load Balancer to distribute the traffic across all Availability Zones within the same Region
- D. Implement an Amazon Route 53 weighted routing policy. Use an internet-facing Network Load Balancer to distribute the traffic across all Availability Zones within the same Region

Suggested Answer: B

A company recently performed a lift and shift migration of its on-premises Oracle database workload to run on an Amazon EC2 memory optimized Linux instance. The EC2 Linux instance uses a 1 TB Provisioned IOPS SSD (101) EBS volume with 64,000 IOPS

The database storage performance after the migration is slower than the performance of the on-premises database

Which solution will improve storage performance?

- A. Add more Provisioned IOPS SSD (1) EBS volumes. Use OS commands to create a Logical Volume Management (LVM) stripe
- B. Increase the Provisioned IOPS SSD (101) EBS volume to more than 64,000 IOPS
- C. Increase the size of the Provisioned IOPS SSD (101) EBS volume to 2 TB
- D. Change the EC2 Linux instance to a storage optimized instance type. Do not change the Provisioned IOPS SSD (1) EBS volume

Suggested Answer: D

A medical company wants to perform transformations on a large amount of clinical trial data that comes from several customers. The company must extract the data from a relational database that contains the customer data. Then the company will transform the data by using a series of complex rules. The company will load the data to Amazon S3 when the transformations are complete

All data must be encrypted where it is processed before the company stores the data in Amazon S3. All data must be encrypted by using customer-specific keys

Which solution will meet these requirements with the LEAST amount of operational effort?

- A. Create one AWS Glue job for each customer. Attach a security configuration to each job that uses server-side encryption with Amazon S3 managed keys (SSE-S3) to encrypt the data.
- B. Create one Amazon EMR cluster for each customer. Attach a security configuration to each cluster that uses client-side encryption with a custom client-side root key (CSE-Custom) to encrypt the data
- C. Create one AWS Glue job for each customer. Attach a security configuration to each job that uses client-side encryption with AWS KMS managed keys (CSE-KMS) to encrypt the data
- D. Create one Amazon EMR cluster for each customer. Attach a security configuration to each cluster that uses server-side encryption with AWS KMS keys (SSE-KMS) to encrypt the data

Suggested Answer: C

A company recently migrated a monolithic application to an Amazon EC2 instance and Amazon RDS. The application has tightly coupled modules. The existing design of the application gives the ability to run on only a single EC2 instance,

The company has noticed high CPU utilization on the EC2 instance during peak usage times. The high CPU utilization corresponds to degraded performance on Amazon RDS for adus. The company wants to reduce the high CPU utilization and improve read request performance.

Which solution will meet these requirements?

- A. Resize the EC2 instance to an EC2 instance type that has more CPU capacity. Configure an Auto Scaling group with a minimum and maximum size of 1. Configure an RDS read replica for read requests.
- B. Resize the EC2 instance to an EC2 instance type that has more CPU capacity. Configure an Auto Scaling group with a minimum and maximum size of 1. Add an RDS read replica and direct read/write traffic to the replica.
- C. Configure an Auto Scaling group with a minimum size of 1 and maximum size of 2. Resize the RDS DB instance to an instance type that has more CPU capacity.
- D. Resize the EC2 instance to an EC2 instance type that has more CPU capacity. Configure an Auto Scaling group with a minimum and maximum size of 1. Resize the RDS DB instance to an instance type that has more CPU capacity.

Suggested Answer: D

A telemarketing company is designing its customer call center functionality on AWS. The company needs a solution that provides multiple speaker recognition and generates transcript files. The company wants to query the transcript files to analyze the business patterns.

Which solution will meet these requirements?

- A. Use Amazon Rekognition for multiple speaker recognition. Store the transcript files in Amazon S3. Use machine learning (ML) models to analyze the transcript files.
- B. Use Amazon Transcribe for multiple speaker recognition. Use Amazon Athena to analyze the transcript files.
- C. Use Amazon Translate for multiple speaker recognition. Store the transcript files in Amazon Redshift. Use SQL queries to analyze the transcript files.
- D. Use Amazon Rekognition for multiple speaker recognition. Store the transcript files in Amazon S3. Use Amazon Textract to analyze the transcript files.

Suggested Answer: B

A company hosts a monolithic web application on an Amazon EC2 instance. Application users have recently reported poor performance at specific times. Analysis of Amazon CloudWatch metrics shows that CPU utilization is 100% during the periods of poor performance.

The company wants to resolve this performance issue and improve application availability

Which combination of steps will meet these requirements MOST cost-effectively? (Select TWO)

- A. Use AWS Compute Optimizer to obtain a recommendation for an instance type to scale vertically
- B. Create an Amazon Machine image (AMI) from the web server. Reference the AMI in a new launch template
- C. Create an Auto Scaling group and an Application Load Balancer to scale vertically
- D. Use AWS Compute Optimizer to obtain a recommendation for an instance type to scale horizontally.
- E. Create an Auto Scaling group and an Application Load Balancer to scale horizontally,

Suggested Answer: AE

A company is migrating an application from an on-premises location to Amazon Elastic Kubernetes Service (Amazon EKS). The company must use a custom subnet for pods that are in the company's VPC to comply with requirements. The company also needs to ensure that the pods can communicate securely within the pods' VPC

Which solution will meet these requirements?

- A. Configure AWS Transit Gateway to directly manage custom subnet configurations for the pods in Amazon EKS
- B. Create an AWS Direct Connect connection from the company's on-premises IP address ranges to the EKS pods.
- C. Use the Amazon VPC CNI plugin for Kubernetes. Define custom subnets in the VPC cluster for the pods to use.
- D. Implement a Kubernetes network policy that has pod anti-affinity rules to restrict pod placement to specific nodes that are within custom subnets

Suggested Answer: C

A company's image-hosting website gives users around the world the ability to upload, view, and download images from their mobile devices. The company currently hosts the static website in an Amazon S3 bucket.

Because of the website's growing popularity, the website's performance has decreased. Users have reported latency issues when they upload and download images.

The company must improve the performance of the website.

Which solution will meet these requirements with the LEAST implementation effort?

- A. Configure an Amazon CloudFront distribution for the S3 bucket to improve the download performance. Enable S3 Transfer Acceleration to improve the upload performance.
- B.. Configure Amazon EC2 instances of the right sizes in multiple AWS Regions. Migrate the application to the EC2 instances. Use an Application Load Balancer to distribute the website traffic equally among the EC2 instances. Configure AWS Global Accelerator to address global demand with low latency.
- C. Configure an Amazon CloudFront distribution that uses the S3 bucket as an origin to improve the download performance. Configure the application to use CloudFront to upload images to improve the upload performance. Create S3 buckets in multiple AWS Regions. Configure replication rules for the buckets to replicate users' data based on the users' location. Redirect downloads to the S3 bucket that is closest to each user's location.
- D. Configure AWS Global Accelerator for the S3 bucket to improve network performance. Create an endpoint for the application to use Global Accelerator instead of the S3 bucket.

Suggested Answer: A

A company is migrating its on-premises Oracle database to an Amazon RDS for Oracle database. The company needs to retain data for 90 days to meet regulatory requirements. The company must also be able to restore the database to a specific point in time for up to 14 days.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create Amazon RDS automated backups. Set the retention period to 90 days.
- B. Create an Amazon RDS manual snapshot every day. Delete manual snapshots that are older than 90 days.
- C. Use the Amazon Aurora Clone feature for Oracle to create a point-in-time restore. Delete clones that are older than 90 days.

D. Create a backup plan that has a retention period of 90 days by using AWS Backup for Amazon RDS.

Suggested Answer: A

A company is migrating its databases to Amazon RDS for PostgreSQL. The company is migrating its applications to Amazon EC2 instances. The company wants to optimize costs for long-running workloads.

Which solution will meet this requirement MOST cost-effectively?

A. Use On-Demand Instances for the Amazon RDS for PostgreSQL workloads. Purchase a 1 year Compute Savings Plan with the No Upfront option for the EC2 instances

B. Purchase Reserved Instances for a 1 year term with the No Upfront option for the Amazon RDS for PostgreSQL workloads. Purchase a 1 year EC2 Instance Savings Plan with the No Upfront option for the EC2 instances.

C. Purchase Reserved Instances for a 1 year term with the Partial Upfront option for the Amazon RDS for PostgreSQL workloads. Purchase a 1 year EC2 Instance Savings Plan with the Partial Upfront option for the EC2 instances.

D. Purchase Reserved Instances for a 3 year term with the All Upfront option for the Amazon RDS for PostgreSQL workloads. Purchase a 3 year EC2 Instance Savings Plan with the All Upfront option for the EC2 instances.

Suggested Answer: D

A company hosts an application on AWS. The application gives users the ability to upload photos and store the photos in an Amazon S3 bucket. The company wants to use Amazon CloudFront and a custom domain name to upload the photo files to the S3 bucket in the eu-west-1 Region.

Which solution will meet these requirements? (Select TWO.)

A. Use AWS Certificate Manager (ACM) to create a public certificate in the us-east-1 Region. Use the certificate in CloudFront.

B. Use AWS Certificate Manager (ACM) to create a public certificate in eu-west-1. Use the certificate in CloudFront.

C. Configure Amazon S3 to allow uploads from CloudFront. Configure S3 Transfer Acceleration

D. Configure Amazon S3 to allow uploads from CloudFront origin access control (OAC).

E. Configure Amazon S3 to allow uploads from CloudFront. Configure an Amazon S3 website endpoint.

Suggested Answer: BC

A logistics company is creating a data exchange platform to share shipment status information with shippers. The logistics company can see all shipment information and metadata. The company distributes shipment data updates to shippers.

Each shipper should see only shipment updates that are relevant to their company. Shippers should not see the full detail that is visible to the logistics company. The company creates an Amazon Simple Notification Service (Amazon SNS) topic for each shipper to share data. Some shippers use a mobile app to submit shipment status updates.

The company needs to create a data exchange platform that provides each shipper specific access to the data that is relevant to their company.

Which solution will meet these requirements with the LEAST operational overhead?

A. Ingest the shipment updates from the mobile app into Amazon Simple Queue Service (Amazon SQS). Publish the updates to the SNS topic. Apply a filter policy to rewrite the body of each message.

B. Ingest the shipment updates from the mobile app into Amazon Simple Queue Service (Amazon SQS). Use an AWS Lambda function to consume the updates from Amazon SQS and rewrite the body of each message. Publish the updates to the SNS topic.

C. Ingest the shipment updates from the mobile app into a second SNS topic. Publish the updates to the shipper SNS topic. Apply a filter policy to rewrite the body of each message

D. Ingest the shipment updates from the mobile app into Amazon Simple Queue Service (Amazon SQS). Filter and rewrite the messages in Amazon EventBridge Pipes. Publish the updates to the SNS topic

Suggested Answer: B

A company stores 1 TB of customer transaction data in CSV format in an Amazon S3 bucket. The company needs to run a one-time query to compute the total value of transactions for each customer. Which solution will meet these requirements with the LEAST operational overhead?

- A. Use an Amazon EMR cluster. Run a PySpark script to query the transaction data in the S3 bucket.
- B. Create an Amazon Redshift Serverless warehouse. Use Amazon Redshift Spectrum to query the transaction data in the S3 bucket.
- C. Use Amazon Athena to create a new database and table for the transaction data in the S3 bucket. Use SQL to query the transaction data in the Athena table.
- D. Create an Amazon Redshift cluster. Use Amazon Redshift Spectrum to query the transaction data in the S3 bucket.

Suggested Answer: C

A company is designing an application to connect AWS Lambda functions to an Amazon RDS for MySQL DB instance. The DB instance manages many connections. The company needs to modify the application to improve connectivity and recovery.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon RDS Proxy for connection pooling. Modify the application to use the RDS Proxy for connections to the DB instance.
- B. Create a new RDS instance for connection pooling. Modify the application to use the new RDS instance for connectivity
- C. Create read replicas to distribute the load of the DB instance. Create a Network Load Balancer to distribute the load across the read replicas.
- D. Migrate the RDS for MySQL DB instance to Amazon Aurora MySQL to increase DB instance performance.

Suggested Answer: A

A company that is in the ap-northeast-1 Region has a fleet of thousands of AWS Outposts servers. The company has deployed the servers at remote locations around the world. All the servers regularly download new software versions that consist of 100 files. There is significant latency before all servers run the new software versions.

The company must reduce the deployment latency for new software versions.

Which solution will meet this requirement with the LEAST operational overhead?

- A. Create an Amazon S3 bucket in ap-northeast-1. Set up an Amazon CloudFront distribution in ap-northeast-1 that includes a Caching Disabled cache policy. Configure the S3 bucket as the origin. Download the software by using signed URLs.
- B. Create an Amazon S3 bucket in ap-northeast-1. Create a second S3 bucket in the us-east-1 Region. Configure replication between the buckets. Set up an Amazon CloudFront distribution that uses ap-northeast-1 as the primary origin and us-east-1 as the secondary origin. Download the software by using signed URLs.
- C. Create an Amazon S3 bucket in ap-northeast-1. Configure Amazon S3 Transfer Acceleration. Download the software by using the S3 Transfer Acceleration endpoint.
- D. Create an Amazon S3 bucket in ap-northeast-1. Set up an Amazon CloudFront distribution. Configure the S3 bucket as the origin. Download the software by using signed URLs.

Suggested Answer: A

A financial services company wants to conduct fraud detection checks against customer details each time there is an update to a customer profile on the company's banking application.

The company must perform the fraud checks immediately. The checks must not affect the user experience. The checks must be performed asynchronously.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Publish profile update events to a data stream in Amazon Kinesis Data Streams. Create one AWS Lambda function for each fraud detection check. Configure the Lambda functions to consume messages from an Amazon Kinesis Data Streams shard.
- B. Publish profile update events to an Amazon Simple Notification Service (Amazon SNS) topic. Create one AWS Lambda function for each fraud detection check. Subscribe each Lambda function to the SNS topic.
- C. Publish profile update events to an Amazon MQ message queue. Create one AWS Lambda function for each fraud detection check. Subscribe each Lambda function to the Amazon MQ message queue.
- D. Publish profile update events to an Amazon Managed Streaming for Apache Kafka (Amazon MSK) topic. Create one AWS Lambda function for each fraud detection check, Subscribe each Lambda function to the Amazon MSK topic.

Suggested Answer: A

A company is migrating a production environment application to the AWS Cloud. The company uses Amazon RDS for Oracle for the database layer. The company needs to configure the database to meet the needs of high I/O intensive workloads that require low latency and consistent throughput. The database workloads are read intensive and write intensive.

Which solution will meet these requirements?

- A. Use a Multi-AZ DB instance deployment for the RDS for Oracle database
- B. Configure the RDS for Oracle database to use the Provisioned IOPS SSD storage type
- C. Configure the RDS for Oracle database to use the General Purpose SSD storage type.
- D. Enable RDS read replicas for RDS for Oracle.

Suggested Answer: B

A solutions architect is designing an application that helps users fill out and submit registration forms. The solutions architect plans to use a two-tier architecture that includes a web application server tier and a worker tier.

The application needs to process submitted forms quickly. The application needs to process each form exactly once. The solution must ensure that no data is lost

Which solution will meet these requirements?

- A. Use an Amazon Simple Queue Service (Amazon SQS) FIFO queue between the web application server tier and the worker tier to store and forward form data.
- B. Use an Amazon API Gateway HTTP API between the web application server tier and the worker tier to store and forward form data
- C. Use an Amazon Simple Queue Service (Amazon SQS) standard queue between the web application server tier and the worker tier to store and forward form data.
- D. Use an AWS Step Functions workflow. Create a synchronous workflow between the web application server tier and the worker tier that stores and forwards form data

Suggested Answer: D

A company must consume data that is written as JSON objects to an Amazon S3 bucket. The data is written in batches every 5 minutes and can range up to 100 MB per hour. The data needs to be extracted and written to an existing Amazon Aurora database cluster.

The company has a Python application that reads the JSON objects and converts the data to load into the database cluster. The application runs every hour and often takes more than 30 minutes to run. The company needs a highly available solution.

Which solution will meet these requirements?

- A. Set up an Amazon EventBridge scheduled event that runs every hour to invoke an AWS Step Functions state machine. Configure the Python application as an Amazon EMR Serverless job Configure the Step Functions state machine to run the task to invoke the Amazon EMR Serverless job.
- B. Set up the Python application as an AWS Lambda function. Set up an Amazon EventBridge scheduled event that runs every hour to invoke the Lambda function.

C. Use an AWS CloudFormation template to launch an Amazon EC2 On-Demand Instance. Use the CloudFormation template UserData property to install the Python application that is needed to read the JSON files. Create a crontab entry to launch the application every hour.

D. Use an AWS CloudFormation template to launch an Amazon EMR cluster with a 3-year, All Upfront Reserved Instance. Use the CloudFormation template UserData property to install the Python application. Invoke the application every hour by using an Amazon EventBridge scheduled event.

Suggested Answer: B

A company currently runs an on-premises stock trading application by using Microsoft Windows Server. The company wants to migrate the application to the AWS Cloud

The company needs to design a highly available solution that provides low-latency access to block storage across multiple Availability Zones.

Which solution will meet these requirements with the LEAST implementation effort?

A. Configure a Windows Server cluster that spans two Availability Zones on Amazon EC2 instances. Install the application on both cluster nodes. Use Amazon FSx for Windows File Server as shared storage between the two cluster nodes.

B. Configure a Windows Server cluster that spans two Availability Zones on Amazon EC2 instances. Install the application on both cluster nodes. Use Amazon Elastic Block Store (Amazon EBS) general Purpose SSD (gp3) volumes as storage attached to the EC2 instances. Set up application-level replication to sync data from one EBS volume in one Availability Zone to another EBS volume in the second Availability Zone.

C. Deploy the application on Amazon EC2 instances in two Availability Zones. Configure one EC2 instance as active and the second EC2 instance in standby mode. Use an Amazon FSx for NetApp ONTAP Multi-AZ file system to access the data by using Internet Small Computer Systems Interface (iSCSI) protocol.

D. Deploy the application on Amazon EC2 instances in two Availability Zones. Configure one EC2 instance as active and the second EC2 instance in standby mode. Use Amazon Elastic Block Store (Amazon EBS) Provisioned IOPS SSD (io2) volumes as storage attached to the EC2 instances. Set up Amazon EBS level

replication to sync data from one io2 volume in one Availability Zone to another io2 volume in the second Availability Zone.

Suggested Answer: B

A company runs an on-premises managed file transfer solution to collect images from its clients. The company uses an open source transfer tool to transfer and integrate the images into the company's workflow. The company then runs a custom application to add watermarks to the images.

The company needs to migrate this workload to AWS and wants to use AWS managed services where possible. Uploaded images must be stored as objects. The company wants to automate the watermark addition

Which solution will meet these requirements?

- A. Use AWS DataSync to automate file transfers. Store the images in an Amazon S3 bucket. Use an application that runs on Amazon EC2 instances to add watermarks
- B. Use REST APIs to transfer files. Store the images in an Amazon S3 bucket. Use AWS Batch jobs to add watermarks.
- C. Use SFTP with AWS Transfer Family to automate file transfers into Amazon S3 buckets. Configure the Transfer Family workflow to invoke an AWS Lambda function to add watermarks.
- D. Use AWS Transfer Family to transfer images. Store the images in Amazon S3 Glacier Deep Archive, Run an AWS Step Functions state machine to add watermarks.

Suggested Answer: C

A company is running a media store across multiple Amazon EC2 instances distributed across multiple Availability Zones in a single VPC. The company wants a high-performing solution to share data between all the EC2 instances, and prefers to keep the data within the VPC only.

What should a solutions architect recommend?

- A. Create an Amazon S3 bucket and call the service APIs from each instance's application.
- B. Create an Amazon S3 bucket and configure all instances to access it as a mounted volume

- C. Configure an Amazon Elastic Block Store (Amazon EBS) volume and mount it across all instances.
- D. Configure an Amazon Elastic File System (Amazon EFS) file system and mount it across all instances.

Suggested Answer: D

A company is running a media store across multiple Amazon EC2 instances distributed across multiple Availability Zones in a single VPC. The company wants a high-performing solution to share data between all the EC2 instances, and prefers to keep the data within the VPC only.

What should a solutions architect recommend?

- A. Create an Amazon S3 bucket and call the service APIs from each instance's application.
- B. Create an Amazon S3 bucket and configure all instances to access it as a mounted volume
- C. Configure an Amazon Elastic Block Store (Amazon EBS) volume and mount it across all instances.
- D. Configure an Amazon Elastic File System (Amazon EFS) file system and mount it across all instances.

Suggested Answer: D

A company is developing an application in the AWS Cloud. The application's HTTP API contains critical information that is published in Amazon API Gateway. The critical information must be accessible from only a limited set of trusted IP addresses that belong to the company's internal network.

Which solution will meet these requirements?

- A. Set up an API Gateway private integration to restrict access to a predefined set of IP addresses.
- B. Create a resource policy for the API that denies access to any IP address that is not specifically allowed.
- C. Directly deploy the API in a private subnet. Create a network ACL. Set up rules to allow the traffic from specific IP addresses.
- D. Modify the security group that is attached to API Gateway to allow inbound traffic from only the trusted IP addresses.

Suggested Answer: B

A company is using an Amazon Elastic Kubernetes Service (Amazon EKS) cluster. The company must ensure that Kubernetes service accounts in the EKS cluster have secure and granular access to specific AWS resources by using IAM roles for service accounts (IRSA).

Which combination of solutions will meet these requirements? (Select TWO.)

- A. Create an IAM policy that defines the required permissions. Attach the policy directly to the IAM role of the EKS nodes.
- B. Implement network policies within the EKS cluster to prevent Kubernetes service accounts from accessing specific AWS services.
- C. Modify the EKS cluster's IAM role to include permissions for each Kubernetes service account. Ensure a one-to-one mapping between IAM roles and Kubernetes roles.
- D. Define an IAM role that includes the necessary permissions. Annotate the Kubernetes service accounts with the Amazon Resource Name (ARN) of the IAM role.
- E. Set up a trust relationship between the IAM roles for the service accounts and an OpenID Connect (OIDC) identity provider.

Suggested Answer: CD

A company is moving data from an on-premises data center to the AWS Cloud. The company must store all its data in an Amazon S3 bucket. To comply with regulations, the company must also ensure that the data will be protected against overwriting indefinitely.

Which solution will ensure that the data in the S3 bucket cannot be overwritten?

- A. Enable versioning for the S3 bucket. Use server-side encryption with Amazon S3 managed keys (SSE-S3) to protect the data.
- B. Disable versioning for the S3 bucket. Configure S3 Object Lock for the S3 bucket with a retention period of 1 year.
- C. Enable versioning for the S3 bucket. Configure S3 Object Lock for the S3 bucket with a legal hold

D. Configure S3 Storage Lens for the S3 bucket. Use server-side encryption with customer-provided keys (SSE-C) to protect the data

Suggested Answer: B

A company runs database workloads on AWS that are the backend for the company's customer portals. The company runs a Multi-AZ database cluster on Amazon RDS for PostgreSQL

The company needs to implement a 30-day backup retention policy. The company currently has both automated RDS backups and manual RDS backups. The company wants to maintain both types of existing RDS backups that are less than 30 days old.

Which solution will meet these requirements MOST cost-effectively?

A. Configure the RDS backup retention policy to 30 days for automated backups by using AWS Backup. Manually delete manual backups that are older than 30 days.

B. Disable RDS automated backups. Delete automated backups and manual backups that are older than 30 days. Configure the RDS backup retention policy to 30 days for automated backups

C. Configure the RDS backup retention policy to 30 days for automated backups. Manually delete manual backups that are older than 30 days

D. Disable RDS automated backups. Delete automated backups and manual backups that are older than 30 days automatically by using AWS CloudFormation. Configure the RDS backup retention policy to 30 days for automated backups.

Suggested Answer: C

A company uses AWS to run its workloads. The company uses AWS Organizations to manage its accounts. The company needs to identify which departments are responsible for specific costs.

New accounts are constantly created in the Organizations account structure. The Organizations continuous integration and continuous delivery (CI/CD) framework already adds the populated department tag to the AWS resources. The company wants to use an AWS Cost Explorer report to identify the service costs by department from all AWS accounts.

Which combination of steps will meet these requirements with the MOST operational efficiency? (Select TWO.)

- A. Activate the aws createdBy cost allocation tag and the department cost allocation tag in the management account.
- B. Create a new cost and usage report in Cost Explorer. Group by the department cost allocation tag. Apply a filter to see all linked accounts and services.
- C. Activate only the department cost allocation tag in the management account.
- D. Create a new cost and usage report in Cost Explorer. Group by the department cost allocation tag without any other filters.
- E. Activate only the aws createdBy cost allocation tag in the management account.

Suggested Answer: BC

A company needs to grant a team of developers access to the company's AWS resources. The company must maintain a high level of security for the resources.

The company requires an access control solution that will prevent unauthorized access to the sensitive data.

Which solution will meet these requirements?

- A. Share the IAM user credentials for each development team member with the rest of the team to simplify access management and to streamline development workflows.
- B. Define IAM roles that have fine-grained permissions based on the principle of least privilege. Assign an IAM role to each developer.
- C. Create IAM access keys to grant programmatic access to AWS resources. Allow only developers to interact with AWS resources through API calls by using the access keys.
- D. Create an AWS Cognito user pool. Grant developers access to AWS resources by using the user pool.

Suggested Answer: B

Suggested Answer:

Suggested Answer:

Suggested Answer:

Suggested Answer: