

# Template Tags / Code

## Substitution

```
{{ zap }}  
{{ zap|safe }}
```

## Calling code

```
{% url 'cat-detail' cat.id %}  
{% author.get_absolute_url %}
```

## Logic

```
{% if zap > 100 %}  
{% endif %}
```

## Blocks


```
{% block content %}  
{% endblock %}
```

<https://samples.dj4e.com/tmpl/loop>

```
def loop(request) :  
    f = ['Apple', 'Orange', 'Banana', 'Lychee']  
    n = ['peanut', 'cashew']  
    x = {'fruits' : f, 'nuts' : n, 'zap' : '42' }  
    return render(request, 'tmpl/loop.html', x)
```

[dj4e-samples/tmpl/templates/tmpl/loop.html](https://samples.dj4e.com/tmpl/templates/tmpl/loop.html)

```
<ul>  
{% for x in fruits %}  
<li>{{ x }}</li>  
{% endfor %}  
</ul>  
{% if nuts %}  
    <p>Number of nuts: {{ nuts|length }}</p>  
{% else %}  
    <p>No nuts.</p>  
{% endif %}
```




<https://samples.dj4e.com/tmpl/nested>

```
def nested(request) :  
    x = { 'outer' : { 'inner' : '42' } }  
    return render(request, 'tmpl/nested.html', x)
```

[dj4e-samples/tmpl/templates/tmpl/nested.html](https://samples.dj4e.com/tmpl/templates/tmpl/nested.html)

```
<body>  
    <p>Your guess was {{ outer.inner }}</p>  
</body>
```




<https://samples.dj4e.com/tmpl/game/200>

```
path('game/<slug:guess>', views.GameView.as_view())
```

```
class GameView(View) :  
    def get(self, request, guess) :  
        x = {'guess' : int(guess) }  
        return render(request, 'tmpl/cond.html', x)
```

[dj4e-samples/tmpl/templates/tmpl/cond.html](https://samples.dj4e.com/tmpl/templates/tmpl/cond.html)

```
<p>Your guess was {{ guess }}</p>  
{% if guess < 42 %}  
    <p>Too low</p>  
{% elif guess > 42 %}  
    <p>Too high</p>  
{% else %}  
    <p>Just right</p>  
{% endif %}
```



# Template Inheritance

## tmpl/templates/tmpl/cond.html

```
<html>
<head>
  <title>A conditional template</title>
</head>
<body>
  <p>Your guess was {{ guess }}</p>
  {% if guess < 42 %}
    <p>Too low</p>
  {% elif guess > 42 %}
    <p>Too high</p>
  {% else %}
    <p>Just right</p>
  {% endif %}
</body>
</html>
```

## tmpl/templates/tmpl/base.html

```
<html>
<head>
  <title>Base template</title>
</head>
<body>
  {% block content %}{% endblock %}
</body>
</html>
```

## tmpl/templates/tmpl/cond2.html

```
{% extends "tmpl/base.html" %}

{% block content %}
  <p>Your guess was {{ guess }}</p>
  {% if guess < 42 %}
    <p>Too low</p>
  {% elif guess > 42 %}
    <p>Too high</p>
  {% else %}
    <p>Just right</p>
  {% endif %}
{% endblock %}
```



```
app_name = 'route'
urlpatterns = [
    path('', TemplateView.as_view(template_name='route/main.html')),
    path('first', views.FirstView.as_view(), name='first-view'),
    path('second', views.SecondView.as_view(), name='second-view'),
]
```

[dj4e-samples/route/urls.py](#)

[dj4e-samples/route/templates/routes/main.html](#)

```
<li>
    <a href="/route/second">
        hard-coded</a> (not DRY)
</li>
<li>
    {% url 'route:first-view' %}
    (url 'route:first-view')
</li>
<li>
    <a href="{% url 'route:second-view' %}">
        url 'route:second-view'</a>
</li>
```

**route:first-view**

application  
name

view  
name

Using the url tag  
in a template

### `dj4e-samples/gview/urls.py`

```
app_name = 'gview'
urlpatterns = [
    path('cats', views.CatListView.as_view(), name='cats'),
    path('cat/<int:pk_from_url>', views.CatDetailView.as_view(), name='cat'),
]
```

### `dj4e-samples/route/templates/route/main.html`

```
<li>
    {% url 'gview:cats' %}
    (url 'gview:cats') from gview/urls.py
</li>
<li>
    {% url 'gview:cat' 42 %}
    (url 'gview:cat' 42) from gview/urls.py
</li>
```

Parameter

`'gview:cat'` 42

application name	view name

Other applications  
and parameters

```
path('second', views.SecondView.as_view(), name='second-view'),
```

`dj4e-samples/route/urls.py`

`dj4e-samples/route/views.py`

```
from django.shortcuts import render
from django.urls import reverse, reverse_lazy
from django.views import View

class SecondView(View):
    def get(self, request) :
        u = reverse_lazy('gview:cats')
        u2 = reverse_lazy('gview:dogs')
        u3 = reverse('gview:dog', args=['42'] )
        ctx = {'x1' : u, 'x2': u2, 'x3': u3 }
        return render(request, 'route/second.html', ctx)
```

`dj4e-samples/route/templates/route/main.html`

```
<li>
    <a href="{% url 'route:first-view' %}">
        route:first-view</a>
</li>
<li>
    {{ x1 }} (x1 from context)
</li>
<li>
    {{ x2 }} (x2 from context)
</li>
<li>
    {{ x3 }} (x3 from context)
</li>
```