Project 3: OpenStreetMap Data Wrangling with SQL

Name: Shivam Bhardwaj

Map Area: Pune, Maharashtra, India as i have spent a lot of time in this city.

Location: Pune, IndiaOpenStreetMap URL

• MapZen URL

1. Data Audit

Unique Tags

Looking at the XML file, I found that it uses different types of tags. And also my filesize is quite large for myPC so i sampled the data. Then parsed the Pune, India dataset using Element Tree and count number of the unique tags. mapparser.py is used to count the numbers of unique tags.

• 'member': 195,

• 'nd': 55896,

'node': 47133,

'osm': 1,

'relation': 72,

'tag': 10203,

• 'way': 8998

Patterns in the Tags

The "k" value of each tag contain different patterns. Using tags.py , I created 3 regular expressions to check for certain patterns in the tags.

I have counted each of four tag categories.

- "lower": 9939, for tags that contain only lowercase letters and are valid,
- "lower_colon" : 260 , for otherwise valid tags with a colon in their names,
- "problemchars": 0, for tags with problematic characters, and
- "other": 4, for other tags that do not fall into the other three categories.

2. Problems Encountered in the Map

Street address inconsistencies

The main problem we encountered in the dataset is the street name inconsistencies. Below is the old name corrected w better name. Using audit.py, we updated the names.

- Abbreviations
 - ∘ Rd -> Road
- LowerCase
 - pune -> Pune
- Misspelling
 - socity -> Society
- Hindi names
 - Marg -> Path

City name inconsistencies

Using audit.py, we update the names

- LowerCase
 - puna -> Pune
- Misspelling

3. Data Overview

File sizes:

• pune_india.osm: 307.3 MB

nodes csv: 3.9 MB

nodes_tags.csv: 16.9 KB

ways_csv: 549.1 KB

ways_nodes.csv: 1.3 MB

ways_tags.csv: 316.8 KB

• pune_sample : 10.3 MB

pune.db: 7.0 MB

Number of nodes:

```
sqlite> SELECT COUNT(*) FROM nodes
```

Output:

47133

Number of ways:

```
sqlite> SELECT COUNT(*) FROM ways
```

Output:

8998

Number of unique users:

```
sqlite> SELECT COUNT(DISTINCT(e.uid))
FROM (SELECT uid FROM nodes UNION ALL SELECT uid FROM ways) e;
```

Output:

276

Top contributing users:

```
sqlite> SELECT e.user, COUNT(*) as num
FROM (SELECT user FROM nodes UNION ALL SELECT user FROM ways) e
GROUP BY e.user
ORDER BY num DESC
LIMIT 10;
```

Output:

Sramesh: 1918
Praveeng: 1904
Shiva05: 1740
Anushapyata: 1616
Kranthikumar: 1589

Harishk : 1436 Saikumar : 1337

Number of users contributing only once:

```
sqlite> SELECT COUNT(*)
FROM
  (SELECT e.user, COUNT(*) as num
  FROM (SELECT user FROM nodes UNION ALL SELECT user FROM ways) e
  GROUP BY e.user
  HAVING num=1) u;
```

Output:

103

4. Additional Data Exploration

Biggest religion:

```
sqlite> SELECT nodes_tags.value, COUNT(*) as num

FROM nodes_tags

JOIN (SELECT DISTINCT(id) FROM nodes_tags WHERE value='place_of_worship') i

ON nodes_tags.id=i.id

WHERE nodes_tags.key='religion'

GROUP BY nodes_tags.value

ORDER BY num DESC

LIMIT 1;
```

Output:

Hindu: 4

Popular cuisines

```
sqlite> SELECT nodes_tags.value, COUNT(*) as num

FROM nodes_tags

JOIN (SELECT DISTINCT(id) FROM nodes_tags WHERE value='restaurant') i

ON nodes_tags.id=i.id

WHERE nodes_tags.key='cuisine'

GROUP BY nodes_tags.value

ORDER BY num DESC;
```

Output:

Barbecue:1

5. Conclusion

The OpenStreetMap data of Pune is of fairly reasonable quality but the typo errors caused by the human inputs are significant. I have cleaned a significant amount of the data which is required for this project. But, there are lots of improvement needed in the dataset. The dataset contains very less amount of additional information such as amenities, tourist attractions, popular places and other useful interest. The dataset contains very old information which is now incomparable to that of Google Maps or Bing Maps.So, I think there are several opportunities for cleaning and validation of the data in the future.

Benefits, Suggestions and Ideas

Benefits:

1. Formatting Street Names will help maintaing a uniformity across the map for all kinds of users for the city.

Several locals provided names were directly given to streets which increases confusion for the map user are fixed through this attempt for the city Pune.

2. Many misspelled words and names in regional languages has been changed to their corrected and standard version which provides a better accuracy for maps and also users from out of the city to understand the map.

My contributions mostly benefitted in increasing standarization of the map for city Pune.

Suggestions:

- 1. Control typo errors: We can build parser which parse every word input by the users.
- 2.Setting up rules: We can make some rules or patterns to input data which users follow everytime to input their data. This will also restrict users input in their native language.
- 3. Use of Machine learning: We can develop script or bot to detect or clean the data regularly.
- 4. Power to user: Also we can give user of the maps to authenticate the data on the map.

Ideas:

The tourists or even the city people search map to see the basic amenities provided in the city or what are the popular places and attractions in the city or near outside the city. So, the users must be motivated to also provide these informations in the map. If we can provide these informations then there are more chances to increase views on the map because many people directly enter the famous names on the map.

Files

README.md: Description for the project sample.osm: sample data of the OSM file

audit.py: audit street, city and update their names

data.py: build CSV files from OSM and also parse, clean and shape data

database.py : create database of the CSV files mapparser.py : find unique tags in the data

query.py: different queries about the database using SQL

report.pdf : pdf of this document

sample.py: extract sample data from the OSM file

tags.py: count multiple patterns in the tags

schema.py: Helper file for data.py