



| Qty 1  |                                   |                  |  |         |         |          |       |        |
|--|-----------------------------------|------------------|--|---------|---------|----------|-------|--------|
| Туре І   |                                   |                  |  |         |         |          |       |        |
| Tolerances in um = 1/1000 mm                                     |                                   | <del></del>      |  |         |         |          |       |        |
| Max. Deviation tolerated.  Dimensional: ±100 um                  |                                   |                  |  |         |         |          |       |        |
| Max. Deviation tolerated. Angular:                               |                                   | Chg.Nr. Change   |  |         |         |          | Date  | Signed |
| * Sweeping attack max: 20 um                                     | Material: Nichtrostender St. RRMD |                  |  |         | Scale   | Drawn    | T.V.N |        |
| ♦ Lateral runout max: 20 um Without * Sweeping attack max: 50 um | Type:   Group                     |                  |  |         | 5:1     | Checked  | CODY  |        |
| Without Stateral runout max: 50 um  Prevailing Surface finish    |                                   | Crank Handle Pin |  |         |         | Approved | CODY  |        |
|  | CIGIR HAHAIC I III                |                  |  |         |         |          |       |        |
| Surface treatment  |                                   |                  |  |         |         |          |       |        |
| -<br>Heat treatment  | Assembly Number: 10242 ReCurta    |                  |  | ReCurta | 10022-4 |          |       |        |
|  |                                   |                  |  |         |         |          |       |        |