



**Министерство науки и высшего образования Российской Федерации
Федеральное государственное бюджетное образовательное учреждение
высшего образования
«Московский государственный технический университет
имени Н.Э. Баумана
(национальный исследовательский университет)»
(МГТУ им. Н.Э. Баумана)**

**Факультет «Информатика, искусственный и системы управления»
Кафедра «Системы обработки информации и управления»**

**Отчет по Лабораторной работе №5
*«Ансамбли моделей
машинного обучения»*
по дисциплине «Технология машинного обучения»**

**Выполнил:
студент группы ИУ5-61Б
И.А. Абуховский**

**Проверил:
Ю.Е. Гапанюк**

2023 г.

```
In [1]: %pip install graphviz
```

Requirement already satisfied: graphviz in ./opt/anaconda3/lib/python3.9/site-packages (0.20.1)
Note: you may need to restart the kernel to use updated packages.

```
In [2]: %pip install pydotplus
```

Requirement already satisfied: pydotplus in ./opt/anaconda3/lib/python3.9/site-packages (2.0.2)
Requirement already satisfied: pyparsing>=2.0.1 in ./opt/anaconda3/lib/python3.9/site-packages (from pydotplus) (3.0.9)
Note: you may need to restart the kernel to use updated packages.

Предварительный анализ

Загрузим необходимые библиотеки

```
In [22]: from io import StringIO
from IPython.display import Image
import graphviz
import pydotplus
import numpy as np
import pandas as pd
from typing import Dict, Tuple
from sklearn.datasets import load_iris, load_wine, load_boston
from sklearn.tree import DecisionTreeClassifier, DecisionTreeRegressor, export_graphviz
from sklearn.model_selection import train_test_split
from sklearn.model_selection import GridSearchCV
from sklearn.ensemble import RandomForestRegressor, GradientBoostingRegressor
from sklearn.ensemble import RandomForestClassifier, GradientBoostingClassifier
from sklearn.preprocessing import StandardScaler
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_score
from sklearn.metrics import mean_absolute_error
from sklearn.metrics import median_absolute_error, r2_score
from sklearn.svm import NuSVR
from sklearn import tree
import matplotlib.pyplot as plt
%matplotlib inline
from sklearn.datasets import make_classification
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import BaggingClassifier, RandomForestClassifier
from sklearn.metrics import accuracy_score
import matplotlib.pyplot as plt
```

```
In [4]: df = pd.read_csv('gym.csv')
```

Изучим полученные данные

```
In [6]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 4000 entries, 0 to 3999
Data columns (total 15 columns):
 #   Column                                  Non-Null Count  Dtype  
---  -
 0   Unnamed: 0                             4000 non-null   int64  
 1   gender                                 4000 non-null   int64  
 2   Near_Location                         4000 non-null   int64  
 3   Partner                               4000 non-null   int64  
 4   Promo_friends                         4000 non-null   int64  
 5   Phone                                 4000 non-null   int64  
 6   Contract_period                       4000 non-null   int64  
 7   Group_visits                          4000 non-null   int64  
 8   Age                                   4000 non-null   int64  
 9   Avg_additional_charges_total          4000 non-null   float64 
10   Month_to_end_contract                 4000 non-null   float64 
11   Lifetime                              4000 non-null   int64  
12   Avg_class_frequency_total             4000 non-null   float64 
13   Avg_class_frequency_current_month     4000 non-null   float64 
14   Churn                                 4000 non-null   int64  
dtypes: float64(4), int64(11)
memory usage: 468.9 KB
```

```
In [25]: X = df.drop(['Churn'], axis = 1)
y = df['Churn']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=0)
```

```
In [26]: #1. Модель бэггинга - случайный лес (Random Forest):
```

```
from sklearn.ensemble import RandomForestClassifier

# Создаем модель случайного леса с 100 деревьями
rf_model = RandomForestClassifier(n_estimators=100)
```

```

# Обучаем модель на тренировочных данных
rf_model.fit(X_train, y_train)

# Оцениваем качество модели на тестовых данных
accuracy = rf_model.score(X_test, y_test)
print("Accuracy:", accuracy)

#2. Модель бустинга - градиентный бустинг (Gradient Boosting):

from sklearn.ensemble import GradientBoostingClassifier

# Создаем модель градиентного бустинга с 100 деревьями и скоростью обучения 0.1
gb_model = GradientBoostingClassifier(n_estimators=100, learning_rate=0.1)

# Обучаем модель на тренировочных данных
gb_model.fit(X_train, y_train)

# Оцениваем качество модели на тестовых данных
accuracy = gb_model.score(X_test, y_test)
print("Accuracy:", accuracy)

#3. Модель стекинга - мета-классификатор на основе логистической регрессии:

from sklearn.ensemble import RandomForestClassifier, GradientBoostingClassifier
from sklearn.linear_model import LogisticRegression
from sklearn.model_selection import cross_val_predict

# Обучаем базовые модели на тренировочных данных
rf_preds = cross_val_predict(rf_model, X_train, y_train, cv=5, method='predict_proba')
gb_preds = cross_val_predict(gb_model, X_train, y_train, cv=5, method='predict_proba')

# Создаем мета-классификатор на основе логистической регрессии
meta_model = LogisticRegression()

# Обучаем мета-классификатор на прогнозах базовых моделей
meta_model.fit(np.hstack([rf_preds, gb_preds]), y_train)
rf_model = RandomForestClassifier(n_estimators=100)
rf_model.fit(X_train, y_train)
rf_test_preds = rf_model.predict_proba(X_test)
gb_model.fit(X_train, y_train)
gb_test_preds = gb_model.predict_proba(X_test)

# Оцениваем качество модели на тестовых данных

meta_test_preds = meta_model.predict_proba(np.hstack([rf_test_preds, gb_test_preds]))
accuracy = meta_model.score(np.hstack([rf_test_preds, gb_test_preds]), y_test)
print("Accuracy:", accuracy)

Accuracy: 0.91
Accuracy: 0.92875
Accuracy: 0.9275

```

In [27]: # Создаем три модели: решающее дерево, бэггинг и случайный лес

```

bg = gb_model
rf = rf_model

# Обучаем модели на обучающей выборке

bg.fit(X_train, y_train)
rf.fit(X_train, y_train)

# Получаем предсказания на тестовой выборке

bg_pred = bg.predict(X_test)
rf_pred = rf.predict(X_test)

# Вычисляем точность предсказания каждой модели

bg_acc = accuracy_score(y_test, bg_pred)
rf_acc = accuracy_score(y_test, rf_pred)

# Выводим точность каждой модели на экран

print("Accuracy of Bagging Classifier: {:.2f}%".format(bg_acc*100))
print("Accuracy of Random Forest Classifier: {:.2f}%".format(rf_acc*100))

# Создаем график точности предсказания каждой модели
models = [ 'Bagging', 'Random Forest' ]
accuracies = [ bg_acc, rf_acc ]
plt.bar(models, accuracies)
plt.ylabel('Accuracy')
plt.title('Classifier Accuracy Comparison')
plt.show()

```

Accuracy of Bagging Classifier: 92.88%
Accuracy of Random Forest Classifier: 90.62%

