Borehole/ Location	Depth Range	Unit Weight γ		Pore Pressure Adjustment
		Ground	Ground Water	Factor K
	[m]	[kN/m ³]	[kN/m ³]	[-]
CPT_WFS4_2	0.00 to 0.80 0.80 to 10.65 10.65 to 24.50 24.50 to 27.10 27.10 to 27.75 27.75 to 33.40 33.40 to 34.90 34.90 to 38.10 38.10 to bottom	20.00 20.50 20.00 19.50 19.50 19.50 19.50 18.50 20.00	10.0	
CPT_WFS4_3	0.00 to 6.80 6.80 to 11.00 11.00 to 20.95 20.95 to 23.30 23.30 to 23.90 23.90 to 28.20 28.20 to 30.65 30.65 to 34.35 34.35 to bottom	20.00 20.50 20.00 19.50 19.50 19.50 19.50 20.00	10.0	
CPT_WFS4_4	0.00 to 0.90 0.90 to 9.60 9.60 to 12.25 12.25 to 14.45 14.45 to 17.50 17.50 to bottom	20.00 20.50 20.00 20.00 20.00 20.00	10.0	
CPT_WFS4_5	0.00 to 2.45 2.45 to 12.30 12.30 to 15.50 15.50 to 24.80 24.80 to bottom	20.00 20.50 20.50 20.00 20.00	10.0	
CPT_WFS4_6	0.00 to 4.90 4.90 to 12.60 12.60 to 14.35 14.35 to 17.10 17.10 to 19.75 19.75 to bottom	20.00 20.50 20.50 20.50 20.50 20.50	10.0	
CPT_WFS4_8	0.00 to 1.80 1.80 to 12.20 12.20 to 13.90 13.90 to 15.90 15.90 to 19.70 19.70 to bottom	20.00 20.50 19.50 19.50 18.50 20.00	10.0	
CPT_WFS4_9	0.00 to 3.50 3.50 to bottom	20.00 20.50	10.0	

PARAMETER VALUES FOR NET CONE RESISTANCE CALCULATION BORSSELE WIND FARM ZONE, WFS IV - DUTCH SECTOR, NORTH SEA

Note:1. The adjustment factor K applies only to probes with a pore pressure filter in the face of the cone.