

# Approximate Minimum-Weight Partial Matching under Translation

Pankaj Agarwal <sup>1</sup>   Haim Kaplan <sup>2</sup>   Geva Kipper <sup>2</sup>  
Wolfgang Mulzer <sup>3</sup>   Günter Rote <sup>3</sup>   Micha Sharir <sup>2</sup>   Allen Xiao <sup>1</sup>


<sup>1</sup>Duke University

<sup>2</sup>Tel Aviv University

<sup>3</sup>Freie Universität Berlin


December 2018

# Example




$\mathbb{R}^2$


# Example



# Example




# Example




$\mathbb{R}^2$

# Example




$\mathbb{R}^2$

# Example



# Example



Find the minimum-cost matching over all translations

# Cost function

- ▶ Given point sets  $A, B$ , with  $|A| = m$  and  $|B| = n$ , match  $A$  into an  $m$ -subset of  $B$  after translation  $t$ .
- ▶ For matching  $M$  and translation  $t$ , define the **root-mean-square (RMS) cost** of the matching:

$$\text{cost}(M, t) := \left[ \frac{1}{m} \sum_{(a,b) \in M} \|a + t - b\|^p \right]^{1/2}$$

- ▶ Can generalize to  $p$ -th power/ $p$ -th root (versus 2), and matching of size  $k$  (versus  $m$ ).
- ▶ Best matching cost at each translation:

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$

# Cost function

- ▶ Given point sets  $A, B$ , with  $|A| = m$  and  $|B| = n$ , match  $A$  into an  $m$ -subset of  $B$  after translation  $t$ .
- ▶ For matching  $M$  and translation  $t$ , define the **root-mean-square (RMS) cost** of the matching:

$$\text{cost}(M, t) := \left[ \frac{1}{m} \sum_{(a,b) \in M} \|a + t - b\|^p \right]^{1/2}$$

- ▶ Can generalize to  $p$ -th power/ $p$ -th root (versus 2), and matching of size  $k$  (versus  $m$ ).
- ▶ Best matching cost at each translation:

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$

# Cost function

- ▶ Given point sets  $A, B$ , with  $|A| = m$  and  $|B| = n$ , match  $A$  into an  $m$ -subset of  $B$  after translation  $t$ .
- ▶ For matching  $M$  and translation  $t$ , define the **root-mean-square (RMS) cost** of the matching:


$$\text{cost}(M, t) := \left[ \frac{1}{m} \sum_{(a,b) \in M} \|a + t - b\|^p \right]^{1/2}$$

- ▶ Can generalize to  $p$ -th power/ $p$ -th root (versus 2), and matching of size  $k$  (versus  $m$ ).
- ▶ Best matching cost at each translation:

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$

# Cost function under perturbations


$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$



- ▶ How many distinct matchings appear in  $\text{cost}^*(t)$ ?

# Cost function under perturbations


$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$



- ▶ How many distinct matchings appear in  $\text{cost}^*(t)$ ?

# Cost function under perturbations


$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$



- ▶ How many distinct matchings appear in  $\text{cost}^*(t)$ ?

# Cost function under perturbations


$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$



- ▶ How many distinct matchings appear in  $\text{cost}^*(t)$ ?

# Cost function under perturbations


$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$



- ▶ How many distinct matchings appear in  $\text{cost}^*(t)$ ?

# Cost function under perturbations

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$



- ▶ How many distinct matchings appear in  $\text{cost}^*(t)$ ?


# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$




# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$




# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$




# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$




# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$




# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$




# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$





# How many distinct matchings? (1-dimensional)

$$\text{cost}^*(t) := \min_{\text{matching } M} \text{cost}(M, t)$$



# How many distinct matchings? (2-dimensional)



- ▶ How many distinct matchings appear in  $\text{cost}^*(t)$ ?
- ▶ What is the combinatorial complexity of  $\mathcal{M}$ ?

## Questions and prior results

1. How quickly can we compute  $t^*$ , a global minimum of  $\text{cost}^*(t)$ ?
2. What is the combinatorial complexity of  $\mathcal{M}$ ?

- ▶ [Rote 10]: in 1D, at most  $m(n - m) + 1$ .
- ▶ [Ben-Avraham *et al.* 14]:  $O(n^2m^{3.5}(e \ln m + e)^m)$
- ▶ Open to find  $t^*$  in polytime, and whether  $\mathcal{M}$  has polynomial complexity.
- ▶ Approximation?


## Questions and prior results

1. How quickly can we compute  $t^*$ , a global minimum of  $\text{cost}^*(t)$ ?
2. What is the combinatorial complexity of  $\mathcal{M}$ ?
  - ▶ [Rote 10]: in 1D, at most  $m(n - m) + 1$ .
  - ▶ [Ben-Avraham *et al.* 14]:  $O(n^2m^{3.5}(e \ln m + e)^m)$
- ▶ Open to find  $t^*$  in polytime, and whether  $\mathcal{M}$  has polynomial complexity.
- ▶ Approximation?


## Questions and prior results

1. How quickly can we compute  $t^*$ , a global minimum of  $\text{cost}^*(t)$ ?
2. What is the combinatorial complexity of  $\mathcal{M}$ ?
  - ▶ [Rote 10]: in 1D, at most  $m(n - m) + 1$ .
  - ▶ [Ben-Avraham *et al.* 14]:  $O(n^2m^{3.5}(e \ln m + e)^m)$
- ▶ Open to find  $t^*$  in polytime, and whether  $\mathcal{M}$  has polynomial complexity.
- ▶ Approximation?


# Approximating $\mathcal{M}$ (1-dimensional)




# Approximating $\mathcal{M}$ (1-dimensional)




# Approximating $\mathcal{M}$ (1-dimensional)




# Approximating $\mathcal{M}$ (1-dimensional)




# Approximating $\mathcal{M}$ (2-dimensional)




# Approximating $\mathcal{M}$ (2-dimensional)




# Approximating $\mathcal{M}$ (2-dimensional)




# Approximating $\mathcal{M}$ (2-dimensional)



# Approximating $\mathcal{M}$ (2-dimensional)



# Approximating $\mathcal{M}$ (2-dimensional)



# Our results (approximation helps)

1. How quickly can we compute  $t^*$ , a global minimum of  $\text{cost}^*(t)$ ?

## Theorem

*In  $\text{poly}(m, n, \varepsilon^{-1})$  time, can compute a  $(1 + \varepsilon)$  approximation to  $\text{cost}^*(t^*)$  by exploring the faces of  $\tilde{\mathcal{M}}$ .*

2. What is the combinatorial complexity of  $\mathcal{M}$ ?

## Theorem

*In  $\text{poly}(m, n, \varepsilon^{-1})$  time, can construct a  $(1 + \varepsilon)$  approximate diagram  $\tilde{\mathcal{M}}$  of complexity  $O(n\varepsilon^{-2} \log \varepsilon^{-1})$ .*

# Overview

1. The set of point-to-point translations give a constant approximate diagram of size  $mn$ .
2. Using exponential grids, constant  $\rightarrow (1 + \varepsilon)$  approximation of size  $O(mn\varepsilon^{-2} \log \varepsilon^{-1})$ .
3. Reduce size to  $O(n\varepsilon^{-2} \log \varepsilon^{-1})$  by clustering.

# Overview

1. The set of point-to-point translations give a constant approximate diagram of size  $mn$ .
2. Using exponential grids, constant  $\rightarrow (1 + \varepsilon)$  approximation of size  $O(mn\varepsilon^{-2} \log \varepsilon^{-1})$ .
3. Reduce size to  $O(n\varepsilon^{-2} \log \varepsilon^{-1})$  by clustering.


# Overview

1. The set of point-to-point translations give a constant approximate diagram of size  $mn$ .
2. Using exponential grids, constant  $\rightarrow (1 + \varepsilon)$  approximation of size  $O(mn\varepsilon^{-2} \log \varepsilon^{-1})$ .
3. Reduce size to  $O(n\varepsilon^{-2} \log \varepsilon^{-1})$  by clustering.

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations

- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# Point-to-point translations


- ▶ Point-to-point translations [Cabello et al. 08]:

$$T := \{t_{ba} = (b - a) \mid a \in A, b \in B\}$$




- ▶ Enough to look at the optimal matching of each  $t_{ba} \in T$ .

# $O(1)$ -approximate diagram from point-to-point translations




- ▶  $\tilde{\mathcal{M}}$  is a constant-approximate diagram of size  $|T| = mn$ .

# $O(1)$ -approximate diagram from point-to-point translations




- ▶  $\tilde{\mathcal{M}}$  is a constant-approximate diagram of size  $|T| = mn$ .

# $O(1)$ -approximate diagram from point-to-point translations




- ▶  $\tilde{\mathcal{M}}$  is a constant-approximate diagram of size  $|T| = mn$ .

# $O(1)$ -approximate diagram from point-to-point translations




- ▶  $\tilde{\mathcal{M}}$  is a constant-approximate diagram of size  $|T| = mn$ .

# $O(1)$ -approximate diagram from point-to-point translations




- ▶  $\tilde{\mathcal{M}}$  is a constant-approximate diagram of size  $|T| = mn$ .

# $O(1)$ -approximate diagram from point-to-point translations



- ▶  $\tilde{\mathcal{M}}$  is a constant-approximate diagram of size  $|T| = mn$ .


$O(1) \rightarrow (1 + \varepsilon)$  approximation



- ▶  $(1 + \varepsilon)$  approximate diagram of size  
 $O(|T|\varepsilon^{-2} \log \varepsilon^{-1}) = O((mn)\varepsilon^{-2} \log \varepsilon^{-1})$

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$


- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

## Near-linear size: clustering $T$

- ▶ Any  $O(1)$  approx. diagram is enough for the  $(1 + \varepsilon)$  diagram.
- ▶ Partition  $T$  into clusters of size at least  $m/2$ .



- ▶ Reduces diagram size from  $mn \rightarrow O(n)$ .

# Open questions

1. Is the complexity of  $\mathcal{M}$  polynomial?
2. Approximate diagrams for rotations? Rigid transforms?

# The End

Thank you.