

Geometric Partial Matchings and Unbalanced Transportation Problem

Pankaj K. Agarwal

Duke University, USA

pankaj@cs.duke.edu

Hsien-Chih Chang

Duke University, USA

hsienchih.chang@duke.edu

Allen Xiao

Duke University, USA

axiao@cs.duke.edu

Abstract

Let A and B be two point sets in the plane with uneven sizes r and n respectively (assuming r is at most n), and let k be a parameter. The geometric partial matching problem asks to find the minimum-cost size- k matching between A and B under powers of L_p distances. Applying combinatorial algorithms for partial matching in general graphs to our setting naïvely requires quadratic time due to existence of many edges between point sets A and B . Most previous work for geometric matching has focused on the setting when k , r , and n are all equal. The best algorithm in this setting, due to Sharathkumar and Agarwal [STOC 2012], runs in time $O(n \text{ polylog } n \cdot \text{poly } \varepsilon^{-1})$, but is limited to matching objectives that are sum-of-distances.

We present the first set of geometric algorithms which work for any powers of L_p -norm matching objective: An exact algorithm which runs in $O((n + k^2) \text{ polylog } n)$ time, and a $(1 + \varepsilon)$ -approximation which runs in $O((n + k\sqrt{k}) \text{ polylog } n \cdot \log \varepsilon^{-1})$ time. Both algorithms are based on primal-dual flow augmentation scheme; the main improvements are obtained by using dynamic data structures to achieve efficient flow augmentations. Using similar techniques, we give an exact algorithm for the planar transportation problem, which runs in $O(rn^{3/2} \text{ polylog } n)$ time. This is the first sub-quadratic time exact algorithm when $r = o(\sqrt{n})$, which improves over the state-of-art quadratic time algorithm by Agarwal *et al.* [SOCG 2016].

2012 ACM Subject Classification Theory of computation → Design and analysis of algorithms

Keywords and phrases partial matching, transportation, minimum-cost flow, rms-distance, bichromatic closest pair, cost scaling, excess scaling, primal-dual

Lines 1058

1 Introduction

«REWRITE AFTER TECHNICAL SECTIONS»

Consider the problem of finding a minimum-cost bichromatic matching between a set of red points A and a set of blue points B lying in the plane, where the cost of a matching edge (a, b) is the Euclidean distance $\|a - b\|$; in other words, the minimum-cost bipartite matching problem on the Euclidean complete graph $G = (A \cup B, A \times B)$. Let $r := |A|$ and $n := |B|$. Without loss of generality, assume that $r \leq n$. We consider the problem of *partial matching* (also called *imperfect matching*), where the task is to find a minimum-cost matching of size $k \leq r$. When $k = r = n$, we say the matching instance is *balanced*. When $k = r < n$ (A and B have different sizes, but the matching is maximal), we say the matching instance is



© Pankaj K. Agarwal, Hsien-Chih Chang, Allen Xiao;
licensed under Creative Commons License CC-BY

The 35th International Symposium on Computational Geometry (SOCG 2019).



Leibniz International Proceedings in Informatics

Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany



28 *unbalanced*. We call the geometric problem of finding a size k matching of point sets A and
 29 B the *geometric partial matching problem*. **«talk about the near-linear time algorithm»**

30 1.1 Contributions

31 In this paper, we present two algorithms for geometric partial matching that are based on
 32 fitting nearest-neighbor (NN) and geometric closest pair (BCP) oracles into primal-dual
 33 algorithms for non-geometric bipartite matching and minimum-cost flow. This pattern is
 34 not new, see for example (...) **«TODO cite»**. Unlike these previous works, we focus on
 35 obtaining running time dependencies on k or r instead of n , that is, faster for inputs with
 36 small r or k . We begin in Section ?? by introducing notation for matching and minimum-cost
 37 flow.

38 First in Section 2, we show that the Hungarian algorithm [7] combined with a BCP
 39 oracle solves geometric partial matching exactly in time $O((n + k^2) \text{polylog } n)$. Mainly, we
 40 show that we can separate the $O(n \text{polylog } n)$ preprocessing time for building the BCP data
 41 structure from the augmenting paths' search time, and update duals in a lazy fashion such
 42 that the number of dual updates per augmenting path is $O(k)$.

43 **► Theorem 1.1.** *Let A and B be two point sets in the plane with $|A| = r$ and $|B| = n$
 44 satisfying $r \leq n$, and let k be a parameter. A minimum-cost geometric partial matching of
 45 size k can be computed between A and B in $O((n + k^2) \text{polylog } n)$ time.*

46 **«State the settings separately so no need to repeat in the theorem statement.»**

47 Next in Section 3, we apply a similar technique to the unit-capacity min-cost circulation
 48 algorithm of Goldberg, Hed, Kaplan, and Tarjan [4]. The resulting algorithm finds a $(1 + \varepsilon)$ -
 49 approximation to the optimal geometric partial matching in $O((n + k\sqrt{k}) \text{polylog } n \log(n/\varepsilon))$
 50 time.

51 **► Theorem 1.2.** *Let A and B be two point sets in the plane with $|A| = r$ and $|B| = n$
 52 satisfying $r \leq n$, and let k be a parameter. A $(1 + \varepsilon)$ geometric partial matching of size k
 53 can be computed between A and B in $O((n + k\sqrt{k}) \text{polylog } n \log(1/\varepsilon))$ time.*

54 Our third algorithm solves the transportation problem in the unbalanced setting. The
 55 transportation problem is a weighted generalization of the matching problem. Each point of
 56 A is weighted with an integer *supply* and each point of B is weighted with integer *demand*
 57 such that the sum of supply and demand are equal. The goal of the transportation problem
 58 is to find a minimum-cost mapping of all supplies to demands, where the cost of moving a
 59 unit of supply at $a \in A$ to satisfy a unit of demand at $b \in B$ is $\|a - b\|$. For this, we use the
 60 strongly polynomial uncapacitated min-cost flow algorithm by Orlin [8]. The result is an
 61 $O(n^{3/2}r \text{polylog } n)$ time algorithm for unbalanced transportation. This improves over the
 62 $O(n^2 \text{polylog } n)$ time algorithm of Agarwal *et al.* [1] when $r = o(\sqrt{n})$.

63 **► Theorem 1.3.** *Let A and B be two point sets in the plane with $|A| = r$ and $|B| = n$
 64 satisfying $r \leq n$, with supplies and demands given by the function $\lambda : (A \cup B) \rightarrow \mathbb{Z}$
 65 such that $\sum_{a \in A} \lambda(a) = \sum_{b \in B} \lambda(b)$. An optimal transportation map can be computed in
 66 $O(rn^{3/2} \text{polylog } n)$ time.*

67 By nature of the BCP/NN oracles we use, these results generalize to when $\|a - b\|$ is any
 68 L_p distance, and if we use p' -th power costs $c(a, b) = \|a - b\|^{p'}$ for any $1 \leq p' < \infty$.

2 Minimum-Cost Partial Matchings using Hungarian Algorithm

The Hungarian algorithm [7] is a primal-dual algorithm for min-cost bipartite matching in general graphs that can be adapted to solve the partial matching problem exactly if one terminates the algorithm after k iterations (see e.g. [9]). In this section, we prove Theorem 1.1 by implementing the Hungarian algorithm in $O((n + k^2) \text{polylog } n)$ time.

2.1 Matching Terminologies

Let G be a bipartite graph between vertex sets A and B and edge set E , with costs $c(v, w)$ for each edge (v, w) in G . A *matching* $M \subseteq E$ is a set of edges where no two edges share an endpoint. A vertex v is *matched* by M if v is the endpoint of some matching edge in M ; otherwise v is *unmatched*. The *size* of a matching is the number of edges in the set, and the *cost* of a matching is the sum of costs of its edges. For a parameter k , the *minimum-cost partial matching problem (MPM)* asks to find a size- k matching of minimum cost. In the geometric partial matching setting, we have $E = A \times B$ and $c(a, b) = \|a - b\|_p^q$ for every edge (a, b) in G .

The linear program dual to the standard linear program for MPM has dual variables for each vertex, called *potentials* π . Given potentials π , we can define the *reduced cost* on the edges to be $c_\pi(v, w) := c(v, w) - \pi(v) + \pi(w)$. Potentials π are *feasible* if the reduced costs are nonnegative for all edges in G . We say that an edge (v, w) is *admissible* under potentials π if $c_\pi(v, w) = 0$.

Consider a matching M of size less than r . An *augmenting path* $\Pi = (a_1, b_1, \dots, a_\ell, b_\ell)$ is an odd-length path with unmatched endpoints $(a_1$ and $b_\ell)$ and all other points matched. The edges of Π alternate between edges outside and inside of matching M . The symmetric difference $M \oplus \Pi$ creates a new matching of size $|M| + 1$. We say that $M \oplus \Pi$ is the result of *augmenting* M by Π .

2.2 The Hungarian Algorithm

The Hungarian algorithm is initialized with $M = \emptyset$ and $\pi = 0$. Each iteration of the Hungarian algorithm augments M with an admissible augmenting path Π , discovered using a procedure called the *Hungarian search*. The algorithm terminates once M has size k ; Ramshaw and Tarjan [9] showed that M is guaranteed to be an optimal partial matching.

The Hungarian search tries to grow a set of *reachable vertices* S by augmenting paths consisting of admissible edges. Initially, S is the set of unmatched vertices in A . Let the *frontier* of S be the edges in $(A \cap S) \times (B \setminus S)$. In each iteration, the Hungarian search first *relaxes* the minimum-reduced-cost edge (a, b) in the frontier, raising $\pi(a)$ by $c_\pi(a, b)$ for all $a \in S$ to make (a, b) admissible, and adding b into S . It is easy to verify that this potential change preserves feasibility. If b is already matched, then we also relax the matching edge (a', b) and add a' into S . The search finishes when b is unmatched, and an admissible augmenting path now can be recovered.

The remainder of this section describes an implementation of Hungarian search that runs in $O(k \text{polylog } n)$ time after an $O(n \text{polylog } n)$ time preprocessing (see Lemma 2.1). Our implementation of the Hungarian algorithm therefore runs in $O((n + k^2) \text{polylog } n)$ time, which proves Theorem 1.1.

2.3 A fast implementation of Hungarian search

The most expensive step in augmentation is to find the minimum-reduced-cost frontier edge that needs to be relaxed — the search must “look at every edge”. In the geometric setting, we find the min-cost edge using a dynamic *bichromatic closest pair* (BCP) data structure, as observed in [1]. Given two point sets P and Q in the plane, the bichromatic closest pair are two points $p \in P$ and $q \in Q$ minimizing the additively weighted distance $\|p - q\| - \omega(p) + \omega(q)$ for some real-valued vertex weights ω . Thus, the minimum reduced-cost among the frontier edges is precisely the cost of the BCP of point sets $P = A \cap S$ and $Q = B \setminus S$, with $\omega(p) = \pi(p)$.

«Under the assumption ... on the metric,» The state of the art dynamic BCP data structure from Kaplan *et al.* [6] supports point insertions and deletions in $O(\text{polylog } n)$ time, and answers queries in $O(\log^2 n)$ time. During each relaxation, we perform at most one query and add a vertex to S incurring one BCP insertion or deletion. Thus the running time for the search is $O(k \text{ polylog } n)$.

Initial BCP sets by rewinding. Recall that in the beginning of each iteration, S is initialized to the set of unmatched vertices in A , and therefore $Q = B \setminus S$ has size n «what?». We cannot afford to take $O(n \text{ polylog } n)$ time initialize the BCP data structure at the beginning of every Hungarian search beyond the first. However, the set of unmatched A vertices has changed by exactly one vertex since the last Hungarian search — the augmentation newly matched one vertex $a^* \in A$. Thus, given the initial BCP sets P', Q' from the beginning of the last Hungarian search, we can construct P and Q for the current iteration using a single BCP deletion in $O(\text{polylog } n)$ time.

To acquire P' and Q' , we keep track of a list of the points added to S over the course of the Hungarian search. At the end of each Hungarian search we *rewind* the BCP data structure by tracing the list in reverse order. The number of points in the list is at most $O(k)$ as it is bounded by the number of relaxations per Hungarian search. Thus, in $O(k \text{ polylog } n)$ time, we can reconstruct P' and Q' for each Hungarian search beyond the first. We refer to this procedure as the *rewinding mechanism*.

Potential updates. «REWRITE TO BE MORE SUCCINCT.»

We modify a trick from Vaidya [11] for batching potential updates. Potentials have a *stored value*, i.e. the currently recorded value of $\pi(v)$, and a *true value*, which may have changed from $\pi(v)$. The resulting algorithm queries the minimum-reduced-cost under the true values of π and updates the stored value occasionally.

Throughout the entire Hungarian algorithm, we maintain a nonnegative scalar δ (initially set to 0) which aggregates potential changes. Vertices $a \in A$ that are added to S are inserted into BCP with weight $\omega(a) \leftarrow \pi(a) - \delta$, for whatever value δ is at the time of insertion. Similarly, vertices $b \in B$ that are added to S have $\omega(b) \leftarrow \pi(b) - \delta$ recorded ($B \cap S$ points aren't added into a BCP set). When the Hungarian search wants to raise the potentials of points in S , δ is increased by that amount instead. Thus, true value for any potential of a point in S is always $\omega(p) + \delta$. For points of $(A \cup B) \setminus S$, the true potential is equal to the stored potential. Since all the points of $A \cap S$ have weights uniformly offset from their true potentials, the minimum edge returned by the BCP does not change. «why?»

Once a point is removed from S (i.e. by an augmentation or the rewinding mechanism), we update its stored potential $\pi(p) \leftarrow \omega(p) + \delta$, again for the current value of δ . Most importantly, δ is not reset at the end of a Hungarian search and persists through the entire algorithm. Thus, the initial BCP sets constructed by the rewinding mechanism have true potentials accurately represented by δ and $\omega(p)$.

We update δ once per edge relaxations; thus $O(k)$ times in total per Hungarian search. There are $O(k)$ stored values updated per Hungarian search during the rewinding process. The time spent on potential updates per Hungarian search is therefore $O(k)$.

Putting everything together we obtain the following:

► **Lemma 2.1.** *Each Hungarian search can be implemented in $O(k \text{ polylog } n)$ time after a one-time $O(n \text{ polylog } n)$ preprocessing.*

3 Approximating Min-Cost Partial Matching through Cost-Scaling

The goal of section is to prove Theorem 1.2; that is, to compute a size- k geometric partial matching between two point sets A and B in the plane, with cost at most $(1 + \varepsilon)$ times the optimal matching, in time $O((n + k\sqrt{k}) \text{ polylog } n \log(1/\varepsilon))$.

After introducing the necessary terminologies in Section 3.1, we reduce the partial matching problem to computing an approximate minimum-cost flow on a unit-capacity reduction network in Section 3.2. In Section 3.3 we outline the high-level overview of the cost-scaling algorithm. We postpone the fast implementation using dynamic data structures to Section 4.

3.1 Preliminaries on Network Flows

Network. Let $G = (V, E)$ be a directed graph, augmented by edge costs c and capacities u , and a supply-demand function ϕ defined on the vertices. One can turn the graph G into a *network* $N = (V, \vec{E})$: For each directed edge (v, w) in E , insert two *arcs* $v \rightarrow w$ and $w \rightarrow v$ into the arc set \vec{E} ; the *forward arc* $v \rightarrow w$ inherits the capacity and cost from the directed graph G , while the *backward arc* $w \rightarrow v$ satisfies $u(w \rightarrow v) = 0$ and $c(w \rightarrow v) = -c(v \rightarrow w)$. This we ensure that the graph (V, \vec{E}) is *symmetric* and the cost function c is *antisymmetric* on N . The positive values of $\phi(v)$ are referred to as *supply*, and the negative values of $\phi(v)$ as *demand*. We assume that all capacities are nonnegative, all supplies and demands are integers, and the sum of supplies and demands is equal to zero. A *unit-capacity* network has all its edge capacities equal to 1. In this section we assume all networks are of unit-capacity.

Pseudoflows. Given a network $N := (V, \vec{E}, c, u, \phi)$, a *pseudoflow* (or *flow* to be short) $f: \vec{E} \rightarrow \mathbb{Z}^1$ on N is an antisymmetric function on the arcs of N satisfying $f(v \rightarrow w) \leq u(v \rightarrow w)$ for every arc $v \rightarrow w$. We sometimes abuse the terminology by allowing pseudoflow to be defined on a directed graph, in which case we are actually referring to the pseudoflow on the corresponding network by extending the flow values antisymmetrically to the arcs. We say that f *saturates* an arc $v \rightarrow w$ if $f(v \rightarrow w) = u(v \rightarrow w)$; an arc $v \rightarrow w$ is *residual* if $f(v \rightarrow w) < u(v \rightarrow w)$. The *support* of f in N , denoted as $\text{supp}(f)$, is the set of arcs with positive flows:

$$\text{supp}(f) := \left\{ v \rightarrow w \in \vec{E} \mid f(v \rightarrow w) > 0 \right\}.$$

Given a pseudoflow f , we define the *imbalance* of a vertex (with respect to f) to be

$$\phi_f(v) := \phi(v) + \sum_{w \rightarrow v \in \vec{E}} f(w \rightarrow v) - \sum_{v \rightarrow w \in \vec{E}} f(v \rightarrow w).$$

¹ In general the pseudoflows are allowed to take real-values. Here under the unit-capacity assumption any optimal flows are integer-valued. *«cite integrality theorem?»*

We call positive imbalance *excess* and negative imbalance *deficit*; and vertices with positive and negative imbalance *excess vertices* and *deficit vertices*, respectively. A vertex is *balanced* if it has zero imbalance. If all vertices are balanced, the pseudoflow is a *circulation*. The *cost* of a pseudoflow is defined to be

$$\text{cost}(f) := \sum_{v \rightarrow w \in \text{supp}(f)} c(v \rightarrow w) \cdot f(v \rightarrow w).$$

The *minimum-cost flow problem (MCF)* asks to find a circulation of minimum cost inside a given directed graph.

Residual graph. Given a pseudoflow f , one can define the *residual network* as follows. Recall that the set of *residual arcs* \vec{E}_f under f are those arcs $v \rightarrow w$ satisfying $f(v \rightarrow w) < u(v \rightarrow w)$. In other words, an arc that is not saturated by f is a residual arc; similarly, given an arc $v \rightarrow w$ with positive flow value, the backward arc $w \rightarrow v$ is a residual arc.

Let $N = (V, \vec{E}, c, u, \phi)$ be a network constructed from graph G , with a pseudoflow f on N . The *residual graph* G_f of f has V as its vertex set and \vec{E}_f as its arc set. The *residual capacity* u_f with respect to pseudoflow f is defined to be $u_f(v \rightarrow w) := u(v \rightarrow w) - f(v \rightarrow w)$. Observe that the residual capacity is always nonnegative. We can define residual arcs differently using residual capacities:

$$\vec{E}_f = \{v \rightarrow w \mid u_f(v \rightarrow w) > 0\}.$$

In other words, the set of residual arcs are precisely those arcs in the residual graph, each of which has nonzero residual capacity.

LP-duality and admissibility. To solve the minimum-cost flow problem, we focus on the primal-dual algorithms using linear programming. Let $G = (V, E)$ be a given directed graph with the corresponding network $N = (V, \vec{E}, c, u, \phi)$. Formally, the *potentials* $\pi(v)$ are the variables of the linear program dual to the standard linear program for the minimum-cost flow problem with variables $f(v, w)$ for each directed edge in E . Assignments to the primal variables satisfying the capacity constraints extend naturally into a pseudoflow on the network N . Let $G_f = (V, \vec{E}_f)$ be the residual graph under pseudoflow f . The *reduced cost* of an arc $v \rightarrow w$ in \vec{E}_f with respect to π is defined as

$$c_\pi(v \rightarrow w) := c(v \rightarrow w) - \pi(v) + \pi(w).$$

Notice that the cost function c_π is also antisymmetric.

The *dual feasibility constraint* says that $c_\pi(v \rightarrow w) \geq 0$ holds for every directed edge (v, w) in E ; potentials π which satisfy this constraint are said to be *feasible*. Suppose we relax the dual feasibility constraint to allow some small violation in the value of $c_\pi(v \rightarrow w)$. We say that a pair of pseudoflow f and potential π is *ε -optimal* [?, ?] if $c_\pi(v \rightarrow w) \geq -\varepsilon$ for every residual arc $v \rightarrow w$ in \vec{E}_f . Pseudoflow f is *ε -optimal* if it is ε -optimal with respect to some potentials π ; potential π is *ε -optimal* if it is ε -optimal with respect to some pseudoflow f . Given a pseudoflow f and potentials π , a residual arc $v \rightarrow w$ in \vec{E}_f is *admissible* if $c_\pi(v \rightarrow w) \leq 0$. We say that a pseudoflow g in G_f is *admissible* if all support arcs of g on G_f are admissible; in other words, $g(v \rightarrow w) > 0$ holds only on admissible arcs $v \rightarrow w$.

► **Lemma 3.1.** *Let f be an ε -optimal pseudoflow in G and let f' be an admissible flow in G_f . Then $f + f'$ is also ε -optimal. <<Lemma 5.3 in [5]? Also, where is this used?>>*

3.2 Reduction to Unit-Capacity Min-Cost Flow Problem

The goal of the subsection is to reduce the minimum-cost partial matching problem to the unit-capacity minimum-cost flow problem with a polynomial bound on diameter. To this end we first provide an upper bound on the size of support of an integral pseudoflow on the standard reduction network between the two problems. This upper bound in turn provides an additive approximation on the cost of an ε -optimal circulation. Next we employ a technique by Sharathkumar and Agarwal [10] to transform an additive ε -approximate solution into a multiplicative $(1 + \varepsilon)$ -approximation for the geometric partial matching problem. The reduction does not work out of the box, as Sharathkumar and Agarwal were tackling a similar but different problem on geometric transportations.

► **Lemma 3.2.** *Computing a $(1 + \varepsilon)$ -approximate geometric partial matching can be reduced to the following problem in $O(n \text{ polylog } n)$ time: Given a reduction network N over a point set with diameter at most $K \cdot kn^3$ for some constant K , compute a $(K \cdot \varepsilon / 6k)$ -optimal circulation on N .*

Additive approximation. Given a bipartite graph $G = (A, B, E_0)$ for the geometric partial matching problem with cost function c , we construct the *reduction network* N_H as follows: Direct the edges in E_0 from A to B , and assign each directed edge with capacity 1. Now add a dummy vertex s with directed edges to all vertices in A , and add a dummy vertex t with directed edges from all vertices in B ; each edge added this way has cost 0 and capacity 1. Denote the new graph with vertex set $V = A \cup B \cup \{s, t\}$ and edge set E as the *reduction graph* H . Assign vertex s with supply k and vertex t with demand k ; the rest of the vertices in H have zero supply-demand. We call the network naturally corresponds to H as the *reduction network*, denoted by N_H .

It is straightforward to show that any integer circulation f on N_H uses exactly k of the A -to- B arcs, which correspond to the edges of a size- k matching M_f . Notice that the cost of the circulation f is equal to the cost of the corresponding matching M_f . In other words, a $(1 + \varepsilon)$ -approximation to the MCF problem on the reduction network N_H translates to a $(1 + \varepsilon)$ -approximation to the geometric matching problem on the input graph G .

First we show that the number of arcs used by any integer pseudoflow in N_H is asymptotically bounded by the excess of the pseudoflow.

► **Lemma 3.3.** *Let f be an integer circulation in the reduction network N_H . Then, the size of the support of f is at most $3k$. As a corollary, the number of residual backward arcs is at most $3k$.*

Using the bound on the support size, we show that an ε -optimal integral circulation gives an additive $O(k\varepsilon)$ -approximation to the MCF problem.

► **Lemma 3.4.** *Let f be an ε -optimal integer circulation in N_H , and f^* be an optimal integer circulation for N_H . Then, $\text{cost}(f) \leq \text{cost}(f^*) + 6k\varepsilon$.*

Multiplicative approximation. Now we employ a technique from Sharathkumar and Agarwal [10] to convert the additive approximation into a multiplicative one. Here we sketch a proof to Lemma 3.2; a complete proof can be found in the Appendix.

«Sketch Sharathkumar and Agarwal [10] with our modification.»

3.3 High-Level Description of Cost-Scaling Algorithm

Our main algorithm for the unit-capacity minimum-cost flow problem is based on the *cost-scaling* technique, originally due to Goldberg and Tarjan [5]; Goldberg, Hed, Kaplan, and Tarjan [4] applied the technique on unit-capacity networks. The algorithm finds ε -optimal circulations for geometrically shrinking values of ε . Each fixed value of ε is called a *cost scale*. Once ε is sufficiently small, the ε -optimal flow is a suitable approximation according to Lemma 3.2.²

The cost-scaling algorithm initializes the flow f and the potential π to be zero. Note that the zero flow is trivially a kC -optimal flow, where C is the maximum arc cost. At the beginning of each scale starting at $\varepsilon = kC$,

- SCALE-INIT takes the previous circulation (now 2ε -optimal) and transforms it into an ε -optimal pseudoflow with $O(k)$ excess.
- REFINE then reduces the excess in the newly constructed pseudoflow to zero, making it an ε -optimal circulation.

Thus, the algorithm produces an ε^* -optimal circulation after $O(\log(kC/\varepsilon^*))$ scales. Using the reduction in Lemma 3.2, we have the diameter of the point set, thus maximum cost C , bounded by $O(K \cdot kn^3)$ for some value K . By setting ε^* to be $K \cdot \varepsilon/6k$, the number of cost scales is bounded above by $O(\log(n/\varepsilon))$.

Scale initialization. Recall that H is the *reduction graph* and N_H is the *reduction network*, both constructed in Section 3.2. The vertex set of H consists of two point sets A and B , as well as two dummy vertices s and t . The directed edges in H are pointed from s to A , from A to B , and from B to t . We call those arcs in N_H whose direction is consistent with their corresponding directed edges as *forward arcs*, and those arcs that points in the opposite direction as *backward arcs*.

The procedure SCALE-INIT transforms a 2ε -optimal circulation from the previous cost scale into an ε -optimal flow with $O(k)$ excess, by raising the potentials π of all vertices in A by ε , those in B by 2ε , and the potential of t by 3ε . The potential of s remains unchanged. Now the reduced cost of every forward arc is dropped by ε , and thus all the forward arcs have reduced cost at least $-\varepsilon$.

As for backward arcs, the procedure SCALE-INIT continues by setting the flow on $v \rightarrow w$ to zero for each backward arc $w \rightarrow v$ violating the ε -optimality constraint. In other words, we set $f(v \rightarrow w) = 0$ whenever $c_\pi(w \rightarrow v) < -\varepsilon$. This ensures that all such backward arcs are no longer residual, and therefore the flow (now with excess) is ε -optimal.

Because the arcs are of unit-capacity in N_H , each arc desaturation creates one unit of excess. By Lemma 3.3 the number of backward arcs is at most $3k$. Thus the total amount of excess created is also $O(k)$.

In total, potential updates and backward arc desaturations, thus the whole procedure SCALE-INIT, take $O(n)$ time.

Refinement. The procedure REFINE is implemented using a primal-dual augmentation algorithm, which sends flows on admissible arcs to reduce the total excess, like the Hungarian algorithm. Unlike the Hungarian algorithm, it uses *blocking flows* instead of augmenting paths. An *augmenting path* is a path in the residual network from an excess vertex to a

² When the costs are integers, an ε -optimal circulation for a sufficiently small ε (say less than $1/n$) is itself an optimal solution [4, 5]. We present this algorithm without the integral-cost assumption because in the geometric partial matching setting (with respect to L_p norms) the costs are generally not integers.

deficit vertex. We call a pseudoflow f on residual network N_g a *blocking flow* if f saturates at least one residual arc in every augmenting path in N_g . In other words, there is no admissible augmenting path in N_{f+g} from an excess vertex to a deficit vertex.

Each iteration of REFINE finds an admissible blocking flow that is then added to the current pseudoflow in two stages:

1. A *Hungarian search*, which increases the dual variables π of vertices that are reachable from an excess vertex by at least ε , in a Dijkstra-like manner, until there is an excess-deficit path of admissible edges.
2. A *depth-first search* through the set of admissible edges to construct an admissible blocking flow. It suffices to repeatedly extract admissible augmenting paths until no more admissible excess-deficit paths remain. By definition, the union of such paths is a blocking flow. **«Move to where the blocking flow is introduced?»**

The algorithm continues until the total excess becomes zero and the ε -optimal flow is now a circulation.

First we analyze the number of iterations executed by REFINE. The proof follows the strategy in Goldberg *et al.* [4, Section 3.2]. **«and maybe §5 of Goldberg-Tarjan?»** To this end we need a bound on the size of the support of f right before and throughout the execution of REFINE.

► **Lemma 3.5.** *Let f be an integer pseudoflow in N_H with $O(k)$ excess. Then, the size of the support of f is at most $O(k)$.*

► **Corollary 3.6.** *The size of $\text{supp}(f)$ is at most $O(k)$ for pseudoflow f right before or during the execution of REFINE.*

► **Lemma 3.7.** *Let f be a pseudoflow in N_H with $O(k)$ excess. The procedure REFINE runs for $O(\sqrt{k})$ iterations before the excess of f becomes zero.*

The goal of the next section is to show that after $O(n \text{ polylog } n)$ time preprocessing, each Hungarian search and depth-first search can be implemented in $O(k \text{ polylog } n)$ time. Combined with the $O(\sqrt{k})$ bound on the number of iterations we just proved, the procedure REFINE can be implemented in $O((n + k\sqrt{k}) \text{ polylog } n)$ time. Together with our analysis on scale initialization and the bound on number of cost scales, this concludes the proof to Theorem 1.2.

4 Fast Implementation

Both Hungarian search and depth-first search are implemented in a Dijkstra-like fashion, traversing through the residual graph using admissible arcs starting from the excess vertices. Each step of the search procedures *relaxes* a minimum-reduced-cost arc from the set of visited vertices to an unvisited vertex, until a deficit vertex is reached. At a high level, our analysis strategy is to charge the relaxation events to the support arcs of f , which has size at most $O(k)$ by Corollary 3.6.

4.1 Null vertices and shortcut graph

«A figure might be helpful for this section.»

As it turns out, there are some vertices visited by a relaxation event which we cannot charge to $\text{supp}(f)$. Unfortunately the number of such vertices can be as large as $\Omega(n)$ (consider the residual graph under the zero flow). To overcome this issue, we replace the residual graph with an equivalent graph that excludes all the null vertices, and run the Hungarian search and depth-first search on the resulting graph instead.

Null vertices. We say a vertex v in the residual graph N_f is a *null vertex* if $\phi_f(v) = 0$ and no arcs of $\text{supp}(f)$ is incident to v . We use A_\emptyset and B_\emptyset to denote the null vertices A and B respectively. Vertices that are not null are called *normal vertices*. A *null 2-path* is a length-2 subpath in N_f from a normal vertex to another normal vertex, passing through a null vertex. As every vertex in A has in-degree 1 and every vertex in B has out-degree 1 in the residual graph, the null 2-paths must be of the form either (s, v, b) for some vertex b in $B \setminus B_\emptyset$ or (a, v, t) for some vertex a in $A \setminus A_\emptyset$. In either case, we say that the null 2-path *passes through* null vertex v . Similarly, we define the length-3 path from s to t that passes through two null vertices to be a *null 3-path*. Because reduced costs telescope for residual paths, the reduced cost of any null 2-path or null 3-path does not depend on the null vertices it passes through.

Shortcut graph. We construct the *shortcut graph* \tilde{H}_f from the reduction network H by removing all null vertices and their incident edges, followed by inserting an arc from the head of each null path Π to its tail, with cost equals to the sum of costs on the arcs. We call this arc the *shortcut* of null path Π , denoted as $\text{short}(\Pi)$. The resulting multigraph \tilde{H}_f contains only normal vertices of H_f , and the reduced cost of any path between normal vertices are preserved. We argue now that \tilde{H}_f is fine as a surrogate for H_f . Let $\tilde{\pi}$ be an ε -optimal potential on \tilde{H}_f . Construct potentials π on H_f which extends $\tilde{\pi}$ to null vertices, by setting $\pi(a) := \tilde{\pi}(s)$ for $a \in A_\emptyset$ and $\pi(b) := \tilde{\pi}(t)$ for $b \in B_\emptyset$.

► **Lemma 4.1.** *Consider $\tilde{\pi}$ an ε -optimal potential on \tilde{H}_f and π the corresponding potential constructed on H_f . Then,*

1. *potential π is ε -optimal on H_f , and*
2. *if arc $\text{short}(\Pi)$ is admissible under $\tilde{\pi}$, then every arc in Π is admissible under π .*

4.2 Dynamic data structures for search procedures

Hungarian search. «*Shortly describe the Hungarian search and depth-first search implementations.*»

Conceptually, we are executing the Hungarian search on the shortcut graph \tilde{H}_f . We describe how we can query the minimum-reduced-cost arc leaving \tilde{S} in $O(\text{polylog } n)$ time for the shortcut graph, without constructing \tilde{H}_f explicitly. For this purpose, let \tilde{S} be a set of “reached” vertices maintained, identical to \tilde{S} except whenever a shortcut is relaxed, we add the null vertices passed by the corresponding null path to \tilde{S} in addition to its (normal) endpoints. Observe that the arcs of \tilde{H}_f leaving \tilde{S} fall into $O(1)$ categories.

By construction, the distance returned by each of the BCP data structure is equal to the reduced cost of the shortcut, which is equal to the reduced cost of the corresponding null path. Each of the above data structures requires one query per relaxation, and an update operation whenever a new vertex moves into \tilde{S} . The data structures above can perform both queries and updates in $O(\text{polylog } n)$ time each, so the running time of the Hungarian search other than the potential updates can be charged to the number of relaxation steps.

Depth-first search. The depth-first search is similar to Hungarian search in that it uses the relaxation of minimum-reduced-cost arcs/null paths, this time to identify admissible arcs/null paths in a depth-first manner. This requires some adjustments to the data structures for finding the minimum-reduced-cost arc leaving $v' \in \tilde{S}$.

Each data structure performs a constant number of queries and updates per relaxation, each of which can be implemented in $O(\text{polylog } n)$ time []; so the running time is again bounded by $O(\text{polylog } n)$ times the number of relaxations.

4.3 Time analysis

First we bound the number of relaxations performed by both the Hungarian search and the depth-first search.

► **Lemma 4.2.** *Both Hungarian search and depth-first search performs $O(k)$ relaxations before a deficit vertex is reached.*

Now we complete the time analysis by showing that each Hungarian search and depth-first search can be implemented in $O(k \text{ polylog } n)$ time after a one-time $O(n \text{ polylog } n)$ -time preprocessing.

► **Lemma 4.3.** *After $O(n \text{ polylog } n)$ -time preprocessing, each Hungarian search and depth-first search can be implemented in $O(k \text{ polylog } n)$ time.*

4.4 Number of potential updates on null vertices

In our implementation of REFINE, we do not explicitly construct \tilde{H}_f ; instead we query its edges using BCP/NN oracles and min/max heaps on elements of H_f . Potentials on the null vertices are only required right before an augmentation sends a flow through a null path, making the null vertices it passes normal. We use the construction from Lemma 4.1 to obtain potential π on H_f such that the flow f is both ε -optimal and admissible with respect to π .

Size of blocking flows. Now we bound the total number arcs whose flow is updated by a blocking flow during the course of REFINE. This bounds both the time spent updating the flow on these arcs and also the time spent on null vertex potential updates (Lemma 4.5).

► **Lemma 4.4.** *The support of each blocking flow found in REFINE is of size $O(k)$.*

► **Lemma 4.5.** *The number of end-of-REFINE null vertex potential updates is $O(n)$. The number of augmentation-induced null vertex potential updates in each invocation of REFINE is $O(k \log k)$.*

Now combining Lemma B.3, Lemma B.4, and Lemma 4.5 completes the proof of Theorem 1.2.

5 Unbalanced Transportation

In this section, we give an exact algorithm which solves the planar transportation problem in $O(rn^{3/2} \text{ polylog } n)$ time, proving Theorem 1.3. We describe a geometric implementation of the uncapacitated min-cost flow algorithm due to Orlin [8], combined with some of the tools developed in Sections 2 and 3. Mainly, we batch potential updates and use the rewinding mechanism to initialize each Hungarian search in time proportional to the previous Hungarian search.

Let A and B be point sets in the plane. Let $\lambda : A \cup B \rightarrow \mathbb{Z}$ be a *supply-demand function* with positive value on points of A , negative value on points of B , satisfying $\sum_{a \in A} \lambda(a) = -\sum_{b \in B} \lambda(b)$. Define $U := \max_{p \in A \cup B} |\lambda(p)|$. A *transportation map* is a function $\tau : A \times B \rightarrow \mathbb{R}_{\geq 0}$. A transportation map τ is *feasible* if $\sum_{b \in B} \tau(a, b) = \lambda(a)$ for all $a \in A$, and $\sum_{a \in A} \tau(a, b) = -\lambda(b)$ for all $b \in B$. In other words, the value $\tau(a, b)$ describes how much supply at a should be sent to meet demands at b , and we require that all supplies are sent and all demands are met. We define the *cost* of τ to be

$$\text{cost}(\tau) := \sum_{(a,b) \in A \times B} \|a - b\|_p^q \cdot \tau(a, b).$$

Given A , B , and λ , the *transportation problem* asks to find a feasible transportation map of minimum cost. We focus on the case when the point sets are *unbalanced*; that is, the given point sets have different sizes r and n ; without loss of generality assuming $r \leq n$.

There is a simple reduction from the transportation problem to the uncapacitated min-cost flow problem. Consider the complete bipartite graph G between A and B (with all edges directed from A to B). Set the costs $c(a, b)$ to be $\|a - b\|_p^q$, all capacities $u(a, b)$ to infinity, and the supply-demand function $\phi = \lambda$. Any circulation f in the network $N = (G, c, u, \phi)$ can be converted into a feasible transportation map τ_f by taking $\tau_f(a, b) := f(a \rightarrow b)$ for every edges (a, b) . One simply has $\text{cost}(f) = \text{cost}(\tau_f)$.

5.1 Uncapacitated MCF by excess scaling

We give an outline of the strongly polynomial algorithm for uncapacitated min-cost flow problem from Orlin [8]. Orlin's algorithm follows an *excess-scaling* paradigm originally due to Edmonds and Karp [2]. Consider the basic primal-dual framework used in the previous sections: The algorithm begins with both flow f and potentials π set to zero. Repeatedly runs a *Hungarian search* that raises potentials (while maintaining dual feasibility) to create an admissible augmenting excess-deficit path, on which we perform flow augmentations. In terms of cost, f is maintained to be 0-optimal with respect to π and each augmentation over admissible edges preserve such property by Lemma 3.1. Thus, the final circulation must be optimal. The excess-scaling paradigm builds on top of this skeleton by specifying (i) between which excess and deficit vertices we send flows, and (ii) how much flow is sent by the augmentation.

The excess-scaling algorithm maintains a *scale parameter* Δ , initially set to U . A vertex v with $|\phi_f(v)| \geq \Delta$ is called *active*. Each augmenting path is chosen between an active excess vertex and an active deficit vertex. Once there are no more active excess or deficit vertices, Δ is halved. Each sequence of augmentations where Δ holds a constant value is called an *excess scale*. There are $O(\log U)$ excess scales before $\Delta < 1$ and, by integrality of supplies/demands, f is a circulation.

With some modifications to the excess-scaling algorithm, Orlin [8] obtains a strongly polynomial bound on the number of augmentations and excess scales. First, an *active* vertex is redefined to be one satisfying $|\phi_f(v)| \geq \alpha\Delta$, for a fixed parameter $\alpha \in (0.5, 1)$. Second, arcs with flow value at least $3n\Delta$ at the beginning of a scale are *contracted* to create a new vertex, whose supply-demand is the sum of those on the two endpoints of the contracted arc. We use $\hat{G} = (\hat{V}, \hat{E})$ to denote the resulting *contracted graph*, where each $\hat{v} \in \hat{V}$ is a contracted component of vertices from V . Intuitively, the flow is so high on contracted arcs that no set of future augmentations can remove the arc from $\text{supp}(f)$. Third, in addition to halving, Δ is aggressively lowered to $\max_{v \in V} \phi_f(v)$ if there are no active excess vertices and $f(v \rightarrow w) = 0$ holds for every arc $v \rightarrow w \in \hat{E}$. Finally, flow values are not tracked within contracted components, but once an optimal circulation is found on \hat{G} , optimal potentials π^* can be *recovered* for G by sequentially undoing the contractions. The algorithm then performs a post-processing step which finds the optimal circulation f^* on G by solving a max-flow problem on the set of admissible arcs under π^* .

► **Theorem 5.1 (Orlin [8, Theorems 2 and 3]).** *Orlin's algorithm finds a set of optimal potentials after $O(n \log n)$ scaling phases and $O(n \log n)$ total augmentations.*

The remainder of the section focuses on showing that each augmentation can be implemented in $O(r\sqrt{n} \text{polylog } n)$ time (after preprocessing). Additionally, we show that f^* can be recovered from π^* very quickly in our setting.

Implementing contractions. Following Agarwal *et al.* [1], our geometric data structures must deal with real points in the plane instead of the contracted components. We will track the contracted components described in \hat{G} (e.g. with a disjoint-set data structure) and mark the arcs of $\text{supp}(f)$ that are contracted. We maintain potentials on the points A and B directly, instead of the contracted components.

When conducting the Hungarian search, we initialize S to be the set of vertices from *active excess contracted components* who (in sum) meet the imbalance criteria. **«unclear»** Upon relaxing any $v \in \hat{v}$, we immediately relax all the contracted support arcs which span \hat{v} . Since the input network is uncapacitated, each contracted component is strongly connected in the residual network by the admissible forward/backward arcs of each contracted arc. **«unparsable»** To relax arcs in \hat{E} , we relax the support arcs before attempting to relax any non-support arcs. **«mention the reason to make support acyclic»** Relaxations of support arcs can be performed without further potential changes, since they are admissible by invariant.

During the augmentations, contracted residual arcs are considered to have infinite capacity, and we do not update the value of flows on these arcs. We allow augmenting paths to begin from any point $a \in \hat{v} \cap A$ in an active excess component \hat{v} , and end at any point $b \in \hat{w} \cap B$ in an active deficit component \hat{w} .

Recovering optimal flow. Rewinding contracted components to recover an optimal flow naïvely takes $O(rn^2)$ time. Use a strategy from Agarwal *et al.* [1], we can recover the optimal flow in time $O(n \text{ polylog } n)$. If furthermore the cost function is just the p -norm (without the q th-power), an even stronger result stands: In this case, the set of admissible arcs under an optimal potential forms a planar graph, and thus we can apply the planar maximum-flow algorithm [?, 3] which runs in $O(n \log n)$ time. For details see the appendix.

5.2 Dead vertices and support stars

Our goal is to implement each augmentation in $O(r\sqrt{n} \text{ polylog } n)$ time. To find an augmenting path, we again use a Hungarian search with geometric data structures to perform relaxations quickly. Like in Section 3, there are vertices which cannot be charged to the flow support. Even worse, the flow support for the transportation problem may have size $\Omega(n)$ (consider when A has one point, and demands are uniformly distributed among the vertices of B). Our strategy is summarized as follows:

- Discard vertices which lead to dead ends in the search (not on a path to a deficit vertex).
- Cluster parts of the flow support, such that the number of support arcs outside clusters is $O(r)$. The number of relaxations we perform is proportional to the number of support arcs outside of clusters.

Querying/updating clusters degrades our amortized time per relaxation from $O(\text{polylog } n)$ to $O(\sqrt{n} \text{ polylog } n)$. Thus overall each augmentation takes $O(r\sqrt{n} \text{ polylog } n)$ time.

Dead vertices. Let the *support degree* of a vertex be its degree in the graph induced by the underlying edges of $\text{supp}(f)$. We call a vertex $b \in B$ *dead* if b has support degree 0 and is not an active excess or deficit vertex; call it *live* otherwise. Dead vertices are essentially equivalent to the *null vertices* of Section 3. However, since the reduction in this section does not use a super-source/super-sink, we can simply remove these from consideration during a Hungarian search — they will not terminate the search, and have no outgoing residual arcs. Like the null vertices, we ignore dead vertex potentials and infer feasible potentials when they become live again. We use A_ℓ and B_ℓ to denote the living vertices of points in A and

538 B , respectively. Note that being dead/alive is a notion strictly defined only for vertices, and
 539 not for contracted components.

540 We say a dead vertex is *revived* when it stops meeting either condition of the definition.
 541 Dead vertices are only revived after Δ decreases (at the start of a subsequent excess scale)
 542 as no augmenting path will cross a dead vertex and they cannot meet the criteria for
 543 contractions. When a dead vertex is revived, we must add it back into each of our data
 544 structures and give it a feasible potential. For revived $b \in B$, a feasible choice of potential
 545 is $\pi(b) \leftarrow \max_{a \in A} (\pi(a) - c(a, b))$ which we can query by maintaining a weighted nearest
 546 neighbor data structure on the points of A . The total number of revivals is bounded above
 547 by the number of augmentations: since the final flow is a circulation on \hat{G} and a newly
 548 revived vertex v has no incident arcs in $\text{supp}(f)$ and cannot be contracted, there is at least
 549 one subsequent augmentation which uses v as its beginning or end. Thus, the total number
 550 of revivals is $O(n \log n)$.

551 **Support stars.** The vertices of B with support degree 1 are partitioned into subsets $\Sigma_a \subset B$
 552 by the $a \in A$ lying on the other end of their single support arc. We call Σ_a the *support star*
 553 centered at $a \in A$.

554 Roughly speaking, we would like to handle each support star as a single unit. When the
 555 Hungarian search reaches a or any $b \in \Sigma_a$, the entirety of Σ_a (as well as a) is also admissibly-
 556 reachable and can be included into S without further potential updates. Additionally, the
 557 only outgoing residual arcs of every $b \in \Sigma_a$ lead to a , thus the only way to leave $\Sigma_a \cup \{a\}$
 558 is through an arc leaving a . Once a relaxation step reaches some $b \in \Sigma_a$ or a itself, we
 559 would like to quickly update the state such that the rest of $b \in \Sigma_a$ is also reached without
 560 performing relaxation steps to each individual $b \in \Sigma_a$.

561 5.3 Implementation details

562 Before describing our workaround for support stars, we analyze the number of relaxation
 563 steps for arcs outside of support stars.

564 ► **Lemma 5.2.** *Suppose we have stripped the graph of dead vertices. The number of relaxation*
 565 *steps in a Hungarian search outside of support stars is $O(r)$.*

566 The running time of a Hungarian search will be $O(r)$ times the time it takes us to
 567 implement each relaxation.

568 **Relaxations outside support stars.** For relaxations that don't involve support star vertices,
 569 we can once again maintain a BCP to query the minimum A_ℓ -to- B_ℓ arc. To elaborate, this is
 570 the BCP between $P = A_\ell \cap S$ and $Q = (B_\ell \setminus (\bigcup_{a \in A_\ell} \Sigma_a)) \setminus S$, weighted by potentials. This
 571 can be queried in $O(\log n)$ time and updated in $O(\text{polylog } n)$ time per point. Since it doesn't
 572 deal with support stars, there is at most one insertion/deletion per relaxation step.

573 For B_ℓ -to- A_ℓ , backward (support) arcs are kept admissible by invariant, so we relax them
 574 immediately when they arrive on the frontier.

575 **Relaxing a support star.** We classify support stars into two categories: *big stars* are those
 576 with $|\Sigma_a| > \sqrt{n}$, and *small stars* are those with $|\Sigma_a| \leq \sqrt{n}$. Let $A_{\text{big}} \subseteq A$ denote the centers
 577 of big stars and $A_{\text{small}} \subseteq A$ denote the centers of small stars. We keep the following
 578 data structures to manage support stars.

1. For each big star Σ_a , we use a data structure $\mathcal{D}_{\text{big}}(a)$ to maintain BCP between $P = A_\ell \cap S$ and $Q = \Sigma_a$, weighted by potentials. We query this until $a \in S$ or any vertex of Σ_a is added to S .
2. All small stars are added to a single BCP data structure $\mathcal{D}_{\text{small}}$ between $P = A_\ell \cap S$ and $Q = (\bigcup_{a \in A_{\text{small}}} \Sigma_a) \setminus S$, weighted by potentials. When an $a \in A_{\text{small}}$ or any vertex of its support star is added to S , we remove the points of Σ_a from $\mathcal{D}_{\text{small}}$ using $|\Sigma_a|$ deletion operations.

We will update these data structures as each support star center is added into S . If a relaxation step adds some $b \in B_\ell$ and b is in a support star Σ_a , then we immediately relax $b \rightarrow a$, as all support arcs are admissible. Relaxations of non-support star $b \in B_\ell$ will not affect the support star data structures.

Suppose a relaxation step adds some $a \in A_\ell$ to S . For the support star data structures, we must (i) remove a from every \mathcal{D}_{big} , (ii) remove a from $\mathcal{D}_{\text{small}}$. If $a \in A_{\text{big}}$, we also (iii) deactivate $\mathcal{D}_{\text{big}}(a)$. If $a \in A_{\text{small}}$, we also (iv) remove the points of Σ_a from $\mathcal{D}_{\text{small}}$. The operations (i–iii) can be performed in $O(\text{polylog } n)$ time each, but (iv) may take up to $O(\sqrt{n} \text{ polylog } n)$ time.

On the other hand, there are now $O(\sqrt{n})$ data structures to query during each relaxation step, as there are $O(n/\sqrt{n})$ data structures $\mathcal{D}_{\text{big}}(\cdot)$. Thus, the query time within each relaxation step is $O(\sqrt{n} \log n)$. We can now bound the time spent within the Hungarian search.

► **Lemma 5.3.** *Hungarian search takes $O(r\sqrt{n} \text{ polylog } n)$ time.*

Updating support stars. As the flow support changes, the membership of support stars may shift and a big star may eventually become small (or vice versa). To efficiently support this, introduce some fuzziness to when a star should be big or small. Standard charging argument shows that the amortized update time is $O(r\sqrt{n}(r + \sqrt{n}) \text{ polylog } n)$.

Membership of support stars can only be changed by augmentations, so the number of star membership changes by a single augmenting path is bounded above by twice its length (each vertex may be removed from one star, and/or added to another star). Thus, individual membership changes can be performed in $O(\text{polylog } n)$ time each, and there are $O(rn \log n)$ total.

Preprocessing time. To build the very first set of data structures, we take $O(rn \text{ polylog } n)$ time. There are $r|\Sigma_a|$ points in each $\mathcal{D}_{\text{big}}(a)$, but the Σ_a are disjoint, so the total points to insert is $O(rn)$. $\mathcal{D}_{\text{small}}$ also has at most $O(rn)$ points. Each BCP data structure can be constructed in $O(\text{polylog } n)$ times its size, so the total preprocessing time is $O(rn \text{ polylog } n)$.

Between searches. After an augmentation, we reset the above data structures to their initial state plus the change from the augmentation using the rewinding mechanism. By reversing the sequence of insertions/deletions to each data structure over the course of the Hungarian search, we can recover the versions data structures as they were when the Hungarian search began. This takes time proportional to the time of the Hungarian search, $O(r\sqrt{n} \text{ polylog } n)$ by Lemma 5.3. The most recent augmentation may have deactivated at most one active excess and at most one active deficit, which we can update in the data structures in $O(\sqrt{n} \text{ polylog } n)$ time. Additionally, the augmentation may have changed the membership of some support stars, but we analyzed the time for membership changes earlier. Finally, we note that an augmenting path cannot reduce the support degree of a vertex to zero, and therefore no new dead vertices are created by augmentation.

Between excess scales. When the excess scale changes, vertices that were previously inactive may become active, and vertices that were dead may be revived (however, no active vertices deactivate, and no live vertices die as the result of Δ decreasing). If we have the data structures built on the active excesses at the end of the previous scale, then we can add in each newly active $a \in A$ and charge this insertion to the (future) augmenting path or contraction which eventually makes the vertex inactive, or absorbs it into another component. By Theorem 5.1, there are $O(n \log n)$ such newly active vertices. The time to perform data structure updates for each of them is $O(\sqrt{n} \text{polylog } n)$, so the total time spent bookkeeping newly active vertices is $O(n^{3/2} \text{polylog } n)$.

Putting it together. After $O(rn \text{polylog } n)$ preprocessing, we spend $O(r\sqrt{n} \text{polylog } n)$ time each Hungarian search by Lemma 5.3. After each augmentation, we spend the same amount of time (plus $O(\text{polylog } n)$ extra) to initialize data structures for the next Hungarian search. We spend up to $O((rn + r^2\sqrt{n}) \text{polylog } n)$ total time making big-small star switching updates. We spend $O(n^{3/2} \text{polylog } n)$ time activating and reviving vertices. Thus, the algorithm takes $O(rn(r/\sqrt{n} + \sqrt{n}) \text{polylog } n)$ time to produce optimal potentials π^* , from which we can recover f^* in $O(r\sqrt{n} \text{polylog } n)$ additional time. This completes the proof of Theorem 1.3.

Acknowledgment.

References

- 1 Pankaj K. Agarwal, Kyle Fox, Debmalya Panigrahi, Kasturi R. Varadarajan, and Allen Xiao. Faster algorithms for the geometric transportation problem. *33rd International Symposium on Computational Geometry, SoCG 2017, July 4-7, 2017, Brisbane, Australia*, 7:1–7:16, 2017. <https://doi.org/10.4230/LIPIcs.SocG.2017.7>.
- 2 Jack Edmonds and Richard M. Karp. Theoretical improvements in algorithmic efficiency for network flow problems. *J. ACM* 19(2):248–264, 1972. <https://doi.org/10.1145/321694.321699>.
- 3 Jeff Erickson. Maximum flows and parametric shortest paths in planar graphs. *Proceedings of the Twenty-First Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2010, Austin, Texas, USA, January 17-19, 2010*, 794–804, 2010. <https://doi.org/10.1137/1.9781611973075.65>.
- 4 Andrew V. Goldberg, Sagi Hed, Haim Kaplan, and Robert E. Tarjan. Minimum-cost flows in unit-capacity networks. *Theory Comput. Syst.* 61(4):987–1010, 2017. <https://doi.org/10.1007/s00224-017-9776-7>.
- 5 Andrew V. Goldberg and Robert E. Tarjan. Finding minimum-cost circulations by successive approximation. *Math. Oper. Res.* 15(3):430–466, 1990. <https://doi.org/10.1287/moor.15.3.430>.
- 6 Haim Kaplan, Wolfgang Mulzer, Liam Roditty, Paul Seiferth, and Micha Sharir. Dynamic planar voronoi diagrams for general distance functions and their algorithmic applications. *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2017, Barcelona, Spain, Hotel Porta Fira, January 16-19*, 2495–2504, 2017. <https://doi.org/10.1137/1.9781611974782.165>.
- 7 Harold W Kuhn. The Hungarian method for the assignment problem. *Naval Research Logistics (NRL)* 2(1-2):83–97. Wiley Online Library, 1955.
- 8 James B. Orlin. A faster strongly polynomial minimum cost flow algorithm. *Operations Research* 41(2):338–350, 1993. <https://doi.org/10.1287/opre.41.2.338>.
- 9 Lyle Ramshaw and Robert Endre Tarjan. A weight-scaling algorithm for min-cost imperfect matchings in bipartite graphs. *53rd Annual IEEE Symposium on Foundations of*

- 670 *Computer Science, FOCS 2012, New Brunswick, NJ, USA, October 20-23, 2012*, 581–590,
671 2012. <https://doi.org/10.1109/FOCS.2012.9>.
- 672 **10** R. Sharathkumar and Pankaj K. Agarwal. Algorithms for the transportation problem in geo-
673 metric settings. *Proceedings of the Twenty-Third Annual ACM-SIAM Symposium on Dis-*
674 *crete Algorithms, SODA 2012, Kyoto, Japan, January 17-19, 2012*, 306–317, 2012. [http:](http://portal.acm.org/citation.cfm?id=2095145&CFID=63838676&CFTOKEN=79617016)
675 [://portal.acm.org/citation.cfm?id=2095145&CFID=63838676&CFTOKEN=79617016](http://portal.acm.org/citation.cfm?id=2095145&CFID=63838676&CFTOKEN=79617016).
- 676 **11** Pravin M. Vaidya. Geometry helps in matching. *SIAM J. Comput.* 18(6):1201–1225, 1989.
677 <https://doi.org/10.1137/0218080>.

A Proofs from Section 3

► **Lemma 3.1.** *Let f be an ε -optimal pseudoflow in G and let f' be an admissible flow in G_f . Then $f + f'$ is also ε -optimal. «(Lemma 5.3 in [GT90]? Also, where is this used?)»*

Proof. Augmentation by f' will not change the potentials, so any previously ε -optimal arcs remain ε -optimal. However, it may introduce new arcs $v \rightarrow w$ with $u_{f+f'}(v \rightarrow w) > 0$, that previously had $u_f(v \rightarrow w) = 0$. We will verify that these arcs satisfy the ε -optimality condition.

If an arc $v \rightarrow w$ is newly introduced this way, then by definition of residual capacities $f(v \rightarrow w) = u(v \rightarrow w)$. At the same time, $u_{f+f'}(v \rightarrow w) > 0$ implies that $(f + f')(v \rightarrow w) < u(v \rightarrow w)$. This means that f' augmented flow in the reverse direction of $v \rightarrow w$ ($f'(w \rightarrow v) > 0$). By assumption, the arcs of $\text{supp}(f')$ are admissible, so $w \rightarrow v$ was an admissible arc ($c_\pi(w \rightarrow v) \leq 0$). By antisymmetry of reduced costs, this implies $c_\pi(v \rightarrow w) \geq 0 \geq -\varepsilon$. Therefore, all arcs with $u_{f+f'}(v, w) > 0$ respect the ε -optimality condition, and thus $f + f'$ is ε -optimal. ◀

► **Lemma 3.3.** *Let f be an integer circulation in the reduction network N_H . Then, the size of the support of f is at most $3k$. As a corollary, the number of residual backward arcs is at most $3k$.*

Proof. Because f is a circulation, $\text{supp}(f)$ can be decomposed into k paths from s to t . Each s -to- t path in N_H is of length three, so the size of $\text{supp}(f)$ is at most $3k$. As every backward arc in the residual network must be induced by positive flow in the opposite direction, the total number of residual backward arcs is at most $3k$. ◀

► **Lemma 3.4.** *Let f be an ε -optimal integer circulation in N_H , and f^* be an optimal integer circulation for N_H . Then, $\text{cost}(f) \leq \text{cost}(f^*) + 6k\varepsilon$.*

Proof. By Lemma 3.3, the total number of backward arcs in the residual network N_f is at most $3k$. Consider the residual flow in N_f defined by the difference between f^* and f . Since both f and f^* are both circulations and N_H has unit-capacity, the flow $f - f^*$ is comprised of unit flows on a collection of edge-disjoint residual cycles $\Gamma_1, \dots, \Gamma_\ell$. Observe that each residual cycle Γ_i must have exactly half of its arcs being backward arcs, and thus we have $\sum_i |\Gamma_i| \leq 6k$.

Let π be some potential certifying that f is ε -optimal. Because Γ_i is a residual cycle, we have $c_\pi(\Gamma_i) = c(\Gamma_i)$ since the potential terms telescope. We then see that

$$\text{cost}(f) - \text{cost}(f^*) = \sum_i c(\Gamma_i) = \sum_i c_\pi(\Gamma_i) \geq \sum_i (-\varepsilon) \cdot |\Gamma_i| \geq -6k\varepsilon,$$

where the second-to-last inequality follows from the ε -optimality of f with respect to π . Rearranging the terms we have that $\text{cost}(f) \leq \text{cost}(f^*) + 6k\varepsilon$. ◀

Let T be the minimum spanning tree on input graph G and order its edges by increasing length as e_1, \dots, e_{r+n-1} . Let T_ℓ denote the subgraph of T obtained by removing the heaviest ℓ edges in T . Let i be the largest index so that the optimal solution to the MPM problem has edges between components of T_i . Choose j to be the smallest index larger than i satisfying $c(e_j) \geq kn \cdot c(e_i)$. For each component K of T_j , let G_K be the subgraph of G induced on vertices of K ; let $A_K := K \cap A$ and $B_K := K \cap B$, respectively. We partition A and B into the collection of sets A_K and B_K according to the components K of T_j . Since $j < i$, the optimal partial matching in G can be partitioned into edges between A_K and B_K within G_K ; no optimal matching edges lie between components.

719 ► **Lemma A.1 (Sharathkumar and Agarwal [SA12, §3.5]).** *Let $G = (A, B, E_0)$ be the input*
 720 *to MPM problem, and consider the partitions A_K and B_K defined as above. Let M^* be the*
 721 *optimal partial matching in G . Then,*

- 722 (i) $c(e_i) \leq \text{cost}(M^*) \leq kn \cdot c(e_i)$, and
 723 (ii) *the diameter of G_K is at most $kn^2 \cdot c(e_i)$ for every $K \in T_j$,*

724 To prove Lemma 3.2, we need to further modify the point set so that the cost of the
 725 optimal solution does not change, while the diameter of the *whole* point set is bounded. Move
 726 the points within each component in *translation* so that the minimum distances between
 727 points across components are at least $kn \cdot c(e_i)$ but at most $O(n \cdot kn^2 \cdot c(e_i))$. This will
 728 guarantee that the optimal solution still uses edges within the components by Lemma A.1.
 729 The simplest way of achieving this is by aligning the components one by one into a “straight
 730 line”, so that the distance between the two farthest components is at most $O(n)$ times the
 731 maximum diameter of the cluster.

732 Now one can prove Lemma 3.2 by computing an $(\varepsilon c(e_i)/6k)$ -optimal circulation f on the
 733 point set after translations using additive approximation from Lemma 3.4, together with the
 734 bound $c(e_i) \leq \text{cost}(M^*)$ from Lemma A.1.

735 One small problem remains: We need to show that such reduction can be performed in
 736 $O(n \text{ polylog } n)$ time. Sharathkumar and Agarwal [SA12] have shown that the partition of A
 737 and B into A_K s and B_K s can be computed in $O(n \text{ polylog } n)$ time, assuming that the indices
 738 i and j can be determined in such time as well. However in our application the choice of
 739 index i depends on the optimal solution of MPM problem which we do not know.

740 To solve this issue we perform a binary search on the edges e_1, \dots, e_{r+n-1} . **«Hmm, we**
 741 **have no way to check Lemma 4.5(i); but in fact a polynomial bound is good enough.»**
 742 **«UNRESOLVED ISSUE»**

743 ► **Lemma 3.5.** *Let f be an integer pseudoflow in N_H with $O(k)$ excess. Then, the size of*
 744 *the support of f is at most $O(k)$.*

745 **Proof.** Observe that the reduction graph H is a directed acyclic graph, and thus the support
 746 of f does not contain a cycle. Now $\text{supp}(f)$ can be decomposed into a set of inclusion-maximal
 747 paths, each of which contributes a single unit of excess to the flow if the path does not
 748 terminate at t or if more than k paths terminate at t . By assumption, there are $O(k)$ units
 749 of excess to which we can associate to the paths, and at most k paths (those that terminate
 750 at t) that we cannot associate with a unit of excess. The length of any such paths is at most
 751 three by construction of the reduction graph H . Therefore we can conclude that the number
 752 of arcs in the support of f is $O(k)$. ◀

753 ► **Lemma 3.7.** *Let f be a pseudoflow in N_H with $O(k)$ excess. The procedure REFINE runs*
 754 *for $O(\sqrt{k})$ iterations before the excess of f becomes zero.*

755 **Proof.** Let f_0 and π_0 be the flow and potential at the start of the procedure REFINE. Let f
 756 and π be the current flow and the potential. Let $d(v)$ defined to be the amount of potential
 757 increase at v , measured in units of ε ; in other words, $d(v) := (\pi(v) - \pi_0(v))/\varepsilon$.

758 Now divide the iterations executed by the procedure REFINE into two phases: The
 759 transition from the first phase to the second happens when every excess vertex v has
 760 $d(v) \geq \sqrt{k}$. At most \sqrt{k} iterations belong to the first phase as each Hungarian search
 761 increases the potential π by at least ε for each excess vertex (and thus increases $d(v)$ by at
 762 least one).

763 The number of iterations belonging to the second phase is upper bounded by the amount
 764 of total excess at the end of the first phase, because each subsequent push of a blocking

flow reduces the total excess by at least one. We now show that the amount of such excess is at most $O(\sqrt{k})$. Consider the set of arcs $E^+ := \{v \rightarrow w \mid f(v \rightarrow w) < f_0(v \rightarrow w)\}$. The total amount of excess is upper bounded by the number of arcs in E^+ that crosses an arbitrarily given cut X that separates the excess vertices from the deficit vertices, when the network has unit-capacity [GHKT17, Lemma 3.6]. Consider the set of cuts $X_i := \{v \mid d(v) > i\}$ for $0 \leq i < \sqrt{k}$; every such cut separates the excess vertices from the deficit vertices at the end of first phase. Each arc in E^+ crosses at most 3 cuts of type X_i [GHKT17, Lemma 3.1]. So there is one X_i crossed by at most $3|E^+|/\sqrt{k}$ arcs in E^+ . The size of E^+ is bounded by the sum of support sizes of f and f_0 ; by Corollary 3.6 the size of E^+ is $O(k)$. This implies an $O(\sqrt{k})$ bound on the total excess after the first phase, which in turn bounds the number of iterations in the second phase. ◀

B Proofs from Section 4

► **Lemma 4.1.** *Consider $\tilde{\pi}$ an ε -optimal potential on \tilde{H}_f and π the corresponding potential constructed on H_f . Then,*

1. *potential π is ε -optimal on H_f , and*
2. *if arc $\text{short}(\Pi)$ is admissible under $\tilde{\pi}$, then every arc in Π is admissible under π .*

Proof. Reduced costs for any arc from a normal vertex another is unchanged under either $\tilde{\pi}$ or π . Recall that a null path is comprised of one A -to- B arc, and one or two zero-cost arcs (connecting the null vertex/vertices to s and/or t). With our choice of null vertex potentials, we observe that the zero-cost arcs still have zero reduced cost. It remains to prove that an arbitrary **«residual?»** arc (a, b) **«arc or directed edge?»** satisfies the ε -optimality condition and admissibility when either a or b is a null vertex.

By construction of the shortcut graph, there is always a null path Π that contains (a, b) . Observe that $c_\pi(a, b) = c_\pi(\Pi)$, independent to the type of null path. Again by construction, $c_\pi(\Pi) = c_{\tilde{\pi}}(\text{short}(\Pi))$, so we have $c_\pi(a, b) = c_{\tilde{\pi}}(\text{short}(\Pi)) \geq -\varepsilon$. Additionally, if $\text{short}(\Pi)$ is admissible under $\tilde{\pi}$, then so is (a, b) under π . This proves the lemma. ◀

1. Non-shortcut backward arcs (v, w) with $(w, v) \in \text{supp}(f)$. For these, we can maintain a min-heap on $\text{supp}(f)$ arcs as each v arrives in \tilde{S} .
2. Non-shortcut A -to- B forward arcs. For these, we can use a BCP data structure between $(A \setminus A_\emptyset) \cap \tilde{S}$ and $(B \setminus B_\emptyset) \setminus \tilde{S}$, weighted by potential.
3. Non-shortcut forward arcs from s -to- A and from B -to- t . For s , we can maintain a min-heap on the potentials of $B \setminus \tilde{S}$, queried while $s \in \tilde{S}$. For t , we can maintain a max-heap on the potentials of $A \cap \tilde{S}$, queried while $t \notin \tilde{S}$.
4. Shortcut arcs (s, b) corresponding to null 2-paths from s to $b \in (B \setminus B_\emptyset) \setminus S$. For these, we maintain a BCP data structure with $P = A_\emptyset$, $Q = (B \setminus B_\emptyset) \setminus S$ with weights $\omega(p) = \pi(s)$ for all $p \in P$, and $\omega(q) = \pi(q)$ for all $q \in Q$. A response (a, b) corresponds to th null 2-path (s, a, b) . This is only queried while $s \in S$.
5. Shortcut arcs (a, t) corresponding to null 2-paths from $a \in (A \setminus A_\emptyset) \cap S$ to t . For these, we maintain a BCP data structure with $P = (A \setminus A_\emptyset) \cap S$, $Q = B_\emptyset \setminus S$ with weights $\omega(p) = \pi(p)$ for all $p \in P$, and $\omega(q) = \pi(t)$ for all $q \in Q$. A response (a, b) corresponds to th null 2-path (a, b, t) . This is only queried while $t \notin S$.
6. Shortcut arcs (s, t) corresponding to null 3-paths. For these, we maintain in a BCP data structure with $P = A_\emptyset \setminus S$, $Q = B_\emptyset \setminus S$ with weights $\omega(p) = \pi(s)$ for all $p \in P$, and $\omega(q) = \pi(t)$ for all $q \in Q$. A response (a, b) corresponds to th null 3-path (s, a, b, t) . This is only queried while $s \in S$ and $t \notin S$.

810 Given $v' \in \tilde{S}$, we would like to query:

- 811 1. Non-shortcut backward arcs (v', w') with $(w', v') \in \text{supp}(f)$. For these, we can maintain
812 a min-heap on $(w', v') \in \text{supp}(f)$ arcs for each normal $v' \in V$.
- 813 2. Non-shortcut A -to- B forward arcs. For these, we maintain a NN data structure over
814 $P = (B \setminus B_\emptyset) \setminus \tilde{S}$, with weights $\omega(p) = \pi(p)$ for each $p \in P$. We subtract $\pi(v')$ from the
815 NN distance to recover the reduced cost of the arc from v' .
- 816 3. Non-shortcut forward arcs from s -to- A and from B -to- t . For s , we can maintain a
817 min-heap on the potentials of $B \setminus \tilde{S}$, queried only if $v' = s$. For B -to- t arcs, there is only
818 one arc to check if $v' \in B$, which we can examine manually.
- 819 4. Shortcut arcs (s, b) corresponding to null 2-paths from s to $b \in (B \setminus B_\emptyset) \setminus S$. For these, we
820 maintain a BCP data structure with $P = A_\emptyset$, $Q = (B \setminus B_\emptyset) \setminus S$ with weights $\omega(p) = \pi(s)$
821 for all $p \in P$, and $\omega(q) = \pi(q)$ for all $q \in Q$. A response (a, b) corresponds to th null
822 2-path (s, a, b) . This is only queried if $v' = s$.
- 823 5. Shortcut arcs (a, t) corresponding to null 2-paths from $a \in (A \setminus A_\emptyset) \cap S$ to t . For these,
824 we maintain a NN data structure over $P = B_\emptyset \setminus S$ with weights $\omega(p) = \pi(t)$ for each
825 $p \in P$. A response (v', b) corresponds to th null 2-path (v', b, t) . We subtract $\pi(v')$ from
826 the NN distance to recover the reduced cost of the arc from v' . This is not queried if
827 $t \in \tilde{S}$.
- 828 6. Shortcut arcs (s, t) corresponding to null 3-paths. For these, we maintain in a BCP data
829 structure with $P = A_\emptyset \setminus S$, $Q = B_\emptyset \setminus S$ with weights $\omega(p) = \pi(s)$ for all $p \in P$, and
830 $\omega(q) = \pi(t)$ for all $q \in Q$. A response (a, b) corresponds to th null 3-path (s, a, b, t) . This
831 is only queried while $v' = s$ and $t \notin S$.

832 ► **Lemma B.1.** *Hungarian search performs $O(k)$ relaxations before a deficit vertex is reached.*

833 **Proof.** **«TO BE REWRITTEN.»** First we prove that there are $O(k)$ non-shortcut relaxa-
834 tions. Each edge relaxation adds a new vertex to S , and non-shortcut relaxations only add
835 normal vertices. The vertices of $V \setminus S$ fall into several categories: (i) s or t , (ii) vertices of A
836 or B with 0 imbalance, and (iii) deficit vertices of A or B (S contains all excess vertices).
837 The number of vertices in (i) and (iii) is $O(k)$, leaving us to bound the number of (ii) vertices.

838 An A or B vertex with 0 imbalance must have an even number of $\text{supp}(f)$ edges. There is
839 either only one positive-capacity incoming arc (for A) or outgoing arc (for B), so this quantity
840 is either 0 or 2. Since the vertex is normal, this must be 2. We charge 0.5 to each of the two
841 $\text{supp}(f)$ arcs; the arcs of $\text{supp}(f)$ have no more than 1 charge each. Thus, the number of
842 type (ii) vertex relaxations is $O(|\text{supp}(f)|)$. By Corollary 3.6, $O(|\text{supp}(f)|) = O(k)$.

843 Next we prove that there are $O(k)$ shortcut relaxations. Recall the categories of shortcuts
844 from the list of data structures above. We have shortcuts corresponding to (i) null 2-paths
845 surrounding $a \in A_\emptyset$, (ii) null 2-paths surrounding $b \in B_\emptyset$, and (iii) null 3-paths, which go
846 from s to t . There is only one relaxation of type (iii), since t can only be added to S once.
847 The same argument holds for type (ii).

848 Each type (i) relaxation adds some normal $b \in B \setminus B_\emptyset$ into S . Since b is normal, it must
849 either have deficit or an adjacent arc of $\text{supp}(f)$. We charge this relaxation to b if it is deficit,
850 or the adjacent arc of $\text{supp}(f)$ otherwise. No vertex is charged more than once, and no
851 $\text{supp}(f)$ edge is charged more than twice, therefore the total number of type (i) relaxations
852 is $O(|\text{supp}(f)|)$. By Corollary 3.6, $O(|\text{supp}(f)|) = O(k)$. ◀

853 Similarly we can prove that there are $O(k)$ relaxations during the DFS.

854 ► **Corollary B.2.** *Depth-first search performs $O(k)$ relaxations before a deficit vertex is*
855 *reached.*

► **Lemma B.3.** *After $O(n \text{ polylog } n)$ -time preprocessing, each Hungarian search can be implemented in $O(k \text{ polylog } n)$ time.*

Proof. Each of the constant number of data structures used by the Hungarian search can be constructed in $O(n \text{ polylog } n)$ time. For each data structure queried during a relaxation, the new vertex moved into S causes a constant number of updates, each of which can be implemented in $O(\text{polylog } n)$ time. We first prove that the number of BCP operations during the Hungarian search over is bounded by $O(k)$.

1. Let S^t denote the initial set S at the beginning of the t -th Hungarian search. Assume for now that, at the beginning of the $(t + 1)$ -th Hungarian search, we have the set S^t from the previous iteration. To construct S^{t+1} , we remove the vertices that had excess decreased to zero by the t -th blocking flow. Thus, we are able to initialize S at the cost of one BCP deletion per excess vertex, which sums to $O(k)$ over the entire course of REFINE. **«Too strong as a bound? Is it enough to look at one Hungarian search?»**
2. During each Hungarian search, a vertex entering S may incur one BCP insertion/deletion. We can charge the updates to the number of relaxations over the course of Hungarian search. The number of relaxations in a Hungarian search is $O(k)$ by Lemma B.1.
3. To obtain S^t , we keep track of the points added to S^t since the last Hungarian search. After the augmentation, we remove those points added to S^t . By (2) there are $O(k)$ such points to be deleted, so reconstructing S^t takes $O(k)$ BCP operations.

For potential updates, we use the same trick by Vaidya [Vai89] to lazily update potentials after vertices leave S (similar to Lemma ??), but this time only for normal vertices. Normal vertices are stored in each data structure with weight $\omega(v) = \pi(v) - \delta$, and δ is increased in lieu of increasing the potential of vertices in S . When a vertex leave S (through the rewind mechanism above), we restore its potential as $\pi(v) \leftarrow \omega(v) + \delta$. With lazy updates, the number of potential updates on normal vertices is bounded by the number of relaxations in the Hungarian search, which is $O(k)$ by Lemma B.1. Note that null vertex potentials are not handled in the Hungarian search. **«then where? Lemma 4.5»** ◀

There are no potentials to update within DFS, so the running time of DFS boils down to the time spent to querying and updating the data structures.

► **Lemma B.4.** *After $O(n \text{ polylog } n)$ -time preprocessing, each depth-first search can be implemented in $O(k \text{ polylog } n)$ time.*

Proof. At the beginning of REFINE, we can initialize the $O(1)$ data structures used in DFS in $O(n \text{ polylog } n)$ time. We use the same rewinding mechanism as in Hungarian search (Lemma B.3) to avoid reconstructing the data structures across iterations of REFINE, so the total time spent is bounded by the $O(\text{polylog } n)$ times the number of relaxations. By Corollary B.2, the running time for depth-first search is $O(k \text{ polylog } n)$. ◀

► **Lemma 4.4.** *The support of each blocking flow found in REFINE is of size $O(k)$.*

Proof. Let i be fixed and consider the invocation of DFS which produces the i -th blocking flow f_i . DFS constructs f_i as a sequence of admissible excess-deficit paths, which appear as path P in Algorithm ??. Every arc in P is an arc relaxed by DFS, so N_i is bounded by the number of relaxations performed in DFS. Using Corollary B.2, we have $N_i = O(k)$. ◀

► **Lemma 4.5.** *The number of end-of-REFINE null vertex potential updates is $O(n)$. The number of augmentation-induced null vertex potential updates in each invocation of REFINE is $O(k \log k)$.*

Proof. The number of end-of-REFINE potential updates is $O(n)$. Each update due to flow augmentation involves a blocking flow sending positive flow through a null path, causing a potential update on the passed null vertex. We charge this potential update to the edges of that null path, which are in turn arcs with positive flow in the blocking flow. For each blocking flow, no positive arc is charged more than twice. It follows that the number of augmentation-induced updates is at most the size of support of the blocking flow, which is $O(k)$ by Lemma 4.4. According to Lemma 3.7 there are $O(\sqrt{k})$ iterations of REFINE before it terminates. Summing up we have an $O(k\sqrt{k})$ bound over the course of REFINE. ◀

C Proofs from Section 5

Recovering the optimal flow. «use this one if we want to use exponent > 1 . »

«Move everything to appendix and left a pointer to the socg 2016 paper.»

We use a strategy from Agarwal *et al.* [AFP⁺17]. Instead of finding a max flow in the entire admissible network under π^* , we claim that is sufficient to find a max flow in a *spanning tree* of admissible arcs, e.g. a shortest path tree on reduced costs. There are some details to explain — like where the tree should be rooted, how to ensure the underlying network is strongly connected by admissible arcs — but we give the intuition first: Such a spanning tree is a maximal set of linearly independent dual LP constraints for the optimal dual (π^*) , so there exists an optimal primal solution (f^*) with support only on these arcs. To see this, we can use a perturbation argument: raising the cost of each non-tree edge by $\varepsilon > 0$ does not change $\text{cost}(\pi^*)$ or the feasibility of π^* , but does raise the cost of any circulation f using non-tree edges. Strong duality suggests that $\text{cost}(f^*) = \text{cost}(\pi^*)$ is unchanged, therefore f^* must have support only on the tree edges.

«TODO: the SPT construction requires describing Dijkstra and promising strong connectivity»

Recovering the optimal flow. «use this one if we only use exponent 1. »

Instead of running a generic max-flow algorithm after finding the optimal potentials, we use the following observation.

Up until now, we have not placed restrictions on coincidence between A and B , but for the next proof it is useful to do so. We can assume that all points within $A \cup B$ are distinct, otherwise we can replace all points coincident at $x \in \mathbb{R}^2$ with a single point whose supply/demand is $\sum_{v \in A \cup B: v=x} \lambda(v)$. This is roughly equivalent to transporting as much as we can between coincident supply and demand, and is optimal by triangle inequality. So without loss of generality, we assume all points of $A \cup B$ are distinct.

Without loss of generality, assume π^* is nonnegative (raising π^* uniformly on all points does not change the objective or feasibility). Recall that feasibility of π^* states that, for all $a \in A$ and $b \in B$

$$c_{\pi^*}(a, b) = \|a - b\|_p - \pi^*(a) + \pi^*(b) \geq 0.$$

An arc $a \rightarrow b$ is admissible when

$$c_{\pi^*}(a, b) = \|a - b\|_p - \pi^*(a) + \pi^*(b) = 0.$$

We note that these definitions have a nice visual: Place disks D_q of radius $\pi(q)$ at each $q \in A \cup B$. Feasibility states that for all $a \in A$ and $b \in B$, D_a cannot contain D_b with a gap between their boundaries. The arc $a \rightarrow b$ is admissible when D_a contains D_b and their boundaries are tangent.

► **Lemma C.1.** *Let π^* be a set of optimal potentials for the point sets A and B , under costs $c(a, b) = \|a - b\|_p$. Then, the set of admissible arcs under π^* form a planar graph.*

Proof. We assume the points of $A \cup B$ are in general position (e.g. by symbolic perturbation) such that no three points are collinear. Let $a_1 \rightarrow b_1$ and $a_2 \rightarrow b_2$ be any pair of admissible arcs under π^* . We will isolate them from the rest of the points, considering π^* restricted to the four points $\{a_1, a_2, b_1, b_2\}$. Clearly, this does not change whether the two arcs cross. Observe that we can raise $\pi^*(a_2)$ and $\pi^*(b_2)$ uniformly, until $c_\pi(a_2, b_1) = 0$, without breaking feasibility or changing admissibility of $a_1 \rightarrow b_1$ and $a_2 \rightarrow b_2$. Henceforth, we assume that we have modified π^* in this way to make $a_2 \rightarrow b_1$ admissible. Given positions of a_1 , a_2 , and b_1 , we now try to place b_2 such that $a_1 \rightarrow b_1$ and $a_2 \rightarrow b_2$ cross. Specifically, b_2 must be placed within a region \mathcal{F} that lies between the rays $\overrightarrow{a_2 a_1}$ and $\overrightarrow{a_2 b_1}$, and within the halfplane bounded by $\overrightarrow{a_1 b_1}$ that does not contain a_2 .

Let $g_a(q) := \|a - q\| - \pi^*(a)$ for $a \in A$ and $q \in \mathbb{R}^2$. Let the *bisector* between a_1 and a_2 be $\beta := \{q \in \mathbb{R}^2 \mid g_{a_1}(q) = g_{a_2}(q)\}$. β is a curve subdividing the plane into two open faces, one where g_{a_1} is minimized and the other where g_{a_2} is. From these definitions, admissibility of $a_1 \rightarrow b_1$ and $a_2 \rightarrow b_1$ imply that b_1 is a point of the bisector.

We show that \mathcal{F} lies entirely on the g_{a_1} side of the bisector. First, we prove that the closed segment $\overline{a_1 b_1}$ lies entirely on the g_{a_1} side, except b_1 which lies on β . Any $q \in \overline{a_1 b_1}$ can be written parametrically as $q(t) = (1 - t)b_1 + ta_1$ for $t \in [0, 1]$. Consider the single-variable functions $g_{a_1}(q(t))$ and $g_{a_2}(q(t))$.

$$\begin{aligned} g_{a_1}(q(t)) &= (1 - t)\|a_1 - b_1\| - \pi(a_1) \\ g_{a_2}(q(t)) &= \|(a_2 - b_1) - t(a_1 - b_1)\| - \pi(a_2) \end{aligned}$$

At $t = 0$, these expressions are equal. Observe that the derivative with respect to t of $g_{a_1}(q(t))$ is less than $g_{a_2}(q(t))$. Indeed, the value of $\frac{d}{dt}\|(a_2 - b_1) - t(a_1 - b_1)\|$ is at least $-\|a_1 - b_1\| = \frac{d}{dt}g_{a_1}(q(t))$, which is realized if and only if $\frac{(a_2 - b_1)}{\|a_2 - b_1\|} = \frac{(a_1 - b_1)}{\|a_1 - b_1\|}$. This corresponds to $\overrightarrow{a_2 b_1}$ and $\overrightarrow{a_1 b_1}$ being parallel, but this is disallowed since a_1, a_2, b_1 are in general position. Thus, $g_{a_1}(q(t)) \leq g_{a_2}(q(t))$ with equality only at b_1 .

Now, we parameterize each point of \mathcal{F} in terms of points on $\overline{a_1 b_1}$. Every $q \in \mathcal{F}$ can be written as $q(t') = q' + t'(q' - a_2)$ for some $q' \in \overline{a_1 b_1}$ and $t \geq 0$, i.e. $q' = \overline{a_1 b_1} \cap \overline{a_2 q}$. We call q' the *projection* of q onto $\overline{a_1 b_1}$. We can write g_{a_1} and g_{a_2} in terms of t' and observe that $\frac{d}{dt'}g_{a_1}(q(t')) \leq \frac{d}{dt'}g_{a_2}(q(t'))$, as the derivative of $g_a(q(t'))$ is maximized if $(q(t') - a)$ is parallel to $(q(t') - a_2)$ and lower otherwise. Notably, $q(t')$ with projection b_1 have $\frac{d}{dt'}g_{a_1}(q(t')) < \frac{d}{dt'}g_{a_2}(q(t'))$, since a_1, a_2, b_1 are in general position. Any $q(t')$ with a different projection do not have strict inequality, but the projection itself has $g_{a_1}(q') < g_{a_2}(q')$ for $q' \neq b_1$ since it lies on $\overline{a_1 b_1}$. Therefore, for all $q \in \mathcal{F} \setminus \{b_1\}$, $g_{a_1}(q') < g_{a_2}(q')$, and \mathcal{F} lies on the g_{a_1} side of the bisector except for b_1 which lies on β . We can eliminate b_1 as a candidate position for b_2 , since points of B cannot coincide.

Observe that $g_{a_1}(b) < g_{a_2}(b)$ for $b \in B$ implies that $c_\pi(a_1, b) < c_\pi(a_2, b)$, and $c_\pi(a_1, b) = c_\pi(a_2, b)$ if and only if b lies on β . This holds for all $b \in \mathcal{F}$ including our prospective b_2 , but then $c_\pi(a_1, b_2) < c_\pi(a_2, b_2) = 0$ since $a_2 \rightarrow b_2$ is admissible. This violates feasibility of $a_1 \rightarrow b_2$, so there is no feasible placement of b_2 which also crosses $a_1 \rightarrow b_1$ with $a_2 \rightarrow b_2$. ◀

We can construct the entire set of admissible arcs by repeatedly querying the minimum-reduced-cost outgoing arc for each $a \in A$ until the result is not admissible. By Lemma C.1 the resulting arc set forms a planar graph, so by Euler's formula the number of arcs to query is $O(n)$. We can then find the maximum flow in time $O(n \log n)$ time, using for example the planar maximum-flow algorithm by Erickson [Eri10]. ◀◀cite others like Klein▶▶

By prioritizing the relaxation of support arcs, we also have the following lemma.

► **Lemma C.2 (Agarwal et al. [AFP⁺17]).** *If arcs of $\text{supp}(f)$ are relaxed first as they arrive on the frontier, then $E(\text{supp}(f))$ is acyclic.*

Proof. Let f_i be the pseudoflow after the i -th augmentation, and let T_i be the forest of relaxed arcs generated by the Hungarian search for the i -th augmentation. Namely, the i -th augmenting path is an excess-deficit path in T_i , and all arcs of T_i are admissible by the time the augmentation is performed. Let $E(T_i)$ be the undirected edges corresponding to arcs of T_i . Notice that, $E(\text{supp}(f_{i+1})) \subseteq E(\text{supp}(f_i)) \cup E(T_i)$. We prove that $E(\text{supp}(f_i)) \cup E(T_i)$ is acyclic by induction on i ; as $E(\text{supp}(f_{i+1}))$ is a subset of these edges, it must also be acyclic. At the beginning with $f_0 = 0$, $E(\text{supp}(f_0))$ is vacuously acyclic.

Let $E(\text{supp}(f_i))$ be acyclic by induction hypothesis. Since T_i is a forest (thus, acyclic), any hypothetical cycle Γ that forms in $E(\text{supp}(f_i)) \cup E(T_i)$ must contain edges from both $E(\text{supp}(f_i))$ and $E(T_i)$. To give a visual analogy, we will color $e \in \Gamma$ *purple* if $e \in E(\text{supp}(f_i)) \cap E(T_i)$, *red* if $e \in E(\text{supp}(f_i))$ but $e \notin E(T_i)$, and *blue* if $e \in E(T_i)$ but $e \notin E(\text{supp}(f_i))$. Then, Γ is neither entirely red nor entirely blue. We say that red and purple edges are *red-tinted*, and similarly blue and purple edges are *blue-tinted*. Roughly speaking, our implementation of the Hungarian search prioritizes relaxing red-tinted admissible arcs over pure blue arcs.

We can sort the blue-tinted edges of Γ by the order they were relaxed into S during the Hungarian search forming T_i . Let $(v, w) \in \Gamma$ be the last pure blue edge relaxed, of all the blue-tinted edges in Γ — after (v, w) is relaxed, the remaining unrelaxed, blue-tinted edges of Γ are purple.

Let us pause the Hungarian search the moment before (v, w) is relaxed. At this point, $v \in S$ and $w \notin S$, and the Hungarian search must have finished relaxing all frontier support arcs. By our choice of (v, w) , $\Gamma \setminus (v, w)$ is a path of relaxed blue edges and red-tinted edges which connect v and w . Walking around $\Gamma \setminus (v, w)$ from v to w , we see that every vertex of the cycle must be in S already: $v \in S$, relaxed blue edges have both endpoints in S , and any unrelaxed red-tinted edge must have both endpoints in S , since the Hungarian search would have prioritized relaxing the red-tinted edges to grow S before relaxing (v, w) (a blue edge). It follows that $w \in S$ already, a contradiction.

No such cycle Γ can exist, thus $E(\text{supp}(f_i)) \cup E(T_i)$ is acyclic and $E(\text{supp}(f_{i+1})) \subseteq E(\text{supp}(f_i)) \cup E(T_i)$ is acyclic. By induction, $E(\text{supp}(f_i))$ is acyclic for all i . ◀

Let $E(\Sigma_a)$ *◀only used once▶* be the underlying edges of the support star centered at a and $F := E(\text{supp}(f)) \setminus \bigcup_{a \in A} E(\Sigma_a)$. Using Lemma C.2, we can show that the number of support arcs outside support stars ($|F|$) is small.

► **Lemma C.3.** $|B_\ell \setminus \bigcup_{a \in A} \Sigma_a| \leq r$.

Proof. F is constructed from $E(\text{supp}(f))$ by eliminating edges in support stars, therefore all edges in F must adjoin vertices in B of support degree at least 2. By Lemma C.2, $E(\text{supp}(f))$ is acyclic and therefore forms a spanning forest over $A \cup B_\ell$, so F is also a bipartite forest. All leaves of F are therefore vertices of A .

Pick an arbitrary root for each connected component of F to establish parent-child relationships for each edge. As no vertex in B is a leaf, each vertex in B has at least one child. Charge each vertex in B to one of its children in F , which must belong to A . Each vertex in A is charged at most once. Thus, the number of B_ℓ vertices outside of support stars is no more than r . ◀

1033 ► **Lemma 5.2.** *Suppose we have stripped the graph of dead vertices. The number of relaxation*
 1034 *steps in a Hungarian search outside of support stars is $O(r)$.*

1035 **Proof.** If there are no dead vertices, then each non-support star relaxation step adds either
 1036 (i) an active deficit vertex, (ii) a non-deficit vertex $a \in A_\ell$, or (iii) a non-deficit vertex $b \in B_\ell$
 1037 of support degree at least 2. There is a single relaxation of type (i), as it terminates the
 1038 search. The number of vertices of type (ii) is r , and the number of vertices of type (iii) is at
 1039 most r by Lemma C.3. The lemma follows. ◀

1040 ► **Lemma 5.3.** *Hungarian search takes $O(r\sqrt{n} \text{ polylog } n)$ time.*

1041 **Proof.** The number of relaxation steps outside of support stars is $O(r)$ by Lemma 5.2. The
 1042 time per relaxation outside of support stars is $O(\sqrt{n} \text{ polylog } n)$. The time spent processing
 1043 relaxations within a support star is $O(\sqrt{n} \text{ polylog } n)$, and at most r are relaxed during the
 1044 search. The total time is therefore $O(r\sqrt{n} \text{ polylog } n)$. ◀

1045 Initially, we label stars big or small according to the \sqrt{n} threshold. A star that is currently
 1046 big is turned into a small star once $|\Sigma_a| \leq \sqrt{n}/2$. A star that is currently small is turned into
 1047 a big star once $|\Sigma_a| \geq 2\sqrt{n}$. This way, the time spent rebuilding/updating the respective
 1048 data structures can be amortized to the insertions/deletions that preceded the switch, plus
 1049 some $O(r)$ extra work if the the update is small-to-big.

1050 A star Σ_a that is switching from big-to-small has size $|\Sigma_a| \leq \sqrt{n}/2$. When switching, we
 1051 delete $\mathcal{D}_{\text{big}}(a)$ and insert Σ_a into $\mathcal{D}_{\text{small}}$. Thus, the time spent for big-to-small update is
 1052 $O(\sqrt{n} \text{ polylog } n)$, and there were at least $\sqrt{n}/2$ points removed from Σ_a since it was last big.

1053 A star Σ_a that is switching from small-to-big has size $|\Sigma_a| = \sqrt{n} + x \geq 2\sqrt{n}$, for some
 1054 integer $x \geq \sqrt{n}$. Rearranging, we have $|\Sigma_a| \leq 2x$. When switching, we delete all $|\Sigma_a|$
 1055 points from $\mathcal{D}_{\text{small}}$ and construct a new $\mathcal{D}_{\text{big}}(a)$. Constructing $\mathcal{D}_{\text{big}}(a)$ requires inserting
 1056 $O(r)$ points of A (into P) and the $|\Sigma_a|$ points of the star (into Q). Thus, the time spent for
 1057 a small-to-big update is $O((r+x) \text{ polylog } n)$, and there were at least $x \geq \sqrt{n}$ points added
 1058 to Σ_a since it was last small.

1059 — References for the Appendix —

- 1060 **AFP⁺17** Pankaj K. Agarwal, Kyle Fox, Debmalaya Panigrahi, Kasturi R. Varadarajan, and Allen
 1061 Xiao. Faster algorithms for the geometric transportation problem. In *33rd International*
 1062 *Symposium on Computational Geometry, SoCG 2017, July 4-7, 2017, Brisbane, Australia*,
 1063 pages 7:1–7:16, 2017.
- 1064 **Eri10** Jeff Erickson. Maximum flows and parametric shortest paths in planar graphs. In *Proceed-*
 1065 *ings of the Twenty-First Annual ACM-SIAM Symposium on Discrete Algorithms, SODA*
 1066 *2010, Austin, Texas, USA, January 17-19, 2010*, pages 794–804, 2010.
- 1067 **GHKT17** Andrew V. Goldberg, Sagi Hed, Haim Kaplan, and Robert E. Tarjan. Minimum-cost flows
 1068 in unit-capacity networks. *Theory Comput. Syst.*, 61(4):987–1010, 2017.
- 1069 **GT90** Andrew V. Goldberg and Robert E. Tarjan. Finding minimum-cost circulations by success-
 1070 ive approximation. *Math. Oper. Res.*, 15(3):430–466, 1990.
- 1071 **SA12** R. Sharathkumar and Pankaj K. Agarwal. Algorithms for the transportation problem in
 1072 geometric settings. In *Proceedings of the Twenty-Third Annual ACM-SIAM Symposium*
 1073 *on Discrete Algorithms, SODA 2012, Kyoto, Japan, January 17-19, 2012*, pages 306–317,
 1074 2012.
- 1075 **Vai89** Pravin M. Vaidya. Geometry helps in matching. *SIAM J. Comput.*, 18(6):1201–1225, 1989.