

# Stanford CS193p

## Developing Applications for iOS

### Fall 2013-14



# Today

- ⦿ **Introduction to Objective-C (con't)**

Continue showing Card Game Model with Deck, PlayingCard, PlayingCardDeck

- ⦿ **Xcode 5 Demonstration**

Start building the simple Card Game

# Objective-C

Card.h

```
#import <Foundation/Foundation.h>

@interface Card : NSObject

@property (strong, nonatomic) NSString *contents;

@property (nonatomic, getter=isChosen) BOOL chosen;
@property (nonatomic, getter=isMatched) BOOL matched;

- (int)match:(NSArray *)otherCards;

@end
```

Card.m

```
#import "Card.h"

@interface Card()

@end

@implementation Card

- (int)match:(NSArray *)otherCards
{
    int score = 0;

    for (Card *card in otherCards) {
        if ([card.contents isEqualToString:self.contents]) {
            score = 1;
        }
    }

    return score;
}

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>

@interface Deck : NSObject

@end
```

Let's look at another class.  
This one represents a deck of cards.

Deck.m

```
#import "Deck.h"

@interface Deck()

@end

@implementation Deck
```

@end

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;

- (Card *)drawRandomCard;

@end
```

```
#import "Deck.h"

@interface Deck()

@end

@implementation Deck
```

Note that this method has 2 arguments  
(and returns nothing).  
It's called “addCard:atTop:”.

And this one takes no arguments and returns a Card  
(i.e. a pointer to an instance of a Card in the heap).

@end

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;

- (Card *)drawRandomCard;

@end
```

We must `#import` the header file for any class we use in this file (e.g. Card).

Deck.m

```
#import "Deck.h"

@interface Deck()

@end

@implementation Deck
```

```
@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;

- (Card *)drawRandomCard;

@end
```

Deck.m

```
#import "Deck.h"

@interface Deck()

@end

@implementation Deck

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{

}

- (Card *)drawRandomCard { }

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject
- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (Card *)drawRandomCard;
@end
```

Deck.m

```
#import "Deck.h"

Arguments to methods
(like the atTop: argument)
are never “optional.”

@implementation Deck

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
}

- (Card *)drawRandomCard { }

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject
- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;
- (Card *)drawRandomCard;
@end
```

Deck.m

```
#import "Deck.h"
@implementation Deck
```

Arguments to methods  
(like the atTop: argument)  
are never “optional.”

```
@end
```

However, if we want an addCard:  
method without atTop:, we can  
define it separately.

```
- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
}

- (Card *)drawRandomCard { }

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject
- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;
- (Card *)drawRandomCard;
@end
```

```
#import "Deck.h"
```

Arguments to methods  
(like the atTop: argument)  
are never “optional.”

```
@implementation Deck
```

However, if we want an addCard:  
method without atTop:, we can  
define it separately.

```
- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

And then simply implement it in  
terms of the the other method.

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

A deck of cards obviously needs some storage to keep the cards in. We need an `@property` for that. But we don't want it to be public (since it's part of our private, internal implementation).

Deck.m

```
#import "Deck.h"

@interface Deck()

@end

@implementation Deck

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

A deck of cards obviously needs some storage to keep the cards in. We need an `@property` for that. But we don't want it to be public (since it's part of our private, internal implementation).

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

So we put the `@property` declaration we need here in our `@implementation`.

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

self.cards is an `NSMutableArray` ...

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck
```

Now that we have a property to store our cards in, let's take a look at a sample implementation of the addCard:atTop: method.

```
- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
    if (atTop) {
        [self.cards insertObject:card atIndex:0];
    } else {
        [self.cards addObject:card];
    }
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

... and these are `NSMutableArray` methods.  
(`insertObject:atIndex:` and `addObject:`).

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject
- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

But there's a problem here.

When does the object pointed to by the pointer returned by `self.cards` ever get created?

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
    if (atTop) {
        [self.cards insertObject:card atIndex:0];
    } else {
        [self.cards addObject:card];
    }
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

Declaring a `@property` makes space in the instance for the pointer itself, but not does not allocate space in the heap for the object the pointer points to.

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject
- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;
@end
```

The place to put this needed heap allocation is  
in the getter for the cards @property.

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
    if (atTop) {
        [self.cards insertObject:card atIndex:0];
    } else {
        [self.cards addObject:card];
    }
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

The place to put this needed heap allocation is  
in the getter for the cards @property.

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [[NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
    if (atTop) {
        [self.cards insertObject:card atIndex:0];
    } else {
        [self.cards addObject:card];
    }
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

All properties start out with a value of 0  
(called nil for pointers to objects).  
So all we need to do is allocate and initialize the object if  
the pointer to it is nil.

This is called “lazy instantiation”.

Now you can start to see the usefulness of a @property.

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject
- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;
- (Card *)drawRandomCard;
@end
```

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck
- (NSMutableArray *)cards
{
    if (!_cards) _cards = [[NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
    if (atTop) {
        [self.cards insertObject:card atIndex:0];
    } else {
        [self.cards addObject:card];
    }
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

We'll talk about allocating and initializing objects more later, but here's a simple way to do it.

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

Now the cards property will always at least be an empty mutable array, so this code will always do what we want.

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [[NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
    if (atTop) {
        [self.cards insertObject:card atIndex:0];
    } else {
        [self.cards addObject:card];
    }
}

- (void)addCard:(Card *)card
{
    [self addCard:card atTop:NO];
}

- (Card *)drawRandomCard { }

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

Let's collapse the code we've written so far to make some space.

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [ [NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop { ... }
- (void)addCard:(Card *)card { ... }

- (Card *)drawRandomCard
{

}
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [ [NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop { ... }
- (void)addCard:(Card *)card { ... }

- (Card *)drawRandomCard
{
    Card *randomCard = nil;

    return randomCard;
}
```

drawRandomCard simply grabs a card from a random spot in our `self.cards` array.

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [[NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop { ... }
- (void)addCard:(Card *)card { ... }

- (Card *)drawRandomCard
{
    arc4random() randomCard = nil; arc4random() returns a random integer.
    This is the C modulo operator.

    unsigned index = arc4random() % [self.cards count];
    randomCard = self.cards[index];
    [self.cards removeObjectAtIndex:index]; These square brackets actually are the equivalent of sending the message objectAtIndexedSubscript: to the array.

    return randomCard;
}

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

Calling objectAtIndexedSubscript: with an argument of zero on an empty array will **crash** (array index out of bounds)!

So let's protect against that case.

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [[NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop { ... }
- (void)addCard:(Card *)card { ... }

- (Card *)drawRandomCard
{
    Card *randomCard = nil;

    if ([self.cards count]) {
        unsigned index = arc4random() % [self.cards count];
        randomCard = self.cards[index];
        [self.cards removeObjectAtIndex:index];
    }

    return randomCard;
}

@end
```

# Objective-C

Deck.h

```
#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

Deck.m

```
#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [[NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop { ... }
- (void)addCard:(Card *)card { ... }

- (Card *)drawRandomCard
{
    Card *randomCard = nil;

    if ([self.cards count]) {
        unsigned index = arc4random() % [self.cards count];
        randomCard = self.cards[index];
        [self.cards removeObjectAtIndex:index];
    }

    return randomCard;
}

@end
```

# Objective-C

PlayingCard.h

PlayingCard.m

Let's see what it's like to make a subclass of one of our own classes.  
In this example, a subclass of Card specific to a playing card (e.g.A♠).

# Objective-C

PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@end
```

PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard
```

Of course we must `#import` our superclass.

And `#import` our own header file in our implementation file.

@end

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

@end
```

A PlayingCard has some properties that a vanilla Card doesn't have.  
Namely, the PlayingCard's suit and rank.

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

`NSUInteger` is a typedef for an unsigned integer.

```
#import "PlayingCard.h"

@implementation PlayingCard
```

We'll represent the suit as an `NSString` that simply contains a single character corresponding to the suit (i.e. one of these characters: ♠♣♥♦).  
If this property is `nil`, it'll mean “suit not set”.

We'll represent the rank as an integer from 0 (rank not set) to 13 (a King).

We could just use the C type `unsigned int` here.  
It's mostly a style choice.  
Many people like to use `NSUInteger` and `NSInteger` in public API  
and `unsigned int` and `int` inside implementation.  
But be careful, `int` is 32 bits, `NSInteger` might be 64 bits.  
If you have an `NSInteger` that is really big (i.e. > 32 bits worth)  
it could get truncated if you assign it to an `int`.  
Probably safer to use one or the other everywhere.

```
@end
```

## PlayingCard.m

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

Users of our PlayingCard class might well simply access suit and rank properties directly.

But we can also support our superclass's contents property by overriding the getter to return a suitable (no pun intended) `NSString`.

Even though we are overriding the implementation of the `contents` method, we are not re-declaring the `contents` property in our header file. We'll just inherit that declaration from our superclass.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    return [NSString stringWithFormat:@"%d%@", self.rank, self.suit];
}
```

```
@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

Users of our PlayingCard class might well simply access suit and rank properties directly.

But we can also support our superclass's contents property by overriding the getter to return a suitable (no pun intended) `NSString`.

Even though we are overriding the implementation of the `contents` method, we are not re-declaring the `contents` property in our header file. We'll just inherit that declaration from our superclass.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    return [NSString stringWithFormat:@"%d%@", self.rank, self.suit];
}
```

The method `stringWithFormat:` is an `NSString` method that's sort of like using the C function `printf` to create the string.

Note we are creating an `NSString` here in a different way than `alloc/init`. We'll see more about "class methods" like `stringWithFormat:` a little later.

@end

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    return [NSString stringWithFormat:@"%d%@", self.rank, self.suit];
}
```

Calling the getters of our two properties  
(rank and suit) on ourself.

But this is a pretty bad representation of the card  
(e.g., it would say 11♣ instead of J♣ and 1♥ instead of A♥).

@end

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}
```

We'll create an `NSArray` of `NSStrings`, each of which corresponds to a given rank.

Again, 0 will be “rank not set” (so we'll use ?).  
11, 12 and 13 will be J Q K and 1 will be A.

Then we'll create our “J ♠” string by appending (with the `stringByAppendingString:` method) the suit onto the end of the string we get by looking in the array.

```
@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}
```

Notice the `@[]` notation to create an array.

Here's the array-accessing `[]` notation again  
(like we used with `self.cards[index]` earlier).

Also note the `@“ ”` notation to create a (constant) `NSString`.

All of these notations are converted into normal message-sends by the compiler.

For example, `@[ ... ]` is `[ [NSArray alloc] initWithObjects:... ]`.  
`rankStrings[self.rank]` is `[rankStrings objectAtIndexIndexedSubscript:self.rank]`.

`@end`

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic)NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}
```

This is nice because a “not yet set” rank shows up as ?.

But what about a “not yet set” suit?  
Let’s override the getter for suit to make a suit of `nil` return ?.

Yet another nice use for properties versus direct instance variables.

```
- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

Let's take this a little further and override the setter for suit to have it check to be sure no one tries to set a suit to something invalid.

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}
```

```
- (void)setSuit:(NSString *)suit
{
    if ([@[@"\u2665", @"\u2666", @"\u2663", @"\u2660"] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}
```

Notice that we can embed the array creation as the target of this message send. We're simply sending `containsObject:` to the array created by the `@[ ]`.

```
- (void)setSuit:(NSString *)suit
{
    if (@[@"\u2665", @"\u2666", @"\u2663", @"\u2664"] containsObject:suit) {
        _suit = suit;
    }
}
- (NSString *)suit
{
    return _suit ? _suit : @"";
}
```

`containsObject:` is an `NSArray` method.

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

But there's a problem here now.  
A compiler warning will be generated  
if we do this.

Why?

Because if you implement BOTH the  
setter and the getter for a property,  
then you have to create the instance  
variable for the property yourself.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

- (void)setSuit:(NSString *)suit
{
    if ([@[@"\u2665", @"\u2666", @"\u2663", @"\u2664"] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

But there's a problem here now.  
A compiler warning will be generated  
if we do this.

Why?

Because if you implement BOTH the  
setter and the getter for a property,  
then you have to create the instance  
variable for the property yourself.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

- (void)setSuit:(NSString *)suit
{
    if (@[@[@"\u2665"], @[@"\u2666"], @[@"\u2667"], @[@"\u2664"] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

Luckily, the compiler can help with this  
using the `@synthesize` directive.

If you implement only the setter OR  
the getter (or neither), the compiler  
adds this `@synthesize` for you.

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

Name of the property  
we're creating an  
instance variable for.

Name of the instance  
variable to associate with  
the property.

We almost always pick an  
instance variable name that is  
underbar followed by the  
name of the property.

- (void)setSuit:(NSString *)suit
{
    if ([@[@"\u2665", @"\u2666", @"\u2663", @"\u2660"] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter
```

You should only ever access the instance variable directly ...

```
- (void)setSuit:(NSString *)suit
{
    if ([@[@"\u2665", @"\u2666", @"\u2663", @"\u2660"] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}
```

... in the property's setter ...

... in its getter ...

... or in an initializer (more on this later).

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

All of the methods we've seen so far are “instance methods”.

They are methods sent to instances of a class.  
But it is also possible to create methods that are sent to the class itself.  
Usually these are either creation methods (like `alloc` or `stringWithFormat:`) or utility methods.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

- (void)setSuit:(NSString *)suit
{
    if ([@[@"\u2665", @"\u2666", @"\u2663", @"\u2660"] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

Class methods start with +
Instance methods start with -

@end
```

Here's an example of a class utility method which returns an `NSArray` of the `NSStrings` which are valid suits (e.g. ♠, ♣, ♥, and ♦).

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

+ (NSArray *)validSuits
{
    return ...
}

- (void)setSuit:(NSString *)suit
{
    if ([@[@"\u2665", @"\u2666", @"\u2663", @"\u2664"] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

Since a class method is not sent to an instance, we cannot reference our properties in here (since properties represent per-instance storage).

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

Here's an example of a class utility method which returns an `NSArray` of the `NSStrings` which are valid suits (e.g. ♠, ♣, ♥, and ♦).

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

+ (NSArray *)validSuits
{
    return @[@"\u2665", @"\u2666", @"\u2663", @"\u2664"];
}

- (void)setSuit:(NSString *)suit
{
    if ([containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

We actually already have the array of valid suits, so let's just move that up into our new class method.

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

Now let's invoke our new class method here.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

+ (NSArray *)validSuits
{
    return @[@"\u2665", @"\u2666", @"\u2663", @"\u2664"];
}

- (void)setSuit:(NSString *)suit
{
    if ([[PlayingCard validSuits] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

See how the name of the class appears in the place you'd normally see a pointer to an instance of an object?

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

@end
```

Now let's invoke our new class method here.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

+ (NSArray *)validSuits
{
    return @[@"\u2665", @"\u2666", @"\u2663", @"\u2664"];
}

- (void)setSuit:(NSString *)suit
{
    if ([[PlayingCard validSuits] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

See how the name of the class appears in the place you'd normally see a pointer to an instance of an object?

It'd probably be instructive to go back and look at the invocation of the `NSString` class method `stringWithFormat:` a few slides ago.

Also, make sure you understand that `stringByAppendingString:` above is not a class method, it is an instance method.

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;
+ (NSArray *)validSuits;

@end
```

The `validSuits` class method might be useful to users of our `PlayingCard` class, so let's make it public.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter

+ (NSArray *)validSuits
{
    return @[@"♥", @"♦", @"♠", @"♣"];
}

- (void)setSuit:(NSString *)suit
{
    if ([[PlayingCard validSuits] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"";
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;
+ (NSArray *)validSuits;

@end
```

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter
+ (NSArray *)validSuits { ... }
- (void)setSuit:(NSString *)suit { ... }
- (NSString *)suit { ... }

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

+ (NSArray *)validSuits;

@end
```

Let's move our other array  
(the strings of the ranks)  
into a class method too.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings =
        return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter
+ (NSArray *)validSuits { ... }
- (void)setSuit:(NSString *)suit { ... }
- (NSString *)suit { ... }

+ (NSArray *)rankStrings
{
    return @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

+ (NSArray *)validSuits;

@end
```

We'll leave this one private because the public API for the rank is purely numeric.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = [PlayingCard rankStrings];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter
+ (NSArray *)validSuits { ... }
- (void)setSuit:(NSString *)suit { ... }
- (NSString *)suit { ... }

+ (NSArray *)rankStrings
{
    return @{@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"};
}

@end
```

And now let's call that class method.

Note that we are not required to declare this earlier in the file than we use it.

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

+ (NSArray *)validSuits;
+ (NSUInteger)maxRank;

@end
```

But here's another class method that might be good to make public.

So we'll add it to the header file.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = [PlayingCard rankStrings];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter
+ (NSArray *)validSuits { ... }
- (void)setSuit:(NSString *)suit { ... }
- (NSString *)suit { ... }

+ (NSArray *)rankStrings
{
    return @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
}

+ (NSUInteger)maxRank { return [[self rankStrings] count]-1; }

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

+ (NSArray *)validSuits;
+ (NSUInteger)maxRank;

@end
```

And, finally, let's use maxRank inside the setter for the rank `@property` to make sure the rank is never set to an improper value.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = [PlayingCard rankStrings];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter
+ (NSArray *)validSuits { ... }
- (void)setSuit:(NSString *)suit { ... }
- (NSString *)suit { ... }

+ (NSArray *)rankStrings
{
    return @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
}

+ (NSUInteger)maxRank { return [[self rankStrings] count]-1; }

- (void)setRank:(NSUInteger)rank
{
    if (rank <= [PlayingCard maxRank]) {
        _rank = rank;
    }
}

@end
```

# Objective-C

## PlayingCard.h

```
#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic)NSUInteger rank;

+ (NSArray *)validSuits;
+ (NSUInteger)maxRank;

@end
```

That's it for our PlayingCard.  
It's a good example of array  
notation, `@synthesize`, class  
methods, and using getters and  
setters for validation.

## PlayingCard.m

```
#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = [PlayingCard rankStrings];
    return [rankStrings[self.rank] stringByAppendingString:self.suit];
}

@synthesize suit = _suit; // because we provide setter AND getter
+ (NSArray *)validSuits { ... }
- (void)setSuit:(NSString *)suit { ... }
- (NSString *)suit { ... }

+ (NSArray *)rankStrings
{
    return @[@"?", @"A", @"2", @"3", ..., @"10", @"J", @"Q", @"K"];
}

+ (NSUInteger)maxRank { return [[self rankStrings] count]-1; }

- (void)setRank:(NSUInteger)rank
{
    if (rank <= [PlayingCard maxRank]) {
        _rank = rank;
    }
}

@end
```

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

Let's look at one last class.  
This one is a subclass of Deck and  
represents a full 52-card deck of  
PlayingCards.

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck

@end
```

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

It appears to have no public API,  
but it is going to override a  
method that Deck inherits from  
NSObject called `init`.

`init` will contain everything  
necessary to initialize a  
PlayingCardDeck.

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck
```

```
@end
```

## PlayingCardDeck.m

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck

- (instancetype)init
{
```

Initialization in Objective-C happens immediately after allocation.

We always nest a call to init around a call to alloc.

e.g. Deck \*myDeck = [[PlayingCardDeck alloc] init]  
or NSMutableArray \*cards = [[NSMutableArray alloc] init]

Classes can have more complicated initializers than just plain “init”  
(e.g. initWithCapacity: or some such).

We’ll talk more about that next week as well.

```
}
```

Only call an init method immediately after calling alloc to make space in the heap for that new object. And never call alloc without immediately calling some init method on the newly allocated object.

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck

- (instancetype)init
{

}

@end
```

Notice this weird “return type” of `instancetype`. It basically tells the compiler that this method returns an object which will be the same type as the object that this message was sent to.

We will pretty much only use it for `init` methods.  
Don’t worry about it too much for now.  
But always use this return type for your `init` methods.

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck

- (instancetype)init
{
    self = [super init];

    if (self) {

    }

    return self;
}

@end
```

This sequence of code might also seem weird.  
Especially an assignment to `self`!

This is the ONLY time you would ever assign something to `self`.  
The idea here is to return `nil` if you cannot initialize this object.  
But we have to check to see if our `super`class can initialize itself.  
The assignment to `self` is a bit of protection against our trying to  
continue to initialize ourselves if our `super`class couldn't initialize.

Just always do this and don't worry about it too much.

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck
@end
```

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck
- (instancetype)init
{
    self = [super init];
    if (self) {

    }
    return self;
}
@end
```

Sending a message to `super` is how we send a message to ourselves, but use our superclass's implementation instead of our own.

Standard object-oriented stuff.

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

The implementation of init is quite simple.  
We'll just iterate through all the suits and  
then through all the ranks in that suit ...

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck

- (instancetype)init
{
    self = [super init];

    if (self) {
        for (NSString *suit in [PlayingCard validSuits]) {
            for (NSUInteger rank = 1; rank <= [PlayingCard maxRank]; rank++) {

            }
        }
    }

    return self;
}

@end
```

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

Then we will allocate and initialize  
a PlayingCard  
and then set its suit and rank.

```
#import "PlayingCardDeck.h"

@implementation PlayingCardDeck

- (instancetype)init
{
    self = [super init];

    if (self) {
        for (NSString *suit in [PlayingCard validSuits]) {
            for (NSUInteger rank = 1; rank <= [PlayingCard maxRank]; rank++) {
                PlayingCard *card = [[PlayingCard alloc] init];
                card.rank = rank;
                card.suit = suit;
            }
        }
    }
    return self;
}

@end
```

We never implemented an `init` method in `PlayingCard`, so it just inherits the one from `NSObject`. Even so, we must always call an `init` method after `alloc`.

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck
@end
```

Then we will allocate and initialize  
a PlayingCard  
and then set its suit and rank.

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"
#import "PlayingCard.h"

@implementation PlayingCardDeck

- (instancetype)init
{
    self = [super init];

    if (self) {
        for (NSString *suit in [PlayingCard validSuits]) {
            for (NSUInteger rank = 1; rank <= [PlayingCard maxRank]; rank++) {
                PlayingCard *card = [[PlayingCard alloc] init];
                card.rank = rank;
                card.suit = suit;
            }
        }
    }
    return self;
}

@end
```

We will need to `#import`  
PlayingCard's header file  
since we are referencing it now  
in our implementation.

We never implemented an `init`  
method in PlayingCard, so it just  
inherits the one from `NSObject`.  
Even so, we must always call an  
`init` method after `alloc`.

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

Finally we just add each PlayingCard  
we create to ourself  
(we are a Deck, remember).

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"
#import "PlayingCard.h"

@implementation PlayingCardDeck

- (instancetype)init
{
    self = [super init];

    if (self) {
        for (NSString *suit in [PlayingCard validSuits]) {
            for (NSUInteger rank = 1; rank <= [PlayingCard maxRank]; rank++) {
                PlayingCard *card = [[PlayingCard alloc] init];
                card.rank = rank;
                card.suit = suit;
                [self addCard:card];
            }
        }
    }
    return self;
}

@end
```

# Objective-C

## PlayingCardDeck.h

```
#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

## PlayingCardDeck.m

```
#import "PlayingCardDeck.h"
#import "PlayingCard.h"

@implementation PlayingCardDeck

- (instancetype)init
{
    self = [super init];

    if (self) {
        for (NSString *suit in [PlayingCard validSuits]) {
            for (NSUInteger rank = 1; rank <= [PlayingCard maxRank]; rank++) {
                PlayingCard *card = [[PlayingCard alloc] init];
                card.rank = rank;
                card.suit = suit;
                [self addCard:card];
            }
        }
    }
    return self;
}

@end
```

And that's it!  
We inherit everything else we need to  
be a Deck of cards  
(like the ability to drawRandomCard)  
from our superclass.

# Demo

- Let's start building a Card Game out of these classes

Today we'll just have a single card that we can flip over to reveal the Ace of clubs.

The following slides are a walkthrough of the demonstration done in class.  
You will need this walkthrough to do your first homework assignment.

Green Bubbles  
are just for  
“information.”

Yellow Bubbles  
mean “do something.”


Red Bubbles  
mean “important!”

Green Bubbles  
with small text is for  
“minor notes.”



Launch Xcode 5 and click here to create a new project.

As you create projects, they will appear here.



These buttons are used to select a template which Xcode 5 uses to generate some code to get you started.

Click on the “Single View Application” template. It creates a simple MVC application.

Then click Next.

Our first application is going to be a Card Matching Game

These fields describe your project. We'll be filling them in during the next few slides.

Choose options for your new project:


Product Name Matchismo  
Organization Name   
Company Identifier   
Bundle Identifier com.yourcompany.Matchismo  
Class Prefix   
Devices Universal


Cancel


No Issues

No Selection

The name of our project is going to be “Matchismo” so type that in here.









Loading

No Issues



Choose options for your new project:

Product Name: Matchismo  
Organization Name: CS193p  
Company Identifier: edu.stanford.cs193p.instructor  
Bundle Identifier: edu.stanford.cs193p.instructor.Matchismo

Class Prefix:  iPad iPhone

Device:  Universal

Cancel Previous Next

No Selection

Set the Device we're developing for to iPhone.

Our first application is going to be for the iPhone (not iPad). At least for starters.

A Universal application runs on both iPhone and iPad. In a Universal application, the iPad and the iPhone each has its own UI design (since they have different UI idioms). Xcode provides tools for designing two different UIs in the same application.

Loading

No Issues

Choose options for your new project:

Product Name Matchismo

Organization Name CS193p

Company Identifier edu.stanford.cs193p.instructor

Bundle Identifier edu.stanford.cs193p.instructor.Matchismo

Class Prefix CardGame

Devices iPhone

Cancel

Previous

Next

No Selection

Then click Next.

Xcode wants to know where to store this project's directory.

Home directory.

“Developer” folder inside the home directory.  
There are no projects in it currently.


We will hopefully be covering source control in this course.  
But not for this first project, so leave this switch turned off.

If you don't have a Developer folder in your home directory, you can create it with this New Folder button.

Navigate to a directory called “Developer” in your home directory (create it if needed).

Then click Create to create your project directory inside ~/Developer.





The Single View Application template we chose at the beginning has created a simple MVC for us.

Our MVC's View is inside Main.storyboard.

CardGameViewController.m is the code for our MVC's Controller.

We'll have to create our MVC's Model ourselves later.

Let's open up and look at our MVC's View by clicking on Main.storyboard.

Don't worry about CardGameAppDelegate.m for this project.

Matchismo.xcodeproj

No Issues

Matchismo

Main.storyboard

CardGameAppDelegate.h

CardGameAppDelegate.m

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

General Capabilities Info Build Phases Build Rules

Identity and Type

Name Matchismo

Location Absolute

Bundle Identifier edu.stanford.cs193p.instructor.Matchismo

Full Path /Users/CS193p/Developer/Matchismo/Matchismo.xcodeproj

Project Document

Project Format Xcode 3.2-compatible

Organization CS193p

Class Prefix CardGame

Text Settings

Indent Using Spaces

Widths Tab 4 Indent 4

Wrap lines

Source Control

Repository --

Type --

Current Branch --


Version --


Status No changes

Location

Stanford CS193p

Fall 2013





Matchismo  
2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files


MatchismoTests

Frameworks

Products

Matchismo > Matchismo > Main.storyboard > Main.storyboard (Base) > No Selection

Card Game View Controller Scene



Identity and Type

Name Main.storyboard

Type Default - Interface Bu...

Location Relative to Group

Base.Iproj/  
Main.storyboard

Full Path /Users/CS193p/  
Developer/Matchismo/  
Matchismo/Base.Iproj/  
Main.storyboard

Interface Builder Document

Opens in Default (5.0)

Builds for Project Deployment T...

View as iOS 7.0 and Later

Use Autolayout

Global Tint Default

Localization

Base

English

Localizable Strings

Target Membership

Matchismo

MatchismoTests

Repository


Type --

Current Branch --

Version --

Status No changes

Fall 2013



Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo iPhone Retina (3.5-inch)

Main.storyboard (Base) No Selection

Identity and Type

- Name Main.storyboard
- Type Default - Interface Bu...
- Location Relative to Group
- Base.lproj/
- Main.storyboard
- Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Base.lproj/Main.storyboard

Interface Builder Document

- Opens in Default (5.0)
- Builds for Project Deployment T...
- View as iOS 7.0 and Later
- Use Autolayout

Card Game View Controller

Drag this bar up (if necessary) to expose the Library Area.

Click here (if necessary) to select the Objects Palette.

Stanford CS193p Fall 2013

This slide is just for reference.  
Don't worry about all these details for now.

**Card Game View Controller**

**File Inspector**  
Shows information about the file containing the selected item.

**Quick Help**  
If the selected item at the left has some documentation reference, this shows a “summary” version of it.

**Media Library** Document  
Images, sounds, etc.

**Object Library**  
Buttons, text fields, controllers, etc.

**File Template Library**  
Templates for storyboards, classes, etc.

**Code Snippet Library**  
Snippets of code for common tasks.

**Class Hierarchy**

**Logs**  
Every time you build/run, a log of it is saved.  
Access old ones here.

**Breakpoints**  
We'll cover the debugger later.

**Threads**  
We'll cover multithreading later too.

**Tests**  
We'll cover Unit Testing later.

**Issues**  
Compiler warnings/errors, etc.

**Search**  
Find/replace in files in your Project.

**Matchismo.xcodeproj — Main.storyboard**  
Matchismo: Ready | Today No Issues

Matchismo  
2 targets, iOS SDK 7.0

Main.storyboard

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

File Inspector

Identity and Type

Name: Main.storyboard

Type: Default - Interface Bu...

Location: Relative to Group

Base.Iproj/

Main.storyboard

/Users/CS193p/

Developer/Matchismo/

Matchismo/Base.Iproj/

Main.storyboard

Logs

Breakpoints

Threads

Tests

Issues

Search

Class Hierarchy

File Inspector

Identity and Type

Builds for: Project Deployment T...

View as: iOS 7.0 and Later

Use Autolayout

Objects

View Controller - A controller that supports the fundamental view-management model in iPhone OS.

Table View Controller - A controller that manages a table view.

Collection View Controller - A controller that manages a collection view.

Navigation Controller - A controller that manages navigation through a hierarchy of views.

Tab Bar Controller - A controller that manages a set of view controllers that represent tab bar items.

Stanford CS193p Winter 2013

Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo > iPhone Retina (3.5-inch)

Main.storyboard (Base) > No Selection

Identity and Type

- Name Main.storyboard
- Type Default - Interface Bu...
- Location Relative to Group
- Base.Iproj/ Main.storyboard
- Full Path /Users/CS193p/ Developer/Matchismo/ Matchismo/Base.Iproj/ Main.storyboard

Interface Builder Document

- Opens in Default (5.0)
- Builds for Project Deployment T...
- View as iOS 7.0 and Later
- Use Autolayout

directly available in Interface...

Label Label - A variably sized amount of static text.

Button Button - Intercepts touch events and sends an action message to a target object when it's tapped.

Segmented Control Segmented Control - Displays multiple segments, each of which functions as a discrete button.

Text Text Field - Displays editable text and sends an action message to a target object when Return...

Slider Slider - Displays a continuous

Stanford CS193p Fall 2013

It's time to start building the user-interface in our MVC View. We're building a card game, so we'll start with our first "card." We'll use a button to represent it.

The Objects Palette contains a bunch of objects you can use to build your View.

Scroll down to find Button.

If you are not seeing Button in the list, try clicking on your View.

Card Game View Controller

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo iPhone Retina (3.5-inch)

Main.storyboard (Base) No Selection

Identity and Type

Name Main.storyboard

Type Default – Interface Bu...

Location Relative to Group

Base.Iproj/  
Main.storyboard

Full Path /Users/CS193p/  
Developer/Matchismo/  
Matchismo/Base.Iproj/  
Main.storyboard

Interface Builder Document

Opens in Default (5.0)

Builds for Project Deployment T...

View as iOS 7.0 and Later

Use Autolayout

directly available in Interface...

Label Label – A variably sized amount of static text.

Button Button – Intercepts touch events and sends an action message to a target object when it's tapped.

Segmented Control Segmented Control – Displays multiple segments, each of which functions as a discrete button.

Text Text Field – Displays editable text and sends an action message to a target object when Return...

Slider Slider – Displays a continuous

Stanford CS193p Fall 2013

Card Game View Controller

Drag a Button from the Object Library to your View.

The screenshot shows the Xcode interface with the project 'Matchismo' selected. The storyboard editor is open, showing a blank white view. A callout bubble with the text 'Drag a Button from the Object Library to your View.' is positioned above the storyboard. A large yellow arrow points from the bottom right towards the storyboard canvas. The 'Object Library' is visible on the right side of the interface, showing various UI components like 'Label', 'Button', 'Segmented Control', 'Text Field', and 'Slider'. The 'Button' item is currently selected. The status bar at the bottom indicates 'Card Game View Controller'.

Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo > iPhone Retina (3.5-inch)

Main.storyboard (Base) > No Selection

Identity and Type

- Name Main.storyboard
- Type Default – Interface Bu...
- Location Relative to Group
- Base.lproj/
- Main.storyboard
- Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Base.lproj/Main.storyboard

Interface Builder Document

- Opens in Default (5.0)
- Builds for Project Deployment T...
- View as iOS 7.0 and Later
- Use Autolayout

directly available in Interface...

Label Label – A variably sized amount of static text.

Button Button – Intercepts touch events and sends an action message to a target object when it's tapped.

Segmented Control Segmented Control – Displays multiple segments, each of which functions as a discrete button.

Text Text Field – Displays editable text and sends an action message to a target object when Return...

Slider Slider – Displays a continuous


Card Game View Controller

Drop the Button into the very center of your View.

Notice the dashed blue lines which Xcode displays as you drag which help you line things up nicely.

Buttons are instances of the class `UIButton` in the iOS SDK.

Stanford CS193p Fall 2013



Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo > iPhone Retina (3.5-inch)

Main.storyboard

Card Game View Controller

Card Game View Controller

View

Button - Button

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

There are all kinds of attributes about the button you can set. We'll do this in a moment.

Drag this back down to make more room for the Attributes.

Button

Type System

State Config Default

Title Plain

Font System 15.0

Text Color Default

Shadow Color Default

Image Default Image

Background Default Background Image

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Drawing Shows Touch On Highlight

directly available in Interface...

Label Label - A variably sized amount of static text.


Button - Intercepts touch events and sends an action message to a target object when it's tapped.

Segmented Control - Displays multiple segments, each of which functions as a discrete button.

Text Text - Displays editable text and sends an action message to a target object when Return...

Slider - Displays a continuous

Stanford CS193p Fall 2013



Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo iPhone Retina (3.5-inch)

Main.storyboard

Card Game View Controller

View

Mode Scale To Fill

Tag 0

Interaction  User Interaction Enabled  
 Multiple Touch

Alpha 1

Background White Color

Tint Default

Drawing  Opaque  Hidden  
 Clears Graphics Context  
 Clip Subviews  
 Autoresizes Subviews

Stretching 0 0

X 1 Y 1

Width 1 Height 1


This is what buttons look like usually in iOS 7.  
Think of them sort of like links in a web page.


We're going to change the look of the button dramatically  
(to look like a card) using images, but that's actually somewhat unusual.


Hopefully the Attributes Inspector now  
shows the attributes of the area which is  
at the root of our MVC's View.

Let's change the Background  
color of the root of our  
MVC's View by clicking here ...

Stanford CS193p  
Fall 2013







Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo

iPhone Retina (3.5-inch)

Matchismo: Ready | Today No Issues

Matchismo

Main.storyboard

Card Game

View

Button - Button

Button

Type System

State Config Default

Title Plain

Font System 15.0

Text Color Default

Shadow Color Default

Image Default Image

Background Default Background Image

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Drawing Shows Touch On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset 0 0

Top Bottom

Left Right

Control

Alignment Horizontal

Vertical

Content Selected Enabled

Highlighted

Stanford CS193p

Fall 2013

Click on the Button again.


You can see the current selection here.


Notice these little white resize handles. Seeing these is another way to know the Button is selected.


The Button's attributes should appear here.

Next we're going to set a background image for the Button (to a blank white card).

A screenshot of the Xcode interface showing the Matchismo project. The storyboard preview shows a green button with a white background and some white resize handles. A callout bubble points to the button with the text "Click on the Button again.". Another callout bubble points to the top right of the screen with the text "You can see the current selection here.". A third callout bubble points to the Attributes Inspector on the right with the text "The Button's attributes should appear here.". A fourth callout bubble points to the bottom bar with the text "Next we're going to set a background image for the Button (to a blank white card.)". A red annotation "Stanford CS193p Fall 2013" is visible in the bottom right corner.







Matchismo.xcodeproj — Images.xcassets

No Issues

Matchismo > iPhone Retina (3.5-inch)

Matchismo > Matchismo > Images.xcassets > stanford

Identity and Type

- Name Images.xcassets
- Type Default - assetcatalog
- Location Relative to Group
- Images.xcassets
- Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Images.xcassets

Target Membership

- Matchismo

stanford

blank card rounded corner

1x 2x

Universal

Images

FAVORITES

- All My Files
- CS193p
- AirDrop
- Documents
- Applications
- Downloads
- Stanford
- Paul
- CS193p

SHARED

DEVICES

Developer Images

blank card hi-res

blank card rounded corner

stanford

stanford tree

Name blank card rounded corner

Kind Portable Network Graphics...

Size 2 KB

Created January 23, 2013 5:24 PM

Modified Yesterday 11:34 AM

Last opened Yesterday 11:34 AM

Dimensions 64 x 96


OSX Lion > Users > CS193p > Images > blank card rounded corner

1 of 4 selected, 221.66 GB available

Show Slicing

Stanford CS193p

Fall 2013



Matchismo.xcodeproj — Images.xcassets

Matchismo: Ready | Today No Issues

Matchismo iPhone Retina (3.5-inch)

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo

Matchismo

Images.xcassets

blank card rounded corner

AppIcon

blank card rounded corner

LaunchImage

stanford

blank card rounded corner

1x 2x

Universal

You may not want the name of the image  
(as referred to in your code)  
to be the same as the name of the file.  
You can simply double-click on it  
and change the name.

Identity and Type

Name Images.xcassets

Type Default - assetcatalog

Location Relative to Group

Images.xcassets

Full Path /Users/CS193p/Developer/  
Matchismo/Matchismo/  
Images.xcassets

Target Membership

Matchismo

MatchismoTests

Source Control

Repository --

Type --

Current Branch --

Version --

Status No changes

Location

Show Slicing

Stanford CS193p

Fall 2013

Matchismo.xcodeproj — Images.xcassets

Matchismo: Ready | Today No Issues

Matchismo > iPhone Retina (3.5-inch)

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo > Matchismo > Images.xcassets > cardfront

AppIcon

cardfront

LaunchImage

stanford

cardfront

1x 2x

Universal

We'll use the name "cardfront" to refer to the button's background when the card is "face up".

Show Slicing

Identity and Type

Name Images.xcassets

Type Default - assetcatalog

Location Relative to Group

Images.xcassets

Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Images.xcassets

Target Membership

Matchismo

MatchismoTests

Source Control

Repository --

Type --

Current Branch --

Version --

Status No changes

Location

Stanford CS193p

Fall 2013

Matchismo.xcodeproj — Images.xcassets

Matchismo: Ready | Today No Issues

Matchismo > iPhone Retina (3.5-inch)

Matchismo

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo > Matchismo > Images.xcassets > stanford

stanford

AppIcon

cardfront

LaunchImage

stanford

S

1x 2x

Universal

We'll change the name of the image on the back of the card from "stanford" to ...

Identity and Type

Name Images.xcassets

Type Default - assetcatalog

Location Relative to Group

Images.xcassets

Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Images.xcassets

Target Membership

Matchismo

MatchismoTests

Source Control

Repository

Type

Current Branch

Version


Status No changes

Location

Show Slicing

Stanford CS193p

Fall 2013



Matchismo.xcodeproj — Images.xcassets

No Issues

Matchismo iPhone Retina (3.5-inch)

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

Items can also be deleted from this list by right clicking on them and choosing Remove.

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo

Matchismo

Images.xcassets

cardback

AppIcon

cardback

cardfront

LaunchImage

cardback

1x

2x

Universal

Identity and Type

Type Default assetcatalog

Location Relative to Group

Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Images.xcassets

Target Membership Matchismo

Drag the higher resolution version into the 2x slot.

Sometimes the Retina version might be able to show more detail.

Showing the tree here is sort of an extreme example just to demonstrate this.

Hi-res Stanford Logo.

These buttons also can be used to add/remove images.

blank card hi-res

blank card rounded corner

stanford

stanford tree

Name stanford tree

Kind Portable Network Graphics...

Size 12 KB

Created Today 2:42 PM

Modified Today 2:49 PM

Last opened Today 4:45 PM

Dimensions 128 x 192

Applications

Downloads

Stanford

Paul

CS193p

Shared

Devices

OSX Lion > Users > CS193p > Images > stanford tree

1 of 4 selected, 221.65 GB available

Show Slicing

Stanford CS193p

Fall 2013

Matchismo.xcodeproj — Images.xcassets

No Issues

Matchismo iPhone Retina (3.5-inch)

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo

Images.xcassets

Matchismo

Images.xcassets

cardback

AppIcon

cardback

cardfront

LaunchImage

cardback

1x 2x

Universal

Identity and Type

Name Images.xcassets

Type Default - assetcatalog

Location Relative to Group

Images.xcassets

Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Images.xcassets

Target Membership

Matchismo

Now you can see both versions.

Images

FAVORITES

All My Files

CS193p

AirDrop

Documents

Applications

Downloads

Stanford

Paul

CS193p

SHARED

DEVICES

Developer

Images

blank card hi-res

blank card rounded corner

stanford

stanford tree

stanford tree

Name stanford tree

Kind Portable Network Graphics...

Size 12 KB

Created Today 2:42 PM

Modified Today 2:49 PM

Last opened Today 4:45 PM

Dimensions 128 x 192

OSX Lion > Users > CS193p > Images > stanford tree

1 of 4 selected, 221.65 GB available

Show Slicing

Stanford CS193p

Fall 2013

Matchismo.xcodeproj — Images.xcassets

No Issues

Matchismo iPhone Retina (3.5-inch)

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo > Matchismo > Images.xcassets > cardfront

cardfront

AppIcon

cardback

cardfront

LaunchImage

blank card hi-res

1x

2x

Universal

Identity and Type

Name Images.xcassets

Type Default - assetcatalog

Location Relative to Group

Images.xcassets

Let's do the same for the hi-res version of the background of the front of the card.

Matchismo

Images

FAVORITES

All My Files

CS193p

AirDrop

Documents

Applications

Downloads

Stanford

Paul

CS193p

SHARED

DEVICES

Developer

Images

blank card hi-res

blank card rounded corner

stanford

stanford tree

Name blank card hi-res

Kind Portable Network Graphics...

Size 1 KB

Created Today 2:42 PM

Modified Today 2:42 PM

Last opened Today 2:42 PM

Dimensions 128 x 192

OSX Lion > Users > CS193p > Images > blank card hi-res

1 of 4 selected, 221.65 GB available

Show Slicing

Stanford CS193p

Fall 2013

Matchismo.xcodeproj — Images.xcassets

Matchismo: Ready | Today No Issues

Matchismo iPhone Retina (3.5-inch)

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo

Matchismo

Images.xcassets

cardfront

AppIcon

cardback

cardfront

LaunchImage

1x 2x

Universal

Identity and Type

Name Images.xcassets

Type Default - assetcatalog

Location Relative to Group

Images.xcassets

Full Path /Users/CS193p/Developer/Matchismo/Matchismo/Images.xcassets

Target Membership

Matchismo

MatchismoTests

Source Control

Repository

Type

Current Branch

Version

Status No changes


Location


It's hard to see these two since they are blank, but they are white "rounded rectangles." You'll be able to see them better in the UI.

Show Slicing

Stanford CS193p

Fall 2013








Matchismo  
2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

If you press and hold on one of the resize handles, you can see the size of the button.



### Button

Type System

State Config Default

Title Plain

Button

Font System 15.0

Text Color Default

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Shows Touch On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset 0 0

Top Bottom

0 0

Left Right

### Control

Alignment

Horizontal


Vertical


Content Selected Enabled


Highlighted


Stanford CS193p

Fall 2013









Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo > iPhone Retina (3.5-inch)

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo: Ready | Today No Issues

Main.storyboard

CardGameViewController.h

CardGameViewController.m

View

Button - Button

Button

Type System

State Config Default

Title Plain

Button

Font System 15.0

Text Color Default

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Drawing Shows Touch On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset 0 0

Top Bottom

Left Right

Control

Alignment Horizontal

Vertical

Content Selected Enabled

Highlighted

Stanford CS193p

Fall 2013

Let's put the A♣ on the card.  
The A is easy ...

A

Matchismo

Main.storyboard

CardGameViewController.h

CardGameViewController.m

View

Button - Button

Button

Type System

State Config Default

Title Plain

Button

Font System 15.0

Text Color Default

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Drawing Shows Touch On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset 0 0

Top Bottom

Left Right

Control

Alignment Horizontal


Vertical

Content Selected Enabled

Highlighted

Stanford CS193p

Fall 2013



Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo iPhone Retina (3.5-inch)

Main.storyboard

A button can show different attributes in different states.  
We're going to only set Default attributes.  
The Default attributes are what will show in any button state  
that does not have specific attributes set.

This is not quite what we want.  
We want a little bigger font and for  
the A to be black, not blue.

Button

Type System

State Conf ✓ Default

Title

- Highlighted
- Selected
- Disabled

Font System 15.0

Text Color Default

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Shows Touch On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset Top 0 Bottom 0

Left 0 Right 0

Control

Alignment Horizontal


Vertical

Content Selected Enabled

Highlighted

Stanford CS193p

Fall 2013




We can fix the font size by clicking this little button ...

The size has been bumped up to 24 point from 15 point.

ghlighted Stanford CS193p

Fall 2013



Matchismo.xcodeproj — Main.storyboard

Matchismo: Ready | Today No Issues

Matchismo iPhone Retina (3.5-inch)

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

View

Button - A♣

Button

Type System

State Config Default

Title Plain

A♣

Custom

System

Font System

Family System

Style System

Size System

Text Styles

Body

Caption 1

Caption 2

Footnote

Headline

Subhead

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset 0 0

Top 0 Bottom 0

Left 0 Right 0

Control

Alignment Horizontal

Vertical

Content Selected Enabled

Highlighted


Stanford CS193p


Fall 2013

... and then change the font, it's family or style, and size.

We'll leave this set to the System font for now.

Typography is crucially important to iOS 7 user-interface design. We'll talk about that (especially these Text Styles) later in the course.





Matchismo.xcodeproj — Main.storyboard

Building Matchismo: Matchismo | Linking No Issues

Matchismo iPhone Retina (3.5-inch)

Main.storyboard

Card Game View Controller

Card Game View Controller

View

Button - A♣

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

As the application is built, you'll see status here.

Button

Type: System

State Config: Default

Title: Plain

Image: A♣

Font: System 24.0

Text Color: Black Color

Shadow Color: Default

Background: cardfront

Shadow Offset: 0.0 0.0

Width: 0.0 Height: 0.0

Reverses On Highlight:

Drawing: Shows Touch On Highlight:

Highlighted Adjusts Image:

Disabled Adjusts Image:

Line Break: Truncate Middle

Edge: Content

Inset: 0 0

Top: 0 Bottom: 0

Left: 0 Right: 0

Control

Alignment: Horizontal

Vertical

Content: Selected:  Enabled:

Highlighted:

Stanford CS193p Fall 2013


File


Editor


View


Search

Help












And swipe over to see (and run)  
other applications.

You can swipe back and click on your application  
(Matchismo) to get back to debugging it.







When an MVC View is showing,  
the Assistant Editor will bring up  
the code for the corresponding  
MVC Controller.  
That's exactly what we want.

Click here to show the Assistant Editor.

This is the code for our MVC's Controller.  
So far it's just some stubs created by Xcode  
based on the template we chose at the start.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
  
@end  
  
@implementation CardGameViewController  
  
- (void)viewDidLoad  
{  
    [super viewDidLoad];  
    // Do any additional setup after loading the view, typically from a nib.}  
  
- (void)didReceiveMemoryWarning  
{  
    [super didReceiveMemoryWarning];  
    // Dispose of any resources that can be recreated.}  
  
@end
```

You can adjust the space between the two panes of the editor by just dragging the space between them.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Main.storyboard CardGameViewController.h CardGameViewController.m

CardGameAppDelegate.h CardGameAppDelegate.m

Supporting Files Images.xcassets

MatchismoTests Frameworks Products

A card with the value 'A' and a club symbol is displayed on the storyboard.

//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
  
@end  
  
@implementation CardGameViewController  
  
- (void)viewDidLoad  
{  
 [super viewDidLoad];  
 // Do any additional setup after loading the view, typically from a nib.  
}  
  
- (void)didReceiveMemoryWarning  
{  
 [super didReceiveMemoryWarning];  
 // Dispose of any resources that can be recreated.  
}  
  
@end

If you want to edit the header file of the Controller (to make something public for example), you can switch it here.

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.h > No Selection

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files

MatchismoTests

Frameworks

Products


```
// CardGameViewController.h
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.
//
#import <UIKit/UIKit.h>

@interface CardGameViewController : UIViewController

@end
```

All Controllers inherit from UIViewController.

Switch back to the Controller's implementation.



These two methods are part of the View Controller Lifecycle.

We'll talk about that in-depth next week.

For now, we're not going to use them.

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.
```

```
#import "CardGameViewController.h"
```

```
@interface CardGameViewController : UIViewController
```

```
@end
```

```
@implementation CardGameViewController
```

```
- (void)viewDidLoad
```


```
{  
    [super viewDidLoad];  
    // Do any additional setup after loading the view, typically from a nib.  
}
```


```
- (void)didReceiveMemoryWarning
```


```
{  
    [super didReceiveMemoryWarning];  
    // Dispose of any resources that can be recreated.  
}
```

```
@end
```

Select all of the code inside the **@implementation** block ...












Matchismo  
2 targets, iOS SDK 7.0  
Matchismo  
CardGameAppDelegate.h  
CardGameAppDelegate.m  
Main.storyboard  
CardGameViewController.h  
CardGameViewController.m  
Images.xcassets  
Supporting Files  
MatchismoTests  
Frameworks  
Products



```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
@end
```

Let's name this action method touchCardBody.



Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

Main.storyboard

Action

Object: Card Game View Co...

Name: touchCardBody

Type: id

Event: UIButton

Arguments: Sender

Cancel Connect

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
@end
```

We know that the sender of this action is a **UIButton**. If this action could be sent from objects of another class (e.g. a **UISlider**), we could leave the type “**id**” (which means an object of any (unknown) class).

Specifying that we know the class of the sender makes it easier for the compiler to check that the code in our action method is not faulty.

We'll talk more about this type **id** next week.

Stanford CS193p Fall 2013

Matchismo  
2 targets, iOS SDK 7.0


Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files

MatchismoTests

Frameworks

Products



```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
@end  
  
@implementation CardGameViewController  
@end
```

Make sure it says UIButton here.

```
//
// CardGameViewController.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.
```

```
#import "CardGameViewController.h"
```

```
@interface CardGameViewController ()
```


@end

```
@implementation CardGameViewController
```

@end

Action methods are allowed to have either no arguments,  
one argument (the object sending the message),  
or even two arguments

(the sender and the touch event provoking the action). In this case, though, what we want is just the sending button so that we can change it when it is touched.





Main.storyboard

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
@end
```

Card Game View Co... touchCardButton UIButton Touch Up Inside Sender

Cancel Connect

Once you've set up the action as shown, click Connect to create the action method.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

Main.storyboard

```
// CardGameViewController.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "CardGameViewController.h"

@interface CardGameViewController : UIViewController

@end

@implementation CardGameViewController

- (IBAction)touchCardButton:(UIButton *)sender
{
    NSLog(@"Button tapped!");
}


@end
```

The only argument to this method is the object that is sending the message to us ("us" is the Controller). In the previous slide, we made it clear that it is a button, so that's why the type of this argument is `UIButton` (instead of `id`).

The name of this method is actually `touchCardButton:`, not `touchCardButton`.

This method's return type is actually `void`, but Xcode uses the typedef `IBAction` instead just so that Xcode can keep track that this is not just a random method that returns `void`, but rather, it's an action method.

Apart from that, `IBAction` is exactly the same thing as `void`.



Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Our implementation of this method is quite simple.  
We're just going to change the text on the button to be blank  
and change the background image to be our card back  
(the Stanford logo), thus “flipping the card over to its back.”

```
// CardGameViewController.m
// Copyright (c) 2013 Stanford University.
#import "CardGameViewController.h"

@interface CardGameViewController : UIViewController
@end

@implementation CardGameViewController
- (IBAction)touchCardButton:(UIButton *)sender
{
    UIImage *cardImage =
}
@end
```

Let's start by declaring a *local variable* called `cardImage` to hold the cardback image (the Stanford logo we imported). The local variable is a pointer to an instance of the class `UIImage` which represents a JPEG, PNG, TIFF or other image.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

Uh-oh, a warning!

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];  
}  
@end
```

Remember that @"" notation just creates an NSString object.

UIImage has a *class method* called imageNamed: which creates an instance of UIImage given the name of an image in the image assets library. We just specify cardback (what we called the Stanford logo in the assets library).

Stanford CS193p  
Fall 2013

Xcode is constantly parsing your code in the background.  
Thus, warnings and errors will appear in this gutter without  
your having to explicitly build your project.

```
#import "CardGameViewController.h"

@interface CardGameViewController : UIViewController

@end


@implementation CardGameViewController

- (IBAction)touchCardButton:(UIButton *)sender
{
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];
}

@end
```

To get more details about a warning or error, click on the triangle.

This warning is correct (we are not using the local variable cardImage yet), but nothing to worry about since we'll be using it in a moment.



Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) ! 1

Automatic > CardGameViewController.m -touchCardButton:

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A card with the letter A and a spade symbol is displayed on the storyboard.

... then the name of the message with the arguments interspersed ...

We only have to type the first few letters of the message and Xcode will immediately suggest matching method names.

```
//  
// CardGameViewController.m  
// Matchismo  
// Copyright (c) 2013 Stanford University.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];  
    [sender setBackgroundImage:(UIImage *) forState:(UIControlState)]  
}  
M void setBackgroundColor:(UIColor *)  
@end M void setBackgroundImage:(UIImage *) forState:(UIControlState)  
M void setBounds:(CGRect)  
  
Sets the background image to use for the specified button state. More...
```

Type setB and then choose the method setBackgroundImage:forState: from the list that appears.

You can select from the list using the arrow keys and then TAB or you can double-click on the method you want.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files

MatchismoTests

Frameworks

Products

The screenshot shows the Xcode interface with the Main.storyboard file selected in the project navigator. The storyboard preview window displays a single button with the text "A ♠". The code editor window shows the implementation of the CardGameViewController. A callout bubble points to the line of code where a local variable "cardImage" is assigned from a UIImage imageNamed:@"cardback".

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];  
    [sender setBackgroundImage:(UIImage *) forState:(UIControlState)]  
}  
@end
```

After choosing the method you want, it should fill that method in and highlight the first argument. This argument is obviously the image to set as the background of the UIButton.

For us, that's the cardImage local variable.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) ! 1

Automatic > CardGameViewController.m -touchCardButton:

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A card labeled "A ♠" is displayed on the iPhone Retina (3.5-inch) simulator screen.

//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
//

Again, you need only type a couple of characters before Xcode will suggest what you want.

Then double-click on the list or hit TAB once the one you want is selected.

```
#import "CardGameViewController.h"

@interface CardGameViewController : UIViewController

@end

@implementation CardGameViewController

- (IBAction)touchCardButton:(UIButton *)sender
{
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];
    [sender setBackgroundImage:cardImage forState:(UIControlState)CALLBACK_API_C_STDCALL(_type, _name)]
    CALLBACK_API_C_STDCALL(_type, _name)
    CALLBACK_API_STDCALL(_type, _name)
    void * calloc(size_t, size_t)
    V UIImage * cardImage
    # CAST_USER_ADDR_T(a_ptr)
    f CATransform3D CATransform3DConcat(CATransform3D a, CATransform3D b)
    f bool CATransform3DEqualToTransform(CATransform3D a, CATransform3D b)
    CCAffineTransform CATransform2DGetAffineTransform(CATransform2D +)
```

Notice that there are LOTS of things that start with the two letters "ca", but that Xcode is pretty smart about guessing which one you intend based on context.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Matchismo 2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A Ace of Spades card image

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];  
    [sender setBackgroundImage:cardImage forState:UIControlStateNormal];  
}  
  
@end
```

The `setBackgroundImage:forState:` method asks for the state because you can set different background images for selected, highlighted or disabled states of the `UIButton`.

We're just going to set the background for the default (Normal) state so it will be that way in all button states.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A♣

```
//  
// CardGameViewController.m  
// Matchismo  
//  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];  
    [sender setBackgroundImage:cardImage forState:UIControlStateNormal]  
}  
  
@end
```

enum UIControlEvents UIControlEventTouchUpInside  
enum UIControlEvents UIControlEventValueChanged  
enum UIControlState UIControlStateApplication  
enum UIControlState UIControlStateDisabled  
enum UIControlState UIControlStateHighlighted  
enum UIControlState UIControlStateNormal  
enum UIControlState UIControlStateReserved  
enum UIControlState UIControlStateSelected

Start typing UIC and you'll get close to what we want (UIControlStateNormal) ...

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m


Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products



A screenshot of an iPhone Retina (3.5-inch) simulator displaying a single playing card, the Ace of Spades, centered on a green background. The card has a light blue back and the letter 'A' with a spade symbol in the center.

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];  
    [sender setBackgroundImage:cardImage forState:UIControlStateNormal]  
}  
  
@end
```

enum UIControlEvents UIControlEventTouchUpInside  
enum UIControlEvents UIControlEventValueChanged  
enum UIControlState UIControlStateApplication  
enum UIControlState UIControlStateDisabled  
enum UIControlState UIControlStateHighlighted  
enum UIControlState UIControlStateNormal  
enum UIControlState UIControlStateReserved  
enum UIControlState UIControlStateSelected

Now choose UIControlStateNormal.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A♣

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = [UIImage imageNamed:@"cardback"];  
    [sender setBackgroundImage:cardImage forState:UIControlStateNormal];  
}  
  
@end
```

Easy!

But we don't actually need this local variable.  
We can just embed that message-send in-line.

So select this message send ...

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A♣

```
//  
// CardGameViewController.m  
// Matchismo  
//  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = ;  
    [sender setBackgroundImage:cardImage forState:UIControlStateNormal];  
}  
  
@end
```

... cut it ...

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A♣

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = ;  
    [sender setBackgroundImage:cardImage forState:UIControlStateNormal];  
}  
@end
```

... select the variable here ...

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = ;  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"] forState:  
        UIControlStateNormal];  
}  
@end
```

... and paste.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Automatic CardGameViewController.m -touchCardButton:

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    UIImage *cardImage = ;  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"] forState:  
        UIControlStateNormal];  
}  
@end
```

Now we can select this line ...

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A♣

... and hit delete to get rid of it.

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"] forState:  
    UIControlStateNormal];  
}  
  
@end
```

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A♣

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"] forState:  
    UIControlStateNormal];  
}  
@end
```

This line of code is so long  
that it is wrapping now.  
And not really in a great spot.

Put your cursor here ...

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
        forState:UIControlStateNormal];  
}  
@end
```

... and press the return key.

Notice that Xcode lined up the two colons in the message name!

You should always line up the colons when you manually wrap the arguments of a method (in other words, don't undo what Xcode will do for you).

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files

MatchismoTests

Frameworks


Products

iPhone Retina (3.5-inch)

//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
@interface CardGameViewController : UIViewController  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton \*)sender  
{  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
 forState:UIControlStateNormal];  
 [sender setTitle: (NSString \*) forState: (UIControlState)]  
}  
  
@end

To “flip the card over” not only do we need to set the background image to the Stanford logo, we need to get rid of the A♣.

Send the message `setTitle:forState:` to the `UIButton` ...



Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
        forState:UIControlStateNormal];  
    [sender setTitle:@"" forState:UIControlStateNormal];  
}  
  
@end
```

... with an empty string as the title.

Forgetting the @ before the "" is a very common coding error.  
"" without the @ is a const char \*.  
const char \*, while legal, is almost never used in Objective-C.

Matchismo

2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A club card (Ace of Spades) is displayed on the iPhone Retina (3.5-inch) simulator screen.

Navigation bar icons: Stop, Back, Forward, Home, Refresh, Stop, Refresh, Stop, Refresh.

Search bar icons: Search, Equals, Search.

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
     forState:UIControlStateNormal];  
    [sender setTitle:@"" forState:UIControlStateNormal];  
}  
@end
```

Again, we specify that we are setting this title for the default (Normal) button state.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Matchismo

Carrier

Let's run again!


Starts out the same as before ...

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
        forState:UIControlStateNormal];  
    [sender setTitle:@"" forState:UIControlStateNormal];  
}  
  
@end
```

No Selection

Auto All Output


Stanford CS193p Fall 2013




...but now when you touch the button,  
it “flips the card over.”

Unfortunately, if you touch it again, it doesn't flip back!  
Let's fix that.

```
//  
// CardGameViewController.m  
// Matchismo  
//  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
    touch the button,  
    card over.”  
    @implementation CardGameViewController  
  
    - (IBAction)touchCardButton:(UIButton *)sender  
    {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    }  
}
```





```
//  
// CardGameViewController.m  
// Matchismo  
//  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
//
```

```
#import "CardGameViewController.h"  
If the sending button's current
```

@end

```
@implementation CardGameViewController
```

```
    if (sender.currentTitle)
```

AttributedString \* currentAttributedString;

`UIImage * currentBackgroundImage`

`UIImage * currentImage`

**NSString \* currentTitle**

UIColors \* *suspectTitleColor*

**Color \*** currentlittlecolor

```
UIColor * currentTitleShadowColor
```

current title that is displayed on the button. (read-more...)

Notice that `currentTitle` is a `@property` of the button, so we are using dot notation here.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) 1

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A♣

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
{  
    ...  
}  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if (sender.currentTitle.length)  
        [sender setEnabled:NO];  
    else  
        [sender setEnabled:YES];  
}  
  
@end
```

NSUInteger length

NSUInteger lengthOfBytesUsingEncoding:(NSStringEncoding)

Returns the number of Unicode characters in the receiver. [More...](#)

Checking the length of an `NSString` to see if it is blank is cool because it works whether the string is the empty string (i.e. `@""`) or is `nil`.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks


Products

A♣

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length])  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
    [sender setTitle:@"" forState:UIControlStateNormal];  
}  
@end
```

... (note that we don't have to type the [, since Xcode automatically adds it when we type ]) ...

Stanford CS193p  
Fall 2013



```
//  
//  CardGameViewController.m  
//  Matchismo  
//  
//  Created by CS193p Instructor.  
//  Copyright (c) 2013 Stanford University.  
//  All rights reserved.  
  
#import "CardGameViewController.h"  
... is non-zero (front is showing), then ...  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    }  
    @end
```

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks


Products

A♣


```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
    }  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
        forState:UIControlStateNormal];  
    [sender setTitle:@"" forState:UIControlStateNormal];  
}  
  
@end
```

Move this code inside  
the curly braces.

Stanford CS193p  
Fall 2013



```
//  
//  CardGameViewController.m  
//  Matchismo  
//  
//  Created by CS193p Instructor.  
//  Copyright (c) 2013 Stanford University.  
//  All rights reserved.  
  
#import "CardGameViewController.h"  
... flip the card over to show it's back ...  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    }  
}  
@end
```



```
//  
//  CardGameViewController.m  
//  Matchismo  
//  
//  Created by CS193p Instructor.  
//  Copyright (c) 2013 Stanford University.  
//  All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
    }  
}  
@end
```

Copy/paste this code into the else ...

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files

MatchismoTests


Frameworks

Products

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
}  
}  
@end
```

... and change cardback to cardfront ...

Stanford CS193p  
Fall 2013



```
//  
//  CardGameViewController.m  
//  Matchismo  
//  
//  Created by CS193p Instructor.  
//  Copyright (c) 2013 Stanford University.  
//  All rights reserved.  
  
#import "CardGameViewController.h"  
... flip back over to the A♣ (the front).  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
@end
```

... and change @"" to @"A♣".

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

Now let's Run again ...

```
//  
// CardGameViewController.m  
// Matchismo  
//  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
@end
```

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Matchismo

Carrier

Touch once ...


A ♣


```
//  
// CardGameViewController.m  
// Matchismo  
//  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

No Selection

Auto All Output

Stanford CS193p Fall 2013





Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

Stop!

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193P Instructors  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

Let's take a little timeout to talk about documentation.

There are numerous ways to transition to the documentation, but an easy one is to use the ALT key.

Hold down the ALT key and hover your mouse over something like currentTitle.

A dashed line should appear underneath and the cursor should be a question mark.

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic > CardGameViewController.m -touchCardButton:

Main.storyboard

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

A Club

//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
**@interface CardGameViewController ()**  
  
**@end**  
  
**@implementation CardGameViewController**  
  
**- (IBAction)touchCardButton:(UIButton \*)sender**  
**{**  
    **if ([sender.currentTitle length]) {**  
        **[sender setBackgroundImage:[UIImage imageNamed:@"cardback"]**  
        **];**  
    **}[sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]**  
    **];**  
}

Declaration @property(nonatomic, readonly, retain) NSString \* currentTitle

Description The current title that is displayed on the button. (read-only)  
The value for this property is set automatically whenever the button state changes. For states that do not have a custom title string associated with them, this method returns the title that is currently displayed, which is typically the one associated with the UIControlStateNormal state. The value may be nil.

Availability iOS (2.0 and later)

Declared In UIButton.h

Reference UIButton Class Reference

ALT-clicking on `currentTitle` will bring up this “mini-documentation” in-line.

retain is the same as strong.  
We'll cover the `readonly` directive next lecture.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard


Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

TIP: If you ever accidentally navigate away from your source code, you can click on this back button to get back.



Automatic > CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController : UIViewController  
{  
    @end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
    }  
}
```

Click on the [UIButton Class Reference](#) link in this little “mini-documentation” window to get more detailed documentation.

You can also hold down the ALT key and double-click on a term go directly to the documentation.

Declaration @property(nonatomic, readonly, retain) NSString \* currentTitle


Description The current title that is displayed on the button. (read-only)  
The value for this property is set automatically whenever the button state changes. For states that do not have a custom title string associated with them, this method returns the title that is currently displayed, which is typically the one associated with the UIControlStateNormal state. The value may be nil.

Availability iOS (2.0 and later)

Declared In UIButton.h

Reference [UIButton Class Reference](#)

Stanford CS193p Fall 2013



## Overview

This is the Documentation window.

**Important:** This is a preliminary document for an API or technology in development. Although this document has been reviewed for technical accuracy, it is not final. This Apple confidential information is for use only by registered members of the applicable Apple Developer program. Apple is supplying this confidential information to help you plan for the adoption of the technologies and programming interfaces described herein. This information is subject to change, and software implemented according to this document should be tested with final operating system software and final documentation. Newer versions of this document may be provided with future seeds of the API or technology.

An instance of the `UIButton` class implements a button on the touch screen. A button intercepts touch events and sends an action message to a target object when tapped. Methods for setting the target and action are inherited from `UIControl`. This class provides methods for setting the title, image, and other appearance properties of a button. By using these accessors, you can specify a different appearance for each button state.

For information about basic view behaviors, see [View Programming Guide for iOS](#).

For more information about appearance and behavior configuration, see "Buttons".

## Tasks

### Creating Buttons

+ `buttonWithType:`

### Configuring the Button Title

`titleLabel` *property*

`reversesTitleShadowWhenHighlighted` *property*

- `setTitle:forState:`

- `setAttributedTitle:forState:`

- `setTitleColor:forState:`

- `setTitleShadowColor:forState:`

- `titleColorForState:`

- `titleForState:`

- `attributedTitleForState:`

- `titleShadowColorForState:`

### Configuring Button Presentation

You should explore what is here.

It is substantial.

Being able to maneuver through the documentation is critical to success in  
iOS Development.

Provide Feedback

<b>UIButton Class Reference</b>	
<b>Overview</b>	
Tasks	
Creating Buttons	Configuring the Button Title
Configuring Button Presentation	Configuring Edge Insets
Getting the Current State	Getting Dimensions
Deprecated Properties	
Properties	
<code>adjustsImageWhenDisabled</code>	<code>adjustsImageWhenHighlighted</code>
<code>buttonType</code>	<code>contentEdgeInsets</code>
<code>currentAttributedTitle</code>	<code>currentBackgroundImage</code>
<code>currentImage</code>	<code>currentTitle</code>
<code>currentTitleColor</code>	<code>currentTitleShadowColor</code>
<code>imageEdgeInsets</code>	<code>imageView</code>
<code>reversesTitleShadowWhenHighlighted</code>	<code>reversesTitleShadowWhenHighlighted</code>
<code>showsTouchWhenHighlighted</code>	<code>tintColor</code>
<code>tintColor</code>	<code>titleEdgeInsets</code>
<code>titleLabel</code>	<code>titleLabel</code>
Class Methods	
<code>buttonWithType:</code>	
Instance Methods	
<code>attributedTitleForState:</code>	<code>backgroundImageForState:</code>
<code>backgroundImageForState:</code>	<code>backgroundRectForBounds:</code>
<code>backgroundRectForBounds:</code>	<code>contentRectForBounds:</code>
<code>contentRectForBounds:</code>	<code>imageForState:</code>

Search documentation

Available in iOS 6.0 and later.

**Declared In**

UIButton.h

**setBackgroundImage:forState:**

Sets the background image to use for the specified button state.

```
- (void)setBackgroundImage:(UIImage *)image forState:(UIControlState)state
```

**Parameters***image*

The background image to use for the specified state.

*state*

The state that uses the specified image. The values are described in UIControlState.

**Discussion**

In general, if a property is not specified for a state, the default is to use the UIControlStateNormal value. If the UIControlStateNormal value is not set, then the property defaults to a system value. Therefore, at a minimum, you should set the value for the normal state.

**Availability**

Available in iOS 2.0 and later.

**See Also**[- backgroundImageForState:](#)**Related Sample Code**[Accessory](#)[AddMusic](#)[UICatalog](#)**Declared In**

UIButton.h

**setImage:forState:**

Sets the image to use for the specified state.

```
- (void)setImage:(UIImage *)image forState:(UIControlState)state
```

**Parameters**

For example, scroll down to  
setBackgroundImage:forState:.

[Provide Feedback](#)

	UIButton Class Reference
Overview	
Tasks	
Creating Buttons	
Configuring the Button Title	
Configuring Button Presentation	
Configuring Edge Insets	
Getting the Current State	
Getting Dimensions	
Deprecated Properties	
Properties	
adjustsImageWhenDisabled	
adjustsImageWhenHighlighted	
buttonType	
contentEdgeInsets	
currentAttributedTitle	
currentBackgroundImage	
currentImage	
currentTitle	
currentTitleColor	
currentTitleShadowColor	
imageEdgeInsets	
imageView	
reversesTitleShadowWhenHighlighted	
showsTouchWhenHighlighted	
tintColor	
titleEdgeInsets	
titleLabel	
Class Methods	
buttonWithType:	
Instance Methods	
attributedTitleForState:	
backgroundImageForState:	
backgroundRectForBounds:	
contentRectForBounds:	
imageForState:	

# UIImage Class Reference

[Next](#)

And get detailed class overviews.

## Overview

**Important:** This is a preliminary document for an API or technology in development. Although this document has been reviewed for technical accuracy, it is not final. This Apple confidential information is for use only by registered members of the applicable Apple Developer program. Apple is supplying this confidential information to help you plan for the adoption of the technologies and programming interfaces described herein. This information is subject to change, and software implemented according to this document should be tested with final operating system software and final documentation. Newer versions of this document may be provided with future seeds of the API or technology.

A `UIImage` object is a high-level way to display image data. You can create images from files, from Quartz image objects, or from raw image data you receive. The `UIImage` class also offers several options for drawing images to the current graphics context using different blend modes and opacity values.

Image objects are immutable, so you cannot change their properties after creation. This means that you generally specify an image's properties at initialization time or rely on the image's metadata to provide the property value. It also means that image objects are themselves safe to use from any thread. The way you change the properties of an existing image object is to use one of the available convenience methods to create a copy of the image but with the custom value you want.

Because image objects are immutable, they also do not provide direct access to their underlying image data. However, you can get an `NSData` object containing either a PNG or JPEG representation of the image data using the `UIImagePNGRepresentation` and `UIImageJPEGRepresentation` functions.

The system uses image objects to represent still pictures taken with the camera on supported devices. To take a picture, use the `UIImagePickerController` class. To save a picture to the Saved Photos album, use the `UIImageWriteToSavedPhotosAlbum` function.

## Images and Memory Management

In low-memory situations, image data may be purged from a `UIImage` object to free up memory on the system. This purging behavior affects only the image data stored internally by the `UIImage` object and not the object itself. When you attempt to draw an image whose data has been purged, the image object automatically reloads the data from its original file. This extra load step, however, may incur a small performance penalty.

You should avoid creating `UIImage` objects that are greater than 1024 x 1024 in size. Besides the large amount of memory such an image would consume, you may run into problems when using the image as a texture in OpenGL ES or when drawing the image to a view or layer. This size restriction does not apply if you are performing code-based manipulations, such as resizing an image larger than 1024 x 1024 pixels by d to a bitmap-backed graphics context. In fact, you may need to resize an image in this manner (or break it into several smaller images) in order to

## UIImage Class Reference

### Overview

Images and Memory Management

Supported Image Formats

### Tasks

Cached Image Loading Routines

Creating New Images

Initializing Images

Image Attributes

Drawing Images

### Properties

alignmentRectInsets

capInsets

CGImage

CIImage

duration

imageOrientation

images

renderingMode

resizingMode

scale

size

### Class Methods

animatedImageNamed:duration:

animatedImageWithImages:duration:

animatedResizableImageNamed:ca...

animatedResizableImageNamed:ca...

imageNamed:

imageWithCGImage:

imageWithCGImage:scale:orientation:

imageWithCIImage:

imageWithCIImage:scale:orientation:

imageWithContentsOfFile:

imageWithData:Stanford CS193p

imageWithData:scale:Fall 2013

### Instance Methods

Provide Feedback

 **NSString**

Top Hit

**NSString**

API Reference

[Appendix A: Deprecated NSString Methods](#)[NSString Class Reference](#)[Appendix A: Deprecated NSString UIKit Additions Methods](#)[NSString UIKit Additions Reference](#)[CFStringConvertEncodingToNSStringEncoding](#)[CFStringConvertNSStringEncodingToEncoding](#)**NSString**

SDK Guides

[NSString](#)[Appendix A: Old-Style ASCII Property...](#)[Strings Are Represented by Instances of the NSString Class](#)[Objects Can Represent Primitive Values](#)[NSString from C Strings and Data](#)[Creating Strings](#)[Technical Q&A QA1235](#)[Converting to Precomposed Unicode](#)

Sample Code

[Birthdays](#)[IDEs](#)[LLDBCustomDataFormatter](#)[Languages & Utilities](#)[Show All Results](#)

## Supported

Table 1 lists the

## Table 1 Supported

### Format

### Tagged Image

### Joint Photogr...

### Graphic Inter...

### Portable Netw...

### Windows Bitm...

### Windows Icon

### Windows Cursor

.cur

### XWindow bitmap

.xbm

You can also search for classes, methods,  
or just general topics of interest.

**Note:** Windows Bitmap Format (BMP) files that are formatted as RGB-565 are converted to ARGB-1555 when they are loaded.

## Tasks


### Cached Image Loading Routines

[+ imageNamed:](#)

### Creating New Images

[+ imageWithContentsOfFile:](#)[Provide Feedback](#)

 <a href="#">UIImage Class Reference</a>
 <a href="#">Overview</a>
<a href="#">Images and Memory Management</a>
<a href="#">Supported Image Formats</a>
 <a href="#">Tasks</a>
<a href="#">Cached Image Loading Routines</a>
<a href="#">Creating New Images</a>
<a href="#">Initializing Images</a>
<a href="#">Image Attributes</a>
<a href="#">Drawing Images</a>
 <a href="#">Properties</a>
<a href="#">alignmentRectInsets</a>
<a href="#">capInsets</a>
<a href="#">CGImage</a>
<a href="#">CILImage</a>
<a href="#">duration</a>
<a href="#">imageOrientation</a>
<a href="#">images</a>
<a href="#">renderingMode</a>
<a href="#">resizingMode</a>
<a href="#">scale</a>
<a href="#">size</a>
 <a href="#">Class Methods</a>
<a href="#">animatedImageNamed:duration:</a>
<a href="#">animatedImageWithImages:duration:</a>
<a href="#">animatedResizableImageNamed:ca...</a>
<a href="#">animatedResizableImageNamed:ca...</a>
<a href="#">imageNamed:</a>
<a href="#">imageWithCGImage:</a>
<a href="#">imageWithCGImage:scale:orientation:</a>
<a href="#">imageWithCILImage:</a>
<a href="#">imageWithCILImage:scale:orientation:</a>
<a href="#">imageWithContentsOfFile:</a>
<a href="#">imageWithData:<span style="color:red">Stanford CS193p</span></a>
<a href="#">imageWithData:scale:<span style="color:red">Fall 2013</span></a>
 <a href="#">Instance Methods</a>



//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Team on 10/1/13.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
//  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()

@end


@implementation CardGameViewController

- (IBAction)touchCardButton:(UIButton \*)sender

{  
 if ([sender.currentTitle length]) {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"" forState:UIControlStateNormal];  
 } else {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"A♣" forState:UIControlStateNormal];  
 }  
}

@end

Hide the Navigator ...



```
//  
//  CardGameViewController.m  
//  Matchismo  
//  
//  Created by CS193p Instructor.  
//  Copyright (c) 2013 Stanford University.  
//  All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                             forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                             forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

... and bring back the Utilities area.

**Button**

Type System

State Config Default

Title Plain

A♣

Font System 24.0

Text Color Black Color

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset 0 0

Top Bottom

Left Right

**Control**


Alignment Horizontal

Vertical

Content Selected Enabled

Highlighted

Matchismo &gt; iPhone Retina (3.5-inch)



Automatic &gt; CardGameViewController.m &gt; -touchCardButton:



```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length] == 0){  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
  
@end
```



And bring back the Object Palette by dragging this bar up from the bottom.

<b>Button</b>
Type System
State Config Default
Title Plain
A♣
Font System 24.0
Text Color Black Color
Shadow Color Default
Image Default Image
Background cardfront
Shadow Offset 0.0 0.0
Width Height
<input type="checkbox"/> Reverses On Highlight
<input type="checkbox"/> Shows Touch On Highlight
{ }
directly available in Interface...
<b>Label</b> Label - A variably sized amount of static text.
<b>Button</b> Button - Intercepts touch events and sends an action message to a target object when it's tapped.
<b>Segmented Control</b> Segmented Control - Displays multiple segments, each of which functions as a discrete button.
<b>Text</b> Text Field - Displays editable text and sends an action message to a target object when Return... is pressed.
<b>Slider</b> Slider - Displays a continuous

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
// CardGameViewController.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.

#import "CardGameViewController.h"

@interface CardGameViewController : UIViewController
@end

@implementation CardGameViewController

- (IBAction)touchCardButton:(UIButton *)sender
{
    if ([sender.currentTitle length]) {
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]
                           forState:UIControlStateNormal];
        [sender setTitle:@"" forState:UIControlStateNormal];
    } else {
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]
                           forState:UIControlStateNormal];
        [sender setTitle:@"A♣" forState:UIControlStateNormal];
    }
}

@end
```

**Button**

Type System

State Config Default

Title Plain

A♣

Font System 24.0

Text Color Black Color

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Shows Touch On Highlight

directly available in Interface...

**Label**

Label - A variably sized amount of static text.

**Button**

Button - Intercepts touch events and sends an action message to a target object when it's tapped.

**Segmented Control**

1 2 Segmented Control - Displays multiple segments, each of which functions as a discrete button.

**Text**

Text Field - Displays editable text and sends an action message to a target object when Return... is pressed.

**Slider**

Slider - Displays a continuous

Stanford CS193p Fall 2013

We're going to have a bit of text in our UI which shows how many times we've flipped the card. A **UILabel** is the **UIKit** class we want (it displays small bits of uneditable text).

Find **UILabel** in the Object Palette (it's right above **UIButton**).

The screenshot shows the Xcode interface with the storyboard editor on the left, the code editor in the center, and the object library on the right. A green callout bubble points from the text "Find UILabel in the Object Palette (it's right above UIButton)." to the "Label" section in the object library. The storyboard view shows a blue button with the text "A♣". The code editor shows the implementation of the CardGameViewController. The object library lists various UI components like Button, Label, Segmented Control, Text, and Slider.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

Label

View

Drag one into the lower left corner of the View.  
Use the blue guidelines to place it.

Button

Type System

State Config Default

Title Plain

A♣

Font System 24.0

Text Color Black Color

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Shows Touch On Highlight

{} { } { }

directly available in Interface...

Label Label - A variably sized amount of static text.

Button Button - Intercepts touch events and sends an action message to a target object when it's tapped.

Segmented Control Segmented Control - Displays multiple segments, each of which functions as a discrete button.

Text Text - Displays editable text and sends an action message to a target object when Return... is pressed.

Slider Slider - Displays a continuous

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

The Attributes Inspector has now changed to show attributes of the Label.

Put this away by dragging it down.

Label

Text Plain

Label

Color Black Color

Font System 17.0

Alignment

Lines 1

Behavior Enabled

Baseline Align Baselines

Line Breaks Truncate Tail

Autoshrink Fixed Font Size

Tighten Letter Spacing

directly available in Interface...

Label Label – A variably sized amount of static text.

Button Button – Intercepts touch events and sends an action message to a target object when it's tapped.

Segmented Control Segmented Control – Displays multiple segments, each of which functions as a discrete button.

Text Text Field – Displays editable text and sends an action message to a target object when Return... is pressed.

Slider Slider – Displays a continuous slider.

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

Label

Text Plain

Color Black Color

Font System 17.0

Alignment

Lines 1

Behavior  Enabled  
 Highlighted

Baseline Align Baselines

Line Breaks Truncate Tail

Autoshrink Fixed Font Size  
 Tighten Letter Spacing

Highlighted Default

Shadow Default

Shadow Offset 0 -1

Horizontal Vertical

View

Mode Left

Tag 0

Interaction  User Interaction Enabled  
 Multiple Touch

Alpha 1

Background Default

Tint Default

Drawing  Opaque  Hidden  
 Clear Graphics Context  
 Clip Subviews

Stanford CS193p Fall 2013

Grab a resize handle and make this **UILabel** very wide (again, use the blue guidelines).

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

Label

Text Plain

Color Black Color

Font System 17.0

Alignment

Lines 1

Behavior  Enabled  
 Highlighted

Baseline Align Baselines

Line Breaks Truncate Tail

Autoshrink Fixed Font Size  
 Tighten Letter Spacing

Highlighted Default

Shadow Default

Shadow Offset 0 -1

Horizontal Vertical

View

Mode Left

Tag 0

Interaction  User Interaction Enabled  
 Multiple Touch

Alpha 1

Background Default

Tint Default

Drawing  Opaque  Hidden  
 Clear Graphics Context  
 Clip Subviews

Stanford CS193p Fall 2013

A♣

Label

Now double-click on it to change the text ...

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                             forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                             forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

Label

Text Plain

Color Black Color

Font System 17.0

Alignment

Lines 1

Behavior  Enabled  
 Highlighted

Baseline Align Baselines

Line Breaks Truncate Tail

Autoshrink Fixed Font Size  
 Tighten Letter Spacing

Highlighted Default

Shadow Default

Shadow Offset 0 -1

Horizontal Vertical

View

Mode Left

Tag 0

Interaction  User Interaction Enabled  
 Multiple Touch


Alpha 1

Background Default

Tint Default

Drawing  Opaque  Hidden  
 Clear Graphics Context  
 Clip Subviews

Stanford CS193p Fall 2013



... to “Flips: 0”.

We’re actually going to set this text entirely from our code, but “Flips: 0” is what is going to appear when our application first launches.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

Label

Text: Plain

Flips: 0

Color: Black Color

Font: System 17.0

Alignment: Center

Lines: 1

Behavior: Enabled

Baseline: Align Baselines

Line Breaks: Truncate Tail

Autoshrink: Fixed Font Size

Shadow: Default

Shadow Offset: 0 -1

View

Mode: Left

Tag: 0

Interaction: User Interaction Enabled

Alpha: 1

Background: Default

Tint: Default

Drawing: Opaque

Clears Graphics Context: Checked

Clin Subviews: Checked

Stanford CS193p Fall 2013

A♣

Flips: 0

Now we have to connect this label to our Controller.  
We do this by dragging to our code again  
(but to the **@interface** instead of the **@implementation**).

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
@end
```

Label

Text Plain

Flips: 0

Color Black Color

Font System 17.0

Alignment

Lines 1

Behavior Enabled

Baseline Align Baselines

Line Breaks Truncate Tail

Autoshrink Fixed Font Size

Tighten Letter Spacing

Highlighted Default

Shadow Default

Shadow Offset 0 -1

View

Mode Left

Tag 0

User Interaction Enabled

Multiple Touch

Alpha 1

Background Default

Tint Default

Opaque

Hidden

Clears Graphics Context

Clin Subviews

A ♠

Flips: 0


Hold down the CTRL key while dragging the mouse from the label to the code (then let go). Since we're creating a **@property** here, we drag somewhere between the **@interface** and the **@end**.

This **@property** we're going to create is called an “outlet property” or “outlet” for short.

Stanford CS193p Fall 2013

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                             forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                             forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
  
@end
```

The `@property` created by this process is `weak` because the MVC's View already keeps a `strong` pointer to the `UILabel`, so there's no need for the Controller to do so as well. And if the `UILabel` ever left the View, the Controller most likely wouldn't want a pointer to it anyway (but if you did want to keep a pointer to it even if it left the View, you could change this to `strong` (very rare)).




**Label**

Text: Plain  
Flips: 0  
Color: Black Color  
Font: System 17.0  
Alignment: Center  
Lines: 1  
Behavior: Enabled  
Highlighted  
Baseline: Align Baselines  
Line Breaks: Truncate Tail  
Autoshrink: Fixed Font Size  
Tighten Letter Spacing  
Highlighted: Default  
Shadow: Default  
Shadow Offset: 0 -1  
Horizontal Vertical


**View**

Mode: Left  
Tag: 0  
User Interaction Enabled  
Multiple Touch  
Alpha: 1  
Background: Default  
Tint: Default  
Opaque: Hidden  
Clear Graphics Context  
Clip Subviews  
Drawing: Opaque  
Hidden  
Clip Subviews  
Stanford CS193p  
Fall 2013



Automatic CardGameViewController.m -touchCardButton:

&lt; 2 &gt;



Connection **Outlet**  
Object **Card Game View Co...**  
Name **flipsLabel**  
Type **UILabel**  
Storage **Weak**

Cancel

Connect



Flips: 0



```
//
//  CardGameViewController.m
//  Matchismo
//
//  Created by CS193p Instructor.
//  Copyright (c) 2013 Stanford University.
//  All rights reserved.
//

#import "CardGameViewController.h"

@interface CardGameViewController : UIViewController

@end

@implementation CardGameViewController

- (IBAction)touchCardButton:(UIButton *)sender
{
    if ([sender.currentTitle length]) {
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]
                           forState:UIControlStateNormal];
        [sender setTitle:@"" forState:UIControlStateNormal];
    } else {
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]
                           forState:UIControlStateNormal];
        [sender setTitle:@"A♣" forState:UIControlStateNormal];
    }
}

@end
```

We'll call this **UILabel** **flipsLabel**.

Then press Connect.

**Label**

Text	Plain
Flips:	0
Color	Black Color
Font	System 17.0
Alignment	Center
Lines	1
Behavior	<input checked="" type="checkbox"/> Enabled <input type="checkbox"/> Highlighted
Baseline	Align Baselines
Line Breaks	Truncate Tail
Autoshrink	Fixed Font Size
	<input type="checkbox"/> Tighten Letter Spacing
Highlighted	Default
Shadow	Default
Shadow Offset	Horizontal: 0 Vertical: -1

**View**

Mode	Left
Tag	0
Interaction	<input type="checkbox"/> User Interaction Enabled <input type="checkbox"/> Multiple Touch
Alpha	1
Background	Default
Tint	Default
Drawing	<input type="checkbox"/> Opaque <input type="checkbox"/> Hidden <input checked="" type="checkbox"/> Clear Graphics Context <input checked="" type="checkbox"/> Clip Subviews

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo > iPhone Retina (3.5-inch)

Label

Text: Plain  
Flips: 0  
Color: Black Color  
Font: System 17.0  
Alignment: Center  
Lines: 1  
Behavior: Enabled  
Baseline: Align Baselines  
Line Breaks: Truncate Tail  
Autoshrink: Fixed Font Size  
Tighten Letter Spacing: Off  
Highlighted: Default  
Shadow: Default  
Shadow Offset: 0 -1  
Horizontal Vertical  
View  
Mode: Left  
Tag: 0  
User Interaction Enabled: Off  
Multiple Touch: Off  
Alpha: 1  
Background: Default  
Tint: Default  
Drawing: Opaque  
Hidden: Off  
Clears Graphics Context: On  
Cling Subviews: On

//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@property (weak, nonatomic) IBOutlet UILabel \*flipsLabel;  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton \*)sender  
{  
 if ([sender.currentTitle length]) {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"" forState:UIControlStateNormal];  
 } else {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"A♣" forState:UIControlStateNormal];  
 }  
}  
@end

A♣

Flips: 0

Stanford CS193p Fall 2013

IBOutlet is a keyword Xcode puts here (similar to IBAction) to remind Xcode that this is not just a random @property, it's an outlet (i.e. a connection to the View). The compiler ignores it.

Otherwise this syntax should all be familiar to you.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Label

Text Plain

Flips: 0

Color Black Color

Font System 17.0

Alignment

Lines 1

Behavior  Enabled  Highlighted

Baseline Align Baselines

Line Breaks Truncate Tail

Autoshrink Fixed Font Size

Tighten Letter Spacing

Highlighted Default

Shadow Default

Shadow Offset 0 -1

Horizontal Vertical

View

Mode Left

Tag 0

Interaction  User Interaction Enabled  Multiple Touch

Alpha 1

Background Default

Tint Default

Drawing  Opaque  Hidden

Clear Graphics Context  Clip Subviews

Stanford CS193p Fall 2013

//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@property (weak, nonatomic) IBOutlet UILabel \*flipsLabel;  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton \*)sender  
{  
 if ([sender.currentTitle length]) {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"" forState:UIControlStateNormal];  
 } else {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"A♣" forState:UIControlStateNormal];  
 }  
}  
@end

A♣

Highlighted!


Flips: 0

Label - Flips:

Just like with an action, you can mouse over this icon to see what the outlet connects to.




```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
@interface CardGameViewController ()  
@end  
  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
@end
```





It is also possible to see the connections between your View and Controller by right-clicking on an element in your View.


For example, right-click on the Flips:0 label.

Here are all the connections to/from this **UILabel**.  
Notice the outlet **flipsLabel**.










Flips: 0

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
@end
```

You can also “right-click” on your Controller itself (and thus see all connections) by using this icon.



Card Game View Controller



**Button**

Type: System

State Config: Default

Title: Plain

A ♠

Font: System 24.0

Text Color: Black Color

Shadow Color: Default

Image: Default Image

Background: cardfront

Shadow Offset: 0.0 0.0

Width: 0.0 Height: 0.0

Reverses On Highlight

Drawing:  Shows Touch On Highlight  Highlighted Adjusts Image  Disabled Adjusts Image

Line Break: Truncate Middle

Edge: Content

Inset: 0 0 Top: 0 Bottom: 0

Left: 0 Right: 0

**Control**

Alignment: Horizontal

Vertical


Content:  Selected  Enabled  Highlighted

Stanford CS193p

Fall 2013



Matchismo | iPhone Retina (3.5-inch) | Autom... | CardGameViewController.m | @interface CardGameViewController() | 2 | + | X



Right-click  
on this  
icon.



### Card Game View Controller

Triggered Segues	
Outlets	
flipsLabel	* Label - Flips: 0
searchDisplayController	
view	* View
Presenting Segues	
relationship	
push	
modal	
custom	
embed	
Referencing Outlets	
New Referencing Outlet	
Referencing Outlet Collections	
New Referencing Outlet Collection	
Received Actions	
touchCardButton:	* Button - A♣
	Touch Up Inside

This title bar says that we are looking at  
the connections to/from our Controller.

```

// CardGameViewController.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "CardGameViewController.h"

@interface CardGameViewController ()  

@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  

@end

@implementation CardGameViewController  

- (IBAction)touchCardButton:(UIButton *)sender  

{  

    if ([sender.currentTitle length]) {  

        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  

                             forState:UIControlStateNormal];  

        [sender setTitle:@"" forState:UIControlStateNormal];  

    } else {  

        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  

                             forState:UIControlStateNormal];  

        [sender setTitle:@"A♣" forState:UIControlStateNormal];  


    }  

}

```


### Button

Type	System
State Config	Default
Title	Plain
Font	System 24.0
Text Color	Black Color
Shadow Color	Default
Image	Default Image
Background	cardfront
Shadow Offset	0.0 0.0
Width	Height
<input type="checkbox"/> Reverses On Highlight	
Drawing	<input type="checkbox"/> Shows Touch On Highlight
	<input checked="" type="checkbox"/> Highlighted Adjusts Image
	<input checked="" type="checkbox"/> Disabled Adjusts Image
Line Break	Truncate Middle
Edge	Content
Inset	0 0
Top	Bottom
Left	Right
Control	
Alignment	
Horizontal	
Vertical	
Content	<input type="checkbox"/> Selected <input checked="" type="checkbox"/> Enabled
	<input type="checkbox"/> Highlighted





Matchismo > iPhone Retina (3.5-inch) | Button... | Autom... | CardGameViewController.m | @interface CardGameViewController()



Highlighted!

Flips: 0

Card Game View Controller

Triggered Segues

Outlets

flipsLabel

searchDisplayController

view

Presenting Segues

relationship

push

modal

custom

embed

Referencing Outlets

New Referencing Outlet

Referencing Outlet Collections

New Referencing Outlet Collection

Received Actions

touchCardButton:

\* Button - A♣  
Touch Up Inside

```

// CardGameViewController.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "CardGameViewController.h"

@interface CardGameViewController ()  

@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  

@end

@implementation CardGameViewController  

- (IBAction)touchCardButton:(UIButton *)sender  

{  

    if ([sender.currentTitle length]) {  

        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  

                           forState:UIControlStateNormal];  

        [sender setTitle:@"" forState:UIControlStateNormal];  

    } else {  

        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  

                           forState:UIControlStateNormal];  

        [sender setTitle:@"A♣" forState:UIControlStateNormal];  

    }
}

```

Mouse over

This is an automatically connected outlet from  
your Controller to the top-level of your View.  
We'll talk about that later in the course.

Button

Type System

State Config Default

Title Plain



Font System 24.0

Text Color Black Color

Shadow Color Default

Image Default Image

Background cardfront

Shadow Offset 0.0 0.0

Width Height

Reverses On Highlight

Shows Touch On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break Truncate Middle

Edge Content

Inset 0 0

Top Bottom

0 0

Left Right

Alignment

Horizontal

Vertical


Selected

Enabled

Highlighted

Fall 2013

Stanford CS193p



```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
}  
@end
```

Let's hide the Utilities area again to make more room for code.

**Button**

Type: System

State Config: Default

Title: Plain

A♣

Font: System 24.0

Text Color: Black Color

Shadow Color: Default

Image: Default Image

Background: cardfront

Shadow Offset: 0.0 0.0

Width: 0.0 Height: 0.0

Reverses On Highlight

Drawing: Shows Touch On Highlight

Highlighted Adjusts Image

Disabled Adjusts Image

Line Break: Truncate Middle

Edge: Content

Inset: 0 0

Top: 0 Bottom: 0

Left: 0 Right: 0

**Control**

Alignment: Horizontal

Vertical

Content: Selected  Enabled

Highlighted

Stanford CS193p

Fall 2013


Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m @interface CardGameViewController()

//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@property (weak, nonatomic) IBOutlet UILabel \*flipsLabel;  
@end  
  
@implementation CardGameViewController  
  
- (IBAction)touchCardButton:(UIButton \*)sender  
{  
 if ([sender.currentTitle length]) {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"" forState:UIControlStateNormal];  
 } else {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"A♣" forState:UIControlStateNormal];  
 }  
}  
@end

We are going to keep track of the number of flips of the card using a new `@property`.



Flips: 0

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m @interface CardGameViewController()

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end  
  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
}  
@end
```

We'll call this **@property** `flipCount`.

Nothing special about this **@property**, it's just an integer.  
We could use `NSInteger` or `NSUInteger` here,  
but we're using `int`, just to show doing so.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -touchCardButton:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end  
  
@implementation CardGameViewController  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A♣" forState:UIControlStateNormal];  
    }  
    self.flipCount++;  
}  
@end
```


A screenshot of Xcode showing the Matchismo project. The storyboard preview on the left shows a card with 'A♣' on it. The code editor on the right shows the implementation of the touchCardButton method. A callout bubble points from the 'self.flipCount++' line to a note explaining it.

Flips: 0

And we'll just increment it each time we flip the card.

Notice that we can use `++` notation just like with a variable. This is the same as `self.flipCount = self.flipCount + 1`. In other words, `self.flipCount++` invokes both the getter and the setter for the `flipCount` `@property`.

Stanford CS193p Fall 2013



But how can we coordinate the `flipCount` `@property` with the `flipsLabel` `UILabel`?

Easy! We'll use the setter of the flipCount `@property`.  
This is yet another advantage of using `@property` instead of accessing instance variables directly.

This is what the setter for  
flipCount would normally look like.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -setFlipCount:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end  
  
@implementation CardGameViewController  
  
- (void)setFlipCount:(int)flipCount  
{  
    _flipCount = flipCount;  
    self.flipsLabel.text = [NSString stringWithFormat:@"Flips: %d", self.flipCount];  
}  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length] == 0)  
        [sender setImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
    [sender setTitle:@"" forState:UIControlStateNormal];  
} else {  
    [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
        forState:UIControlStateNormal];  
    [sender setTitle:@"A♣" forState:UIControlStateNormal];  
}  
self.flipCount++;  
}  
@end
```

Flips: 0

A♣

We'll just add this one line of code to set the `text` `@property` of the `flipsLabel` to a string formatted to include the `flipCount`.

Now any time the `flipCount` `@property` changes, the `flipsLabel` `UILabel` will get updated.

Advanced thinking: note that we use `self.flipCount` here instead of just `_flipCount`. Imagine if a subclass wanted to control the value of `flipCount` by overriding the getter but still benefit from this method's display of it. Subtle.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -setFlipCount:

```
// CardGameViewController.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "CardGameViewController.h"

@interface CardGameViewController ()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end

@implementation CardGameViewController

- (void)setFlipCount:(int)flipCount  
{  
    _flipCount = flipCount;  
    self.flipsLabel.text = [NSString stringWithFormat:@"Flips: %d", self.flipCount];  
    NSLog(@"flipCount changed to %d", self.flipCount);  
}

- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A ♠" forState:UIControlStateNormal];  
    }  
    self.flipCount++;  
}
```

The first argument to `NSLog()` must always be an `@""`. Not any other kind of `NSString`.

Remember, the console will automatically appear at the bottom of the screen when you run.

While we're here, let's take another aside to look at a debugging technique. We can output something to the console any time we want.

We do it using the C function `NSLog()`. The first argument to `NSLog()` is a `@""` printf-like format string specifying what to output. The rest of the arguments are the values matching up with the `%`'s in the format string.

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Main.storyboard

Running Matchismo on iPhone Retina (3.5-inch)

No Issues

Carrier

Okay, let's run again!

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end  
  
@implementation CardGameViewController  
  
- (void)setFlipCount:(int)flipCount  
{  
    _flipCount = flipCount;  
    self.flipsLabel.text = [NSString stringWithFormat:@"Flips: %d", flipCount];  
    NSLog(@"flipCount changed to %d", self.flipCount);  
}  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length] == 0){  
        [sender setBackgroundImage:[UIImage imageNamed:@"card-back.png"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"card-front.png"]  
                           forState:UIControlStateNormal];  
    }  
}
```

Flips: 0

Flips: 0

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Main.storyboard

Running Matchismo on iPhone Retina (3.5-inch)

No Issues

Matchismo > iPhone Retina (3.5-inch) | Button... | Automatic | CardGameViewController.m | -setFlipCount:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end  
  
@implementation CardGameViewController  
  
- (void)setFlipCount:(int)flipCount  
{  
    _flipCount = flipCount;  
    self.flipsLabel.text = [NSString stringWithFormat:@"Flips: %d", flipCount];  
    NSLog(@"flipCount changed to %d", self.flipCount);  
}  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"card-flipped.png"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"card-normal.png"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A ♣" forState:UIControlStateNormal];  
    }  
}
```

Carrier

Flips: 0

A ♣

Touch

This should change.

Flips: 1

Stanford S logo

2013-00-00 14:29:14.411 Matchismo[72114:a0b] flipCount changed to 1

And here's the output of the NSLog().

Matchismo.xcodeproj — Main.storyboard

Running Matchismo on iPhone Retina (3.5-inch)

No Issues

Matchismo > iPhone Retina (3.5-inch) | Button... | Automatic | CardGameViewController.m | -setFlipCount:

```
//  
// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController ()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end  
  
@implementation CardGameViewController  
  
- (void)setFlipCount:(int)flipCount  
{  
    _flipCount = flipCount;  
    self.flipsLabel.text = [NSString stringWithFormat:@"Flips: %d", flipCount];  
    NSLog(@"flipCount changed to %d", self.flipCount);  
}  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"card-flipped.png"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"card-normal.png"]  
                           forState:UIControlStateNormal];  
        [sender setTitle:@"A ♠" forState:UIControlStateNormal];  
    }  
}
```

Carrier

Touch again.

Changes again.

Flips: 0

A ♠

Flips: 2

2013-00-00 14:29:14.411 Matchismo[72114:a0b] flipCount changed to 1  
2013-00-00 14:29:14.834 Matchismo[72114:a0b] flipCount changed to 2

And outputs here again.

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Automatic CardGameViewController.m -setFlipCount:

Stop.

// CardGameViewController.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
//

#import "CardGameViewController.h"  
@interface CardGameViewController()  
@property (weak, nonatomic) IBOutlet UILabel \*flipsLabel;  
@property (nonatomic) int flipCount;  
@end

@implementation CardGameViewController

- (void)setFlipCount:(int)flipCount  
{  
 \_flipCount = flipCount;  
 self.flipsLabel.text = [NSString stringWithFormat:@"Flips: %d", self.flipCount];  
 NSLog(@"flipCount changed to %d", self.flipCount);  
}

- (IBAction)touchCardButton:(UIButton \*)sender  
{  
 if ([sender.currentTitle length]) {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"" forState:UIControlStateNormal];  
 } else {  
 [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
 forState:UIControlStateNormal];  
 [sender setTitle:@"A♣" forState:UIControlStateNormal];  
 }  
 self.flipCount++;  
}

@end

Well this is all wonderful, but it's sort of boring since it only shows the A♣ all the time.

If only we had a Deck of PlayingCards to drawRandomCard from, we could make each flip show a different card.

Hmmm ...


Let's start by revealing the Navigator again.


Flips: 0


A♣


Stop.


Stanford CS193p Fall 2013

















Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- Card.h**
- Card.m
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

```
// Card.h
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>

@interface Card : NSObject

@end
```

```
// Card.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card

@end
```

Here is a (blank) Card class.  
You will have to go through the slides from  
earlier and type in the implementation of Card.

It is important to *type the code in*  
(not copy/paste it from somewhere)  
so that you gain experience with entering code in Xcode.

Stanford CS193p  
Fall 2013

You can put the header file in either the left or right side of the Assistant Editor as you prefer.

You can choose which goes where by clicking on the name of the file at the top of the pane in question.

```
//  
// Card.h  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import <Foundation/Foundation.h>  
  
@interface Card : NSObject  
@end
```

```
//  
// Card.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "Card.h"  
  
@implementation Card  
  
@end
```

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch)

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

Card.h

Card.m

CardGameViewController.h

CardGameViewController.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

// Card.h  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import <Foundation/Foundation.h>  
  
@interface Card : NSObject  
  
@end

Manual

Counterparts (1)

Superclasses

Subclasses

Siblings

Categories

Protocols

User Interfaces

Includes

Included By

Callers

Callees

Test Classes


Test Callers

Preprocess

Choosing the header or implementation from the Counterparts menu at the top of the pane ensures that Xcode will continue to always match the implementation up with the interface (or vice versa), even if you change what is in the left pane.

Stanford CS193p

Fall 2013



Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- New Group
  - Card.h
  - Card.m
  - CardGameViewController.h
  - CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

// Card.h  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import <Foundation/Foundation.h>  
  
@interface Card : NSObject  
  
@end

// Card.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "Card.h"  
  
@implementation Card  
  
@end

And we'll rename the group ...

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard

Model

- Card.h
- Card.m
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

```
// Card.h
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>

@interface Card : NSObject

@end
```

```
// Card.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card

@end
```

... to Model.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- Model**
- Card.h
- Card.m
- CardGameViewController.h
- CardGameViewController.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

```
// Card.h
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>

@interface Card : NSObject
@end

// Card.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card
@end
```

A group in the File Navigator can be linked to a directory in the filesystem or not, as you prefer. You control this from the File Inspector in the Utilities area.

Identity and Type

- Name Card.h
- Type Default C Header
- Absolute Path
- Relative to Group**
- Relative to Project
- Relative to Developer Directory
- Relative to Build Products
- Relative to SDK

Target Membership

- Matchismo
- MatchismoTests

Text Settings

- Text Encoding Default – Unicode (UTF-8)
- Line Endings Default – OS X / Unix (LF)
- Indent Using Spaces
- Widths Tab 4 Indent 4
- Wrap lines

Source Control

- Repository  --
- Type --
- Current Branch --
- Version --
- Status No changes
- Location

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

CardGameAppDelegate.h

CardGameAppDelegate.m

Main.storyboard

Model

Card.h

Card.m

CardGameViewController.h

CardGameViewController.m

Model

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

```
// Card.h
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>

@interface Card : NSObject

@end
```

```
// Card.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card

@end
```

You can drag things around in the File Navigator to put them in whatever order you want.

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m

Model

- Card.h
- Card.m
- Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

```
// Card.h
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>

@interface Card : NSObject

@end

// Card.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card

@end
```

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Matchismo

- CardGameAppDelegate.h
- CardGameAppDelegate.m
- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m

Model

- Card.h
- Card.m

Images.xcassets

CardGameAppDelegate.h

Supporting Files

- CardGameAppDelegate.plist
- Matchismo-Info.plist
- InfoPlist.strings
- main.m
- Matchismo-Prefix.pch

MatchismoTests

Frameworks

Products

```
// Card.h
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@interface Card : NSObject

@end
```

```
// Card.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card

@end
```

For example, often we'll drag the AppDelegate.[mh] into Supporting Files group since we rarely edit them.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Main.storyboard CardGameViewController.h CardGameViewController.m Model Card.h Card.m Images.xcassets Supporting Files CardGameAppDelegate.h CardGameAppDelegate.m Matchismo-Info.plist InfoPlist.strings main.m Matchismo-Prefix.pch

Card.h

```
// Card.h
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>

@interface Card : NSObject

@end
```

Card.m

```
// Card.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card

@end
```

If you explicitly click on Card.h in the File Navigator, it will show it in the left pane of the Assistant Editor.

And Card.m will automatically appear in the right pane as long as Counterparts is selected here.

Stanford CS193p  
Fall 2013

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Main.storyboard CardGameViewController.h CardGameViewController.m Model Card.h Card.m Images.xcassets Supporting Files MatchismoTests Frameworks Products

// Card.h  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import <Foundation/Foundation.h>  
  
@interface Card : NSObject  
  
@end

// Card.m  
// Matchismo  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "Card.h"  
  
@implementation Card  
  
@end

Close Supporting Files folder.

Stanford CS193p Fall 2013

Matchismo.xcodeproj — Card.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Main.storyboard CardGameViewController.h CardGameViewController.m Model Card.h Card.m Images.xcassets Supporting Files MatchismoTests Frameworks Products

```
// Card.h
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>

@interface Card : NSObject

@property (strong, nonatomic) NSString *contents;
@property (nonatomic, getter=isChosen) BOOL chosen;
@property (nonatomic, getter=isMatched) BOOL matched;

- (int)match:(NSArray *)otherCards;
@end

// Card.m
// Matchismo
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@implementation Card

- (int)match:(NSArray *)otherCards
{
    int score = 0;

    for (Card *card in otherCards) {
        if ([card.contents isEqualToString:self.contents]) {
            score = 1;
        }
    }


    return score;
}

@end
```


Type in the code for Card. [mh].


Now let's move on to creating templates for the Deck, PlayingCard and PlayingCardDeck classes.


Stanford CS193p  
Fall 2013



Stanford CS193p  
Fall 2013







Matchismo  
2 targets, iOS SDK 7.0

Matchismo

- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Model
  - Card.h
  - Card.m
  - PlayingCard.h
  - PlayingCard.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

```
// PlayingCard.h
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@interface PlayingCard : Card

@end
```

```
// PlayingCard.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "PlayingCard.h"

@implementation PlayingCard

@end
```

Hopefully PlayingCard.[mh] appeared  
in your Model group!

Drag it in if not.

Matchismo  
2 targets, iOS SDK 7.0

Matchismo  
Main.storyboard  
CardGameViewController.h  
CardGameViewController.m  
Model  
Card.h  
Card.m  
PlayingCard.h  
PlayingCard.m  
Images.xcassets  
Supporting Files  
MatchismoTests  
Frameworks  
Products

```
// PlayingCard.h
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Card.h"

@interface PlayingCard : Card

@property (strong, nonatomic) NSString *suit;
@property (nonatomic) NSUInteger rank;

+ (NSArray *)validSuits;
+ (NSUInteger)maxRank;

@end
```

```
// PlayingCard.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "PlayingCard.h"

@implementation PlayingCard

- (NSString *)contents
{
    NSArray *rankStrings = [PlayingCard rankStrings];
    return [rankStrings[self.rank] stringByAppendingString:suit];
}

@synthesize suit = _suit;

+ (NSArray *)validSuits
{
    return @[@"♠", @"♦", @"♥", @"♦"];
}

- (void)setSuit:(NSString *)suit
{
    if ([[PlayingCard validSuits] containsObject:suit]) {
        _suit = suit;
    }
}

- (NSString *)suit
{
    return _suit ? _suit : @"?";
}

+ (NSArray *)rankStrings
{
    return @[@"?", @"A", @"2", @"3", @"4", @"5", @"6",
             @"7", @"8", @"9", @"10", @"J", @"Q", @"K"];
}
```

Type in the code for PlayingCard. [mh].

All the code doesn't fit here, so use the other lecture slides to enter this code.

Matchismo.xcodeproj — Deck.h

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Matchismo 2 targets, iOS SDK 7.0

Main.storyboard CardGameViewController.h CardGameViewController.m Model Card.h Card.m PlayingCard.h PlayingCard.m Deck.h Deck.m Images.xcassets Supporting Files MatchismoTests Frameworks Products

```
// Deck.h
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import <Foundation/Foundation.h>
#import "Card.h"

@interface Deck : NSObject

- (void)addCard:(Card *)card atTop:(BOOL)atTop;
- (void)addCard:(Card *)card;

- (Card *)drawRandomCard;

@end
```

```
// Deck.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "Deck.h"

@interface Deck()
@property (strong, nonatomic) NSMutableArray *cards; // of Card
@end

@implementation Deck

- (NSMutableArray *)cards
{
    if (!_cards) _cards = [[NSMutableArray alloc] init];
    return _cards;
}

- (void)addCard:(Card *)card atTop:(BOOL)atTop
{
    if (atTop) {
        [self.cards insertObject:card atIndex:0];
    } else {
        [self.cards addObject:card];
    }
}

- (void)addCard:(Card *)card
{...}

- (Card *)drawRandomCard
{
    Card *randomCard = nil;

    if ([self.cards count]) {
        unsigned index = arc4random() % [self.cards count];
        randomCard = self.cards[index];
        [self.cards removeObjectAtIndex:index];
    }
}
```

All the code doesn't fit here, so use the other lecture slides to enter this code.

Repeat for Deck. [mh].

Stanford CS193p  
Fall 2013

Matchismo  
2 targets, iOS SDK 7.0

Matchismo

- Main.storyboard
- CardGameViewController.h
- CardGameViewController.m
- Model
  - Card.h
  - Card.m
  - PlayingCard.h
  - PlayingCard.m
  - Deck.h
  - Deck.m
  - PlayingCardDeck.h
  - PlayingCardDeck.m
- Images.xcassets
- Supporting Files
- MatchismoTests
- Frameworks
- Products

```
// PlayingCardDeck.h
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford Univ.
// All rights reserved.

#import "Deck.h"

@interface PlayingCardDeck : Deck

@end
```

```
// PlayingCardDeck.m
// Matchismo
//
// Created by CS193p Instructor.
// Copyright (c) 2013 Stanford University.
// All rights reserved.

#import "PlayingCardDeck.h"
#import "PlayingCard.h"

@implementation PlayingCardDeck

- (instancetype)init
{
    self = [super init];

    if (self) {
        for (NSString *suit in [PlayingCard validSuits]) {
            for (NSUInteger rank = 1; rank <= [PlayingCard maxRank]; rank++) {
                PlayingCard *card = [[PlayingCard alloc] init];
                card.rank = rank;
                card.suit = suit;
                [self addCard:card];
            }
        }
    }

    return self;
}

@end
```

Repeat for PlayingCardDeck. [mh].

Matchismo.xcodeproj — Main.storyboard

Finished running Matchismo on iPhone Retina (3.5-inch) No Issues

Main.storyboard Card Game View Controller View Automatic CardGameViewController.m No Selection

Matchismo 2 targets, iOS SDK 7.0

Matchismo

Main.storyboard

CardGameViewController.h

CardGameViewController.m

Model

Card.h

Card.m

PlayingCard.h

PlayingCard.m

Deck.h

Deck.m

PlayingCardDeck.h

PlayingCardDeck.m

Images.xcassets

Supporting Files

MatchismoTests

Frameworks

Products

Click here to go back to the View.

A ♣

Flips: 0

We did all this so that we could have each card not be A ♣.  
Your homework is to make each flip draw a new random card.  
One of the first things you'll want is a `@property` for a Deck.

Good luck!

```
//  
// CardGameViewController.m  
// Matchismo  
//  
// Created by CS193p Instructor.  
// Copyright (c) 2013 Stanford University.  
// All rights reserved.  
  
#import "CardGameViewController.h"  
  
@interface CardGameViewController()  
@property (weak, nonatomic) IBOutlet UILabel *flipsLabel;  
@property (nonatomic) int flipCount;  
@end  
  
@implementation CardGameViewController  
  
- (void)setFlipCount:(int)flipCount  
{  
    _flipCount = flipCount;  
    self.flipsLabel.text = [NSString stringWithFormat:@"Flips: %d", self.flipCount];  
    NSLog(@"flipCount changed to %d", self.flipCount);  
}  
  
- (IBAction)touchCardButton:(UIButton *)sender  
{ Whew!  
    if ([sender.currentTitle length]) {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardback"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"" forState:UIControlStateNormal];  
    } else {  
        [sender setBackgroundImage:[UIImage imageNamed:@"cardfront"]  
            forState:UIControlStateNormal];  
        [sender setTitle:@"A♦" forState:UIControlStateNormal];  
    }  
    self.flipCount++;  
}  
@end
```

Stanford CS193p  
Fall 2013

# Coming Up

## ⌚ Needs more Card Game!

Your homework will be to have that single card flip through an entire Deck of PlayingCards.  
Next week we'll make multiple cards and put in logic to match them against each other.

## ⌚ Also next week ...

Objective-C language in depth

Foundation classes: arrays, dictionaries, strings, etc.

Dynamic vs. static typing

Protocols, categories and much, much more!