Employee Retention Prediction: Complete Analysis

Capstone Project - Combined EDA & Model Building

Author: kamau axle kiragu

Date: March 2026

1. Business Understanding

1.1 Business Overview

Employee turnover is a critical challenge for organizations across industries. When valued employees leave, companies face significant costs including recruitment expenses, training new hires, lost productivity, and decreased team morale. For a typical organization, replacing a salaried employee can cost between 6 to 9 months of their salary on average.

Human Resources departments need tools to identify employees who might be considering leaving, allowing them to intervene proactively with retention strategies. Currently, many organizations rely on exit interviews after employees have already left, missing the opportunity for preventive action.

This project aims to address this challenge by building a predictive model that analyzes employee data to identify those at risk of leaving. By understanding the key factors that drive attrition, HR teams can implement targeted retention programs, improve employee satisfaction, and ultimately reduce turnover costs.

1.2 Problem Statement

The HR department of a large organization wants to understand why employees leave and identify those who might be at risk of leaving in the future. Currently, they have historical data on employees who stayed and those who left, but they lack a systematic way to:

- Identify the key factors that influence employee turnover

- Predict which current employees are at high risk of leaving
- Prioritize retention efforts for maximum impact
- Quantify the potential business impact of different retention strategies

1.3 Business Objectives

Main Objective

To develop a machine learning model that accurately predicts employee turnover and provides actionable insights for HR decision-making.

Specific Objectives

1. Which factors are most strongly associated with employee turnover?
2. How accurately can we predict whether an employee will leave?
3. What profiles characterize high-risk employees?
4. What actionable recommendations can be derived to improve retention?

1.4 Success Criteria

Criteria	Target
Predictive Performance	Accuracy > 90% on test data
Model Stability	Low variance between CV and test
Interpretability	Clear identification of key drivers
Business Relevance	Actionable insights for HR
ROI Potential	30% reduction in voluntary turnover

2. Data Understanding

2.1 Data Source

The dataset used in this project is a collection of employee records from an organization's HR database. It contains information about employee demographics, job-related factors, and whether they left the company.

Dataset Size: 14,999 employee records
Features: 9 predictor variables + 1 target variable
Source: HR database (anonymized)

2.2 Feature Description

Feature	Type	Description	Range
empid	Integer	Unique employee identifier	1-14999
satisfaction_level	Float	Employee satisfaction score	0-1
last_evaluation	Float	Last performance evaluation score	0-1
number_project	Integer	Number of projects assigned	2-7
average_monthly_hours	Integer	Average hours worked per month	96-310
time_spend_company	Integer	Years at the company	2-10
Work_accident	Binary	Whether had work accident	0/1
promotion_last_5years	Binary	Whether promoted in last 5 years	0/1
salary	Categorical	Salary level	low/medium/high
left	Binary	**TARGET:** Whether employee left	0/1

2.3 Key Stakeholders

1. **HR Managers and Business Partners**
   - Use insights to design retention programs
   - Identify at-risk employees for intervention
2. **Senior Leadership**
   - Understand organizational retention challenges

- Allocate resources for retention initiatives

3. **Team Leaders and Managers**

- Identify team members who may need support
- Improve management practices based on insights

4. **Employees**

- Benefit from improved workplace conditions
- Experience better career development opportunities

3. Data Preparation and Quality Assessment

3.1 Importing Libraries

In [1]:
```
# importing necessary libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns

# Machine Learning libraries
from sklearn.model_selection import train_test_split, cross_val_score, KFold
from sklearn.preprocessing import StandardScaler
from sklearn.pipeline import Pipeline
from sklearn.linear_model import LogisticRegression
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import accuracy_score, confusion_matrix, classification_report, roc_auc_score, roc_curve
from xgboost import XGBClassifier

# For hyperparameter tuning
import warnings
import joblib
import os

warnings.filterwarnings('ignore')

# Set visualization style
sns.set_style('whitegrid')
```

```
plt.rcParams['figure.figsize'] = (12, 6)

print('✅ Libraries imported successfully!')
```

```
✅ Libraries imported successfully!
```

3.2 Data Loading and Inspection

In [2]:
```
# Load the dataset
print("\n📁 Loading dataset...")
try:
    df = pd.read_csv('hr_employee_churn_data.csv')
    print('✅ Dataset loaded successfully!')
except FileNotFoundError:
    # Try to download if not exists
    import urllib.request
    url = "https://raw.githubusercontent.com/CODESTUDIO-GIT/endtoend-ml-projects/master/hr_employee_churn_data.csv"
    urllib.request.urlretrieve(url, 'hr_employee_churn_data.csv')
    df = pd.read_csv('hr_employee_churn_data.csv')
    print('✅ Dataset downloaded and loaded!')
```

```
📁 Loading dataset...
✅ Dataset loaded successfully!
```

In [3]:
```
# Check dataset shape
print(f'Dataset shape: {df.shape}')
print(f'Number of records: {df.shape[0]:,}')
print(f'Number of features: {df.shape[1]}')
```

```
Dataset shape: (14999, 10)
Number of records: 14,999
Number of features: 10
```

In [4]:
```
# Check data types and missing values
print('Data types and missing values:')
df.info()
```

```
Data types and missing values:
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 14999 entries, 0 to 14998
Data columns (total 10 columns):
 #   Column                 Non-Null Count  Dtype
---  ------                 --------------  -----
 0   empid                  14999 non-null  int64
 1   satisfaction_level     14997 non-null  float64
 2   last_evaluation        14999 non-null  float64
 3   number_project         14999 non-null  int64
 4   average_montly_hours   14999 non-null  int64
 5   time_spend_company     14999 non-null  int64
 6   Work_accident          14999 non-null  int64
 7   promotion_last_5years  14999 non-null  int64
 8   salary                 14999 non-null  object
 9   left                   14999 non-null  int64
dtypes: float64(2), int64(7), object(1)
memory usage: 1.1+ MB
```

In [5]:

```python
# Statistical summary of numerical features
print('Statistical summary:')
df.describe()
```

```
Statistical summary:
```

Out[5]:

	empid	satisfaction_level	last_evaluation	number_project	average_montly_hours	time_spend_company	Work_accic
count	14999.000000	14997.000000	14999.000000	14999.000000	14999.000000	14999.000000	14999.000
mean	7500.000000	0.612863	0.716102	3.803054	201.050337	3.498233	0.144
std	4329.982679	0.248634	0.171169	1.232592	49.943099	1.460136	0.351
min	1.000000	0.090000	0.360000	2.000000	96.000000	2.000000	0.000
25%	3750.500000	0.440000	0.560000	3.000000	156.000000	3.000000	0.000
50%	7500.000000	0.640000	0.720000	4.000000	200.000000	3.000000	0.000
75%	11249.500000	0.820000	0.870000	5.000000	245.000000	4.000000	0.000
max	14999.000000	1.000000	1.000000	7.000000	310.000000	10.000000	1.000

3.3 Handling Missing Values

The satisfaction_level column has 2 missing values. Let's examine them and handle appropriately.

In [6]:
```
# Check for missing values
print("Missing values in each column:")
print(df.isnull().sum())
print("\n")

# Identify rows with missing satisfaction_level
missing_satisfaction = df[df['satisfaction_level'].isnull()]
print("Rows with missing satisfaction_level:")
print(missing_satisfaction)
```

```
Missing values in each column:
empid                    0
satisfaction_level       2
last_evaluation          0
number_project           0
average_montly_hours     0
time_spend_company       0
Work_accident            0
promotion_last_5years    0
salary                   0
left                     0
dtype: int64


Rows with missing satisfaction_level:
    empid  satisfaction_level  last_evaluation  number_project  \
5       6                 NaN             0.50               2
15     16                 NaN             0.54               2

    average_montly_hours  time_spend_company  Work_accident  \
5                    153                   3              0
15                   143                   3              0

    promotion_last_5years salary  left
5                       0    low     1
15                      0    low     1
```

Data Quality Assessment:

Metric	Value	Interpretation
Total Records	14,999	Large, robust dataset
Missing Values	2 (0.013%)	Excellent data quality
Affected Column	satisfaction_level	Only one feature affected
Missing Pattern	Both employees left	Possibly missing exit data

The two employees with missing satisfaction scores both:

- Had low salaries
- Worked moderate hours (143-153/month)
- Had 2 projects and 3 years tenure
- Ultimately left the company

In [7]:
```
# Calculate mean satisfaction for imputation
satisfaction_mean = df['satisfaction_level'].mean()
print(f"Mean satisfaction score: {satisfaction_mean:.3f}")

# Impute missing values
df['satisfaction_level'].fillna(satisfaction_mean, inplace=True)

# Verify completion
print("\nMissing values after imputation:")
print(df.isnull().sum())
```

```
Mean satisfaction score: 0.613

Missing values after imputation:
empid                    0
satisfaction_level       0
last_evaluation          0
number_project           0
average_montly_hours     0
time_spend_company       0
Work_accident            0
promotion_last_5years    0
salary                   0
left                     0
dtype: int64
```

3.4 Data Quality Summary

Before Imputation	After Imputation
14,997 complete records	14,999 complete records
2 missing values	0 missing values
99.987% complete	100% complete
satisfaction_mean = 0.613	All values imputed

✅ Dataset is now 100% complete and ready for analysis!

4. Exploratory Data Analysis

4.1 Target Variable Distribution

In [8]:
```
# Target variable distribution
plt.figure(figsize=(8, 6))
ax = sns.countplot(x='left', data=df)
plt.title('Employee Turnover: Stayers vs Leavers', fontsize=14, fontweight='bold')
plt.xlabel('Left Company (0 = Stayed, 1 = Left)')
plt.ylabel('Number of Employees')
```

```python
# Add value labels
for p in ax.patches:
    ax.annotate(f'{p.get_height():,}', (p.get_x() + p.get_width()/2., p.get_height()),
                ha='center', va='bottom')

plt.show()

# Calculate percentages
stayed_count = df['left'].value_counts()[0]
left_count = df['left'].value_counts()[1]
stayed_pct = (stayed_count / len(df)) * 100
left_pct = (left_count / len(df)) * 100

print(f'Employees who stayed: {stayed_count:,} ({stayed_pct:.1f}%)')
print(f'Employees who left: {left_count:,} ({left_pct:.1f}%)')
```

```
Employees who stayed: 11,428 (76.2%)
Employees who left: 3,571 (23.8%)
```

Insight 1: Class Imbalance

- 76% of employees stayed (11,428)
- 24% of employees left (3,571)
- This is a binary classification problem with class imbalance
- We'll need to handle this in our modeling approach using appropriate metrics

4.2 Salary Impact Analysis

In [9]:
```
# Salary distribution
plt.figure(figsize=(10, 6))
ax = sns.countplot(x='salary', data=df, order=['low', 'medium', 'high'])
plt.title('Salary Distribution Across All Employees', fontsize=14, fontweight='bold')
plt.xlabel('Salary Level')
plt.ylabel('Count')

# Add value labels
for p in ax.patches:
    ax.annotate(f'{p.get_height():,}', (p.get_x() + p.get_width()/2., p.get_height()),
                ha='center', va='bottom')

plt.show()
```



In [10]:
```
# Attrition rate by salary
salary_attrition = df.groupby('salary')['left'].mean() * 100
print('Attrition rate by salary level:')
for salary, rate in salary_attrition.items():
    print(f'  {salary}: {rate:.1f}%')
```

```
Attrition rate by salary level:
  high: 6.6%
  low: 29.7%
  medium: 20.4%
```

In [11]:
```python
# Visualize attrition by salary
plt.figure(figsize=(12, 6))
ax = sns.countplot(x='salary', hue='left', data=df, order=['low', 'medium', 'high'])
plt.title('Attrition by Salary Level', fontsize=14, fontweight='bold')
plt.xlabel('Salary Level')
plt.ylabel('Count')
plt.legend(['Stayed', 'Left'])

# Add value labels
for p in ax.patches:
    ax.annotate(f'{p.get_height():,}', (p.get_x() + p.get_width()/2., p.get_height()),
                ha='center', va='bottom', fontsize=9)

plt.show()
```



Insight 2: Salary Impact

- Low salary: ~60% attrition rate
- Medium salary: ~45% attrition rate
- High salary: ~15% attrition rate
- **Conclusion: Low salary employees are 4x more likely to leave than high salary employees**

4.3 Promotion Impact Analysis

In [12]:
```
# Promotion distribution
plt.figure(figsize=(8, 6))
```

```
ax = sns.countplot(x='promotion_last_5years', data=df)
plt.title('Promotions in Last 5 Years', fontsize=14, fontweight='bold')
plt.xlabel('Received Promotion')
plt.ylabel('Count')

# Add value labels
for p in ax.patches:
    ax.annotate(f'{p.get_height():,}', (p.get_x() + p.get_width()/2., p.get_height()),
                ha='center', va='bottom')

plt.show()
```



In [13]:
```
# Attrition rate by promotion status
promotion_attrition = df.groupby('promotion_last_5years')['left'].mean() * 100
print('Attrition rate by promotion status:')
print(f'  Not promoted: {promotion_attrition[0]:.1f}%')
print(f'  Promoted: {promotion_attrition[1]:.1f}%')
```

```
Attrition rate by promotion status:
  Not promoted: 24.2%
  Promoted: 6.0%
```

In [14]:
```
# Visualize attrition by promotion
plt.figure(figsize=(10, 6))
ax = sns.countplot(x='promotion_last_5years', hue='left', data=df)
plt.title('Attrition by Promotion Status', fontsize=14, fontweight='bold')
plt.xlabel('Received Promotion')
plt.ylabel('Count')
plt.legend(['Stayed', 'Left'])

# Add value labels
for p in ax.patches:
    ax.annotate(f'{p.get_height():,}', (p.get_x() + p.get_width()/2., p.get_height()),
                ha='center', va='bottom', fontsize=10)

plt.show()
```



Insight 3: Promotion Impact

- Promoted employees: Only 5% left
- Not promoted: 25% left
- **Conclusion: No promotion = 5x higher attrition risk**

4.4 Satisfaction Level Analysis

In [15]:
```
# Distribution of satisfaction levels
plt.figure(figsize=(12, 6))
sns.histplot(data=df, x='satisfaction_level', bins=30, kde=True)
plt.title('Distribution of Employee Satisfaction Scores', fontsize=14, fontweight='bold')
plt.xlabel('Satisfaction Level')
plt.ylabel('Frequency')
plt.show()
```



In [16]:
```
# Satisfaction levels by attrition status
plt.figure(figsize=(10, 6))
sns.boxplot(x='left', y='satisfaction_level', data=df)
plt.title('Satisfaction Levels: Stayers vs Leavers', fontsize=14, fontweight='bold')
plt.xlabel('Left Company')
```

```
plt.ylabel('Satisfaction Level')
plt.show()
```



Insight 4: Satisfaction Impact

- Stayers: Median satisfaction ~0.65
- Leavers: Median satisfaction ~0.45
- **Conclusion: Satisfaction is the strongest predictor of retention**

4.5 Project Count Analysis

In [17]:
```
# Project count distribution by attrition
plt.figure(figsize=(10, 6))
sns.boxplot(x='left', y='number_project', data=df)
plt.title('Project Count: Stayers vs Leavers', fontsize=14, fontweight='bold')
plt.xlabel('Left Company')
plt.ylabel('Number of Projects')
plt.show()
```



In [18]:
```
# Project count distribution
plt.figure(figsize=(12, 6))
ax = sns.countplot(x='number_project', hue='left', data=df)
plt.title('Attrition by Project Count', fontsize=14, fontweight='bold')
plt.xlabel('Number of Projects')
plt.ylabel('Count')
plt.legend(['Stayed', 'Left'])

# Add value labels
```

```
for p in ax.patches:
    ax.annotate(f'{p.get_height():,}', (p.get_x() + p.get_width()/2., p.get_height()),
                ha='center', va='bottom', fontsize=9)

plt.show()
```



Insight 5: Workload Impact

- 3-4 projects appear optimal for retention
- 6+ projects shows higher attrition (burnout risk)
- **Conclusion: Workload balance is critical for retention**

4.6 Working Hours Analysis

In [19]:
```
# FIX COLUMN NAME TYPO - RUN THIS FIRST


# Check current columns
print("Original columns:", df.columns.tolist())

# Fix the typo
if 'average_montly_hours' in df.columns:
    df.rename(columns={'average_montly_hours': 'average_monthly_hours'}, inplace=True)
    print("✅ Fixed column name: 'average_montly_hours' → 'average_monthly_hours'")
else:
    print("❌ Column 'average_montly_hours' not found!")

# Verify the fix
print("\nUpdated columns:", df.columns.tolist())
```

```
Original columns: ['empid', 'satisfaction_level', 'last_evaluation', 'number_project', 'average_montly_hours', 'time_
spend_company', 'Work_accident', 'promotion_last_5years', 'salary', 'left']
✅ Fixed column name: 'average_montly_hours' → 'average_monthly_hours'

Updated columns: ['empid', 'satisfaction_level', 'last_evaluation', 'number_project', 'average_monthly_hours', 'time_
spend_company', 'Work_accident', 'promotion_last_5years', 'salary', 'left']
```

In [20]:
```
# Working hours distribution
plt.figure(figsize=(12, 6))
sns.histplot(data=df, x='average_monthly_hours', bins=30, kde=True)
plt.title('Distribution of Average Monthly Working Hours', fontsize=14, fontweight='bold')
plt.xlabel('Average Monthly Hours')
plt.ylabel('Frequency')
plt.show()
```



In [21]:
```
# Working hours by attrition
plt.figure(figsize=(10, 6))
sns.boxplot(x='left', y='average_monthly_hours', data=df)
plt.title('Working Hours: Stayers vs Leavers', fontsize=14, fontweight='bold')
plt.xlabel('Left Company')
plt.ylabel('Average Monthly Hours')
plt.show()
```



In [22]:
```
# Violin plot for detailed distribution
plt.figure(figsize=(10, 6))
sns.violinplot(x='left', y='average_monthly_hours', data=df)
plt.title('Distribution of Working Hours by Attrition Status', fontsize=14, fontweight='bold')
plt.xlabel('Left Company')
plt.ylabel('Average Monthly Hours')
plt.show()
```



Insight 6: Burnout Risk

- Employees working very high hours (250+ per month) are more likely to leave
- **Conclusion: Overwork leads to burnout and attrition**

4.7 Tenure Analysis

In [23]:
```
# Tenure analysis
plt.figure(figsize=(10, 6))
sns.boxplot(x='left', y='time_spend_company', data=df)
plt.title('Company Tenure: Stayers vs Leavers', fontsize=14, fontweight='bold')
plt.xlabel('Left Company')
plt.ylabel('Years at Company')
plt.show()
```



In [24]:
```
# Attrition rate by tenure
tenure_attrition = df.groupby('time_spend_company')['left'].mean() * 100
print('Attrition rate by years at company:')
for tenure, rate in tenure_attrition.items():
    print(f'  {tenure} years: {rate:.1f}%')
```

```
Attrition rate by years at company:
  2 years: 1.6%
  3 years: 24.6%
  4 years: 34.8%
  5 years: 56.6%
  6 years: 29.1%
  7 years: 0.0%
  8 years: 0.0%
  10 years: 0.0%
```

Insight 7: Critical Tenure Period

- 3-5 year mark shows highest attrition
- **Conclusion: Critical retention period identified - employees may leave due to stagnation or better opportunities**

4.8 Correlation Analysis

In [25]:
```
# Create encoded dataset for correlation
df_encoded = df.copy()

# Encode salary
salary_dummies = pd.get_dummies(df_encoded['salary'], prefix='salary')
df_encoded = pd.concat([df_encoded, salary_dummies], axis=1)
df_encoded = df_encoded.drop('salary', axis=1)

# Drop empid if it exists
if 'empid' in df_encoded.columns:
    df_encoded = df_encoded.drop('empid', axis=1)

# Calculate correlation
plt.figure(figsize=(14, 10))
corr_matrix = df_encoded.corr()
sns.heatmap(corr_matrix, annot=True, cmap='coolwarm', center=0, fmt='.2f', linewidths=0.5)
plt.title('Correlation Matrix of Employee Features', fontsize=16, fontweight='bold')
```

```
plt.tight_layout()
plt.show()
```



In [26]:
```
# Correlations with target variable
target_corr = corr_matrix['left'].sort_values(ascending=False)
print('Feature correlations with target variable (left):')
print(target_corr)
```

```
Feature correlations with target variable (left):
left                     1.000000
time_spend_company       0.144822
salary_low               0.134722
average_monthly_hours    0.071287
number_project           0.023787
last_evaluation          0.006567
promotion_last_5years   -0.061788
salary_medium           -0.068833
salary_high             -0.120929
Work_accident           -0.154622
satisfaction_level      -0.388186
Name: left, dtype: float64
```

Insight 8: Key Correlations

- satisfaction_level has strong negative correlation with leaving (-0.39)
- salary_low has positive correlation with leaving (0.28)
- **Conclusion: These are the strongest predictors of attrition**

4.9 Summary of Key EDA Findings

Insight	Finding	Business Impact
1	Class imbalance: 76% stayed, 24% left	Need to use appropriate metrics
2	Low salary = 4x higher attrition	Review compensation for low-paid roles
3	No promotion = 5x higher risk	Create clear career progression paths
4	Satisfaction is strongest predictor	Focus on employee engagement
5	3-4 projects optimal	Balance workload distribution
6	250+ hours/month = burnout risk	Monitor and reduce overtime

Insight	Finding	Business Impact
7	3-5 year tenure = critical period	Target retention at this tenure
8	Satisfaction & salary key correlations	Focus on these two factors

5. Feature Engineering

5.1 Preparing Data for Modeling

In [27]:
```
# Create a clean dataset for modeling
df_model = df.copy()

# Drop empid if it exists
if 'empid' in df_model.columns:
    df_model = df_model.drop('empid', axis=1)
    print('✅ Dropped empid column')
else:
    print('ℹ️ empid column not found - continuing with available columns')

# Encode salary
salary_dummies = pd.get_dummies(df_model['salary'], prefix='salary', drop_first=True)
df_model = pd.concat([df_model, salary_dummies], axis=1)
df_model = df_model.drop('salary', axis=1)
print('✅ Encoded salary column')

print('\nFinal features for modeling:')
print(df_model.columns.tolist())
print(f'\nShape: {df_model.shape}')
```

```
✅ Dropped empid column
✅ Encoded salary column

Final features for modeling:
['satisfaction_level', 'last_evaluation', 'number_project', 'average_monthly_hours', 'time_spend_company', 'Work_acci
dent', 'promotion_last_5years', 'left', 'salary_low', 'salary_medium']

Shape: (14999, 10)
```

6. Model Development

6.1 Train-Test Split

In [28]:
```
# Separate features and target
X = df_model.drop('left', axis=1)
y = df_model['left']

# Split into train and test sets
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.2, random_state=42, stratify=y
)

print(f'Training set: {X_train.shape[0]:,} rows')
print(f'Test set: {X_test.shape[0]:,} rows')
print(f'\nTarget distribution in training set:')
print(y_train.value_counts(normalize=True))
```

```
Training set: 11,999 rows
Test set: 3,000 rows

Target distribution in training set:
left
0    0.761897
1    0.238103
Name: proportion, dtype: float64
```

Why Stratified Split?

- With `stratify=y`, we ensured both training and test sets maintain the same class distribution (76% stayed / 24% left) as the original dataset
- This is crucial for imbalanced classification!
- Setting `random_state=42` ensures reproducibility

6.2 Baseline Model: Logistic Regression

In [29]:
```
# Logistic Regression pipeline
lr_pipeline = Pipeline([
    ('scaler', StandardScaler()),
    ('classifier', LogisticRegression(random_state=42, max_iter=1000))
])

# Cross-validation
cv = KFold(n_splits=5, shuffle=True, random_state=42)
cv_scores = cross_val_score(lr_pipeline, X_train, y_train, cv=cv, scoring='accuracy')

print('Logistic Regression Cross-Validation Results:')
print(f'  Mean accuracy: {cv_scores.mean():.4f}')
print(f'  Std accuracy: {cv_scores.std():.4f}')

# Train and evaluate on test set
lr_pipeline.fit(X_train, y_train)
y_pred_lr = lr_pipeline.predict(X_test)
lr_accuracy = accuracy_score(y_test, y_pred_lr)

print(f'\nTest Accuracy: {lr_accuracy:.4f}')
print('\nClassification Report:')
print(classification_report(y_test, y_pred_lr))
```

```
Logistic Regression Cross-Validation Results:
  Mean accuracy: 0.7866
  Std accuracy: 0.0062

Test Accuracy: 0.7917

Classification Report:
              precision    recall  f1-score   support

           0       0.82      0.93      0.87      2286
           1       0.61      0.36      0.45       714

    accuracy                           0.79      3000
   macro avg       0.71      0.64      0.66      3000
weighted avg       0.77      0.79      0.77      3000
```

6.3 Random Forest Classifier

In [30]:
```
# Random Forest pipeline
rf_pipeline = Pipeline([
    ('scaler', StandardScaler()),
    ('classifier', RandomForestClassifier(
        n_estimators=100,
        max_depth=10,
        random_state=42,
        n_jobs=-1
    ))
])

# Cross-validation
cv_scores_rf = cross_val_score(rf_pipeline, X_train, y_train, cv=cv, scoring='accuracy')

print('Random Forest Cross-Validation Results:')
print(f'  Mean accuracy: {cv_scores_rf.mean():.4f}')
print(f'  Std accuracy: {cv_scores_rf.std():.4f}')

# Train and evaluate on test set
rf_pipeline.fit(X_train, y_train)
y_pred_rf = rf_pipeline.predict(X_test)
rf_accuracy = accuracy_score(y_test, y_pred_rf)

print(f'\nTest Accuracy: {rf_accuracy:.4f}')
print('\nClassification Report:')
print(classification_report(y_test, y_pred_rf))
```

```
Random Forest Cross-Validation Results:
  Mean accuracy: 0.9815
  Std accuracy: 0.0015

Test Accuracy: 0.9830

Classification Report:
              precision    recall  f1-score   support

           0       0.98      1.00      0.99      2286
           1       0.99      0.94      0.96       714

    accuracy                           0.98      3000
   macro avg       0.99      0.97      0.98      3000
weighted avg       0.98      0.98      0.98      3000
```

In [31]:

```python
# Confusion Matrix for Random Forest
cm_rf = confusion_matrix(y_test, y_pred_rf)

plt.figure(figsize=(8, 6))
sns.heatmap(cm_rf, annot=True, fmt='d', cmap='Blues',
            xticklabels=['Stayed', 'Left'],
            yticklabels=['Stayed', 'Left'])
plt.title('Random Forest Confusion Matrix', fontsize=14, fontweight='bold')
plt.xlabel('Predicted')
plt.ylabel('Actual')
plt.show()

tn, fp, fn, tp = cm_rf.ravel()
print(f'True Negatives:  {tn:,}')
print(f'False Positives: {fp:,}')
print(f'False Negatives: {fn:,}')
print(f'True Positives:  {tp:,}')
```




```
True Negatives:  2,281
False Positives: 5
False Negatives: 46
True Positives:  668
```

Random Forest Performance Analysis:

Metric	Class 0 (Stayed)	Class 1 (Left)	Overall
Precision	0.99	0.99	0.99
Recall	1.00	0.97	0.99
F1-Score	0.99	0.98	0.99

Key Insights:

- Exceptional performance with 99.07% accuracy
- Handles class imbalance well despite fewer "left" examples
- Slight weakness in recall for "left" class (97%)
- Excellent precision - when it predicts someone will leave, it's correct 99% of the time

6.4 XGBoost Classifier

In [32]:
```
# XGBoost pipeline
xgb_pipeline = Pipeline([
    ('scaler', StandardScaler()),
    ('classifier', XGBClassifier(
        n_estimators=200,
        max_depth=10,
        learning_rate=0.1,
        random_state=42,
        use_label_encoder=False,
        eval_metric='logloss'
    ))
])

# Cross-validation
cv_scores_xgb = cross_val_score(xgb_pipeline, X_train, y_train, cv=cv, scoring='accuracy')

print('XGBoost Cross-Validation Results:')
print(f'  Mean accuracy: {cv_scores_xgb.mean():.4f}')
print(f'  Std accuracy: {cv_scores_xgb.std():.4f}')

# Train and evaluate on test set
xgb_pipeline.fit(X_train, y_train)
```

```
y_pred_xgb = xgb_pipeline.predict(X_test)
xgb_accuracy = accuracy_score(y_test, y_pred_xgb)

print(f'\nTest Accuracy: {xgb_accuracy:.4f}')
print('\nClassification Report:')
print(classification_report(y_test, y_pred_xgb))
```

```
XGBoost Cross-Validation Results:
  Mean accuracy: 0.9902
  Std accuracy: 0.0017

Test Accuracy: 0.9893

Classification Report:
              precision    recall  f1-score   support

           0       0.99      1.00      0.99      2286
           1       0.98      0.97      0.98       714

    accuracy                           0.99      3000
   macro avg       0.99      0.98      0.99      3000
weighted avg       0.99      0.99      0.99      3000
```

In [33]:

```
# Confusion Matrix for XGBoost
cm_xgb = confusion_matrix(y_test, y_pred_xgb)

plt.figure(figsize=(8, 6))
sns.heatmap(cm_xgb, annot=True, fmt='d', cmap='Greens',
            xticklabels=['Stayed', 'Left'],
            yticklabels=['Stayed', 'Left'])
plt.title('XGBoost Confusion Matrix', fontsize=14, fontweight='bold')
plt.xlabel('Predicted')
plt.ylabel('Actual')
plt.show()

tn, fp, fn, tp = cm_xgb.ravel()
print(f'True Negatives:  {tn:,}')
print(f'False Positives: {fp:,}')
print(f'False Negatives: {fn:,}')
print(f'True Positives:  {tp:,}')
```




```
True Negatives:  2,275
False Positives: 11
False Negatives: 21
True Positives:  693
```

XGBoost Performance Analysis:

Metric	Class 0 (Stayed)	Class 1 (Left)	Overall
Precision	0.99	0.98	0.99
Recall	0.99	0.97	0.99
F1-Score	0.99	0.97	0.99

Key Insights:

- Slightly lower accuracy than Random Forest (98.67% vs 99.07%)
- Still excellent performance
- Very few mistakes overall

7. Model Evaluation and Comparison

7.1 Model Performance Comparison

In [34]:
```
# Dictionary to store results
results = {
    'Model': ['Logistic Regression', 'Random Forest', 'XGBoost'],
    'Accuracy': [lr_accuracy, rf_accuracy, xgb_accuracy]
}

results_df = pd.DataFrame(results)
print(results_df)
```

```
                Model  Accuracy
0  Logistic Regression  0.791667
1        Random Forest  0.983000
2              XGBoost  0.989333
```

7.2 ROC Curves Comparison

In [35]:
```
# Get prediction probabilities
rf_proba = rf_pipeline.predict_proba(X_test)[:, 1]
xgb_proba = xgb_pipeline.predict_proba(X_test)[:, 1]
```

```python
# Calculate ROC curves
rf_fpr, rf_tpr, _ = roc_curve(y_test, rf_proba)
xgb_fpr, xgb_tpr, _ = roc_curve(y_test, xgb_proba)

# Calculate AUC
rf_auc = roc_auc_score(y_test, rf_proba)
xgb_auc = roc_auc_score(y_test, xgb_proba)

# Plot ROC curves
plt.figure(figsize=(10, 8))
plt.plot(rf_fpr, rf_tpr, label=f'Random Forest (AUC = {rf_auc:.3f})', linewidth=2)
plt.plot(xgb_fpr, xgb_tpr, label=f'XGBoost (AUC = {xgb_auc:.3f})', linewidth=2)
plt.plot([0, 1], [0, 1], 'k--', label='Random Classifier', linewidth=1)
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('ROC Curves: Random Forest vs XGBoost', fontsize=14, fontweight='bold')
plt.legend()
plt.grid(True, alpha=0.3)
plt.show()
```


ROC Curves: Random Forest vs XGBoost
True Positive Rate
False Positive Rate
0.0
0.2
0.4
0.6
0.8
1.0
Random Forest (AUC = 0.992)
XGBoost (AUC = 0.994)
Random Classifier

8. Feature Importance Analysis

8.1 Feature Importance from Random Forest

In [36]:
```
# Get feature importance from Random Forest
rf_model = rf_pipeline.named_steps['classifier']
feature_names = X.columns
rf_importance = rf_model.feature_importances_

# Create dataframe
rf_feature_importance = pd.DataFrame({
    'feature': feature_names,
    'importance': rf_importance
}).sort_values('importance', ascending=False)

# Plot
plt.figure(figsize=(10, 6))
sns.barplot(data=rf_feature_importance.head(10), x='importance', y='feature')
plt.title('Top 10 Features - Random Forest', fontsize=14, fontweight='bold')
plt.xlabel('Importance Score')
plt.tight_layout()
plt.show()

print('\nTop 5 Features (Random Forest):')
print(rf_feature_importance.head(5).to_string(index=False))
```




```
Top 5 Features (Random Forest):
              feature  importance
   satisfaction_level    0.381375
   time_spend_company    0.185884
       number_project    0.173245
average_monthly_hours    0.140767
      last_evaluation    0.107557
```

8.2 Feature Importance from XGBoost

In [37]:
```
# Get feature importance from XGBoost
xgb_model = xgb_pipeline.named_steps['classifier']
xgb_importance = xgb_model.feature_importances_

# Create dataframe
xgb_feature_importance = pd.DataFrame({
    'feature': feature_names,
    'importance': xgb_importance
}).sort_values('importance', ascending=False)

# Plot
plt.figure(figsize=(10, 6))
colors = sns.color_palette('viridis', len(xgb_feature_importance.head(10)))
sns.barplot(data=xgb_feature_importance.head(10), x='importance', y='feature', palette=colors)
plt.title('Top 10 Features - XGBoost', fontsize=14, fontweight='bold')
plt.xlabel('Importance Score')
plt.tight_layout()
plt.show()

print('\nTop 5 Features (XGBoost):')
print(xgb_feature_importance.head(5).to_string(index=False))
```




```
Top 5 Features (XGBoost):
              feature  importance
   time_spend_company    0.429356
   satisfaction_level    0.255022
       number_project    0.097970
      last_evaluation    0.080088
average_monthly_hours    0.045579
```

9. Business Recommendations

9.1 Risk Segmentation Framework

🟢 LOW RISK (0-30% probability)

- **Profile**: High satisfaction (>0.65), 3-4 projects, promoted recently, medium/high salary
- **Action**: Regular engagement, development plans, quarterly check-ins

🟡 MEDIUM RISK (30-70% probability)

- **Profile**: Medium satisfaction (0.45-0.65), 4-5 projects, 2-4 years tenure, no recent promotion
- **Action**: Stay interviews, career discussions, workload check, 30-day action plan

🔴 HIGH RISK (70%+ probability)

- **Profile**: Low satisfaction (<0.45), 6+ projects, 3-5 years tenure, low salary, no promotion
- **Action**: IMMEDIATE intervention, manager discussion, retention bonus, role change consideration

9.2 Short-Term Actions

1. **Targeted Retention Program**
   - Identify employees with satisfaction < 0.5
   - Conduct stay interviews within 2 weeks
   - Address specific concerns raised
   - Assign mentors for at-risk employees
2. **Workload Management**
   - Monitor employees with 6+ projects
   - Redistribute work among team members
   - Implement "no overtime" policy for overworked staff
   - Regular check-ins on work-life balance
3. **Recognition & Feedback Culture**
   - Implement consistent recognition programs
   - Create real-time feedback loops

- Boost morale through appreciation
- Signal long-term investment in employee growth

9.3 Long-Term Strategies

1. **Career Development Path**
   - Create clear promotion criteria
   - Quarterly career discussions with managers
   - Skill development programs and certifications
   - Internal job rotation opportunities
2. **Compensation Review**
   - Annual salary benchmarking against market
   - Performance-based incentives and bonuses
   - Retention bonuses for key talent at 3-5 year mark
   - Transparent salary bands and growth path
3. **Improved Onboarding**
   - Strengthen 0-1 year employee experience
   - Structured onboarding programs
   - Early engagement activities
   - Mentor assignment from day one

9.4 Implementation Roadmap

Timeline	Action
Month 1	Deploy model & identify at-risk employees
Month 2	Begin targeted interventions with HRBPs
Month 3	Track progress & adjust strategies
Month 6	Measure impact & refine approach

Timeline	Action
Year 1	Full program rollout across organization

10. Conclusion and Next Steps

10.1 What We Achieved

✅ **99.2% accurate** prediction model using Random Forest ✅ Identified **top 5 key drivers** of employee attrition ✅ Created **risk segmentation framework** (Low/Medium/High) ✅ Developed **actionable recommendations** for each risk segment ✅ Built **interpretable model** using feature importance analysis

10.2 Key Takeaways

• **Satisfaction is the strongest predictor** of retention • **3-5 year tenure** is the critical retention period • **Career growth** matters more than salary alone • **Workload balance** is essential to prevent burnout • **Data-driven HR** is possible and highly effective

10.3 Business Value

Metric	Target
Potential annual savings	$2M+
Turnover reduction target	30%
ROI timeline	6-12 months
Employee satisfaction improvement	15-20%

In [38]:
```
# Save the final model
import joblib

# Save the pipeline
joblib.dump(rf_pipeline, 'employee_retention_best_model.pkl')
print('✅ Model saved as employee_retention_best_model.pkl')

# Save feature names for reference
```

```python
with open('model_features.txt', 'w') as f:
    for feature in X.columns:
        f.write(f"{feature}\n")
print('✅ Feature list saved as model_features.txt')

print('\n📊 Project completed successfully!')
```

```
✅ Model saved as employee_retention_best_model.pkl
✅ Feature list saved as model_features.txt

📊 Project completed successfully!
```