

The Axona Programmer Guide

Build apps that have no server. (*kernel 4.11.2 · testnet*)

You're about to build something unusual: an application with no backend. No database to stand up, no message broker to rent, no API keys, nothing to deploy before your first user shows up. Your users' browsers and devices *are* the infrastructure — they find each other, carry each other's messages, and keep the whole thing alive.

This guide is for application programmers. You do not need to know how distributed hash tables work, and this guide will not make you learn. (If the machinery genuinely interests you, it's all in Under the hood at the end — strictly optional.)

Companions:

- Quick Start — a working roundtrip in 5 minutes. Do it first.
- API Reference — every signature, exactly.
- AI Grounding — building with an AI assistant? Hand it this file.
- Services Guide — running bridges and relays (you can skip this for a long time).

Building with an AI? Most Axona apps are. Paste Axona-AI-Grounding-v4.11.2.md into your assistant's context and it will know every rule in this guide. Keep this guide for *you* — it explains the why.

Table of contents

1. The five ideas
2. First contact
3. Idea by idea, gently
4. Recipes
5. Things that will bite you
6. Errors, when they happen
7. Limits worth knowing
8. Going live
9. Under the hood (*optional*)
10. Appendix: what's coming, and migrating from older lines

1. The five ideas

Everything you'll ever do with Axona is a combination of five ideas. Here they are in full; the rest of this guide is elaboration.

1. **A peer.** Your app running, connected to the network. It has a *connection identity* minted fresh each run — think of it as the seat your app happens to be sitting in today.
2. **An author.** A signing key that says *who wrote this*. It has no location, works from any device, and is the only thing worth saving to disk. If your app has “users,” an author key is a user.

3. **A topic.** A place messages go. Not a string — a small object: `{ region: 'useast', name: 'lobby' }`. Anyone who writes the same fields gets the same place. No registration, no server assigning channels: shared fields *are* the rendezvous.
4. **Publish.** Send a message to a topic, signed by an author: `peer.pub(topic, message, { signWith: author })`.
5. **Subscribe.** Receive a topic's messages, live and (if you ask) recent history: `peer.sub(topic, handler, { since: 'all' })`.

That's the protocol. Chat, feeds, presence, file sharing, multiplayer state, agent-to-agent traffic — they're all arrangements of these five.

2. First contact

If you haven't run the Quick Start, do it now — five minutes, a real message through the real network. The heart of it:

```
// after the peer assembly (Quick Start step 4, reproduced in §3.1 below)
await peer.ready(); // wait for the mesh

const TOPIC = { region: 'useast', name: 'quick-start-demo' };

await peer.sub(TOPIC, (env) => {
  console.log('[recv]', env.message);
}, { since: 'all' });

await peer.pub(TOPIC, 'hello, everyone', { signWith: author });
```

You publish; the network routes it; everyone subscribed — including you — receives it. That echo of your own message is not an accident, and you'll learn to love it (§5, “There is no ack”).

3. Idea by idea, gently

3.1 The peer — your seat at the table

A peer is assembled from a few kernel pieces and pointed at a *bridge* — the meeting point where peers first find each other (after that, they talk directly). This is the one ceremonial block in every Axona app; paste it and move on:

```
import {
  AxonaPeer, AxonaDomain, NeuronNode,
  createNodeIdentity, createAuthorIdentity,
} from '@axona/protocol';
import { webTransport } from '@axona/protocol/transport/web/index.js';

const BRIDGE = 'wss://testnet.axona.net';
const HERE = { lat: 38.0, lng: -77.0 }; // the user's real location
```

```

const nodeIdentity = await createNodeIdentity(HERE);
const author      = await createAuthorIdentity({ persistAs: 'myapp:author' });

const transport = webTransport({ bridgeUrl: BRIDGE, identity: nodeIdentity });
const node      = new NeuronNode({ id: BigInt('0x' + nodeIdentity.id),
                                   lat: HERE.lat, lng: HERE.lng });
node.transport = transport;
const peer = new AxonaPeer({ domain: new AxonaDomain({ k: 20 }),
                           node, nodeIdentity, transport });

await transport.start(nodeIdentity.id);
await peer.start();
await peer.ready();           // resolves when the mesh is warm (~a few seconds)

```

Getting shorter soon. The next kernel release collapses this whole block into one call — `const { peer, author } = await connect({ bridge, location })`. Until it reaches testnet, the block above is the way.

Why the location? Axona is geographic: the first byte of every address is a region of the Earth, and traffic for a region's topics stays among that region's peers. Your user in Virginia is a `useast` peer; their local topics never detour through Frankfurt.

The connection identity is deliberately disposable — fresh each run, like a dynamic IP. Don't save it, don't display it, don't build on it. The thing with a lifespan is:

3.2 The author — the only key you keep

```

const author = await createAuthorIdentity({ persistAs: 'myapp:author' });

```

An author is an Ed25519 keypair. Its public half — `author.authorId` — is what other people recognize: it appears (as `signerPubkey`) on every message it signs, from any device, from any location, forever. Persist it (`persistAs` uses `localStorage` in the browser) and your user has a stable identity across sessions. Skip `persistAs` and you have a throwaway persona — also sometimes exactly what you want. One app can hold several authors at once (work self, home self, bot self).

There's no account creation, no email verification, no password reset — because there's no one to reset it *with*. The key is the identity. That's liberating and unforgiving in equal measure: lose the key, lose the identity. Persist it.

3.3 The topic — an address you compute, not a channel you create

```

const lobby = { region: 'useast', name: 'lobby' };           // anyone writes
const feed  = { region: 'useast', owner: me.authorId, name: 'posts' }; // only I write
const inbox = { region: 'useast', owner: me.authorId, name: 'inbox', write: 'open' }; //
↪ anyone writes TO me

```

Those three shapes cover a startling share of application design:

- **The open room** (`{ region, name }`) — a chat, a game lobby, a public firehose. Anyone who knows the fields can read and write.
- **The owned feed** (`owner` present; `write` defaults to `'owner'`) — a blog, a profile, a bot's announcements. Everyone can read; only the owner's key can write, and the *network itself* enforces that — a forged post is refused by the peers storing the topic, not just by polite clients.
- **The inbox** (`owner + write: 'open'`) — messages *to* someone. Anyone writes; the owner's app reads.

Two rules keep topic bugs out of your life. First, **publisher and subscriber must use identical fields** — the topic ID is a hash of them, so `{ region: 'useast', name: 'lobby' }` and `{ name: 'lobby' }` are different places (the second defaulted its region to wherever the publisher happened to be). Centralize your descriptors in one function and call it from both sides. Second, **prefer naming the region explicitly** for anything two differently-located users must both find.

Need a shareable read handle? `await deriveTopicId(topic)` returns the 66-hex ID; `sub` and `pull` accept it directly.

3.4 Publish — signed, fire-and-forget, and that's a feature

```
const msgId = await peer.pub(topic, { text: 'shipped it' }, { signWith: author });
```

The message is any JSON-serializable value. The signature travels with it; every receiver verifies it before your handler ever sees it. The returned `msgId` is a *content address* — a hash of `author + payload` — which buys you two elegant behaviors free of charge: publishing the identical thing twice doesn't duplicate (it refreshes), and any message can later be fetched or retracted by its id.

To publish anonymously, say so out loud: `{ signWith: ANONYMOUS }`. Forgetting `signWith` entirely is an error — Axona never guesses who's speaking.

And no, there is no delivery callback. See §5 for why that's a feature and what to do instead (spoiler: you're already subscribed — watch your own message arrive).

3.5 Subscribe — live tail, with as much history as you ask for

```
const sub = await peer.sub(topic, (env) => {
  if (env.deleted) return removeFromUI(env.msgId);           // a retraction marker
  render(env.message, env.signerPubkey);                     // verified author (or undefined)
}, { since: 'all' });
```

The `since` option is your replay dial:

since	You receive
<i>(omitted)</i>	live messages only, from now
'latest'	the newest cached message, then live
'all'	recent history (the cached queue, ~24 h), then live
1719954000000	everything newer than that timestamp, then live

Deliveries are exactly-once per message per subscriber — the kernel dedups by `msgId`, so you never write defensive “have I seen this?” code. `sub.stop()` ends one subscription; `peer.unsub(topic)` ends all of yours for that topic.

4. Recipes

Real shapes, ready to lift. Each assumes the assembled `peer` and `author` from §3.1.

4.1 A chat room

```
const room = (name) => ({ region: 'useast', name: `chat:${name}` });

async function join(name, onMessage) {
  return peer.sub(room(name), (env) => {
    if (env.deleted) return;
    onMessage({ text: env.message.text,
                  from: (env.signerPubkey ?? 'anon').slice(0, 8),
                  at:   env.ts });
  }, { since: 'all' });    // newcomers see recent history
}

async function say(name, text) {
  return peer.pub(room(name), { text }, { signWith: author });
}
```

That’s a chat app. History for late joiners, live tail for everyone, authorship on every line — and notice what’s missing: no room creation step. The first person to publish *is* the room springing into existence.

4.2 A personal feed (and reading someone else’s)

```
const myFeed = { region: 'useast', owner: author.authorId, name: 'posts' };

await peer.pub(myFeed, { title: 'First post', body: '...' }, { signWith: author });
```

Only your key can write it — enforced by the network, not by convention. For a friend to read your feed they need two facts: your `authorId` and the region you keep it in. Publish those anywhere (a QR code, an inbox message, a chat), then:

```
const theirFeed = { region: 'useast', owner: theirAuthorId, name: 'posts' };
await peer.sub(theirFeed, (env) => renderPost(env.message), { since: 'all' });
```

4.3 An inbox

```
const inboxOf = (authorId) => ({ region: 'useast', owner: authorId, name: 'inbox', write:
  ↪ 'open' });
```

```
// anyone sends:
await peer.pub(inboxOf(theirAuthorId), { from: author.authorId, text: 'hi!' },
  { signWith: author });
// the owner reads:
await peer.sub(inboxOf(author.authorId), (env) => showDM(env.message), { since: 'all' });
```

The envelope's `signerPubkey` tells the owner who *really* sent each message (the `from` field inside the payload is just a courtesy copy — trust the signature, display the field).

4.4 Who's here? (presence)

```
const presence = { region: 'useast', name: 'myapp:presence' };
const here = new Map(); // authorId -> last heartbeat

setInterval(() => peer.pub(presence, { at: Date.now() }, { signWith: author }), 30_000);

await peer.sub(presence, (env) => {
  if (env.signerPubkey) here.set(env.signerPubkey, env.ts);
});
// online = heartbeat within the last ~90s
const online = [...here].filter(([, t]) => Date.now() - t < 90_000);
```

Presence is just a topic everyone heartbeats into. Messages age out of the cache on their own; nobody cleans up.

4.5 Taking it back (kill)

```
const msgId = await peer.pub(room('general'), { text: 'typo galore' }, { signWith: author });
await peer.kill(room('general'), msgId, { signWith: author }); // same author key!
```

Every subscriber's handler receives `{ deleted: true, msgId }` — drop it from your UI. Honesty clause: retraction is cooperative, not magical. A device that already displayed the message has, well, displayed it. And an anonymous message can never be killed — no key, no proof it's yours.

4.6 Sharing files (std/chunk)

Single publishes over ~15 KB are unreliable on real browser channels, so don't send big payloads — chunk them. The kernel ships the helper:

```
import { publishChunkedBytes, receiveChunkedBytes } from '@axona/protocol/std/chunk.js';

const drop = { region: 'useast', name: 'myapp:drops' };

await publishChunkedBytes(peer, fileBytes /* Uint8Array */, {
  topic: drop, signWith: author,
  meta: { filename: 'demo.png', mime: 'image/png' },
});
```

```
await receiveChunkedBytes(peer, drop, {
  onComplete: ({ bytes, meta }) => showImage(bytes, meta),
  onProgress: ({ received, total }) => bar.set(received / total),
});
```

4.7 Direct messages (device to device)

Pub/sub addresses *audiences*. To address one specific connected device:

```
peer.onMessage(async (fromNodeId, msg) => ({ pong: msg.ping })); // respond
const reply = await peer.send(someNodeId, { ping: 1 });          // RPC
peer.notify(someNodeId, { fyi: true });                          // fire-and-forget
```

Node IDs come from `peer.peers()` / `peer.onPeerJoin`. Remember: a node ID is a *session*, not a person — for person-to-person, use an inbox (§4.3).

4.8 How busy is this topic?

```
import { metricTopic, deriveTopicId } from '@axona/protocol';

const snap = await peer.metrics(topic); // one-shot { subscribers, current_count, ...
  ↪ }

await peer.sub(metricTopic(await deriveTopicId(topic)), (env) => {
  const m = JSON.parse(env.message);
  badge.textContent = `${m.subscribers} watching`;
}, { since: 'latest' }); // live-updating counter
```

Counts are advisory — decorate with them, never authorize with them.

4.9 Remembering your users

The complete persistence story for most apps is one line you've already written: `createAuthorIdentity({ persistAs: 'myapp:author' })`. Node identity? Re-mint each run. Subscriptions? Re-subscribe on startup (with `since`, you'll catch up on what you missed). Messages? The network holds the recent window; anything your app must keep beyond ~24 h, store like any other app data.

4.10 Playing nicely with other apps

Topics are shared space — another app can subscribe to your topic. If you want your messages legible to it (and its to you), use the standard body:

```
import { makeMessage, readMessage } from '@axona/protocol/std/message.js';

await peer.pub(topic, makeMessage('hello', { mood: 'sunny' }), { signWith: author });
const { text } = readMessage(env.message); // tolerant of other apps' shapes
```

4.11 If your author is a bot, say so

```
await peer.setAuthorClass('agent', { signWith: author, label: 'ticker-bot' });
```

A voluntary, signed declaration that this key is operated by software. Readers resolve it with `getAuthorClass(authorId)` and can badge, rank, or filter. It gates nothing — it’s honesty infrastructure, and well-behaved bots (and AI-built apps!) should use it.

5. Things that will bite you

Learn these five here rather than in production.

1. Two descriptors, one character apart, are two different topics. No error, no warning — just silence. The classic: publisher says { `region: 'useast', name: 'lobby'` }, subscriber says { `name: 'lobby'` } from a laptop in Berlin, and its defaulted region is `eucentral`. One shared `topics.js` with functions like `room(name)` ends this bug forever.

2. There is no ack — stop waiting for one. `pub()` resolves when the message is *sent*, not delivered, and no receipt ever comes (it would stitch your connection to your authorship — an identity leak Axona refuses on principle). The idiom: you’re subscribed to what you publish; when your own `msgId` comes back through your handler, it went through. The kernel meanwhile retries quietly on your behalf.

3. Publishing before `ready()` is a coin flip. The mesh takes a few seconds to warm after `start()`. `await peer.ready()` — that’s what it’s for. (Your first publish would *probably* survive anyway; the kernel bursts a newcomer’s first messages. “Probably” is not a UX.)

4. Messages are not rows. The network keeps a rolling ~24-hour window per topic, and open topics quota each author’s share of it. Build for a living stream: late joiners see recent history, not the archive. Need an archive? That’s your app’s job (and re-publishing refreshes a message you want kept warm).

5. 15 KB. Above it, real-world WebRTC channels start dropping frames even though the hard cap is 256 KB. `std/chunk` exists so you never think about this again.

6. Errors, when they happen

Everything the kernel throws is an `AxonaError` with a stable `.code` — switch on codes, not message text:

Code	You did	Do instead
<code>PUBLISH_NO_PUBLISH_IDENTITY</code>	pub without <code>signWith</code>	pass an author, or <code>ANONYMOUS</code> explicitly
<code>WRITE_POLICY_VIOLATION</code>	wrote to someone else’s owned topic	only the owner key writes; use their inbox
<code>TOPIC_REGION_REQUIRED</code>	derived an open topic with no region anywhere	name a <code>region</code>
<code>PUBLISH_PAYLOAD_T00_LARGE</code>	>256 KB publish	<code>std/chunk</code>

Code	You did	Do instead
KILL_SIGN_FAILED	killed with a different key	retract with the key that signed
WS close 4426	version mismatch with the bridge	reinstall the pinned kernel tag

Not errors, by design: `pull()` returning `null` (gone or never existed) and `kill()` resolving `{ ok: false }` (nothing to retract).

7. Limits worth knowing

Thing	Value
Reliable message size	15 KB (chunk above; 256 KB absolute)
Message lifetime	~24 h (48 h max; re-publish to refresh)
History for late joiners	the cached queue — recent, bounded, not forever
One author’s share of an open topic	quota-bounded (no flooding)
Clock skew tolerance on live publishes	±5 minutes (keep device clocks sane)

8. Going live

- **Point at the right network.** This guide’s line (4.x) runs on **testnet**: `wss://testnet.axona.net`. Production bridges run the older 3.x line and will refuse 4.x apps (close 4426) — match your kernel pin to your bridge.
- **HTTPS is mandatory** in the browser (`crypto.subtle`).
- **Surface your versions.** Show the kernel version somewhere findable (`KERNEL_VERSION` import) — future-you debugging a mixed fleet will be grateful.
- **Durability beyond browser tabs.** An app whose topics matter when no user is online wants a small always-on peer that `host()`s them — that’s a *relay*, a five-minute Node deployment. When you reach that point, the Services Guide is yours; not before.

9. Under the hood — optional

You can build everything above without this section. For the curious:

The mesh. Peers connect via a bridge (a meeting point, not a server — it relays introductions and can pass messages, but owns nothing), then directly to each other over WebRTC. Each peer maintains a small routing table; the network is navigable without anyone holding a map. It self-heals: dead connections are detected by heartbeat and routed around, no configuration, no ops.

The tree. Every topic ID is an address in the same space as peer IDs. The live peer *closest* to a topic’s address automatically becomes its **root** — the coordinator that stamps, caches, and fans out that topic’s messages. Nobody elects it; proximity appoints it. Popular topics grow a distribution

tree (the root delegates batches of subscribers to child relays), so no node ever serves more than a bounded number directly.

Durability. The root continuously copies its cache to the peers next in line; when a root vanishes (a laptop closes), a warm backup notices within a minute and takes over, and every subscriber’s periodic renewal re-attaches automatically. Your app sees, at worst, a brief pause. Your messages are also retried by your own peer until it observes them delivered. All of this is why the guide keeps saying *you don’t manage the network* — it manages itself, aggressively.

Regions. The first byte of every ID is one of 192 real geographic cells, so a region’s topics naturally live on that region’s peers — locality without a CDN. (A stricter mode, where a topic may *only* be served in its own region, is built and waiting for network density to justify switching on.)

The full story — with diagrams — is the Axona Architecture note.

10. Appendix

Coming soon

- **connect()** — the §3.1 assembly block as one call. Already in the kernel’s next release; this guide switches to it the moment it reaches testnet.

Migrating from the v2/v3 lines

Only relevant if you have code from early 2026. The v3 flag-day replaced `deriveIdentity` with the two factories, string topics with descriptors, and `publisher/sign:false` with per-publish `sign-with`; v4 changed nothing in the app API — it rebuilt reliability underneath (single-root axon trees, cohort replication, cold-publish burst, nearest-replica reads). `unpub` was removed and `touch` retired (re-publish to refresh a message instead). If a symbol you remember is missing from the API Reference, it didn’t survive v3 — the reference is the source of truth.