


P&D Electronics and Chipdesign GMSK100

Group 4:

- Jonas Bertels
- Jasper Depuydt
- Ruben Heyrman
- Ziyu Zhou

Midterm Presentation

Analog




- Variable gain amplifier: amplifies 1..100 mV input signal to desired level for ADC
- ADC: converts analog input to digital N-bit output
- $SNR = 6.02N + 1.76\text{dB}$
- Sampling at certain F_s

Variable Gain Amplifier


Specifications

- Input = 1..100mV, output = 500 mV
-> Closed Loop gain = 5..500



Solution 1.0


- Telescopic OTA
- 85 dB gain, 25 kHz BW
- Resistorbank feedback
- Gain = $-R_f/R_{in}$ (ideal)



Variable Gain Amplifier


Specifications

- Input = 1..100mV, output = 500 mV
-> Closed Loop gain = 5..500




Solution 2.0

- S&H amplifier
- Capacitorbank feedback
- Gain = $-C_1/C_2$ (ideal)
- $F_s = 60 \text{ kHz} (> 2 \times F_{in})$




Flash ADC

- 3-bit \rightarrow SNR = $6.02N + 1.76$ dB = 20 dB
- Thermometer code
- Mux-based decoder = easy to implement and small enough delay for Fs
- Resistor chain for Vref
- 7 StrongArm comparators (see next slide)
- Vref decoupled



StrongArm Comparator


- V_{in2} = input
- V_{in1} = V_{ref}
- Combines functionality of comparator and latch
- Capacitive load matching with inverters at X and Y




To do

- Design new OTA
- Implement S&H switchcap circuit
- Optimize ADC


Digital





Finding the perfect matched filter in Matlab




Matched filter pulse shape vs regular MSK




CORDIC:



VHDL: CORDIC ARCTAN ROTATE UNTIL (1,0)




If outside circle, mirror, possibly in combination with swapping x and y



Varicode is just a table lookup (big if else statement)

Symbol(s)	Char	Symbol(s)	Char	Symbol(s)	Char	Symbol(s)	Char
0	SPACE	0-29	@	0-30	~	0-31	=
1	a	1-29	A	1-30	1	1-31	[
2	b	2-29	B	2-30	2	2-31	\
3	c	3-29	C	3-30	3	3-31]
4	d	4-29	D	4-30	4	4-31	^
5	e	5-29	E	5-30	5	5-31	
6	f	6-29	F	6-30	6	6-31	{
7	g	7-29	G	7-30	7	7-31	
8	h	8-29	H	8-30	8	8-31	}
9	i	9-29	I	9-30	9	9-31	`
10	j	10-29	J	10-30	0	10-31	±
11	k	11-29	K	11-30	!	11-31	÷
12	l	12-29	L	12-30	quote	12-31	°
13	m	13-29	M	13-30	#	13-31	×
14	n	14-29	N	14-30	\$	14-31	£
15	o	15-29	O	15-30	%	15-31	
16	p	16-29	P	16-30	&	16-31	
17	q	17-29	Q	17-30		17-31	
18	r	18-29	R	18-30	(18-31	
19	s	19-29	S	19-30)	19-31	
20	t	20-29	T	20-30	*	20-31	
21	u	21-29	U	21-30	+	21-31	
22	v	22-29	V	22-30	-	22-31	
23	w	23-29	W	23-30	/	23-31	
24	x	24-29	X	24-30	:	24-31	
25	y	25-29	Y	25-30	;	25-31	
26	z	26-29	Z	26-30	<	26-31	
27	.	27-29	,	27-30	>	27-31	BS
28	CRLF	28-29	?	28-30	IDLE	28-31	DEL

Differentiator and matched filter via lattice ladder



Planning

		week 1	week 2	week 3	week 4	week 5	week 6	week 7	week 8		week 9	week 10	week 11	week 12		week 13	
Matlab simulations				FB moment						Midterm					Deadline	Final Presentation	
Incoherent detection w/ hardcoded f										Presentation					Report		
Clock Recovery										Presentation					Report		
Carrier Recovery																	
Convolutional codes																	
OTA design															Design		
Sample & Hold																	
Strongarm Comparator																	
Digital Encoder																	
Finish ADC																	
Integration																	
		12-Feb	19-Feb	26-Feb	4-Mar	11-Mar	18-Mar	25-Mar	1-Apr	3-Apr	22-Apr	29-Apr	6-May	13-May	17-May	20-May	