

Runbook — Deploy Fly GACA (superseded; pointer to the product-repo runbook)

SECTION 06-operations-it

TYPE runbook

STATUS **draft**

OWNER Founder

UPDATED 2026-08-19

[!WARNING] Retired 2026-08-19 — this runbook deployed a static, no-build PWA to **Firestore Hosting** with `firebase deploy --only hosting`. None of that exists any more: there is no Firebase project, no `firebase.json`, no `.firebaserc`, no `sw.js` version to bump by hand, and the `flygaca-firebase` project is deleted. Do not run a single command from the old version of this page.

What replaced it: a Vite build (`dist/`) published to a **Cloud Storage** bucket behind an **HTTPS load balancer**, with `/api/*` routed to an **Express 5 service on Cloud Run** backed by **Cloud SQL for PostgreSQL** — all in `me-central2` (Dammam).

Go to instead: `docs/RUNBOOK-deploy.md` in [ay2m/FlyGACA](#). That is the authoritative, maintained sequence — it lives with the code, so it cannot drift from the Dockerfile, the env vars or the migration runner. `../hosting-facts.md` is the one-page summary of what runs where.

Why this file still exists

`../hosting-facts.md` links here as the Office-side entry point for "how does this thing get deployed". It is a **signpost, not a mirror** — deliberately, because a copied deploy sequence in a documents repo goes stale the first time the Dockerfile changes.

The shape of a deploy, for orientation only

Step	Where it happens
Provision the project, Cloud SQL instance, OAuth client, Secret Manager entries	Google Cloud, once
Apply the schema	<code>server/migrations/</code> , via the forward-only migration runner
Deploy the API	<code>gcloud run deploy</code> from the repo root — prices and secrets are set on the revision
Publish the SPA	<code>npm run build</code> , then sync <code>dist/</code> to the bucket
Front it	HTTPS load balancer: bucket backend on <code>/*</code> , serverless NEG on <code>/api/*</code>

Step	Where it happens
Renewals	Cloud Scheduler → <code>POST /api/billing/renew</code> with <code>CRON_SECRET</code>
Payments	Moyasar webhook + the server-to-server confirm leg

Two things worth carrying in your head before you open the real runbook:

- **Cloud Run and Cloud SQL must be in the same region** — the service reaches the database over a Cloud SQL unix socket, so there is no IP allowlist and no proxy sidecar.
- **A price left unset is not a silent SAR 0** — the checkout kind fails loudly instead. Set every price you intend to sell.

There is no one-command deploy, and `npm run deploy` in the product repo deliberately fails with a pointer to the real runbook.

Pre-launch reminders that outlived the Firebase era

- The legal pages need Saudi counsel's review before a public announcement (see the lawyer brief in `02-legal/`).
- The GACAR / AIP redistribution position (P0-1) should be confirmed by counsel.
- Contact mailboxes route per `../02-legal/email-routing.md`.