

RUNBOOK — Cloudflare hosting

SECTION 06-operations-it

TYPE runbook

STATUS **active**

OWNER Founder

UPDATED 2026-06-16

Production hosting for `flygaca.com` is a **Cloudflare Worker** that serves the static site and proxies `/api/*` to the Firebase Cloud Functions. The backend (Captain Adel gateway, content, billing) **stays on Firebase me-central2** — the Worker never processes user questions or data, it only forwards the request, so the PDPL in-Kingdom posture is unchanged.

Pieces

File	Role
<code>wrangler.jsonc</code>	Worker config: name <code>flygaca</code> , <code>main</code> worker, <code>assets</code> = <code>./dist</code> , build hook.
<code>worker/index.js</code>	Routing (clean URLs + redirects), <code>/api/*</code> proxy, security headers/CSP.
<code>scripts/build-cloudflare.js</code>	Assembles <code>dist/</code> — the exact file set Firebase served (mirrors <code>firebase.json</code> <code>public</code> / <code>ignore</code>). Run by <code>npm run build:cloudflare</code> .
<code>firebase.json</code>	Retained for <code>firebase serve</code> (local dev) and as the rollback host. Keep its rewrites/redirects/headers in sync with <code>worker/index.js</code> .

`dist/` is generated (git-ignored) — never commit it.

Cloudflare project settings (one-time)

The **Workers Builds** Git integration deploys the `flygaca` Worker on every push. In the Cloudflare dashboard for the Worker:

- Build command:** `npm run build:cloudflare` (also wired as the `build` hook in `wrangler.jsonc`, so the default `npx wrangler deploy` triggers it).
- Deploy command:** `npx wrangler deploy` (default).
- Variables** (Settings → Variables) — set the two function endpoints:
 - `CHAT_FUNCTION_URL` → the deployed `chat` function URL
 - `CONTENT_FUNCTION_URL` → the deployed `protectedContent` function URL

Find these in the Firebase/GCP console (Cloud Functions / Cloud Run, region me-central2; interim me-central1). Until they are set, `/api/*` returns 503 but the static site is fully up.

Custom domain (flygaca.com)

The Worker is bound to the production domain in `wrangler.jsonc` so it serves `flygaca.com` rather than only the default `flygaca.flygaca.workers.dev` URL:

```
"routes": [  
  { "pattern": "flygaca.com", "custom_domain": true },  
  { "pattern": "www.flygaca.com", "custom_domain": true }  
]
```

- **Prereq:** the `flygaca.com` zone must be active in the same Cloudflare account. `custom_domain: true` auto-creates the proxied DNS records for the apex and `www` on `npx wrangler deploy` — no manual DNS step.
- **Canonical host:** `worker/index.js` 301-redirects `www.flygaca.com` and the leftover `*.workers.dev` host to the apex `https://flygaca.com`, so the served URL matches the `<link rel="canonical"> / og:url / JSON-LD` tags (which all point at the apex). Local dev hosts are exempt from the redirect.
- The Firebase rollback host attaches its own custom domain separately via the Firebase console (Hosting → Add custom domain) — unchanged by this binding.

Local

```
npm run build:cloudflare      # assemble dist/  
npx wrangler dev              # run the Worker + assets locally  
# or, against the Firebase config instead:  
firebase serve                # legacy/rollback host
```

Deploy / rollback

- **Deploy:** push to the branch the Workers project tracks (the Git integration builds + deploys). Or manually: `npm run build:cloudflare && npx wrangler deploy`.
- **Rollback:** Cloudflare dashboard → the Worker → Deployments → roll back to a previous version. As a full fallback, `firebase deploy --only hosting` still serves the same site from Firebase Hosting.

What still lives on Firebase

- **Cloud Functions** (`chat`, `protectedContent`, billing, webhooks) — deployed from `office/runbook-deploy.md` (they need the Gemini/Adel secrets).
- **Firestore + security rules** — rules deploy from CI (`firebase deploy --only firestore:rules`) on push to `main`.

Keep in sync

`worker/index.js` and `firebase.json` encode the same routing, redirects and headers/CSP. When you change one (a new clean URL, a CSP origin, a redirect), change the other. New external origins must be added to the CSP in **both**.