

# K-ALU TAPE M.S-BEE

Technical Data Sheet

**Product Description:** Aluminium foil tape is coated with a Strong Hot melt adhesive and Laminated with release liner.

**Product Packing**

Backing	Adhesive	Colour	Liner	Standard Sizes		
Soft Temper  Aluminium Foil 8011	Hot melt	Shiny Silver	White release Paper	W(mm)	L(Yds)	Rolls/Box
				48	30	24
				72	30	16
				96	30	12

Custom Size can be produced as per Customer Specifications

**Product Specification**

Properties	Parameter	ASTM Test method
Backing Thickness	20+/-2 micron	ASTM-D-3652
Total Thickness	45 +/-5 micron	ASTM-D-3652
Adhesion To Steel	1800 gms / Inch	ASTM-D-3330
Tensile Strength	2000 gms / Inch	ASTM-D-3759
Elongation at Break	5%	ASTM-D3759
Shear Strength	> 96 Hours	ASTM-D-3654
Tack Rolling Ball	130 mm	ASTM-D-3121
Temperature Range	-5°C to 65° C	

**Features**

- Low moisture content of these products makes these tapes as a good sealant.
- Aluminium foil backing gives excellent reflection of both heat and light
- The Aggressive Hot melt adhesives offer for long serviceable life in outdoor as well as high humid atmosphere.
- Suitable as a masking in electroplating of Aluminium due to its non contamination properties
- Best Result Obtained when its applied to clean and dry surface

**Application**

- Lamination for air conditioning ducting systems
- Roofing Application like flashing ,joints and insulations
- Duct sealing and joining for refrigerator and excellent barrier to vapor
- General purpose holding ,patching sealing applications-indoor and outdoor
- Made in U.A.E

**Storage:** Storage under normal room temperature and 50% RH in the original packing

**Shelf Life:** Use within 12 months.

**Main Distributor:** KILZI & Co. sal  
  
Fanar, Industrial Zone, Kilzi Bldg, PO Box 90820  
  
Tel: +961 872 133, [info@kilzico.com](mailto:info@kilzico.com)