

Facial Recognition

*

1st AYA NASER ALHNATE

*Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
analhnate22@cit.just.edu.jo*

2nd Dana Zeyad Jaradat

*Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
dzjaradat22@cit.just.edu.jo*

3rd Malak Abdulsalam Almajali

*Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
maalmajali22@cit.just.edu.jo*

4th Rayan Nabeel Al Omari

*Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
rnalomari22@cit.just.edu.jo*

Abstract—This paper presents a comprehensive data processing pipeline developed to prepare heterogeneous facial image data for use in modern facial recognition systems. The work focuses on organizing, integrating, and transforming images captured under different conditions and from multiple camera types into a unified, structured, and machine readable dataset. The pipeline includes automated data extraction, metadata generation, integrity validation, and standardized preprocessing steps that ensure consistency across all images.

A series of exploratory analyses were performed to understand dataset distribution, subject representation, and image quality. Cleaning procedures were applied to eliminate inconsistencies, unify labeling formats, and ensure that all image files are valid and usable. Transformations such as color normalization, resizing, and feature computation were incorporated to enhance dataset readiness and support downstream machine-learning tasks.

The resulting dataset is fully documented, reproducible, and optimized for future analytical and recognition applications. By establishing a clear data lineage and a reliable preprocessing framework, this work provides a solid foundation upon which advanced facial recognition models and evaluation workflows can be developed.

Index Terms—Facial recognition, data preprocessing, ETL pipeline, image processing, metadata integration, data cleaning, feature engineering, computer vision, dataset preparation

I. INTRODUCTION

Facial recognition has become a foundational technology in modern computer vision systems, especially as organizations generate and rely on large-scale visual data for analytics, automation, and intelligent decision-making. As the volume and complexity of image datasets continue to increase, traditional manual methods of organizing, identifying, or analyzing visual information are no longer efficient or scalable. This creates a strong need for robust data pipelines capable of processing facial image datasets accurately, consistently, and in real time. In many real world environments, facial images are captured

under diverse conditions different camera types, resolutions, lighting variations, viewing angles, and levels of image quality. Such variability introduces significant challenges for machine learning models, which rely heavily on high-quality, well structured, and properly labeled datasets. Therefore, the ability to integrate data from multiple sources, clean and standardize it, and prepare it for feature extraction or model training is crucial for achieving reliable and high-performance facial recognition systems. To address these challenges, this project focuses on building a complete and repeatable ETL (Extract, Transform, Load) pipeline for facial recognition datasets. The pipeline automates the process of collecting images from different directories, extracting metadata, validating data quality, handling missing or inconsistent values, generating structured datasets, and applying necessary transformations such as resizing, format normalization, and feature consistency checks. By leveraging cloud ready technologies and Python based tools, the system ensures that data is processed efficiently and prepared for subsequent analytical tasks, including model development, evaluation, and real time recognition applications.

II. EASE OF USE

A. Maintaining the Integrity of the Specifications

To ensure consistency, traceability, and reproducibility across all processing stages, the proposed ETL pipeline was designed with a strong emphasis on maintaining data integrity. All steps including extraction, cleaning, transformation, and feature engineering were developed using standardized Python libraries and structured workflows to prevent deviations in formatting, preprocessing methods, or file organization.

Furthermore, the directory structure, naming conventions, metadata schema, and image formats were unified across all components of the dataset. This standardization ensures that the dataset can be reused or extended without requiring structural modifications, making the pipeline both reliable and easy to scale. By maintaining strict consistency throughout

the system, the project preserves the original dataset’s core characteristics while enhancing its usability for downstream facial recognition tasks.

III. PREPARE YOUR PAPER BEFORE STYLING

Before you begin to format your paper, first write and save the content as a separate text file. Complete all content and organizational editing before formatting. Please note sections III-A–III-E below for more information on proofreading, spelling and grammar.

Keep your text and graphic files separate until after the text has been formatted and styled. Do not number text heads— $\LaTeX$ will do that for you.

A. Abbreviations and Acronyms

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, ac, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

B. Data Units and Metrics

- Use consistent units for image dimensions and feature values. All image resolutions are reported in pixels (width $\times$ height, e.g., 128×160).
- Brightness is measured in mean pixel intensity (0–255 grayscale scale).
- Blur variance is computed as the variance of the Laplacian operator (higher values indicate sharper images).
- No mixed units are used; all features are dimensionless or in pixel-based metrics to avoid dimensional inconsistencies.
- Spell out metrics when appearing in text: “mean brightness”, not “MB”. Use a zero before decimal points in metrics: “0.25 variance”, not “.25”.

C. Data Transformation Workflow

The transformation of images and metadata can be formally described as a sequential workflow:

- Image loading from raw directories.
- Conversion to RGB format.
- Resizing to 224×224 pixels.
- Linking processed images to metadata including person ID and source.
- Optional feature computation: brightness and blur variance.

This workflow ensures consistency, traceability, and reproducibility across the dataset.

This sequential workflow ensures consistent preprocessing, traceability, and reproducibility, analogous to defining a formal equation in other domains.

Be sure that the symbols in your equation have been defined before or immediately following the equation. Use “(??)”, not “Eq. (??)” or “equation (??)”, except at the beginning of a sentence: “Equation (??) is . . .”

D. LaTeX-Specific Advice for Data Projects

Soft references (`\ref{}`) are used for figures, tables, and sections to maintain consistency. All figures and tables include descriptive labels and captions to document image sources, metadata fields, and preprocessing steps. BibTeX is used for references. Labels are unique to avoid conflicts. This ensures a fully traceable and reproducible workflow for the facial recognition dataset.

E. Some Common Data Processing Mistakes

- Incorrect labeling of images or subjects.
- Inconsistent image resolutions across datasets.
- Misalignment between image files and metadata.
- Missing or corrupted images not detected.

F. Authors and Affiliations

Aya Naser Alhnate

Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
analhnate22@cit.just.edu.jo

Dana Zeyad Jaradat

Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
dzjaradat22@cit.just.edu.jo

Malak Abdulsalam Almajali

Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
maalmajali22@cit.just.edu.jo

Rayan Nabeel Al Omari

Department of Computer Information Technology
Jordan University of Science and Technology
Irbid, Jordan
rnalomari22@cit.just.edu.jo

G. Identify the Headings

Headings, or heads, are organizational devices that guide the reader through your paper. There are two types: component heads and text heads.

Component heads identify the different components of your paper and are not topically subordinate to each other. Examples include Acknowledgments and References and, for these, the correct style to use is “Heading 5”. Use “figure caption” for your Figure captions, and “table head” for your table title. Run-in heads, such as “Abstract”, will require you to apply a style (in this case, italic) in addition to the style provided by the drop down menu to differentiate the head from the text.

Text heads organize the topics on a relational, hierarchical basis. For example, the paper title is the primary text head because all subsequent material relates and elaborates on this one topic. If there are two or more sub-topics, the next level head (uppercase Roman numerals) should be used and, conversely, if there are not at least two sub-topics, then no subheads should be introduced.

H. Figures and Tables

a) *Positioning Figures and Tables:* Place figures and tables at the top and bottom of columns. Avoid placing them in the middle of columns. Large figures and tables may span across both columns. Figure captions should be below the figures; table heads should appear above the tables. Insert figures and tables after they are cited in the text. Use the abbreviation “Fig. ??”, even at the beginning of a sentence.

TABLE I
TABLE TYPE STYLES

Table Head	Table Column Head		
	Table column subhead	Subhead	Subhead
copy	More table copy ^a		

^aSample of a Table footnote.




Fig. 1. Comprehensive exploratory data analysis of the SCface dataset, showing the distribution of images by type (visible surveillance, infrared, mugshot), distance categories, camera sources, image counts per folder, number of images per person, and relationships between type and distance.

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when writing Figure axis labels to avoid confusing the reader. As an example, write the quantity “Magnetization”, or “Magnetization, M”, not just “M”. If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write “Magnetization (A/m)” or “Magnetization {A[m(1)]}”, not just “A/m”. Do not label axes with a ratio of quantities and units. For example, write “Temperature (K)”, not “Temperature/K”.

ACKNOWLEDGMENT

The preferred spelling of the word “acknowledgment” in America is without an “e” after the “g”. Avoid the stilted expression “one of us (R. B. G.) thanks ...”. Instead, try “R. B. G. thanks...”. Put sponsor acknowledgments in the unnumbered footnote on the first page.

REFERENCES

- [1] Li, C., Ge, S., Zhang, D., & Li, J., “Look through masks: Towards masked face recognition with de-occlusion distillation,” in *Proceedings of the 28th ACM International Conference on Multimedia*, pp. 3016–3024, Oct. 2020. [Online]. Available: <https://arxiv.org/abs/2409.12385>
- [2] Zhalgas, A., Amirgaliyev, B., & Sovet, A., “Robust Face Recognition Under Challenging Conditions: A Comprehensive Review of Deep Learning Methods and Challenges,” *Applied Sciences*, vol. 15, no. 17, 9390, 2025. [Online]. Available: <https://www.mdpi.com/2076-3417/15/17/9390>
- [3] Zhang, K., Zhang, Z., Li, Z., & Qiao, Y., “Joint face detection and alignment using multitask cascaded convolutional networks,” *IEEE Signal Processing Letters*, vol. 23, no. 10, pp. 1499–1503, 2016. [Online]. Available: <https://arxiv.org/abs/1604.02878>
- [4] Liu, Z., Luo, P., Wang, X., & Tang, X., “Deep learning face attributes in the wild,” in *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3730–3738, 2015. [Online]. Available: <https://arxiv.org/abs/1411.7764>
- [5] Zhu, K., He, X., Lv, Z., Zhang, X., Hao, R., He, X., ... & Mu, Z., “A 3D occlusion facial recognition network based on a multi-feature combination threshold,” *Applied Sciences*, vol. 13, no. 10, 5950, 2023. [Online]. Available: <https://www.mdpi.com/2076-3417/13/10/5950>

IEEE conference templates contain guidance text for composing and formatting conference papers. Please ensure that all template text is removed from your conference paper prior to submission to the conference. Failure to remove the template text from your paper may result in your paper not being published.